The Journal of Open Source Software

CATS: The Climate Aware Task Scheduler

Sadie L. Bartholomew [1,2], **Lincoln Colling** [3], **Abhishek Dasgupta** [4], **Anthony J. Greenberg** [5], **Loïc Lannelongue** [6,7,8], **Thibault Lestang** [9], **Carlos Martinez-Ortiz** [10], **Colin Sauzé** [11], **Andrew M. Walker** [12¶], and **Adam Stuart Ward** [13]

1 National Centre for Atmospheric Science, Fairbairn House, 71-75 Clarendon Road, Leeds, LS2 9PH, United Kingdom **2** Department of Meteorology, Brian Hoskins Building, University of Reading, Whiteknights campus, RG6 6ET, United Kingdom **3** School of Psychology, University of Sussex, Brighton, United Kingdom **4** Oxford Research Software Engineering Group, Doctoral Training Centre, University of Oxford, 1-4 Keble Road, Oxford, OX1 3NP, United Kingdom **5** Bayesic Research, Ithaca, NY, USA **6** British Heart Foundation Cardiovascular Epidemiology Unit, Department of Public Health and Primary Care, University of Cambridge, Cambridge, United Kingdom **7** Victor Phillip Dahdaleh Heart and Lung Research Institute, University of Cambridge, Cambridge, United Kingdom **8** Health Data Research UK Cambridge, Wellcome Genome Campus and University of Cambridge, Cambridge, United Kingdom **9** CNRM, Université de Toulouse, Météo-France, CNRS, Toulouse, France **10** Netherlands eScience Center, Science Park 402 (Matrix THREE), 1098 XH Amsterdam, Netherlands **11** National Oceanography Centre, Joseph Proudman Building, 6 Brownlow Street, Liverpool, L3 5DA, United Kingdom **12** Department of Earth Sciences, University of Oxford, South Parks Road, Oxford, OX1 3AN, United Kingdom **13** National Oceanography Centre, European Way, Southampton, SO14 3ZH, United Kingdom ¶ Corresponding author

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Jack Atkinson

Reviewers:

- @christopheredsall
- @LiamPattinson
- @aturner-epcc

Submitted: 16 April 2025
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

The environmental impact of research computing is increasingly a topic of concern for researchers. One of the main contributors of compute-related greenhouse gas (GHG) emissions is the production of electricity to power digital research infrastructures (DRIs). The carbon footprint per unit of electricity consumption (called carbon intensity) depends mostly on the grid's energy mix i.e. the share of renewable vs. high-carbon production methods, which varies greatly with time and location. Here, we describe the Climate Aware Task Scheduler (CATS) which lets researchers schedule computing when low-carbon electricity is available. CATS leverages carbon intensity forecasts, e.g. from the power grid operators, to find the best window of time to run a particular job with minimal climate cost. CATS also provides an assessment of the carbon savings due to delaying compute as opposed to running it immediately. We demonstrate how the tool benefits researchers in the UK using forecasts of the National Grid's regional carbon intensity.

Statement of need

The climate impact of research computing, computer science, and computational science is hard to understate. Computing impacts the environment in many ways, from water and abiotic resource usage to GHG emissions from energy consumption and electronic waste. For many researchers, the CO_2e (CO_2-equivalent, the usual metric of carbon footprint aggregating the main GHGs) cost associated with running their models is larger than that of any other aspects of their life (Portegies Zwart, 2020). The global carbon footprint of data centres is estimated at 126 Mt CO_2e (Malmodin et al., 2024), equivalent to the entire American commercial aviation sector, and individual computing projects can reach dozens, if not hundreds, of tonnes of CO_2e (Grealey et al., 2022; Luccioni et al., 2022; Portegies Zwart, 2020). This is becoming clear to

researchers and funders, who are exploring different approaches to reducing and accounting for the climate impact of the research they commission (Juckes et al., 2023; Lannelongue et al., 2025; Weber et al., 2024). There is a clear need to provide tools for motivated researchers to minimise the detrimental contribution of their research on the climate emergency, and to educate researchers around this impact.

There are several approaches that have been proposed and/or implemented to reduce the carbon footprint of computing, which are summarised in The Turing Way (https://book.the-turing-way.org/ethical-research/activism/activism-env-impact) and in the CATS documentation (https://greenscheduler.github.io/cats/). One of these is time shifting the computation such that it runs when the power supplied by the local electricity grid is dominated by renewable generation such as on windy or sunny days rather than periods where legacy fossil fuel generation dominates. The potential impact of minimally-invasive time-shifting approaches has been shown to result in significantly reduced carbon footprints (27% in one AI benchmark Dodge et al., 2022). CATS helps researchers timeshift their own computation such that it is scheduled when the forecast carbon intensity of the power grid is minimised. This timeshifting approach has been applied in the cloud (Wiesner et al., 2021), for large-language model training (Jagannadharao et al., 2025), and to take account of carbon intensity when scaling Kubernetes workloads on Azure (Nordlander & Lybecker, 2023), but we are not aware of a similar user facing tool.

Approach and functionality

At its core CATS is an open-source (MIT licence) Python package (tested with Python 3.9-3.12) that combines data on the forecast carbon intensity of the local electricity supply with information about a proposed job's duration to assess the best start time of the computation within the validity interval of the forecast. Users typically interact with CATS via a command-line interface targeting the UNIX Shell (CATS is tested on Linux and MacOS) and the best start time can be provided in an informative format (that the user can then use with their infrastructure) or in a way that can be passed on to job schedulers to set the calculation start time. CATS is available via the Python Package Index (PyPI) and can be installed along with its handful of dependencies into a Python environment with pip. Development takes place on GitHub (https://github.com/GreenScheduler/cats) and documentation, including a fuller description of the approach, is available (https://greenscheduler.github.io/cats/).

The user provides CATS with the duration of the proposed computation on the command line. They may also provide the location, the command to run and information about the scheduler. CATS then accesses a prediction of the carbon intensity of the relevant power distribution network and computes the start time that minimises the carbon intensity over the duration of the computation. An illustration of this calculation is provided in Figure 1. Once the carbon intensity minimisation has been completed, CATS can optionally submit the computation to a queueing system or make a more detailed report on the climate impact of the proposed computation.

DRAFT



Figure 1: illustration of the carbon intensity time series for (blue) with the predicted energy use for running a 8.3 hour calculation in Glasgow now (red) or at a time that minimises the integrated carbon intensity (green).

Providing further information about the carbon cost of the proposed computation improves the educational impact of CATS. This can be optionally enabled if information about the compute hardware is available. This calculation follows that used by the Green Algorithms project (Lannelongue et al., 2021), which also provides some easy to understand "equivalent" statements to put these numbers in context.

Limitations and future work

While by itself, CATS is unlikely to drastically reduce the carbon footprint of research computing, it addresses a "low-hanging fruit" of the issue and empowers researchers to adapt their practices. The approach is likely to work best on DRIs that are not fully utilised and where all users are willing to collaborate to move computation to times of lower carbon intensity. It is important to note that CATS does not account for the embodied costs of computer manufacture which, for laptops or desktop machines, can amount to 50-70% of their lifecycle carbon footprint (Apple Inc, 2024; Lannelongue et al., 2024). However, CATS is a tool that has been designed to be conceptually simple and user-friendly with the aim to encourage research groups to discuss the carbon cost of their computation and be a useful test-bed for more complex approaches that may be applied on larger machines. To this end, we are investigating methods to make use of the same carbon intensity data used by CATS to allow batch queueing systems to include the target of minimising the climate cost of computation as part of the scheduling algorithm.

Acknowledgments

We are grateful to the staff of the Software Sustainability Institute and the organisers of Collaborations Workshop 2023 (CW23), whose efforts allowed us to enjoy the process of beginning the development of CATS as part of the CW23 Hack Day, and to others who contributed to the development via bug reports, questions, and the other contributions that help open-source software evolve. The author list is in alphabetical order. This work has been supported by the Software Sustainability Institute EPSRC, BBSRC, ESRC, NERC, AHRC, STFC and MRC (EP/S021779/1) and UKRI (AH/Z000114/1) grants.

References

Apple Inc. (2024). https://www.apple.com/environment/pdf/products/notebooks/MacBook_Pro_16-inch_PER_Oct2024.pdf

Dodge, J., Prewitt, T., Tachet des Combes, R., Odmark, E., Schwartz, R., Strubell, E., Luccioni, A. S., Smith, N. A., DeCario, N., & Buchanan, W. (2022). Measuring the carbon intensity of AI in cloud instances. *2022 ACM Conference on Fairness, Accountability, and Transparency*, 1877–1894. https://doi.org/10.1145/3531146.3533234

Grealey, J., Lannelongue, L., Saw, W.-Y., Marten, J., Méric, G., Ruiz-Carmona, S., & Inouye, M. (2022). The carbon footprint of bioinformatics. *Molecular Biology and Evolution*, msac034. https://doi.org/10.1093/molbev/msac034

Jagannadharao, A., Beckage, N., Nafus, D., & Chamberlin, S. (2025). Timeshifting strategies for carbon-efficient long-running large language model training. *Innovations in Systems and Software Engineering*, *21*, 517–531. https://doi.org/10.1007/s11334-023-00546-x

Juckes, M., Bane, M., Bulpett, J., Cartmell, K., MacFarlane, M., MacRae, M., Owen, A., Pascoe, C., & Townsend, P. (2023). *Sustainability in digital research infrastructure: UKRI net zero DRI scoping project final technical report*. Zenodo. https://doi.org/10.5281/zenodo.8199984

Lannelongue, L., Fropier, J., & Matencio, E. (2025). *How to include environmental sustainability criteria in national AI funding schemes? Reflecting on the example of france and the green algorithms tool*. https://doi.org/10.5281/ZENODO.14607021

Lannelongue, L., Grealey, J., & Inouye, M. (2021). Green algorithms: Quantifying the carbon footprint of computation. *Advanced Science*, *8*(12), 2100707. https://doi.org/10.1002/advs.202100707

Lannelongue, L., Vegad, V., & Dorn, E. (2024). *Environmental impacts of the UK digital sector - data driven report*. https://doi.org/10.17863/CAM.114743

Luccioni, A. S., Viguier, S., & Ligozat, A.-L. (2022). *Estimating the carbon footprint of BLOOM, a 176B parameter language model*. *arXiv:2211.02001*. http://arxiv.org/abs/2211.02001

Malmodin, J., Lövehagen, N., Bergmark, P., & Lundén, D. (2024). ICT sector electricity consumption and greenhouse gas emissions – 2020 outcome. *Telecommunications Policy*, 102701. https://doi.org/10.1016/j.telpol.2023.102701

Nordlander, T. F., & Lybecker, A. (2023). *Saving CO2 using location and time shifting in Azure*. https://devblogs.microsoft.com/ise/saving-co2-using-location-and-time-shifting-in-azure/

Portegies Zwart, S. (2020). The ecological impact of high-performance computing in astrophysics. *Nature Astronomy*, *4*(99), 819–822. https://doi.org/10.1038/s41550-020-1208-y

Weber, P. M., Bendiscioli, S., Wallon, G., Ahsen, U. von, Beaufort, A. M. de, Boland, M., Dekkers, F., Dunon-Bluteau, D., Farley, M., Fox, A., Guillot, S., Lannelongue, L.,

DRAFT

Łazarowicz-Kowalik, M., Rouse, B., Samuel, G., Sanchis, T., Simon, S., Tata, M., Goot, G. van der, & Watt, F. M. (2024). *The heidelberg agreement on environmental sustainability in research funding*. https://doi.org/10.5281/ZENODO.13938809

Wiesner, P., Behnke, I., Scheinert, D., Gontarska, K., & Thamsen, L. (2021). Let's wait awhile: how temporal workload shifting can reduce carbon emissions in the cloud. *Middleware '21: Proceedings of the 22nd International Middleware Conference*, 260–272. https://doi.org/10.1145/3464298.349339

DRAFT