The Journal of Open Source Software

Giga Connectome: a BIDS-app for time series and functional connectome extraction

Hao-Ting Wang [1,2¶], **Rémi Gau** [3], **Natasha Clarke** [1], **Quentin Dessain** [4], and **Pierre Bellec** [1,2,5]

1 Centre de Recherche de l'Institut Universitaire de Gériatrie de Montréal, Université de Montréal, Montréal, QC, Canada **2** Psychology Department, University of Montreal, Montreal, Canada **3** Neuro Data Science ORIGAMI Laboratory, McConnell Brain Imaging Centre, Faculty of Medicine, McGill University, Montréal, Canada. **4** Institute of Information and Communication Technologies, Electronics and Applied Mathematics (ICTEAM), UCLouvain, Louvain-la-Neuve, Belgium **5** Mila, University of Montreal, Montreal, Canada ¶ Corresponding author

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor:

Submitted: 12 April 2024
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

Researchers perform two steps before Functional magnetic resonance imaging (fMRI) data analysis: standardised preprocessing and customised denoising. `fMRIPrep` [Esteban et al. (2019); RRID:SCR_016216], a popular software in the neuroimaging community, is a common choice for preprocessing. `fMRIPrep` performs minimal preprocessing, leaving a few steps for the end user: smoothing, denoising, and standardisation. The present software, `giga-connectome`, is a Brain Imaging Data Structure [BIDS; Gorgolewski et al. (2016); RRID:SCR_016124] compliant container image that aims to perform these steps as well as extract time series signals and generate connectomes for machine learning applications. All these steps are implemented with functions from `nilearn` [Nilearn contributors (2024); RRID:SCR_001362], a python library for machine learning in neuroimaging.

The tool performs smoothing, denoising, and standardisation on voxel level data. Smoothing is implemented with a 5mm full width at half maximum kernel and the user can change the kernel size based on the voxel size of their fMRI data. For the denoising step, we built the workflow closely aligned with the design choice of `fmriprep` and worked with the `fmriprep` developers while implementing a key Application Programming Interface (API), `load_confounds`, implemented in the software library `nilearn`. The tool provides some preset strategies based on Wang et al. (2024) and the current long-term support release `fMRIPrep`. Users can implement their own strategy using configuration files to directly interact with the `load_confounds` API. The details of the process can be found in the user documentation. Finally the data is standardised as z-scores.

The atlas for time series extraction was retrieved through `templateflow` [Ciric et al. (2022); RRID:SCR_021876], a brain template and atlas naming system with a Python API. The container image provides some default atlases (Harvard-Oxford (Desikan et al., 2006; Frazier et al., 2005; Goldstein et al., 2007; Makris et al., 2006), Schaefer (Schaefer et al., 2018), MIST (Urchs et al., 2019), and DiFuMo (Dadi et al., 2020)) that are already available in the `templateflow` repository. Customised atlases will have to be formatted in `templateflow` convention and supplied using a configuration file. We aim to include more default atlases when they are included in the `templateflow` repository.

The time series extraction is implemented with `nilearn` objects `NiftiLabelsMasker` and `NiftiMapsMasker`. The generated time series are used to construct connectomes calculated as Pearson's correlation with `nilearn` object `ConnectivityMeasure`.

Finally the saved time series and connectomes follow the format of BIDS-connectome specifi-

cation. Users can follow the specification to interpret and retrieve the relevant results. The coverage of the atlas is also included as a html visual report, provided by `nilearn.masker` for users to examine the quality of the atlas coverage. More information about the usage, workflow, and outputs can be found on the official documentation.

Statement of need

`giga-connectome` is created for large scale deployment on multiple `fMRIPrep` preprocessed neuroimaging datasets. We aimed to create a tool that is lightweight in terms of code base complexity, software dependencies, and command line interface (CLI). The current software follows the BIDS-apps API (Gorgolewski et al., 2017) and is the first of its kind that creates outputs in the BIDS-connectome. Both users and developers would benefit from the detailed definition of BIDS-apps API and BIDS-connectome for shared usage documentation and development guidelines. The key dependencies of the software are python clients of BIDS or BIDS adjacent projects (`pyBIDS` and `templateflow` python client) and `nilearn`, which is an open source library of high quality and with a clear development cycle for future maintenance. We used configuration files to structure the choice of denoising strategies and brain atlas to avoid crowding the CLI and ensure the choices of the user are traceable.

We aim to provide a lightweight alternative to other existing post-fMRIPrep processing software such as XCP-D (Mehta et al., 2023) and HALFPipe (Waller et al., 2022), or preprocessing software with fMRIPrep support such as C-PAC (Li et al., 2024) and CONN [Whitfield-Gabrieli & Nieto-Castanon (2012); RRID:SCR_009550]. These tools provide more flexibility and options for denoising and more types of downstream feature extraction for a wider range of fMRI analysis. `giga-connectome` was intentionally designed with a narrow scope for quick deployment and the ease for machine learning researchers to adopt. We hope this modular implementation can eventually be included as part of these existing workflows so all `fMRIPrep` outputs can share a time series and connectome extraction tool that's minimal and streamlined. Furthermore, this lean design choice aims to reduce the barrier to learning the code base and the ease of on-boarding new contributors. We hope this choice will invite more users to contribute to the tool and benefit from the open source neuroimaging community.

`giga-connectome` has already been deployed on multiple large neuroimaging datasets such as ABIDE (Di Martino et al., 2014), ADHD200 (Milham et al., 2012), UK Biobank (Sudlow et al., 2015), and more. The generated time series and connectomes have been included in a registered report (Clarke et al., 2024), and various work under preparation in the SIMEXP lab and CNeuromod project. The data processing scripts using `giga-connectome` can be found here for UK Biobank and this repository for the other datasets.

Acknowledgement

The project was supported by the following fundings: Digital Alliance Canada Resource Allocation Competition (RAC 1827 and RAC 4455) to PB, Institut de Valorisation des Données projets de recherche stratégiques (IVADO PFR3) to PB, and Canadian Consortium on Neurodegeneration in Aging (CCNA; team 9 "discovering new biomarkers") to PB, the Courtois Foundation to PB, and Institut national de recherche en sciences et technologies du numérique (INRIA; Programme Équipes Associées - NeuroMind Team DRI-012229) to PB. HTW is supported by IVADO postdoc fellowship. NC is supported by IVADO postdoc fellowship. QD is a research fellow of the Fonds de la Recherche Scientifique - FNRS of Belgium. RG is supported by funding from the Chan Zuckerberg Initiative. PB was funded by Fonds de Recherche du Québec - Santé.

Reference

Ciric, R., Thompson, W. H., Lorenz, R., Goncalves, M., MacNicol, E. E., Markiewicz, C. J., Halchenko, Y. O., Ghosh, S. S., Gorgolewski, K. J., Poldrack, R. A., & Esteban, O. (2022). TemplateFlow: FAIR-sharing of multi-scale, multi-species brain models. *Nature Methods*, *19*(12), 1568–1571. https://doi.org/10.1038/s41592-022-01681-2

Clarke, N., Moreau, C. A., Harvey, A., Wang, H.-T., Orban, P., Zahinoor, I., Jacquemont, S., & Bellec, P. (2024). Investigating the convergence of resting-state functional connectivity profiles in Alzheimer's disease with neuropsychiatric symptoms and schizophrenia. *Brain Communications*. https://doi.org/10.17605/OSF.IO/T7JKZ

Dadi, K., Varoquaux, G., Machlouzarides-Shalit, A., Gorgolewski, K. J., Wassermann, D., Thirion, B., & Mensch, A. (2020). Fine-grain atlases of functional modes for fMRI analysis. *NeuroImage*, *221*, 117126. https://doi.org/10.1016/j.neuroimage.2020.117126

Desikan, R. S., Ségonne, F., Fischl, B., Quinn, B. T., Dickerson, B. C., Blacker, D., Buckner, R. L., Dale, A. M., Maguire, R. P., Hyman, B. T., Albert, M. S., & Killiany, R. J. (2006). An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest. *NeuroImage*, *31*(3), 968–980. https://doi.org/10.1016/j.neuroimage.2006.01.021

Di Martino, A., Yan, C.-G., Li, Q., Denio, E., Castellanos, F. X., Alaerts, K., Anderson, J. S., Assaf, M., Bookheimer, S. Y., Dapretto, M., Deen, B., Delmonte, S., Dinstein, I., Ertl-Wagner, B., Fair, D. A., Gallagher, L., Kennedy, D. P., Keown, C. L., Keysers, C., … Milham, M. P. (2014). The Autism Brain Imaging Data Exchange: Towards Large-Scale Evaluation of the Intrinsic Brain Architecture in Autism. *Molecular Psychiatry*, *19*(6), 659–667. https://doi.org/10.1038/mp.2013.78

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., Kent, J. D., Goncalves, M., DuPre, E., Snyder, M., Oya, H., Ghosh, S. S., Wright, J., Durnez, J., Poldrack, R. A., & Gorgolewski, K. J. (2019). fMRIPrep: A robust preprocessing pipeline for functional MRI. *Nature Methods*, *16*(1), 111–116. https://doi.org/10.1038/s41592-018-0235-4

Frazier, J. A., Chiu, S., Breeze, J. L., Makris, N., Lange, N., Kennedy, D. N., Herbert, M. R., Bent, E. K., Koneru, V. K., Dieterich, M. E., Hodge, S. M., Rauch, S. L., Grant, P. E., Cohen, B. M., Seidman, L. J., Caviness, V. S., & Biederman, J. (2005). Structural brain magnetic resonance imaging of limbic and thalamic volumes in pediatric bipolar disorder. *The American Journal of Psychiatry*, *162*(7), 1256–1265. https://doi.org/10.1176/appi.ajp.162.7.1256

Goldstein, J. M., Seidman, L. J., Makris, N., Ahern, T., O'Brien, L. M., Caviness, V. S., Kennedy, D. N., Faraone, S. V., & Tsuang, M. T. (2007). Hypothalamic abnormalities in schizophrenia: Sex effects and genetic vulnerability. *Biological Psychiatry*, *61*(8), 935–945. https://doi.org/10.1016/j.biopsych.2006.06.027

Gorgolewski, K. J., Alfaro-Almagro, F., Auer, T., Bellec, P., Capotă, M., Chakravarty, M. M., Churchill, N. W., Cohen, A. L., Craddock, R. C., Devenyi, G. A., Eklund, A., Esteban, O., Flandin, G., Ghosh, S. S., Guntupalli, J. S., Jenkinson, M., Keshavan, A., Kiar, G., Liem, F., … Poldrack, R. A. (2017). BIDS apps: Improving ease of use, accessibility, and reproducibility of neuroimaging data analysis methods. *PLOS Computational Biology*, *13*(3), e1005209. https://doi.org/10.1371/journal.pcbi.1005209

Gorgolewski, K. J., Auer, T., Calhoun, V. D., Craddock, R. C., Das, S., Duff, E. P., Flandin, G., Ghosh, S. S., Glatard, T., Halchenko, Y. O., Handwerker, D. A., Hanke, M., Keator, D., Li, X., Michael, Z., Maumet, C., Nichols, B. N., Nichols, T. E., Pellman, J., … Poldrack, R. A. (2016). The brain imaging data structure, a format for organizing

DRAFT

and describing outputs of neuroimaging experiments. *Scientific Data*, *3*(1), 160044. https://doi.org/10.1038/sdata.2016.44

Li, X., Esper, N. B., Ai, L., Giavasis, S., Jin, H., Feczko, E., Xu, T., Clucas, J., Franco, A., Heinsfeld, A. S., Adebimpe, A., Vogelstein, J. T., Yan, C.-G., Esteban, O., Poldrack, R. A., Craddock, C., Fair, D., Satterthwaite, T., Kiar, G., & Milham, M. P. (2024). *Moving Beyond Processing and Analysis-Related Variation in Neuroscience*. bioRxiv. https://doi.org/10.1101/2021.12.01.470790

Makris, N., Goldstein, J. M., Kennedy, D., Hodge, S. M., Caviness, V. S., Faraone, S. V., Tsuang, M. T., & Seidman, L. J. (2006). Decreased volume of left and total anterior insular lobule in schizophrenia. *Schizophrenia Research*, *83*(2-3), 155–171. https://doi.org/10.1016/j.schres.2005.11.020

Mehta, K., Salo, T., Madison, T., Adebimpe, A., Bassett, D. S., Bertolero, M., Cieslak, M., Covitz, S., Houghton, A., Keller, A. S., Luo, A., Miranda-Dominguez, O., Nelson, S. M., Shafiei, G., Shanmugan, S., Shinohara, R. T., Sydnor, V. J., Feczko, E., Fair, D. A., & Satterthwaite, T. D. (2023). *XCP-D: A Robust Pipeline for the post-processing of fMRI data*. bioRxiv. https://doi.org/10.1101/2023.11.20.567926

Milham, M. P. P. D., Fair, D. P.-C., Mennes, M. P. D., & Mostofsky, S. H. M. D. (2012). The adhd-200 consortium: A model to advance the translational potential of neuroimaging in clinical neuroscience. *Frontiers in Systems Neuroscience*, *6*. https://doi.org/10.3389/fnsys.2012.00062

Nilearn contributors. (2024). *nilearn*. https://doi.org/10.5281/zenodo.8397156

Schaefer, A., Kong, R., Gordon, E. M., Laumann, T. O., Zuo, X.-N., Holmes, A. J., Eickhoff, S. B., & Yeo, B. T. T. (2018). Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic Functional Connectivity MRI. *Cerebral Cortex (New York, N.Y.: 1991)*, *28*(9), 3095–3114. https://doi.org/10.1093/cercor/bhx179

Sudlow, C., Gallacher, J., Allen, N., Beral, V., Burton, P., Danesh, J., Downey, P., Elliott, P., Green, J., Landray, M., Liu, B., Matthews, P., Ong, G., Pell, J., Silman, A., Young, A., Sprosen, T., Peakman, T., & Collins, R. (2015). UK Biobank: An Open Access Resource for Identifying the Causes of a Wide Range of Complex Diseases of Middle and Old Age. *PLOS Medicine*, *12*(3), e1001779. https://doi.org/10.1371/journal.pmed.1001779

Urchs, S., Armoza, J., Moreau, C., Benhajali, Y., St-Aubin, J., Orban, P., & Bellec, P. (2019). MIST: A multi-resolution parcellation of functional brain networks. *MNI Open Research*, *1*, 3. https://doi.org/10.12688/mniopenres.12767.2

Waller, L., Erk, S., Pozzi, E., Toenders, Y. J., Haswell, C. C., Büttner, M., Thompson, P. M., Schmaal, L., Morey, R. A., Walter, H., & Veer, I. M. (2022). ENIGMA HALFpipe: Interactive, reproducible, and efficient analysis for resting-state and task-based fMRI data. *Human Brain Mapping*, *43*(9), 2727–2742. https://doi.org/10.1002/hbm.25829

Wang, H.-T., Meisler, S. L., Sharmarke, H., Clarke, N., Gensollen, N., Markiewicz, C. J., Paugam, F., Thirion, B., & Bellec, P. (2024). Continuous evaluation of denoising strategies in resting-state fMRI connectivity using fMRIPrep and Nilearn. *PLOS Computational Biology*, *20*(3), e1011942. https://doi.org/10.1371/journal.pcbi.1011942

Whitfield-Gabrieli, S., & Nieto-Castanon, A. (2012). Conn: A functional connectivity toolbox for correlated and anticorrelated brain networks. *Brain Connectivity*, *2*(3), 125–141. https://doi.org/10.1089/brain.2012.0073

DRAFT