

# BrainSurf: An Open-Source Python Library for EEG Signal Analysis in Meditation Research

Preethi V. Hiremath<sup>1</sup>, Rakshitha B. R.<sup>1</sup>, and Rashi Prasad<sup>1</sup>

<sup>1</sup> Department of Information Science and Engineering, BMS College of Engineering, Bengaluru, India

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: Britta Westner

## Reviewers:

- [@neurosignal](#)
- [@wmvanvliet](#)
- [@vferat](#)

Submitted: 28 October 2025

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).

## Summary

**BrainSurf** is an open-source Python library developed for preprocessing, feature extraction, and statistical analysis of EEG (Electroencephalography) signals, with a focus on meditation-based cognitive neuroscience research. It provides predefined functions for high-pass and low-pass filtering, Common Average Referencing (CAR), artifact removal using ICA (via MNE), epoching, power spectral density (PSD) computation, nonlinear complexity analysis, and inter-channel connectivity estimation.

The library was developed to support EEG-based meditation research, where neural patterns before and after meditative states are studied for their cognitive implications. BrainSurf enables reproducible EEG analysis through an intuitive API and modular design, empowering researchers to efficiently process large EEG datasets and extract meaningful cognitive features. It is available on PyPI (`pip install brainsurf`) and is built on NumPy, SciPy, Matplotlib, MNE, pyabf, and nolds.

## Statement of Need

EEG analysis is critical in understanding how meditation alters cognitive states such as attention, relaxation, and emotional balance. However, existing EEG software—such as MNE-Python (Gramfort et al., 2013) and EEGLAB (Delorme & Makeig, 2004)—are architected around clinical and experimental paradigms (e.g., event-related potentials, source localisation) that do not map naturally onto the continuous, steady-state nature of meditation recordings. These tools require researchers to write substantial custom scripts to compute domain-specific cognitive indices such as frontal alpha asymmetry, theta/alpha engagement ratios, and multifractal complexity measures.

BrainSurf addresses this gap by offering a Python-based, extensible, and open-source library focused on meditation and cognitive EEG research. The package is suitable for:

- Neuroscientists investigating EEG correlates of meditation,
- Psychologists studying mindfulness and cognition,
- Machine learning practitioners building EEG-based classification models,
- Undergraduate and postgraduate students learning EEG signal processing.

## State of the Field

Meditation EEG studies typically rely on a mix of general-purpose preprocessing tools and researcher-written analysis code. Packages such as MNE-Python (Gramfort et al., 2013) and EEGLAB (Delorme & Makeig, 2004) provide strong foundations for filtering, ICA-based artifact removal, and common EEG representations, but they do not bundle meditation-specific, cognition-oriented feature sets in a way that can be reused consistently across projects. In

39 practice, researchers still need to implement custom workflows to compute cognitive indices  
40 (e.g., alpha asymmetry, engagement or relaxation ratios, and nonlinear complexity measures)  
41 and to adapt these computations to the particular structure of meditation recordings (pre/post  
42 comparisons and continuous resting-state segments).

43 This gap matters because small differences in preprocessing parameters, epoching choices, and  
44 feature definitions can materially affect reported effects. BrainSurf's contribution is to package  
45 this domain-specific analysis logic into a focused Python library with a modular, reproducible  
46 API—so that labs can run comparable pipelines, more easily interpret outputs, and share code  
47 patterns rather than duplicating ad-hoc scripts.

## 48 Software Design

### 49 Build vs. Contribute Justification

50 MNE-Python (Gramfort et al., 2013) and EEGLAB (Delorme & Makeig, 2004) are powerful  
51 and well-maintained, but contributing meditation-specific cognitive indices to these projects  
52 would have required substantial refactoring of their core data models, which are optimised  
53 for event-driven paradigms. BrainSurf was therefore created as a focused, standalone library  
54 rather than a downstream extension, allowing a simpler API tailored specifically to continuous  
55 resting-state and meditation recordings.

### 56 Architecture and Design Trade-offs

57 BrainSurf is organised as a collection of loosely coupled modules—preprocessing, analysis,  
58 visualization, and cognitive—each importable independently:

```
import brainsurf.data as data
import brainsurf.preprocessing as pre
import brainsurf.analysis as analysis
import brainsurf.visualization as vis
```

59 This flat, modular structure was preferred over a monolithic pipeline object to lower the barrier  
60 for beginners who need only a subset of functionality. The trade-off is that inter-module state  
61 (e.g., sampling frequency) must be passed explicitly, which adds verbosity but avoids hidden  
62 side effects.

63 Data are represented as NumPy arrays throughout, so BrainSurf outputs are immediately  
64 compatible with SciPy, Pandas, and MNE. ICA-based artifact removal delegates to MNE's  
65 built-in ICA implementation rather than a bespoke solver, keeping the core codebase lean.  
66 Nonlinear complexity analysis (e.g., Hurst exponent, DFA, multifractal measures) is provided  
67 via the nolds library, a deliberate choice to leverage a maintained specialist dependency rather  
68 than re-implementing these algorithms. File-format support (EDF, CSV, MFF, XLSX) was  
69 prioritised to accommodate the heterogeneous recording equipment common in university  
70 meditation laboratories—the MFF format in particular is the native format of EGI/Philips  
71 high-density EEG systems widely used in cognitive neuroscience.

## 72 Functionality and Features

73 BrainSurf provides a complete EEG analysis workflow:

74 **Preprocessing** - Common Average Referencing (CAR) - High-pass and low-pass filtering -  
75 Independent Component Analysis (ICA)-based artifact removal (via MNE) - Epoch segmentation

76 **Analysis** - Power Spectral Density (PSD) computation (Welch method) - Band power estimation  
77 (alpha, beta, theta, gamma) - Wavelet transforms - Multifractal and nonlinear complexity  
78 analysis (via nolds) - Coherence-based functional connectivity and inter-channel correlation

79 **Cognitive Indices** - Indices for arousal, engagement, and relaxation states - Pre- vs. post-  
80 meditation statistical comparison

81 **Visualization** - Topographic mapping - Power spectrum plots - Heatmaps and correlation  
82 matrices

83 **Machine Learning** - EEG classification using RNNs, LDA, or SVMs

## 84 Example Usage

```
import brainsurf.data as data
import brainsurf.preprocessing as pre
import brainsurf.analysis as analysis
import brainsurf.visualization as vis

# Load EEG data from file
eeg_data = data.read_edf_file('eeg_data.edf')

# Preprocess the data
preprocessed_data = pre.bandpass_filter(eeg_data, low_cutoff=1, high_cutoff=40)

# Compute power spectral density
freqs, psd = analysis.psd_welch(preprocessed_data, sampling_freq=256)

# Visualize results
vis.plot_power_spectrum(freqs, psd)
```

## 85 Validation and Application

86 BrainSurf was validated using EEG datasets collected from guided meditation sessions involving  
87 20 meditators and 11 non-meditators. Analysis using BrainSurf's preprocessing and spectral  
88 analysis pipeline showed a statistically significant increase in alpha and theta band power after  
89 meditation, consistent with enhanced relaxation and focus reported in the literature (Hadli et  
90 al., 2020; Wahbeh et al., 2018).

91 The Jupyter notebooks included in the repository (notebooks/demos/demo.ipynb,  
92 notebooks/cognitive/brainSurf\_Cognitive.ipynb, notebooks/meditation/prePost.ipynb,  
93 notebooks/meditation/med\_nonmed.ipynb) document this analysis end-to-end, from raw  
94 EEG loading through preprocessing and cognitive index extraction to visualisation, providing  
95 fully reproducible reference analyses.

## 96 Research Impact Statement

97 BrainSurf addresses a practical gap in the meditation-neuroscience toolchain: the absence of a  
98 Python-native library that bundles domain-specific cognitive indices (frontal alpha asymmetry,  
99 engagement ratio, multifractal complexity) with standard EEG preprocessing in a single, pip-  
100 installable package. Existing general-purpose tools require researchers to assemble these indices  
101 from disparate custom scripts, increasing the risk of implementation inconsistency across  
102 studies.

103 The library has been validated on a real dataset of 31 participants (20 meditators, 11 non-  
104 meditators), with results consistent with established EEG literature on meditation. Community-  
105 readiness signals are in place: the software is publicly available on PyPI, distributed under the  
106 MIT License, and its source is openly hosted on GitHub. Multiple Jupyter notebooks serve

as reproducible reference analyses, and contributions are accepted via GitHub issues and pull requests.

Near-term impact is anticipated in three areas. First, undergraduate and postgraduate laboratories studying contemplative neuroscience can adopt BrainSurf as a teaching tool, replacing ad-hoc scripts with a documented, version-controlled pipeline. Second, the machine learning module (supporting RNN, LDA, and SVM classifiers) provides a baseline classification workflow that future studies can benchmark against. Third, the multi-format file reader (EDF, CSV, MFF, XLSX) reduces the friction of pooling data across recording devices, a known bottleneck in multi-site meditation studies.

## AI Usage Disclosure

The authors did not use generative AI tools in the development of the BrainSurf software, the preparation of this manuscript, or the generation of documentation included in the repository.

## Acknowledgements

We thank Prof. Rajeshwari K, Department of Information Science and Engineering, BMS College of Engineering, for supervision and guidance during development. We also acknowledge contributors to the open-source EEG analysis community whose prior work inspired this project.

## References

- Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial EEG dynamics including independent component analysis. *Journal of Neuroscience Methods*, 134(1), 9–21. <https://doi.org/10.1016/j.jneumeth.2003.10.009>
- Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., Goj, R., Jas, M., Brooks, T., Parkkonen, L., & Hämäläinen, M. S. (2013). MEG and EEG data analysis with MNE-python. *Frontiers in Neuroscience*, 7(267), 1–13. <https://doi.org/10.3389/fnins.2013.00267>
- Hadli, M. A., Kottary, N. K., Acharya, P. S., & Baliga, S. (2020). Detection and analysis of EEG signals before and after meditation. *International Journal of Research in Engineering, Science and Management*, 3(5), 1053–1056. [https://www.ijresm.com/Vol.3\\_2020/Vol3\\_Iss5\\_May20/IJRESM\\_V3\\_I5\\_281.pdf](https://www.ijresm.com/Vol.3_2020/Vol3_Iss5_May20/IJRESM_V3_I5_281.pdf)
- Wahbeh, H., Sagher, A., Back, W., Pundhir, P., & Travis, F. (2018). A systematic review of transcendent states across meditation and contemplative traditions. *Explore*, 14(1), 19–35. <https://doi.org/10.1016/j.explore.2017.07.007>