The Journal of Open Source Software

Smokescreen: A Python package for data vector blinding and encryption in cosmological analyses

Arthur Loureiro [1,2¶], **Jessica Muir** [3], **Jonathan Blazek** [4], **Nora Elisa Chisari** [5,6], **Pedro H. Costa Ribeiro** [7,8], **Christos Georgiou** [9], **Mustapha Ishak**[10], **C. Danielle Leonard** [11], **Bruno Moraes** [12,7], **Marc Paterno** [13], **Nikolina Šarčević** [14], **Tilman Tröster** [15], **Sandro D. P. Vitenti** [8], **and the LSST Dark Energy Science Collaboration**[16]

1 Oskar Klein Centre for Cosmoparticle Physics, Department of Physics, Stockholm University, Stockholm, SE-106 91, Sweden **2** Astrophysics Group, Blackett Laboratory, Imperial College London, London SW7 2AZ, UK **3** University of Cincinnati, Cincinnati, Ohio 45221, USA **4** Department of Physics, Northeastern University, Boston, MA 02115, USA **5** Institute for Theoretical Physics, Utrecht University, Princetonplein 5, 3584 CC, Utrecht, the Netherlands **6** Leiden Observatory, Leiden University, Niels Bohrweg 2, 2333 CA, Leiden, the Netherlands **7** Instituto de Física, Universidade Federal do Rio de Janeiro, Cidade Universitária, Rio de Janeiro, 21941-909, Brazil **8** Departamento de Física, Universidade Estadual de Londrina, Rod. Celso Garcia Cid, Km 380, 86057 970, Londrina, Paraná, Brazil **9** Institut de Física d'Altes Energies (IFAE), The Barcelona Institute of Science and Technology, Campus UAB, 08193 Bellaterra (Barcelona), Spain **10** Department of Physics, The University of Texas at Dallas, Richardson, Texas, USA **11** School of Mathematics, Statistics and Physics, Newcastle University, Newcastle upon Tyne, NE1 7RU, United Kingdom **12** CBPF - Centro Brasileiro de Pesquisas Físicas, 22290-180, Rio de Janeiro, RJ, Brazil **13** Fermi National Accelerator Laboratory, Batavia, IL 60510-0500, U.S.A. **14** Department of Physics, Duke University, Science Dr, Durham, NC 27710, USA **15** Institute for Particle Physics and Astrophysics, ETH Zurich, 8093 Zurich, Switzerland **16** SLAC National Accelerator Laboratory, Menlo Park, CA 94025, USA ¶ Corresponding author

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor:

Submitted: 30 April 2026
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

Smokescreen is an open-source Python library for data-vector concealment (blinding) in cosmological analyses. Data-vector blinding works by applying cosmology-dependent shifts to the observed data vector, moving it away from the true cosmological signal without affecting its statistical properties, so that analysts cannot infer the true result until the analysis is frozen and the blinding is lifted. The package computes these shifts using Firecrown[1] likelihoods applied to data vectors stored in the SACC format[2], ensuring that the theoretical model used for blinding is identical to that used for inference whilst remaining agnostic to the specific observable being blinded. To prevent accidental unblinding, the original SACC file, containing the true cosmology, is encrypted. Although developed for the Vera C. Rubin Observatory Legacy Survey of Space and Time (LSST), Smokescreen is applicable to any experiment using Firecrown likelihoods and the SACC data format.

Statement of need

Modern cosmological analyses require robust data concealment (blinding) strategies to prevent experimenter bias. Cosmological experiments are particularly challenging to blind due to a fundamental limitation: we can only observe one Universe, making it extremely hard to design analyses in a double-blind or even single-blind manner. Additionally, cosmological signals are

[1] https://firecrown.readthedocs.io/en/latest/
[2] https://sacc.readthedocs.io/en/latest/intro.html

DRAFT

not localized events but statistical patterns distributed across large data sets such as correlation functions or power spectra, leaving no clear "signal region" that can simply be hidden. Without a principled approach, analysts risk unconsciously tuning their pipelines towards an expected result or towards the results of other experiments, compromising the scientific integrity of the measurement.

Muir et al. (2020) formalised this discussion by defining three criteria for a reliable data concealment strategy: **(I)** the concealment must hide the true results while producing a physically reasonable posterior that preserves known parameter degeneracies; **(II)** it must retain the ability to perform validation tests, including goodness-of-fit and systematic null tests; and **(III)** it must be straightforward to implement and unblind, while still preventing accidental unblinding. Muir et al. (2020) further showed that applying cosmology-dependent shifts in data vector space satisfies all three requirements.

Smokescreen follows this approach: given a reference cosmology and a randomly-drawn blinded cosmology, it computes the difference between the corresponding theory predictions and applies the shift to the observed data vector. With LSST Y1 data forthcoming and DESC analyses (LSST Dark Energy Science Collaboration, 2012) requiring a collaboration-wide blinding strategy, no existing tool in the DESC software ecosystem (or outside it) provided a standardised implementation of this method. Smokescreen was developed to fill this gap.

State of the field

Blinding in cosmological surveys can be implemented at several stages of the analysis pipeline. Catalogue-level methods (Brieden et al., 2020; e.g., Jarvis et al., 2016) provide robust concealment but are difficult to implement, particularly for multi-probe experiments. Posterior-level methods (e.g., Conley et al., 2006) are simple but leave the data vectors unblinded throughout the analysis. Covariance-level blinding (Sellentin, 2020) is mathematically elegant but harder to apply in practice, as covariance matrices in multi-probe analyses are constructed in a variety of ways — analytically, from simulations, or via resampling methods, for example. Data vector blinding (Muir et al., 2020) provides a practical compromise, offering stronger guarantees than posterior-level methods while remaining easier to implement than catalogue- or covariance-level methods.

The Dark Energy Survey (DES Collaboration et al., 2026), Kilo Degree Survey (Wright et al., 2025), and Hyper Suprime-Cam (Miyatake et al., 2023) have used combinations of these strategies in their analyses, but these implementations were largely *ad hoc* and not easily reusable. Smokescreen provides a dedicated open-source library for data vector blinding designed to integrate with collaboration-wide analysis pipelines. By making the concealment procedure transparent and reproducible, it also allows the wider community to inspect and verify how blinding shifts are computed prior to and post unblinding.

Software design

Smokescreen is structured around a single primary abstraction, the `ConcealDataVector` class, with thin command-line and encryption wrappers layered on top. The design follows a separation-of-concerns principle keeping four responsibilities independent: **(I)** cosmological parameter perturbation (`param_shifts.py`), **(II)** theory vector computation via an external likelihood framework (`datavector.py`), **(III)** data security (`encryption.py`), and **(IV)** user-facing orchestration (`__main__.py`). This structure allows any Firecrown[3]-compatible likelihood to be used, guaranteeing that the theoretical modelling used for concealment is identical to that used for inference, preserving Criterion II of Muir et al. (2020). Smokescreen can perform shifts in any of the base cosmological parameters present in CCL (Chisari et al., 2019).

[3]Firecrown is DESC's likelihood library, see https://github.com/LSSTDESC/firecrown for more information.

DRAFT

The Journal of Open Source Software

Core blinding algorithm

Smokescreen implements the data vector blinding methodology of Muir et al. (2020) in five steps. First, for each cosmological parameter θ_i the user specifies the parameters of a shift distribution (deterministic, flat uniform, or Gaussian; see *Parameter shift strategies* below) from which $\Delta\theta_i$ is drawn. Second, a concealed cosmology is constructed:

$$\boldsymbol{\theta}_{\rm blind} = \boldsymbol{\theta}_{\rm ref} + \boldsymbol{\Delta\theta}.$$

where $\theta_{\rm ref}$ is a reference cosmology defined by the user. Third, the theory vector, $T(\boldsymbol{\theta}, \boldsymbol{s})$, is evaluated by the Firecrown likelihood object at both cosmologies with nuisance parameters $\boldsymbol{s}_{\rm ref}$ fixed at their reference values:

$$\mathbf{d}_{\rm ref} = T(\boldsymbol{\theta}_{\rm ref},\, \boldsymbol{s}_{\rm ref})\,, \qquad \mathbf{d}_{\rm blind} = T(\boldsymbol{\theta}_{\rm blind},\, \boldsymbol{s}_{\rm ref})\,.$$

Fourth, a blinding factor is computed in either additive or multiplicative form:

$$f^{\rm add} = \mathbf{d}_{\rm blind} - \mathbf{d}_{\rm ref}, \qquad f^{\rm mult} = \mathbf{d}_{\rm blind} \,/\, \mathbf{d}_{\rm ref},$$

applied according to the observable. Fifth, the factor is applied to the measured data vector:

$$\hat{\mathbf{d}} = \mathbf{d}_{\rm obs} + f^{\rm add} \quad \text{or} \quad \hat{\mathbf{d}} = \mathbf{d}_{\rm obs} \cdot f^{\rm mult}.$$

Fixing $\boldsymbol{s}_{\rm ref}$ in both evaluations ensures the blinding factor carries only the cosmological shift, leaving the covariance matrix unchanged and allowing standard inference pipelines to run on $\hat{\mathbf{d}}$ without modification.

Software architecture

Figure 1 shows the workflow as a sequential data-flow diagram. The `ConcealDataVector` class orchestrates the process: it evaluates the theory vectors (4.1–4.1), applies the blinding factor (4.1), and writes the output SACC file[4].

Two validation guards prevent common configuration errors. `_verify_sacc_consistency()` checks the return SACC from the likelihood matches the user's input to floating-point tolerance (10^{-10}), while `_check_amplitude_parameter()` ensures consistent specification of the amplitude parameters A_s/σ_8 across the reference cosmology, Firecrown's `CCLFactory`[5], and the shift dictionary.

Supporting modules handle parameter shift generation (`param_shifts.py`, implemented as a stateless module for independent unit testing and modularity), symmetric encryption via `Fernet`[6] (`AES-128-CBC + HMAC-SHA256` with a fresh key per blinding operation) (`encryption.py`, also exposed through command line interface (CLI) subcommands), and SACC format auto-detection with cosmology construction (`utils.py`).

[4] The SACC file format stores correlations, covariances, and associated metadata for cosmological analyses.
[5] Firecrown interfaces with the DESC Core Cosmology Library, CCL (Chisari et al., 2019).
[6] https://github.com/pyca/cryptography

DRAFT




Figure 1: Smokescreen data-flow architecture. Solid arrows show the main execution sequence; dashed arrows show outputs produced by each step; green boxes show outputs. `datavector_main()` orchestrates `ConcealDataVector`, which triggers encryption; `encrypt_main()` provides a standalone encryption path; `decrypt_main()` restores the original SACC file given the `.encrpt` and `.key` files.

DRAFT

Firecrown likelihood integration

Smokescreen requires only a Python module exporting a `build_likelihood(build_parameters)` factory returning a `(Likelihood, ModelingTools)` tuple conforming to the Firecrown interface — the same interface used by Firecrown with the `CosmoSIS`/`Cobaya`/`NumCosmos` (Torrado & Lewis, 2021; Vitenti & Penna-Lima, 2014, respectively; Zuntz et al., 2015) connectors. Therefore, existing likelihood modules do not require modification.

Security and data integrity

After the concealed SACC file is written, the original is encrypted with `Fernet` and deleted by default. The `.key` file is stored separately from the `.encrpt` data file, allowing a blinding committee to distribute them through independent channels. The blinded SACC embeds audit metadata (seed, timestamp, username) sufficient to reconstruct the blinding configuration without external logs.

Application: LSST Y1 3×2pt concealment

We demonstrate Smokescreen on a simulated LSST Y1 3×2pt data vector comprising cosmic shear $C_\ell^{\gamma\gamma}$, galaxy–galaxy lensing $C_\ell^{g\gamma}$, and galaxy clustering C_ℓ^{gg} (Prat et al., 2023) across

five tomographic redshift bins, yielding 415 data points sampled at 20 log-spaced multipoles $\ell \in [20, 2000]$ with the samples containing galaxy clustering restricted to scales $k \leq 0.1$ Mpc^{-1}.

Smokescreen configuration

Two blinded realisations ("Blind A" and "Blind B") were produced with deterministic A_s and w shifts from the fiducial value $A_s^{\rm fid} = 1.9019 \times 10^{-9}$, and $w^{\rm fid} = -1.0$.

Blind A settings are:

```yaml
path_to_sacc: "./sacc_forecasting_y1_3x2pt.sacc"
likelihood_path: "./3x2pt_likelihood.py"
output_suffix: "blind_A"
shifts_dict:
    A_s: 2.00e-09  # +5.2% shift from fiducial
    w: -1.1  # +10.0% shift from fiducial
shift_distribution: "flat"
systematics:
    lens0_bias: 1.2497
    lens1_bias: 1.3809
    lens2_bias: 1.5231
    lens3_bias: 1.6716
    lens4_bias: 1.8245
    ia_bias: 1.0
    alphaz: 0.0
    z_piv: 0.62
reference_cosmology:
    A_s: 1.9019e-09
    Omega_c: 0.2906
keep_original_sacc: true
```

While Blind B uses:

```yaml
output_suffix: "blind_B"
shifts_dict:
    A_s: 1.80e-09  # -5.2% shift from fiducial
    w: -0.9  # -10.0% shift from fiducial
```

and is otherwise identical.

In a non-determinist shift case, the user would specify a list with two values, e.g. the limits of a uniform distribution and a seed:

```yaml
shifts_dict:
    A_s: [1.70e-09, 2.20e-09]
    w: [-1.3, -0.8]
shift_distribution: "flat"
seed: 2112
```

Finally, the concealment of the data vector is invoked as:

```
smokescreen datavector --config conceal_lsst_y1_3x2pt_blind_[A/B].yaml
```

producing `sacc_forecasting_y1_3x2pt_blind_[A/B].sacc` and an encrypted copy of the original. The resulting concealed data vectors are shown in Figure 2.

DRAFT

The Journal of Open Source Software




Figure 2: Example of multi-probe concealment for a simulated LSST Y1 3×2pt data vector: (left) cosmic shear, (middle) galaxy clustering, and (right) galaxy–galaxy lensing. Green circles show the original data vector ($A_s = 1.9 \times 10^{-9}$, $w = -1.0$). Red squares (purple triangles) show *Blind A* (*Blind B*), produced by deterministic shifts to $A_s = 2.0 \times 10^{-9}$, $w = -1.1$ ($A_s = 1.8 \times 10^{-9}$, $w = -0.9$).

Cosmological validation

Following Muir et al. (2020), valid concealment shifts should move the posterior best-fit sufficiently to blind the posterior while leaving the goodness-of-fit unchanged (Criterion II). We verify this with a lightweight inference over three cosmological parameters: A_s, w, and $\Omega_{\rm cdm}$ only[7], using CosmoSIS (Zuntz et al., 2015) and the same Firecrown likelihood supplied to Smokescreen. Deterministic shifts allow direct comparison with the known input cosmology. A full validation on realistic simulated analyses, including the complete parameter space and systematics, will be presented in a forthcoming LSST DESC study.

Figure 3 confirms the expected behaviour: posteriors shift towards the blinded cosmology, whilst the goodness-of-fit remains unchanged ($\chi^2_{\rm red} = 0$ for the noiseless fiducial vector). The Bayesian log-evidence $\log Z$, computed via `Nautilus` (Lange, 2023), is likewise unaffected: $|\Delta \log Z| \leq 1$ for both blinded runs (Blind A: -0.97, Blind B: -0.47), which is inconclusive on the Jeffreys scale and confirms the blinded analyses are statistically indistinguishable from the unblinded one. The results are summarised in Table 1.

Table 1: Best fit values, goodness-of-fit, and log-evidence for all three cases in Figure 3.

	$A_s \times 10^{-9}$	w	$\Omega_{\rm cdm}$	$\chi^2_{\rm red}$	$\log Z$
True Cosmology	1.88	-0.99	0.292	0.0039	-16.67 ± 0.03
Blind A	1.97	-1.09	0.294	0.0084	-17.64 ± 0.03
Blind B	1.79	-0.90	0.290	0.0069	-17.14 ± 0.03

[7]Note that only A_s and w are concealed in this test, while $\Omega_{\rm cdm}$ is kept the same.

DRAFT




Figure 3: Marginalised 1D and 2D posterior distributions from cosmological inference on the data vectors shown in Figure 2, using the same Firecrown likelihood provided to Smokescreen. The true cosmology (cyan), Blind A (red), and Blind B (purple) posteriors shift consistently towards their respective input concealing cosmologies, marked by filled circles and dashed lines. Cross markers indicate the posterior best-fits reported in Table 1. Note that $\Omega_{\rm cdm}$ was not shifted by Smokescreen, yet its posterior shifts a tiny amount as a consequence of the known A_s–$\Omega_{\rm cdm}$–w degeneracy, demonstrating that Criterion I is satisfied.

DRAFT

Research impact statement

Smokescreen is designed as a standard blinding infrastructure for LSST DESC cosmological analyses ahead of LSST's decade-long survey. It eliminates inconsistencies between blinding and inference models that can arise from independent *ad hoc* implementations across analysis teams. Adoption is already extending beyond LSST DESC: the KiDS collaboration is using Smokescreen to blind their upcoming 6×2pt legacy analysis, demonstrating its applicability to any experiment using Firecrown likelihoods and the SACC format. More broadly, we hope Smokescreen will help drive the community towards more consistent, open, and verifiable blinding infrastructures ahead of the Stage-IV survey era.

AI usage disclosure

Generative AI tools, including GitHub Copilot and Claude Code, played a minor supporting role in the development of Smokescreen, primarily in the generation of unit tests and in resolving small, localised bugs. All AI-assisted code was reviewed and edited by the authors before being incorporated into the codebase. The core design of the library, its scientific grounding, and all key implementation decisions were made entirely by the authors. The writing in this paper is our own; AI assistance was limited to occasional grammar corrections and light rephrasing to

improve fluency, as several of the authors are non-native English speakers.

Acknowledgments

This paper has undergone internal review in the LSST Dark Energy Science Collaboration. We thank Joe Zuntz and Jayme Ruiz-Zapatero for acting as DESC internal reviewers for this work. AL acknowledges support from the Swedish National Space Agency (Rymdstyrelsen) under Career Grant Project Dnr 2024-00171 and from the research project grant 'Understanding the Dynamic Universe' funded by the Knut and Alice Wallenberg Foundation under Dnr KAW 2018.0067. Smokescreen was developed as a part of the Stockholm University in-kind software contributions to the Vera Rubin Observatory's Legacy Survey of Space and Time. CG is funded by the MICINN project PID2022-141079NB-C32. IFAE is partially funded by the CERCA program of the Generalitat de Catalunya. NŠ is supported in part by the OpenUniverse effort, which is funded by NASA under JPL Contract Task 70-711320, 'Maximizing Science Exploitation of Simulated Cosmological Survey Data Across Surveys.' TT acknowledges funding from the Swiss National Science Foundation under the Ambizione project PZ00P2_193352

Software acknowledgments

This project is largely possible thanks to several key software tools and packages. We gratefully acknowledge the Python programming language, without which this work would not have been possible.[8] Our development and analysis efforts relied heavily on essential Python libraries, including: NumPy (Harris et al., 2020), SciPy (Virtanen et al., 2020), Matplotlib (Hunter, 2007), ChainConsumer (Hinton, 2016), AstroPy (Astropy Collaboration et al., 2013, 2018, 2022), HDF5 (Collette et al., 2022) and cosmology packages like CCL (Chisari et al., 2019), CosmoSIS (Zuntz et al., 2015), CAMB (Howlett et al., 2012; Lewis et al., 2000), HMCode2020 (Mead et al., 2021), and NaMaster (Alonso et al., 2019).

We also acknowledge the use of Jupyter Notebooks (Kluyver et al., 2016) as an interactive computing environment for prototyping and documenting analyses.

Author contributions

We outline the different contributions below using keywords based on the Contribution Roles Taxonomy (CRediT; Brand et al. (2015)). **AL (core developer & maintainer of Smokescreen):** Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Resources, Writing - Original Draft, Visualization, Project administration; **JM:** Conceptualization, Methodology, Project administration; **JB:** Conceptualization, Project administration; **NEC:** LSST DESC Builder, contributor to `pyCCL`; **PHCR:** Data Curation, Software*; **CG:** Software; **MI** LSST DESC Builder, contributor to `pyCCL`; **CDL:** LSST DESC Builder, contributor to `pyCCL`; **BM:** Software*; **MP:** Software; **NŠ:** Writing - Review & Editing, Visualization; **TT:** LSST DESC Builder, contributor to `pyCCL` & `Firecrown`. **SPDV:** Software*;

* not direct Smokescreen development, but software used in the work presented here.

Alonso, D., Sanchez, J., Slosar, A., & LSST Dark Energy Science Collaboration. (2019). A unified pseudo-C_ℓ framework. *484*(3), 4127–4151. https://doi.org/10.1093/mnras/stz093

Astropy Collaboration, Price-Whelan, A. M., Lim, P. L., Earl, N., Starkman, N., Bradley, L., Shupe, D. L., Patil, A. A., Corrales, L., Brasseur, C. E., N"othe, M., Donath, A., Tollerud, E., Morris, B. M., Ginsburg, A., Vaher, E., Weaver, B. A., Tocknell, J., Jamieson, W., … Astropy Project Contributors. (2022). The Astropy Project: Sustaining and Growing a

[8] https://www.python.org

DRAFT

Community-oriented Open-source Project and the Latest Major Release (v5.0) of the Core Package. *935*(2), 167. https://doi.org/10.3847/1538-4357/ac7c74

Astropy Collaboration, Price-Whelan, A. M., Sipőcz, B. M., Günther, H. M., Lim, P. L., Crawford, S. M., Conseil, S., Shupe, D. L., Craig, M. W., Dencheva, N., Ginsburg, A., Vand erPlas, J. T., Bradley, L. D., Pérez-Suárez, D., de Val-Borro, M., Aldcroft, T. L., Cruz, K. L., Robitaille, T. P., Tollerud, E. J., … Astropy Contributors. (2018). The Astropy Project: Building an Open-science Project and Status of the v2.0 Core Package. *156*(3), 123. https://doi.org/10.3847/1538-3881/aabc4f

Astropy Collaboration, Robitaille, T. P., Tollerud, E. J., Greenfield, P., Droettboom, M., Bray, E., Aldcroft, T., Davis, M., Ginsburg, A., Price-Whelan, A. M., Kerzendorf, W. E., Conley, A., Crighton, N., Barbary, K., Muna, D., Ferguson, H., Grollier, F., Parikh, M. M., Nair, P. H., … Streicher, O. (2013). Astropy: A community Python package for astronomy. *558*, A33. https://doi.org/10.1051/0004-6361/201322068

Brand, A., Allen, L., Altman, M., Hlava, M., & Scott, J. (2015). Beyond authorship: Attribution, contribution, collaboration, and credit. *Learned Publishing*, *28*(2), 151–155. https://doi.org/10.1087/20150211

Brieden, S., Gil-Marín, H., Verde, L., & Bernal, J. L. (2020). Blind Observers of the Sky. *2020*(9), 052. https://doi.org/10.1088/1475-7516/2020/09/052

Chisari, N. E., Alonso, D., Krause, E., Leonard, C. D., Bull, P., Neveu, J., Villarreal, A. S., Singh, S., McClintock, T., Ellison, J., Du, Z., Zuntz, J., Mead, A., Joudaki, S., Lorenz, C. S., Tröster, T., Sanchez, J., Lanusse, F., Ishak, M., … LSST Dark Energy Science Collaboration. (2019). Core Cosmology Library: Precision Cosmological Predictions for LSST. *242*(1), 2. https://doi.org/10.3847/1538-4365/ab1658

Collette, A., Kluyver, T., Caswell, T. A., Tocknell, J., Kieffer, J., Jelenak, A., Scopatz, A., Dale, D., Chen, VINCENT, T., Einhorn, M., payno, juliagarriga, Sciarelli, P., Valls, V., Ghosh, S., Pedersen, U. K., jakirkham, Raspaud, M., … Kittisopikul, M. (2022). *h5py/h5py: 3.7.0* (Version 3.7.0). Zenodo. https://doi.org/10.5281/zenodo.6575970

Conley, A., Goldhaber, G., Wang, L., Aldering, G., Amanullah, R., Commins, E. D., Fadeyev, V., Folatelli, G., Garavini, G., Gibbons, R., Goobar, A., Groom, D. E., Hook, I., Howell, D. A., Kim, A. G., Knop, R. A., Kowalski, M., Kuznetsova, N., Lidman, C., … Supernova Cosmology Project. (2006). Measurement of Ω_m, Ω_Λ from a Blind Analysis of Type Ia Supernovae with CMAGIC: Using Color Information to Verify the Acceleration of the Universe. *644*(1), 1–20. https://doi.org/10.1086/503533

DES Collaboration, Abbott, T. M. C., Adamow, M., Aguena, M., Alarcon, A., Allam, S. S., Alves, O., Amon, A., Anbajagane, D., Andrade-Oliveira, F., Avila, S., Bacon, D., Baxter, E. J., Beas-Gonzalez, J., Bechtol, K., Becker, M. R., Bernstein, G. M., Bertin, E., Blazek, J., … Zuntz, J. (2026). Dark Energy Survey Year 6 Results: Cosmological Constraints from Galaxy Clustering and Weak Lensing. *arXiv e-Prints*, arXiv:2601.14559. https://doi.org/10.48550/arXiv.2601.14559

Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk, M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., … Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, *585*(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2

Hinton, S. R. (2016). ChainConsumer. *The Journal of Open Source Software*, *1*, 00045. https://doi.org/10.21105/joss.00045

Howlett, C., Lewis, A., Hall, A., & Challinor, A. (2012). CMB power spectrum parameter degeneracies in the era of precision cosmology. *2012*(4), 027. https://doi.org/10.1088/1475-7516/2012/04/027

DRAFT

Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, *9*(3), 90–95. https://doi.org/10.1109/MCSE.2007.55

Jarvis, M., Sheldon, E., Zuntz, J., Kacprzak, T., Bridle, S. L., Amara, A., Armstrong, R., Becker, M. R., Bernstein, G. M., Bonnett, C., Chang, C., Das, R., Dietrich, J. P., Drlica-Wagner, A., Eifler, T. F., Gangkofner, C., Gruen, D., Hirsch, M., Huff, E. M., … Wechsler, R. H. (2016). The DES Science Verification weak lensing shear catalogues. *460*(2), 2245–2281. https://doi.org/10.1093/mnras/stw990

Kluyver, T., Ragan-Kelley, B., Pérez, F., Granger, B., Bussonnier, M., Frederic, J., Kelley, K., Hamrick, J., Grout, J., Corlay, S., Ivanov, P., Avila, D., Abdalla, S., Willing, C., & Jupyter Development Team. (2016). Jupyter Notebooks—a publishing format for reproducible computational workflows. In *IOS press* (pp. 87–90). https://doi.org/10.3233/978-1-61499-649-1-87

Lange, J. U. (2023). nautilus: boosting Bayesian importance nested sampling with deep learning. *Monthly Notices of the Royal Astronomical Society*, *525*(2), 3181–3194. https://doi.org/10.1093/mnras/stad2441

Lewis, A., Challinor, A., & Lasenby, A. (2000). Efficient Computation of Cosmic Microwave Background Anisotropies in Closed Friedmann-Robertson-Walker Models. *538*(2), 473–476. https://doi.org/10.1086/309179

LSST Dark Energy Science Collaboration. (2012). Large Synoptic Survey Telescope: Dark Energy Science Collaboration. *arXiv e-Prints*, arXiv:1211.0310. https://doi.org/10.48550/arXiv.1211.0310

Mead, A. J., Brieden, S., Tröster, T., & Heymans, C. (2021). HMCODE-2020: improved modelling of non-linear cosmological power spectra with baryonic feedback. *502*(1), 1401–1422. https://doi.org/10.1093/mnras/stab082

Miyatake, H., Sugiyama, S., Takada, M., Nishimichi, T., Li, X., Shirasaki, M., More, S., Kobayashi, Y., Nishizawa, A. J., Rau, M. M., Zhang, T., Takahashi, R., Dalal, R., Mandelbaum, R., Strauss, M. A., Hamana, T., Oguri, M., Osato, K., Luo, W., … Wang, S.-Y. (2023). Hyper Suprime-Cam Year 3 results: Cosmology from galaxy clustering and weak lensing with HSC and SDSS using the emulator based halo model. *108*(12), 123517. https://doi.org/10.1103/PhysRevD.108.123517

Muir, J., Bernstein, G. M., Huterer, D., Elsner, F., Krause, E., Roodman, A., Allam, S., Annis, J., Avila, S., Bechtol, K., Bertin, E., Brooks, D., Buckley-Geer, E., Burke, D. L., Carnero Rosell, A., Carrasco Kind, M., Carretero, J., Cawthon, R., Costanzi, M., … DES Collaboration. (2020). Blinding multiprobe cosmological experiments. *494*(3), 4454–4470. https://doi.org/10.1093/mnras/staa965

Prat, J., Zuntz, J., Chang, C., Tröster, T., Pedersen, E., García-García, C., Phillips-Longley, E., Sanchez, J., Alonso, D., Fang, X., Gawiser, E., Heitmann, K., Ishak, M., Jarvis, M., Kovacs, E., Larsen, P., Mao, Y.-Y., Medina Varela, L., Paterno, M., … LSST Dark Energy Science Collaboration. (2023). The catalog-to-cosmology framework for weak lensing and galaxy clustering for LSST. *The Open Journal of Astrophysics*, *6*, 13. https://doi.org/10.21105/astro.2212.09345

Sellentin, E. (2020). A blinding solution for inference from astronomical data. *492*(3), 3396–3407. https://doi.org/10.1093/mnras/staa043

Torrado, J., & Lewis, A. (2021). Cobaya: code for Bayesian analysis of hierarchical physical models. *2021*(5), 057. https://doi.org/10.1088/1475-7516/2021/05/057

Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S. J., Brett, M., Wilson, J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E., … SciPy 1.0 Contributors. (2020). SciPy 1.0: Fundamental Algorithms for Scientific Computing in

DRAFT

Python. *Nature Methods*, *17*, 261–272. https://doi.org/10.1038/s41592-019-0686-2

Vitenti, S. D. P., & Penna-Lima, M. (2014). Astrophysics Source Code Library.

Wright, A. H., Stölzner, B., Asgari, M., Bilicki, M., Giblin, B., Heymans, C., Hildebrandt, H., Hoekstra, H., Joachimi, B., Kuijken, K., Li, S.-S., Reischke, R., von Wietersheim-Kramsta, M., Yoon, M., Burger, P., Chisari, N. E., de Jong, J., Dvornik, A., Georgiou, C., … Zhang, Y.-H. (2025). KiDS-Legacy: Cosmological constraints from cosmic shear with the complete Kilo-Degree Survey. *703*, A158. https://doi.org/10.1051/0004-6361/202554908

Zuntz, J., Paterno, M., Jennings, E., Rudd, D., Manzotti, A., Dodelson, S., Bridle, S., Sehrish, S., & Kowalkowski, J. (2015). CosmoSIS: Modular cosmological parameter estimation. *Astronomy and Computing*, *12*, 45–59. https://doi.org/10.1016/j.ascom.2015.05.005

DRAFT