The Journal of Open Source Software

Athlytics: A Computational Framework for Longitudinal Analysis of Exercise Physiology Metrics from Wearable Sensor Data

Zhiang He[1]

1 Independent researcher

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: julia ferraioli

Submitted: 15 May 2025
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

The proliferation of wearable sensors and consumer platforms like Strava has generated vast longitudinal data streams, creating unprecedented opportunities to investigate dynamic human physiological responses to exercise. However, translating this raw data into scientifically rigorous insights for exercise physiology research faces considerable methodological and computational challenges. *Athlytics* is an R [R Core Team (2025)] package designed as a computational framework to streamline the acquisition, analysis, and visualization of key exercise physiology metrics directly from Strava API data. It enables researchers and practitioners to systematically quantify indicators such as Acute:Chronic Workload Ratio (ACWR) [Gabbett (2016); Hulin et al. (2016)], Efficiency Factor (EF) [Allen et al. (2019)], cardiovascular decoupling [Maunder et al. (2021)], and track personal bests (PBs). By providing standardized function interfaces adhering to `tidyverse` principles [Wickham et al. (2019)], *Athlytics* significantly lowers the technical barrier for conducting complex longitudinal analyses, thereby enhancing the feasibility, efficiency, and reproducibility of quantitative research utilizing widely available physiological sensor data.

Statement of Need

Athlytics targets sports scientists, physiologists, and applied researchers studying longitudinal adaptations to endurance training using consumer wearables and Strava as a data hub. Despite the ubiquity of Strava data access via `rStrava` [Beck et al. (2024)], there is no standardized, open-source workflow in R that transforms raw API outputs into core physiological indicators (e.g., ACWR, EF, decoupling) with tidy, reproducible interfaces. This methodological gap forces many researchers to spend substantial effort on bespoke scripts for data retrieval, metric calculation, and visualization, limiting analytical scale, efficiency, and methodological transparency [Sanders et al. (2017)].

Athlytics addresses this gap by providing an integrated framework from data acquisition to the calculation and visualization of multiple physiological metrics, using paired `calculate_*` and `plot_*` functions built on the `tidyverse` [Wickham et al. (2019)]. The package is designed to lower the technical barrier for such analyses while maintaining scientific rigor.

Key Functionalities

Athlytics offers a modular structure, generally featuring paired `calculate_*` and `plot_*` functions for each analytical task, built upon `dplyr` [Wickham et al. (2023)], `ggplot2` [Wickham et al. (2025)], and other `tidyverse` packages.

- **Data Acquisition and Preprocessing:** Leverages `rStrava` [Beck et al. (2024)] for Strava API authentication and data retrieval. Handles date/time operations using `lubridate`

[Grolemund & Wickham (2011)] and rolling calculations with `zoo` [Zeileis & Grothendieck (2005)].

- **ACWR Trend Analysis:**
  - `calculate_acwr`: Computes daily acute (e.g., 7-day) and chronic (e.g., 28-day) rolling loads and their ratio (ACWR) based on user-specified load metrics (duration, distance, or approximated TSS/HRSS).
  - `plot_acwr`: Visualizes the ACWR time series, optionally highlighting risk zones.
- **Load Exposure Analysis:**
  - `calculate_exposure`: Computes daily acute and chronic loads to facilitate a 2D visualization of training state.
  - `plot_exposure`: Generates a scatter plot of acute vs. chronic load, often with ACWR-derived risk zones.
- **Personal Bests (PBs) Tracking:**
  - `calculate_pbs`: Identifies and records best performance times for user-specified distances from Strava activity data (relying on Strava's `best_efforts` field).
  - `plot_pbs`: Visualizes PB progression over time.
- **Efficiency Factor (EF) Analysis:**
  - `calculate_ef`: Computes EF (e.g., average speed/HR or average power/HR) from activity summary data.
  - `plot_ef`: Visualizes EF trends over time, optionally with a smoothing line.
- **Decoupling Analysis:**
  - `calculate_decoupling`: Calculates heart rate/power (or pace/heart rate) decoupling by comparing the efficiency ratio of the first half of an activity to the second half, using detailed activity stream data.
  - `plot_decoupling`: Visualizes decoupling percentages over time.

Comparison with Similar Software

Within the R ecosystem for sports science analytics, *Athlytics* occupies a distinct niche through its integrated analytical workflow designed for Strava API data and a curated set of physiological metrics. The table below summarizes how it compares to related tools:

Research Capability	**Athlytics**	`rStrava`	`trackeR`	Single-metric packages (e.g., `ACWR`)
Data acquisition scope	**Direct Strava API; handles both summary and stream-level physiological data**	Strava API only (OAuth); raw activities and segments	Local files (GPX/TCX/JSON/DB3); no Strava API	User-provided load table only
Key physiological metrics	**ACWR (ATL/CTL), Efficiency Factor, aerobic decoupling, personal best tracking**	None	Generic performance summaries (speed, zones, W)	ACWR only (EWMA/RAC/RAU)
Research reproducibility	**Integrated calculation + visualization in R; outputs tidy data for statistical modelling and meta-analysis**	No analysis layer	Data structuring + generic plots	Single metric; must combine with other tools

DRAFT

This design eliminates the need for researchers to piece together multiple single-function packages and supports reproducible longitudinal research directly from a widely-used data source.

Interactive Example

This interactive example demonstrates how to use *Athlytics* to calculate ACWR for multiple athletes and integrate it into a modeling workflow.

```
library(Athlytics)
library(dplyr); library(purrr); library(tidyr); library(lme4)

mod <- read.csv("tokens_access.csv") %>%          # 1. Read athlete tokens

  # 2. Calculate ACWR for each athlete using their token
  mutate(acw = map(access_token, calculate_acwr,
                   activity_type = "Run",
                   load_metric   = "duration_mins",
                   acute_period  = 7,
                   chronic_period= 28)) %>%
  unnest(acw) %>%

  # 3. Prepare data for modeling
  group_by(athlete_id) %>%
  arrange(date) %>%
  mutate(lag_ACWR = lag(acwr),        # Predictor: lag-1 ACWR
         perf = run_distance_m) %>%   # Response: run distance
  drop_na(perf, lag_ACWR) %>%

  # 4. Fit a mixed-effects model
  lmer(perf ~ lag_ACWR + (1 | athlete_id), data = .)

# 5. Extract and print model coefficients
print(summary(mod)$coefficients)
```


Acknowledgments

The development of *Athlytics* [He (2025b)], which is now available from the Comprehensive R Archive Network (CRAN), relied upon the R programming language [R Core Team (2025)] and benefited from numerous open-source R packages, including `rStrava` [Beck et al. (2024)], `ggplot2` [Wickham et al. (2025)], `dplyr` [Wickham et al. (2023)], `tidyr` [Wickham et al. (2024)], `lubridate` [Grolemund & Wickham (2011)], `zoo` [Zeileis & Grothendieck (2005)], `purrr` [Wickham & Henry (2025)], and `rlang` [Henry & Wickham (2025)]. Access to data was made possible by the Strava API. We also acknowledge the preprint of this work on bioRxiv [He (2025a)].

References

Allen, H., Coggan, A. R., & McGregor, S. (2019). *Training and Racing with a Power Meter* (3rd ed.). VeloPress. ISBN: 9781937715939

Beck, M. W., Villarroel, P., Padfield, D., Gaborini, L., & Maltzahn, N. von. (2024). *rStrava: Access the 'Strava' API*. https://doi.org/10.32614/CRAN.package.rStrava

Gabbett, T. J. (2016). The training—injury prevention paradox: should athletes be training smarter and harder? *British Journal of Sports Medicine*, *50*(5), 273–280. https://doi.org/10.1136/bjsports-2015-095788

DRAFT

Grolemund, G., & Wickham, H. (2011). Dates and Times Made Easy with lubridate. *Journal of Statistical Software*, *40*(3), 1–25. https://doi.org/10.18637/jss.v040.i03

He, Z. (2025a). Athlytics: A Computational Framework for Longitudinal Analysis of Exercise Physiology Metrics from Wearable Sensor Data. *bioRxiv*. https://doi.org/10.1101/2025.05.01.651597

He, Z. (2025b). *Athlytics: Advanced Sports Performance Analysis for 'Strava' Data*. https://doi.org/10.32614/CRAN.package.Athlytics

Henry, L., & Wickham, H. (2025). *rlang: Functions for Base Types and Core R and 'Tidyverse' Features*. https://doi.org/10.32614/CRAN.package.rlang

Hulin, B. T., Gabbett, T. J., Lawson, D. W., Caputi, P., & Sampson, J. A. (2016). The acute: chronic workload ratio predicts injury: high chronic workload may decrease injury risk in elite rugby league players. *British Journal of Sports Medicine*, *50*(4), 231–236. https://doi.org/10.1136/bjsports-2015-094817

Maunder, E., Seiler, S., Mildenhall, M. J., Kilding, A. E., & Plews, D. J. (2021). The Importance of 'Durability' in the Physiological Profiling of Endurance Athletes. *Sports Medicine*, *51*(8), 1619–1628. https://doi.org/10.1007/s40279-021-01459-0

R Core Team. (2025). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. https://www.R-project.org/

Sanders, D., Abt, G., Hesselink, M. K. C., Myers, T., & Akubat, I. (2017). Methods of Monitoring Training Load and Their Relationships to Changes in Fitness and Performance in Competitive Road Cyclists. *International Journal of Sports Physiology and Performance*, *12*(5), 668–675. https://doi.org/10.1123/ijspp.2016-0454

Wickham, H., Averick, M., Bryan, J., Chang, W., D'Agostino McGowan, L., François, R., Grolemund, G., Hayes, A., Henry, L., Hester, J., Kuhn, M., Pedersen, T. L., Miller, E., Bache, S. M., Müller, K., Ooms, J., Robinson, D., Seidel, D. P., Spinu, V., … Yutani, H. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, *4*(43), 1686. https://doi.org/10.21105/joss.01686

Wickham, H., Chang, W., Henry, L., Pedersen, T. L., Takahashi, K., Wilke, C., Woo, K., Yutani, H., & Dunnington, D. (2025). *ggplot2: Create elegant data visualisations using the grammar of graphics*. https://doi.org/10.32614/CRAN.package.ggplot2

Wickham, H., François, R., Henry, L., Müller, K., & Vaughan, D. (2023). *dplyr: A Grammar of Data Manipulation*. https://doi.org/10.32614/CRAN.package.dplyr

Wickham, H., & Henry, L. (2025). *purrr: Functional Programming Tools*. https://doi.org/10.32614/CRAN.package.purrr

Wickham, H., Vaughan, D., & Girlich, M. (2024). *tidyr: Tidy Messy Data*. https://doi.org/10.32614/CRAN.package.tidyr

Zeileis, A., & Grothendieck, G. (2005). zoo: S3 Infrastructure for Regular and Irregular Time Series. *Journal of Statistical Software*, *14*(6), 1–27. https://doi.org/10.18637/jss.v014.i06

DRAFT