The Journal of Open Source Software

Mesa 3: Agent-based modeling with Python in 2025

Ewout ter Hoeven [1], **Jan Kwakkel** [1], **Vincent Hess** [2], **Thomas D. Pike** [3], **Boyu Wang** [4], **rht** [5], **and Jackie Kazil** [3]

1 Delft University of Technology (Faculty of Technology, Policy and Management), the Netherlands **2** Independent Researcher, Germany **3** George Mason University (Department of Computational Social Science), United States **4** University at Buffalo (Department of Geography), United States **5** Independent Researcher

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: George K. Thiruvathukal

Reviewers:

- @martibosch
- @jofmi

Submitted: 30 December 2024
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

Mesa is an open-source Python framework for agent-based modeling (ABM) that enables researchers to create, analyze, and visualize agent-based simulations. Mesa provides a comprehensive set of tools and abstractions for modeling complex systems, with capabilities spanning from basic agent management to sophisticated representation of spaces where agents interact. First released in 2014 and published in Masad et al. (2015) (with updates published in Kazil et al. (2020)), this paper highlights advancements and presents Mesa in its current version (3.1.1) as of late 2024.

Statement of need

Agent-based models (ABMs), or artificial societies, are composed of autonomous heterogeneous agents interacting locally with other agents. These interactions give rise to emergent phenomena. The aggregate dynamics of a system under study emerge from these local interactions (Joshua M. Epstein & Axtell, 1996) (Joshua M. Epstein, 1999). This type of modeling quickly grew more sophisticated, requiring frameworks to execute them. This led to the establishment of NetLogo and MASON.

However, before Mesa, there was no modern Python-based framework for ABMs that integrated with the scientific Python ecosystem. Since its creation in 2014, Mesa has been applied to modeling everything from economics and sociology to ecology and epidemiology and has been cited in more than 500 papers and 800 authors. With its most recent major release, Mesa has advanced usability and stabilized functionality. These features include enhanced management of agents, data collection advancements, improved visualization framework, and making it easier for researchers to create and analyze complex simulations.

Core capabilities

Mesa is a Python-based framework for ABM that provides a comprehensive set of tools for creating, running, and analyzing ABMs. Mesa integrates with the wider scientific Python ecosystem with libraries such as NumPy, pandas, Matplotlib, NetworkX, and more. Mesa is implemented in pure Python (3+) with a modular architecture comprised of three main components: 1. Core ABM components (*i.e.,* agents, spaces, agent activation, control over random numbers)to build models 2. Data collection and support for model experimentation 3. Visualization systems

This decoupled design allows selective use of components while enabling extension and customization.

DRAFT

The Journal of Open Source Software

Core ABM components

Model

The central class in Mesa is the Model. To build a model, the user instantiates a the model, then within it, the user instantiates the space and populates the space with agent instances. Since ABMs are typically stochastic simulations, Mesa was built with a random number generation, and for reproductility proposes, the ability to pass a seed.

Agents

Central to ABMs are the autonomous heterogeneous agents. Mesa provides a variety of base agent classes which the user can subclass. In its most basic implementation, an agent subclass specifies the `__init__` and `step` method. Any subclass of the basic mesa agent subclass registers itself with the specified model instance, and via `agent.remove` it will remove itself from the model. It is strongly encouraged to rely on `remove`, and even extend it if needed to ensure agents are fully removed from the simulation.

Agent management

One significant advancement of Mesa 3 is expanded functionality around agent management. The new `AgentSet` class provides methods that allow users to filter, group, and analyze agents, making it easier to express complex model logic.

```
# Select wealthy agents and calculate average wealth
wealthy = model.agents.select(lambda a: a.wealth > 1000)
avg_wealth = wealthy.agg("wealth", func=np.mean)

# Group agents by type and apply behaviors
grouped = model.agents.groupby("species")
for species, agents in grouped:
    agents.shuffle_do("reproduce")
```

Spaces

Mesa 3 provides both discrete (cell-based) and continuous space implementations. In discrete spaces, an agent occupies a cell. Mesa implements discrete spaces using a doubly-linked structure where each cell maintains connections to its neighbors. The framework includes several discrete space variants with a consistent API:

- Grid-based: `OrthogonalMooreGrid`, `OrthogonalVonNeumanGrid`, and `HexGrid`
- Network-based: `Network` for graph-based topologies
- Voronoi-based: `VoronoiMesh` for irregular tessellations

Example grid creation:

```
grid = OrthogonalVonNeumannGrid((width, height), torus=False, random=model.random)
```

In Mesa 3, specialized agent classes for spatial interactions in discrete spaces were added:

- `FixedAgent`: Is assigned to a cell, can access this cell, but cannot move to another cell.
- `CellAgent`: Can move between cells
- `Grid2DMovingAgent`: Extends `CellAgent` with directional movement methods

All discrete spaces support PropertyLayers - efficient numpy-based arrays for storing cell-level properties. This newly added feature allows for agents to interact with spatial properties of the cell more easily:

```
grid.create_property_layer("elevation", default_value=10)
high_ground = grid.elevation.select_cells(lambda x: x > 50)
```

DRAFT

For models where agents need to move continuously through space rather than between discrete locations, `ContinuousSpace` allows agents to occupy any coordinate within defined boundaries:

```
space = ContinuousSpace(x_max, y_max, torus=True)
space.move_agent(agent, (new_x, new_y))
```

The space module is stable but under active development. The new cell-based spaces in Mesa 3 are currently being tested and considered feature-complete. The code snippets reflected in this paper are the future expected state of Mesa. Features not yet merged into core are imported from experimental:

```
from mesa.experimental.cell_space ...
```

Time advancement

Typically, ABMs represent time incrementally and call the units ticks. For each tick, the step method of the model is called, and the agents are activated to take their designated actions. The most frequently implemented approach is shown below, which runs a model for 100 ticks.

```
model = Model(seed=42)

for _ in range(100):
    model.step()
```

Before Mesa 3, all agents were activated within the step method of the model. However, the newly added `AgentSet` class provides a more flexible way to activate agents. These changes include the removal of the Scheduler API and its previously available fixed patterns.

```
model.agents.do("step")  # Sequential activation

model.agents.shuffle_do("step")  # Random activation

# Multi-stage activation:
for stage in ["move", "eat", "reproduce"]:
    model.agents.do(stage)

# Activation by agent subclass:
for klass in model.agent_types:
    model.agents_by_type[klass].do("step")
```

Next-event time progression is an additional feature, which is currently in an experimental state with plans for support in the future. In this approach, the simulation consists of time-stamped events executed chronologically, with the simulation clock advancing to each event's timestamp. This enables both pure discrete event-based models and hybrid approaches combining incremental time progression with event scheduling on the ticks, as shown below. The latter hybrid approach combines traditional ABM time steps with the flexibility and potential performance benefits of event scheduling.

```
# Pure event-based scheduling
simulator = DiscreteEventSimulator()
model = Model(seed=42, simulator=simulator)
simulator.schedule_event_relative(some_function, 3.1415)

# Hybrid time-step and event scheduling
model = Model(seed=42, simulator=ABMSimulator())
model.simulator.schedule_event_next_tick(some_function)
```

DRAFT

Visualization

Mesa's visualization module, [SolaraViz](https://mesa.readthedocs.io/latest/tutorials/visualization_tutorial.html, allows for interactive browser-based model exploration. Advancements with Mesa 3 update the visualization from harder-to-maintain custom code to Solara, a standardized library. Usage of the visualization module can be seen below:

```
visualization = SolaraViz(
    model,
    [
        make_space_component(agent_portrayal),
        make_plot_component(["population", "average_wealth"]),
        lambda m: f"Step {m.steps}: {len(m.agents)} agents"
    ],
    model_params=parameter_controls
)
```



Figure 1: A screenshot of the WolfSheep Model in Mesa

Key features include:

- Interactive model controls
- Real-time data visualization
- Customizable agent and space portrayal
- Support for multiple visualization types, including grids, networks, and charts

Experimentation and analysis

Data collection

Mesa's DataCollector enables systematic data gathering during simulations:

```
collector = DataCollector(
    model_reporters={"population": lambda m: len(m.agents)},
    agent_reporters={"wealth": "wealth"},
    agenttype_reporters={
        Predator: {"kills": "kills_count"},
        Prey: {"distance_fled": "flight_distance"}
```

```
        }
    )
```

The collected data integrates seamlessly with pandas for analysis:

```
model_data = collector.get_model_vars_dataframe()
agent_data = collector.get_agent_vars_dataframe()
```

Parameter sweeps

Mesa supports systematic parameter exploration:

```
parameters = {
    "num_agents": range(10, 100, 10),
    "growth_rate": [0.1, 0.2, 0.3]
}
results = mesa.batch_run(MyModel, parameters, iterations=5, max_steps=10)
```

Applications

Mesa has been applied across diverse domains, including:

- Infrastructure resilience and post-disaster recovery planning (Sun & Zhang, 2020)
- Market modeling, including renewable energy auctions and consumer behavior (Anatolitis & Welisch, 2017a)
- Transportation optimization, such as combined truck-drone delivery routing (Leon-Blanco et al., 2022)
- Recommender systems analysis examining consumer-business value tradeoffs over time (Ghanem et al., 2022)
- Climate adaptation modeling examining household-level behavioral responses to environmental shocks (Anatolitis & Welisch, 2017b)
- SEIR modeling of Sars-CoV-2 (Covid-19) (Pham et al., 2021)
- Management of edge computing resources (Souza et al., 2023)

These applications showcase Mesa's versatility in modeling complex systems with autonomous interacting agents, whether representing individual consumers, infrastructure components, buildings, or vehicles.

The framework is particularly suited for: - Models with heterogeneous agent populations - Systems requiring sophisticated spatial interactions - Interactive exploration of parameter spaces - Teaching and learning agent-based modeling

Community and ecosystem

Mesa has grown into a complete ecosystem with extensions including:

- Mesa-Geo for geospatial modeling (Wang et al., 2022)
- Mesa-Frames for high-performance simulations
- A rich collection of community-contributed extensions, example models, and tutorials

Acknowledgements

The advancements leading to Mesa 3 were developed by six maintainers (the authors) and an active community with over 140 contributors. We would especially like to thank David Masad for his foundational work on Mesa.

DRAFT

Conclusions

Mesa 3 introduces significant advancements to the Python ABM framework, enhancing the core toolkit with greater control, interactivity, and speed for researchers. These notable improvements, paired with its foundational integration with the scientific Python ecosystem, modular architecture, and active community, make it an indispensable tool for researchers across disciplines working in Python who need to create and analyze agent-based models.

References

Anatolitis, V., & Welisch, M. (2017a). Putting renewable energy auctions into action–an agent-based model of onshore wind power auctions in germany. *Energy Policy*, *110*, 394–402. https://doi.org/10.1016/j.enpol.2017.08.024

Anatolitis, V., & Welisch, M. (2017b). Putting renewable energy auctions into action–an agent-based model of onshore wind power auctions in germany. *Energy Policy*, *110*, 394–402. https://doi.org/10.1016/j.enpol.2017.08.024

Epstein, Joshua M. (1999). Agent-based computational models and generative social science. *Complexity*, *4*(5), 41–60.

Epstein, Joshua M., & Axtell, R. (1996). *Growing artificial societies: Social science from the bottom up*. Brookings Institution Press; MIT Press. ISBN: 9780262550253

Ghanem, N., Leitner, S., & Jannach, D. (2022). Balancing consumer and business value of recommender systems: A simulation-based analysis. *Electronic Commerce Research and Applications*, *55*, 101195. https://doi.org/10.1016/j.elerap.2022.101195

Kazil, J., Masad, D., & Crooks, A. (2020). Utilizing python for agent-based modeling: The mesa framework. *Social, Cultural, and Behavioral Modeling: 13th International Conference, SBP-BRiMS 2020*, 308–317. https://doi.org/10.1007/978-3-030-61255-9_30

Leon-Blanco, J. M., Gonzalez-R, P. L., Andrade-Pineda, J. L., Canca, D., & Calle, M. (2022). A multi-agent approach to the truck multi-drone routing problem. *Expert Systems with Applications*, *195*, 116604. https://doi.org/10.1016/j.eswa.2022.116604

Masad, D., Kazil, J. L., & others. (2015). Mesa: An agent-based modeling framework. *SciPy*, 51–58. https://doi.org/10.25080/Majora-7b98e3ed-009

Pham, T. M., Tahir, H., Wijgert, J. H. H. M. van de, Van der Roest, B. R., Ellerbroek, P., Bonten, M. J. M., Bootsma, M. C. J., & Kretzschmar, M. E. (2021). Interventions to control nosocomial transmission of SARS-CoV-2: A modelling study. *BMC Medicine*, *19*, 211. https://doi.org/10.1186/s12916-021-02060-y

Souza, P. S., Ferreto, T., & Calheiros, R. N. (2023). EdgeSimPy: Python-based modeling and simulation of edge computing resource management policies. *Future Generation Computer Systems*, *148*, 446–459. https://doi.org/https://doi.org/10.1016/j.future.2023.06.013

Sun, J., & Zhang, Z. (2020). A post-disaster resource allocation framework for improving resilience of interdependent infrastructure networks. *Transportation Research Part D: Transport and Environment*, *85*, 102455. https://doi.org/10.1016/j.trd.2020.102455

Wang, B., Hess, V., & Crooks, A. (2022). Mesa-geo: A GIS extension for the mesa agent-based modeling framework in python. *Proceedings of the 5th ACM SIGSPATIAL International Workshop on GeoSpatial Simulation*, 1–10. https://doi.org/10.1145/3557989.3566157

DRAFT