The Journal of Open Source Software

constrained_manipulability: A ROS 2 library to Compute and Visualize Constrained Capacities for Robotic Manipulators

Mark Zolotas [1*¶], **Philip Long** [2*], **Keerthi Sagar** [3], and **Taskin Padir** [1,4]

1 Northeastern University, USA (at the time of this work) **2** Atlantic Technological University, Ireland **3** Irish Manufacturing Research Limited, Mullingar, Ireland **4** Amazon Robotics, USA ¶ Corresponding author * These authors contributed equally.

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Chris Vernon

Reviewers:

- @askuric
- @JHartzer

Submitted: 15 August 2024
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

This paper presents `constrained_manipulability`, a C++ library to compute and visualize a robot manipulator's constrained motion capacities. Manipulability polytopes provide a geometrical tool to evaluate the volume of free space surrounding the robotic arm when considering both environmental and intrinsic robot constraints, such as collisions and joint limits, respectively. Moreover, the polytopes defined by these convex constraints represent feasible configurations for the whole robot, that can be utilized in inverse kinematics (IK) optimization algorithms to produce collision-free motion trajectories.

The library is encapsulated in a Robot Operating System (ROS) package (Quigley et al., 2009). We include ROS 1 and ROS 2 (Macenski et al., 2022) implementations of the core C++ library. The `constrained_manipulability` package also heavily depends on our `robot_collision_checking` package, a ROS interface for collision checking via the Flexible Collision Library (FCL) (Pan et al., 2012).

The main program of the `constrained_manipulability` package reads a kinematic chain from a robot manipulator's Unified Robot Description Format (URDF), from a user defined root of the robot (e.g., the robot's base frame) to a tip (e.g., the end-effector or tool). Joint position and velocity limits are also read from the URDF, while a collision world is maintained to express environmental constraints on the robot's motion. A variety of collision objects can be added or removed using common ROS message types, such as Octomaps (Hornung et al., 2013), mesh files or solid primitives. These joint limit and obstacle constraints are then stacked together to define different polytopes, such as the allowable motion polytope (Long et al., 2019) and the constrained velocity polytope (Long & Padır, 2018).

Statement of Need

Generating complex constraint geometries efficiently is a significant challenge for real-time robot manipulation. For applications, like motion planning or remote teleoperation, being able to represent the space of obstacle-free allowable motion around an end-effector is vital. Given such a representation a collision-free IK solution can be obtained to maximize the free space of a robot moving in a constrained environment. Manipulability polytopes represent manipulability capacities, e.g., the capacity for the robot to transmit velocities and forces from the configuration space to the task space. The benefit of using convex polytopes is that they capture exact velocity bounds, rather than the approximation provided by for example ellipsoids (Yoshikawa, 1984). While the aforementionned ellipsoids have been the dominant paradigm due to historic computational constraints, more efficient polytope generation methods (Sagar

et al., 2023; Skuric et al., 2023) coupled with more computation availability has led to an increased usage.

Furthermore, since a polytope is defined by a set of inequality constraints, additional constraints can be easily incorporated into existing polytopes, e.g., mobile robot toppling constraints (Rasheed et al., 2018), friction cones (Caron et al., 2016), and maximum danger values.

The `constrained_manipulability` ROS 2 package aims to fulfil this need for constrained robot capacity calculation by supplying the robotics community with a fast C++ implementation that computes various types of polytopes. These geometrical constructs can also be visualized for workspace analysis or to guide an operator through the Cartesian motions available due to joint limits, kinematic constraints, and obstacles in the workspace, as illustrated in Figure 1. The utility of these visualizations has proven advantageous in remote teleoperation scenarios involving virtual reality headsets (Zolotas et al., 2021). Moreover, the package provides an interface to the `robot_collision_checking` package and a set of convenience functions for checking the distance/collision between a robot manipulator and the environment.

Figure 1: Collision-free path for a robot manipulator visualized as a trajectory of polytopes generated by maximizing the volume of allowable motion around the robot's end-effector.

Polytope and Manipulator Model

A polytope, $\mathcal{P}$, can be represented as the convex hull of its vertex set, or as a volume bounded by a finite number of half-spaces,known as the $\mathcal{V}$-representation and $\mathcal{H}$-representation and denoted as $\mathcal{P}^V$ and $\mathcal{P}^H$, respectively. Converting between the $\mathcal{V}$ and $\mathcal{H}$ representations can be carried out in several ways, however the `constrained_manipulability` package uses the

double description method (Fukuda & Prodon, 1996).

The `constrained_manipulability` provides two types of polytope representation, Constrained Motion Polytopes which modify the classical manipulability velocity polytope (Kokkinis & Paden, 1989) to include joint limits and capacities reductions due to nearby obstacles and the Allowable Motion Polytope a linearisation of the above to generate a measure of free space or allowable motions in which a robot can move while satisfying all constraints.

In both cases, the polytope is contructed as follows. First a system of linear inequalities is constructed in joint space, for instance based on the joint velocities limits:

$$\mathcal{Q}^H = \begin{bmatrix} \mathbb{I}_n \\ -\mathbb{I}_n \end{bmatrix} \dot{\mathbf{q}} \leq \begin{bmatrix} \dot{\mathbf{q}}^{max} \\ -\dot{\mathbf{q}}^{min} \end{bmatrix}, \tag{1}$$

where $\dot{\mathbf{q}}^{max}$ and $\dot{\mathbf{q}}^{min}$ are the robot's maximum and minimum joint velocities. Using the double description method, an equivalent polytope in the $\mathcal{V}$-representation (i.e., defined by its vertices) is written as:

$$\mathcal{Q}^V = \{ \ \dot{\mathbf{q}}_1^v, \ \dot{\mathbf{q}}_2^v, \ \dots, \ \dot{\mathbf{q}}_q^v \ \}, \tag{2}$$

where $\dot{\mathbf{q}}_i^v$ denotes the ith vertex of the polytope $\mathcal{Q}$, given q vertices in n-dimensional space. A Cartesian polytope, denoted as $\mathcal{MP}$, can be obtained by transforming the vertices of Equation 2 to Cartesian space using the forward kinematics. $\mathcal{MP}$'s vertex set representation of p vertices in 3-dimensional space is given as:

$$\mathcal{MP}^V = \{ \ \boldsymbol{\nu}_1^v, \ \dots, \ \boldsymbol{\nu}_p^v \ \} = \{ \ \mathbf{J}_n \dot{\mathbf{q}}_1^v, \ \dots, \ \mathbf{J}_n \dot{\mathbf{q}}_p^v \ \}, \tag{3}$$

with $\boldsymbol{\nu}_j^v = \mathbf{J}_n \dot{\mathbf{q}}_j^v$ and $p \leq q$. The convexity of a polytope is preserved under affine transformation, thus a bounded volume of $\mathcal{MP}$ that represents the system's manipulability can easily be obtained to serve as an exact indicator of robot performance.

For the Constrained Motion Polytopes, the following constraints are supported, joint velocity limits, joint velocity damping due to positional joint limits, joint velocity damping due obstacle proximity to the kinematic chain. For the allowable motion polytope the following constraints are supported, positional joint limits, positional limits due obstacle proximity to the kinematic chain, linearization limits. Increasing the values of the linearisation expands the free space virtual fixture at a cost of reduced fidelity. Our implementation uses a scalar linearization limit for all joints that can also be altered at run time e.g. could be increased to enlarge the solution or shrunk to guide the user towards a defined goal configuration, as described in (Zolotas et al., 2021). Finally, in our implementation, we select at every instant the point along each link nearest to all environmental obstacles. Hence, the system considers the set of instantaneous collision-free joint motion for each link on the robot's kinematic chain, considering all obstacles $\mathcal{O}$.

Block Diagram

Any joint position and velocity limits are extracted from the robot's URDF description via ROS 2 parameter operations. Polytopes are calculated as described above using these limits and by obtaining the minimum distance from each link on the robot to objects in the collision world. FCL (Pan et al., 2012) is required to compute these distances and is accessible via the interface package robot_collision_checking. Polytopes in Cartesian space can then be returned from getter functions, like:

```
Polytope getConstrainedAllowableMotionPolytope(
  const sensor_msgs::msg::JointState& joint_state,
  bool show_polytope,
  Eigen::MatrixXd& AHrep,
  Eigen::VectorXd& bHrep,
  Eigen::Vector3d& offset_position,
```

DRAFT

```
  const std::vector<double>& color_pts,
  const std::vector<double>& color_line);
```

where `AHrep` and `bHrep` represent the joint space polytope constraints defined in **??**.

A diagram summarizing the `constrained_manipulability` package architecture and ROS 2 communication flow is displayed in Figure 2.



Figure 2: Block diagram for the constrained_manipulability ROS 2 package.

Acknowledgements

Mark Zolotas is currently at Toyota Research Institute (TRI), Cambridge, MA, USA. This paper describes work performed at Northeastern University and is not associated with TRI.

Taskin Padir holds concurrent appointments as a Professor of Electrical and Computer Engineering at Northeastern University and as an Amazon Scholar. This paper describes work performed at Northeastern University and is not associated with Amazon.

References

Caron, S., Pham, Q.-C., & Nakamura, Y. (2016). Zmp support areas for multicontact mobility under frictional constraints. *IEEE Transactions on Robotics*, *33*(1), 67–80.

Fukuda, K., & Prodon, A. (1996). Double description method revisited. *Combinatorics and Computer Science*, *1120*, 91.

Hornung, A., Wurm, K. M., Bennewitz, M., Stachniss, C., & Burgard, W. (2013). OctoMap: An efficient probabilistic 3D mapping framework based on octrees. *Autonomous Robots*, *34*, 189–206.

Kokkinis, T., & Paden, B. (1989). Kinetostatic performance limits of cooperating robot manipulators using force-velocity polytopes. *Proceedings of the ASME Winter Annual Meeting*, 151–155.

Long, P., Keleştemur, T., Önol, A. Ö., & Padir, T. (2019). Optimization-based human-in-the-loop manipulation using joint space polytopes. *International Conference on Robotics and Automation*, 204–210.

Long, P., & Padır, T. (2018). Evaluating robot manipulability in constrained environments by velocity polytope reduction. *IEEE-RAS International Conference on Humanoid Robots*, 497–502.

DRAFT

Macenski, S., Foote, T., Gerkey, B., Lalancette, C., & Woodall, W. (2022). Robot operating system 2: Design, architecture, and uses in the wild. *Science Robotics*, *7*(66), eabm6074. https://doi.org/10.1126/scirobotics.abm6074

Pan, J., Chitta, S., & Manocha, D. (2012). FCL: A general purpose library for collision and proximity queries. *IEEE International Conference on Robotics and Automation*, 3859–3866. https://doi.org/10.1109/ICRA.2012.6225337

Quigley, M., Conley, K., Gerkey, B., Faust, J., Foote, T., Leibs, J., Wheeler, R., & Ng, A. (2009). ROS: An open-source robot operating system. *ICRA Workshop on Open Source Software*, *3*.

Rasheed, T., Long, P., Marquez-Gamez, D., & Caro, S. (2018). Tension distribution algorithm for planar mobile cable-driven parallel robots. *Cable-Driven Parallel Robots: Proceedings of the Third International Conference on Cable-Driven Parallel Robots*, 268–279.

Sagar, K., Caro, S., Padır, T., & Long, P. (2023). Polytope-based continuous scalar performance measure with analytical gradient for effective robot manipulation. *IEEE Robotics and Automation Letters*, *8*(11), 7289–7296. https://doi.org/10.1109/LRA.2023.3313926

Skuric, A., Padois, V., & Daney, D. (2023). Pycapacity: A real-time task-space capacity calculation package for robotics and biomechanics. *Journal of Open Source Software*, *8*(89), 5670. https://doi.org/10.21105/joss.05670

Yoshikawa, T. (1984). Analysis and control of robot manipulators with redundancy. *International Symposium on Robotics Research*, 735–747.

Zolotas, M., Wonsick, M., Long, P., & Padır, T. (2021). Motion Polytopes in Virtual Reality for Shared Control in Remote Manipulation Applications. *Frontiers in Robotics and AI*, *8*, 286. https://doi.org/10.3389/frobt.2021.730433

DRAFT