

bde: A Python Package for Bayesian Deep Ensembles via MILE

Vyron Arvanitis^{1*}, Angelos Aslanidis^{1*}, Emanuel Sommer^{2,3*¶}, and David Rügamer³

¹ Faculty of Physics, LMU Munich, Munich, Germany ² Department of Statistics, LMU Munich, Munich, Germany ³ Munich Center for Machine Learning, Munich, Germany ¶ Corresponding author * These authors contributed equally.

DOI: [10.21105/joss.10653](https://doi.org/10.21105/joss.10653)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Owen Lockwood](#) ↗ 

Reviewers:

- [@mbsuraj](#)
- [@tbrown122387](#)

Submitted: 03 February 2026

Published: 27 July 2026

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

bde is a Python package designed to bring state-of-the-art sampling-based Bayesian Deep Learning (BDL) to practitioners and researchers. The package combines the speed and high-performance capabilities of JAX ([Bradbury et al., 2018](#)) and blackjax ([Cabezas et al., 2024](#)) with the user-friendly API of scikit-learn ([Pedregosa et al., 2011](#)). It targets tabular supervised learning tasks, including distributional regression and (multi-class) classification, providing a seamless interface for Bayesian Deep Ensembles (BDEs) ([Sommer et al., 2024](#)) specifically implementing **Microcanonical Langevin Ensembles (MILE)** ([Sommer et al., 2025](#)).

The workflow of bde implements the two-stage BDE inference process of MILE. First, it optimizes `n_members` independent instances of a flexibly configurable feed-forward neural network using regularized empirical risk minimization (with the negative log-likelihood as loss) via the AdamW optimizer ([Loshchilov & Hutter, 2019](#)). Second, it transitions to a sampling phase using Microcanonical Langevin Monte Carlo ([Robnik et al., 2023](#); [Robnik & Seljak, 2024](#)), enhanced with a tuning phase adapted for Bayesian neural networks. This combination is referred to as MILE ([Sommer et al., 2025](#)). In essence, the optimization of the ensemble of neural networks first finds diverse high-likelihood modes, from which sampling then explores local posterior structure. This process generates an ensemble of samples (models) that constitute an implicit posterior approximation.

Software design

Because optimization and sampling across ensemble members are independent, bde exploits JAX's parallelization and just-in-time compilation to scale efficiently across CPUs, GPUs, and TPUs. Given new test data, the package approximates the posterior predictive, enabling point predictions, credible intervals, coverage estimates, and other uncertainty metrics through a unified interface. Further, this work currently targets the well-studied and empirically validated full-batch, fully-connected network setting for tabular data also studied in MILE ([Sommer et al., 2025](#)). This makes it particularly suitable for the chosen scikit-learn framework. Stochastic-gradient variants such as SMILE ([Sommer et al., 2026](#)) require different algorithmic and software design choices, yet will be considered for future extensions.

State of the field

Reliable uncertainty quantification (UQ) is increasingly viewed as a critical component of modern machine learning systems, and BDL provides a principled framework for achieving it ([Papamarkou et al., 2024](#)). While several libraries support optimization-based approaches such

as variational inference (Duffield et al., 2025), Laplace approximations (Daxberger et al., 2021), or classical Bayesian modeling (Abril-Pla et al., 2023), accessible tools for sampling-based inference in Bayesian neural networks remain scarce. Existing probabilistic programming and inference frameworks such as NumPyro (Phan et al., 2019) and blackjax (Cabezas et al., 2024) offer MCMC building blocks but require substantial manual configuration to achieve competitive Bayesian neural-network workflows.

Statement of need

bde addresses the gap outlined above by providing the first user-friendly implementation of MILE - a hybrid sampling technique shown to deliver strong predictive accuracy and calibrated uncertainty for Bayesian neural networks (Sommer et al., 2025). By providing full scikit-learn compatibility, the package enables seamless integration into existing machine learning workflows, allowing users to obtain principled Bayesian uncertainty estimates without specialized knowledge of MCMC dynamics, initialization strategies, or JAX internals.

Through automated orchestration of optimization, sampling, parallelization, and predictive inference, bde offers a fast, reproducible, and practical solution for applying sampling-based BDL methods to tabular supervised learning tasks.

Research impact statement

bde bridges the gap between high-performance MCMC research and practical data science. By providing a curated implementation of MILE for tabular data, it enables researchers and practitioners alike to easily apply BDEs. Its inclusion in the scikit-learn-contrib organization ensures adherence to rigorous software standards and API consistency, making it a trusted, community-ready tool for reproducible UQ in tabular machine learning.

Usage example

The following example illustrates a regression task with UQ using bde in only a few lines of code. Training inputs are assumed to be preprocessed and normalized. The workflow specifies the ensemble and sampling hyperparameters, fits the model, and obtains posterior predictive quantities, including predictive moments, credible intervals, and raw ensemble outputs.

```
from bde import BdeRegressor

regressor = BdeRegressor(
    n_members=8, # parallelizes over the available cores
    hidden_layers=[16, 16], # 2 hidden layers of width 16
    activation="relu", # (default)
    epochs=1000,
    validation_split=0.15,
    lr=1e-3,
    weight_decay=1e-4,
    patience=20,
    warmup_steps=5000,
    n_samples=200, # 200/10 x 8 = 160 final posterior samples
    n_thinning=10,
    # Controls MCMC exploration (default):
    desired_energy_var_start=0.5,
    desired_energy_var_end=0.1,
)
```

```
regressor.fit(x=X_train, y=y_train)
```

```
means, sigmas = regressor.predict(X_test, mean_and_std=True)
```

```
means, intervals = regressor.predict(X_test, credible_intervals=[0.1, 0.9])
```

```
raw = regressor.predict(X_test, raw=True)
```

Classification follows analogously using BdeClassifier.

Regression benchmark

We provide a small benchmark of bde on the airfoil (Dua & Graff, 2017) and the bikesharing (Fanaee-T, 2013) datasets. We report mean predictive performance (RMSE), UQ metrics (NLL in the distributional and mean regression formulation), reported as mean $\pm$ standard deviation over 5 independent model seeds and fixed train/test splits. The results show competitive out-of-the-box performance of BDE especially in UQ with its native distributional regression capability.

airfoil	RMSE	NLL (distr. regr.)	NLL (mean regr.)
Linear Model	0.6598 $\pm$ 0.0000	-	1.0032 $\pm$ 0.0000
Random Forest	0.2560 $\pm$ 0.0015	-	0.0567 $\pm$ 0.0057
XGBoost	0.2025 $\pm$ 0.0055	-	-0.1782 $\pm$ 0.0269
CatBoost	0.2393 $\pm$ 0.0036	0.1479 $\pm$ 0.1414	-0.0109 $\pm$ 0.0152
Deep Ensemble	0.3650 $\pm$ 0.0038	0.1760 $\pm$ 0.0043	0.4100 $\pm$ 0.0105
TabPFN (V2)	0.1359 $\pm$ 0.0028	-0.9338 $\pm$ 0.0195	-0.5769 $\pm$ 0.0205
BDE	0.1215 $\pm$ 0.0042	-0.9126 $\pm$ 0.0131	-0.6888 $\pm$ 0.0347

bikesharing	RMSE	NLL (distr. regr.)	NLL (mean regr.)
Linear Model	0.7796 $\pm$ 0.0000	-	1.1700 $\pm$ 0.0000
Random Forest	0.2440 $\pm$ 0.0020	-	0.0085 $\pm$ 0.0009
XGBoost	0.2143 $\pm$ 0.0010	-	-0.1215 $\pm$ 0.0049
CatBoost	0.2652 $\pm$ 0.0021	-0.3737 $\pm$ 0.0229	0.0918 $\pm$ 0.0080
Deep Ensemble	0.2880 $\pm$ 0.0052	-0.4550 $\pm$ 0.0173	0.1740 $\pm$ 0.0181
TabPFN (V2)	0.2103 $\pm$ 0.0008	-0.6856 $\pm$ 0.0063	-0.1400 $\pm$ 0.0041
BDE	0.2261 $\pm$ 0.0016	-0.7315 $\pm$ 0.0098	-0.0679 $\pm$ 0.0071

All models used 10 CPU cores without additional tuning. For BDE, we generated 1000 posterior samples from a feed-forward neural network with four hidden layers of width 16. While even highly optimized BDEs generally incur a higher computational cost than optimization-based competitors due to the iterative nature of MCMC sampling, this investment enables the construction of a flexible, non-parametric posterior approximation. This trade-off, as demonstrated above, yields strong performance and rigorous epistemic UQ, e.g. through calibrated credible intervals. All experimental configurations are provided in the released codebase to ensure reproducibility.

AI usage disclosure

Generative AI was used via GitHub Copilot for local, line- or block-level code autocompletion during software development, using the Claude Sonnet 3.7 and 4 models. Codex (codex-1) was additionally used to assist with the initial draft of the package documentation and minor refactors to ensure compatibility with the scikit-learn API. No AI tools were used for ideation, architectural or design decisions, code review, or testing strategy. All AI-generated suggestions

were critically reviewed, modified where necessary, and fully validated by the authors, who retain complete responsibility.

References

- Abril-Pla, O., Andreani, V., Carroll, C., Dong, L., Fonnesbeck, C. J., Kochurov, M., Kumar, R., Lao, J., Luhmann, C. C., Martin, O. A., Osthege, M., Vieira, R., Wiecki, T., & Zinkov, R. (2023). PyMC: A modern and comprehensive probabilistic programming framework in Python. *PeerJ Computer Science*, 9(e1516). <https://doi.org/10.7717/peerj-cs.1516>
- Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G., Paszke, A., VanderPlas, J., Wanderman-Milne, S., & Zhang, Q. (2018). *JAX: Composable transformations of Python+NumPy programs* (Version 0.3.13). <http://github.com/google/jax>
- Cabezas, A., Corenflos, A., Lao, J., & Louf, R. (2024). *BlackJAX: Composable Bayesian inference in JAX*. <https://arxiv.org/abs/2402.10797>
- Daxberger, E., Kristiadi, A., Immer, A., Eschenhagen, R., Bauer, M., & Hennig, P. (2021). Laplace Redux – Effortless Bayesian Deep Learning. *35th Conference on Neural Information Processing Systems (NeurIPS 2021)*.
- Dua, D., & Graff, C. (2017). *UCI machine learning repository*. University of California, Irvine, School of Information and Computer Sciences. <http://archive.ics.uci.edu/ml>
- Duffield, S., Donatella, K., Chiu, J., Klett, P., & Simpson, D. (2025). Scalable Bayesian Learning with posteriors. *The Thirteenth International Conference on Learning Representations*.
- Fanaee-T, H. (2013). *Bike Sharing Dataset*. UCI Machine Learning Repository.
- Loshchilov, I., & Hutter, F. (2019). Decoupled weight decay regularization. *International Conference on Learning Representations*.
- Papamarkou, T., Skoularidou, M., Palla, K., Aitchison, L., Arbel, J., Dunson, D., Filippone, M., Fortuin, V., Hennig, P., Hernández-Lobato, J. M., Hubin, A., Immer, A., Karaletsos, T., Khan, M. E., Kristiadi, A., Li, Y., Mandt, S., Nemeth, C., Osborne, M. A., ... Zhang, R. (2024). Position: Bayesian Deep Learning is Needed in the Age of Large-Scale AI. *Proceedings of the 41st International Conference on Machine Learning*.
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, E. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12, 2825–2830.
- Phan, D., Pradhan, N., & Jankowiak, M. (2019). Composable effects for flexible and accelerated probabilistic programming in NumPyro. *arXiv Preprint arXiv:1912.11554*.
- Robnik, J., De Luca, G. B., Silverstein, E., & Seljak, U. (2023). Microcanonical Hamiltonian Monte Carlo. *The Journal of Machine Learning Research*, 24(1), 14696–14729.
- Robnik, J., & Seljak, U. (2024). Fluctuation without dissipation: Microcanonical Langevin Monte Carlo. *Symposium on Advances in Approximate Bayesian Inference*, 111–126.
- Sommer, E., Diao, K., Robnik, J., Seljak, U., & Rügamer, D. (2026). Can Microcanonical Langevin Dynamics Leverage Mini-Batch Gradient Noise? *Forty-Third International Conference on Machine Learning*.
- Sommer, E., Robnik, J., Nozadze, G., Seljak, U., & Rügamer, D. (2025). Microcanonical Langevin Ensembles: Advancing the Sampling of Bayesian Neural Networks. *The Thirteenth International Conference on Learning Representations*.

Sommer, E., Wimmer, L., Papamarkou, T., Bothmann, L., Bischl, B., & Rügamer, D. (2024). Connecting the Dots: Is Mode-Connectedness the Key to Feasible Sample-Based Inference in Bayesian Neural Networks? *Proceedings of the 41st International Conference on Machine Learning*.