

eratosthenes: Synchronizing archaeological chronologies with a focus on artifact types

Stephen A. Collins-Elliott ¹✉

¹ Department of Classics, University of Tennessee, Knoxville, Tennessee, United States  
Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Arfon Smith](#)  

Reviewers:

- [@sebastien-plutniak](#)
- [@bocinsky](#)
- [@joeroe](#)

Submitted: 30 June 2025

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Archaeological chronology-building centers on two types of dates, absolute and relative. Absolute dates are associated with a calendrical date (even approximate), and relative refer to events only known via relationships to others (before/after). Relative events are then associated to absolute via contextual or logical associations. E.g. a *terminus post quem* (*t.p.q.*) of a datable coin found in a soil deposit ensures the deposit came after the production of the coin. Applying probabilistic methods to chronology has traditionally centered on radiocarbon dating, but the broader goal of extending formal methods to all aspects of chronology necessitate a way to address artifact typologies. Artifacts largely persist in being dated by qualitative judgment (e.g. “around the start of the 4th century BCE”). Moreover, typologies are in a constant state of revision and adjustment, such that the dates of types may differ according to authority. The reasons why a type is dated the way it is (i.e., which sites, deposits, and comparisons inform its date) can also become opaque, such that investigators inherently resist chronological revisions in order to assess its bibliography (on this conservatism, see Rotroff (2005, p. 20)). This situation presents a challenge for any researcher applying statistical methods to datable artifacts, as one must make *ad hoc* and often awkward decisions, resulting in what Lavan (2021, p. 15) has called “abonimable dates.”

The R package *eratosthenes* (named after Eratosthenes of Cyrene, author of the *Chronographiai*) provides functions for chronology-building, above all to bring artifact dating within the scope of formal mathematical estimation. Hence, an investigator can obtain separate probability density functions (p.d.f.) for the production, use, and deposition of an artifact type, in addition to marginal p.d.f.s for all relative sequential events (howsoever determined) and absolute constraints (howsoever defined). It uses Gibbs sampling, by now a conventional Markov Chain Monte Carlo method in archaeological chronology (Buck et al., 1996; Geman & Geman, 1984). Using Rcpp (Eddelbuettel & Balamuta, 2018), *eratosthenes* performs a two-step Gibbs routine, the first a preliminary sampler to select a starting date, and a second main sampler that uses consistent batch means (CBM) as a stopping rule, given that convergence in distribution is assured (Flegal et al., 2008; Jones et al., 2006). Full reporting on the Monte Carlo standard errors (MCSE) is provided, giving an error in +/- years for each marginal density. Finally, *eratosthenes* provides functions for assessing the level of dependence of events upon each other within the joint conditional. Changes in dates brought about by any alteration in the structure of a chronology can therefore be readily evaluated. In sum, *eratosthenes* allows for expedient revision of chronologies, transparency in the definition of the full joint conditional, and statistics on the certainty of estimates via MCSE.

Statement of Need

Constructing chronologies via formal means is a major disciplinary goal, with a broad array of software developed to those ends. The draft of the [CRAN Task View: Archaeological](#)

Science maintained by Ben Marwick provides a section on chronological dating software in R (R Core Team, 2024). The calibration of ^{14}C dates and the estimation of their posterior probability densities given constraints (Buck & Juárez, 2025) are well served by OxCal (Bronk Ramsey, 2009) and BCal (Buck et al., 1999), as well as R packages oxCAAR (Hinz et al., 2021), Bchron (Haslett & Parnell, 2008), c14bazAAR (Schmid et al., 2019), and rcarbon (Crema et al., 2017). General chronological modeling is served by Chronomodel (Lanos & Philippe, 2017), which also centers on radiocarbon dating, and ChronoLog (Levy et al., 2021), which focuses on discretized time intervals. The R package ArchaeoPhases (Philippe & Vibet, 2020) handles post-processing of samples from OxCal, BCal, and ChronoModel. Other chronological software has focused on modeling count data over time, such as kairos (Frerebeau, 2025) and baorista (Crema, 2025), which focuses on counts of durative/interval events.

Given that there exists substantial software for calibrating radiocarbon dates, eratosthenes does not aim to perform this task. Likewise, the formal process of establishing relative sequences of contexts and finds via comparison, called seriation (or ordination), is a computationally difficult problem well served by many R packages, such as seriation (Hahsler et al., 2008), vegan (Oksanen et al., 2024), borai (Hui, 2016), ecoCopula (Popovic et al., 2022), VGAM (Yee, 2004), and lakthesis (Collins-Elliott, 2026a).

Two needs which eratosthenes aims to satisfy are (1) estimation of artifact dates (production, use, deposition) via formal means and (2) tools for evaluating the dependence of events on each other, which are discussed in detail below. The approach taken by eratosthenes, in which different aspects of artifact dates are determined *a posteriori* via contextual relationships, can be contrasted with other approaches, such as cerardat in the R SPARTAAS package (Bellanger & Husi, 2012), which works from a single artifact date given as fixed *a priori* input (see also Bellanger et al., 2021).

Estimating Dates of Artifact Production, Use, and Deposition

Dating artifact types is handled by working backwards from depositional contexts, which is their primary point of observation. Estimating the date of artifact production requires a stated rule, with two options given in eratosthenes. To start, initial threshold boundaries are established between the earliest depositional context containing that artifact-type and the context immediately prior in sequence lacking it. The "earliest" rule samples from within those initial thresholds. The default, "naive" rule samples between a sample taken using the "earliest" rule as the lower bound and an upper bound formed by depositional date of that artifact. After estimating production dates, a use date is sampled between its dates of production and deposition. Figure 1 illustrates these rules.




Figure 1: Rules of earliest and naive (default) for estimating the date of production of an artifact type, sampled on each m iteration of the Gibbs sampler.

Evaluating Displacement of Events

The impact of events on one another is assessed via “displacement,” representing the shift in the date of a target event i should another event j be omitted from the joint conditional. Let $\tilde{x}_i$ be the estimated marginalized Monte Carlo mean date using all events within the joint conditional, and let $\tilde{x}_i^{(-j)}$ be the Monte Carlo mean when event j has been omitted. Squared displacement of j upon i is defined as

$$\delta^2(i, j) = (\tilde{x}_i^{(-j)} - \tilde{x}_i)^2.$$

The omission of j changes the date of i by $\sqrt{\delta^2}$ amount of time (typically years). Conversely, the influence of an event j upon all others is measured by mean squared displacement (MSD), which is the mean of all squared displacements when event j has been omitted. Where Θ represents the set of all relative and absolute events, MSD is defined as

$$\text{MSD}(j) = \frac{1}{n-1} \sum_{i \in \Theta, i \neq j} \delta^2(i, j).$$

eratosthenes computes the MSD for all events via a “jackknife” or “leave one out”-style of routine, omitting each event iteratively.

Application

For the purposes of illustration, an initial application was undertaken for a small sample of events in the Mediterranean from the last four centuries BCE (see `inst/eda20250628.rmd` in the package directory). Results are shown in Figure 2 for a selection of two depositional contexts and five shipwrecks. One can note, for example, the effect of using the sack of Carthage in 146 BCE as a *terminus ante quem* (*t.a.q.*) for the depositional date of context Byrsa II B 19.2 at that site (Lancel et al., 1982, p. 194).

The sack of Carthage has also been a key point for dating a particular type of ceramic transport container, the Dressel 1 amphora type. Since it has not been found in pre-destruction layers, the start of its production has been dated to the later part of the 2nd century BCE (Tchernia, 1986, p. 42). Rather than just relying on one site, however, absence from any context within the entire set of conditional events in eda20250628 yields densities for its production, use, and deposition (Figure 3).

Future Work

Current work in progress by the author which relies upon eratosthenes involves the synchronism of ceramics, coinage, radiocarbon dates, depositional/seriated sequences, and historical events for the central Mediterranean in the last four centuries BCE. Regular progress is tracked via git at [eratosthenes-data](https://github.com/eratosthenes-data), with major releases uploaded to Zenodo (Collins-Elliott, 2026b).




Figure 2: Marginal p.d.f.s of 2 depositional events and 5 shipwrecks from the Mediterranean, given the joint conditional constructed in `inst/eda20250628.rmd`. The wreck Grand Congloué A is earlier than the traditional date: future datasets will work to revise sequencing and constraints.




Figure 3: P.d.f.s of the production, use, and deposition of the Dressel 1B type amphora, using the “naive” production rule and given the joint conditional constructed in `inst/eda20250628.rmd`.

Acknowledgments

The author would like to thank the reviewers for their helpful comments and suggestions. Any errors remain those of the author.

References

- Bellanger, L., Coulon, A., & Husi, P. (2021). PerioClust: A Simple Hierarchical Agglomerative Clustering Approach Including Constraints. In T. Chadjipadelis, T. Lausen, A. Markos, T. R. Lee, A. Montanari, & R. Nugent (Eds.), *Data Analysis and Rationality in a Complex World* (pp. 1–8). Springer. https://doi.org/10.1007/978-3-030-60104-1_1
- Bellanger, L., & Husi, P. (2012). Statistical tool for dating and interpreting archaeological contexts using pottery. *Journal of Archaeological Science*, 34, 777–790. <https://doi.org/10.1016/j.jas.2011.06.031>
- Bronk Ramsey, C. (2009). Bayesian Analysis of Radiocarbon Dates. *Radiocarbon*, 51, 337–360. <https://doi.org/10.1017/s0033822200033865>
- Buck, C. E., Cavanagh, W. G., & Litton, C. D. (1996). *Bayesian Approach to Interpreting Archaeological Data*. John Wiley and Sons.
- Buck, C. E., Christen, J. A., & James, G. N. (1999). BCal: An On-line Bayesian Radiocarbon Calibration Tool. *Internet Archaeology*, 7. <https://doi.org/10.11141/ia.7.1>
- Buck, C. E., & Juárez, M. (2025). Bayesian radiocarbon modelling for beginners. *Archaeometry*, 67, 31–48. <https://doi.org/10.1111/arcm.12998>
- Collins-Elliott, S. A. (2026a). Lakthesis: Consensus seriation via iterative regression of partial rankings for binary data. *Journal of Applied Statistics*, 1–23. <https://doi.org/10.1080/02664763.2026.2672564>
- Collins-Elliott, S. A. (2026b). *Probability Densities of Archaeological Dates in the Central Mediterranean, ca. 4th-1st c. BCE*. <https://doi.org/10.5281/zenodo.21580368>
- Crema, E. R. (2025). A Bayesian alternative for aoristic analyses in archaeology. *Archaeometry*, 67, 7–30. <https://doi.org/10.1111/arcm.12984>
- Crema, E. R., Bevan, A., & Shennan, S. (2017). Spatio-temporal approaches to archaeological radiocarbon dates. *Journal of Archaeological Science*, 87, 1–9. <https://doi.org/10.1016/j.jas.2017.09.007>
- Eddelbuettel, D., & Balamuta, J. J. (2018). Extending R with C++: A Brief Introduction to Rcpp. *The American Statistician*, 72, 28–36. <https://doi.org/10.1080/00031305.2017.1375990>
- Flegal, J. M., Haran, M., & Jones, G. L. (2008). Markov Chain Monte Carlo: Can We Trust the Third Significant Figure? *Statistical Science*, 23, 250–260. <https://doi.org/10.1214/08-STS257>
- Frerebeau, S. (2025). *Kairos: Analysis of Chronological Patterns from Archaeological Count Data*. <https://CRAN.R-project.org/package=kairos>
- Geman, S., & Geman, D. (1984). Stochastic Relaxation, Gibbs Distributions, and the Bayesian Restoration of Images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 6, 721–741. <https://doi.org/10.1016/b978-0-08-051581-6.50057-x>
- Hahsler, M., Hornik, K., & Buchta, C. (2008). Getting Things in Order: An Introduction to the R Package seriation. *Journal of Statistical Software*, 25, 1–34. <https://doi.org/10.18637/jss.v025.i03>

- 150 Haslett, J., & Parnell, A. C. (2008). A Simple Monotone Process with Application to
151 Radiocarbon-Dated Depth Chronologies. *Journal of the Royal Statistical Society: Series C*
152 (*Applied Statistics*), 57, 399–418. <https://doi.org/10.1111/j.1467-9876.2008.00623.x>
- 153 Hinz, M., Schmid, C., Knitter, D., & Tietze. (2021). *oxcAAR: Interface to 'OxCal' Radiocarbon*
154 *Calibration*. <https://doi.org/10.32614/CRAN.package.oxcAAR>
- 155 Hui, F. K. C. (2016). Boral: Bayesian Ordination and Regression Analysis of Multivariate
156 Abundance Data in R. *Methods in Ecology and Evolution*, 7, 744–750. <https://doi.org/10.1111/2041-210X.12514>
- 158 Jones, G. L., Haran, M., Caffo, B. S., & Neath, R. (2006). Fixed-Width Output Analysis
159 for Markov Chain Monte Carlo. *Journal of the American Statistical Association*, 101,
160 1537–1547. <https://doi.org/10.1198/016214506000000492>
- 161 Lancel, S., Morel, J.-P., & Thuillier, J.-P. (1982). *Byrsa II: rapports préliminaires sur les*
162 *fouilles 1977-1978 : niveaux et vestiges puniques*. École française de Rome.
- 163 Lanos, P., & Philippe, A. (2017). Hierarchical Bayesian modeling for combining dates in
164 archeological context. *Journal de La Société Française de Statistique*, 158, 72–88.
- 165 Lavan, L. (2021). Checklist of Dates for Pottery Types. In *Public Space in the Late Antique*
166 *City: Volume 2* (pp. 15–82). Brill. https://doi.org/10.1163/9789004423824_015
- 167 Levy, E., Geeraerts, G., Pluquet, F., Piasetzky, E., & Fantalkin, A. (2021). Chronological
168 networks in archaeology: A formalised scheme. *Journal of Archaeological Science*, 127,
169 105225. <https://doi.org/10.1016/j.jas.2020.105225>
- 170 Oksanen, J., Simpson, G. L., Blanchet, F. G., Kindt, R., Legendre, P., Minchin, P. R., O'Hara,
171 R. B., Solymos, P., Stevens, M. H. H., Szoecs, E., Wagner, H., Barbour, M., Bedward,
172 M., Bolker, B., Borcard, D., Carvalho, G., Chirico, M., De Caceres, M., Durand, S., ...
173 Weedon, J. (2024). *Vegan: Community Ecology Package*. <https://doi.org/10.32614/CRAN.package.vegan>
- 175 Philippe, A., & Vibet, M.-A. (2020). Analysis of Archaeological Phases Using the R Package
176 *ArchaeoPhases*. *Journal of Statistical Software*, 93(Code Snippet 1), 1–25. <https://doi.org/10.18637/jss.v093.c01>
- 178 Popovic, G. C., Hui, F. K. C., & Warton, D. I. (2022). Fast Model-Based Ordination with
179 Copulas. *Methods in Ecology and Evolution*, 13, 194–202. <https://doi.org/10.1111/2041-210X.13733>
- 181 R Core Team. (2024). *R: A Language and Environment for Statistical Computing*. R
182 Foundation for Statistical Computing. <http://www.r-project.org/>
- 183 Rotroff, S. I. (2005). Four centuries of Athenian pottery. In V. F. Stolba & L. Hannestad
184 (Eds.), *Chronologies of the Black Sea area in the period c. 400-100 BC*. Aarhus University
185 Press.
- 186 Schmid, C., Seidensticker, D., & Hinz, M. (2019). c14bazAAR: An R package for downloading
187 and preparing C14 dates from different source databases. *Journal of Open Source Software*,
188 4, 1914. <https://doi.org/10.21105/joss.01914>
- 189 Tchernia, A. (1986). *Le vin de l'Italie romaine. Essai d'histoire économique d'après les*
190 *amphores*. École française de Rome.
- 191 Yee, T. W. (2004). A New Technique for Maximum-Likelihood Canonical Gaussian Ordination.
192 *Ecological Monographs*, 74, 685–701. <https://doi.org/10.1890/03-0078>