The Journal of Open Source Software

k-diagram: Rethinking Forecasting Uncertainty via Polar-based Visualization

Kouao Laurent Kouadio [1,2]

1 School of Geosciences and Info-Physics, Central South University, Changsha, Hunan, 410083, China **2** Hunan Key Laboratory of Nonferrous Resources and Geological Hazards Exploration, Changsha, Hunan, 410083, China

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Julia Romanowska

Reviewers:

- @ChinniAbburi
- @cbueth

Submitted: 09 May 2025
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

`k-diagram` is an open-source Python package designed for the in-depth interpretation and diagnosis of probabilistic forecasts. Moving beyond traditional aggregate metrics, the package provides a suite of novel visualization tools, primarily based on polar coordinate systems, to dissect the complex spatiotemporal structure of forecast uncertainty and errors. By mapping statistical properties such as sharpness, reliability, and temporal stability onto intuitive geometric representations, `k-diagram` enables researchers and practitioners to identify model biases, understand forecast degradation over time, and communicate uncertainty characteristics more effectively. The package is designed to be a practical extension to the standard forecasting workflow, providing the visual evidence needed for more robust model evaluation and trustworthy, context-aware decision-making.

Statement of Need

The evaluation of probabilistic forecasts has a rigorous theoretical foundation based on concepts of calibration and sharpness, which are jointly assessed using proper scoring rules (Gneiting et al., 2007). However, these scores are typically aggregated into a single value, which can obscure vital information about a model's performance in heterogeneous spatiotemporal settings. This is a critical limitation, as modern machine learning models, such as Temporal Fusion Transformers (Lim et al., 2021), are increasingly applied to complex, high-dimensional problems where understanding the local and temporal behavior of uncertainty is paramount. A growing body of applied research highlights this challenge in fields as diverse as predictive policing (Rummens & Hardyns, 2021), energy forecasting (Y. Liu et al., 2021), chaotic market dynamics (Caulk et al., 2022), climatology (Baillie & Chung, 2002) and geohazard (J. Liu et al., 2024).

While an ecosystem of open-source forecasting tools exists, many focus on specific modeling or post-processing tasks, such as forecast reconciliation (Biswas et al., 2025), or provide verification suites for specific domains like climate science (Brady & Spring, 2021). General-purpose libraries like matplotlib (Hunter, 2007) and seaborn (Waskom, 2021) provide the building blocks but lack dedicated functions for the specialized diagnostics needed for high-dimensional uncertainty. Even established visualizations like fan charts, which have seen recent innovations (Sokol, 2025), are primarily designed for single time series and do not scale well to problems involving thousands of simultaneous forecasts(Hong et al., 2025). This creates a critical gap between the generation of complex probabilistic forecasts and the ability to interpret them effectively.

`k-diagram` addresses this gap by providing a scalable and intuitive toolkit designed specifically for the visual diagnosis of spatiotemporal probabilistic forecasts (Kouadio, 2025; J. Liu et al.,

DRAFT

2024). The package's novelty lies in its use of polar coordinates to map different dimensions of forecast performance, such as uncertainty magnitude, reliability, and temporal stability, onto angle and radius. This approach provides compact overviews that reveal patterns obscured in traditional Cartesian plots. By providing clear visual answers to key diagnostic questions (e.g., "Where is a forecast least certain?", "How is its uncertainty evolving?"), `k-diagram` serves as an essential tool for any researcher or practitioner seeking to move beyond aggregate metrics and gain a deeper, more actionable understanding of their forecasting models.

Functionality

`k-diagram` is implemented in Python (Python Software Foundation, 2008; Van Rossum & Drake, 2009), leveraging core scientific libraries including `numpy` (Harris et al., 2020), `pandas` (McKinney, 2010; Reback et al., 2020), `matplotlib` (Hunter, 2007), `scipy` (Virtanen et al., 2020), and `scikit-learn` (Pedregosa et al., 2011). The core functionality is organized around a cohesive API for diagnosing key aspects of forecast quality (see Figure 1):

- **Uncertainty and Error Diagnostics:** The primary contribution of `k-diagram` is a suite of novel polar visualizations for dissecting forecast performance (Kouadio, 2025). The `kdiagram.plot.uncertainty`, `kdiagram.plot.errors`, and `kdiagram.plot.probabilistic` modules provide functions to visualize:
  - **Interval Performance:** Metrics such as prediction interval coverage, the magnitude of interval failures (anomalies), and the temporal consistency of interval widths.
  - **Error Distributions:** Polar error bands are used to separate systemic bias from random error, while polar violins—a novel adaptation of the traditional violin plot (Hintze & Nelson, 1998)—are used to compare the full error distributions of multiple models.
  - **Probabilistic Diagnostics:** A dedicated suite of plots for evaluating the full predictive distribution, including Polar Probability Integral Transform (PIT) Histograms for calibration, Sharpness Diagrams for precision, and Continuous Ranked Probability Score (CRPS) plots for overall skill, based on the foundational concepts of probabilistic forecasting (Gneiting et al., 2007).
  - **2D Uncertainty:** The package introduces velocity diagram, polar heatmaps, quiver plots, and error ellipses to visualize complex, multi-dimensional error and uncertainty structures.
- **Model Evaluation and Comparison:** The package implements established, well-regarded evaluation methods, adapting them for clarity and comparison:
  - **Taylor Diagrams:** Functions in `kdiagram.plot.evaluation` generate Taylor Diagrams based on the original formulation by (Taylor, 2001) to compare models on correlation, standard deviation, and RMSD.
  - **Reliability Diagrams:** The `kdiagram.plot.comparison` module provides functions to plot reliability diagrams, a standard method in forecast verification for assessing calibration (Jolliffe & Stephenson, 2012).
- **Distribution and Feature Visualization:**
  - **1D Distributions:** Utilities are provided for plotting histograms and Kernel Density Estimates (KDEs), a standard non-parametric density estimation technique (Silverman, 1986), both in Cartesian and novel polar ring formats.
  - **Feature Importance:** Radar charts under `kdiagram.plot.feature_based` visualize and compare feature importance profiles ("fingerprints") across models.
- **Relationship Visualization**: Polar plots in `kdiagram.plot.relationship` offer a novel perspective on the correlation between true and predicted values by mapping them to angle and radius.

DRAFT

- **Utilities and Interface:** The package is supported by a set of helper functions for reshaping quantile-based forecast data and a command-line interface (CLI) for generating key plots directly from data files.



Figure 1: Structure of the k-diagram, illustrating the identification of global components.

The package is designed for ease of use and customization, allowing users to control plot aesthetics, angular coverage (`acov`), and color mapping to tailor the visualizations for their specific domain.

Illustrative Diagnostics and Application

The practical utility of `k-diagram` is best demonstrated through its key diagnostic plots, which are grounded in clear statistical concepts and reveal model behaviors often hidden by aggregate metrics (see Figure 2).

The **Coverage Evaluation** plot (Figure 2a) provides a point-wise diagnostic of interval performance. For each observation y_i and its corresponding prediction interval $[L_i, U_i]$, a binary coverage value c_i is determined as:

$$c_i = \mathbf{1}(L_i \leq y_i \leq U_i)$$

where $\mathbf{1}(\cdot)$ is the indicator function. The plot visualizes each c_i, allowing for a granular analysis of where interval failures occur. The average of these outcomes provides the overall empirical coverage, which at 81.1% is close to the nominal 80% for the Q10-Q90 interval shown.

The **Model Error Distributions** diagram (Figure 2b) offers a comparative view by visualizing the full error distribution for multiple models. It uses polar violins, where the shape of each violin is determined by the Kernel Density Estimate (KDE) of the model's errors (Silverman, 1986). The resulting diagram clearly distinguishes a "Good Model" (unbiased and narrow) from a "Biased Model" (shifted from the zero-error line) and an "Inconsistent Model" (wide and dispersed), revealing performance trade-offs that a single error score would miss.

Finally, the **Forecast Horizon Drift** diagram (Figure 2c) visualizes how uncertainty evolves over time. For each forecast horizon j, it calculates the mean interval width, $\bar{w}_j$, across all N spatial locations as:

$$\bar{w}_j = \frac{1}{N} \sum_{i=1}^{N} (U_{i,j} - L_{i,j})$$

The increasing height of the bars from 2023 to 2026 provides an immediate and intuitive confirmation that the model's uncertainty grows as it forecasts further into the future.

DRAFT



Figure 2: Figure 2: Model performance evaluation. (a) Coverage Evaluation: radial plot comparing empirical coverage against nominal quantile levels (average coverage = 0.811). (b) Model Error Distributions: The radial axis represents the error value, with the dashed circle indicating zero error. The width of each violin shows the density of errors, revealing that the "Good Model" is unbiased and consistent, the "Biased Model" consistently under-predicts, and the "Inconsistent Model" has high variance. (c) Forecast Horizon Drift: radial bar chart of uncertainty width (Q90–Q10) for forecast years 2023–2026, illustrating increasing prediction uncertainty.

These visualization methods were developed alongside research applying advanced deep learning models, such as physics-informed deep learning[1], to complex environmental forecasting challenges. Specifically, these polar diagnostics were utilized to analyze and interpret the uncertainty associated with land subsidence predictions using an Extreme Temporal Fusion Transformer model (Kouadio et al., 2025) in Nansha city, China.

Full usage examples and a gallery of all plot types are available in the official documentation's gallery section. For a deeper understanding of the mathematical concepts and interpretation guides, please refer to the detailed User Guide. The complete mathematical foundations and derivations for all visualizations are provided in the official Technical Report (Kouadio, 2025).

Availability and Community

The latest stable release of `k-diagram` is available on the Python Package Index (PyPI) and can be installed via `pip install k-diagram`. The package is distributed under the OSI-approved Apache License 2.0. Comprehensive documentation, including a user guide, an example gallery, and a detailed API reference, is hosted at https://k-diagram.readthedocs.io/. I welcome contributions from the community; bug reports, feature requests, and development discussions occur on the GitHub repository. Detailed guidelines for contributors can be found in the documentation.

Acknowledgements

I extend my sincere gratitude to the anonymous colleagues who provided invaluable feedback during the development of `k-diagram`, as well as those who rigorously tested its early iterations. Their insights and dedication were instrumental in refining the software. I also appreciate the constructive feedback from reviewers and early users, whose contributions have significantly enhanced the quality and usability of the project.

[1]For an overview of the concepts behind Physics-Informed Neural Networks (PINNs), see: https://fusion-lab.readthedocs.io/en/latest/user_guide/models/pinn/index.html

References

Baillie, R. T., & Chung, S. K. (2002). Modeling and forecasting from trend-stationary long memory models with applications to climatology. *International Journal of Forecasting*, *18*(2), 215–226. https://doi.org/10.1016/S0169-2070(01)00154-6

Biswas, A., Nespoli, L., Azzimonti, D., Zambon, L., Rubattu, N., & Corani, G. (2025). BayesReconPy: A python package for forecast reconciliation. *Journal of Open Source Software*, *10*(111), 8336. https://doi.org/10.21105/joss.08336

Brady, R. X., & Spring, A. (2021). Climpred: Verification of weather and climate forecasts. *Journal of Open Source Software*, *6*(59), 2781. https://doi.org/10.21105/joss.02781

Caulk, R. A., Törnquist, E., Voppichler, M., Lawless, A. R., McMullan, R., Santos, W. C., Pogue, T. C., Vlugt, J. van der, Gehring, S. P., & Schmidt, P. (2022). FreqAI: Generalizing adaptive modeling for chaotic time-series market forecasts. *Journal of Open Source Software*, *7*(80), 4864. https://doi.org/10.21105/joss.04864

Gneiting, T., Balabdaoui, F., & Raftery, A. E. (2007). Probabilistic forecasts, calibration and sharpness. *Journal of the Royal Statistical Society. Series B: Statistical Methodology*, *69*(2), 243–268. https://doi.org/10.1111/j.1467-9868.2007.00587.x

Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Memmesheimer, S., Backx, T., & others. (2020). Array programming with NumPy. *Nature*, *585*(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2

Hintze, J. L., & Nelson, R. D. (1998). Violin plots: A box plot-density trace synergism. *The American Statistician*, *52*(2), 181–184. https://doi.org/10.2307/2685478

Hong, S., Choi, Y., & Jeon, J. J. (2025). Interpretable water level forecaster with spatiotemporal causal attention mechanisms. *International Journal of Forecasting*, *41*(3), 1037–1054. https://doi.org/10.1016/j.ijforecast.2024.10.003

Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, *9*(3), 90–95. https://doi.org/10.1109/MCSE.2007.55

Jolliffe, I. T., & Stephenson, D. B. (2012). *Forecast verification: A practitioner's guide in atmospheric science*. Wiley. https://doi.org/10.1002/9781119960003

Kouadio, K. L. (2025). *k-diagram: Technical report — derivations and details* (Version 1.2.3). School of Geosciences; Info-physics, Central South University. https://doi.org/10.5281/zenodo.17051183

Kouadio, K. L., Liu, Z., Liu, R., Bizimana, P. C., Yang, G., & Liu, W. (2025). *XTFT: A Next-Generation Temporal Fusion Transformer for Uncertainty-Rich Time Series Forecasting*. TechRxiv. https://doi.org/10.22541/au.175390529.91420978/v1

Lim, B., Arík, S. O., Loeff, N., & Pfister, T. (2021). Temporal fusion transformers for interpretable multi-horizon time series forecasting. *International Journal of Forecasting*, *37*(4), 1748–1764. https://doi.org/10.1016/j.ijforecast.2021.03.012

Liu, J., Liu, W., Allechy, F. B., Zheng, Z., Liu, R., & Kouadio, K. L. (2024). Machine learning-based techniques for land subsidence simulation in an urban area. *Journal of Environmental Management*, *352*(2024), 17. https://doi.org/10.1016/j.jenvman.2024.120078

Liu, Y., Davanloo Tajbakhsh, S., & Conejo, A. J. (2021). Spatiotemporal wind forecasting by learning a hierarchically sparse inverse covariance matrix using wind directions. *International Journal of Forecasting*, *37*(2), 812–824. https://doi.org/10.1016/j.ijforecast.2020.09.009

McKinney, W. (2010). Data Structures for Statistical Computing in Python. In S. van der Walt & J. Millman (Eds.), *Proceedings of the 9th python in science conference* (pp. 56–61). SciPy. https://doi.org/10.25080/majora-92bf1922-00a

DRAFT

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Olsczewski, B., Blondel, M., Prejbal, F., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, É. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, *12*, 2825–2830. https://scikit-learn.org/stable/

Python Software Foundation. (2008). *Python language reference, version 3.x*. https://www.python.org

Reback, J., McKinney, W., Bossche, J. V. den, Augspurger, T., Cloud, P., Sinhrks, & others. (2020). pandas: a foundational Python library for data analysis and manipulation. *Proceedings of the 19th Python in Science Conference*, 1–9. https://doi.org/10.25080/majora-342d178e-001

Rummens, A., & Hardyns, W. (2021). The effect of spatiotemporal resolution on predictive policing model performance. *International Journal of Forecasting*, *37*(1), 125–133. https://doi.org/10.1016/j.ijforecast.2020.03.006

Silverman, B. W. (1986). *Density estimation for statistics and data analysis*. Chapman; Hall/CRC. ISBN: 9780412246203

Sokol, A. (2025). Fan charts 2.0: Flexible forecast distributions with expert judgement. *International Journal of Forecasting*, *41*(3), 1148–1164. https://doi.org/10.1016/j.ijforecast.2024.11.009

Taylor, K. E. (2001). Summarizing quantitative measures of model performance in a single diagram. *Journal of Geophysical Research: Atmospheres*, *106*(D7), 7183–7192. https://doi.org/10.1029/2000JD900719

Van Rossum, G., & Drake, F. L. (2009). *Python 3 reference manual*. CreateSpace. ISBN: 1441412697

Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Wehrer, W., Huttunen, J., Håcklin, T., Straub, S., Pike, J., Petroff, A., Conti, K., Lieberman, R., Pollard, J., Nichols, B., Raimi, J., … Vázquez-Baeza, Y. (2020). SciPy 1.0: fundamental algorithms for scientific computing in Python. *Nature Methods*, *17*(3), 261–272. https://doi.org/10.1038/s41592-019-0686-2

Waskom, M. L. (2021). Seaborn: Statistical data visualization. *Journal of Open Source Software*, *6*(60), 3021. https://doi.org/10.21105/joss.03021

DRAFT