The Journal of Open Source Software

pytau: A Python package for streamlined changepoint model analysis in neuroscience

Abuzar Mahmood [1,2]

1 Swartz Foundation Computational Neuroscience Fellow, Volen Center for Complex Systems, Brandeis University, Waltham, MA, USA **2** Department of Psychology, Brandeis University, Waltham, MA, USA

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: Frederick Boehm

Reviewers:

- @ZachLoschin
- @rly
- @JustinShenk
- @HectorMozo3110

Submitted: 08 April 2025
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Summary

Analyzing complex biological data, particularly time-series data from neuroscience experiments, often requires sophisticated statistical modeling to identify significant changes in system dynamics. Several decades of research has emphasized that the dynamics of neural activity may show sharp changes accurately captured by models detecting state transitions such as Hidden aMarkov Models and changepoint models (Giahi Saravani et al., 2019; Jones et al., 2007; Seidemann et al., 1996). pytau is a Python software package designed to perform streamlined, batched inference for changepoint models across different parameter grids and datasets. It provides tools to efficiently query and analyze the results from sets of fitted models, facilitating the study of dynamic processes in biological systems, such as neural ensemble activity in response to stimuli. The package integrates with PyMC3 for Bayesian inference of these models (providing estimates of uncertainty in inference which are critical for noisy datasets usually with small sample sizes and low channel counts common in neuroscience) and provides utilities for data preprocessing, model fitting, and result visualization. The package has been successfully used in published research (Flores & Lin, 2023; Mahmood et al., 2023) and is currently being utilized in several ongoing studies (Baas-Thomas et al., 2025; Calia-Bogan et al., 2025; Mahmood et al., 2025; Mazzio et al., 2025).

Statement of need

Understanding how neural populations encode information often involves analyzing activity changes over time, potentially across different experimental conditions, parameters, or subjects. Fitting and comparing complex models like Bayesian changepoint models across numerous datasets or parameter settings can be computationally intensive and logistically challenging. There is a need for tools that streamline this process, enabling researchers to efficiently apply these models in batch, manage the results, and compare outcomes across conditions. pytau aims to fill this gap by providing a modularized pipeline specifically for fitting and analyzing changepoint models applied to neuroscience data, enabling efficient comparisons and analysis. This need is demonstrated by the tool's adoption in recent studies examining neural dynamics in taste processing (Mahmood et al., 2023) and taste aversion learning (Flores & Lin, 2023).

The package offers several key advantages:

1. **Batch processing**: Automates the fitting of models across multiple datasets and parameter configurations
2. **Database management**: Organizes and tracks model fits for easy retrieval and comparison
3. **Visualization tools**: Provides specialized plotting functions for changepoint model results, including:
    - Raster plots with overlaid changepoints
    - State-dependent firing rate visualizations

DRAFT

- Transition-aligned activity plots
- Model comparison visualizations

4. **Flexible model specification**: Supports various changepoint model configurations for different analysis needs
5. **Statistical analysis**: Includes tools for significance testing of state-dependent neural activity, such as:
    - ANOVA-based detection of neurons with significant state-dependent firing
    - Pairwise t-tests for transition-triggered neural activity
    - Cross-trial analysis of state transitions



Figure 1: Spike rasters with changepoint overlays provide a first visualization of the inferred changepoints

These features make pytau particularly valuable for neuroscientists studying state transitions in neural activity, such as taste processing, decision-making, or learning paradigms.

Implementation and architecture

pytau is implemented in Python and built on several key libraries including NumPy, SciPy, PyMC3, and Matplotlib (Harris et al., 2020; Salvatier et al., 2016). The package is organized into several modules:

1. **changepoint_model.py**: Contains model definitions for various changepoint models including Poisson and Gaussian models for neural data

2. **changepoint_io.py**: Handles data loading, preprocessing, and result storage through the `FitHandler` and `DatabaseHandler` classes
3. **changepoint_analysis.py**: Provides tools for analyzing fitted models, including significance testing and visualization
4. **changepoint_preprocess.py**: Contains functions for data preprocessing, binning, and transformations
5. **utils/**: Contains utility functions for plotting, data handling, and batch processing

The core workflow in `pytau` involves:

1. Loading neural data (typically spike trains) using the `EphysData` class
2. Preprocessing the data for model fitting with functions from `changepoint_preprocess`
3. Defining and fitting changepoint models using PyMC3-based implementations in `changepoint_model`
4. Storing results in a queryable database managed by `DatabaseHandler`
5. Analyzing and visualizing the results with functions from `changepoint_analysis`

The mathematical foundation of the package is Bayesian changepoint detection. For a time series $X = \{x_1, x_2, ..., x_T\}$, we model the data as having K distinct states with transitions at times $\tau = \{\tau_1, \tau_2, ..., \tau_{K-1}\}$. The emission distribution within each state k is parameterized by θ_k:

$$p(x_t|\theta_k) \text{ for } \tau_{k-1} < t \leq \tau_k$$

For neural spike train data, the package implements Poisson emission models:

$$x_t \sim \text{Poisson}(\lambda_k) \text{ for } \tau_{k-1} < t \leq \tau_k$$

Where λ_k represents the firing rate in state k.

Fitting Methods

`pytau` employs advanced Bayesian inference techniques to fit changepoint models. The package utilizes both Automatic Differentiation Variational Inference (ADVI) (Kucukelbir et al., 2017) and Markov Chain Monte Carlo (MCMC) methods, including the No-U-Turn Sampler (NUTS) (Hoffman & Gelman, 2014), to perform efficient and accurate model fitting. These methods are integrated through PyMC3, allowing for robust estimation of model parameters and uncertainty quantification.

The use of ADVI provides a fast approximation to the posterior distribution, making it suitable for initial exploration and parameter tuning. For more precise inference, `pytau` leverages the NUTS sampler, a variant of MCMC that adapts the step size and trajectory length during sampling, ensuring efficient exploration of the parameter space.

A key feature of `pytau` is the creation of states through the stacking of sigmoid functions. This approach allows for continuous exploration of parameters, enabling the detection of subtle changes in neural activity. By modeling state transitions with sigmoid functions, the package captures the gradual nature of neural dynamics, providing a more nuanced understanding of state-dependent processes.

Example usage

Below is a simple example of using `pytau` to fit a changepoint model to neural data:

```
from pytau.changepoint_io import FitHandler
```

```python
# Initialize fit handler
fh = FitHandler(
    data_dir='/path/to/data',
    taste_num=1,
    region_name='GC',
    experiment_name='example_experiment'
)

# Set preprocessing parameters
fh.set_preprocess_params(
    time_lims=[0, 2000],  # Time window in ms
    bin_width=10,         # Bin width in ms
    data_transform=None   # No transformation
)

# Set model parameters
fh.set_model_params(
    states=3,             # Number of states to fit
    fit=5000,             # ADVI iterations
    samples=1000,         # Number of posterior samples
    model_kwargs={}       # Additional model parameters
)

# Run the full pipeline
fh.load_spike_trains()
fh.preprocess_data()
fh.create_model()
fh.run_inference()
fh.save_fit_output()
```

After fitting, the results can be analyzed using the `PklHandler` class:

```python
from pytau.changepoint_analysis import PklHandler

# Load fitted model
pkl_handler = PklHandler('/path/to/saved/model.pkl')

# Access model components
tau = pkl_handler.tau  # Changepoint times
firing = pkl_handler.firing  # Firing rate analysis

# Analyze significant neurons
significant_neurons = firing.anova_significant_neurons

# Access transition analysis data
transition_snippets = firing.transition_snips
pairwise_significant = firing.pairwise_significant_neurons

# Visualize the results (using functions from pytau.utils.plotting)
import matplotlib.pyplot as plt
from pytau.utils.plotting import plot_changepoint_raster, plot_state_firing_rates

# Plot spike rasters with changepoint overlays
fig, ax = plt.subplots(figsize=(10, 6))
plot_changepoint_raster(pkl_handler.processed_spikes, pkl_handler.tau.scaled_mode_tau,
                        plot_lims=[0, 2000])
```

DRAFT

```
# Plot state-dependent firing rates
plot_state_firing_rates(pkl_handler.processed_spikes, pkl_handler.tau.scaled_mode_tau)
```



Figure 2: Overview of state timing: A general overview of state-durations across trials fit, as well as the distribution of transition times.

DRAFT



Figure 3: State-specific neuron activity: Visuaizing state-specific firing rates of neurons allows assessment of the fraction of neurons showing differential activity and distribution of firing rates and firing-rate changes between neurons

This example demonstrates the streamlined workflow for fitting a changepoint model to taste response data, analyzing the results, and visualizing the findings.

Tutorials and documentation

For users interested in learning how to effectively use the `pytau` package, a series of tutorials are available in the `how_to` directory of the repository. These include:

1. **Jupyter notebooks**: Step-by-step walkthroughs demonstrating the package functionality with and without handlers. These notebooks cover various scenarios and use cases, providing a hands-on approach to learning.

2. **Example scripts**: Ready-to-run Python scripts showing how to fit models manually or using the `FitHandler`. These scripts serve as practical examples for users to understand the workflow and customize it for their needs.
3. **Test data**: Scripts to download test datasets for practicing with the package. This allows users to experiment with the package features without needing their own data initially.

These tutorials provide comprehensive guidance on various features and use cases of the package, helping users to get started quickly and efficiently with changepoint analysis of neural data.

References to Recent Works

The `pytau` package has been utilized in several published and ongoing research projects in neuroscience, demonstrating its practical utility for analyzing neural dynamics:

- **Published Research**:
  - Mahmood et al. (2023) used `pytau` to analyze the coupled dynamics between gustatory cortex and basolateral amygdala during taste processing, revealing coordinated state transitions across these regions.
  - Flores & Lin (2023) applied the package to investigate how taste experience enhances cortical response reliability during taste aversion learning.
- **Ongoing Research**:
  - Mazzio et al. (2025) is using `pytau` to study cortical dynamics underlying learned and non-learned aversive behavior.
  - (**?**) is investigating neural signals driving consummatory responses in rats.
  - Mahmood et al. (2025) is examining asymmetric interactions between basolateral amygdala and gustatory cortex during taste processing.
  - Calia-Bogan et al. (2025) is analyzing taste-evoked intra-state dynamics in the gustatory cortex.
  - (**?**) is using inferred changepoints to align neural activity with free consumption behaviors in a rat model.

These applications demonstrate the versatility of `pytau` for analyzing state transitions in neural activity across different experimental paradigms and brain regions.

Model types and features

`pytau` implements several types of changepoint models to accommodate different analysis needs:

1. **Single taste Poisson models**: For analyzing single-taste responses with Poisson emission distributions

```
# From changepoint_model.py
single_taste_poisson(spike_array, states, **kwargs)
```

2. **Variable sigmoid models**: Models with learnable transition sharpness

```
# From changepoint_model.py
single_taste_poisson_varsig(spike_array, states, **kwargs)
```

3. **Fixed sigmoid models**: Models with fixed transition sharpness

```
# From changepoint_model.py
single_taste_poisson_varsig_fixed(spike_array, states, inds_span=1)
```

4. **All-taste models**: For analyzing responses across multiple stimuli

DRAFT

```
# From changepoint_model.py
all_taste_poisson(spike_array, states, **kwargs)
```

5. **Dirichlet process models**: For automatically determining the number of states

```
# From changepoint_model.py
single_taste_poisson_dirichlet(spike_array, max_states=10, **kwargs)
```

The package also provides tools for statistical analysis of fitted models, including:

1. **State-dependent firing rate analysis**:

```
# From changepoint_analysis.py
get_state_firing(spike_array, tau_array)
```

2. **Significance testing**:

```
# From changepoint_analysis.py
calc_significant_neurons_firing(state_firing, p_val=0.05)
```

3. **Transition analysis**:

```
# From changepoint_analysis.py
get_transition_snips(spike_array, tau_array, window_radius=300)
calc_significant_neurons_snippets(transition_snips, p_val=0.05)
```

4. **Visualization tools**:

```
# From utils/plotting.py
plot_changepoint_raster(spike_array, tau, plot_lims=None)
plot_changepoint_overview(tau, plot_lims)
plot_aligned_state_firing(spike_array, tau, window_radius=300)
plot_state_firing_rates(spike_array, tau)
plot_elbo_history(fit_model, final_window=0.05)
```



Figure 4: Transition-aligned activity: Alignment of neural activity to transitions across trials allows us to visualize patterns of change across different transitions.

These visualization and analysis functions enable researchers to: - Examine neural activity with overlaid changepoints - Visualize the distribution of changepoints across trials - Analyze neural activity aligned to state transitions - Compare firing rates across different states - Identify neurons with significant state-dependent activity - Detect neurons that respond significantly to state transitions

Comparison with existing tools

Several tools exist for changepoint detection, including:

DRAFT

1. **ruptures** (Truong et al., 2018): A Python package for offline change point detection
2. **bayesloop**: A probabilistic programming framework for time series analysis
3. **PyChange**: A Python package for change point detection in time series
4. **Bayesian online changepoint detection** (Adams & MacKay, 2007; Fearnhead & Liu, 2007): Methods for online detection of changepoints

pytau differs from these tools in its specific focus on neuroscience applications, particularly for analyzing neural ensemble data across multiple experimental conditions. It provides specialized functionality for:

1. Handling multi-trial, multi-neuron spike train data
2. Batch processing across parameter grids
3. Database management for model comparison
4. Specialized visualization for neural data
5. Statistical analysis of state-dependent neural activity

While general-purpose changepoint detection tools are valuable, pytau addresses the specific needs of neuroscientists analyzing state transitions in neural population activity.

Acknowledgements

We acknowledge contributions from collaborators and support from the Katz Lab during the development of this project. Special thanks to the PyMC development team for providing the Bayesian modeling framework that powers the core functionality of pytau.

References

Adams, R. P., & MacKay, D. J. (2007). Bayesian online changepoint detection. *arXiv Preprint arXiv:0710.3742*. https://doi.org/10.48550/arXiv.0710.3742

Baas-Thomas, N., Mahmood, A., & Katz, D. B. (2025). *Investigating the neural signals driving the consummatory response in rats*.

Calia-Bogan, V., Mahmood, A., Steindler, J. R., & Katz, D. B. (2025). *Taste-evoked intra-state dynamics in the gustatory cortex*.

Fearnhead, P., & Liu, Z. (2007). On-line inference for multiple changepoint problems. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, *69*(4), 589–605. https://doi.org/10.1111/j.1467-9868.2007.00601.x

Flores, V. L., & Lin, J.-Y. (2023). Taste experience enhances cortical response reliability during latent enhancement of taste aversion learning. *bioRxiv*. https://doi.org/10.1101/2023.12.19.572413

Giahi Saravani, A., Forseth, K. J., Tandon, N., & Pitkow, X. (2019). Dynamic brain interactions during picture naming. *Eneuro*, *6*(4). https://doi.org/10.1523/eneuro.0472-18.2019

Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk, M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., … Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, *585*(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2

Hoffman, M. D., & Gelman, A. (2014). The no-u-turn sampler: Adaptively setting path lengths in hamiltonian monte carlo. *Journal of Machine Learning Research*, *15*, 1593–1623. https://doi.org/10.48550/arXiv.1111.4246

Jones, L. M., Fontanini, A., Sadacca, B. F., Miller, P., & Katz, D. B. (2007). Natural stimuli evoke dynamic sequences of states in sensory cortical ensembles. *Proceedings of the National*

DRAFT

Academy of Sciences, *104*(47), 18772–18777. https://doi.org/10.1073/pnas.0705546104

Kucukelbir, A., Tran, D., Ranganath, R., Gelman, A., & Blei, D. M. (2017). Automatic differentiation variational inference. *Journal of Machine Learning Research*, *18*(14), 1–45. https://doi.org/10.48550/arXiv.1603.00788

Mahmood, A., Steindler, J. R., & Katz, D. B. (2025). *Basolateral amygdala and gustatory cortex interact asymmetrically during taste processing in rodents*.

Mahmood, A., Steindler, J., Germaine, H., Miller, P., & Katz, D. B. (2023). Coupled dynamics of stimulus-evoked gustatory cortical and basolateral amygdalar activity. *Journal of Neuroscience*, *43*(3), 386–404. https://doi.org/10.1523/JNEUROSCI.1412-22.2022

Mazzio, C., Germaine, H., Lin, J.-Y., & Katz, D. B. (2025). *Cortical dynamics underlying learned and non-learned aversive behavior*.

Salvatier, J., Wiecki, T. V., & Fonnesbeck, C. (2016). Probabilistic programming in python using PyMC3. *PeerJ Computer Science*, *2*, e55. https://doi.org/10.7717/peerj-cs.55

Seidemann, E., Meilijson, I., Abeles, M., Bergman, H., & Vaadia, E. (1996). Simultaneously recorded single units in the frontal cortex go through sequences of discrete and stable states in monkeys performing a delayed localization task. *The Journal of Neuroscience*, *16*(2), 752–768. https://doi.org/10.1523/jneurosci.16-02-00752.1996

Truong, C., Oudre, L., & Vayatis, N. (2018). Ruptures: Change point detection in python. *arXiv Preprint arXiv:1801.00826*. https://doi.org/10.48550/arXiv.1801.00826

DRAFT