

1 GroupFunctions.jl: computing individual entries of the 2 irreducible representations of the unitary group $U(d)$

3 David Amaro-Alcalá ¹ and Konrad Szymański ¹

4 ¹ Research Centre for Quantum Information, Institute of Physics, Slovak Academy of Sciences,
5 Dúbravská cesta 9, Bratislava, Slovakia

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: 

Submitted: 31 July 2026

Published: unpublished

License

Authors of papers retain copyright
and release the work under a
Creative Commons Attribution 4.0
International License ([CC BY 4.0](#)).

6 Summary

7 [GroupFunctions.jl](#)¹ is a Julia library for computing individual matrix elements of irreducible
8 representations of $U(d)$. These matrix elements, called group functions, can be evaluated
9 symbolically or numerically. For $SU(2)$, they reduce to the Wigner D -functions. The library
10 computes these matrix elements in a carrier-space basis enumerated by Gelfand-Tsetlin patterns
11 (Gelfand & Tsetlin, 1950). It can also compute entire representation operators, construct input
12 unitaries from parameterisations common in quantum optics, translate Gelfand-Tsetlin patterns
13 into occupation-number kets, and compute the associated Schur functions. Results can be
14 exported in a form compatible with Mathematica.

Statement of need

16 Representations of the unitary group $U(d)$ arise in many subfields of physics and mathematics,
17 and computations often reduce to evaluating their matrix elements, called group functions.
18 For an irrep labelled by λ , the corresponding object is

$$D_{\text{out,init}}^{(\lambda)}(U) = \langle \text{out} | D^{(\lambda)}(U) | \text{init} \rangle,$$

19 where init and out denote basis states in the representation carrier space.

20 In mathematics, summing the diagonal group functions gives the trace of the representation
21 matrix of U . This trace is the character of the representation and the Schur polynomial of the
22 eigenvalues of U , an object central to algebraic combinatorics and symmetric function theory.

23 In quantum physics, group functions appear in several settings. In quantum optics, a group
24 function gives the transition amplitude of photons through a linear optical network (de Guise et
25 al., 2014). The same object can be used to characterise the performance of quantum devices
26 (Amaro-Alcalá, 2026) and to describe the symmetry properties of states (Otto & Szymański,
27 2024). One important subproblem is boson sampling (Aaronson & Arkhipov, 2011), where the
28 transition amplitude reduces to a permanent whose evaluation is classically computationally
29 hard. Whether noisy real-world quantum devices can perform this computation remains an
30 open question.

31 Some of these tasks require only a numerical estimate, whereas others require an exact symbolic
32 group function. `GroupFunctions.jl` addresses the latter. Although related packages exist (see
33 below), to our knowledge, none are designed to compute the representation matrix symbolically,

¹David Amaro-Alcalá developed the package, its algorithms, and its test suite, and prepared the initial
documentation. Konrad Szymański substantially revised and expanded the documentation and developed
additional examples, and contributed to the standardisation of the API.

one matrix element at a time – the cheaper route when a calculation requires only a few of them.

State of the field

Several existing packages relate to `GroupFunctions.jl` but address different problems. `SUNRepresentations.jl` ([QuantumKitHub contributors, 2020](#)) and the algorithm presented in the appendix of ([Alex et al., 2011](#)) compute $SU(d)$ Clebsch-Gordan coefficients. `RepLAB` ([Rosset et al., 2021](#)) supports manipulating irreducible representations of various groups, including $U(d)$, but provides only indirect numerical access to group functions. `IntegrateUnitary.jl` ([Pawela & Puchała, 2026](#)) performs symbolic integration over compact groups rather than evaluating representation matrices. `haarpy` ([Cardin et al., 2024](#)) implements Weingarten-calculus methods. Other libraries focus on quantum optics. `BosonSampling.jl` ([Seron & Restivo, 2024](#)), `Perceval` ([Heurtel et al., 2023](#)), and `Q0ptCraft` ([Aguado et al., 2023](#)) numerically model linear optical devices, while `The Walrus` ([Gupt et al., 2019](#)) helps compute amplitudes for Gaussian boson sampling. These packages do not target the symbolic computation of individual representation-matrix entries, which is the primary purpose of `GroupFunctions.jl`.

Software design

This library provides a unified method for computing representation matrix elements of $U(d)$ irreps specified by integer partitions of length at most d , including computations with symbolic input matrices. Several computational routes are possible in principle. For symmetric irreps, which model fully indistinguishable bosons, one can manipulate states as polynomials of creation operators applied to the vacuum. Another approach constructs and exponentiates the Lie algebra generators in the chosen representation. Both approaches are computationally expensive. More restricted methods based on generating functions also exist ([Prakash, 1996](#)).

The authors chose the Grabmeier-Kerber formula ([Grabmeier & Kerber, 1987](#)) as the most general solution. It expresses the matrix element as a sum of monomials in the entries of the input matrix, weighted by the irreducible representation and the states in question. Our implementation optimises the enumeration of the double cosets that index this sum by grouping permutations that contribute the same monomial. This implementation provides the library's main function, `group_function`.

Internally, the algorithm represents basis states as semistandard Young tableaux. The user-facing functions expose the equivalent Gelfand-Tsetlin patterns through the `GTPattern` data structure and provide utility functions for common quantum optics scenarios, such as `occupation_number`.

Research impact statement

`GroupFunctions.jl` has been used to evaluate matrix elements and group characters in published work on filtered randomized benchmarking ([Amaro-Alcalá, 2026](#)). The library has been under continuous development since 2020 and is tested in CI; it is registered in the Julia General registry under the MIT licence, installable with the following command:

```
] add GroupFunctions
```

The following example evaluates, symbolically, a matrix element between states of the $U(4)$ mixed-symmetry irrep.

```
λ = [2,2,1,0]; basis=basis_states(λ); # integer partition and basis
group_function(λ, basis[1], basis[end]) # symbolic matrix element
```

74 The result is a polynomial in the entries of the $U(4)$ matrix. For symmetric irreps the matrix
 75 element reduces to a permanent, which symbolic algebra packages also compute; for mixed-
 76 symmetry ones no existing software computes these elements symbolically. Further examples,
 77 applications, and mathematical background are available in [the documentation](#).

78 AI usage disclosure

79 OpenAI Codex (GPT-5.3) assisted with optimising the performance of the double-coset
 80 enumeration at a late stage. The authors developed the mathematical design and proof of
 81 correctness of the optimised algorithm. Anthropic Claude (Opus 4.8) assisted with code review
 82 and language review of the documentation and manuscript. The authors reviewed and edited
 83 all AI-assisted changes.

84 Acknowledgements

85 We thank Dr. Hubert de Guise for helpful discussions and suggestions on the bibliography,
 86 and Dr. Alonso Botero for suggestions that improved the presentation. Mitacs CALAREO,
 87 DeQHOST APVV-22-0570, QUAS VEGA 2/0164/25, Postdokgrant APD0161, and the Stefan
 88 Schwarz programme supported this work. David Amaro-Alcalá acknowledges the indirect
 89 support of the Government of Alberta and NSERC during his PhD studies at the University of
 90 Calgary.

91 References

- 92 Aaronson, S., & Arkhipov, A. (2011). The computational complexity of linear optics.
 93 *Proceedings of the Forty-Third Annual ACM Symposium on Theory of Computing*, 333–342.
 94 <https://doi.org/10.1145/1993636.1993682>
- 95 Aguado, D. G., Gimeno, V., Moyano-Fernández, J. J., & Garcia-Escartin, J. C. (2023).
 96 QOptCraft: A Python package for the design and study of linear optical quantum systems.
 97 *Computer Physics Communications*. <https://doi.org/10.1016/j.cpc.2022.108511>
- 98 Alex, A., Kalus, M., Huckleberry, A., & Delft, J. von. (2011). A numerical algorithm for
 99 the explicit calculation of $SU(N)$ and $SL(N, \mathbb{C})$ Clebsch-Gordan coefficients. *Journal of*
 100 *Mathematical Physics*, 52(2), 023507. <https://doi.org/10.1063/1.3521562>
- 101 Amaro-Alcalá, D. (2026). Kostant relation in filtered randomized benchmarking for passive
 102 bosonic devices. In *Physical Review A* (Vol. 113). American Physical Society. <https://doi.org/10.1103/xmlq-vssg>
- 104 Cardin, Y., de Guise, H., & Quesada, N. (2024). Haarpy, a Python library for Weingarten
 105 calculus and integration of classical compact groups and ensembles. In *GitHub repository*
 106 (Version 0.0.6). <https://github.com/polyquantique/haarpy>; GitHub.
- 107 de Guise, H., Tan, S.-H., Poulin, I. P., & Sanders, B. C. (2014). Coincidence landscapes for
 108 three-channel linear optical networks. *Physical Review A*, 89(6). <https://doi.org/10.1103/physreva.89.063819>
- 110 Gelfand, I. M., & Tsetlin, M. L. (1950). Finite-dimensional representations of the group of
 111 unimodular matrices. *Doklady Akademii Nauk SSSR*, 71, 825–828.
- 112 Grabmeier, J., & Kerber, A. (1987). The evaluation of irreducible polynomial representations
 113 of the general linear groups and of the unitary groups over fields of characteristic 0. *Acta*
 114 *Applicandae Mathematicae*, 8(3), 271–291. <https://doi.org/10.1007/bf00046717>
- 115 Gupt, B., Izaac, J., & Quesada, N. (2019). The Walrus: A library for the calculation of
 116 hafnians, Hermite polynomials and Gaussian boson sampling. *Journal of Open Source*

- 117 Software, 4(44), 1705. <https://doi.org/10.21105/joss.01705>
- 118 Heurtel, N., Fyrrillas, A., Gliniasty, G. de, & others. (2023). Perceval: A software platform
119 for discrete variable photonic quantum computing. *Quantum*, 7, 931. [https://doi.org/10.](https://doi.org/10.22331/q-2023-02-21-931)
120 22331/q-2023-02-21-931
- 121 Otto, F., & Szymański, K. (2024). Rotational covariance restricts available quantum states.
122 *Physical Review A*, 110(2), 022440. <https://doi.org/10.1103/PhysRevA.110.022440>
- 123 Pawela, Ł., & Puchała, Z. (2026). *IntegrateUnitary.jl: A Julia package for symbolic integration*
124 *over Haar measures*. <https://arxiv.org/abs/2605.23830>
- 125 Prakash, J. (1996). Wigner's D-matrix elements for SU(3)-a generating function approach.
126 *Journal of Physics A: Mathematical and General*, 29(18), 6059–6072. [https://doi.org/10.](https://doi.org/10.1088/0305-4470/29/18/032)
127 1088/0305-4470/29/18/032
- 128 QuantumKitHub contributors. (2020). *SUNRepresentations.jl*. [https://github.com/](https://github.com/QuantumKitHub/SUNRepresentations.jl)
129 QuantumKitHub/SUNRepresentations.jl.
- 130 Rosset, D., Montealegre-Mora, F., & Bancal, J.-D. (2021). *RepLAB: A computational/numerical*
131 *approach to representation theory*. <https://github.com/replab/replab>; Springer
132 International Publishing. https://doi.org/10.1007/978-3-030-55777-5_60
- 133 Seron, B., & Restivo, A. (2024). BosonSampling.jl: A Julia package for quantum multi-photon
134 interferometry. *Quantum*, 8, 1378. <https://doi.org/10.22331/q-2024-06-18-1378>

DRAFT