The Journal of Open Source Software

NeuroCAPs: A Python Package for Performing Co-Activation Patterns Analyses on Resting-State and Task-Based fMRI Data

Donisha Smith[1]

1 Department of Psychology, Florida International University

DOI: 10.xxxxxx/draft

Software

- Review
- Repository
- Archive

Editor: julia ferraioli

Reviewers:

- @robbisg
- @yibeichan

Submitted: 21 March 2025
Published: unpublished

License
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

Summary

Co-Activation Patterns (CAPs) is a dynamic functional connectivity technique that clusters similar spatial distributions of brain activity. To make this analytical technique more accessible to neuroimaging researchers, NeuroCAPs, an open source Python package, was developed. This package performs end-to-end CAPs analyses on preprocessed resting-state or task-based functional magnetic resonance imaging (fMRI) data, and is most optimized for data preprocessed with fMRIPrep, a robust preprocessing pipeline designed to minimize manual user input and enhance reproducibility (Esteban et al., 2019).

Background

Numerous fMRI studies employ static functional connectivity (sFC) techniques to analyze correlative activity within and between brain regions. However, these approaches operate under the assumption that functional connectivity patterns, which change within seconds (Jiang et al., 2022), remain stationary throughout the entire data acquisition period (Hutchison et al., 2013).

Unlike sFC approaches, dynamic functional connectivity (dFC) methods enable the analysis of dynamic functional states, which are characterized by consistent, replicable, and distinct periods of time-varying brain connectivity patterns (Rabany et al., 2019). Among these techniques, CAPs analysis aggregates similar spatial distributions of brain activity using clustering techniques, such as the k-means algorithm, to capture the dynamic nature of brain activity (Liu et al., 2013, 2018).

Statement of Need

Currently, performing an end-to-end CAPs analysis presents challenges due to the numerous steps required. Researchers must:

1. clean timeseries data through nuisance regression and censor frames with high framewise displacement (excessive head motion).
2. perform spatial dimensionality reduction.
3. concatenate timeseries data across multiple subjects for k-means clustering.
4. select an optimal cluster size using heuristics such as the elbow or silhouette methods.
5. implement various visualization techniques to enhance interpretability of the results.

While other excellent CAPs toolboxes exist, they are often implemented in proprietary languages such as MATLAB (which is the case for TbCAPs (Bolton et al., 2020)), lack comprehensive end-to-end analytical pipelines for both resting-state and task-based fMRI data with temporal

dynamic metrics and visualization capabilities (such as capcalc (Frederick & Drucker, 2022)), or are comprehensive, but generalized toolboxes for evaluating and comparing different dFC methods (such as pydFC (Torabi et al., 2024)). NeuroCAPs addresses these limitations by providing an accessible Python package specifically for performing end-to-end CAPs analyses, from post-processing of fMRI data to creation of temporal metrics for downstream statistical analyses and visualizations to facilitate interpretations. However, many of NeuroCAPs' post-processing functionalities assumes that fMRI data is organized in a Brain Imaging Data Structure (BIDS) compliant directory and is most optimized for data preprocessed with fMRIPrep (Esteban et al., 2019) or preprocessing pipelines that generate similar outputs (e.g. NiBabies (Goncalves et al., 2025)).

Modules

NeuroCAPs consists of four modules, with core functionality primarily distributed between two main modules (`neurocaps.extraction` and `neurocaps.analysis`) that handle the entire workflow, from post-processing to temporal metric computation and visualization capabilities.

neurocaps.exceptions

This module contains custom exceptions. These include `BIDSQueryError`, which supports NeuroCAPs' integration with PyBIDS (Yarkoni et al., 2019) by providing guidance when issues arise with BIDS directories; `NoElbowDetectedError`, which offers solutions when optimal cluster determination fails using the elbow method implemented via Kneed (Arvai, 2023); and `UnsupportedFileExtensionError`, which handles cases when pickled inputs have unsupported file extensions.

neurocaps.extraction

This module contains the `TimeseriesExtractor` class, which:

- leverages extracts Nilearn's (contributors, n.d.) `NiftiLabelsMasker` to perform nuisance regression on resting-state and task-based fMRI data and use parcellations (such as the Schaefer (Schaefer et al., 2018), Automated Anatomical Labeling (Tzourio-Mazoyer et al., 2002), and Human Connectome Project extended (Huang et al., 2022)) for spatial dimensionality reduction.
- censors high-motion volumes using fMRIPrep-derived framewise displacement values and stores the extracted timeseries information in a dictionary mapping subject IDs to run IDs and their associated timeseries.
- reports quality control information related to framewise displacement and dummy volumes.
- saves extracted timeseries data as a pickle file.
- visualizes timeseries data for a specific subject's run.

neurocaps.analysis

This module contains the `CAP` class, which:

- allows group-specific analyses or analyses on all subjects.
- performs k-means clustering (from Scikit-learn (Pedregosa et al., 2011)) for CAP identification, while supporting a single cluster size or a range of clusters in combination with various cluster selection methods to determine the optimal cluster size.
- computes various subject-level temporal dynamics metrics for downstream statistical analyses.
- enables conversion of CAPs to NIfTI statistical maps.
- provides diverse visualization options, using Matplotlib (Hunter, 2007), Seaborn (Waskom, 2021), Plotly (Inc., n.d.), and Surfplot (Gale et al., 2021), to facilitate scientific interpretations.

Additionally, the module provides standalone functions for:

- changing the data type (Harris et al., 2020) and performing additional standardization of timeseries data produced by `TimeseriesExtractor`.
- merging multiple timeseries data across different dictionaries produced by `TimeseriesExtractor` by identifying similar subjects and concatenating their data, which facilitates analyses to identify CAPs across sessions or tasks.
- creating averaged transition probability matrices from subject-level transition probabilities.

neurocaps.typing

This module provides custom type definitions compatible with static type checkers, enabling proper construction of dictionary structures for parcellations or timeseries data when manual creation is necessary.

Examples

Comprehensive demonstrations and tutorials for NeuroCAPs can be found on its repository at https://github.com/donishadsmith/neurocaps and its documentation at https://neurocaps.readthedocs.io/.

Research Utility

NeuroCAPs was originally developed (and later refined for broader use) to facilitate the analysis in Smith et al. (2025), which has been submitted for peer review by the same author.

Acknowledgements

Funding provided by the Dissertation Year Fellowship (DYF) Program at Florida International University (FIU) assisted in further refinement of NeuroCAPs.

References

Arvai, K. (2023). *Kneed*. Zenodo. https://doi.org/10.5281/ZENODO.8127224

Bolton, T. A. W., Tuleasca, C., Wotruba, D., Rey, G., Dhanis, H., Gauthier, B., Delavari, F., Morgenroth, E., Gaviria, J., Blondiaux, E., Smigielski, L., & Van De Ville, D. (2020). TbCAPs: A toolbox for co-activation pattern analysis. *NeuroImage*, *211*, 116621. https://doi.org/10.1016/j.neuroimage.2020.116621

contributors, N. (n.d.). *nilearn*. https://doi.org/10.5281/zenodo.8397156

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., Kent, J. D., Goncalves, M., DuPre, E., Snyder, M., Oya, H., Ghosh, S. S., Wright, J., Durnez, J., Poldrack, R. A., & Gorgolewski, K. J. (2019). fMRIPrep: A robust preprocessing pipeline for functional MRI. *Nature Methods*, *16*(1), 111–116. https://doi.org/10.1038/s41592-018-0235-4

Frederick, B. D., & Drucker, D. M. (2022). *Bbfrederick/capcalc: Version 1.2.2.2 - 8/30/22 deployment bug fix*. Zenodo. https://doi.org/10.5281/ZENODO.7035806

Gale, D. J., Vos de Wael., R., Benkarim, O., & Bernhardt, B. (2021). *Surfplot: Publication-ready brain surface figures*. Zenodo. https://doi.org/10.5281/ZENODO.5567926

Goncalves, M., Markiewicz, C. J., Esteban, O., Feczko, E., Poldrack, R. A., & Fair, D. A. (2025). *NiBabies: A robust preprocessing pipeline for infant functional MRI*. Zenodo. https://doi.org/10.5281/ZENODO.14811979

DRAFT

Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk, M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., … Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, *585*(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2

Huang, C.-C., Rolls, E. T., Feng, J., & Lin, C.-P. (2022). An extended human connectome project multimodal parcellation atlas of the human cortex and subcortical areas. *Brain Structure and Function*, *227*(3), 763–778. https://doi.org/10.1007/s00429-021-02421-6

Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, *9*(3), 90–95. https://doi.org/10.1109/MCSE.2007.55

Hutchison, R. M., Womelsdorf, T., Allen, E. A., Bandettini, P. A., Calhoun, V. D., Corbetta, M., Della Penna, S., Duyn, J. H., Glover, G. H., Gonzalez-Castillo, J., Handwerker, D. A., Keilholz, S., Kiviniemi, V., Leopold, D. A., De Pasquale, F., Sporns, O., Walter, M., & Chang, C. (2013). Dynamic functional connectivity: Promise, issues, and interpretations. *NeuroImage*, *80*, 360–378. https://doi.org/10.1016/j.neuroimage.2013.05.079

Inc., P. T. (n.d.). *Chart title*. https://plotly.com/python/radar-chart/; Plotly Technologies Inc.

Jiang, F., Jin, H., Gao, Y., Xie, X., Cummings, J., Raj, A., & Nagarajan, S. (2022). Time-varying dynamic network model for dynamic resting state functional connectivity in fMRI and MEG imaging. *NeuroImage*, *254*, 119131. https://doi.org/10.1016/j.neuroimage.2022.119131

Liu, X., Chang, C., & Duyn, J. H. (2013). Decomposition of spontaneous brain activity into distinct fMRI co-activation patterns. *Frontiers in Systems Neuroscience*, *7*. https://doi.org/10.3389/fnsys.2013.00101

Liu, X., Zhang, N., Chang, C., & Duyn, J. H. (2018). Co-activation patterns in resting-state fMRI signals. *NeuroImage*, *180*, 485–494. https://doi.org/10.1016/j.neuroimage.2018.01.041

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, E. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, *12*, 2825–2830.

Rabany, L., Brocke, S., Calhoun, V. D., Pittman, B., Corbera, S., Wexler, B. E., Bell, M. D., Pelphrey, K., Pearlson, G. D., & Assaf, M. (2019). Dynamic functional connectivity in schizophrenia and autism spectrum disorder: Convergence, divergence and classification. *NeuroImage: Clinical*, *24*, 101966. https://doi.org/10.1016/j.nicl.2019.101966

Schaefer, A., Kong, R., Gordon, E. M., Laumann, T. O., Zuo, X.-N., Holmes, A. J., Eickhoff, S. B., & Yeo, B. T. T. (2018). Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity MRI. *Cerebral Cortex*, *28*(9), 3095–3114. https://doi.org/10.1093/cercor/bhx179

Smith, D. D., Bartley, J. E., Peraza, J. A., Bottenhorn, K. L., Nomi, J. S., Uddin, L. Q., Riedel, M. C., Salo, T., Laird, R. W., Pruden, S. M., Sutherland, M. T., Brewe, E., & Laird, A. R. (2025). *Dynamic reconfiguration of brain coactivation states associated with active and lecture-based learning of university physics*. https://doi.org/10.1101/2025.02.22.639361

Torabi, M., Mitsis, G. D., & Poline, J.-B. (2024). On the variability of dynamic functional connectivity assessment methods. *GigaScience*, *13*, giae009. https://doi.org/10.1093/gigascience/giae009

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N., Mazoyer, B., & Joliot, M. (2002). Automated anatomical labeling of activations in

DRAFT

SPM using a macroscopic anatomical parcellation of the MNI MRI single-subject brain. *NeuroImage*, *15*(1), 273–289. https://doi.org/10.1006/nimg.2001.0978

Waskom, M. L. (2021). Seaborn: Statistical data visualization. *Journal of Open Source Software*, *6*(60), 3021. https://doi.org/10.21105/joss.03021

Yarkoni, T., Markiewicz, C., De La Vega, A., Gorgolewski, K., Salo, T., Halchenko, Y., McNamara, Q., DeStasio, K., Poline, J.-B., Petrov, D., Hayot-Sasson, V., Nielson, D., Carlin, J., Kiar, G., Whitaker, K., DuPre, E., Wagner, A., Tirrell, L., Jas, M., … Blair, R. (2019). PyBIDS: Python tools for BIDS datasets. *Journal of Open Source Software*, *4*(40), 1294. https://doi.org/10.21105/joss.01294

DRAFT