



OpenLCB Standard	
Configuration Description Information	
August 7, 2024	Draft

1 Introduction (Informative)

This document defines a standard for the format of static information that describes the configuration options available on an OpenLCB node, called “Configuration Description Information (CDI)”. “Configuration Description Information” in this context refers to *fixed* information available from an OpenLCB device, via OpenLCB, so that other devices can properly and correctly configure it.

This Standard does not address how the CDI is stored, retrieved, or used.

2 Intended Use (Informative)

CDI is intended to be used by a configurable, self-contained OpenLCB node to tell a Configuration Tool (CT) how to configure the node. The configuration tool will use the CDI information to help the user configure all aspects of the node's capabilities.

The configurable values are expressed as variables, with each variable having a specific type, a size in bytes, a value for its memory space and address (to locate the variable), and name and description as user-readable strings so that users understand the use of the particular setting.

Variables can be grouped together, groups can be repeated (for example if a node has multiple outputs) and nested to express complex configuration setups with concise description.

3 References and Context (Informative)

For more information on format and presentation, see:

- OpenLCB Common Information Technical Note

For information on OpenLCB message transport and OpenLCB communications, see:

- OpenLCB Message Network Standard

For information on how to fetch the CDI information from a node, and how to read and write the configuration information, see:

- OpenLCB Memory Configuration Protocol Standard

For information on XML encoding and XML Schema, see:

- World Wide Web Consortium (W3C) “Extensible Markup Language (XML)”¹
- World Wide Web Consortium (W3C) “XML Schema”²

4 Content (Normative)

30 The configuration description information for a node is invariant while the node has any OpenLCB connections in the Initialized state.

The CDI has three parts:

- Identification: Provides specific information about the type of the node.
- ACDI: Indicates that certain configuration information in the node has a standardized simplified format.
- 35 • Segments: The configuration information in the node is organized in zero or more segments, each of which contains zero or more configurable variables. A variable is the basic unit of configuration. The segment definition specifies the organization of each segment. A segment consists of zero or more bytes within a linear address space.

5 Format (Normative)

40 The CDI is provided as a zero-terminated string of bytes. The bytes encode UTF-8 characters. There is no byte-order mark (BOM) at the start of the string. Lines in the string are delimited with 0x0A Newline (NL) characters.

The content defines the configuration description information in XML 1.0 format using a specific XML vocabulary defined by an XML Schema. No extensions to XML 1.0 are permitted.

45 This version of this Standard specifies version 1.43 of the schema. That version of the schema is defined at <https://openlcb.org/schema/cdi/1/43/cdi.xsd> and in Appendix A of this document. The CDI content shall pass validation against its referenced schema. Nodes are not required to do the validation.

The version number of an OpenLCB CDI schema contains two numbers: The major version first, and the minor version second.

50 The first line of the CDI is:

```
<?xml version="1.0"?>
```

to define the XML version of the content.

The root element of the CDI XML is:

55 |

```
<cdi xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:noNamespaceSchemaLocation="https://openlcb.org/schema/cdi/1/43/cdi.xsd">
```

to define the OpenLCB CDI version of the content.

The schema contents are normative.

¹ <http://www.w3.org/XML/>

² <http://www.w3.org/XML/Schema>

Numerical values in attributes and element text shall be specified as decimal numbers. OpenLCB nodes are not required to parse any other numeric format.

5.1 XML Elements

5.1.1 <identification> Element

The <identification> element, if present, specifies manufacturer-provided identification information about the node. This information is not user-editable. If this element is provided and the node also supports the OpenLCB Simple Node Information Protocol (SNIP), the contents of the SNIP Reply shall match the respective tags in the <identification> element. If this element is provided, and the node also provides the <acdi> element, the contents provided by the ACDI spaces shall match the respective tags in the <identification> element.

5.1.2 <acdi> Element

The <acdi> element, if specified without the attribute 'fixed', or with the attribute 'fixed="4"' or higher, specifies that the following information is available for read:

Space	Address	Size (bytes)	Type	Description
252	0	1	int	Version
252	1	41	string	Manufacturer
252	42	41	string	Model
252	83	21	string	Hardware version
252	104	21	string	Software version

The value at the version variable shall be the same as the value of the attribute 'fixed'.

The <acdi> element, if specified without the attribute 'var', or with the attribute 'var="2"' or higher, specifies that the following information is available for read and write:

Space	Address	Size (bytes)	Type	Description
251	0	1	int	Version
251	1	63	string	User-supplied name
251	64	64	string	User-supplied description

The value at the version variable shall be the same as the value of the attribute 'var'.

The <acdi> element shall be specified if and only if the Protocol Support Reply message carries the 'ACDI' bit set. See the OpenLCB Message Network Standard for the Protocol Support Reply message.

If the <acdi> element is specified, and the node also supports the OpenLCB Simple Node Information Protocol (SNIP), then the information provided by the SNIP Reply shall match the respective values provided in the ACDI space.

A node may, but is not required to, express the same configuration options as specific segments and data elements therein.

5.1.3 <segment> Element

85 A <segment> element defines the value of the memory space in the attribute `space`, which shall apply to all data elements within, and the value of `origin`, which shall be considered as the address of a data element of size 0 (zero) at the beginning of the <segment>³.

A configuration tool may, but is not required to, perform visual separation of the contents of different segments by appropriate UI elements, such as tabs, boxes or horizontal bars.

90 A <segment> element shall contain an optional user-readable name and optional description tags, and a sequence of zero or more data elements. The user-readable name and description are intended as hints for optional UI display by configuration tools.

5.1.4 Data Elements

The following elements are considered data elements: <group>, <int>, <string>, <eventid>, <float>.

95 The value of the address within the segment is accumulated during a depth-first traversal of the contents of the segment definition element. The address is initialized with the value of the attribute `origin` on the <segment> element. Each time an offset attribute is encountered, the value of the address is incremented by the offset (which may be negative) before any other processing of the element is done. If the element defines a variable, the variable is located at the current address, and the address is then incremented by the size of that variable before advancing to the next element. This is formalized as follows.

100 For each data element the following values are defined:

- Space, which is defined by the enclosing <segment> element.
- Address, which is defined as the end address of the previous data element plus the value of the attribute `offset` on the data element.
- Size (in bytes)
- 105 • End address, which is defined as address + size, unless otherwise specified.

The data element's <name> and <description> elements and the <group> element's <repname> element are intended as hints for optional UI display by configuration tools.

5.1.4.1 <group> Element

110 The <group> element allows logical grouping of variables, providing common documentation for them, and making multiple copies of the contained variables. CDI implementors may, but are not required to, use this feature to express configuration of repeated hardware or software components (such as multiple input ports, output ports etc).

115 A <group> element shall contain an optional user-readable name, optional description and a sequence of zero or more data elements. This sequence is considered to contain a data element of size 0 (zero) before the specified data elements³.

If the `replication` attribute is present with the value of N, then the group shall be considered as if the entire sequence of data elements were repeated N times.

³This is required to make "previous element" an unambiguous reference for the first element in the contained sequence.

120 The end address of a <group> element is defined as the end address of the last data element in the contained sequence (after replication). The size of a <group> element is defined as the end address minus the address of the <group> element.

Configuration Tools shall not render a <group> element with no child elements⁴ on their UI.

5.1.4.2 <int> Element

The <int> element defines a variable of integer value.

125 The size of the <int> element is defined as the value of the 'size' attribute in bytes. Valid values are 1, 2, 4 and 8 bytes.

The integer value shall be stored as an unsigned integer unless a <min> sub-element with a value less than zero is present, in which case the integer value shall be stored as a signed integer. The integer value shall be written to the bytes pointed to in big-endian byte order. All bytes shall be written.

130 Values smaller than defined by the <min> or larger than defined by the <max> sub-element, if present, are invalid and shall not be written. The default value of the <min> sub-element is zero, and the default value of the <max> sub-element is the largest possible value for the given size.

If the <map> enumeration [sub-element](#) is present, then values not present in the list of <property> entries of the enumeration are invalid and shall not be written.

135 The optional <hints> sub-element provides hints to a configuration tool on how it might best display the integer variable. No specific behavior is required by the presence of this element. Available sub-elements for the <hints> element are <slider>, <radiobutton> and <checkbox>.

140 • <slider> hints that the configuration tool should present the variable value as a slider between the min and max values. The optional "tickSpacing" attribute recommends a value for the spacing between tick marks on the slider. The optional "immediate" attribute recommends that the slider value be written to the node's configuration memory immediately when the slider value is changed, without waiting for a "Write" button to be pressed.

• <radiobutton> hints that the configuration tool should present the variable value as a set of radio buttons corresponding to the <property> elements in the associated <map> element. The <map> element must be present.

145 • <checkbox> hints that the configuration tool should present the variable value as a checkbox. The unchecked value corresponds to the first <property> element in the associated <map> element. The checked value corresponds to the second <property> element in the associated <map> element. The <map> element must be present.

5.1.4.3 <string> Element

150 The <string> element defines a variable holding a UTF-8 string that is user-readable.

The size of the <string> element is defined as the value of the 'size' attribute in bytes.

⁴No name, no description and no Data Elements contained.

The string value shall be written to the bytes pointed to, starting at the address of the <string> element, with at least one trailing 0 (null) byte.

155 If the <map> enumeration is present, then values not present in the list of <property> entries of the enumeration are invalid and shall not be written.

5.1.4.4 <eventid> Element

The <eventid> element defines a variable holding an 8-byte value representing an event ID.

The size of the <eventid> element is defined as 8 bytes.

160 The event ID shall be written to the bytes pointed to in big-endian byte order (most significant byte first).

If the <map> enumeration is present, then values not present in the list of <property> entries of the enumeration are invalid and shall not be written.

5.1.4.5 <float> Element

The <float> element defines a variable of floating point value.

165 The size of the <float> element is defined as the value of the 'size' attribute in bytes. Valid values are 2, 4, and 8 bytes. The format of the bits within the element shall follow the IEEE format of the corresponding size.

The floating point value shall be written to the bytes pointed to in big-endian byte order. All bytes shall be written.

170 Values smaller than defined by the <min> or larger than defined by the <max> sub-element, if present, are invalid and shall not be written. The default value of the <min> sub-element is zero, and the default value of the <max> sub-element is the largest possible value for the given size.

If the <map> enumeration is present, then values not present in the list of <property> entries of the enumeration are invalid and shall not be written.

175 The optional "floatFormat" attribute defines a preferred, but not mandatory, printf-style format for displaying the data to the user.

5.1.4.6 <action> Element

The <action> element defines a write-only variable that causes the target node to perform some specific action. It may be linked to e.g. a button in the GUI.

180 The size of the <action> element is defined as the value of the 'size' attribute in bytes. Valid values are 1, 2, 4, and 8 bytes.

The optional <buttonText> sub-element, when present, is a hint to the rendering code about what should appear in the user interface e.g. as the text on the button that triggers the action's write operation. Note that no specific behavior is required.

185 | The optional <dialogText> sub-element, when non-blank, suggests to the GUI that it would be good to provide an additional warning to the user before triggering the action's write operation. This could be done by e.g. presenting an OK/Confirm dialog with the dialogText value. A blank or not-present value for the element is a hint that no additional warning is requested. Note that no specific behavior is required.

190 | The required <value> sub-element is the specific decimal value to be written when the action is triggered.

The write-only variable defined by the <action> element must not be written other than when the action is to be triggered.

5.1.4.7 <blob> Element

195 | The <blob> element defines a region of memory that a GUI can transfer to an external file ("read"), transfer from an external file ("write") or both ("readwrite").

The required size and optional offset attributes define a ten-byte section of memory containing:

- 1 byte operation flag;
- 5 bytes of a memory space followed by a four-byte address of the memory blob;
- 4 bytes of length of the memory blob.

To read the blob data:

- Write a value of 1 to the operation flag location.
- Read the memory space and address of the memory blob.
- Read the length of the memory blob.
- Use the Memory Configuration Protocol to read the data.

To write the blob data:

- Write a value of 1 to the operation flag location.
- Read the memory space and address of the memory blob.
- Write the length of the data to be written. The node being configured will positively acknowledge this write if the data can be accepted, and negatively acknowledge it if the data can't be accepted.
- Use the Memory Configuration protocol to write the data.

6 Future Extension (Normative)

215 | Configuration tools implementing a future version of this Standard must be able to process CDI content defined according to any earlier version of the Standard, including this version.

Configuration tools implementing major version 1 of this Standard may assume the following about future minor versions of this Standard:

- No existing tags will change the interpretation or default value of the `offset` and `size` attribute, and accordingly the address and size value, the data type and encoding of the value in the memory space. The <group> tag will not change the interpretation of the `offset` attribute and `replication` attribute.
- All unknown tags that occur within the element <segment> or <group> and have an attribute `size` shall be considered to be data elements with address defined as the end address of the previous data element plus the value of the `offset` attribute, and size defined as the value of the `size` attribute in bytes. The `size` attribute of all future data elements shall be required.

No assumptions may be made about major version 2 and up of this Standard.

A Appendix: Schema

```

230 <?xml version="1.0" encoding="utf-8"?>
<?xml-stylesheet href="schema2xhtml.xsl" type="text/xsl"?>
<!-- XML Schema for OpenLCB Configuration Description Information (CDI) -->
<xs:schema version="CDI-1.3" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <xs:complexType name="mapType">
235   <xs:annotation>
     <xs:documentation>
        A map relates one or more property elements (keys)
        to specific values.
     </xs:documentation>
   </xs:annotation>
240   <xs:sequence>
     <xs:element name="name" minOccurs="0" maxOccurs="1" />
     <xs:element name="description" minOccurs="0" maxOccurs="1" />
     <xs:element name="relation" minOccurs="0" maxOccurs="unbounded">
245       <xs:complexType>
         <xs:sequence>
           <xs:element name="property" minOccurs="1" maxOccurs="1" />
           <xs:element name="value" minOccurs="1" maxOccurs="1" />
         </xs:sequence>
250       </xs:complexType>
     </xs:element>
   </xs:sequence>
 </xs:complexType>
  <xs:complexType name="groupType">
255   <xs:sequence>
     <xs:element name="name" minOccurs="0" maxOccurs="1" />
     <xs:element name="description" minOccurs="0" maxOccurs="1" />
     <xs:element name="repname" minOccurs="0" maxOccurs="unbounded" />
260     <xs:choice minOccurs="0" maxOccurs="unbounded">
       <xs:annotation>
         <xs:documentation>
            Allows any sequence of the contained element types
         </xs:documentation>
265       </xs:annotation>
       <xs:element name="group" type="groupType" minOccurs="0" maxOccurs="1" />
       <xs:element name="string" type="stringType" minOccurs="0" maxOccurs="1" />
       <xs:element name="int" type="intType" minOccurs="0" maxOccurs="1" />
       <xs:element name="eventid" type="eventidType" minOccurs="0" maxOccurs="1" />
270       <xs:element name="float" type="floatType" minOccurs="0" maxOccurs="1" />
     </xs:choice>
     </xs:sequence>
     <xs:attribute name="offset" type="xs:int" default="0">
       <xs:annotation>
275         <xs:documentation>
            Positive or negative offset between the address of
            the end of previous element and the start of
            this group's contents.
            Offset of zero means that this element starts
            immediately after the previous one.
280         </xs:documentation>
       </xs:annotation>
     </xs:attribute>
     <xs:attribute name="replication" type="xs:int" default="1" />
285   </xs:complexType>
  <xs:complexType name="eventidType">
     <xs:sequence>
       <xs:element name="name" minOccurs="0" maxOccurs="1" />
290       <xs:element name="description" minOccurs="0" maxOccurs="1" />
       <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1" />
     </xs:sequence>
     <xs:attribute name="offset" type="xs:int" default="0">
       <xs:annotation>

```

```

295 | <xs:documentation>
| Positive or negative offset between the address of
| the end of previous element and the start of
| this elements's contents.
| Offset of zero means that this element starts
300 | immediately after the previous one.
| </xs:documentation>
| </xs:annotation>
| </xs:attribute>
| </xs:complexType>
305 |
| <xs:complexType name="intType">
| <xs:sequence>
| <xs:element name="name" minOccurs="0" maxOccurs="1" />
| <xs:element name="description" minOccurs="0" maxOccurs="1" />
310 | <xs:element name="min" minOccurs="0" maxOccurs="1" />
| <xs:element name="max" minOccurs="0" maxOccurs="1" />
| <xs:element name="default" minOccurs="0" maxOccurs="1" />
| <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1">
| <xs:annotation>
315 | <xs:documentation>
| The 'value' of each entry is displayed, and
| the 'property' content (number) is sent
| to/from the node
| </xs:documentation>
320 | </xs:annotation>
| </xs:element>
| </xs:sequence>
| <xs:attribute name="size" default="1">
| <xs:annotation>
325 | <xs:documentation>
| Storage size of this variable in bytes.
| </xs:documentation>
| </xs:annotation>
| <xs:simpleType>
330 | <xs:restriction base="xs:token">
| <xs:enumeration value="1"/>
| <xs:enumeration value="2"/>
| <xs:enumeration value="4"/>
| <xs:enumeration value="8"/>
335 | </xs:restriction>
| </xs:simpleType>
| </xs:attribute>
| <xs:attribute name="offset" type="xs:int" default="0">
| <xs:annotation>
340 | <xs:documentation>
| Positive or negative offset between the
| address of the end of previous element and the
| start of this elements's contents.
| Offset of zero means that this element starts
345 | immediately after the previous one.
| </xs:documentation>
| </xs:annotation>
| </xs:attribute>
| </xs:complexType>
350 |
| <xs:simpleType name="floatFormat">
| <xs:restriction base="xs:string">
| <!-- This is a somewhat limiting regex, as it does not allow all possible -->
| <!-- printf formats. It will allow the most common formats that have -->
355 | <!-- been seen and used before, however -->
| <xs:pattern value="%[0-9]*(\.([0-9]*)?)?f"/>
| </xs:restriction>
| </xs:simpleType>
360 |
| <xs:complexType name="floatType">
| <xs:sequence>
| <xs:element name="name" minOccurs="0" maxOccurs="1" />
| <xs:element name="description" minOccurs="0" maxOccurs="1" />
| <xs:element name="min" minOccurs="0" maxOccurs="1" />
365 | <xs:element name="max" minOccurs="0" maxOccurs="1" />

```

```

370 <xs:element name="default" minOccurs="0" maxOccurs="1" />
    <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1">
      <xs:annotation>
        <xs:documentation>
          The 'value' of each entry is displayed, and
          the 'property' content (number) is sent
          to/from the node
        </xs:documentation>
      </xs:annotation>
    </xs:element>
375 </xs:sequence>
    <xs:attribute name="size" use="required">
      <xs:annotation>
        <xs:documentation>
          Storage size of this variable in bytes.
        </xs:documentation>
      </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:token">
385 <xs:enumeration value="2"/>
        <xs:enumeration value="4"/>
        <xs:enumeration value="8"/>
      </xs:restriction>
    </xs:simpleType>
390 </xs:attribute>
    <xs:attribute name="offset" type="xs:int" default="0">
      <xs:annotation>
        <xs:documentation>
          Positive or negative offset between the
395 address of the end of previous element and the
          start of this elements's contents.
          Offset of zero means that this element starts
          immediately after the previous one.
        </xs:documentation>
      </xs:annotation>
400 </xs:attribute>
    <xs:attribute name="formatting" type="floatFormat">
      <xs:annotation>
        <xs:documentation>
          printf style format string for displaying data to the user, like %3.1f
405 </xs:documentation>
      </xs:annotation>
    </xs:attribute>
  </xs:complexType>
410
  <xs:complexType name="stringType">
    <xs:sequence>
      <xs:element name="name" minOccurs="0" maxOccurs="1" />
      <xs:element name="description" minOccurs="0" maxOccurs="1" />
415 <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1" />
    </xs:sequence>
    <xs:attribute name="size" type="xs:int" use="required">
      <xs:annotation>
        <xs:documentation>
          Storage size of this variable in bytes.
          This includes the trailing null byte that
          terminates the string content.
        </xs:documentation>
      </xs:annotation>
425 </xs:attribute>
    <xs:attribute name="offset" type="xs:int" default="0">
      <xs:annotation>
        <xs:documentation>
          Positive or negative offset between the
430 address of the end of previous element and the
          start of this elements's contents.
          Offset of zero means that this element starts
          immediately after the previous one.
        </xs:documentation>
      </xs:annotation>
435 </xs:attribute>

```

```

</xs:complexType>
<xs:element name="cdi">
  <xs:annotation>
    <xs:documentation>
      This is the schema for Configuration
      Description Information (cdi)
    </xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="identification" minOccurs="0" maxOccurs="1">
        <xs:annotation>
          <xs:documentation>
            Common first element to identify the decoder
          </xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="manufacturer" minOccurs="0" maxOccurs="1" />
            <xs:element name="model" minOccurs="0" maxOccurs="1" />
            <xs:element name="hardwareVersion" minOccurs="0" maxOccurs="1" />
            <xs:element name="softwareVersion" minOccurs="0" maxOccurs="1" />
            <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1">
              <xs:annotation>
                <xs:documentation>
                  This map can be used to add arbitrary key/value
                  descriptions of the node.
                </xs:documentation>
              </xs:annotation>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="acdi" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation>
      Element that identifies that memory information is available
      as defined by the Abbreviated Common Description Information
      (ACDI) standard.
    </xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:attribute name="fixed" type="xs:int" default="4">
      <xs:annotation>
        <xs:documentation>
          The decimal version number of the format for the fixed
          information block.
        </xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:attribute name="var" type="xs:int" default="2">
      <xs:annotation>
        <xs:documentation>
          The decimal version number of the format for
          the variable information block.
        </xs:documentation>
      </xs:annotation>
    </xs:attribute>
  </xs:complexType>
</xs:element>
<xs:element name="segment" minOccurs="0" maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>
      Define the contents of a memory space
    </xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="name" minOccurs="0" maxOccurs="1" />
      <xs:element name="description" minOccurs="0" maxOccurs="1" />

```

```

510      <xs:choice minOccurs="0" maxOccurs="unbounded">
511      <xs:annotation>
512      <xs:documentation>
513      Allows any sequence of the contained element types
514      </xs:documentation>
515      </xs:annotation>
516      <xs:element name="group" type="groupType" minOccurs="0" maxOccurs="1">
517      <xs:annotation>
518      <xs:documentation>
519      Allows grouping and replication of multiple locations.
520      </xs:documentation>
521      </xs:annotation>
522      </xs:element>
523      <xs:element name="string" type="stringType" minOccurs="0" maxOccurs="1">
524      <xs:annotation>
525      <xs:documentation>
526      Describes a human readable UTF-8 string in the data.
527      </xs:documentation>
528      </xs:annotation>
529      </xs:element>
530      <xs:element name="int" type="intType" minOccurs="0" maxOccurs="1">
531      <xs:annotation>
532      <xs:documentation>
533      Describes an integer value in the data.
534      The field can be considered either a number,
535      or a set of specific coded values via a map.
536      </xs:documentation>
537      </xs:annotation>
538      </xs:element>
539      <xs:element name="eventid" type="eventidType" minOccurs="0" maxOccurs="1">
540      <xs:annotation>
541      <xs:documentation>
542      Describes an 8-byte Event ID in the data.
543      </xs:documentation>
544      </xs:annotation>
545      </xs:element>
546      <!--
547      XML Schema 1.1 construct expressing extensibility promise
548      <xs:assert test="every $x in * satisfies (exists($x/@size) and $x/@size castable to
549      xs:integer)"/>
550      <xs:assert test="every $x in * satisfies (exists($x/@offset) and $x/@offset castable to
551      xs:integer)"/>
552      <xs:any minOccurs="0" maxOccurs="1" processContents="lax">
553      <xs:annotation>
554      <xs:documentation>
555      Extension point for future schema
556      </xs:documentation>
557      </xs:annotation>
558      </xs:any>
559      </xs:choice>
560      </xs:sequence>
561      <xs:attribute name="space" type="xs:int" use="required">
562      <xs:annotation>
563      <xs:documentation>
564      The decimal number of the address space where the information is found.
565      </xs:documentation>
566      </xs:annotation>
567      </xs:attribute>
568      <xs:attribute name="origin" type="xs:int" default="0">
569      <xs:annotation>
570      <xs:documentation>
571      Starting address of the segment's contents
572      within the memory space.
573      </xs:documentation>
574      </xs:annotation>
575      </xs:attribute>
576      </xs:complexType>
577      </xs:element>

```

```

580 </xs:sequence>
</xs:complexType>
</xs:element>
</xs:schema>
<?xml version="1.0" encoding="utf-8"?>
<?xml-stylesheet href="schema2xhtml.xsl" type="text/xsl"?>
585 <!-- XML Schema for OpenLCB Configuration Description Information (CDI) -->
<xs:schema version="CDI 1.4" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">

<xs:complexType name="mapType">
590 <xs:annotation>
<xs:documentation>
A map relates one or more property elements (keys)
to specific values.
</xs:documentation>
</xs:annotation>
595 <xs:sequence>
<xs:element name="name" minOccurs="0" maxOccurs="1" />
<xs:element name="description" minOccurs="0" maxOccurs="1" />
<xs:element name="relation" minOccurs="0" maxOccurs="unbounded">
600 <xs:complexType>
<xs:sequence>
<xs:element name="property" minOccurs="1" maxOccurs="1" />
<xs:element name="value" minOccurs="1" maxOccurs="1" />
</xs:sequence>
605 </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>

610 <xs:complexType name="groupType">
<xs:sequence>
<xs:element name="name" minOccurs="0" maxOccurs="1" />
<xs:element name="description" minOccurs="0" maxOccurs="1" />
<xs:element name="repname" minOccurs="0" maxOccurs="unbounded" />
615 <xs:choice minOccurs="0" maxOccurs="unbounded">
<xs:annotation>
<xs:documentation>
Allows any sequence of the contained element types
</xs:documentation>
620 </xs:annotation>
<xs:element name="group" type="groupType" minOccurs="0" maxOccurs="1" />
<xs:element name="string" type="stringType" minOccurs="0" maxOccurs="1" />
<xs:element name="int" type="intType" minOccurs="0" maxOccurs="1" />
<xs:element name="eventid" type="eventidType" minOccurs="0" maxOccurs="1" />
625 <xs:element name="float" type="floatType" minOccurs="0" maxOccurs="1" />
<xs:element name="action" type="actionButtonType" minOccurs="0" maxOccurs="1" />

```

<xs:element name="blob" type="blobType" minOccurs="0" maxOccurs="1" />
</xs:choice>
</xs:sequence>
630 <xs:attribute name="offset" type="xs:int" default="0">
<xs:annotation>
<xs:documentation>
Positive or negative offset between the address of
the end of previous element and the start of
635 this group's contents.
Offset of zero means that this element starts
immediately after the previous one.
</xs:documentation>
</xs:annotation>
640 </xs:attribute>
<xs:attribute name="replication" type="xs:int" default="1" />
</xs:complexType>

<xs:complexType name="eventidType">
645 <xs:sequence>
<xs:element name="name" minOccurs="0" maxOccurs="1" />
<xs:element name="description" minOccurs="0" maxOccurs="1" />
<xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1" />
</xs:sequence>
650 <xs:attribute name="offset" type="xs:int" default="0">
<xs:annotation>
<xs:documentation>
Positive or negative offset between the address of
the end of previous element and the start of
655 this elements's contents.
Offset of zero means that this element starts
immediately after the previous one.
</xs:documentation>
</xs:annotation>
660 </xs:attribute>
</xs:complexType>

<xs:simpleType name="yesNoType">
<xs:annotation>
665 <xs:documentation>
General definition of string that's either "yes" or "no".
</xs:documentation>
</xs:annotation>
<xs:restriction base="xs:token">
670 <xs:enumeration value="yes"/>
<xs:enumeration value="no"/>
</xs:restriction>


```

675 </xs:simpleType>
<xs:complexType name="hintsType">
  <xs:annotation>
    <xs:documentation>
      Presents optional hints to a GUI program
      for how to render this variable.
680 </xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="slider" minOccurs="0" maxOccurs="1" >
        <xs:complexType>
685 <xs:attribute name="tickSpacing" type="xs:integer" default="0">
          <xs:annotation>
            <xs:documentation>
              Recommends a value for the spacing between
              tick marks on the slider. For example, "10"
690 with a minimum value of 1 would put ticks at 0, 10, 20 etc
              along the slider axis.
            </xs:documentation>
          </xs:annotation>
        </xs:attribute>
695 <xs:attribute name="immediate" type="yesNoType" default="no">
          <xs:annotation>
            <xs:documentation>
              If yes, the slider will write to the
              configuration memory immediately when changed
700 </xs:documentation>
            </xs:annotation>
          </xs:attribute>
        </xs:complexType>
      </xs:element>
705 <xs:element name="radiobutton" minOccurs="0" maxOccurs="1" />
      <xs:element name="checkbox" minOccurs="0" maxOccurs="1" />
    </xs:sequence>
  </xs:complexType>
710 </xs:complexType name="intType">
  <xs:sequence>
    <xs:element name="name" minOccurs="0" maxOccurs="1" />
    <xs:element name="description" minOccurs="0" maxOccurs="1" />
    <xs:element name="min" minOccurs="0" maxOccurs="1" />
715 <xs:element name="max" minOccurs="0" maxOccurs="1" />
    <xs:element name="default" minOccurs="0" maxOccurs="1" />
    <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1">
      <xs:annotation>

```


720 <xs:documentation>
 The 'value' of each entry is displayed, and
 the 'property' content (number) is sent
 to/from the node
 </xs:documentation>
 </xs:annotation>
 725 </xs:element>
 <xs:element name="hints" type="hintsType" minOccurs="0" maxOccurs="1" />
 </xs:sequence>
 <xs:attribute name="size" default="1">
 <xs:annotation>
 730 <xs:documentation>
 Storage size of this variable in bytes.
 </xs:documentation>
 </xs:annotation>
 <xs:simpleType>
 735 <xs:restriction base="xs:token">
 <xs:enumeration value="1"/>
 <xs:enumeration value="2"/>
 <xs:enumeration value="4"/>
 <xs:enumeration value="8"/>
 740 </xs:restriction>
 </xs:simpleType>
 </xs:attribute>
 <xs:attribute name="offset" type="xs:int" default="0">
 <xs:annotation>
 745 <xs:documentation>
 Positive or negative offset between the
 address of the end of previous element and the
 start of this elements's contents.
 Offset of zero means that this element starts
 750 immediately after the previous one.
 </xs:documentation>
 </xs:annotation>
 </xs:attribute>
 </xs:complexType>
 755 <xs:simpleType name="floatFormat">
 <xs:restriction base="xs:string">
 <!-- This is a somewhat limiting regex, as it does not allow all possible -->
 <!-- printf formats. It will allow the most common formats that I have -->
 760 <!-- seen and used before, however -->
 <xs:pattern value="%[0-9]*(\.[0-9]*)?f"/>
 </xs:restriction>
 </xs:simpleType>

```

765 <xs:complexType name="floatType">
      <xs:sequence>
        <xs:element name="name" minOccurs="0" maxOccurs="1" />
        <xs:element name="description" minOccurs="0" maxOccurs="1" />
        <xs:element name="min" minOccurs="0" maxOccurs="1" />
770 <xs:element name="max" minOccurs="0" maxOccurs="1" />
        <xs:element name="default" minOccurs="0" maxOccurs="1" />
        <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1">
          <xs:annotation>
            <xs:documentation>
775 The 'value' of each entry is displayed, and
            the 'property' content (number) is sent
            to/from the node
          </xs:documentation>
        </xs:annotation>
780 </xs:element>
      </xs:sequence>
      <xs:attribute name="size" use="required">
        <xs:annotation>
          <xs:documentation>
785 Storage size of this variable in bytes. 2, 4 and 8 are valid.
          </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:token">
790 <xs:enumeration value="2"/>
          <xs:enumeration value="4"/>
          <xs:enumeration value="8"/>
          </xs:restriction>
        </xs:simpleType>
795 </xs:attribute>
        <xs:attribute name="offset" type="xs:int" default="0">
          <xs:annotation>
            <xs:documentation>
800 Positive or negative offset between the
            address of the end of previous element and the
            start of this elements's contents.
            Offset of zero means that this element starts
            immediately after the previous one.
          </xs:documentation>
805 </xs:annotation>
        </xs:attribute>
        <xs:attribute name="formatting" type="floatFormat" >
          <xs:annotation>
            <xs:documentation>
810 printf-style format string for displaying data to the user, like %3.1f

```

</xs:documentation>
</xs:annotation>
</xs:attribute>
</xs:complexType>
815
<xs:complexType name="stringType">
<xs:sequence>
<xs:element name="name" minOccurs="0" maxOccurs="1" />
<xs:element name="description" minOccurs="0" maxOccurs="1" />
820 <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1" />
</xs:sequence>
<xs:attribute name="size" type="xs:int" use="required">
<xs:annotation>
<xs:documentation>
825 Storage size of this variable in bytes.
This includes the trailing null byte that
terminates the string content.
</xs:documentation>
</xs:annotation>
830 </xs:attribute>
<xs:attribute name="offset" type="xs:int" default="0">
<xs:annotation>
<xs:documentation>
835 Positive or negative offset between the
address of the end of previous element and the
start of this elements's contents.
Offset of zero means that this element starts
immediately after the previous one.
</xs:documentation>
840 </xs:annotation>
</xs:attribute>
</xs:complexType>

<xs:complexType name="actionButtonType">
845 <xs:sequence>
<xs:element name="name" minOccurs="0" maxOccurs="1" />
<xs:element name="description" minOccurs="0" maxOccurs="1" />
<xs:element name="buttonText" minOccurs="0" maxOccurs="1">
<xs:annotation>
850 <xs:documentation>
Text to be displayed on the button.
This is required.
</xs:documentation>
</xs:annotation>
855 </xs:element>
<xs:element name="dialogText" minOccurs="0" maxOccurs="1">

<xs:annotation>
<xs:documentation>
Text to be displayed on the confirmation dialog.
860 If empty or not present, no confirmation dialog is displayed.
</xs:documentation>
</xs:annotation>
</xs:element>
<xs:element name="value" minOccurs="1" maxOccurs="1">
865 <xs:annotation>
<xs:documentation>
Value to be written when the button is triggered.
This is required.
</xs:documentation>
870 </xs:annotation>
</xs:element>
</xs:sequence>
<xs:attribute name="size" use="required">
<xs:annotation>
875 <xs:documentation>
Storage size of this variable in bytes.
This is required for backwards compatibility.
</xs:documentation>
</xs:annotation>
880 <xs:simpleType>
<xs:restriction base="xs:token">
<xs:enumeration value="1"/>
<xs:enumeration value="2"/>
<xs:enumeration value="4"/>
885 <xs:enumeration value="8"/>
</xs:restriction>
</xs:simpleType>
</xs:attribute>
<xs:attribute name="offset" type="xs:int" default="0">
890 <xs:annotation>
<xs:documentation>
Positive or negative offset between the address of
the end of previous element and the start of
this elements's contents.
895 Offset of zero means that this element starts
immediately after the previous one.
</xs:documentation>
</xs:annotation>
</xs:attribute>
900 </xs:complexType>
<xs:complexType name="blobType">

905 <xs:sequence>
<xs:element name="name" minOccurs="0" maxOccurs="1" />
<xs:element name="description" minOccurs="0" maxOccurs="1" />
</xs:sequence>
<xs:attribute name="size" use="required">
<xs:annotation>
<xs:documentation>
 910 Storage size of this variable in bytes.
This is fixed at 10 bytes.
An explicit value is required for backwards compatibility.
</xs:documentation>
</xs:annotation>
 915 <xs:simpleType>
<xs:restriction base="xs:token">
<xs:enumeration value="10"/>
</xs:restriction>
</xs:simpleType>
 920 </xs:attribute>
<xs:attribute name="offset" type="xs:int" default="0">
<xs:annotation>
<xs:documentation>
 925 Positive or negative offset between the address of
the end of previous element and the start of
this elements's contents.
Offset of zero means that this element starts
immediately after the previous one.
</xs:documentation>
 930 </xs:annotation>
</xs:attribute>
<xs:attribute name="mode" use="required">
<xs:annotation>
<xs:documentation>
 935 Whether the underlying blob can be read ("read"), can be written ("write"),
or both ("readwrite").
</xs:documentation>
</xs:annotation>
<xs:simpleType>
 940 <xs:restriction base="xs:token">
<xs:enumeration value="read"/>
<xs:enumeration value="write"/>
<xs:enumeration value="readwrite"/>
</xs:restriction>
 945 </xs:simpleType>
</xs:attribute>
</xs:complexType>

```

950 <xs:element name="cdi">
    <xs:annotation>
        <xs:documentation>
            This is the schema for Configuration
            Description Information (cdi)
        </xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="identification" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation>
                        Common first element to identify the decoder
                    </xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="manufacturer" minOccurs="0" maxOccurs="1" />
                        <xs:element name="model" minOccurs="0" maxOccurs="1" />
                        <xs:element name="hardwareVersion" minOccurs="0" maxOccurs="1" />
                        <xs:element name="softwareVersion" minOccurs="0" maxOccurs="1" />
                        <xs:element name="map" type="mapType" minOccurs="0" maxOccurs="1">
                            <xs:annotation>
                                <xs:documentation>
                                    This map can be used to add arbitrary key/value
                                    descriptions of the node.
                                </xs:documentation>
                            </xs:annotation>
                        </xs:element>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            <xs:element name="acdi" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation>
                        Element that identifies that memory information is available
                        as defined by the Abbreviated Common Description Information
                        (ACDI) standard.
                    </xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:attribute name="fixed" type="xs:int" default="4">
                        <xs:annotation>
                            <xs:documentation>
                                The decimal version number of the format for the fixed
                                information block.

```

```

995      </xs:documentation>
      </xs:annotation>
      </xs:attribute>
      <xs:attribute name="var" type="xs:int" default="2">
      <xs:annotation>
1000      <xs:documentation>
          The decimal version number of the format for
          the variable information block.
      </xs:documentation>
      </xs:annotation>
      </xs:attribute>
      </xs:complexType>
      </xs:element>
      <xs:element name="segment" minOccurs="0" maxOccurs="unbounded">
      <xs:annotation>
1010      <xs:documentation>
          Define the contents of a memory space
      </xs:documentation>
      </xs:annotation>
      <xs:complexType>
1015      <xs:sequence>
          <xs:element name="name" minOccurs="0" maxOccurs="1" />
          <xs:element name="description" minOccurs="0" maxOccurs="1" />
          <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:annotation>
1020      <xs:documentation>
          Allows any sequence of the contained element types
      </xs:documentation>
      </xs:annotation>
          <xs:element name="group" type="groupType" minOccurs="0" maxOccurs="1">
1025      <xs:annotation>
          <xs:documentation>
          Allows grouping and replication of multiple locations.
      </xs:documentation>
      </xs:annotation>
      </xs:element>
1030      <xs:element name="string" type="stringType" minOccurs="0" maxOccurs="1">
      <xs:annotation>
          <xs:documentation>
          Describes a human-readable UTF-8 string in the data.
1035      </xs:documentation>
      </xs:annotation>
      </xs:element>
          <xs:element name="int" type="intType" minOccurs="0" maxOccurs="1">
      <xs:annotation>
1040      <xs:documentation>

```

Describes an integer value in the data.
 The field can be considered either a number,
 or a set of specific coded values via a map.
 </xs:documentation>
 1045 </xs:annotation>
 </xs:element>
 <xs:element name="eventid" type="eventidType" minOccurs="0" maxOccurs="1">
 <xs:annotation>
 <xs:documentation>
 1050 Describes an 8-byte Event ID in the data.
 </xs:documentation>
 </xs:annotation>
 </xs:element>
 <xs:element name="float" type="floatType" minOccurs="0"
 1055 maxOccurs="1">
 <xs:annotation>
 <xs:documentation>
 Describes a float type in the data
 </xs:documentation>
 1060 </xs:annotation>
 </xs:element>
 <xs:element name="action" type="actionButtonType" minOccurs="0"
 maxOccurs="1">
 <xs:annotation>
 <xs:documentation>
 1065 Describes how to create an action button to write into the data.
 </xs:documentation>
 </xs:annotation>
 </xs:element>
 1070 <xs:element name="blob" type="blobType" minOccurs="0"
 maxOccurs="1">
 <xs:annotation>
 <xs:documentation>
 1075 Describes a blob of data that can be read/written/both.
 </xs:documentation>
 </xs:annotation>
 </xs:element>
 <!--
 1080 XML Schema 1.1 construct expressing extensibility promise
 <xs:any minOccurs="0" maxOccurs="1" processContents="lax">
 <xs:assert test="every \$x in * satisfies
 (exists(\$x/@size) and \$x/@size castable to xs:integer)"/>
 <xs:assert test="every \$x in * satisfies
 1085 (exists(\$x/@offset) and \$x/@offset castable to xs:integer)"/>
 <xs:annotation>

<xs:documentation>
Extension point for future schema
</xs:documentation>
1090 </xs:annotation>
</xs:any>
-->

1095 </xs:choice>
</xs:sequence>
<xs:attribute name="space" type="xs:int" use="required">
<xs:annotation>
<xs:documentation>
The decimal number of the address space where the information is found.
1100 </xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute name="origin" type="xs:int" default="0">
<xs:annotation>
1105 <xs:documentation>
Starting address of the segment's contents
within the memory space.
</xs:documentation>
</xs:annotation>
1110 </xs:attribute>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
1115 </xs:element>
</xs:schema>

Table of Contents

1 Introduction (Informative).....1

2 Intended Use (Informative).....1

3 References and Context (Informative).....1

4 Content (Normative).....2

5 Format (Normative).....2

 5.1 XML Elements.....3

 5.1.1 <identification> Element.....3

 5.1.2 <acdi> Element.....3

 5.1.3 <segment> Element.....4

 5.1.4 Data Elements.....4

 5.1.4.1 <group> Element.....4

 5.1.4.2 <int> Element.....5

 5.1.4.3 <string> Element.....5

 5.1.4.4 <eventid> Element.....5

6 Future Extension (Normative).....5

A Appendix: Schema.....7