



NMRA Standard	
Layout Command Control™ (LCC) Train Search Protocol	
July 22, 2024	S-9.7.4.7

Adopted as a NMRA Standard

The OpenLCB Standard document appended to this cover sheet has been formally adopted as a NMRA Standard by the NMRA Board of Directors on the date shown in the *Adopted* column in the *Version History* table below.

Version History

Date	Adopted	Summary of Changes
July 22, 2024		Initial version submitted for public comment

Important Notices and Disclaimers Concerning NMRA Standards Documents

The Standards (S), Recommended Practices (RP), Technical Note (TN) and Technical Information (TI) documents of the National Model Railroad Association ("NMRA Standards documents") are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading "Important Notices and Disclaimers Concerning NMRA Standards Documents."

Notice and Disclaimer of Liability Concerning the Use of NMRA Standards Documents

NMRA Standards documents are developed within the Standards and Conformance Department of the NMRA in association with certain Working Groups, members, and representatives of manufacturers and sellers. NMRA develops its standards through a consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. NMRA Standards documents are developed by volunteers with modeling, railroading, engineering, and industry-based expertise. Volunteers are not necessarily members of NMRA, and participate without compensation from NMRA.

NMRA does not warrant or represent the accuracy or completeness of the material contained in NMRA Standards documents, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard or recommended practice, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, NMRA disclaims any and all conditions relating to results and workmanlike effort. In addition, NMRA does not warrant or represent that the use of the material contained in NMRA Standards documents is free from patent infringement. NMRA Standards documents are supplied "AS IS" and "WITH ALL FAULTS."

Use of NMRA Standards documents is wholly voluntary. The existence of an NMRA Standard or Recommended Practice does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the NMRA Standards documents. Furthermore, the viewpoint expressed at the time that NMRA approves or issues a Standard or Recommended Practice is subject to change brought about through developments in the state of the art and comments received from users of NMRA Standards documents.

In publishing and making its standards available, NMRA is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is NMRA undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any NMRA Standards document, should rely upon their own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given NMRA Standards documents.

IN NO EVENT SHALL NMRA BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD OR RECOMMENDED PRACTICE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

NMRA's development of NMRA Standards documents involves the review of documents in English only. In the event that an NMRA Standards document is translated, only the English version published by NMRA is the approved NMRA Standards document.

Official Statements

A statement, written or oral, that is not processed in accordance with NMRA policies for distribution of NMRA communications, or approved by the Board of Directors, an officer or committee chairperson, shall not be considered or inferred to be the official position of NMRA or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of NMRA.

Comments on Standards

Comments for revision of NMRA Standards documents are welcome from any interested party, regardless of membership. However, **NMRA does not provide interpretations, consulting information, or advice pertaining to NMRA Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since NMRA standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, NMRA, its departments, Working Groups or committees cannot provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, NMRA does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to NMRA Standards documents may request participation in the relevant NMRA working group.

Laws & Regulations


Users of NMRA Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any NMRA Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. NMRA does not, by the publication of NMRA Standards documents, intend to urge action that is not in compliance with applicable laws, and NMRA Standards documents may not be construed as doing so.

Copyrights

NMRA Standards documents are copyrighted by NMRA under US and international copyright laws. They are made available by NMRA and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of modeling, structural and engineering practices and methods. By making NMRA Standards documents available for use and adoption by public authorities and private users, NMRA does not waive any rights in copyright to the NMRA Standards documents.

IMPORTANT NOTICE

NMRA Standards documents do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other systems, devices or networks. NMRA Standards documents development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of NMRA Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.



OpenLCB Standard

Train Search Protocol

July 22, 2024

Adopted

1 Introduction (Informative)

This standard defines a method for Throttle Nodes to find Train Nodes on the network, and for track protocol use-cases, instruct an OpenLCB Command Station to create a virtual Train Node given a track protocol and an address. This standard is not specific to any link layer choice.

2 Intended Use (Informative)

The OpenLCB Train Control protocol describes how a Node acting as throttle can and should control a Node acting as a train. An important component of an ecosystem is how the throttle can find the remote Train Node that corresponds to the user's desired locomotive to control. This standard defines one possible method on how to find Train Nodes from a throttle. As a basic transport this method uses the Event Transport protocol.

When an OpenLCB Command Station is controlling many locomotives through a track protocol (e.g. DCC), it acts as a gateway between the OpenLCB Train Control protocol and the track protocol. For the purpose of the Train Control protocol, all of the controlled trains have to have unique Train Nodes on the OpenLCB bus, therefore the Command Station is representing many Nodes on the OpenLCB bus. These are called *virtual Nodes*, or *virtual Train Nodes*.

In addition to finding already existing Train Nodes, this standard describes an interaction that can be followed by a Command Station to instantiate the virtual Train Nodes. As part of this interaction, certain options are specifically enumerated in this standard that are specific to current commonly used track protocols (such as DCC), while leaving expansion space for including additional such protocols in future revisions.

Note that this standard does not exclude other methods and standards, including some not yet developed, for the same or similar purposes. See the Train Search Protocol Technical Note for some alternatives that were considered or can be employed based on more general enumeration protocols.

3 References and Context (Normative)

This specification is in the context of the following OpenLCB Standards:

- The Event Transport Standard, which defines the protocol for transporting events, including the messages and interactions for inquiry and discovery of event Producers.
- The Event Identifiers Standard which describes the allocation scheme of Event Identifiers.

For more information on format and presentation, see:

- OpenLCB Common Information Technical Note

4 Message Formats (Normative)

This standard does not define any OpenLCB messages.

5 Allocation (Normative)

5.1 Identifier Range allocation and License terms

For the purpose of the Train Search Protocol the following block of consecutive Event Identifiers is allocated:

09.00.99.FF.00.00.00.00 – 09.00.99.FF.FF.FF.FF

All Event Identifiers in this range are reserved for exclusive use according to the interactions defined by this standard and shall not be used for any other purpose.

The legal entity to whom this Event Identifier range is allocated by the Unique Identifiers Standard, Train Control Systems, Inc, hereby grants an irrevocable, non-transferable license to anyone for using the quoted Event Identifiers on the condition, and only so long as, that their use is compliant to this Standard or any later version of it, published by Train Control Systems, Inc., or the OpenLCB Group.

5.2 Identifier Format

Note that the semantic meaning of these identifiers are defined in Section 6 (Interactions).

Table 1. The Event Identifiers in the given range are defined as follows:

Byte 1	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	Byte 7	Byte 8
09	00	99	FF	qq	qq	qq	rr
Fixed prefix				Search query (6 nibbles)		Flags	

The search query ‘qq qq qq’ shall be a sequence of 6 nibbles in MSB-first order stored in Bytes 5, 6 and 7 of the Event Identifier.

Table 2. Each individual nibble is one position of the search string:

Search Query Nibble value	Description
0 - 9	The given position of the search term is the given number

Search Query Nibble value	Description
0xA - 0xE	Reserved. Do not send, check upon receipt.
0xF	Empty / unused character position. Short queries shall be padded with this nibble value to 6 characters long. Multiple search terms may be concatenated to a search query with this nibble as a separator between them, which means the individual terms shall be evaluated with an AND relation between them.

Table 3. The flag byte ‘rr’ is defined as follows:

Bit 7	Bit 6	Bit 5	Bits 4-0	Description
Allocate				0x80: Force allocate new gateway node 0: Search only existing nodes
	Exact			0x40: Exact match only 0: All matches (including partial match)
		Address only		0x20: Match only in address 0: Match everywhere (address and name)
			Track Protocol	See Table 4 for assignment

55

Table 4. The Track Protocol values are defined as follows:

Bit 4-3	Bit 2	Bits 1-0	Description
0b00	0	0b00	Any / Default track protocol
		0b01	Native OpenLCB Train Node
		0b10	MFX® / M4® track protocol
		0b11	Reserved (do not send, check on receipt).
	1	*	Märklin-Motorola track protocol
		0b00	MM – Any / Default version
		0b01	MM – Protocol version I (14 speed steps + F0)
		0b10	MM – Protocol version II (Directional + F0-F4)

Bit 4-3	Bit 2	Bits 1-0	Description
		0b11	MM – Protocol version II with following address for F5-F8 support.
0b01	*	*	DCC track protocol
	0		DCC – Default address space
	1		DCC – Force 14-bit (long) address
		0b00	DCC – Any / Default speed steps
		0b01	DCC – 14 speed steps
		0b10	DCC – 28 speed steps
		0b11	DCC – 128 speed steps
0b10	*	*	Reserved (do not send, check upon receipt)
0b11	*	*	Reserved (do not send, check upon receipt)

6 Interactions (Normative)

The following hardware and software nodes are taking part in the interactions presented here:

- 60 • The **Train Node** is an OpenLCB Node that implements the Train Control Protocol, controlling a single (physical) train with one or more coupled engines. The hardware implementing the Train Node may be physically built into a model, or it may be built into a centralized gateway hardware that converts to a non-OpenLCB protocol in order to remotely control an engine, for example via Bluetooth or a pre-existing track protocol such as DCC or Märklin-Motorola. In this case a single piece of hardware may be responsible for representing multiple OpenLCB Nodes on the network.
- 65 • The **Throttle Node** is an OpenLCB Node that intends to send Train Control Protocol commands to a desired Train Node. The Throttle Node may be a physical hardware device with a user interface to be used by an operator, a computer software with a user interface for operators to control trains, or a fully automated software.
- 70 • The **Command Station** is a gateway for proxying to some non-OpenLCB protocol, implementing Train Node(s), and having an OpenLCB network connection. There may or may not be a separate OpenLCB Node that represents the Command Station itself on the OpenLCB network.
- 75 A Train Node has a set of properties, the following of which are relevant for the interactions defined in this Standard:
 - **Name** is a user-assigned textual (alphanumeric) description for the train.

- **Protocol** defines the native command set that is used to address this train. The options are listed in Table 4.
- 80 • **Address** is a user-assigned numerical value that uniquely identifies a train within a Protocol. There cannot be two trains with the same Protocol and same Address on the track at the same time. Not all Protocols have a user-assigned Address. The Address for the DCC Protocol also carries a disambiguator on whether it is a short (7-bit) or long (14-bit) DCC address.
- 85 • **Protocol Version** selects the exact command set to use for a Track Protocol. Users sometimes have to select a specific Protocol Version to correctly operate a train or to access all possible features of it.

6.1 Search for existing train nodes

The goal of this use-case is for a Throttle Node to enumerate Train Nodes that exist on the network and match certain criteria. The Throttle Node shall represent the given criteria as an Event Identifier *E* according to Section 5.2, and shall set the flag byte ‘rr’ Bit 7 (Allocate) to zero (0).

- The Throttle Node shall send an “Identify Producer” message with setting the Event Identifier to *E* to the network.
- A Train Node, upon receipt of an Identify Producer message with an Event Identifier *E* falling into the Event Identifier Range of Section 5.1, shall
 - 95 ◦ compare the Train Node’s identifying properties to the search criteria represented by the Event Identifier *E* according to Section 6.3;
 - in case of a match, the Train Node shall emit a “Producer Identified” message with the Event Identifier *E* to the network, setting the Producer validity bits according to Section 6.4 ;
 - 100 ◦ in absence of a match, the Train Node shall not emit a “Producer Identified” message with the Event Identifier *E*.

6.2 Allocate a new Train Node

The goal of this use-case is for a Throttle Node to instruct a Command Station to create a new Train Node in the case that no existing Train Node(s) match the search criteria requested by the Throttle Node. This interaction can also be used to change the Protocol Version of an existing Train Node.

The Throttle Node shall represent the requested address as an Event Identifier *E* according to Section 5.2, with the flag byte ‘rr’ Bit 7 (Allocate) set to one (0x80). The Throttle Node may, but is not required to, specify the desired track protocol in the flag byte. It is recommended that the Throttle Node also sets Bit 6 (Exact) to one (0x40) in the flag byte.

- The Throttle Node shall send an “Identify Producer” message with setting the Event Identifier to *E* to the network.
- A Command Station upon receipt of an Identify Producer message with an Event Identifier *E* falling into the Event Identifier Range of Section 5.1 with the flag byte ‘rr’ Bit 7 (Allocate) set to one, shall

- 115 ○ validate that it has the ability to create a Train Node matching its identifying properties to the search criteria represented by the Event Identifier *E* according to Section 6.3; for properties marked as ‘Any / Default’ by the Event Identifier *E* the Command Station may pick any implementation-specific default or user-configured value;
- 120 ○ wait at least 200 msec for existing Train Nodes to reply with a “Producer Identified” message;
- 125 ○ in the absence of such reply, the Command Station shall
- allocate a new Train Node according to the properties defined by the Event Identifier *E*, or
 - adjust the Protocol Version of an existing Train Node conflicting with the requested address to match the value defined by the Event Identifier *E*,
- then instruct the Train Node to emit a “Producer Identified Valid” message with the Event Identifier *E*.

6.3 Event Identifier matching algorithm

- 130 This section defines when an Event Identifier *E* in the range defined by Section 5.1 matches a Train Node with the identifying properties of *<Name, Address, Protocol, Protocol Version>*.

The Train Node matches the Event Identifier *E* if and only if

- the search query represented by the *qq qq qq* nibbles of *E* matches, AND
- the requirement by the *rr* flag byte matches the *Protocol*, AND
- the Flag byte or the query nibbles specify no reserved values marked as “check upon receipt”.

- 135 The flag byte *rr* matches *Protocol* if and only if the Track Protocol field of *rr* is set to “Default/Any” OR *Protocol* matches the value of the Track Protocol field.

The *Protocol Version* is not used by the matching algorithm.

The Flag byte *rr* requests a DCC long address if and only if *rr* specifies the DCC protocol AND Bit 2 (DCC - Force long address bit) is set.

- 140 The search query represented by the *qq qq qq* nibbles of *E* matches if and only if

- *qq qq qq* matches the *Address* of the Train Node, OR
- Bit 5 (Address only) is clear in the Flag byte *rr* AND *qq qq qq* matches the *Name*.

The *qq qq qq* nibbles of *E* matches the *Address* if and only if *qq qq qq* contains exactly one contiguous sequence of digit nibbles ‘0’-‘9’, AND

- 145 • *Protocol* is not DCC, OR
- the decimal value represented by these nibbles is ≥ 128 , OR
 - the Flag byte *rr* requests a DCC long address AND *Address* is a DCC 14-bit (long) address, OR

- the Flag byte *rr* does not request a DCC long address AND *Address* is a DCC 7-bit (short) address, OR
- 150 • the Flag byte *rr* does not request a DCC long address AND Bit 7 (Allocate) is clear in the Flag byte *rr*

AND

- the Exact bit of the Flag byte *rr* is set AND the decimal value represented by these nibbles is the value of the *Address*, OR
- 155 • the Exact bit if the Flag byte *rr* is clear AND the decimal nibbles form a prefix of the decimal representation of *Address*.

160 The *qq qq qq* nibbles of *E* matches the *Name* if and only if *qq qq qq* contains one or more contiguous sequence of digit nibbles 0x00x-0x9 separated with one or more nibble 0xF and each of those match the *Name*.

A maximal¹ contiguous sequence of digit nibbles *nn...n* in *E* match the *Name* if and only if there is a pair of positions [*p*,*q*] in *Name* such that there is no digit character immediately preceding position *p* in *Name*, AND *nn...n* equals the concatenation of all digit characters found in *Name* from position *p* to *q*², AND

- 165 • Flag byte *rr* has Bit 6 (Exact) not set, OR
- there is no digit character immediately following position *q* in *Name*.

6.4 Search Result Differentiation

170 A Train Node replying with Producer Identified message may, but is not required to to differentiate on how accurately the search query matches the Train Node's properties by picking the response message from the set of Producer Identified Valid, Producer Identified Invalid and Producer Identified Unknown messages. The responses represent the quality of match with 'Valid' > 'Invalid' > 'Unknown'. A Node may use any implementation-specific algorithm, which may also take into account properties not represented in this standard for making the determination.

175 If a Train Node does not make a differentiation, it shall use Producer Identified Unknown as response message for Search responses.

¹No 0x0-0x9 nibbles immediately before or after this substring within *qq qq qq*.

15 ²Any non-digit characters shall be skipped for this definition.

Table of Contents

1	Introduction (Informative).....	1
2	Intended Use (Informative).....	1
3	References and Context (Normative).....	1
4	Message Formats (Normative).....	2
5	Allocation (Normative).....	2
5.1	Identifier Range allocation and License terms.....	2
5.2	Identifier Format.....	2
6	Interactions (Normative).....	4
6.1	Search for existing train nodes.....	5
6.2	Allocate a new Train Node.....	5
6.3	Event Identifier matching algorithm.....	6
6.4	Search Result Differentiation.....	7