


USB Connector



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2


Document Number:

REV:

Date: 6/4/2023 8:28 PM

Sheet: 1/15

Ideal Diode



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.


To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2

Document Number: REV:

Date: 6/4/2023 8:28 PM Sheet: 2/15

Battery Charging



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2


Document Number:

REV:

Date: 6/4/2023 8:28 PM

Sheet: 3/15

SNVS Reg



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2


Document Number:

REV:

Date: 6/4/2023 8:28 PM

Sheet: 4/15

Main Regulator




* PMIC_REG_ON is level shifted to ensure regulator goes into PFM mode

Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>
This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE:	rt1060r2
Document Number:	REV:
Date: 6/4/2023 8:28 PM	Sheet: 5/15

16-BIT SDRAM

* CKE is pulled down by 100K on the RT1062




Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.


To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2	
Document Number:	REV:
Date: 6/4/2023 8:28 PM	Sheet: 6/15

Program QSPI Flash



RGB LED



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2

Document Number:



REV:

Date: 6/4/2023 8:28 PM

Sheet: 7/15

Security

Accelerometer




Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2	
Document Number:	REV:
Date: 6/4/2023 8:28 PM	Sheet: 8/15


SD CARD



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>
This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE:	rt1060r2
Document Number:	REV:
Date: 6/4/2023 8:28 PM	Sheet: 9/15

IMAGE SENSOR CONNECTOR



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.


To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2

Document Number: REV:

Date: 6/4/2023 8:28 PM Sheet: 10/15

I/O HEADERS




Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>
This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2	REV:
Document Number:	
Date: 6/4/2023 8:28 PM	Sheet: 11/15

JTAG

* JTAG_MOD is used for BT_REG_ON - the pin is sampled on the rising edge of reset and is pulled low by 10K



* The JTAG Interface is designed to connect to the SEGGER 9-Pin Cortex-M Adapter.

* Note that JTAG is disabled on the RT1060 by default. Only SWD works.
Given this those I/O pins are routed to the external header.
A fuse must be blown to switch to JTAG which disables SWD.

Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>


TITLE: rt1060r2

Document Number: REV:

Date: 6/4/2023 8:28 PM Sheet: 12/15

Ethernet

* 8KV ESD Protection on MDI pins and the LED pin



Mechanical



H1 MOUNT-PAD-ROUND2.8

H2 MOUNT-PAD-ROUND2.8



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2


Document Number:

REV:

Date: 6/4/2023 8:28 PM

Sheet: 13/15

WiFi/Bluetooth



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>


TITLE: rt1060r2

Document Number:

REV.

Date: 6/4/2023 8:28 PM

MIMXRT1062



Copyright (c) 2013-2023 OpenMV <openmv@openmv.io>

This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>

TITLE: rt1060r2

Document Number:

REV:

Date: 6/4/2023 8:28 PM

Sheet: 15/15