

CSS animation-fill-mode Property

[Reference](#)

Example

Let the <div> element retain the style values from the last keyframe when the animation ends:

```
div {  
  animation-fill-mode: forwards;  
}
```

[Try it Yourself »](#)

More "Try it Yourself" examples below.

Definition and Usage

The **animation-fill-mode** property specifies a style for the element when the animation is not playing (before it starts, after it ends, or both).

CSS animations do not affect the element before the first keyframe is played or after the last keyframe is played. The **animation-fill-mode** property can override this behavior.

Default value:	none
Inherited:	no



HTML

CSS

JAVASCRIPT






**JavaScript syntax:** `object.style.animationFillMode="forwards"`

Try it

Browser Support

The numbers in the table specify the first browser version that fully supports the property.

Numbers followed by -webkit-, -moz-, or -o- specify the first version that worked with a prefix.

Property					
animation-fill-mode	43.0 4.0 -webkit-	10.0	16.0 5.0 -moz-	9.0 4.0 -webkit-	30.0 15.0 -webkit- 12.1 12.0 -o-

CSS Syntax

```
animation-fill-mode: none|forwards|backwards|both|initial|inherit;
```

Property Values

Value	Description
none	Default value. Animation will not apply any styles to the element before or after it is executing
forwards	The element will retain the style values that is set by the last keyframe (depends on animation-direction and animation-iteration-count)
backwards	The element will get the style values that is set by the first keyframe (depends on animation-direction), and retain this during the animation-delay period



HTML

CSS

JAVASCRIPT



inherit

Inherits this property from its parent element. [Read about *inherit*](#)

More Examples

Example

Let the <div> element get the style values set by the first keyframe before the animation starts (during the animation-delay period):

```
div {  
  animation-fill-mode: backwards;  
}
```

[Try it Yourself »](#)

Example

Let the <div> element get the style values set by the first keyframe before the animation starts, and retain the style values from the last keyframe when the animation ends:

```
div {  
  animation-fill-mode: both;  
}
```

[Try it Yourself »](#)

Related Pages

CSS tutorial: [CSS Animations](#)



Menu ▼

✦ Bootcamps

📁 Spaces

Sign Up

Log in



HTML

CSS

JAVASCRIPT

Reference



COLOR PICKER



Join our Mini CSS Bootcamp



★★★★★

“W3Schools Bootcamp is the best investment that I have ever made. All the material from your catalog is really well explained, and has helped me to gain a great background.”

Student at W3Schools

Read more

- Spaces
- Upgrade
- Newsletter
- Get Certified
- Report Error

Top Tutorials



Menu ▼

✦ Bootcamps

📁 Spaces

Sign Up

Log in



HTML

CSS

JAVASCRIPT



[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

