

CSS Tutorial

- CSS HOME
- CSS Introduction
- CSS Syntax
- CSS Selectors
- CSS How To
- CSS Comments
- CSS Colors
- CSS Backgrounds
- CSS Borders
- CSS Margins
- CSS Padding
- CSS Height/Width
- CSS Box Model
- CSS Outline
- CSS Text
- CSS Fonts
- CSS Icons
- CSS Links
- CSS Lists
- CSS Tables
- CSS Display
- CSS Max-width
- CSS Position
- CSS Z-index
- CSS Overflow
- CSS Float
- CSS Inline-block
- CSS Align
- CSS Combinators
- CSS Pseudo-class
- CSS Pseudo-element
- CSS Opacity
- CSS Navigation Bar
- CSS Dropdowns
- CSS Image Gallery
- CSS Image Sprites
- CSS Attr Selectors
- CSS Forms
- CSS Counters
- CSS Website Layout
- CSS Units
- CSS Specificity
- CSS Important
- CSS Math Functions

CSS Advanced

- CSS Rounded Corners
- CSS Border Images
- CSS Backgrounds
- CSS Colors
- CSS Color Keywords
- CSS Gradients
- CSS Shadows
- CSS Text Effects
- CSS Web Fonts
- CSS 2D Transforms
- CSS 3D Transforms
- CSS Transitions

CSS Animations

- CSS Tooltips
- CSS Style Images
- CSS Image Reflection
- CSS object-fit
- CSS object-position
- CSS Masking
- CSS Buttons
- CSS Pagination
- CSS Multiple Columns
- CSS User Interface
- CSS Variables
- CSS Box Sizing
- CSS Media Queries
- CSS MQ Examples
- CSS Flexbox

CSS Responsive

- RWD Intro
- RWD Viewport
- RWD Grnd View
- RWD Media Queries
- RWD Images
- RWD Videos
- RWD Frameworks
- RWD Templates

CSS Grid

- Grid Intro
- Grid Container
- Grid Item

CSS SASS

- SASS Tutorial

CSS Examples

- CSS Templates
- CSS Examples
- CSS Editor
- CSS Snippets
- CSS Quiz
- CSS Exercises
- CSS Bootcamp
- CSS Certificate

CSS References

- CSS Reference
- CSS Selectors
- CSS Functions
- CSS Reference Aural
- CSS Web Safe Fonts
- CSS Animatable
- CSS Units
- CSS PX-EM Converter
- CSS Colors
- CSS Color Values
- CSS Default Values
- CSS Browser Support

CSS Animations

Previous

Next

CSS Animations

CSS allows animation of HTML elements without using JavaScript or Flash!

CSS

In this chapter you will learn about the following properties:

- @keyframes
- animation-name
- animation-duration
- animation-delay
- animation-iteration-count
- animation-direction
- animation-timing-function
- animation-fill-mode
- animation

Browser Support for Animations

The numbers in the table specify the first browser version that fully supports the property.

Property					
@keyframes	43.0	10.0	16.0	9.0	30.0
animation-name	43.0	10.0	16.0	9.0	30.0
animation-duration	43.0	10.0	16.0	9.0	30.0
animation-delay	43.0	10.0	16.0	9.0	30.0
animation-iteration-count	43.0	10.0	16.0	9.0	30.0
animation-direction	43.0	10.0	16.0	9.0	30.0
animation-timing-function	43.0	10.0	16.0	9.0	30.0
animation-fill-mode	43.0	10.0	16.0	9.0	30.0
animation	43.0	10.0	16.0	9.0	30.0

What are CSS Animations?

An animation lets an element gradually change from one style to another.

You can change as many CSS properties you want, as many times as you want.

To use CSS animation, you must first specify some keyframes for the animation.

Keyframes hold what styles the element will have at certain times.

The @keyframes Rule

When you specify CSS styles inside the @keyframes rule, the animation will gradually change from the current style to the new style at certain times.

To get an animation to work, you must bind the animation to an element.

The following example binds the "example" animation to the <div> element. The animation will last for 4 seconds, and it will gradually change the background-color of the <div> element from "red" to "yellow".

Example

```
/* The animation code */
@keyframes example {
  from {background-color: red;}
  to {background-color: yellow;}
}

/* The element to apply the animation to */
div {
  width: 100px;
  height: 100px;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
}
```

Try it Yourself »

Note: The animation-duration property defines how long an animation should take to complete. If the animation-duration property is not specified, no animation will occur, because the default value is 0s (0 seconds).

In the example above we have specified when the style will change by using the keywords "from" and "to" (which represents 0% (start) and 100% (complete)).

It is also possible to use percent. By using percent, you can add as many style changes as you like.

The following example will change the background-color of the <div> element when the animation is 25% complete, 50% complete, and again when the animation is 100% complete:

Example

```
/* The animation code */
@keyframes example {
  0% {background-color: red;}
  25% {background-color: yellow;}
  50% {background-color: blue;}
  100% {background-color: green;}
}

/* The element to apply the animation to */
div {
  width: 100px;
  height: 100px;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
}
```

Try it Yourself »

The following example will change both the background-color and the position of the <div> element when the animation is 25% complete, 50% complete, and again when the animation is 100% complete:

Example

Save \$1118

Invest in your professional development!

Get Lifelong Access To All Current & Future Courses

Get Full Access

COLOR PICKER



SUMMER SALE 50% OFF

From 7th of July 2023 - 1st of August 2023

S

E

JS

Kickstart your Front- end Career!

Get certified today!

Does not include Bootcamps & Subscriptions

W

CSS Tutorial

CSS HOME

CSS Introduction

CSS Syntax

CSS Selectors

CSS How To

CSS Comments

CSS Colors

CSS Backgrounds

CSS Borders

CSS Margins

CSS Padding

CSS Height/Width

CSS Box Model

CSS Outline

CSS Text

CSS Fonts

CSS Icons

CSS Links

CSS Lists

CSS Tables

CSS Display

CSS Max-width

CSS Position

CSS Z-index

CSS Overflow

CSS Float

CSS Inline-block

CSS Align

CSS Combinators

CSS Pseudo-class

CSS Pseudo-element

CSS Opacity

CSS Navigation Bar

CSS Dropdowns

CSS Image Gallery

CSS Image Sprites

CSS Attr Selectors

CSS Forms

CSS Counters

CSS Website Layout

CSS Units

CSS Specificity

CSS Important

CSS Math Functions

CSS Animations

CSS Tooltips

CSS Style Images

CSS Image Reflection

CSS object-fit

CSS object-position

CSS Masking

CSS Buttons

CSS Pagination

CSS Multiple Columns

CSS User Interface

CSS Variables

CSS Box Sizing

CSS Media Queries

CSS MQ Examples

CSS Flexbox

CSS Responsive

RWD Intro

RWD Viewport

RWD Grnd View

RWD Media Queries

RWD Images

RWD Videos

RWD Frameworks

RWD Templates

CSS Grid

Grid Intro

Grid Container

Grid Item

CSS SASS

SASS Tutorial

CSS Examples

CSS Templates

CSS Examples

CSS Editor

CSS Snippets

CSS Quiz

CSS Exercises

CSS Bootcamp

CSS Certificate

CSS References

CSS Reference

CSS Selectors

CSS Functions

CSS Reference Aural

CSS Web Safe Fonts

CSS Animatable

CSS Units

CSS PX-EM Converter

CSS Colors

CSS Color Values

CSS Default Values

CSS Browser Support

```
50% {background-color:blue; left:200px; top:200px;}
75% {background-color:green; left:0px; top:200px;}
100% {background-color:red; left:0px; top:0px;}
}
```

```
/* The element to apply the animation to */
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
}
```

Try it Yourself »

Delay an Animation

The `animation-delay` property specifies a delay for the start of an animation.

The following example has a 2 seconds delay before starting the animation:

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
  animation-delay: 2s;
}
```

Try it Yourself »

Negative values are also allowed. If using negative values, the animation will start as if it had already been playing for *N* seconds.

In the following example, the animation will start as if it had already been playing for 2 seconds:

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
  animation-delay: -2s;
}
```

Try it Yourself »

Set How Many Times an Animation Should Run

The `animation-iteration-count` property specifies the number of times an animation should run.

The following example will run the animation 3 times before it stops:

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
  animation-iteration-count: 3;
}
```

Try it Yourself »

The following example uses the value "infinite" to make the animation continue for ever:

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
  animation-iteration-count: infinite;
}
```

Try it Yourself »

Run Animation in Reverse Direction or Alternate Cycles

The `animation-direction` property specifies whether an animation should be played forwards, backwards or in alternate cycles.

The animation-direction property can have the following values:

- `normal` - The animation is played as normal (forwards). This is default
- `reverse` - The animation is played in reverse direction (backwards)
- `alternate` - The animation is played forwards first, then backwards
- `alternate-reverse` - The animation is played backwards first, then forwards

The following example will run the animation in reverse direction (backwards):

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
}
```


CSS Tutorial

CSS HOME

CSS Introduction

CSS Syntax

CSS Selectors

CSS How To

CSS Comments

CSS Colors

CSS Backgrounds

CSS Borders

CSS Margins

CSS Padding

CSS Height/Width

CSS Box Model

CSS Outline

CSS Text

CSS Fonts

CSS Icons

CSS Links

CSS Lists

CSS Tables

CSS Display

CSS Max-width

CSS Position

CSS Z-index

CSS Overflow

CSS Float

CSS Inline-block

CSS Align

CSS Combinators

CSS Pseudo-class

CSS Pseudo-element

CSS Opacity

CSS Navigation Bar

CSS Dropdowns

CSS Image Gallery

CSS Image Sprites

CSS Attr Selectors

CSS Forms

CSS Counters

CSS Website Layout

CSS Units

CSS Specificity

CSS Important

CSS Math Functions

CSS Advanced

CSS Rounded Corners

CSS Border Images

CSS Backgrounds

CSS Colors

CSS Color Keywords

CSS Gradients

CSS Shadows

CSS Text Effects

CSS Web Fonts

CSS 2D Transforms

CSS 3D Transforms

CSS Transitions

CSS Animations

CSS Tooltips

CSS Style Images

CSS Image Reflection

CSS object-fit

CSS object-position

CSS Masking

CSS Buttons

CSS Pagination

CSS Multiple Columns

CSS User Interface

CSS Variables

CSS Box Sizing

CSS Media Queries

CSS MQ Examples

CSS Flexbox

CSS Responsive

RWD Intro

RWD Viewport

RWD Grnd View

RWD Media Queries

RWD Images

RWD Videos

RWD Frameworks

RWD Templates

CSS Grid

Grid Intro

Grid Container

Grid Item

CSS SASS

SASS Tutorial

CSS Examples

CSS Templates

CSS Examples

CSS Editor

CSS Snippets

CSS Quiz

CSS Exercises

CSS Bootcamp

CSS Certificate

CSS References

CSS Reference

CSS Selectors

CSS Functions

CSS Reference Aural

CSS Web Safe Fonts

CSS Animatable

CSS Units

CSS PX-EM Converter

CSS Colors

CSS Color Values

CSS Default Values

CSS Browser Support

The following example uses the value "alternate" to make the animation run forwards first, then backwards:

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
  animation-iteration-count: 2;
  animation-direction: alternate;
}
```

Try it Yourself »

The following example uses the value "alternate-reverse" to make the animation run backwards first, then forwards:

Example

```
div {
  width: 100px;
  height: 100px;
  position: relative;
  background-color: red;
  animation-name: example;
  animation-duration: 4s;
  animation-iteration-count: 2;
  animation-direction: alternate-reverse;
}
```

Try it Yourself »

Specify the Speed Curve of the Animation

The `animation-timing-function` property specifies the speed curve of the animation.

The animation-timing-function property can have the following values:

- `ease` - Specifies an animation with a slow start, then fast, then end slowly (this is default)
- `linear` - Specifies an animation with the same speed from start to end
- `ease-in` - Specifies an animation with a slow start
- `ease-out` - Specifies an animation with a slow end
- `ease-in-out` - Specifies an animation with a slow start and end
- `cubic-bezier(n,n,n,n)` - Lets you define your own values in a cubic-bezier function

The following example shows some of the different speed curves that can be used:

Example

```
#div1 {animation-timing-function: linear;}
#div2 {animation-timing-function: ease;}
#div3 {animation-timing-function: ease-in;}
#div4 {animation-timing-function: ease-out;}
#div5 {animation-timing-function: ease-in-out;}
```

Try it Yourself »

Specify the fill-mode For an Animation

CSS animations do not affect an element before the first keyframe is played or after the last keyframe is played. The `animation-fill-mode` property can override this behavior.

The `animation-fill-mode` property specifies a style for the target element when the animation is not playing (before it starts, after it ends, or both).

The animation-fill-mode property can have the following values:

- `none` - Default value. Animation will not apply any styles to the element before or after it is executing
- `forwards` - The element will retain the style values that is set by the last keyframe (depends on animation-direction and animation-iteration-count)
- `backwards` - The element will get the style values that is set by the first keyframe (depends on animation-direction), and retain this during the animation-delay period
- `both` - The animation will follow the rules for both forwards and backwards, extending the animation properties in both directions

The following example lets the <div> element retain the style values from the last keyframe when the animation ends:

Example

```
div {
  width: 100px;
  height: 100px;
  background: red;
  position: relative;
  animation-name: example;
  animation-duration: 3s;
  animation-fill-mode: forwards;
}
```

Try it Yourself »

The following example lets the <div> element get the style values set by the first keyframe before the animation starts (during the animation-delay period):

Example

```
div {
  width: 100px;
  height: 100px;
  background: red;
  position: relative;
  animation-name: example;
  animation-duration: 3s;
  animation-delay: 2s;
  animation-fill-mode: backwards;
}
```

Try it Yourself »

The following example lets the <div> element get the style values set by the first keyframe before the animation starts, and retain the style values from the last keyframe when the animation ends:

Example

```
div {
  width: 100px;
  height: 100px;
```

CSS Tutorial

- CSS HOME
- CSS Introduction
- CSS Syntax
- CSS Selectors
- CSS How To
- CSS Comments
- CSS Colors
- CSS Backgrounds
- CSS Borders
- CSS Margins
- CSS Padding
- CSS Height/Width
- CSS Box Model
- CSS Outline
- CSS Text
- CSS Fonts
- CSS Icons
- CSS Links
- CSS Lists
- CSS Tables
- CSS Display
- CSS Max-width
- CSS Position
- CSS Z-index
- CSS Overflow
- CSS Float
- CSS Inline-block
- CSS Align
- CSS Combinators
- CSS Pseudo-class
- CSS Pseudo-element
- CSS Opacity
- CSS Navigation Bar
- CSS Dropdowns
- CSS Image Gallery
- CSS Image Sprites
- CSS Attr Selectors
- CSS Forms
- CSS Counters
- CSS Website Layout
- CSS Units
- CSS Specificity
- CSS Important
- CSS Math Functions

CSS Advanced

- CSS Rounded Corners
- CSS Border Images
- CSS Backgrounds
- CSS Colors
- CSS Color Keywords
- CSS Gradients
- CSS Shadows
- CSS Text Effects
- CSS Web Fonts
- CSS 2D Transforms
- CSS 3D Transforms
- CSS Transitions
- CSS Animations
- CSS Tooltips
- CSS Style Images
- CSS Image Reflection
- CSS object-fit
- CSS object-position
- CSS Masking
- CSS Buttons
- CSS Pagination
- CSS Multiple Columns
- CSS User Interface
- CSS Variables
- CSS Box Sizing
- CSS Media Queries
- CSS MQ Examples
- CSS Flexbox

CSS Responsive

- RWD Intro
- RWD Viewport
- RWD Grnd View
- RWD Media Queries
- RWD Images
- RWD Videos
- RWD Frameworks
- RWD Templates

CSS Grid

- Grid Intro
- Grid Container
- Grid Item

CSS SASS

- SASS Tutorial

CSS Examples

- CSS Templates
- CSS Examples
- CSS Editor
- CSS Snippets
- CSS Quiz
- CSS Exercises
- CSS Bootcamp
- CSS Certificate

CSS References

- CSS Reference
- CSS Selectors
- CSS Functions
- CSS Reference Aural
- CSS Web Safe Fonts
- CSS Animatable
- CSS Units
- CSS PX-EM Converter
- CSS Colors
- CSS Color Values
- CSS Default Values
- CSS Browser Support

```
animation-delay: 2s;
animation-fill-mode: both;
}
```

Try it Yourself »

Animation Shorthand Property

The example below uses six of the animation properties:

Example

```
div {
  animation-name: example;
  animation-duration: 5s;
  animation-timing-function: linear;
  animation-delay: 2s;
  animation-iteration-count: infinite;
  animation-direction: alternate;
}
```

Try it Yourself »

The same animation effect as above can be achieved by using the shorthand `animation` property:

Example

```
div {
  animation: example 5s linear 2s infinite alternate;
}
```

Try it Yourself »

Test Yourself With Exercises

Exercise:

Add a 2 second animation for the <div> element, which changes the color from red to blue. Call the animation "example".

```
<style>
div {
  width: 100px;
  height: 100px;
  background-color: red;
  animation-name: _____ ;
  _____ : 2s;
}

@keyframes example {
  from { _____ : red;}
  to { _____ : blue;}
}
</style>

<body>
  <div>This is a div</div>
</body>
```

Submit Answer »

Start the Exercise

CSS Animation Properties

The following table lists the @keyframes rule and all the CSS animation properties:

Property	Description
@keyframes	Specifies the animation code
animation	A shorthand property for setting all the animation properties
animation-delay	Specifies a delay for the start of an animation
animation-direction	Specifies whether an animation should be played forwards, backwards or in alternate cycles
animation-duration	Specifies how long time an animation should take to complete one cycle
animation-fill-mode	Specifies a style for the element when the animation is not playing (before it starts, after it ends, or both)
animation-iteration-count	Specifies the number of times an animation should be played
animation-name	Specifies the name of the @keyframes animation
animation-play-state	Specifies whether the animation is running or paused
animation-timing-function	Specifies the speed curve of the animation

Previous

Log in to track progress

Next

Spaces

Upgrade

Newsletter

Get Certified

Report Error

Top Tutorials

- HTML Tutorial
- CSS Tutorial
- JavaScript Tutorial
- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial

Top References

- HTML Reference
- CSS Reference
- JavaScript Reference
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors

Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples

Get Certified

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- Front End Certificate
- SQL Certificate
- Python Certificate
- PHP Certificate
- jQuery Certificate
- Java Certificate

CSS Tutorial

- CSS HOME
- CSS Introduction
- CSS Syntax
- CSS Selectors
- CSS How To
- CSS Comments
- CSS Colors
- CSS Backgrounds
- CSS Borders
- CSS Margins
- CSS Padding
- CSS Height/Width
- CSS Box Model
- CSS Outline
- CSS Text
- CSS Fonts
- CSS Icons
- CSS Links
- CSS Lists
- CSS Tables
- CSS Display
- CSS Max-width
- CSS Position
- CSS Z-index
- CSS Overflow
- CSS Float
- CSS Inline-block
- CSS Align
- CSS Combinators
- CSS Pseudo-class
- CSS Pseudo-element
- CSS Opacity
- CSS Navigation Bar
- CSS Dropdowns
- CSS Image Gallery
- CSS Image Sprites
- CSS Attr Selectors
- CSS Forms
- CSS Counters
- CSS Website Layout
- CSS Units
- CSS Specificity
- CSS Important
- CSS Math Functions

CSS Advanced

- CSS Rounded Corners
- CSS Border Images
- CSS Backgrounds
- CSS Colors
- CSS Color Keywords
- CSS Gradients
- CSS Shadows
- CSS Text Effects
- CSS Web Fonts
- CSS 2D Transforms
- CSS 3D Transforms
- CSS Transitions
- CSS Animations
- CSS Tooltips
- CSS Style Images
- CSS Image Reflection
- CSS object-fit
- CSS object-position
- CSS Masking
- CSS Buttons
- CSS Pagination
- CSS Multiple Columns
- CSS User Interface
- CSS Variables
- CSS Box Sizing
- CSS Media Queries
- CSS MQ Examples
- CSS Flexbox

CSS Responsive

- RWD Intro
- RWD Viewport
- RWD Grnd View
- RWD Media Queries
- RWD Images
- RWD Videos
- RWD Frameworks
- RWD Templates

CSS Grid

- Grid Intro
- Grid Container
- Grid Item

CSS SASS

- SASS Tutorial

CSS Examples

- CSS Templates
- CSS Examples
- CSS Editor
- CSS Snippets
- CSS Quiz
- CSS Exercises
- CSS Bootcamp
- CSS Certificate

CSS References

- CSS Reference
- CSS Selectors
- CSS Functions
- CSS Reference Aural
- CSS Web Safe Fonts
- CSS Animatable
- CSS Units
- CSS PX-EM Converter
- CSS Colors
- CSS Color Values
- CSS Default Values
- CSS Browser Support

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

