

CSS break-after Property

[Reference](#)

Example

Always insert a page-break after a <footer> element:

```
@media print {  
  footer {  
    break-after: always;  
  }  
}
```

Definition and Usage

The **break-after** property specifies whether or not a page break, column break, or region break should occur after the specified element.

The **break-after** property extends the CSS2 **page-break-after** property.

Using **break-after**, you can tell the browser to break the page, column, or region after the element the **break-after** property is applied to, or avoid the element to be split and span across two pages.

Default value:	auto
-----------------------	------



HTML

CSS

JAVASCRIPT

**Version:** CSS3**JavaScript syntax:** `object.style.breakAfter="always"`

Browser Support

The numbers in the table specify the first browser version that fully supports the property.

Property					
break-after	50.0	10.0	65.0	10.0	37.0

CSS Syntax

```
break-after: auto|all|always|avoid|avoid-column|avoid-page|avoid-region|column|left|page|recto|region|right|verso|initial|inherit;
```

Property Values

Value	Description
auto	Default. Automatic page/column/region break after the element
all	Always insert a page-break right after the principal box
always	Always insert a page-break after the element
avoid	Avoid a page/column/region break after the element
avoid-column	Avoid a column-break after the element
avoid-page	Avoid a page-break after the element
avoid-region	Avoid a region-break after the element



HTML

CSS

JAVASCRIPT



page	Always insert a page-break after the element
recto	Insert one or two page-breaks after the principal box so that the next page is formatted as a recto page
region	Always insert a region-break after the element
right	Insert one or two page-breaks after the element so that the next page is formatted as a right page
verso	Insert one or two page-breaks after the principal box so that the next page is formatted as a verso page
initial	Sets this property to its default value. Read about <i>initial</i>
inherit	Inherits this property from its parent element. Read about <i>inherit</i>

More Examples

Example

Always insert a page-break after element with id "toc" (table of content):

```
@media print {  
  #toc {  
    break-after: always;  
  }  
}
```

Example

Always insert a region-break after elements in a region:

```
.region ul {  
  break-after: region;  
}
```



Menu ▼

✦ Bootcamps

📁 Spaces

Sign Up

Log in



HTML

CSS

JAVASCRIPT



Reference



50% OFF
All Courses and Certificates

Shop now!

From 7th of July 2023 - 1st of August 2023

Does not include
Bootcamps and Subscriptions



COLOR PICKER



Join our Mini CSS Bootcamp



★★★★★

“W3Schools Bootcamp is the best investment that I have ever made. All the material from your catalog is really well explained, and has helped me to gain a great background.”

Student at W3Schools

Read more

- Spaces
- Upgrade
- Newsletter
- Get Certified
- Report Error

Top Tutorials



Menu ▼

✦ Bootcamps

📁 Spaces

Sign Up

Log in



HTML

CSS

JAVASCRIPT



- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- Java Tutorial
- C++ Tutorial
- jQuery Tutorial

Top References

- HTML Reference
- CSS Reference
- JavaScript Reference
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors
- Java Reference
- Angular Reference
- jQuery Reference

Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- Java Examples
- XML Examples
- jQuery Examples

Get Certified

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- Front End Certificate
- SQL Certificate
- Python Certificate
- PHP Certificate
- jQuery Certificate
- Java Certificate
- C++ Certificate
- C# Certificate
- XML Certificate

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

