

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

# Node.js NPM

[< Previous](#)[Next >](#)

## What is NPM?

NPM is a package manager for Node.js packages, or modules if you like.

[www.npmjs.com](https://www.npmjs.com) hosts thousands of free packages to download and use.

The NPM program is installed on your computer when you install Node.js

NPM is already ready to run on your computer!

## What is a Package?

A package in Node.js contains all the files you need for a module.

Modules are JavaScript libraries you can include in your project.

## Download a Package

Downloading a package is very easy.

Open the command line interface and tell NPM to download the package you want.

I want to download a package called "upper-case":

[Tutorials](#) ▼[Exercises](#) ▼[Services](#) ▼[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

Now you have downloaded and installed your first package!

NPM creates a folder named "node\_modules", where the package will be placed. All packages you install in the future will be placed in this folder.

My project now has a folder structure like this:

```
C:\Users\My Name\node_modules\upper-case
```

## Using a Package

Once the package is installed, it is ready to use.

Include the "upper-case" package the same way you include any other module:

```
var uc = require('upper-case');
```

Create a Node.js file that will convert the output "Hello World!" into upper-case letters:

### Example

[Get your own Node.js Server](#)

```
var http = require('http');
var uc = require('upper-case');
http.createServer(function (req, res) {
  res.writeHead(200, {'Content-Type': 'text/html'});
  res.write(uc.toUpperCase("Hello World!"));
  res.end();
}).listen(8080);
```


[Tutorials](#) ▾[Exercises](#) ▾[Services](#) ▾[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

Save the code above in a file called "demo\_uppercase.js", and initiate the file:

Initiate demo\_uppercase:

```
C:\Users\Your Name>node demo_uppercase.js
```

If you have followed the same steps on your computer, you will see the same result as the example: <http://localhost:8080>

[< Previous](#)[Next >](#)

**W3schools Pathfinder**  
**Track your progress - it's free!**

[Sign Up](#) [Log in](#)

**Level up your  
skills with our  
courses!**

*Gain skills, and get certified.*

[Start Today!](#)

COLOR PICKER