

```
[student@workstation ~]$ oc login -u admin -p redhatocp https://api.ocp4.example.com:6443
Login successful.

You have access to 71 projects, the list has been suppressed. You can list all projects with 'oc projects'

Using project "default".
Welcome! See 'oc help' to get started.
[student@workstation ~]$
```

Storage	Network	Network describes the cluster's desired network configuration. It is consumed by the cluster-network-operator. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).
Builds	operator.openshift.io	
Observe	Node	Node holds cluster-wide information about node specific features. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).
Compute	OAuth	OAuth holds cluster-wide information about OAuth. The canonical name is 'cluster'. It is used to configure the integrated OAuth server. This configuration is only honored when the top level Authentication config has type set to...
User Management	OpenShiftAPIServer	OpenShiftAPIServer provides information to configure an operator to manage openshift-apiserver. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).
Administration	OpenShiftControllerManager	OpenShiftControllerManager provides information to configure an operator to manage openshift-controller-manager. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).
Cluster Settings	OperatorHub	OperatorHub is the Schema for the operatorhubs API. It can be used to change the state of the default hub sources for OperatorHub on the cluster from enabled to disabled and vice versa. Compatibility level 1: Stable within a major release for ...
Namespaces	Project	Project holds cluster-wide information about Project. The canonical name is 'cluster'. Compatibility level 1: Stable within a major release for a minimum of 12 months or 3 minor releases (whichever is longer).
ResourceQuotas		
LimitRanges		
CustomResourceDefinitions		

```
[student@workstation ~]$ ldapsearch -D "cn=Directory Manager" -w redhatocp -H ldaps://rhds.ocp4.example.com
# extended LDIF
#
# LDAPv3
# base <> (default) with scope subtree
# filter: (objectclass=*)
# requesting: ALL
#
# example.com
dn: dc=example,dc=com
objectClass: top
objectClass: domain
dc: example
```

```
shadowWarning: 0
userPassword:: e1NTSEF9Wm1sMWd1WjJLajlRM1dKZGlFVnV6aTNEaCs5NzFPeF
5=
memberOf: cn=administrators,ou=people,dc=example,dc=com

# administrators, people, example.com
dn: cn=administrators,ou=people,dc=example,dc=com
objectClass: top
objectClass: groupOfUniqueNames
cn: administrators
uniqueMember: uid=kristendelgado,ou=people,dc=example,dc=com

# search result
search: 2
```

Add Identity Provider: LDAP

Integrate with an LDAP identity provider.

Name *

Red Hat Directory Server

Unique name of the new identity provider. This cannot be changed later.

URL *

ldaps://rhds.ocp4.example.com/dc=example,dc=com?uid

An RFC 2255 URL which specifies the LDAP search parameters to use.

Bind DN

cn=Directory Manager

DN to bind with during the search phase.

Bind password

Identity providers

Identity providers determine how users log into the cluster.

Add ▼

Name	Type	Mapping method
Red Hat Identity Management	LDAP	claim
Red Hat Directory Server	LDAP	claim

```
[student@workstation sync]$ oc create secret generic rhds-secret  
--from-literal bindPassword='redhatocp'  
secret/rhds-secret created
```

```
[student@workstation sync]$ oc create configmap rhds-config --from-  
file rhds-sync.yaml=rhds-sync.yaml,ca.crt=rhds_ca.crt  
configmap/rhds-config created
```

```
[rhssso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh config credentials --  
server https://sso.ocp4.example.com:8080/auth --user admin --pass  
word redhatocp --realm master  
Logging into https://sso.ocp4.example.com:8080/auth as user admin  
of realm master
```

```
[rhssso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh get users -r external  
_providers --fields 'id,username'  
{  
  "id" : "a175e1b7-6210-40f8-aeda-732021142e84",  
  "username" : "abbyquincy"  
, {  
  "id" : "958fde0c-360c-48f8-b5e5-942708fbb36e",  
  "username" : "fricisritcher"  
, {  
  "id" : "64898122-5875-4418-88ac-c9eeeeaa0f409",  
  "username" : "jayalamont"  
}  
]  
[rhssso@sso ~]$
```

```
[rhssso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh get groups -r externa  
_providers --fields 'id,name'  
{  
  "id" : "e92319be-d5df-4a0c-833a-687fd25ca34c",  
  "name" : "contractors"  
, {  
  "id" : "3dcc3053-4ebf-4894-969a-f26d8e2bc22f",  
  "name" : "partners"  
}  
]  
[rhssso@sso ~]$
```

```
[rhsso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh get users/a175e1b7-6210-40f8-aeda-732021142e84/groups -r external_providers
[
  {
    "id" : "e92319be-d5df-4a0c-833a-687fd25ca34c",
    "name" : "contractors",
    "path" : "/contractors"
  }
]
```

```
[rhsso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh get clients -r external_providers -q clientId=ocp_rhsso
[
  {
    "id" : "f57e9ddc-8c60-4b40-8048-ec0120595be2",
    "clientId" : "ocp_rhsso",
    "surrogateAuthRequired" : false,
    "enabled" : true,
    "alwaysDisplayInConsole" : false,
    "clientAuthenticatorType" : "client-secret",
    "redirectUris" : [ "https://oauth-openshift.apps.ocp4.example.com/*" ],
    "webOrigins" : [ "https://oauth-openshift.apps.ocp4.example.com" ],
    "notBefore" : 0,
    "bearerOnly" : false,
```

```
[rhsso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh get clients/f57e9ddc-8c60-4b40-8048-ec0120595be2/installation/providers/keycloak-oidc-keycloak-json -r external_providers > rhsso.json
```

```
[rhsso@sso ~]$ cat rhsso.json
{
  "realm" : "external_providers",
  "auth-server-url" : "https://sso.ocp4.example.com:8080/auth/",
  "ssl-required" : "external",
  "resource" : "ocp_rhsso",
  "credentials" : {
    "secret" : "X4ZTPfDr0b8loq0FArfidhaHq85bHyiy"
  },
  "confidential-port" : 0
}
```

```
confidential-port . .  
[rhssso@sso ~]$ exit  
logout  
Connection to sso.ocp4.example.com closed.  
[student@workstation ~]$
```

```
[student@workstation ~]$ oc login -u admin -p redhatocp https://api.ocp4.example.com:6443  
login successful.  
  
You have access to 71 projects, the list has been suppressed. You  
can list all projects with 'oc projects'  
  
Using project "auth-oidc".  
[student@workstation ~]$
```

```
[rhssso@sso ~]$ /opt/rh-sso-7.6/bin/kcadm.sh get users -r external  
_providers --fields 'id,username'  
[ {  
  "id" : "a175e1b7-6210-40f8-aeda-732021142e84",  
  "username" : "abbyquincy"  
}, {  
  "id" : "958fde0c-360c-48f8-b5e5-942708fbb36e",  
  "username" : "fricisritcher"  
}, {  
  "id" : "64898122-5875-4418-88ac-c9eeaa0f409",  
  "username" : "jayalamont"  
} ]  
[rhssso@sso ~]$
```