Memory rises above Wall



Life Expectancy
62years (2000) → 68years (2016)

Smart Healthcare Market \$57B (2015) → \$169B (2020)


Industry 4.0

Artificial Intelligence /
IoT / Autonomous Car /
Cyber-physical system based
automation


Energy Demands
11Btoe¹(2005) → 17Btoe(2030)

Relationship with IT Technologies

IT technologies are key solutions to solve the big problems of future megatrends




Semiconductor's Position




[✓] Semiconductor takes important role in every IT technologies

Memory is at the core of New Applications




Snowball Effect in Memory Usage




2017 2018 2019 2020

Memory-centric System Evolution


Extreme B/W, performance/power, data processing, cost effective solutions






Challenges on Memory Hierarchy

Transitioning from single tier main Memory architecture to multi-tier near and far Memory architecture



DRAM Capacity Solutions with Advanced Technologies

Full spectrum of capacity coverage from low-end to high-end



Samsung's Data Center Solution

Highest Performance, Largest Capacity



DDR5 512GB RDIMM

Largest Capacity DIMM in the World


512GB RDIMM opens new data center era through breaking the capacity wall


Largest capacity w/3D

512GB

1.5x Bandwidth

4,800Mbps





* 2P Server base (16slot per CPU)


HBM Flashbolt


Highest Performance DRAM in the World

HBM Flashbolt enables Al supercomputing power achieving 460GB/s

Highest Bandwidth 460.8GB/s

Large Capacity w/3D 16GB / 1 cube







System area (HBM 4pcs vs GDDR 12pcs)

HBM Flashbolt vs. GDDR

Optimized design with better performance

HBM Flashbolt offers compactable design combining state-of-the-art TSV technology






PM9A3 PCIe Gen 4 SSD

Tremendous Performance in Storage System

PM9A3 delivers up to 6,950 MB/s in sequential read speed with form factor flexibility










SZ1735a Z-SSD


Ultra Low Latency SSD in for Data Centers

SZ1735a enables fast system responsiveness with <100 us latency



Product Name	SZ1735a
NAND	V5 SLC NAND
Controller	Samsung Eagle Controller
Capacity (OP 28%)	up to 6.4TB
Interface	PCle Gen4 x4 NVMe
Form Factor	2.5" U.2
DWPD*	30 @3Month, 60 @1Month





Legal Disclaimer

This presentation is intended to provide information concerning SSD and memory industry. We do our best to make sure that information presented is accurate and fully up-to-date. However, the presentation may be subject to technical inaccuracies, information that is not up-to-date or typographical errors. As a consequence, Samsung does not in any way guarantee the accuracy or completeness of information provided on this presentation.

The information in this presentation or accompanying oral statements may include forward-looking statements. These forward-looking statements include all matters that are not historical facts, statements regarding the Samsung Electronics' intentions, beliefs or current expectations concerning, among other things, market prospects, growth, strategies, and the industry in which Samsung operates. By their nature, forward-looking statements involve risks and uncertainties, because they relate to events and depend on circumstances that may or may not occur in the future. Samsung cautions you that forward looking statements are not guarantees of future performance and that the actual developments of Samsung, the market, or industry in which Samsung operates may differ materially from those made or suggested by the forward-looking statements contained in this presentation or in the accompanying oral statements. In addition, even if the information contained herein or the oral statements are shown to be accurate, those developments may not be indicative developments in future periods.

SAMSUNG