# M&R Estimate Saga (v1.36)


- Introduction
- · Process Flow
- Message Set
  - Common elements in both messages
    - Sample preview
    - Definition
      - Elements
      - Sub-elements
  - MRESTIMATE message
    - Sample preview
    - Definition
      - Sub-elements
  - AUTHORIZE return message
    - Sample Preview
    - Definition
      - Sub-elements


## Introduction

The M&R Estimate Saga message is initially sent by the M&R workshop to the lessee or lessor. The lessee or lessor can then enrich the file with authorization information and return it to the M&R workshop.

1 Please note that the data structure allows for custom code sets to be used (classic tankcontainer repair/damage/location codes, boxcontainer ISO codes, customer-specific codes, etc.)

### **Process Flow**





# Message Set

The message has 2 variants of roughly the same message:

- M&R Estimate message (MRESTIMATE)
- M&R Estimate Authorization return message (AUTHORIZE)

### Common elements in both messages

### Sample preview

```
9 <Version>1.1</Version>
10 <CurrencyISO>EUR</CurrencyISO>
11 <ConversationId />
12 </Header>
13
14 M&R ESTIMATE OR AUTHORIZE ELEMENTS WILL COME HERE
15
16 </DepotEstimate>
```

#### **Definition**

#### **Elements**

| Table                                   | Explanation                                   |  |  |
|---|---|--|--|
| <depotestimate></depotestimate>         | The entire message is in this tag             |  |  |
| <header></header>                       | Exactly ONE header record is to be present    |  |  |
| <yardorder></yardorder>                 | Currently there is only ONE suborder per file |  |  |
| <equipment></equipment>                 | Describes equipment information               |  |  |
| <mrestimate></mrestimate>               | Currently there is only ONE suborder per file |  |  |
| <mrestimateremarks></mrestimateremarks> | Remark group                                  |  |  |
| <mrestimateremark></mrestimateremark>   | Remarks                                       |  |  |
| <mrestimatelines></mrestimatelines>     | M&R repair lines group                        |  |  |
| <mrestimateline></mrestimateline>       | M&R repair line                               |  |  |
| <codes></codes>                         | M&R codes group                               |  |  |
| <code></code>                           | M&R code                                      |  |  |

#### **Sub-elements**

| <header></header>                 | Datatype  | Require<br>d | Explanation   |  |
|-----------------------------------|-----------|--------------|---|--|
| <guid></guid>                     | xs:string | Reserved     | GUID  |  |
| <senderid></senderid>             | xs:string | Required     | Agreed between parties  |  |
| <receiverid></receiverid>         | xs:string | Required     | Agreed between parties  |  |
| <datesent></datesent>             |           | Required     | Includes timezone   |  |
| <type></type>                     | xs:string | Required     | M&R workshop sends message to Lessee/Lessor, value=MRESTIMATE     Lessee/Lessor returns authorization to the M&R workshop, value=AUTHORIZE                          |  |
| <version></version>               | xs:string | Required     | Documentation version for this file (see this article header for the version number associated with this syntax: 19.1)  |  |
| <currencyiso></currencyiso>       | xs:string | Required     | ISO of currency for all prices in this message  |  |
| <conversationid></conversationid> | xs:string | Reserved     | This ID is added by the the SYNDA hub to provide a history of the messageflow (saga's).  Sending and receiving parties should not alter the contents of this field. |  |

## MRESTIMATE message

#### Sample preview

```
8
        <Type>MREstimate</Type>
 9
        <Version>19.1</Version>
10
        <CurrencyIS0>EUR</CurrencyIS0>
11
        <ConversationId />
12
      </Header>
13
      <YardOrder>
14
       <Id>956231</Id>
15
        <SupplierReference>NLRD-20230101.005/SupplierReference>
16
        <CustomerReference>E223344.55</CustomerReference>
        <DateIn>2019-06-03T16:30:01.3502087/DateIn>
17
18
        <Equipment>
19
          <EquipmentNumber>ABCD-123456-0</EquipmentNumber>
20
          <EquipmentType>20T0, TANK CONTAINER</EquipmentType>
          <EquipmentTypeISO>20TO</EquipmentTypeISO>
21
22
          <Lessee>LesseeName</Lessee>
23
          <| essor>| essor</| essor>
24
          <Manufacturer>Manufacturer</Manufacturer>
25
          <LastTestType>H</LastTestType>
26
          <LastTestDate>2017-01-03T00:00:00
27
          <CSCDate>2018-04-07T00:00:00</CSCDate>
28
          <Capacity>593873</Capacity>
29
          <BuildingYear>2011</BuildingYear>
30
        </Equipment>
        <MREstimate>
31
32
          <Id>123456</Id>
33
          <SupplierReference>NLRD-20230101.005.R3/SupplierReference>
34
          <DateCreated>2019-06-03T16:30:01.3522034+02:00/DateCreated>
35
          <Version>V1</Version>
          <CustomerReference>12345</CustomerReference>
36
37
          <Description>This is a description/Description>
          <DateInitiallySent>2019-06-03T16:30:01.3522034+02:00/DateInitiallySent>
38
39
          <DateAutorizedLessor>
40
          <DateAuthorizationAcceptedByRepairWorkshop></DateAuthorizationAcceptedByRepairWorkshop>
41
          <DateCancelledLessor>
42
          <MREstimateRemark>
43
            <Guid>1358ce0c-2a85-46dc-bcc4-6f622f19b78c</Guid>
44
           <Date>2019-06-03T16:30:01.3541985
45
           <Author>Jennifer</Author>
46
            <Remark>This is a remark/Remark>
47
          </MREstimateRemark>
48
          <MREstimateRemark>
            <Guid>9119f1ad-e9f5-439d-8028-0da0098b4ca3</Guid>
49
50
           <Date>2019-06-03T16:30:01.3551956
51
           <Author>Jennifer</Author>
            <Remark>And another remark/Remark>
52
53
          </MREstimateRemark>
54
          <MREstimateLine>
55
           <Id>1</Id>
56
           <OriginID>800</OriginID>
57
           <Action>true</Action>
58
            <ThirdParty>false</ThirdParty>
            <Description>Replace valves/Description>
59
            <Quantity>1</Quantity>
60
61
            <LaborTariff>30.1/LaborTariff>
62
            <LaborHours>4</LaborHours>
63
            <LaborCost>120</LaborCost>
            <MaterialCost>250.4</MaterialCost>
64
65
            <LumpSum>250.12</LumpSum>
```

```
66
           <Cat>BTM</Cat>
           <Category>Bottom</Category>
67
68
69
             <KindOfCode>ISOLOC</KindOfCode>
70
             <Value>R2AN</Value>
           </Codes>
71
72
           <Codes>
73
            <KindOfCode>LOC</KindOfCode>
            <Value>BTM</Value>
74
75
           </Codes>
76
           <Codes>
77
             <KindOfCode>MAT</KindOfCode>
78
            <Value>IRON</Value>
79
           </Codes>
80
         </MREstimateLine>
81
      </MREstimate>
82
    </Yard0rder>
83 </DepotEstimate>
```

### **Definition**

#### **Sub-elements**

| <yardorder></yardorder>                 | Datatyp<br>e    | Required                   | Explanation  |
|---|-----------------|----------------------------|--|
| <ld>&lt;</ld>                           | xs:long         | Reserved                   | Unique order ID  |
| <customerreference></customerreference> | xs:string       |                            |  |
| <datein></datein>                       | xs:dateti<br>me | Required                   | Returns the local depot yard time when equipment arrived on the depot yard |
| <equipment></equipment>                 | complex         | Always 1, no more, no less |  |
| <mrestimate></mrestimate>               | complex         | Always 1, no more, no less |  |

| <equipment></equipment>                 | Datatyp<br>e    | Required | Explanation   |
|---|-----------------|----------|---|
| <equipmentnumber></equipmentnumber>     | xs:string       | Required |   |
| <supplierreference></supplierreference> | xs:string       |          | Unique Yard Order reference provided by the depot       |
| <equipmenttype></equipmenttype>         | xs:string       | Required | Equipment type from a depot perspective (example: 20TC) |
| <equipmenttypeiso></equipmenttypeiso>   | xs:string       |          | Equipment type from an ISO standpoint                   |
| <lessee></lessee>                       | xs:string       | Required |   |
| <lessor></lessor>                       | xs:string       | Required |   |
| <manufacturer></manufacturer>           | xs:string       |          |   |
| <lasttesttype></lasttesttype>           | xs:string       |          | • A=  |
|   |                 |          | • H = Hydraulic   |
| <lasttestdate></lasttestdate>           | xs:dateti<br>me |          |   |
| <cscdate></cscdate>                     | xs:dateti<br>me |          |   |
| <capacity></capacity>                   | xs:int          |          |   |
| <buildingyear></buildingyear>           | xs:int          |          | 4 digit year number (for example: 1999)                 |

| <mrestimate></mrestimate> | Datatyp<br>e | Required | Explanation     |
|---------------------------|--------------|----------|-----------------|
| <ld>&lt;</ld>             | xs:long      | Reserved | Unique order ID |

| <supplierreference></supplierreference>  | xs:string       |          | Unique Repair Order reference provided by the depot  |
|--|-----------------|----------|--|
| <datecreated></datecreated>  | xs:dateti<br>me | Required |  |
| <version></version>  | xs:string       |          | M&R workshops assign a version to an estimate, which can only be updated BY the M&R workshop. This is sometimes done when the estimate undergoes massive changes.  Customers that use this message to reply to an estimate should use the same version number here as in the file they received. In this way the authorizations, remarks and price change suggestions that the customer sends back to the M&R workshop can be associated with the proper estimate version. |
| <customerreference></customerreference>  | xs:string       |          | Authorization reference of lessor/lessee   |
| <description></description>  | xs:string       |          |  |
| <dateinitiallysent></dateinitiallysent>  | xs:dateti<br>me | Required |  |
| <dateauthorizedlessor< td=""><td>xs:dateti<br/>me</td><td></td><td></td></dateauthorizedlessor<> | xs:dateti<br>me |          |  |
| <dateauthorizationacce<br>ptedByRepairWorkshop<br/>&gt;</dateauthorizationacce<br>               | xs:dateti<br>me |          |  |
| <datecancelledlessor></datecancelledlessor>  | xs:dateti<br>me |          | Date cancelled always takes precedent over DateAuthorizedLessor  |
| <mrestimateremark></mrestimateremark>  | complex         |          |  |
|  |                 |          |  |

| <mrestimaterem ark=""></mrestimaterem> | Datatype    | Required | Explanation |
|--|-------------|----------|-------------|
| <guid></guid>                          | xs:string   | Required | GUID        |
| <date></date>                          | xs:datetime | Required |             |
| <author></author>                      | xs:string   | Required |             |
| <remark></remark>                      | xs:string   | Required |             |

| <mrestimateline></mrestimateline> | Datatype   | Required | Explanation   |
|-----------------------------------|------------|----------|---|
| <ld></ld>                         | xs:long    | Reserved | Unique line ID  |
| <originid></originid>             | xs:long    |          | Depot repair workshops have catalogs of standard repair line actions. This field is the "catalog id".  Lessors may want to know better understand the catalog of the depot repair workshops for better matching in their big data. However, we would recommend to rather use the repair line Description field and do a text-based comparison instead, since the descriptions may sometimes be altered to provide more detail by the depot repair workshop. |
| <action></action>                 | xs:boolean | Required | Should the M&R workshop perform this action according to the lessee/lessor?   |
| <thirdparty></thirdparty>         | xs:boolean | Required | If a line is for a Third Party then all line amounts will show as 0   |
| <description></description>       | xs:string  |          |   |
| <quantity></quantity>             | xs:integer | Required | 0 is acceptable   |
| <labortariff></labortariff>       | xs:decimal | Required | 0 is acceptable     This field is for reference only.   |
| <laborhours></laborhours>         | xs:decimal | Required | 0 is acceptable     Quantity applies  |
| <laborcost></laborcost>           | xs:decimal | Required | This field is the definitive rounded calculation of (LaborTariff*LaborHours)  This field is for reference only, it is only the result of calculation.  Quantity applies   |
| <materialcost></materialcost>     | xs:decimal | Required | 0 is acceptable     Quantity applies  |
| <lumpsum></lumpsum>               | xs:decimal |          | Lumpsum overrides all labor & material costs     0 means that the price is labor & material, anything non 0 would mean the line is charged as lumpsum     Quantity applies  |
| <cat></cat>                       | xs:string  |          | M&R workshop internal category code which is sometimes shared with lessor/lessee (for example: TESTING, RE-WORK, etc.)  Abbreviated category (aka. category code)   |
| <category></category>             | xs:string  |          |   |

| <codes></codes> | complex   | Please note that this data structure allows for custom code sets to be used (classic tankcontainer repair/damage/location codes, boxcontainer ISO codes, customer-specific codes, etc.) |
|-----------------|-----------|---|
| <memo></memo>   | xs:string | Lessor/lessee information that can be sent back   |

| <codes></codes>           | Datatype  | Required | Explanation   |
|---------------------------|-----------|----------|---|
| <kindofcode></kindofcode> | xs:string | Required | Please note that this data structure allows for custom code sets to be used (classic tankcontainer repair/damage/location codes, boxcontainer ISO codes, customer-specific codes, etc.) |
| <value></value>           | xs:string | Required |   |

### AUTHORIZE return message

#### **Sample Preview**

```
1 <?xml version="1.0" standalone="yes"?>
 2 <DepotEstimate xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns="">
 3
     <Header>
       <Guid>d1355cc8-dc66-4969-ba07-49338febc794</Guid>
 4
 5
       <SenderId>LESSOR</SenderId>
 6
       <ReceiverId>DEPOT</ReceiverId>
 7
       <DateSent>2019-07-03T09:30:01.3492113+02:00/DateSent>
 8
      <Type>AUTHORIZE</Type>
 9
       <Version>19.1</Version>
10
       <CurrencyIS0>EUR</CurrencyIS0>
11
       <ConversationId />
12
     </Header>
     <YardOrder>
13
14
      <Id>956231</Id>
15
      <MREstimate>
16
         <Id>123456</Id>
17
         <Version>V1</Version>
18
         <CustomerReference>12345</CustomerReference>
19
         <DateAutorizedLessor>2019-05-31T16:30:01.3522034+02:00/DateAutorizedLessor>
20
         <DateAuthorizationAcceptedByRepairWorkshop></DateAuthorizationAcceptedByRepairWorkshop>
21
         <DateCancelledLessor>
22
         <MREstimateRemark>
23
           <Guid>1358ce0c-2a85-46dc-bcc4-6f622f19b78c</Guid>
24
           <Date>2019-06-03T16:30:01.3541985
25
           <Author>Joop</Author>
26
           <Remark>We turned off one line
27
         </MREstimateRemark>
28
         <MREstimateLine>
           <Id>1</Id>
29
30
           <Action>false</Action>
31
           <LaborTariff>30.1/LaborTariff>
32
           <LaborHours>4</LaborHours>
           <MaterialCost>250.4</MaterialCost>
33
34
           <LumpSum>250.12</LumpSum>
35
         </MREstimateLine>
36
       </MREstimate>
37
     </YardOrder>
38 </DepotEstimate>
```

#### **Definition**

| <yardorder></yardorder>   | Datatype | Required | Explanation     |
|---------------------------|----------|----------|-----------------|
| <ld></ld>                 | xs:long  | Yes      | Unique order ID |
| <mrestimate></mrestimate> | complex  | Yes      |                 |

| <mrestimate></mrestimate>   | Datatype    | Required                       | Explanation  |
|---|-------------|--------------------------------|--|
| <ld></ld>   | xs:long     | Yes                            | Unique order ID  |
| <version></version>   | xs:string   | Yes                            | M&R workshops assign a version to an estimate, which can only be updated BY the M&R workshop. This is sometimes done when the estimate undergoes massive changes.  Customers that use this message to reply to an estimate should use the same version number here as in the file they received. In this way the authorizations, remarks and price change suggestions that the customer sends back to the M&R workshop can be associated with the proper estimate version. |
| <customerreference></customerreference>   | xs:string   | Often used, max. 64 characters | Authorization reference of lessor/lessee   |
| <dateauthorizedlessor></dateauthorizedlessor>                                       | xs:datetime | Often used                     |  |
| <dateauthorizationacceptedby<br>RepairWorkshop&gt;</dateauthorizationacceptedby<br> | xs:datetime | No                             |  |
| <datecancelledlessor></datecancelledlessor>   | xs:datetime |                                | Date cancelled always takes precedent over DateAuthorizedLessor  |
| <mrestimateremark></mrestimateremark>   | complex     |                                |  |
| <mrestimateline></mrestimateline>   | complex     |                                |  |

| <mrestimateremark></mrestimateremark> | Datatype    | Required | Explanation |
|---------------------------------------|-------------|----------|-------------|
| <guid></guid>                         | xs:string   | Required | GUID        |
| <date></date>                         | xs:datetime | Required |             |
| <author></author>                     | xs:string   | Required |             |
| <remark></remark>                     | xs:string   | Required |             |

| <mrestimateline></mrestimateline> | Datatype   | Required      | Explanation   |
|-----------------------------------|------------|---------------|---|
| <ld></ld>                         | xs:long    | Reserved      | Unique line ID  |
| <action></action>                 | xs:boolean | Required      | Should the M&R workshop perform this action according to the lessee/lessor?   |
| <laborhours></laborhours>         | xs:decimal | Yes           | <ul> <li>0 is acceptable</li> <li>Quantity applies</li> <li>Changeable: If the estimate is returned and this field was changed, receiver can assume that this is a counter offer.</li> </ul>  |
| <materialcost></materialcost>     | xs:decimal | Yes           | <ul> <li>0 is acceptable</li> <li>Quantity applies</li> <li>Changeable: If the estimate is returned and this field was changed, receiver can assume that this is a counter offer.</li> </ul>  |
| <lumpsum></lumpsum>               | xs:decimal | Yes           | <ul> <li>Lumpsum overrides all labor &amp; material costs</li> <li>0 means that the price is labor &amp; material, anything non 0 would mean the line is charged as lumpsum</li> <li>Quantity applies</li> <li>Changeable: If the estimate is returned and this field was changed, receiver can assume that this is a counter offer.</li> </ul> |
| <memo></memo>                     | xs:string  | Commonly used | Lessor/lessee information that can be sent back   |