

# OpenTURNS release highlights : the new Gaussian Process API

S.Haddad (Airbus Central R&T)

User Day #18, June 13th 2025, EDF Lab

**AIRBUS**



- 1 Kriging implementation : current limitations
- 2 New API

# Kriging implementation: basic example

```
import openturns as ot
...
# Call kriging
kriging_algo = ot.KrigingAlgorithm(X_train, Y_train, covarianceModel, basis)
kriging_algo.run()
# Get the result
kriging_result = kriging_algo.getResult()
# Post-processing
func = kriging_result.getMetaModel()
# Conditional variance
cond_var = kriging_result.getConditionalVariance(new_X)
```

First remarks:

- KrigingAlgorithm handles the E2E computation,
- Post-processing methods handled by result structures;

## Kriging implementation: change some parameters

```
import opturns as ot

# Set optimizer
ot.ResourceMap.SetAsString(
    "GeneralLinearModelAlgorithm-DefaultOptimizationAlgorithm", "Cobyla")
ot.ResourceMap.SetAsScalar(
    "GeneralLinearModelAlgorithm-DefaultOptimizationLowerBound", 0)
ot.ResourceMap.SetAsScalar(
    "GeneralLinearModelAlgorithm-DefaultOptimizationUpperBound", 2)
ot.ResourceMap.SetAsString(
    "KrigingAlgorithm-LinearAlgebra", "LAPACK")
#ot.ResourceMap.SetAsString(
#    "GeneralLinearModelAlgorithm-LinearAlgebra", "LAPACK")

...
# Call kriging
kriging_algo = ot.KrigingAlgorithm(X_train, Y_train, covarianceModel, basis)
kriging_algo.run()
# Get the result
kriging_result = kriging_algo.getResult()
# Post-processing
func = kriging_result.getMetaModel()
# Conditional variance
cond_var = kriging_result.getConditionalVariance(new_X)
```

KrigingAlgorithm is used to fit a Kriging model (aka Gaussian Process Regression), relying on a 2-steps procedure :

- GeneralLinearModelAlgorithm: allowing the parametric estimation of a Gaussian Process,
- KrigingAlgorithm: conditioning the Gaussian Process;

→ KrigingAlgorithm.run calibrate a Gaussian Process

- ResourceMap keys duplicate,
- Sequential Kriging hard to handle (example for EGO);

- Trigger explicitly the parameters fitting,
- Perform the conditioning,
- Enrich the API with missing features (such as "known trend"),
- Build as much post-processing functions as needed;

# New API for Gaussian Process Regression

The new API defines the following classes (in the experimental submodule):

- GaussianProcessFitter: Fitting the Gaussian Process (explicitly),
- GaussianProcessFitterResult: result class of a parametric Gaussian Process fitting,
- GaussianProcessRegression: conditioning the Gaussian Process,
- GaussianProcessRegressionResult: result class of a conditional Gaussian Process fitting,
- GaussianProcessRandomVector: generate Gaussian Process realizations,
- GaussianProcessConditionalCovariance: Post-processing Gaussian Process;

```
# Call fitter
fitter_algo = otexp.GaussianProcessFitter(X_train, Y_train, covarianceModel, basis)
fitter_algo.run()
fitter_result = fitter_algo.getResult()
# Conditioning part using the fit result
gpr_algo = otexp.GaussianProcessRegression(fitter_result)
gpr_algo.run()
gpr_result = gpr_algo.getResult()
gpr_metamodel = gpr_result.getMetaModel()
```

## New feature : known trend

```
# trend function
trend_function = ot.SymbolicFunction("x", "-3.1710410094572903")
# Covariance
scale = [4.51669]
amplitude = [8.648]
covariance_opt = ot.MaternModel(scale, amplitude, 1.5)
# Conditioning part using the data
gpr_algo_noopt = otexp.GaussianProcessRegression(x_train, y_train, covariance_opt, t
gpr_algo_noopt.run()
gpr_result_no_opt = gpr_algo_noopt.getResult()
gpr_nopt_Metamodel = gpr_result_no_opt.getMetaModel()
```




## Post-processing : conditional covariance

```
# Call fitter
fitter_algo = otexp.GaussianProcessFitter(X_train, Y_train, covarianceModel, basis)
fitter_algo.run()
fitter_result = fitter_algo.getResult()
# Conditioning part using the fit result
gpr_algo = otexp.GaussianProcessRegression(fitter_result)
gpr_algo.run()
gpr_result = gpr_algo.getResult()
# Conditional covariance
gpcc = otexp.GaussianProcessConditionalCovariance(gpr_result)
cond_var = gpcc.getConditionalVariance(new_X)
```

# Kriging vs Gaussian Process

Reach out [here](#) to learn more !



# OpenTURNS

An Open source initiative for the Treatment of Uncertainties, Risks'N Statistics

OpenTURNS 1.25dev documentation » Contents » Examples » Getting started » Gaussian Process Regression vs KrigingAlgorithm

Home Get it Doc Forum Modules Code Bugs

previous | next | index

## Gaussian Process Regression vs KrigingAlgorithm

The goal of this example is to highlight the main changes between the old API involving `KrigingAlgorithm` and the new one.

It assumes a basic knowledge of Gaussian Process Regression. For that purpose, we create a Gaussian Process Regression surrogate model for a function which has scalar real inputs and outputs. We select a very simple example.

### Introduction

We consider the sine function:

$$y = x \sin(x)$$

for any  $x \in [0, 12]$ .

We want to create a surrogate of this function. This is why we create a sample of  $n$  observations of the function:

$$y_i = x_i \sin(x_i)$$

We are going to consider a Gaussian Process Regression with:

- a constant trend,
- a Matern covariance model.

### Table of Contents

- Gaussian Process Regression vs KrigingAlgorithm
  - Introduction
  - Activating nugget factor
  - Compute confidence bounds
  - Gaussian Process Regression with fixed trend
  - Gaussian Process Regression with heteroscedastic noise
    - Summary of features

### Previous topic

[Getting started](#)

### Next topic

[Data analysis](#)

### This Page

[Show Source](#)

# Summary

Feature	OpenTURNS 1.24	New API
Optimisation	TNC	Cobyla
Heteroscedasticity	KrigingAlgorithm.setNoise	Not implemented
Nugget factor est	CovModel	CovModel
Known trend	Not implemented	Implemented
Conditional covariance	KrigingResult	GPCC*

\*GPCC: GaussianProcessConditionalCovariance

List of classes supporting the new API:

- `EfficientGlobalOptimization`: rely on `GaussianProcessRegressionResult`,
- `ConditionedGaussianProcess`: rely on `GaussianProcessRegressionResult`

Remark : these classes are now part of the experimental submodule!

In parallel, all examples involving Kriging are progressively moving to the new API !

## 2025-2026 work

- Finalize migration of the examples to the new API,
- Algebra of covariance models,
- Analytical gradient of covariance models,
- Integration into the existing algorithms,
- Cross-validation methods,
- Sequential algorithms,

# END

Thank you for your attention!  
Any questions?

