

OtFMI, an OpenTURNS module for uncertainties analysis with 0D/1D system models

Michaël Baudin ¹ Audrey Jardin ¹ Mathias Bouquerel ¹
Anne-Laure Popelin ¹ Audrey Jardin ¹
Julien Schueller ² Sylvain Girard ²

¹EDF R&D. 6, quai Watier, 78401, Chatou Cedex - France, michael.baudin@edf.fr

²Phimeca Engineering. 18/20 boulevard de Reuilly, 75012 Paris - France,
girard@phimeca.com

October 19th 2017

Industrial issue

- ▶ EDF uses 0D/1D system models programmed in Modelica as decision support for the conception and operation of its industrial assets.
- ▶ How to apply OpenTURNS' panoply of methods to these models?

"Regular" models vs 0D/1D system models

"Regular"
modelling



"Packing"

$$\begin{cases} \dot{\mathbf{x}}(t) = f(\mathbf{x}(t), \mathbf{u}(t), t) \\ \mathbf{y}(t) = g(\mathbf{x}(t), \mathbf{u}(t), t) \end{cases}$$


Equation formulation



Solver
programming

"Regular" models vs 0D/1D system models


"Regular"
modelling



0D/1D
system modelling



"Packing"




Equation formulation

$$\begin{cases} \dot{\mathbf{x}}(t) = f(\mathbf{x}(t), \mathbf{u}(t), t) \\ \mathbf{y}(t) = g(\mathbf{x}(t), \mathbf{u}(t), t) \end{cases}$$

$$\begin{cases} \dot{\mathbf{x}}(t) = f(\mathbf{x}(t), \mathbf{u}(t), t) \\ \mathbf{y}(t) = g(\mathbf{x}(t), \mathbf{u}(t), t) \end{cases}$$



Solver
programming



“Regular” models vs 0D/1D system models

“Regular”
modelling



0D/1D
system modelling

Long (minute → hour)

CPU time

Short (second → minute)

2D, 3D

Dimensions

0D, 1D

Discrete versioning

Development rate

Continuous mutation

Numerical analyst, physicist

Actors

Design, process, operation...
engineer

CFD, finite elements,
C++, FORTRAN...

Tools

Modelica, Simulink...

Modelica programming language

- ▶ Modelica is an open language for programming models based on **differential algebraic systems of equations**



- ▶ Equations are written in almost **natural language**, and solved by a multipurpose third party tool.
- ▶ It is object-oriented: available **module libraries** cover most applications
 - ▶ Complex models can be achieved simply by combining this modules using a graphical interface!

Modelica tools

- ▶ Main tools :

- ▶ Dymola (Dassault Systèmes, proprietary)
- ▶ OpenModelica (Open Source Modelica Consortium, open source)

- ▶ Functions

- ▶ Flatten equation systems
- ▶ Compile to machine code after including a solver
- ▶ Development environment
- ▶ Model graphical interface
- ▶ Basic post-processing...

OpenModelica, model graphical view

The screenshot displays the OpenModelica software interface. The top menu bar includes File, Edit, View, Simulation, FMI, Export, Debug, Git, Tools, and Help. Below the menu is a toolbar with various icons for file operations, simulation, and debugging.

The left sidebar shows the "Libraries Browser" with a search filter. The "Libraries" list includes OpenModelica, Modelica, and various sub-libraries like UsersGuide, Blocks, StateGraph, Electrical, Magnetic, Mechanics, Fluid, Media, Thermal, and Fluid...Flow. The "Fluid...Flow" library is expanded, showing sub-libraries like Use...ide and Examples.


The main workspace displays a graphical model diagram titled "PumpAndValve" and "IndirectCooling". The diagram shows a complex system with multiple components, including pumps, valves, pipes, and heat exchangers, connected by fluid flow lines. The components are labeled with names like "ambient", "outerPipe", "innerPipe", "pipe1", "heatFlow", and "pressure".

At the bottom, the "Messages Browser" shows a scripting error message: "[I] 17:09:32 Scripting Error sh: 1: impact: Permission denied".

The bottom status bar indicates the current state: Welcome, Modeling, Plotting, and Debugging.

Piloting models

- ▶ Most OpenTURNS methods apply to functional **black boxes**
 - ▶ Uncertainty propagation and reliability analysis
 - ▶ Sensitivity analysis
 - ▶ Emulation
 - ▶ Parameter estimation




- ▶ We need efficient **input-output data interfaces**,
a.k.a. *wrappers* in OpenTURNS jargon.

Functional mock-up interface (FMI)

- ▶ FMI is a standard for input–output data interface for numerical model.



- ▶ A **functional mock-up unit (FMU)** is a black box following the standard.




OtFMI: integrating FMI support into OpenTURNS

- ▶ The new open source module OtFMI allows transparent use of FMU with OpenTURNS methods.
- ▶ It provides high level classes derived from `ot.PythonFunction`: running an FMU instead of a Python function only requires to **change a single code line!**

```
import otfmi
otfmi.FMUFunction("path/to/fmu",
                  inputs_fmu=["x_1", "x_2", "x_3"],
                  outputs_fmu=["y"])
```

Implementation overview



OtFMI graphical interface

Motivations

- ▶ Provide access to OpenTURNS' methods for Modelica users unfamiliar with Python
- ▶ Considerably ease simple studies

Issues

- ▶ Modelica models often define **hundreds or thousands of variables**

OtFMI graphical interface, FMU overview

OTGui - [Modèle physique FMI]

Fichier Vue

Etudes

- OTStudy_0
 - Modèles physiques**
 - PhysicalModel_0
 - Définition**
 - Modèle probabiliste

Propriétés Variables Différentiation

FMU file

| | |
|---------------------|--|
| Identifiant | bil100partiel_GV_0Unit2_0wlnit |
| Version FMI | 2.0 |
| Outil | Dymola Version 2017 (32-bit), 2016-04-12 (using dassl with tolerance 0.0001) |
| Plateforme | default |
| Auteur | |
| Version | |
| Copyright | |
| Date/Heure | 2016-07-12T11:49:23Z |
| GUID | {44d61dd0-e7a1-4166-ada8-ecdc48a166b7} |
| Nombre de variables | 2451 |
| Causalité | paramètre : 119, entrée : 0, sortie : 0, locale : 2332 |

OtFMI graphical interface, picking inputs and outputs

OTGui - [Modèle physique FMI]

Fichier Vue

Etudes

- OTStudy_0
 - Modèles physiques
 - PhysicalModel_0
 - Définition
 - Modèle probabiliste

Propriétés Variables Différentiation

Filtres

Nom ☐ Casse Variabilité Causalité E/S Effacer

Variables

- rho
- GV1_CFD1
- GV2_CFD1
- GV3_CFD1
- GV4_CFD1
- VVP_1A_VAPF
- VVP_2A_VAPF
- VVP_3A_VAPF
- VVP_4A_VAPF
- DB_GV1_CFD1

| Nom | Description | Variabilité | Causalité | E/S | Valeur |
|-----------|-------------|-------------|-----------|--------|-------------|
| QARE0 | | Fixe | Paramètre | Entrée | 2126,272222 |
| PARE0 | | Fixe | Paramètre | Entrée | 7032780 |
| TARE0 | | Fixe | Paramètre | Entrée | 499,9305 |
| PGCT0 | | Fixe | Paramètre | Entrée | 6540000 |
| QGS0 | | Fixe | Paramètre | Entrée | 183,4088889 |
| OGRE0 | | Fixe | Paramètre | Entrée | 1922,635556 |
| BIL100... | | Fixe | Locale | Sortie | 3788204475 |

Variables sélectionnées : entrée : 6, sortie : 1

Evaluer

Perspectives

- ▶ Most 0D/1D system model are dynamical.
We need methods for sensitivity analysis and emulation of model with **time series inputs or outputs**.
- ▶ EDF is interested into **data assimilation** with its Modelica models.
- ▶ What are the opportunities of **extending the Modelica language** to support stochastic description of variables?

Thank you for your attention.