

# Overview of OpenTURNS, its new features and its graphical user interface

M. Baudin<sup>1</sup>   T. Delage<sup>1</sup>   A. Dutfoy<sup>1</sup>   A. Geay<sup>1</sup>  
O. Mircescu<sup>1</sup>   A. Ladier<sup>2</sup>   J. Schueller<sup>2</sup>   T. Yalamas<sup>2</sup>

<sup>1</sup>EDF R&D. 6, quai Watier, 78401, Chatou Cedex - France, michael.baudin@edf.fr

<sup>2</sup>Phimeca Engineering. 18/20 boulevard de Reuilly, 75012 Paris - France,  
yalamas@phimeca.com

27 March 2020, SIAM UQ 2020, Munich, Germany



# Contents

Introduction

New sequential algorithms

PERSALYS, the graphical user interface

What's next ?

OpenTURNS: [www.openturns.org](http://www.openturns.org)

# OpenTURNS

An Open source initiative for the Treatment of Uncertainties, Risks'N Statistics

- ▶ Multivariate probabilistic modeling including dependence
- ▶ Numerical tools dedicated to the treatment of uncertainties
- ▶ Generic coupling to any type of physical model
- ▶ Open source, LGPL licensed, C++/Python library

# OpenTURNS: [www.openturns.org](http://www.openturns.org)



**AIRBUS**



- ▶ Linux, Windows
- ▶ First release : 2007
- ▶ 5 full time developers
- ▶ Users  $\approx$  1000, mainly in France (370 000 Total Conda downloads)
- ▶ Project size (2018) : 720 classes, more than 6000 services

# OpenTURNS: content

## Data analysis

**Visual analysis:** QQ-Plot, Cobweb

**Fitting tests:** Kolmogorov, Chi2

**Multivariate distribution:** kernel smoothing (KDE), maximum likelihood

**Process:** covariance models, Welch and Whittle estimators

**Bayesian calibration:** Metropolis-Hastings, conditional distribution

## Probabilistic modeling

**Dependence modelling:** elliptical, archimedean copulas.

**Univariate distribution:** Normal, Weibull

**Multivariate distribution:** Student, Dirichlet, Multinomial, User-defined

**Process:** Gaussian, ARMA, Random walk.

**Covariance models:** Matern, Exponential, User-defined

## Meta modeling

**Functional basis methods:** orthogonal basis (polynomials, Fourier, Haar, Soize Ghanem)

**Gaussian process regression:**

General linear model (GLM), Kriging

**Spectral methods:** functional chaos (PCE), Karhunen-Loeve, low-rank tensors

## Reliability, sensitivity

**Sampling methods:** Monte Carlo, LHS, low discrepancy sequences

Variance reduction methods:

importance sampling, subset sampling

**Approximation methods:** FORM, SORM

**Indices:** Spearman, Sobol, ANCOVA

**Importance factors:** perturbation method, FORM, Monte Carlo

## Functional modeling

**Numerical functions:** symbolic, Python-defined, user-defined

**Function operators:** addition, product, composition, gradients

**Function transformation:** linear combination, aggregation, parametrization

**Polynomials:** orthogonal polynomial, algebra

## Numerical methods

**Integration:** Gauss-Kronrod



**Optimization:** NLOpt, Cobyla, TNC

**Root finding:** Brent, Bisection

**Linear algebra:** Matrix, HMat

**Interpolation:** piecewise linear, piecewise Hermite

**Least squares:** SVD, QR, Cholesky



# OpenTURNS: documentation

## LevelSetMesher

(Source code, png, hires.png, pdf)



`class LevelSetMesher(*args)`

Creation of mesh of box type.

**Available constructor:**

`LevelSetMesher(discretization)`

**Parameters:** `discretization`: sequence of int, of dimension  $\leq 3$ .

Discretization of the levelset bounding box.

**solver**: `OptimizationAlgorithm`

Optimization solver used to project the vertices onto the level set. It must be able to solve nearest point problems. Default is `ScipyRunkutta`.

### Note

The meshing algorithm is based on the `IntervalMesher` class. First, the bounding box of the level set (provided by the user or automatically computed) is meshed. Then, all the simplices outside of the level set are rejected, while the simplices with all vertices inside of the level set are kept. The remaining simplices are adapted the following way:

- The mean point of the vertices inside of the level set is computed
- Each vertex outside of the level set is projected onto the level set using a linear interpolation
- If the project flag is `True`, then the projection is refined using an optimization solver.

### Examples

Create a mesh:

```
>>> import openturns as ot
>>> mesher = ot.LevelSetMesher([5, 10])
>>> level = 1.0
>>> function = ot.SymbolicFunction('x0', 'x1', ['x0^2+x1^2'])
>>> levelSet = ot.LevelSet(function, level)
>>> mesh = mesher.build(levelSet)
```

### Methods

<code>build(*args)</code>	Build the mesh of level set type.
<code>getClassname()</code>	Accessor to the object's name.
<code>getDiscretization()</code>	Accessor to the discretization.

- Content: programming interface, examples, theory.
- The doc is generated: *all* classes and methods are documented, partly automatically.
- Examples are automatically tested at *each* update of the code and outputs are checked.

## OpenTURNS: estimate the mean sequentially

Two sequential algorithms based on asymptotic statistics: the mean and Sobol' sensitivity indices.

Part 1 : Estimate the mean with an sequential algorithm.

- ▶ The "classical" way of estimating the mean : set the sample size  $n$ , then use the sample mean  $\bar{\mu} = (1/n) \sum_{j=1}^n y^{(j)}$  and estimate the accuracy (e.g. C.V.).
- ▶ Goal: use the smallest possible sample which achieves a given accuracy. Increase the sample size until a stopping criteria is met.
- ▶ The sample mean is asymptotically gaussian:

$$\bar{\mu} \xrightarrow{D} \mathcal{N} \left( E(Y), \frac{V(Y)}{n} \right).$$

- ▶ The absolute accuracy of the estimate  $\bar{\mu}$  can be evaluated based on the sample standard deviation of the estimator  $\hat{s}/\sqrt{n}$
- ▶ To get good performances on distributed supercomputers and multi-core workstations, the size of the sample increases by block.

# OpenTURNS: estimate the mean sequentially

```
[... Define the Y RandomVector ...]
algo = ot.ExpectationSimulationAlgorithm(Y)
algo.setMaximumOuterSampling(1000)
algo.setBlockSize(10) # Sample size is 0, 10, 20, 30, 40, ...
algo.setMaximumCoefficientOfVariation(0.001)
algo.run()
result = algo.getResult()
expectation = result.getExpectationEstimate()
print("MeanU=U%fU" % expectation[0])
meanDistr = result.getExpectationDistribution()
View(meanDistr.drawPDF())
```

Output:

Mean = -5.972516



Asymptotic distribution of the sample mean.



# OpenTURNS: estimate Sobol' indices sequentially

Part 2 : Estimate Sobol' sensitivity indices with an incremental algorithm based on asymptotic statistics, extending the work of (Janon et al., 2014).

- Assume that the Sobol' estimator is:

$$\bar{S} = \Psi(\bar{U})$$

where  $\Psi$  is a multivariate function,  $U$  is a multivariate sample and  $\bar{U}$  is its sample mean.

- Each Sobol' estimator (e.g. Saltelli, Jansen, etc...) can be associated with a specific choice of function  $\Psi$  and vector  $U$ .
- Therefore, the multivariate delta method implies:

$$\sqrt{n}(\bar{U} - \mu) \xrightarrow{D} \mathcal{N}(0, \nabla\psi(\mu)^T \Gamma \nabla\psi(\mu))$$

where  $\mu$  is the expected value of the Sobol' indice,  $\nabla\psi(\mu)$  is the gradient of the function  $\Psi$  and  $\Gamma$  is the covariance matrix of  $\bar{U}$ .

- An implementation of the exact gradient  $\nabla\psi(\mu)$  was derived for all estimators in OpenTURNS (Dumas, 2018).

# OpenTURNS: estimate Sobol' indices sequentially

```
[... Define the X Distribution , define the g Function ...]
estimator = ot.SaltelliSensitivityAlgorithm()
estimator.setUseAsymptoticDistribution(True)
algo = ot.SobolSimulationAlgorithm(X, g, estimator)
algo.setMaximumOuterSampling(100) # number of iterations
algo.setBlockSize(50) # size of experiment at each iteration
algo.setIndexQuantileLevel(0.1) # the confidence interval level
algo.setIndexQuantileEpsilon(0.2) # length of confidence interval
algo.run()
```



Asymptotic distribution of the first order Sobol' indices for the first variable.

# PERSALYS, the graphical user interface of OpenTURNS

- ▶ Provide a graphical interface of OpenTURNS in and out of the SALOME integration platform
- ▶ Features : probabilistic model, distribution fitting, central tendency, sensitivity analysis, probability estimate, meta-modeling (polynomial chaos, kriging), screening (Morris), optimization, design of experiments
- ▶ GUI language : English, French
- ▶ Partners : EDF, Phiméca
- ▶ Licence : LGPL
- ▶ Schedule : Since summer 2016, two EDF release per year
- ▶ On the internet (free) : SALOME\_EDF since 2018 on [www.salome-platform.org](http://www.salome-platform.org)



# PERSALYS: define the dependence

- ▶ Dependence is defined using copulas
- ▶ Define arbitrary groups of dependent variables
- ▶ Available copulas (same as in OT): gaussian, Ali-Mikhail-Haq, Clayton, Farlie-Gumbel-Morgenstern, Frank, Gumbel
- ▶ Dependence inference from a sample : Bayesian Information Criteria (BIC) or Kendall plot



# PERSALYS: 1D fields

- ▶ Mesh definition and visualization
- ▶ Import from text or csv file



# PERSALYS: 1D fields

- ▶ Functional model definition and probabilistic model
- ▶ Python or symbolic

**Python model**

```
from numpy import maximum, exp
def _exec(z0,v0,m,c):
    g = 9.81
    zmin = 0.
    tau = m / c
    vinf = -m * g / c
    # mesh nodes
    t = getMesh().getVertices()
    z = [maximum(z0 + vinf * t_i[0] + tau
    return z
```

**Definition** **Differentiation**

Inputs

Name	Description	Value
1 z0		100
2 v0		55
3 m		80
4 c		16

Index parameter : t

Outputs

<input checked="" type="checkbox"/> Name	Description
1 <input checked="" type="checkbox"/> z	

☒ Enable multiprocessing



# PERSALYS: 1D fields

- ▶ Probabilistic model
- ▶ Uncertainty propagation with simple Monte-Carlo sampling



## PERSALYS: 1D fields

- ▶ BagChart and Functional Bagchart (from Paraview) based on High Density Regions (Hyndman, 1996).
- ▶ To do this, Paraview uses a principal component analysis decomposition.
- ▶ Linked and interactive selections in the views.





# What's next ?

## PERSALYS Roadmap :

- ▶ Calibration
- ▶ 2D Fields, 3D Fields
- ▶ In-Situ fields based on the MELISSA library (with INRIA):  
when we cannot store the whole sample in memory or on the hard drive, update the statistics (e.g. the mean, Sobol' indices) sequentially, with distributed computing.



The end

Thanks !

Questions ?