



Library development

Julien Schueller - Phimeca

1-3 April 2025

OpenTURNS Consortium

1. CMake
2. C++ development process
3. SWIG
4. Python development process

Basics

CMake is an extensible, open-source system that manages the build process in an operating system and in a compiler-independent manner and covers:

- The detection and configuration aspects of the platform;
- The dependency management of the sources;
- The generation of parallel makefiles;
- The regression tests.

Some core ideas of CMake:

- All the configuration is done through a hierarchy of text files written in the CMake macro language.
- Unlike many cross-platform systems, CMake is designed to be used in conjunction with several generation tools. (Make, NMake, Ninja, ...)

CMake

It consists configuration files placed in each source directory (called CMakeLists.txt files) and cover:

- *configuration* through a master configuration file: the top-level CMakeLists.txt file;
- *source organization* through a set of CMakeLists.txt files disseminated in the whole source tree: each
- *dependency detection* through a set of detection macros: the several .cmake files; such file includes the declaration of the several source files and associated header files, and make a recursive call to the subdirectories.
- *testing* using the associated CTest testing utility, responsible for running C++ and Python tests.

```
1 mkdir build && cd build
2 cmake -DCMAKE_BUILD_TYPE=RelWithDebInfo
3   -DCMAKE_INSTALL_PREFIX=$PWD/install
4   -DCMAKE_CXX_FLAGS="-Wall -Wextra -D_GLIBCXX_ASSERTIONS"
5   -DSWIG_COMPILE_FLAGS="-O1"
6   -DUSE_SPHINX=OFF -DSPHINX_FLAGS="-W -T -j4"
7   ..
8
9 make install -j4
10 ctest -R pyinstall -j4
11
12 make tests -j4
13 ctest -R cppcheck -j4
```

Two main situations

There are two distinct situations in the development of additional capabilities of OpenTURNS:

- The addition of a new instance of an existing concept;
- The introduction of a new concept.

The associated development process shares the same principles in both cases, but the details are more involved in the second case.

Both cases are covered in the [Developer](#) documentation that comes with OpenTURNS, only the first situation will be covered here. We suppose that our extension consist in the creation of a new class called MyClass in an existing directory.

Populate an existing concept

Step 1: create the header file and the associated source file

Create `MyClass.cxx` and `openturns/MyClass.hxx` in a subdirectory of `lib/src`. The files must have the standard header, with a brief description of the class using the Doxygen format and the standard reference to the LGPL license.

For the header file `MyClass.hxx`, the interface must be embraced between the preprocessing clauses to prevent from multiple inclusions.

```
#ifndef OPENTURNS_MYCLASS_HXX
#define OPENTURNS_MYCLASS_HXX

class OT_API MyClass { ... };

#endif /* OPENTURNS_MYCLASS_HXX */
```

See any pair of `.hxx/.cxx` files in the current directory and the coding section as a guide for your development: the use of namespaces, case convention for the static methods, the other methods and the attributes, the trailing underscore for the attribute names to name a few rules.

Step 2: update the CMake source configuration

Modify the CMakeList.txt file in some lib/src subdirectory:

- add openturns/MyClass.hxx using the instruction `ot_install_header_file (MyClass.hxx)`
- add MyClass.cxx using the instruction `ot_add_source_file (MyClass.cxx)`

At this point you can build the library with the new class:

```
make
```


Step 2b: update the subdirectory header

Modify the OTsubdir.hxx file in lib/src/subdir/openturns/ to include the new header:

```
#include "openturns/MyClass.hxx"
```

Step 3: the source code of the test(s)

Create a test file `t_MyClass_std.cxx` in the directory `lib/test`. This test file must check at least the standard functionalities of the class `MyClass`. If relevant, some specific aspects of the class can be checked in specific other test files, such as the exceptional behaviour of the class or its functionalities in extrem configurations (large data set, hard to solve problems etc.).

Populate an existing concept

```
1 int main(int, char *[])
2 {
3     try
4     {
5         ...
6         MyClass algorithm(problem);
7         algo.run();
8         OptimizationResult result = algo.getResult();
9         Point x_star = result.getOptimalPoint();
10        Point p_ref = {0.6, 8.9};
11        std::cout << "x_star=" << x_star << std::endl;
12        assert_almost_equal(x_star, p_ref);
13    }
14    catch (TestFailed & ex)
15    {
16        std::cerr << ex << std::endl;
17        return ExitCode::Error;
18    }
19    return ExitCode::Success;
20 }
```

Step 4: update the CMake test configuration

Modify the CMakeList.txt file in the lib/test directory:

```
ot_check_test (MyClass_std IGNOREOUT)
```

At this point you can build the specific test:

```
make t_MyClass_std
```

And run it:

```
./lib/test/t_MyClass_std
```

Step 5: update the CMake file of the lib/test directory

At this point you can run the specific test:

```
ctest -R cppcheck_MyClass_std --output-on-failure
```

Step 7: validation

If the validation of your class involved advanced mathematics, or was a significant work using other tools, you can add this validation in the `validation/src` directory.

Critical points

- All the classes must include the `CLASSNAME` macro (defined in `Base/Common/Object.hxx`) in their header file in order to benefit from the (basic) introspection mechanisms. The associated `CLASSNAMEINIT` macro must be used in the corresponding source file.
- All the class corresponding to persistent objects must instantiate a static parameterized factory in their source file.
- All the classes must include the `OT_API` macro in their header file in order to export their symbols for win32 targets.
- Implementation classes must provide a clone method.
- Use `std::copy` to duplicate chunks of contiguous data

Critical points

- The const correctness of the code is very important, both for the signature of the methods and for the temporary variables.
- Simple types must use OpenURNS typedefs (Bool, UnsignedInteger, Scalar, Complex)
- Simple types attributes must be initialized in constructors (or in the header itself).
- All the object arguments must be passed using const references. The use of non const references to make side effects must be limited as much as possible.
- Most of the coding rules are described in the coding rules section, but you can infer the rules by looking at the existing code. **The key point is that the only difficult points should be the conception and the algorithms, not the indentation or the coding style!**

Practical case: adding a new distribution to the C++ library

- From an algorithmic point of view, the minimum to do is to implement the `Scalar computeCDF(const Point & point)` method.
- From a development process point of view, each trainee is expected to go through at least the 6 first steps.
- The other methods should be added in the following order:
 1. `Scalar computePDF(const Point & point)`
 2. `Point getRealization()`
 3. `Scalar computeScalarQuantile(const Scalar prob, const Bool tail, const Scalar precision)`
 4. `void computeMean() const`
 5. `void computeCovariance() const`

1. CMake
2. C++ development process
3. SWIG
4. Python development process

A user-friendly interface for the OpenTURNS library

OpenTURNS is intended to be used for complex industrial application. It means the ability to pilot complex simulation software, but also complex probabilistic modelling and involved strategies for uncertainty propagation. A typical graphical user interface does not provide the flexibility to address such needs, so OpenTURNS is proposed to the user as a Python module.

Python is a full-featured object oriented programming language, and allows for complex scripting of functionalities coming from numerous modules. A typical uncertainty propagation study can be fully implemented using OpenTURNS only, but it can be easier to delegate some treatments to other graphical, statistical or numerical packages. For complex studies, it is the only way to do the job.

The standard extension mechanisms proposed by Python to bind an external library are very low level mechanisms. It is mainly a C interface through which all the types are lost: the arguments are mainly void * pointers, and a lot of transtyping is required in order to make the things work.

Several higher level tools have been developed in order to ease this binding, one of the most advanced being SWIG.

A tool to link C/C++ library with script languages

SWIG is a software development tool that connects programs written in C and C++ with a variety of high-level programming languages. SWIG is used with different types of target languages including common scripting languages such as Perl, PHP, Python, Tcl and Ruby. The list of supported languages also includes non-scripting languages such as C#, Common Lisp (CLISP, Allegro CL, CFFI, UFFI), D, Go language, Java, Lua, Modula-3, OCAML, Octave and R. Also several interpreted and compiled Scheme implementations (Guile, MzScheme/Racket, Chicken) are supported. SWIG is most commonly used to create high-level interpreted or compiled programming environments, user interfaces, and as a tool for testing and prototyping C/C++ software. SWIG is typically used to parse C/C++ interfaces and generate the 'glue code' required for the above target languages to call into the C/C++ code.

SWIG: Simplified Wrapper and Interface Generator

A tool to link C/C++ library with script languages

SWIG needs a set of interface files (.i) with custom glue code.

SWIG parses the library headers and swig interface files to generate the corresponding module source yet to be compiled to produce a binary python module, see.

The process is split between several modules for modularity and to speed up compilation time with parallel builds.



Step 9: create the SWIG interface file

In order to make the new class visible in the OpenTURNS Python module, you have to create a specific SWIG interface file, namely the file `MyClass.i` in the `python/src` directory. In most situations, it should be as simple as:

```
// SWIG file MyClass.i
```

```
%{  
#include "MyClass.hxx"  
%}
```

```
%include MyClass_doc.i
```

```
%copyctor OT::MyClass;
```

```
%include MyClass.hxx
```

Step 10: integrate the SWIG interface file into the whole Python interface

- Locate in which of the Python submodule SWIG file you have to include MyClass.i (look for classes from the same source subdirectory)
- Add MyClass.i in the SWIG module source `python/src/xxx_module.i`. Caution: the order of the lines matters!
- Modify the CMakeLists file in `python/src`: add MyClass.i to the identified SWIG module

Step 11: test the new class in the Python module

- Create a test file `t_MyClass_std.py` in the directory `python/test`. This test implements the same tests than `t_MyClass_std.cxx`, but using Python.

```
...
algo = ot.MyClass(problem)
algo.run()
result = algo.getResult()
p_ref = [0.6, 8.9]
x_star = result.getOptimalPoint()
ott.assert_almost_equal(x_star, p_ref)
```

- Modify the `CMakeLists` file in `python/test`:

```
ot_pyinstallcheck_test (MyClass_std IGNOREOUT)
```

- At this point you can run the specific test:

```
ctest -R pyinstallcheck_MyClass_std --output-on-failure
```


Step 12: write the docstring documentation

- Create a docstring file `python/src/MyClass_doc.i` in:
This file contains the documentation of new methods following the Numpydoc style:

```
%feature("docstring") OT:: MyClass
" MyClass optimization solver .
```

Parameters

```
problem : :class: '~ openturns . OptimizationProblem '
    Optimization problem to solve
p1 : int
    Awesome parameter ."
```

- Make sure it will be included from `MyClass.i`:

```
%include MyClass_doc . i
```

Step 13: add an entry in the API manual

- Find the right .rst in python/doc/user_manual;
- Add an entry in the restructured text format:

Step 14: update the examples manual

- Add or expand a `plot_xxx.py` script in a `python/doc/examples` subdirectory

Pitfalls, tips and tricks

Python does not support nested classes. As such, SWIG does not propose any automatic mechanism to expose such classes in Python. The solution retained in OpenTURNS is to typedef the instantiations of the parametric classes to explicit new classes. Example:

- In the C++ library:

```
template <class T> class Collection
typedef Collection< Distribution > DistributionCollection;
```
- In the SWIG interface file:

```
% template(DistributionCollection) OT::
Collection<OT::Distribution>;
```

For the nested classes, no reasonable solution has been found: we had to unnest the class in the SWIG interface file, creating C++ source code to be maintained in the SWIG interface. We decided to do this job in the C++ library instead.

Integration of the new class in the Python bindings

Automatic conversion between C++ types into Python types

The automatic conversion of types is needed both to ease the writing of OpenTURNS scripts by Python users. Two distinct cases are of concern with OpenTURNS:

- The automatic conversion between Python lists/arrays and OpenTURNS collections;
- The automatic promotion of implementation classes into interface classes.

The first point is addressed both at the Python level and the C++ level:

- A set of parametric wrapping methods are defined in a C++ header (see `PythonWrappingFunction.hxx` in `python/src`);
- All the parametric classes are extended at the SWIG level with constructors from Python objects, using these wrapping methods.

The second point is due to the lack of capabilities of SWIG to identify correctly the Bridge pattern and use the existing constructors in order to perform the automatic conversions. It results in a need to make these conversions explicitly in the Python scripts, which is not natural for a Python programmer. The solution retained in OpenTURNS is to use the `typemap` service of SWIG and the wrapping methods in order to make these conversions automatic for the Python programmer (see `Distribution.i` in `python/src`).