HCC1395: somatic mutation and RNA evidence

Whole source-call audit | matched-normal DNA baseline | original tumor RNA | pinned reference ORFs. Counts below describe the specified public call sets and RNA run, not every biological mutation or a validated full-length isoform.

Variant-to-RNA funnel



Boxes show subset order; widths are schematic, not scaled to count.

At a glance

Evidence layer	Count	Interpretation
Ingested small variants	41,072	39,447 SNVs; 1,625 indels
Ingested SV source records	1,788	DNA breakpoint records/events, counted in their source sets
Any annotated exon involved	1,728	At least one changed base or insertion flank overlaps an Ensembl 87 exon
Ensembl 87 coding effect	491	Any annotated protein-coding transcript, reference model
orfdata ncORF coding-block overlap	17	Candidate reference ORF overlap; distinct from mutant translation
Original RNA ALT-observed calls	343	2,681 ALT reads; 2,681 ALT fragments
Calls with local mutant protein contexts	22	119 ranked contexts; full-length isoforms unresolved

Coding annotation and its denominator

Of 41,072 DNA small-variant records, 491 change the coding sequence of at least one Ensembl 87 transcript. The pinned orfdata 0.34.1 GRCh38 catalog (7,264 reference ncORF models; release 2026-10-11.1) has exact coding-block overlaps at 17 calls. The groups overlap at 3 calls, so the union is 505. These are annotation opportunities. The catalog does not assess a cell-line-specific mutant ORF, RNA expression, or peptide evidence.

Reference annotation	All DNA calls	With original RNA ALT
Ensembl coding effect	491	135
orfdata coding-block overlap	17	5
Union of either category	505	see per-call table

SNVs query their changed reference base. Deletions query removed reference bases; insertions use the VCF anchor as a candidate overlap. The per-call table preserves that rule. A coding-block hit does not prove the inserted sequence is in frame.

Any annotated exon is involved in 1,728 calls (4.2% of the small-variant source set). This includes UTR and noncoding-transcript exons. Deletions query every removed reference base, including exon crossings with intronic endpoints; insertions query both neighboring reference bases as candidate exon involvement.

Original RNA and local protein evidence

RNA assay: SRR23456709, ONT direct RNA. Each nominated small variant has a status from this run. An ALT read is a sequence observation; it is not a full-length mutant isoform.

RNA allele status	Small-variant records
alternate observed	343
reference only	239
reference and other only	53
other allele only	19
alignment without allele call	7,300
no alignment overlap	33,118

The 343 ALT-observed calls contribute 2,681 allele-read and 2,681 fragment observations. Isovar resolves at least one read-compatible **local** mutant protein context for 22 calls (119 ranked rows). The remaining 321 ALT-observed calls have no local translation under the stated method. No-overlap and uncallable statuses cannot establish absence of RNA expression.

OSTC F9L and PRDX5 F157L have original-read local contexts. An independent proteomic study observed the mutant residues, not these entire contexts. The bounded ONT cDNA fixture is excluded from whole-run counts.

Structural-variant RNA screen

Breakend screen outcome	Source records
No breakend-window alignment	1,233
One end covered; no split candidate	149
Both ends covered; no split candidate	400
Split candidate; path unresolved	6

Six Talsania records have same-read split-alignment candidates (17 record-level observations). Published POU2F1-NME7 has one candidate read. Junction bases, orientation, splice choice and ORF remain unresolved; no fusion protein is called.

RNA alternate-read support by variant class

ALT reads per variant: all calls



ALT reads per variant: positive support only



The positive-support panel excludes zero-ALT records. Bars stack SNV, insertion, deletion and other-replacement record counts in legend order; the labels show each count. These are variant counts, not read counts.

Local mutant amino-acid span

For each RNA ALT-observed call, count changed amino-acid positions in its top-ranked local protein context. Calls with no local product are shown explicitly. The second panel omits the one-residue category to expose the longer tail; its denominator is smaller. A zero-length interval can represent a deletion junction. These windows do not determine a complete frameshift tail or a full-length isoform.

Changed AA positions: all ALT-observed calls

Changed AA positions: excluding one-AA calls



Mutation classes and resolved outcomes

Category	DNA source	RNA ALT	Local mutant product
DNA-predicted frameshift	9	1	See per-call local contexts
Reference ncORF coding-block overlap	17	5	Mutated ncORF not reconstructed
SV source record	1,788	Breakend screen only	0 resolved products

Frameshifts are Varcode top-effect predictions from DNA, not a count of RNA-confirmed full-length frameshift proteins. SV split/mate candidates do not count as productive until an RNA junction and protein path resolve.

Highest original-RNA ALT support with local products

Source call	Type	Support / self screen	Top local sequence
chr12:6867653:G>C	SNV	236 ALT reads	KQNLGSSSALSTRPRCRPTP
COSM32759	SNV	193 ALT reads	VRLLADPTGALGKETDLLLD
COSM32783	SNV	166 ALT reads	DKLKEAETRAQFAERTVAKL

Least reference-self-like local contexts

Source call	Type	Support / self screen	Top local sequence
chr8:123220221:A>AGGGCTAC	insertion	14/14 novel	HPEVKCVGSVARSPDCLGDCILRRI
chr12:6867653:G>C	SNV	9/9 novel	KQNLGSSSALSTRPRCRPTP
COSM32759	SNV	9/9 novel	VRLLADPTGALGKETDLLLD

The score is the fraction of distinct mutation-overlapping 9-mers absent from the pinned Ensembl 87 reference protein FASTA. It is an exact-match screen of these local windows, not patient-specific self, HLA binding, presentation or immunogenicity.

Highest supported non-SNV local products

Source call	Type	Support / self screen	Top local sequence
chr8:123220221:A>AGGGCTAC	insertion	3 ALT reads	HPEVKCVGSVARSPDCLGDCILRRI

The tables rank source records, not independent molecules. A displayed local context may represent only part of a mutant protein.

Sources, processing and limits

Input	Pinned scope
Matched-normal small variants	SEQC2 v1.2.1 SNV + indel, GRCh38.d1.vd1; HCC1395BL normal
SV benchmark	Talsania et al. 2022 Table S4, HCC1395 vs HCC1395BL
Original RNA	PRJNA934933 / SRR23456709; 1,049,452 ONT direct RNA reads
Alignment	minimap2 2.26 -ax splice -uf -k14; NCBI GRCh38 no-alt

Reference model and interpretation

Small-variant coding effects use Varcode with Ensembl release 87 on GRCh38. The human orfdata 0.34.1 catalog uses Ensembl 101 GRCh38 reference ORFs (7,264 models, dataset 2026-10-11.1). An orfdata coding-block overlap is a reference annotation candidate; this analysis did not translate mutated ncORFs from the RNA reads. Genomic transcript overlap is not RNA-compatible isoform support. Original-read allele counts and local protein contexts are separate observations.

SHA-256 input pins

SEQC2 SNV VCF gzip

`0c49f7e1519fc7860b773f79bdcf07453fe4def8303707f34542471d92494c9d`
SEQC2 indel VCF gzip

`db7dc8be2ec04bab830ff1411146c7d538c217ff684e874b85d98a3dbbda91cf`
Talsania Table S4 xlsx

`11e8d6393b83f0e0b7fdb0b13a57376663fc9662116d78c89a0d5fa530df096b`
SRR23456709 SRA archive

`d69db8e48bbb20665c3e03a1fa35742be818a0127994e015cb3a560afae39ac8`
GRCh38 no-alt FASTA (uncompressed)

`9cce8b926416dd96b152deea85188495b75f7ac8d634cc723a017067be8702b7`
orfdata bundled GRCh38 catalog

`06bc0bf3f81c25a7356f71a38581ff5704c05dcb75752454bc1ca75075ab8c09`
Ensembl 87 GRCh38 protein FASTA gzip (self screen)

`d873c199d5dbf20869db3f2cbd6ac726259215d91c2782f9f1ddcad4bb117cf9`

What remains unresolved

ONT raw-read errors can create other-base calls and competing local contexts. The RNA and DNA libraries come from separate studies. A 500-base breakend window and split-alignment candidate are screening evidence only. Full-length isoform linkage and SV protein reconstruction were not assessed.

Machine-readable per-call annotation, allele, protein, and SV tables and complete reconstruction commands are published with the Isovar HCC1395/COLO829 reports. These PDFs summarize selected public source call sets, not a complete catalogue of every cell-line mutation.