




Ground clip pads




Power supply test points, top side





Copyrights: CC-BY-SA 3.0 Patents: Apache 2.0

Title		
Size	Number	Revision
A		
Date:	3/17/2021	Sheet of
File:	C:\Users\...\power.SchDoc	Drawn By:




A



B




C




Copyrights: CC-BY-SA 3.0 Patents: Apache 2.0

Title		
Size	Number	Revision
A		
Date:	3/17/2021	Sheet 2 of
File:	C:\Users\...\FPGA power v3.SchDoc	Drawn By:




U2C

BANK 2


XC6SLX9-3TQG144C

U2A




XC6SLX9-3TQG144C


P1





U2D

BANK 1**BANK 1**

XC6SLX9-3TQG144C

BANK 3


XC6SLX9-3TQG144C



Copyrights: CC-BY-SA 3.0 Patents: Apache 2.0

Title		Revision
Size	Number	
A		
Date:	3/17/2021	Sheet of
File:	C:\Users\.\fpga.SchDoc	Drawn By:


A



Signals used during FPGA configuration
(see XAPP502):
D0-D7
CSI_B, RDWR_B, CCLK, PROG_B,
DONE, INIT_B, M0, M1


Additional signals used during FIFO mode:
ACBUS0 (RXF#)
ACBUS2 (RD#)
ACBUS3 (WR#)
ACBUSS (CLKOUT)
ACBUS6 (OE#)

spare I/Os:




FT2232H

B



C



D



Copyrights: CC-BY-SA 3.0 Patents: Apache 2.0

Title		Revision
Size	Number	
A		
Date:	3/17/2021	Sheet of
File:	C:\Users\...\usb.SchDoc	Drawn By:

