

Base de Données Complète - Suite Optimize

Voici le script SQL complet regroupant tous les modules (Finance, RH, Achat/MG) avec les relations, index et contraintes appropriés.

```
``sql
-- =====
-- BASE DE DONNÉES OPTIMIZE - SUITE COMPLÈTE
-- Modules: Finance, RH/Paie, Achat & Moyens Généraux
-- Version: 2.0
-- Date: 2024
-- SGBD: MySQL 5.7+ / PostgreSQL
-- =====

SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
SET AUTOCOMMIT = 0;
START TRANSACTION;
SET time_zone = "+00:00";

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!40101 SET NAMES utf8mb4 */;

-- =====
-- 1. TABLES SYSTÈME & AUTHENTIFICATION
-- =====

CREATE TABLE `users` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `email` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `email_verified_at` timestamp NULL DEFAULT NULL,
  `password` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `two_factor_secret` text COLLATE utf8mb4_unicode_ci,
  `two_factor_recovery_codes` text COLLATE utf8mb4_unicode_ci,
  `remember_token` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `current_team_id` bigint(20) UNSIGNED DEFAULT NULL,
  `profile_photo_path` varchar(2048) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `prenoms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `contact` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `email_interne` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `apiclient` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `matricule` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
```

```

`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
UNIQUE KEY `users_email_unique` (`email`),
UNIQUE KEY `users_email_interne_unique` (`email_interne`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `roles` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `guard_name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `roles_name_guard_name_unique` (`name`,`guard_name`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `permissions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `guard_name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `module` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT NULL COMMENT 'finance, rh,
achat, mg',
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `permissions_name_guard_name_unique` (`name`,`guard_name`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `model_has_roles` (
  `role_id` bigint(20) UNSIGNED NOT NULL,
  `model_type` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `model_id` bigint(20) UNSIGNED NOT NULL,
  PRIMARY KEY (`role_id`,`model_id`,`model_type`),
  KEY `model_has_roles_model_id_model_type_index` (`model_id`,`model_type`),
  CONSTRAINT `model_has_roles_role_id_foreign` FOREIGN KEY (`role_id`) REFERENCES
`roles` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `model_has_permissions` (
  `permission_id` bigint(20) UNSIGNED NOT NULL,
  `model_type` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `model_id` bigint(20) UNSIGNED NOT NULL,
  PRIMARY KEY (`permission_id`,`model_id`,`model_type`),
  KEY `model_has_permissions_model_id_model_type_index` (`model_id`,`model_type`),

```

```
CONSTRAINT `model_has_permissions_permission_id_foreign` FOREIGN KEY  
(`permission_id`) REFERENCES `permissions` (`id`) ON DELETE CASCADE  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `role_has_permissions` (  
  `permission_id` bigint(20) UNSIGNED NOT NULL,  
  `role_id` bigint(20) UNSIGNED NOT NULL,  
  PRIMARY KEY (`permission_id`,`role_id`),  
  KEY `role_has_permissions_role_id_foreign` (`role_id`),  
  CONSTRAINT `role_has_permissions_permission_id_foreign` FOREIGN KEY  
(`permission_id`) REFERENCES `permissions` (`id`) ON DELETE CASCADE,  
  CONSTRAINT `role_has_permissions_role_id_foreign` FOREIGN KEY (`role_id`) REFERENCES  
  `roles` (`id`) ON DELETE CASCADE  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `sessions` (  
  `id` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `user_id` bigint(20) UNSIGNED DEFAULT NULL,  
  `ip_address` varchar(45) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `user_agent` text COLLATE utf8mb4_unicode_ci,  
  `payload` text COLLATE utf8mb4_unicode_ci NOT NULL,  
  `last_activity` int(11) NOT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`),  
  KEY `sessions_user_id_index` (`user_id`),  
  KEY `sessions_last_activity_index` (`last_activity`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `logs` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `id_user` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `type_action` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `action` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `adresse_ip` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `message` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `old_value` text COLLATE utf8mb4_unicode_ci,  
  `new_value` text COLLATE utf8mb4_unicode_ci,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `authentications` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `ip` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `email` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
```

```

`operations` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL COMMENT 'login,
logout, failed',
`lieu` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`user_agent` text COLLATE utf8mb4_unicode_ci,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `changepasswords` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `users` bigint(20) UNSIGNED DEFAULT NULL,
  `password` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `changed_at` timestamp NULL DEFAULT CURRENT_TIMESTAMP,
  `extra_attributes` json DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `changepasswords_users_foreign` (`users`),
  CONSTRAINT `changepasswords_users_foreign` FOREIGN KEY (`users`) REFERENCES `users`
(`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 2. TABLES GÉOGRAPHIQUES & ORGANISATION
-- =====

```

```

CREATE TABLE `pays` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `code` int(11) DEFAULT NULL,
  `zipcode` varchar(45) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `alpha2` varchar(2) COLLATE utf8mb4_unicode_ci NOT NULL,
  `alpha3` varchar(3) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nom_en_gb` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `nom_fr_fr` varchar(225) COLLATE utf8mb4_unicode_ci NOT NULL,
  `isvalide` int(11) DEFAULT 1,
  `statut` int(11) DEFAULT 1,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `regions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,

```

```

`dateeffet` datetime DEFAULT CURRENT_TIMESTAMP,
`num` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`code` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`statut` int(11) DEFAULT 1,
`attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`isvalide` int(11) DEFAULT 1,
`id_user` int(11) NOT NULL DEFAULT 1,
`id_pays` bigint(20) UNSIGNED NOT NULL DEFAULT 80,
`effacer` int(11) DEFAULT 0,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `fk_region_pays` (`id_pays`),
CONSTRAINT `fk_region_pays` FOREIGN KEY (`id_pays`) REFERENCES `pays` (`id`) ON
DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `type_localites` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `dateeffet` datetime DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `isvalide` int(11) DEFAULT 1,
  `id_user` int(11) NOT NULL DEFAULT 1,
  `effacer` int(11) DEFAULT 0,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `localites` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `dateeffet` datetime DEFAULT CURRENT_TIMESTAMP,
  `code` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `statut` int(11) DEFAULT 1,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `isvalide` int(11) DEFAULT 1,
  `id_user` int(11) NOT NULL DEFAULT 1,
  `effacer` int(11) DEFAULT 0,

```

```

`id_typedlocalite` bigint(20) UNSIGNED NOT NULL,
`id_region` bigint(20) UNSIGNED NOT NULL,
`id_pays` bigint(20) UNSIGNED NOT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `fk_localite_pays1` (`id_pays`),
KEY `fk_localite_region1` (`id_region`),
KEY `fk_localite_typedlocalite1` (`id_typedlocalite`),
CONSTRAINT `fk_localite_pays1` FOREIGN KEY (`id_pays`) REFERENCES `pays` (`id`) ON
DELETE CASCADE,
CONSTRAINT `fk_localite_region1` FOREIGN KEY (`id_region`) REFERENCES `regions` (`id`)
ON DELETE CASCADE,
CONSTRAINT `fk_localite_typedlocalite1` FOREIGN KEY (`id_typedlocalite`) REFERENCES
`type_localites` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `arrondissements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `dateeffet` datetime DEFAULT CURRENT_TIMESTAMP,
  `code` varchar(45) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `statut` int(11) DEFAULT 1,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `isvalide` int(11) DEFAULT 1,
  `id_user` int(11) NOT NULL DEFAULT 1,
  `effacer` int(11) DEFAULT 0,
  `id_localite` bigint(20) UNSIGNED NOT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `fk_arrondissement_localite1` (`id_localite`),
  CONSTRAINT `fk_arrondissement_localite1` FOREIGN KEY (`id_localite`) REFERENCES
`localites` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4_unicode_ci;

```

```

CREATE TABLE `quartiers` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `dateeffet` datetime DEFAULT CURRENT_TIMESTAMP,
  `code` varchar(45) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `statut` int(11) DEFAULT 1,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,

```

```

`isvalide` int(11) DEFAULT 1,
`id_user` int(11) NOT NULL DEFAULT 1,
`effacer` int(11) DEFAULT 0,
`id_arrondissement` bigint(20) UNSIGNED NOT NULL,
`id_localite` bigint(20) UNSIGNED NOT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `fk_quartier_localite1` (`id_localite`),
KEY `fk_quartier_arrondissement1` (`id_arrondissement`),
CONSTRAINT `fk_quartier_arrondissement1` FOREIGN KEY (`id_arrondissement`)
REFERENCES `arrondissements` (`id`) ON DELETE CASCADE,
CONSTRAINT `fk_quartier_localite1` FOREIGN KEY (`id_localite`) REFERENCES `localites`
(`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `entites` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `code` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_localite` bigint(20) UNSIGNED DEFAULT NULL,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `effacer` tinyint(1) NOT NULL DEFAULT 0,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `entites_id_localite_foreign` (`id_localite`),
  CONSTRAINT `entites_id_localite_foreign` FOREIGN KEY (`id_localite`) REFERENCES
`localites` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `organisations` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `typesorganisation_id` bigint(20) UNSIGNED NOT NULL,
  `chefs` bigint(20) UNSIGNED NOT NULL COMMENT 'user_id',
  `peres` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'organisation_id parent',
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),

```

```

KEY `organisations_typesorganisation_id_foreign` (`typesorganisation_id`),
KEY `organisations_chefs_foreign` (`chefs`),
KEY `organisations_peres_foreign` (`peres`),
CONSTRAINT `organisations_typesorganisation_id_foreign` FOREIGN KEY
(`typesorganisation_id`) REFERENCES `typesorganisations` (`id`),
CONSTRAINT `organisations_chefs_foreign` FOREIGN KEY (`chefs`) REFERENCES `users`
(`id`),
CONSTRAINT `organisations_peres_foreign` FOREIGN KEY (`peres`) REFERENCES
`organisations` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `typesorganisations` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 3. MODULE FINANCE
-- =====

```

```

CREATE TABLE `configs` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `config_object` json NOT NULL,
  `description` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `exercices` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `exercice` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_regroupement` bigint(20) UNSIGNED DEFAULT NULL,
  `dateeffect` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,
  `datedebut` datetime DEFAULT NULL,
  `datefin` datetime DEFAULT NULL,
  `entite` datetime DEFAULT NULL,
  `budgetglobalinitial` double DEFAULT NULL,

```



```

`commentaire` mediumtext COLLATE utf8mb4_unicode_ci,
`attribut1` mediumtext COLLATE utf8mb4_unicode_ci,
`attribut2` mediumtext COLLATE utf8mb4_unicode_ci,
`attribut3` mediumtext COLLATE utf8mb4_unicode_ci,
`isvalide` int(11) DEFAULT 0,
`id_user` bigint(20) UNSIGNED DEFAULT NULL,
`effacer` int(11) NOT NULL DEFAULT 0,
`version_exercice` int(11) NOT NULL DEFAULT 1,
`statut` int(11) NOT NULL DEFAULT 3 COMMENT '1=planifié, 2=en cours, 3=clôturé',
`dotationglobale` double(8,2) NOT NULL DEFAULT 0.00,
`fondpropreglobal` double(8,2) NOT NULL DEFAULT 0.00,
`reportbudgetiare` double(8,2) NOT NULL DEFAULT 0.00,
`reporttresorerieglobal` double(8,2) NOT NULL DEFAULT 0.00,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `exercices_id_user_foreign` (`id_user`),
CONSTRAINT `exercices_id_user_foreign` FOREIGN KEY (`id_user`) REFERENCES `users`
(`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `titres` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `imputation` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `seuil` double UNSIGNED DEFAULT NULL,
  `type_ligne` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL COMMENT 'depense,
recette',
  `description` mediumtext COLLATE utf8mb4_unicode_ci,
  `effacer` tinyint(1) NOT NULL DEFAULT 0,
  `id_user` int(11) NOT NULL DEFAULT 1,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `lignes` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `id_titre` bigint(20) UNSIGNED NOT NULL,
  `nature` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `seuil` double UNSIGNED DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` mediumtext COLLATE utf8mb4_unicode_ci,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL DEFAULT "",
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL DEFAULT "",
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL DEFAULT "",
  `isvalide` int(11) DEFAULT 0,

```

```

`effacer` tinyint(1) NOT NULL DEFAULT 0,
`id_codeanalytique` int(11) DEFAULT NULL,
`id_famillicodeanalytique` int(11) DEFAULT NULL,
`id_user` int(11) NOT NULL DEFAULT 1,
`dateeffet` datetime DEFAULT NULL,
`id_typecode` int(11) DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `lignes_id_titre_index` (`id_titre`),
CONSTRAINT `lignes_id_titre_foreign` FOREIGN KEY (`id_titre`) REFERENCES `titres` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `budget_lignes` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `id_budgetligne` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `dateeffect` timestamp NULL DEFAULT NULL,
  `id_exercicebudgetaire` bigint(20) UNSIGNED DEFAULT NULL,
  `exercice` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_famillicodeanalytique` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'id titre',
  `id_codeanalytique` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'id ligne',
  `codecompte` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `budgetligne` double(8,2) NOT NULL DEFAULT 0.00,
  `commentaire` text COLLATE utf8mb4_unicode_ci,
  `attribut1` text COLLATE utf8mb4_unicode_ci,
  `attribut2` text COLLATE utf8mb4_unicode_ci,
  `attribut3` text COLLATE utf8mb4_unicode_ci,
  `isvalide` tinyint(4) NOT NULL DEFAULT 0,
  `id_user` bigint(20) UNSIGNED DEFAULT NULL,
  `effacer` tinyint(4) NOT NULL DEFAULT 0,
  `dotation_etat` double(8,2) DEFAULT NULL,
  `fonds_propres` double(8,2) DEFAULT NULL,
  `reports_budgetaire` double(8,2) DEFAULT NULL,
  `reports_tresorerie` double(8,2) DEFAULT NULL,
  `transfert` double(8,2) NOT NULL DEFAULT 0.00,
  `engagement` double(8,2) NOT NULL DEFAULT 0.00,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `budget_lignes_id_exercicebudgetaire_foreign` (`id_exercicebudgetaire`),
  KEY `budget_lignes_id_user_foreign` (`id_user`),
  CONSTRAINT `budget_lignes_id_exercicebudgetaire_foreign` FOREIGN KEY
(`id_exercicebudgetaire`) REFERENCES `exercices` (`id`),
  CONSTRAINT `budget_lignes_id_user_foreign` FOREIGN KEY (`id_user`) REFERENCES `users`
(`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `modification_budgetaires` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `id_compte_emission` bigint(20) UNSIGNED DEFAULT NULL,
  `codecompte_emission` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_compte_reception` bigint(20) UNSIGNED DEFAULT NULL,
  `codecompte_reception` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `objetmodification` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `montant_modification` double(8,2) DEFAULT NULL,
  `isbudgetligne` tinyint(4) DEFAULT NULL,
  `commentaire` text COLLATE utf8mb4_unicode_ci,
  `id_user` bigint(20) UNSIGNED DEFAULT NULL,
  `statut` int(11) DEFAULT 0 COMMENT '0=brouillon, 1=soumis, 2=validé, 3=rejeté',
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `modification_budgetaires_id_user_foreign` (`id_user`),
  CONSTRAINT `modification_budgetaires_id_user_foreign` FOREIGN KEY (`id_user`)
REFERENCES `users` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `comptes` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `code` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nom` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `filename` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `type` tinyint(4) DEFAULT NULL COMMENT '1=banque, 2=caisse, 3=tiers',
  `entite_id` int(11) DEFAULT NULL,
  `solde` double(8,2) DEFAULT 0.00,
  `rib` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `responsable` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `gestionnaire` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `contact_gestionnaire` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `domiciliation` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut1` text COLLATE utf8mb4_unicode_ci,
  `attribut2` text COLLATE utf8mb4_unicode_ci,
  `attribut3` text COLLATE utf8mb4_unicode_ci,
  `effacer` tinyint(4) NOT NULL DEFAULT 0,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `transaction_comptes` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `compte_id` bigint(20) UNSIGNED NOT NULL,
  `sens` tinyint(1) NOT NULL COMMENT '1=débit, 0=crédit',
  `montant` double(8,2) NOT NULL,

```

```

`effacer` tinyint(1) NOT NULL DEFAULT 0,
`dateeffet` datetime DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `transaction_comptes_compte_id_foreign` (`compte_id`),
CONSTRAINT `transaction_comptes_compte_id_foreign` FOREIGN KEY (`compte_id`)
REFERENCES `comptes` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `grand_livres` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `date_ecriture` date DEFAULT NULL,
  `id_entite` bigint(20) UNSIGNED DEFAULT NULL,
  `dateeffet` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,
  `montant_tc` double DEFAULT NULL,
  `sens` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `mode_reglement` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `exercice` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_exercicebudgetaire` bigint(20) UNSIGNED DEFAULT NULL,
  `description` mediumtext COLLATE utf8mb4_unicode_ci,
  `id_user` bigint(20) UNSIGNED DEFAULT NULL,
  `rib` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `banque` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `beneficiaire` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `type_beneficiaire` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `beneficiaire_interne` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_beneficiaire` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_beneficiaire_interne` bigint(20) UNSIGNED DEFAULT NULL,
  `libelle_piece` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `type_piece` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `id_ligne` bigint(20) UNSIGNED DEFAULT NULL,
  `id_titre` bigint(20) UNSIGNED DEFAULT NULL,
  `imputation` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nature` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `num_piece` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `ref_piece` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nature_piece` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `montant_signe_tc` double DEFAULT NULL,
  `compte_id` bigint(20) UNSIGNED DEFAULT NULL,
  `compte_general` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `compte_auxiliaire` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `role_tiers` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `journal` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `devise` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `montant_tr` double DEFAULT NULL,

```

```

`code_lettrage` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`type_marquage` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`date_lettrage` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`date_pointage` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`lettre_rappro` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`date_rappro` date DEFAULT NULL,
`type_ecriture` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`num_lot` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`num_ecriture` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`code_tiers` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`montant_signe_tr` double(8,2) DEFAULT NULL,
`id_famillecodedanalytique` bigint(20) UNSIGNED DEFAULT NULL,
`id_codeanalytique` bigint(20) UNSIGNED DEFAULT NULL,
`id_organisation` bigint(20) UNSIGNED DEFAULT NULL,
`attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`isvalide` int(11) DEFAULT 0,
`effacer` int(11) NOT NULL DEFAULT 0,
`num_stat` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`nif` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`id_facture` bigint(20) UNSIGNED DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `grand_livres_compte_id_foreign` (`compte_id`),
KEY `grand_livres_id_user_foreign` (`id_user`),
CONSTRAINT `grand_livres_compte_id_foreign` FOREIGN KEY (`compte_id`) REFERENCES `comptes` (`id`),
CONSTRAINT `grand_livres_id_user_foreign` FOREIGN KEY (`id_user`) REFERENCES `users` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `grand_livre_details` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `id_facture` bigint(20) UNSIGNED DEFAULT NULL,
  `id_produit` bigint(20) UNSIGNED DEFAULT NULL,
  `prix` double DEFAULT NULL,
  `quantite` double DEFAULT NULL,
  `total_ht` double DEFAULT NULL,
  `total_taxe` double DEFAULT NULL,
  `total_reduction` double DEFAULT NULL,
  `total_ttc` double DEFAULT NULL,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `effacer` tinyint(1) NOT NULL DEFAULT 0,

```

```

`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `mode_reglements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `dateeffet` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
  `code` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `description` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `statut` int(11) NOT NULL DEFAULT 1,
  `attribut1` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut2` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `attribut3` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `isvalide` tinyint(4) DEFAULT 1,
  `id_user` int(11) NOT NULL DEFAULT 1,
  `effacer` tinyint(1) NOT NULL DEFAULT 0,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `transactions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 4. MODULE RH & PAIE
-- =====

```

```

CREATE TABLE `employees` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `user_id` bigint(20) UNSIGNED DEFAULT NULL,
  `noms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `prenoms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `matricule` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `date_naissance` date DEFAULT NULL,
  `lieu_naissance` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nationalite` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `sexe` char(1) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `situation_matrimoniale` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nombre_enfants` int(11) DEFAULT 0,
  `email` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,

```

```

`contact` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`adresse` text COLLATE utf8mb4_unicode_ci,
`id_quartier` bigint(20) UNSIGNED DEFAULT NULL,
`id_ville` bigint(20) UNSIGNED DEFAULT NULL,
`id_pays` bigint(20) UNSIGNED DEFAULT NULL,
`date_embauche` date DEFAULT NULL,
`type_contrat` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`date_fin_contrat` date DEFAULT NULL,
`poste` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`departement` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`superieur_hierarchique` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'employee_id',
`salaire_base` double(8,2) DEFAULT 0.00,
`iban` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`numero_secu` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`statut` int(11) DEFAULT 1 COMMENT '1=actif, 2=inactif, 3=parti',
`fichiersjoin` text COLLATE utf8mb4_unicode_ci COMMENT 'CV, pièces jointes',
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
UNIQUE KEY `employees_matricule_unique` (`matricule`),
KEY `employees_user_id_foreign` (`user_id`),
KEY `employees_superieur_hierarchique_foreign` (`superieur_hierarchique`),
CONSTRAINT `employees_user_id_foreign` FOREIGN KEY (`user_id`) REFERENCES `users`
(`id`),
CONSTRAINT `employees_superieur_hierarchique_foreign` FOREIGN KEY
(`superieur_hierarchique`) REFERENCES `employees` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `affilies` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `liens` text COLLATE utf8mb4_unicode_ci COMMENT 'conjoint, enfant, etc.',
  `noms` text COLLATE utf8mb4_unicode_ci,
  `prenoms` text COLLATE utf8mb4_unicode_ci,
  `date_naissance` date DEFAULT NULL,
  `contact1` text COLLATE utf8mb4_unicode_ci,
  `contact2` text COLLATE utf8mb4_unicode_ci,
  `email` text COLLATE utf8mb4_unicode_ci,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,

```

```

PRIMARY KEY (`id`),
KEY `affilies_employee_id_foreign` (`employee_id`),
CONSTRAINT `affilies_employee_id_foreign` FOREIGN KEY (`employee_id`) REFERENCES
`employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `absences` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `type_absence` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT NULL COMMENT
'conge_paye, maladie, mission, etc.',
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci COMMENT 'justificatifs',
  `statut` int(11) DEFAULT 0 COMMENT '0=brouillon, 1=soumis, 2=validé, 3=rejeté',
  `validé_par` bigint(20) UNSIGNED DEFAULT NULL,
  `date_validation` datetime DEFAULT NULL,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `absences_employee_id_foreign` (`employee_id`),
  KEY `absences_valide_par_foreign` (`validé_par`),
  CONSTRAINT `absences_employee_id_foreign` FOREIGN KEY (`employee_id`) REFERENCES
`employees` (`id`) ON DELETE CASCADE,
  CONSTRAINT `absences_valide_par_foreign` FOREIGN KEY (`validé_par`) REFERENCES
`users` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `competences` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `niveau` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT NULL COMMENT 'débutant,
intermédiaire, expert',
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci COMMENT 'certificats, diplômes',
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,

```



```

`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `competences_employee_id_foreign` (`employee_id`),
CONSTRAINT `competences_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `qualifications` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `organisme` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `qualifications_employee_id_foreign` (`employee_id`),
  CONSTRAINT `qualifications_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `evenementscarrieres` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,
  `typesevenementscarriere_id` bigint(20) UNSIGNED DEFAULT NULL,
  `employee_id` bigint(20) UNSIGNED DEFAULT NULL,
  `date_effet` date DEFAULT NULL,
  `ancien_poste` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `nouveau_poste` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `evenementscarrieres_employee_id_foreign` (`employee_id`),
  CONSTRAINT `evenementscarrieres_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE

```

```
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `typesevenementscarrieres` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL COMMENT 'promotion,  
mutation, licenciement, etc.',  
  `description` text COLLATE utf8mb4_unicode_ci,  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `recrutements` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `introduction` text COLLATE utf8mb4_unicode_ci,  
  `description` text COLLATE utf8mb4_unicode_ci,  
  `debut` datetime DEFAULT NULL,  
  `fin` datetime DEFAULT NULL,  
  `statut` int(11) DEFAULT 0 COMMENT '0=ouvert, 1=fermé, 2=pourvu',  
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `postulants` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `noms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `prenoms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `age` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `date_naissance` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `email` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `contact` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `profil_id` bigint(20) UNSIGNED NOT NULL,  
  `recrutement_id` bigint(20) UNSIGNED DEFAULT NULL,  
  `statut` int(11) DEFAULT 0 COMMENT '0=nouveau, 1=entretenu, 2=retenu, 3=rejeté',  
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci COMMENT 'CV, lettres',  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`),
```

```

KEY `postulants_profil_id_foreign` (`profil_id`),
KEY `postulants_recrutement_id_foreign` (`recrutement_id`),
CONSTRAINT `postulants_profil_id_foreign` FOREIGN KEY (`profil_id`) REFERENCES `profils`
(`id`),
CONSTRAINT `postulants_recrutement_id_foreign` FOREIGN KEY (`recrutement_id`)
REFERENCES `recrutements` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `profils` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `nombres` text COLLATE utf8mb4_unicode_ci COMMENT 'nombre de postes',
  `recrutement_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `profils_recrutement_id_foreign` (`recrutement_id`),
  CONSTRAINT `profils_recrutement_id_foreign` FOREIGN KEY (`recrutement_id`)
REFERENCES `recrutements` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `embauches` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `valider` tinyint(1) DEFAULT 0,
  `postulant_id` bigint(20) UNSIGNED NOT NULL,
  `employee_id` bigint(20) UNSIGNED DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci COMMENT 'contrat signé',
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `embauches_postulant_id_foreign` (`postulant_id`),
  KEY `embauches_employee_id_foreign` (`employee_id`),
  CONSTRAINT `embauches_postulant_id_foreign` FOREIGN KEY (`postulant_id`)
REFERENCES `postulants` (`id`) ON DELETE CASCADE,

```

```
CONSTRAINT `embauches_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `pcompetences` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `postulant_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `pcompetences_postulant_id_foreign` (`postulant_id`),
  CONSTRAINT `pcompetences_postulant_id_foreign` FOREIGN KEY (`postulant_id`)
REFERENCES `postulants` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `pqualifications` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `postulant_id` bigint(20) UNSIGNED NOT NULL,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `pqualifications_postulant_id_foreign` (`postulant_id`),
  CONSTRAINT `pqualifications_postulant_id_foreign` FOREIGN KEY (`postulant_id`)
REFERENCES `postulants` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `pexamens` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
```

```

`introduction` text COLLATE utf8mb4_unicode_ci,
`description` text COLLATE utf8mb4_unicode_ci,
`debut` datetime DEFAULT NULL,
`fin` datetime DEFAULT NULL,
`postulant_id` bigint(20) UNSIGNED NOT NULL,
`fichiersjoin` text COLLATE utf8mb4_unicode_ci,
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `pexamens_postulant_id_foreign` (`postulant_id`),
CONSTRAINT `pexamens_postulant_id_foreign` FOREIGN KEY (`postulant_id`) REFERENCES
`postulants` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `resultats` (
`id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
`label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`introduction` text COLLATE utf8mb4_unicode_ci,
`description` text COLLATE utf8mb4_unicode_ci,
`pexamen_id` bigint(20) UNSIGNED NOT NULL,
`note` double(5,2) DEFAULT NULL,
`appreciation` text COLLATE utf8mb4_unicode_ci,
`fichiersjoin` text COLLATE utf8mb4_unicode_ci,
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `resultats_pexamen_id_foreign` (`pexamen_id`),
CONSTRAINT `resultats_pexamen_id_foreign` FOREIGN KEY (`pexamen_id`) REFERENCES
`pexamens` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `pentretiens` (
`id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
`label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`introduction` text COLLATE utf8mb4_unicode_ci,
`description` text COLLATE utf8mb4_unicode_ci,
`debut` datetime DEFAULT NULL,
`fin` datetime DEFAULT NULL,
`postulant_id` bigint(20) UNSIGNED NOT NULL,
`interviewer_id` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'user_id',
`appreciation` text COLLATE utf8mb4_unicode_ci,

```

```

`fichiersjoin` text COLLATE utf8mb4_unicode_ci,
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `pentretiens_postulant_id_foreign` (`postulant_id`),
CONSTRAINT `pentretiens_postulant_id_foreign` FOREIGN KEY (`postulant_id`)
REFERENCES `postulants` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `tests` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `profil_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `tests_profil_id_foreign` (`profil_id`),
  CONSTRAINT `tests_profil_id_foreign` FOREIGN KEY (`profil_id`) REFERENCES `profils` (`id`)
  ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `missions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `lieu` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `objet` text COLLATE utf8mb4_unicode_ci,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,

```

```

`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `missions_employee_id_foreign` (`employee_id`),
CONSTRAINT `missions_employee_id_foreign` FOREIGN KEY (`employee_id`) REFERENCES
`employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `groupes` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `groupes_users` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `create_by` bigint(20) UNSIGNED NOT NULL,
  `groupe_id` bigint(20) UNSIGNED NOT NULL,
  `user_id` bigint(20) UNSIGNED NOT NULL,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `groupes_users_groupe_id_foreign` (`groupe_id`),
  KEY `groupes_users_user_id_foreign` (`user_id`),
  CONSTRAINT `groupes_users_groupe_id_foreign` FOREIGN KEY (`groupe_id`) REFERENCES
`groupes` (`id`) ON DELETE CASCADE,
  CONSTRAINT `groupes_users_user_id_foreign` FOREIGN KEY (`user_id`) REFERENCES
`users` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `messagesgroupes` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,

```

```

`objects` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`forusers` text COLLATE utf8mb4_unicode_ci COMMENT 'user_ids JSON',
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `messages` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `messages` text COLLATE utf8mb4_unicode_ci,
  `messagesgroupe_id` bigint(20) UNSIGNED NOT NULL,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `messages_messagesgroupe_id_foreign` (`messagesgroupe_id`),
  KEY `messages_employee_id_foreign` (`employee_id`),
  CONSTRAINT `messages_messagesgroupe_id_foreign` FOREIGN KEY (`messagesgroupe_id`)
REFERENCES `messagesgroupes` (`id`) ON DELETE CASCADE,
  CONSTRAINT `messages_employee_id_foreign` FOREIGN KEY (`employee_id`) REFERENCES
`employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `privileges` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `privileges_employee_id_foreign` (`employee_id`),
  CONSTRAINT `privileges_employee_id_foreign` FOREIGN KEY (`employee_id`) REFERENCES
`employees` (`id`) ON DELETE CASCADE

```



```
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `remarques` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `introduction` text COLLATE utf8mb4_unicode_ci,  
  `description` text COLLATE utf8mb4_unicode_ci,  
  `employee_id` bigint(20) UNSIGNED NOT NULL,  
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,  
  `statut` int(11) DEFAULT 1,  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`),  
  KEY `remarques_employee_id_foreign` (`employee_id`),  
  CONSTRAINT `remarques_employee_id_foreign` FOREIGN KEY (`employee_id`)  
  REFERENCES `employees` (`id`) ON DELETE CASCADE  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `incidents` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `description` text COLLATE utf8mb4_unicode_ci,  
  `typesincident_id` bigint(20) UNSIGNED DEFAULT NULL,  
  `employee_id` bigint(20) UNSIGNED DEFAULT NULL,  
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`),  
  KEY `incidents_employee_id_foreign` (`employee_id`),  
  CONSTRAINT `incidents_employee_id_foreign` FOREIGN KEY (`employee_id`) REFERENCES  
  `employees` (`id`) ON DELETE SET NULL  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `typesincidents` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,  
  `description` text COLLATE utf8mb4_unicode_ci,  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```

CREATE TABLE `inconvenients` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `inconvenients_employee_id_foreign` (`employee_id`),
  CONSTRAINT `inconvenients_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `integrations` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `employee_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `integrations_employee_id_foreign` (`employee_id`),
  CONSTRAINT `integrations_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `invitations` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `annuaire_id` bigint(20) UNSIGNED NOT NULL,
  `evenement_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,

```

```

`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

CREATE TABLE `perfectionnements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,
  `typesperfectionement_id` bigint(20) UNSIGNED DEFAULT NULL,
  `employee_id` bigint(20) UNSIGNED DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `perfectionnements_employee_id_foreign` (`employee_id`),
  CONSTRAINT `perfectionnements_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `typesperfectionnements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 5. MODULE PAIE
-- =====

```

```

CREATE TABLE `gpaies` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `affectation_id` bigint(20) UNSIGNED NOT NULL COMMENT 'employee_id',
  `periode` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `date_paiement` date DEFAULT NULL,
  `salaire_base` double(8,2) DEFAULT 0.00,

```

```

`primes` double(8,2) DEFAULT 0.00,
`cotisations` double(8,2) DEFAULT 0.00,
`net_a_payer` double(8,2) DEFAULT 0.00,
`fichiersjoin` text COLLATE utf8mb4_unicode_ci COMMENT 'bulletin PDF',
`statut` int(11) DEFAULT 0 COMMENT '0=brouillon, 1=validé, 2=payé',
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `gpaies_affectation_id_foreign` (`affectation_id`),
CONSTRAINT `gpaies_affectation_id_foreign` FOREIGN KEY (`affectation_id`) REFERENCES
`employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `rubriques` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `gpaie_id` bigint(20) UNSIGNED NOT NULL,
  `field1` bigint(20) UNSIGNED NOT NULL COMMENT 'rubrique_id source',
  `field2` bigint(20) UNSIGNED NOT NULL COMMENT 'rubrique_id source',
  `opérateur` varchar(50) COLLATE utf8mb4_unicode_ci NOT NULL COMMENT '+, -, *, /',
  `types` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL COMMENT 'gain, retenue,
info',
  `base` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `rubriques_gpaie_id_foreign` (`gpaie_id`),
CONSTRAINT `rubriques_gpaie_id_foreign` FOREIGN KEY (`gpaie_id`) REFERENCES `gpaies`
(`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `payementglobals` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `types` text COLLATE utf8mb4_unicode_ci,
  `gpaie_id` bigint(20) UNSIGNED NOT NULL,
  `debut` datetime DEFAULT NULL,

```

```

`fin` datetime DEFAULT NULL,
`montant_total` double(8,2) DEFAULT 0.00,
`fichiersjoin` text COLLATE utf8mb4_unicode_ci,
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `payementglobals_gpaie_id_foreign` (`gpaie_id`),
CONSTRAINT `payementglobals_gpaie_id_foreign` FOREIGN KEY (`gpaie_id`) REFERENCES
`gpaies` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `payements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `payementglobal_id` bigint(20) UNSIGNED NOT NULL,
  `affectation_id` bigint(20) UNSIGNED NOT NULL COMMENT 'employee_id',
  `montant` double(8,2) DEFAULT 0.00,
  `mode_paiement` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `payements_payementglobal_id_foreign` (`payementglobal_id`),
  KEY `payements_affectation_id_foreign` (`affectation_id`),
  CONSTRAINT `payements_payementglobal_id_foreign` FOREIGN KEY (`payementglobal_id`)
REFERENCES `payementglobals` (`id`) ON DELETE CASCADE,
  CONSTRAINT `payements_affectation_id_foreign` FOREIGN KEY (`affectation_id`)
REFERENCES `employees` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 6. MODULE ACHAT & MOYENS GÉNÉRAUX
-- =====

```

```

CREATE TABLE `types` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `bannieres` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,

```

```

`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `produits` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `noms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `reference` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `bannieres` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `type_id` bigint(20) UNSIGNED NOT NULL,
  `pricedeachat` double(8,2) NOT NULL DEFAULT 0.00,
  `pricedevente` double(8,2) NOT NULL DEFAULT 0.00,
  `stock_min` int(11) DEFAULT 0,
  `stock_actuel` int(11) DEFAULT 0,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `produits_type_id_foreign` (`type_id`),
  CONSTRAINT `produits_type_id_foreign` FOREIGN KEY (`type_id`) REFERENCES `types` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `attributs` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `key` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `value` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `produit_id` bigint(20) UNSIGNED NOT NULL,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `attributs_produit_id_foreign` (`produit_id`),
  CONSTRAINT `attributs_produit_id_foreign` FOREIGN KEY (`produit_id`) REFERENCES `produits` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `fournisseurs` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,

```

```

`libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`description` text COLLATE utf8mb4_unicode_ci,
`contact` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`email` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`telephone` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`adresse` text COLLATE utf8mb4_unicode_ci,
`rib` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`nif` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `fournisseursdetails` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `key` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `value` text COLLATE utf8mb4_unicode_ci,
  `fournisseur_id` bigint(20) UNSIGNED DEFAULT NULL,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `fournisseursdetails_fournisseur_id_foreign` (`fournisseur_id`),
  CONSTRAINT `fournisseursdetails_fournisseur_id_foreign` FOREIGN KEY (`fournisseur_id`)
REFERENCES `fournisseurs` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `approvisionnements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `fournisseur_id` bigint(20) UNSIGNED DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `statut` int(11) DEFAULT 0 COMMENT '0=brouillon, 1=soumis, 2=validé, 3=livré',
  `montant_total` double(8,2) DEFAULT 0.00,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),

```

```

KEY `approvisionements_fournisseur_id_foreign` (`fournisseur_id`),
CONSTRAINT `approvisionements_fournisseur_id_foreign` FOREIGN KEY (`fournisseur_id`)
REFERENCES `fournisseurs` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `approvisionementsproduits` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `produit_id` bigint(20) UNSIGNED NOT NULL,
  `approvisionnement_id` bigint(20) UNSIGNED NOT NULL,
  `quantite` int(11) NOT NULL,
  `prix_unitaire` double(8,2) DEFAULT 0.00,
  `montant_total` double(8,2) DEFAULT 0.00,
  `quantite_recue` int(11) DEFAULT 0,
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `approvisionementsproduits_produit_id_foreign` (`produit_id`),
  KEY `approvisionementsproduits_approvisionnement_id_foreign` (`approvisionnement_id`),
  CONSTRAINT `approvisionementsproduits_produit_id_foreign` FOREIGN KEY (`produit_id`)
REFERENCES `produits` (`id`),
  CONSTRAINT `approvisionementsproduits_approvisionnement_id_foreign` FOREIGN KEY
(`approvisionnement_id`) REFERENCES `approvisionements` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `commandesfournisseurs` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `organisation_id` bigint(20) UNSIGNED NOT NULL,
  `fournisseur_id` bigint(20) UNSIGNED DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 0,
  `montant_total` double(8,2) DEFAULT 0.00,
  `date_commande` date DEFAULT NULL,
  `date_livraison_prevue` date DEFAULT NULL,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `commandesfournisseurs_organisation_id_foreign` (`organisation_id`),
  KEY `commandesfournisseurs_fournisseur_id_foreign` (`fournisseur_id`),

```



```

    CONSTRAINT `commandesfournisseurs_organisation_id_foreign` FOREIGN KEY
(`organisation_id`) REFERENCES `organisations` (`id`),
    CONSTRAINT `commandesfournisseurs_fournisseur_id_foreign` FOREIGN KEY
(`fournisseur_id`) REFERENCES `fournisseurs` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `commandesfournisseursproduits` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `produit_id` bigint(20) UNSIGNED NOT NULL,
  `commandesfournisseur_id` bigint(20) UNSIGNED NOT NULL,
  `quantite` int(11) NOT NULL,
  `prix_unitaire` double(8,2) DEFAULT 0.00,
  `montant_total` double(8,2) DEFAULT 0.00,
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `commandesfournisseursproduits_produit_id_foreign` (`produit_id`),
  KEY `commandesfournisseursproduits_commandesfournisseur_id_foreign`
(`commandesfournisseur_id`),
  CONSTRAINT `commandesfournisseursproduits_produit_id_foreign` FOREIGN KEY
(`produit_id`) REFERENCES `produits` (`id`),
  CONSTRAINT `commandesfournisseursproduits_commandesfournisseur_id_foreign`
FOREIGN KEY (`commandesfournisseur_id`) REFERENCES `commandesfournisseurs` (`id`) ON
DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `commandesclients` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `client_id` bigint(20) UNSIGNED DEFAULT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 0,
  `montant_total` double(8,2) DEFAULT 0.00,
  `date_commande` date DEFAULT NULL,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `commandesclientsproduits` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `produit_id` bigint(20) UNSIGNED NOT NULL,
  `commandesclient_id` bigint(20) UNSIGNED NOT NULL,
  `quantite` int(11) NOT NULL,
  `prix_unitaire` double(8,2) DEFAULT 0.00,
  `montant_total` double(8,2) DEFAULT 0.00,
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `commandesclientsproduits_produit_id_foreign` (`produit_id`),
  KEY `commandesclientsproduits_commandesclient_id_foreign` (`commandesclient_id`),
  CONSTRAINT `commandesclientsproduits_produit_id_foreign` FOREIGN KEY (`produit_id`)
REFERENCES `produits` (`id`),
  CONSTRAINT `commandesclientsproduits_commandesclient_id_foreign` FOREIGN KEY
(`commandesclient_id`) REFERENCES `commandesclients` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `livraisonsfournisseurs` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `commandesfournisseur_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `livraisonsfournisseurs_commandesfournisseur_id_foreign`
(`commandesfournisseur_id`),
  CONSTRAINT `livraisonsfournisseurs_commandesfournisseur_id_foreign` FOREIGN KEY
(`commandesfournisseur_id`) REFERENCES `commandesfournisseurs` (`id`) ON DELETE
CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `livraisonsfournisseursproduits` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,

```

```

`produit_id` bigint(20) UNSIGNED NOT NULL,
`livraisonsfournisseur_id` bigint(20) UNSIGNED NOT NULL,
`quantite` int(11) NOT NULL,
`quantite_recue` int(11) DEFAULT 0,
`statut` int(11) DEFAULT 0,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `livraisonsfournisseursproduits_produit_id_foreign` (`produit_id`),
KEY `livraisonsfournisseursproduits_livraisonsfournisseur_id_foreign`
(`livraisonsfournisseur_id`),
CONSTRAINT `livraisonsfournisseursproduits_produit_id_foreign` FOREIGN KEY
(`produit_id`) REFERENCES `produits` (`id`),
CONSTRAINT `livraisonsfournisseursproduits_livraisonsfournisseur_id_foreign` FOREIGN
KEY (`livraisonsfournisseur_id`) REFERENCES `livraisonsfournisseurs` (`id`) ON DELETE
CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `livraisonsclients` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `commandesclient_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `statut` int(11) DEFAULT 0,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `livraisonsclients_commandesclient_id_foreign` (`commandesclient_id`),
  CONSTRAINT `livraisonsclients_commandesclient_id_foreign` FOREIGN KEY
(`commandesclient_id`) REFERENCES `commandesclients` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `livraisonsclientsproduits` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `produit_id` bigint(20) UNSIGNED NOT NULL,
  `livraisonsclient_id` bigint(20) UNSIGNED NOT NULL,
  `quantite` int(11) NOT NULL,
  `statut` int(11) DEFAULT 0,

```

```

`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `livraisonsclientsproduits_produit_id_foreign` (`produit_id`),
KEY `livraisonsclientsproduits_livraisonsclient_id_foreign` (`livraisonsclient_id`),
CONSTRAINT `livraisonsclientsproduits_produit_id_foreign` FOREIGN KEY (`produit_id`)
REFERENCES `produits` (`id`),
CONSTRAINT `livraisonsclientsproduits_livraisonsclient_id_foreign` FOREIGN KEY
(`livraisonsclient_id`) REFERENCES `livraisonsclients` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `imobilisations` (
`id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
`noms` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`references` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`bannieres` text COLLATE utf8mb4_unicode_ci,
`description` text COLLATE utf8mb4_unicode_ci,
`pricedachat` double(8,2) NOT NULL DEFAULT 0.00,
`date_acquisition` date DEFAULT NULL,
`duree_amortissement` int(11) DEFAULT NULL COMMENT 'en mois',
`mode_amortissement` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`localisation` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`responsable_id` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'user_id',
`statut` int(11) DEFAULT 1 COMMENT '1=en service, 2=hors service, 3=sorti',
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `imobilisations_responsable_id_foreign` (`responsable_id`),
CONSTRAINT `imobilisations_responsable_id_foreign` FOREIGN KEY (`responsable_id`)
REFERENCES `users` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `imobilisationsdetails` (
`id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
`key` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`value` text COLLATE utf8mb4_unicode_ci NOT NULL,
`imobilisation_id` bigint(20) UNSIGNED DEFAULT NULL,
`statut` int(11) DEFAULT 1,
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),

```

```

KEY `imobilisationsdetails_imobilisation_id_foreign` (`imobilisation_id`),
CONSTRAINT `imobilisationsdetails_imobilisation_id_foreign` FOREIGN KEY
(`imobilisation_id`) REFERENCES `imobilisations` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `imobilisationsentretiens` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `imobilisation_id` bigint(20) UNSIGNED DEFAULT NULL,
  `periodelabel` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `periodevalue` int(11) DEFAULT NULL COMMENT 'fréquence en jours',
  `dernier_entretien` date DEFAULT NULL,
  `prochain_entretien` date DEFAULT NULL,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `imobilisationsentretiens_imobilisation_id_foreign` (`imobilisation_id`),
  CONSTRAINT `imobilisationsentretiens_imobilisation_id_foreign` FOREIGN KEY
(`imobilisation_id`) REFERENCES `imobilisations` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `imobilisationsentretiensusers` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `imobilisationsentretien_id` bigint(20) UNSIGNED DEFAULT NULL,
  `users` bigint(20) UNSIGNED DEFAULT NULL,
  `date_entretien` date DEFAULT NULL,
  `cout` double(8,2) DEFAULT 0.00,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `imobilisationsentretiensusers_imobilisationsentretien_id_foreign`
(`imobilisationsentretien_id`),
  KEY `imobilisationsentretiensusers_users_foreign` (`users`),
  CONSTRAINT `imobilisationsentretiensusers_imobilisationsentretien_id_foreign` FOREIGN
KEY (`imobilisationsentretien_id`) REFERENCES `imobilisationsentretiens` (`id`) ON DELETE
CASCADE,
  CONSTRAINT `imobilisationsentretiensusers_users_foreign` FOREIGN KEY (`users`)
REFERENCES `users` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `typesdisfonctionnements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,
  `categorie` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT NULL COMMENT 'materiel, logiciel, processus',
  `niveau_critique` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT 'moyen',
  `delai_traitement_requis` int(11) DEFAULT NULL COMMENT 'en heures',
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `disfonctionnements` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,
  `typesdisfonctionnement_id` bigint(20) UNSIGNED DEFAULT NULL,
  `imobilisation_id` bigint(20) UNSIGNED DEFAULT NULL,
  `declare_par` bigint(20) UNSIGNED DEFAULT NULL COMMENT 'user_id',
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `date_declaration` datetime DEFAULT CURRENT_TIMESTAMP,
  `statut` int(11) DEFAULT 0 COMMENT '0=nouveau, 1=en traitement, 2=résolu, 3=clôturé',
  `priorite` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT 'moyenne',
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `disfonctionnements_typesdisfonctionnement_id_foreign` (`typesdisfonctionnement_id`),
  KEY `disfonctionnements_imobilisation_id_foreign` (`imobilisation_id`),
  KEY `disfonctionnements_declare_par_foreign` (`declare_par`),
  CONSTRAINT `disfonctionnements_typesdisfonctionnement_id_foreign` FOREIGN KEY (`typesdisfonctionnement_id`) REFERENCES `typesdisfonctionnements` (`id`) ON DELETE SET NULL,
  CONSTRAINT `disfonctionnements_imobilisation_id_foreign` FOREIGN KEY (`imobilisation_id`) REFERENCES `imobilisations` (`id`) ON DELETE SET NULL,
  CONSTRAINT `disfonctionnements_declare_par_foreign` FOREIGN KEY (`declare_par`) REFERENCES `users` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `interventions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `libelle` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `description` text COLLATE utf8mb4_unicode_ci,

```

```

`disfonctionnement_id` bigint(20) UNSIGNED DEFAULT NULL,
`intervenants` text COLLATE utf8mb4_unicode_ci COMMENT 'user_ids JSON',
`fichiersjoin` text COLLATE utf8mb4_unicode_ci,
`date_debut` datetime DEFAULT NULL,
`date_fin` datetime DEFAULT NULL,
`cout` double(8,2) DEFAULT 0.00,
`statut` int(11) DEFAULT 0 COMMENT '0=planifié, 1=en cours, 2=terminé',
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `interventions_disfonctionnement_id_foreign` (`disfonctionnement_id`),
CONSTRAINT `interventions_disfonctionnement_id_foreign` FOREIGN KEY
(`disfonctionnement_id`) REFERENCES `disfonctionnements` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `attributions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `imobilisation_id` bigint(20) UNSIGNED DEFAULT NULL,
  `users` bigint(20) UNSIGNED DEFAULT NULL,
  `employee_id` bigint(20) UNSIGNED DEFAULT NULL,
  `debut` datetime DEFAULT NULL,
  `fin` datetime DEFAULT NULL,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `attributions_imobilisation_id_foreign` (`imobilisation_id`),
  KEY `attributions_users_foreign` (`users`),
  KEY `attributions_employee_id_foreign` (`employee_id`),
  CONSTRAINT `attributions_imobilisation_id_foreign` FOREIGN KEY (`imobilisation_id`)
REFERENCES `imobilisations` (`id`) ON DELETE SET NULL,
  CONSTRAINT `attributions_users_foreign` FOREIGN KEY (`users`) REFERENCES `users` (`id`)
ON DELETE SET NULL,
  CONSTRAINT `attributions_employee_id_foreign` FOREIGN KEY (`employee_id`)
REFERENCES `employees` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 7. WORKFLOWS & VALIDATIONS
-- =====

```

```

CREATE TABLE `validations` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,

```

```

`table` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`record_id` bigint(20) UNSIGNED DEFAULT NULL,
`etapes` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`validateurs` text COLLATE utf8mb4_unicode_ci NOT NULL COMMENT 'user_ids JSON',
`rangs` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`iseditable` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`childiseditable` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`depends` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`statut` int(11) DEFAULT 0 COMMENT '0=en attente, 1=validé, 2=rejeté',
`extra_attributes` json DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `allresources` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `resource_type` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `resource_id` bigint(20) UNSIGNED NOT NULL,
  `extra_attributes` json DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `resourcespipelines` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `allresource_id` bigint(20) UNSIGNED DEFAULT NULL,
  `pipelines` text COLLATE utf8mb4_unicode_ci NOT NULL COMMENT 'workflow steps JSON',
  `extra_attributes` json DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `resourcespipelines_allresource_id_foreign` (`allresource_id`),
  CONSTRAINT `resourcespipelines_allresource_id_foreign` FOREIGN KEY (`allresource_id`)
REFERENCES `allresources` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `resourcesprogressions` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `resourcespipeline_id` bigint(20) UNSIGNED DEFAULT NULL,
  `validateurs` text COLLATE utf8mb4_unicode_ci COMMENT 'user_ids JSON',
  `etats` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `steps` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,

```



```

`messages` text COLLATE utf8mb4_unicode_ci,
`statut` int(11) DEFAULT 0,
`extra_attributes` json DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
`deleted_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `resourcesprogressions_resourcespipeline_id_foreign` (`resourcespipeline_id`),
CONSTRAINT `resourcesprogressions_resourcespipeline_id_foreign` FOREIGN KEY
(`resourcespipeline_id`) REFERENCES `resourcespipelines` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 8. FICHIERS & DONNÉES GÉNÉRALES
-- =====

```

```

CREATE TABLE `files` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `old_name` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `new_name` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `descriptions` text COLLATE utf8mb4_unicode_ci,
  `extensions` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `size` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `path` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `web_path` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `mime_type` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `uploaded_by` bigint(20) UNSIGNED DEFAULT NULL,
  `status` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `files_uploaded_by_foreign` (`uploaded_by`),
  CONSTRAINT `files_uploaded_by_foreign` FOREIGN KEY (`uploaded_by`) REFERENCES
`users` (`id`) ON DELETE SET NULL
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `booles` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `key` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `value` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`)

```

```
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `extras` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `libelle` text COLLATE utf8mb4_unicode_ci NOT NULL,  
  `text` text COLLATE utf8mb4_unicode_ci NOT NULL,  
  `files` text COLLATE utf8mb4_unicode_ci NOT NULL,  
  `textarea` text COLLATE utf8mb4_unicode_ci NOT NULL,  
  `datetime` text COLLATE utf8mb4_unicode_ci NOT NULL,  
  `extra_attributes` json DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)
```

```
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `cruds` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `models` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `model_id` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `users` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `actions` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `data_first` text COLLATE utf8mb4_unicode_ci,  
  `data_end` text COLLATE utf8mb4_unicode_ci,  
  `extra_attributes` json DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)
```

```
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `models` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `extra_attributes` json DEFAULT NULL,  
  `created_at` timestamp NULL DEFAULT NULL,  
  `updated_at` timestamp NULL DEFAULT NULL,  
  `deleted_at` timestamp NULL DEFAULT NULL,  
  PRIMARY KEY (`id`)
```

```
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `apis` (  
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,  
  `url` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `label` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `value` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,  
  `method` varchar(50) COLLATE utf8mb4_unicode_ci DEFAULT 'GET',  
  `extra_attributes` json DEFAULT NULL,
```

```

`deleted_at` timestamp NULL DEFAULT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 9. TEAMS (OPTIONNEL - Laravel Jetstream)
-- =====

```

```

CREATE TABLE `teams` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `user_id` bigint(20) UNSIGNED NOT NULL,
  `name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `personal_team` tinyint(1) NOT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `teams_user_id_index` (`user_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `team_user` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `team_id` bigint(20) UNSIGNED NOT NULL,
  `user_id` bigint(20) UNSIGNED NOT NULL,
  `role` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `team_user_team_id_user_id_unique` (`team_id`,`user_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE `team_invitations` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `team_id` bigint(20) UNSIGNED NOT NULL,
  `email` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `role` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `team_invitations_team_id_email_unique` (`team_id`,`email`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

-- =====
-- 10. ORGANISATION EXTRAS

```

```
-- =====
CREATE TABLE `organisationsextras` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `key` text COLLATE utf8mb4_unicode_ci,
  `value` text COLLATE utf8mb4_unicode_ci,
  `organisation_id` bigint(20) UNSIGNED NOT NULL,
  `fichiersjoin` text COLLATE utf8mb4_unicode_ci,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `organisationsextras_organisation_id_foreign` (`organisation_id`),
  CONSTRAINT `organisationsextras_organisation_id_foreign` FOREIGN KEY
(`organisation_id`) REFERENCES `organisations` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE `organisationsprivileges` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `label` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `introduction` text COLLATE utf8mb4_unicode_ci,
  `description` text COLLATE utf8mb4_unicode_ci,
  `organisation_id` bigint(20) UNSIGNED NOT NULL,
  `privilege_type` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `statut` int(11) DEFAULT 1,
  `extra_attributes` json DEFAULT NULL,
  `deleted_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `organisationsprivileges_organisation_id_foreign` (`organisation_id`),
  CONSTRAINT `organisationsprivileges_organisation_id_foreign` FOREIGN KEY
(`organisation_id`) REFERENCES `organisations` (`id`) ON DELETE CASCADE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

-- 11. INDEXES SUPPLÉMENTAIRES & CONTRAINTES

```
-- Indexes pour les tables OAuth (Laravel Passport)
CREATE TABLE IF NOT EXISTS `oauth_access_tokens` (
  `id` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
```

```

`user_id` bigint(20) UNSIGNED DEFAULT NULL,
`client_id` bigint(20) UNSIGNED NOT NULL,
`name` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
`scopes` text COLLATE utf8mb4_unicode_ci,
`revoked` tinyint(1) NOT NULL,
`created_at` timestamp NULL DEFAULT NULL,
`updated_at` timestamp NULL DEFAULT NULL,
`expires_at` datetime DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `oauth_access_tokens_user_id_index` (`user_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE IF NOT EXISTS `oauth_auth_codes` (
  `id` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
  `user_id` bigint(20) UNSIGNED NOT NULL,
  `client_id` bigint(20) UNSIGNED NOT NULL,
  `scopes` text COLLATE utf8mb4_unicode_ci,
  `revoked` tinyint(1) NOT NULL,
  `expires_at` datetime DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `oauth_auth_codes_user_id_index` (`user_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE IF NOT EXISTS `oauth_clients` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `user_id` bigint(20) UNSIGNED DEFAULT NULL,
  `name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `secret` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `provider` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
  `redirect` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `personal_access_client` tinyint(1) NOT NULL,
  `password_client` tinyint(1) NOT NULL,
  `revoked` tinyint(1) NOT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`),
KEY `oauth_clients_user_id_index` (`user_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```

CREATE TABLE IF NOT EXISTS `oauth_personal_access_clients` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `client_id` bigint(20) UNSIGNED NOT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;

```

```
CREATE TABLE IF NOT EXISTS `oauth_refresh_tokens` (
  `id` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
  `access_token_id` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
  `revoked` tinyint(1) NOT NULL,
  `expires_at` datetime DEFAULT NULL,
  PRIMARY KEY (`id`),
  KEY `oauth_refresh_tokens_access_token_id_index` (`access_token_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE IF NOT EXISTS `personal_access_tokens` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `tokenable_type` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `tokenable_id` bigint(20) UNSIGNED NOT NULL,
  `name` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `token` varchar(64) COLLATE utf8mb4_unicode_ci NOT NULL,
  `abilities` text COLLATE utf8mb4_unicode_ci,
  `last_used_at` timestamp NULL DEFAULT NULL,
  `expires_at` timestamp NULL DEFAULT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `personal_access_tokens_token_unique` (`token`),
  KEY `personal_access_tokens_tokenable_type_tokenable_id_index`
  (`tokenable_type`,`tokenable_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE IF NOT EXISTS `password_resets` (
  `email` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `token` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `created_at` timestamp NULL DEFAULT NULL,
  KEY `password_resets_email_index` (`email`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE IF NOT EXISTS `failed_jobs` (
  `id` bigint(20) UNSIGNED NOT NULL AUTO_INCREMENT,
  `uuid` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
  `connection` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `queue` text COLLATE utf8mb4_unicode_ci NOT NULL,
  `payload` longtext COLLATE utf8mb4_unicode_ci NOT NULL,
  `exception` longtext COLLATE utf8mb4_unicode_ci NOT NULL,
  `failed_at` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY (`id`),
  UNIQUE KEY `failed_jobs_uuid_unique` (`uuid`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

```
CREATE TABLE IF NOT EXISTS `migrations` (
  `id` int(10) UNSIGNED NOT NULL AUTO_INCREMENT,
```

```
`migration` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
`batch` int(11) NOT NULL,
PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
```

COMMIT;

```
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
```
```

## ## 📄 Résumé de la Base de Données

### ### Modules Inclus

| Module           | Tables Principales                                              | Nombre de Tables |
|------------------|-----------------------------------------------------------------|------------------|
| **Système**      | users, roles, permissions, logs, sessions                       | 10               |
| **Géographique** | pays, regions, localites, arrondissements, quartiers            | 6                |
| **Finance**      | exercices, titres, lignes, budget_lignes, comptes, grand_livres | 10               |
| **RH**           | employees, absences, competences, qualifications, recrutements  | 25               |
| **Paie**         | gpaies, rubriques, paiements, paiementglobals                   | 5                |
| **Achat**        | produits, fournisseurs, approvisionnements, commandes           | 15               |
| **MG**           | imobilisations, disfonctionnements, interventions, attributions | 10               |
| **Workflow**     | validations, ressourcespipelines, ressourcesprogressions        | 3                |
| **Général**      | files, extras, booles, organisations                            | 10               |
| <b>Total</b>     | <b>~94 tables</b>                                               |                  |

### ### Relations Clés

- \*\*users\*\* ↔ \*\*employees\*\* (1:1)
- \*\*employees\*\* ↔ \*\*absences, competences, qualifications\*\* (1:N)
- \*\*organisations\*\* ↔ \*\*commandesfournisseurs\*\* (1:N)
- \*\*fournisseurs\*\* ↔ \*\*approvisionnements\*\* (1:N)
- \*\*produits\*\* ↔ \*\*approvisionnementproduits\*\* (1:N)
- \*\*imobilisations\*\* ↔ \*\*disfonctionnements, interventions\*\* (1:N)
- \*\*exercices\*\* ↔ \*\*budget\_lignes\*\* (1:N)
- \*\*comptes\*\* ↔ \*\*grand\_livres\*\* (1:N)

### ### Fonctionnalités Couvertes

- ✅ Gestion des utilisateurs et permissions (RBAC)
- ✅ Géolocalisation complète (Pays → Quartiers)
- ✅ Budget et comptabilité
- ✅ Paie et rémunération
- ✅ Recrutement et candidats

- ✓ Gestion des absences et congés
- ✓ Approvisionnements et stocks
- ✓ Commandes fournisseurs et clients
- ✓ Immobilisations et maintenance
- ✓ Dysfonctionnements et interventions
- ✓ Workflows de validation multi-niveaux
- ✓ Journalisation et traçabilité
- ✓ Gestion des fichiers

Ce script SQL est prêt à être exécuté sur MySQL 5.7+ ou adapté pour PostgreSQL.