
Two networks. One control plane.

Fixed access and mobile access are managed by two disjoint toolchains, two data models and two on-call rotations. Aether puts them behind one.

10 PROTOCOLS · ONE BINARY · SELF-HOSTED · OPEN AGENT

THE PROBLEM

The access network is managed twice.

Every operator runs both of these. Almost nobody runs them from one place.

CPE / WiFi

- uCentral · TIP OpenWiFi
- TR-369 / USP
- WRP · RDK-B
- IEEE 1905.1 EasyMesh
- OpenSync

BROADBAND TEAM

Transport / RAN

- NETCONF + YANG
- SNMP v1/v2c/v3
- gNMI streaming
- O-RAN A1 policy
- VES event collector

RAN + TRANSPORT TEAM

When a subscriber says “my connection is bad” —

no single system can see the home, the backhaul and the radio.

PROTOCOL COVERAGE

Ten protocols. One binary.

uCentral / TIP	WebSocket + JSON · OpenWiFi, OpenWrt
TR-369 / USP	WebSocket + MQTT · protobuf · QSDK, prpIOS
WRP / Xmidt	RDk-B, zero-install via Parodus
IEEE 1905.1	EtherType 0x893a · CMDU · EasyMesh R1–R5
OpenSync	MQTT · Plume migration path
MQTT	3.1 / 5.0 clustered broker · USP MTP
NETCONF / YANG	SSH + XML · RFC 6241 / 6242
SNMP	v1 / v2c / v3 · polling + traps
gNMI	gRPC + protobuf · OpenConfig telemetry
O-RAN A1 / VES	A1 policy → Near-RT RIC · VES collector

ABOVE THE LINE: CPE. BELOW: TRANSPORT, BACKHAUL AND RAN.

PRECISION

Aether is not a RIC. Here is what it is.

IS

- An A1 client — pushes policy toward a Near-RT RIC
- A VES collector — emits events into ONAP-style OSS
- One normalized data model across CPE, transport and RAN
- Self-hosted on your Kubernetes, via Helm

IS NOT

- An xApp or rApp hosting platform
- A Near-RT or Non-RT RIC implementation
- A replacement for your RAN vendor's EMS
- A SaaS that ingests your subscriber data

The hard part was never A1. It was a data model where a TR-181 parameter from an OpenWrt box and a gNMI subscription from an aggregation switch are both first-class.

DEPLOYMENT

Meet the device where it is.

No reflash. No certification cycle. No truck roll.

- **RDK-B**
Terminates the Parodus/WRP session already running.
No firmware change.
- **OpenWrt**
opkg package install. 30k+ router models.
- **QSDK**
Agent wrapping cfg80211tool and qca-hostapd.
- **prpIOS**
Speaks the TR-181 data model bus already present.
- **OpenWiFi**
Native uCentral client.
- **Aggregation gear**
NETCONF or gNMI. SNMP for anything older.

Config changes ship as JSON Patch (RFC 6902)

~200 bytes per update, not a ~50 KB full-config push.



Looking for a few design partners.

Best fit: a messy access network. Multiple CPE silicon vendors, a platform inherited from an acquisition, aggregation gear still on SNMP, and a RAN team you'd like to stop emailing spreadsheets to.

- Founding-partner pricing, locked for the life of the contract
- Direct input on roadmap priority
- Our engineering time on your specific protocol mix

aether-io.com

Running today · Early access · Not a sales process

OPTIM ENTERPRISES BV