

This document was generated on 01/07/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 2171770001

Status: **Active**

Overview: USB Connectors: USB Type-A, USB Type-B, and USB Type-C Plugs and Receptacles Universal Serial Bus (USB) Shielded I/O Receptacle, Type C, Right-Angle, Surface **Description:**

Mount, Mid-Mount, Waterproof IPx5, 6 Circuits, Gold (Au) Plating

Documents:

Packaging Specification 2171770001-PK1 (PDF) 3D Model

3D Model (PDF) Datasheet (PDF)

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification 2171760001-PS (PDF)

General

I/O Connectors **Product Family** Series 217177 Application Wire-to-Board Component Type Receptacle

USB Connectors: USB Type-A, USB Type-B, and USB Overview

Type-C Plugs and Receptacles

Product Name USB USB 2.0 Standard С

Type

UPC 195842116832

Physical

Circuits (Loaded) 6 Circuits (maximum) 6 Black Color - Resin Durability (mating cycles max) 10000 Gender Female Keying to Mating Part None

Lock to Mating Part Yes Material - Metal Copper Alloy

Material - Plating Mating Gold

Material - Resin Liquid Crystal Polymer

Mid-Mount Mounting Style Net Weight 0.720/qNumber of Rows

Orientation Right Angle **PCB** Locator Yes Yes **PCB** Retention PCB Thickness - Recommended 0.60mm

Embossed Tape on Reel Packaging Type

Panel Mount Yes Pitch - Mating Interface 0.50mm Pitch - Termination Interface 0.50mm Plating min - Mating 0.025µm Polarized to Mating Part No Polarized to PCB No Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -40° to +85°C Termination Interface: Style Surface Mount

Waterproof / Dustproof Yes Waterproof / Dustproof Type IPx5

Electrical

Current - Maximum per Contact 1.25A



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant **REACH SVHC**

Not Contained Per -D(2021)4569-DC (8

July 2021) **Halogen-Free Status**

Low-Halogen For more information, please visit Contact US

China ROHS Green Image ELV Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

217177 Series

Mates With

USB Type C Plug/Cable

Grounding to Panel None
Shield Type Full Shield
Shielded Yes
Voltage - Maximum 30V AC/DC

Material Info

Reference - Drawing Numbers

Packaging Specification 2171770001-PK1
Product Specification 2171760001-PS
Sales Drawing 2171770001-000

This document was generated on 01/07/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION