

# Evaluation Report on Twelve Experiments

Anne Anonymous

**Abstract**—This is the evaluation report on twelve experiments, namely P-DCN, holtschulte2013\_ga100, holtschulte2013\_hill, hutter2013\_CMAES, liao2013\_IPOP, liao2013\_IPOP-500, liao2013\_IPOP-tany, liao2013\_IPOP-texp, pal2013\_DE, pal2013\_HMLSL, pal2013\_fmincon, and pal2013\_simplex on 144 benchmark instances. This report has been generated with the version 0.8.4 of the Evaluator Component of the Optimization Benchmarking Tool Suite.

## I. PERFORMANCE COMPARISONS

### A. Estimated Cumulative Distribution Function

We analyze the estimated cumulative distribution function (*ECDF*) [1], [2], [3] of  $F$  over  $\log_{10} FEs$ . The  $ECDF(FEs, F \leq 1.E-8)$  represents the fraction of runs which reach a value of  $F$  less than or equal to  $1.E-8$  for a given elapsed runtime measured in  $FEs$ . The *ECDF* is always computed over the runs of an experiment for a given benchmark instance. If runs for multiple instances are available, we aggregate the results by computing their arithmetic mean. The x-axis does not represent the values of  $FEs$  directly, but instead  $\log_{10} FEs$ . The *ECDF* is always between 0 and 1 — and the higher it is, the better.

The corresponding plot is illustrated in Figure 1.

### B. Estimated Cumulative Distribution Function

We analyze the estimated cumulative distribution function (*ECDF*) [1], [2], [3] of  $F$  over  $\log_{10} FEs$ . The  $ECDF(FEs, F \leq 1.E-8)$  represents the fraction of runs which reach a value of  $F$  less than or equal to  $1.E-8$  for a given elapsed runtime measured in  $FEs$ . The *ECDF* is always computed over the runs of an experiment for a given benchmark instance. If runs for multiple instances are available, we aggregate the results by computing their arithmetic mean. The x-axis does not represent the values of  $FEs$  directly, but instead  $\log_{10} FEs$ . The *ECDF* is always between 0 and 1 — and the higher it is, the better. The instance run sets belonging to instances with the same value of the feature *dim* grouped together.

The corresponding plots are illustrated in Figure 2.

### C. Estimated Cumulative Distribution Function

We analyze the estimated cumulative distribution function (*ECDF*) [1], [2], [3] of  $F$  over  $\log_{10} FEs$ . The  $ECDF(FEs, F \leq 1.E-5)$  represents the fraction of runs which reach a value of  $F$  less than or equal to  $1.E-5$  for a given elapsed runtime measured in  $FEs$ . The *ECDF* is always computed over the runs of an experiment for a given benchmark instance. If runs for multiple instances are available, we aggregate the results by computing their arithmetic mean. The x-axis does not represent the values of  $FEs$  directly, but instead

$\log_{10} FEs$ . The *ECDF* is always between 0 and 1 — and the higher it is, the better. The instance run sets belonging to instances with the same value of the feature *cond* grouped together.

The corresponding plots are illustrated in Figure 3.

### D. Median of Medians

We analyze the median of medians (*med med*) computed based on  $\log_{10} F$  over  $\log_{10} \left( \frac{FEs}{dim^2} \right)$ . The  $med\ med(FEs, \log_{10} F)$  represents the median of the  $\log_{10} F$  for a given elapsed runtime measured in  $FEs$ . The median is always computed over the runs of an experiment for a given benchmark instance. If runs for multiple instances are available, we aggregate these medians by computing their median. The x-axis does not represent the values of  $FEs$  directly, but instead  $\log_{10} \left( \frac{FEs}{dim^2} \right)$ . The instance run sets belonging to instances with the same value of the feature *sep* grouped together.

The corresponding plots are illustrated in Figure 4.

## REFERENCES

- [1] H. H. Hoos and T. Stützle, “Evaluating las vegas algorithms — pitfalls and remedies,” in *Proceedings of the 14th Conference on Uncertainty in Artificial Intelligence (UAI’98)*, G. F. Cooper and S. Moral, Eds. Madison, WI, USA: San Francisco, CA, USA: Morgan Kaufmann Publishers Inc., Jul. 24–26, 1998, pp. 238–245. [Online]. Available: <http://www.intellektik.informatik.tu-darmstadt.de/TR/1998/98-02.ps.Z>
- [2] D. A. D. Tompkins and H. H. Hoos, “Ubsat: An implementation and experimentation environment for sls algorithms for sat and max-sat,” in *Revised Selected Papers from the Seventh International Conference on Theory and Applications of Satisfiability Testing (SAT’04)*, ser. Lecture Notes in Computer Science (LNCS), H. H. Hoos and D. G. Mitchell, Eds., vol. 3542. Vancouver, BC, Canada: Berlin, Germany: Springer-Verlag GmbH, May 10–13, 2004, pp. 306–320. [Online]. Available: <http://ubcsat.dtompkins.com/downloads/sat04proc-ubcsat.pdf?attredirects=0>
- [3] N. Hansen, A. Auger, S. Finck, and R. Ros, “Real-parameter black-box optimization benchmarking: Experimental setup,” Orsay, France: Université Paris Sud, Institut National de Recherche en Informatique et en Automatique (INRIA) Futurs, Équipe TAO, Tech. Rep., Mar. 24, 2012. [Online]. Available: <http://coco.lri.fr/BBOB-downloads/download11.05/bbobdocexperiment.pdf>