

Split one pre-fork UTXO

A coin created before height 961,640 exists on both Bitcoin (SHA-256d) and the Blake2b Knots chain. A normal signature moves both. Split on Blake2b first with SIGHASH_UNIFIED, then move Bitcoin separately.

DO THIS

Self-send one UTXO on Blake2b with hash type 0x21. Broadcast only to this chain. Confirm. Then spend the same outpoint on Bitcoin.

DO NOT

Spend Bitcoin first with a normal wallet. Broadcast the same hex to both explorers. Use stock Electrum / mempool.space as if they were this chain.

Eight steps

- 01 Confirm you have a pre-fork UTXO**
The output must exist before 961,640. Same txid and vout on both chains. If you never held bitcoin before the split, there is nothing to claim.
- 02 Run two backends, not one wallet view**
Blake2b: Bitcoin Knots 29.4.1.knots20260508 or later. Bitcoin: Core or any SHA-256d node. Do not point the Blake2b wallet at a public Electrum server that stopped at activation.
- 03 Use a wallet that can sign 0x21**
Shrike (Sparrow fork) signs SIGHASH_UNIFIED past activation. Knots' own wallet after 29.4.1 does too. Stock Sparrow does not. Hardware devices need firmware that can emit unified sighash.
- 04 Make a fresh receive address on Blake2b**
New wallet or new account in Shrike. Write the seed offline. This address is only the destination of the split — it does not create coins and it is not protection by itself.
- 05 Self-send that one UTXO on Blake2b**
Coin-control: select only that output. Send to the new address, value minus fee. No extra post-fork inputs. On the send screen the spend must read replay-protected / hash type 0x21. If it signed legacy, stop.
- 06 Broadcast only on the Blake2b chain**
Your Knots node, or mempool.guide. Not mempool.space, not Blockstream, not a Bitcoin-connected Sparrow. Wait for confirmations before touching Bitcoin.
- 07 Check both ledgers**
Blake2b: the split tx confirmed, signature last byte 21, new address funded. Bitcoin: the original outpoint still unspent. If Bitcoin also spent it, the tx replayed.
- 08 Then move the Bitcoin side**
Only after step 7. Self-send the Bitcoin UTXO to a Bitcoin-only address if you want clean books. That spend can be a normal signature.

STOP — do not broadcast

- The send screen says unprotected, signed legacy, or does not show 0x21.
- You are about to paste hex into mempool.space or a Bitcoin Electrum server.
- The UTXO is mixed with an input that only exists on one chain.
- This is the first time you have tried the flow and the amount is not dust.
- A hardware keystore was not marked for unified sighash and Shrike fell back.

Verify after the Blake2b spend

Check	Blake2b (this chain)	Bitcoin (SHA-256d)
Outpoint	Spent by your split tx	Still unspent
New address	Funded	Unchanged / irrelevant
Signature	Last byte 21 (UNIFIED+ALL)	Split tx rejected or absent
Explorer	mempool.guide or your Knots	mempool.space or Core
Node RPC	gettxout empty on that outpoint	gettxout still returns the output

Software that matches this flow

Node	Bitcoin Knots 29.4.1.knots20260508+ from bitcoinknots.org — verify hashes. Core follows the other chain.
Wallet	Shrike (shrikewallet.com / github.com/privkeyio/shrike). Unofficial Sparrow fork. Not audited. Verify SHA256SUMS.
Explorer / broadcast	mempool.guide on Blake2b. mempool.space is Bitcoin. Mixing them is how people replay.
Indexers	electrs or Fulcrum builds with Blake2b / 164-byte header support. Stock servers stop at activation.

FALLBACK ONLY — locktime, if you cannot sign 0x21

Stock Sparrow cannot emit SIGHASH_UNIFIED. Some people set an absolute locktime to a Bitcoin height that Blake2b has already passed (Blake2b is thousands of blocks ahead).

Create the self-send in Sparrow → Details → absolute locktime → copy hex. Do not broadcast from a Bitcoin-connected Sparrow. Push the hex to a Blake2b node or mempool.guide.

After it confirms on Blake2b, the Bitcoin outpoint is still unspent because Bitcoin has not reached that height. Then spend Bitcoin normally.

This is a delay, not a cryptographic split. If the hex is later valid on Bitcoin, it can still land there. Prefer 0x21. Do not use locktime on a large UTXO as your first experiment.

How the split fails

- ✗ Wrong backend — wallet shows history from Bitcoin and broadcasts there.
- ✗ Legacy signature — hardware wallet or unmarked keystore; 0x01 is valid on both chains.
- ✗ Bitcoin spent first — that hex is valid on Blake2b; an indexer can take the fork coins.
- ✗ Exchange deposit as the first move — you do not control which chain they credit.
- ✗ A new address alone — same script format on both chains; protection is the signature.

One-line version

Pre-fork coins exist on both chains. Split on Blake2b first with 0x21. Broadcast only here. Confirm Bitcoin still holds the outpoint. Then move Bitcoin. If the wallet cannot sign 0x21, do not improvise on a large UTXO.