

WebLogic Multitenancy Workshop

Contents

INTRODUCTION:.....	3
Domain Partition:.....	3
Resource Groups:.....	3
Virtual Target:	3
Virtual Box Environment.....	6
The Hands on Lab Environment.....	6
LAB 1: DOMAIN CREATION AND NON-MT CONFIG	7
Overview	7
Start the database.....	7
Create WebLogic Restricted JRF Domain	7
Configuration of WebLogic base_domain.....	9
LAB 2: MULTITENANCY CONFIGURATION.....	13
Overview:.....	13
Configuration of Medrec Application in Domain Partition 1	14
Accessing Medrec Application in Domain Partition dp1.....	34
Configuration of Medrec Application in Domain Partition 2	36
Accessing Medrec Application in Domain Partition dp2.....	37
Configuration of Day Trader application in domain partition 3.....	38
Access Day Trader Application in Domain Partition dp3	39
LAB 3: SECURITY ISOLATION	42
Overview	42

Creating a New Security Realm.....	43
Assign the mynewrealm security realm to domain partition dp1.....	46
Verified that we have two security realms in different domain partition in single domain	47
LAB 4: EXPORT/IMPORT DOMAIN PARTITION	48
Overview	48
Stop and remove domain partition dp1 from base_domain.....	49
Create a new dev single server (Admin Server) domain.....	51
Configure domain for Medrec Application	52
Exporting the domain partition	65
Importing the domain partition.....	66
LAB 5: RESOURCE CONSUMPTION MANAGEMENT	68
Overview	68
Enabling RCM by adding extra arguments in Server JAVA_OPTION Arguments	69
Creating a Resource Manager and Configuring Resource Manager for a domain partition	71
Associate the Resource Manager with Medrec-Dev domain partition.	72
LAB 6: OTD INTEGRATION AND RESOURCE MIGRATION	75
Overview	75
Create OTD Restricted JRF Domain.....	76
Registering an OTD Runtime Instance	84
Creating Domain Partition front ended by OTD	86
Deploying simple application to test OTD integration with weblogic	89
Migration Resource Group from one Cluster to other Cluster	91
Access Application through OTD.....	93
CLEANING AND RESETTING.....	94
Cleaning up Environment.....	94

INTRODUCTION:

Multitenancy in WebLogic Server provides a sharable infrastructure for use by client organizations (tenants). By allowing one domain to support multiple tenants, WLS MT improves density and achieves a more efficient use of resources while eliminating the trade-offs that are traditionally made in a shared environment: Isolation issues. Multitenancy essentially creates the tension between isolation and sharing. Isolation separates both the administration and runtime of different tenants from each other, where resource sharing among tenants improves efficiency and reduces operation costs.

Domain Partition:

WebLogic Server MT provides resource isolation with in domain partitions, an administrative and runtime slice of a WebLogic domain that is dedicated to running application instances and related resources for a tenant. Domain Partition achieve greater density by allowing application instances and related resources to share the domain, WebLogic Server itself, the Java virtual machine, and the operating system while isolating tenant specific application data, configuration, and runtime traffic. Each domain partition has its own runtime copy of the application and resources.

Resource Groups:

WLS MT introduces resource groups, simply as a convenient way to group together Java EE applications and the resources they use into a distinct administrative unit within the domain. The resources and applications are “fully qualified” in that administrator provides all information needed to start or connect to those resources, including credentials for connecting to data source and targeting information for Java EE application. A resource group will either contain these deployable resources directly or refer to a resource group templates which contain the resources. Resource group can be defined at the domain level, or be specific to domain partition.

All the resources in or referenced by a resource group are targeted together (to the same target). Resource group can be started and stopped.


Virtual Target:

Encapsulate where a partition or resource group runs and how to route traffic to them, including addresses, protocol settings, and targeting, Request routing is determined by the host name and optional URI.

May Include:-

- Host name and port
- Optional URI
- Network Access Point or Channel
- Protocol specific configuration
 - T3, IIOP
 - Web Server
- Target Clusters and managed servers

In Multitenant environment, We create Virtual Target first, In previous versions of WebLogic Server, We Targeted our application, system resources (JDBC or JMS Resources) to Clusters, Managed Servers part of Cluster or stand alone managed server. But here we target our resources to Virtual Target. After creation of Virtual Target, we create a domain partition, while creating domain partition we can create resource group. A domain partition can have multiple resource groups. Then we target domain partition to the Virtual Target. Below diagram gives you the picture how they work together.



As in the Above Diagram, We created Virtual target 1, Virtual Target 2 which are Targeted to WebLogic Server. Then we created Two Domain partitions, Domain partition 1 has Resource Group 1 and Domain Partition 2 has Resource Group 2.

To know more about the Multitenancy, you can follow the link [here](#).

We have total 6 Labs; the brief information about each lab is given below.

Lab 1 consist Non MT configuration, in this Lab we create basic configuration required for each lab. First we create **base_domain** using the **Restricted-JRF** template. This is the domain we are using in each lab. Using the Fusion Middleware Control Console, we will create machine and one dynamic cluster of initial size of two managed server inside it.

Lab 2 consist creation of MT configuration, in which we creates virtual target, domain partition and resource group. We show you can easily deploy one application twice in a domain in different domain partition. In this case both applications will be connected to different database. Good thing is that you don't need to modify the application deploying to different domain partition because we have JNDI isolation. We also use day trader application which is build by IBM, we made few changes in the application to run the application in Non MT environment, and we took the same application to deploy in MT environment (inside domain partition). So you don't need any specific application development to deploy the application in Multitenant environment.

Lab3 shows how you can have two or more security realms active inside a domain. Traditionally in WebLogic server, we have more than one Security realm but only one is active for the domain. Here, we have multiple domain partition, so you can have separate security realm for each domain partition. In Lab 2 we deploy Medrec application in domain partition dp1 and dp2. As while creating domain partition dp2 we do not choose any security realm so it uses the default security realm. In Lab 3 we create a new security realm and assign it to domain partition dp1. So both domain partitions will have different set of authorized user.

Lab 4 shows how you can easily move domain partition from one environment to another environment. Generally we work in simple development environment, like no restricted JRF, no cluster. But we need to test our application in testing environment, run in production environment. In Lab 4 we create a dev_domain using a by default templates and it consist only admin server. We do the required configuration for Medrec Application in dev_domain, once we have Medrec application is deployed in domain partition Medrec-Dev in dev_domain, we export the domain and import it in base_domain.

Lab 5 shows how you can configure the resource configuration manager. As the domain partition is targeted to the Virtual target which is targeted to a cluster. So multiple domain partition may be using the same cluster, in that scenario to avoid one partition to use the resources excessively, we set the limit using resource configuration management, we specify the limit for notify, slow and shutdown action. As the resource uses reaches that limit, particular action happens.

Lab 6 shows how you can integrate OTD as a front end in domain partition. It shows the steps how to integrate OTD while creating the domain partition. This Lab also shows you the Resource group migration from one cluster to other cluster. As OTD is front ending your domain partition, so without any interruption you can access the application using the same URL.

You create three domains as part of this workshop. There role are as given:

base_domain: We create this domain as part of Lab 1. This is the main domain which we are using in each lab. We create machine, dynamic cluster and domain partitions.

dev_domain: We create this domain as part of Lab 4. This domain uses default template and contain Admin Server only. This domain represent domain which we generally uses for development purposes. We create a domain partition Medrec-Dev inside it, which we later export and import it to base_domain.

otd_domain: We create this domain as part of Lab 6. This domain consist Admin Server, and Load Balance instance.

How to Use Individual Labs:

Lab 1 and Lab 2 are compulsory.

Lab 3: You need to run Lab 1 and Lab2 before executing Lab 3.

Lab 4: You need to run Lab 1 and Lab 2 before executing Lab 4.

Lab 5: You need to run Lab 1 and Lab 2 compulsory for it. And if you do not execute Lab 4 before running Lab 5, then instead of modifying the changes to Medrec-Dev domain, you need to modify the domain partition dp1.

Lab 6: You need to run Lab 1 before executing the Lab 6.

Virtual Box Environment

The Hands on Lab Environment

Operating System Details

Operating System	Oracle Linux 6.4 x86_64
Hostname	localhost, wins-vbox
Root User	root/oracle
Oracle User	oracle/welcome1

Note: For this hand on lab you should only need to use **oracle** user account.

Installation Directories

JDK 1.8.0_60	/usr/java/jdk1.8.0_60/
WebLogic Server 12.2.1	/u01/wins/wls1221/
Oracle Traffic Director 12.2.1	/u01/wins/wls1221/
Oracle Database 12c	/u01/app/oracle/product/12.1.0/dbhome_1/

Workshop Content:

Labs Directory	/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/
----------------	---

LAB 1: DOMAIN CREATION AND NON-MT CONFIG

Overview

In this lab, we are going to perform the below operations.

- We create a WebLogic domain, in that domain we create machine, dynamic cluster.

Start the database


We have two Pluggable database **pdborcl** and **pdb2**; we are going to start both the database.

- a. In Desktop, Double Click on Icon “**Start Database**”.


Note: Wait until the Window disappears.

Create WebLogic Restricted JRF Domain

- a. Open a new terminal.
- b. cd /u01/wins/wls1221/oracle_common/common/bin/
- c. ./config.sh
- d. Select “**Create a new domain**” and Enter
“/u01/wins/wls1221/user_projects/domains/base_domain” as Domain Location then click on **Next**.




- e. Select “**Oracle Enterprise Manager –Restricted JRF-12.2.1 [em]**” as it also select the remaining required check boxes then click on **Next**.



- f. Leave Default on **Application Location** then click on **Next**.
g. Enter **weblogic/welcome1** as Name/Password then click on **Next**.
h. Leave Default on **Domain Mode and JDK Screen** then click on **Next**.
i. Leave Default on **Advanced Configuration** then click on **Next**.
j. Click on **Create**.
k. Click on **Next** then click on **Finish**.

Configuration of WebLogic base_domain

- a. cd /u01/wins/wls1221/user_projects/domains/base_domain/bin/
- b. ./startNodeManager.sh
- c. In tab, Click on **Terminal -> Set Title**. Enter **base_nm** as Title then click on OK.
- d. Open a new tab.
- e. cd /u01/wins/wls1221/user_projects/domains/base_domain/bin/
- f. ./startWebLogic.sh
- g. In tab, Click on **Terminal -> Set Title**. Enter **base_admin** as Title then click on OK.
- h. Go back to Firefox and type the Fusion Middleware Control URL <http://localhost:7001/em>
- i. Enter **weblogic/welcome1** as **username/password** then click on **Login**.



- j. Create a Machine.
 - i. Click on **WebLogic Domain-> Environment -> Machine**.
 - ii. Click on **Create**.
 - iii. Enter “**machine**” as Name, Select “**Unix**” as Machine OS, then click on **Next**.
 - iv. Leave Defaults on Node Manager Properties then click on **Create**.
 - v. Click on the Machine name **machine**.
 - vi. Click on **Monitoring** tab and verify the status as **Reachable**.

k. Create a Dynamic Cluster

- Click on **WebLogic Domain -> Environment -> Clusters.**

The screenshot shows the Oracle Enterprise Manager interface. The left sidebar has three main categories: Server, Cluster, and Deployment. Under the Cluster category, the 'Environment' link is highlighted with a red box. The main content area shows a 'Domain Server' configuration with fields: Name (AdminServer), Host (localhost), and Port (7001). A dropdown menu is open under 'Clusters' with 'Clusters' highlighted by a red box. To the right is a table titled 'Clusters' with columns: Cluster, Machine, and State. One row is visible with the state 'Running'. At the bottom right of the table area, it says 'Servers 1 of 1'.

- Click on **Create -> Dynamic Cluster.**

The screenshot shows the 'Clusters' creation page. The top bar includes 'View', 'Create' (with 'Dynamic Cluster' highlighted by a red box), 'Delete', 'Control', and 'Scale Up/Down'. The main table has columns: Name, Cluster, Cluster Type, Servers, Cluster Messaging Mode, Default Load Algorithm, Replication Type, Multicast Address, and Multicast Port. A sub-table under 'Cluster' shows 'Dynamic Cluster'. Below the table, it says 'No clusters found'.

- Enter **app-cluster** as Name then click on **Next.**

- Leave Default on **Dynamic Server Properties** page and click on **Next.**

- v. Select “Use a single machine for all dynamic servers” and choose the machine, then click on **Next**.

Create a Dynamic Cluster: Machine Bindings

Use this page to associate dynamic servers with machines.

How do you want to distribute dynamic servers across machines?

Use any machine configured in this domain
 Use a single machine for all dynamic servers
Selected Machine **machine**
 Use a subset of machines in this domain

Machine Name Match Expression

- vi. Leave Default on Listen Port Bindings, and then click on **Next**.
vii. Review the Configuration and click on **Create**.

- I. Start Managed Servers.
i. Click on **WebLogic Domain -> Control ->Clusters**.

base_domain

WebLogic Domain

- Control
- Start Up
- Shut Down
- Deployments
- Servers
- Clusters**
- JDBC Data Sources
- Messaging

Admin Server Port	Username	OTD Domain
8001	weblogic	otd_domain


- ii. Check the box near to **app-cluster** to make it highlighted and then Click on **Control -> Start -> Start Servers**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The title bar reads "ORACLE Enterprise Manager Fusion Middleware Control 12c". The top navigation bar includes "WebLogic Domain" and "weblogic", along with standard browser controls like lock, refresh, and auto-refresh. The date and time "Nov 5, 2015 2:26:48 AM PST" are also displayed.

The main content area is titled "Clusters (Control)". It features a pie chart showing the status of clusters, with a large red segment labeled "Down (1)". Below the chart is a table with columns: Name, Cluster Type, Servers, Cluster Messaging Mode, Default Load Algorithm, and Replication Type. One row is selected, showing "app-cluster" in the Name column, "Dynamic" in Cluster Type, "2" in Servers, "Unicast" in Cluster Messaging Mode, "Round Robin" in Default Load Algorithm, and "(None)" in Replication Type.

A context menu is open over the "app-cluster" row, with the "Control" option highlighted by a red box. Sub-options include "Start", "Resume", "Suspend", "Shutdown", and "Restart SSL".

At the bottom of the table, there are buttons for "Rows Selected" (1), "Columns Hidden" (32), and "Clusters 1 of 1".




LAB 2: MULTITENANCY CONFIGURATION

Overview:

In this lab, we are going to learn the following:

- Configuration of Virtual Target, Domain Partition and Resource Group
- Run multiple instances of Medrec application in different domain partition without modifying the application. We try to show **JNDI Isolation** for that we are using the same Medrec applications and same JNDI name for the Datasources, connection factory and Distributed queue in both the domain partition.
- Run Day trader application which is build by WebSphere to WebLogic 12.2.1.
- You don't need to modify your application to run in Multitenant environment. So no special application development needed.

The final deployment architecture will look like the below where we will create three domain partitions . Deploy Medrec application in domain partition dp1 and dp2. And Day Trader application on domain partition dp3.



Configuration of Medrec Application in Domain Partition 1

In the next step we are creating the below configuration for Medrec application in domain partition dp1.

Virtual Target: VT-Medrec-1

Domain Partition: dp1

Resource Group app1RG

app1RG:

Datasource:

Name: MedRecGlobalDataSourceXA

JNDI Name: jdbc/MedRecGlobalDataSourceXA

Mail Session:

Name: MedRecMailSession

JNDI Name: mail/MedRecMailSession

Persistence Store: MedRec-fs

JMS Server: MedRecJMSServer

JMS Module: MedRecModule

MedRecModule:

Subdeployment: MedRecJMS

Connection Factory:

Name: MedRecConnectionFactory

JNDI Name: com.oracle.medrec.jms.connectionFactory

Distributed Queue:

Name: PatientNotificationQueue

JNDI Name: com.oracle.medrec.jms.PatientNotificationQueue

Applications: medrec.ear

physician.ear

chat.war

- a. Open a new tab.
- b. cd /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2/
- c. ./Medrec1DB.sh (It creates the required database user and populate sample data into database)
- d. Close the tab.
- e. In Enterprise Manager, Click on **WebLogic Domain > Environment -> Virtual Targets**.

The screenshot shows the Oracle Enterprise Manager interface. The left sidebar has a tree view with nodes like 'Clusters' (selected), 'Deployment', 'Logs', 'Environment' (highlighted with a red box), 'Deployments', 'JDBC Data Sources', etc. The main content area shows a table for 'Virtual Targets' with columns: Cluster Messaging Mode, Default Load Algorithm, and Replication Type. A tooltip above the table says 'the selected Server(s):app-cluster-2, app-cluster-1'. The bottom right of the table shows 'Clusters 1 of 1'. The 'Virtual Targets' button at the bottom of the table is also highlighted with a red box.

- f. Click on **Create**.
- g. Enter **VT-Medrec-1** as Name and **/dp1** as Uri Prefix and Add **localhost** as Hosts then click on **Next**.

The screenshot shows the 'Create Virtual Target: General' wizard. It's Step 1 of 2. The 'Name' field contains 'VT-Medrec-1' and the 'Uri Prefix' field contains '/dp1'. Under the 'Hosts' section, there's a table with a single row containing 'localhost'. The 'Add' button is highlighted with a red box. The 'Next' button at the top right is also highlighted with a red box.

h. Select Cluster **app-cluster** as Target then click on **Create**.

The screenshot shows the Oracle Enterprise Manager interface for creating a virtual target. The top navigation bar says "ORACLE Enterprise Manager Fusion Middleware Control 12c". Below it, a breadcrumb path shows "base_domain". A tabs section has "General" and "Targets" tabs, with "Targets" being the active one. The main content area is titled "Create Virtual Target: Targets" and includes a message: "Choose a server or cluster to be associated with this virtual target." A dropdown menu shows "Cluster" selected under "app-cluster". Other options include "Server". At the bottom right are buttons for "Back", "Step 2 of 2", "Next", "Create" (which is highlighted with a red box), and "Cancel".

i. Click on **WebLogic Domain -> Environment -> Domain Partitions**.

The screenshot shows the Oracle Enterprise Manager navigation tree. The "WebLogic Domain" node is expanded, and the "Environment" node is selected and highlighted with a red box. Under "Environment", the "Domain Partitions" node is also highlighted with a red box. To the right, a table lists domain partitions used by various components. The table has columns for "Servers", "Used By", and "Log File Name". One entry shows "logs/virtualTarget..". The table footer indicates "Virtual Targets 1 of 1". The top right corner shows the date and time: "Nov 5, 2015 2:34:08 AM PST".

Servers	Used By	Log File Name
		logs/virtualTarget..

- j. Click on “**Enable Lifecycle Manager**”.
- k. Go back to base_admin terminal, press CTRL+C, to stop the admin server.
- l. ./startWebLogic.sh
- m. Go back to Firefox, and type the Fusion Middleware Control Console URL <http://localhost:7001/em>.
- n. Enter **weblogic/welcome1** as **User Name/Password** then Click on **Login**.
- o. Click on **WebLogic Domain -> Environment -> Domain Partition**.
- p. Click on **Create**.
- q. Enter **dp1** as Name then click on Next.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

base_domain i

General Available Targets Resource Group Summary

Create Domain Partition: General

Back Step 1 of 4 **Next** Cancel

Use this page to specify general attributes for this domain partition.

* Name Security Realm

Primary Identity Domain

Load Balancer Configuration

If you wish to use a load balancer to front-end this domain partition, choose an Oracle Traffic Director runtime from the list of registered runtimes shown below. If you wish to register a new OTD runtime, please use the Environment->OTD Runtimes menu item on the WebLogic Domain menu.

Use OTD for load balancing OTD Runtime

- r. Check the left box near **VT-Medrec-1** and also check the box for **Set as Default** then click on **Next**.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

base_domain i

General Available Targets Resource Group Summary

Create Domain Partition: Available Targets

Back Step 2 of 4 **Next** Cancel

Select Virtual Target Set as Default

Select	Virtual Target	Set as Default
<input checked="" type="checkbox"/>	VT-Medrec-1	<input checked="" type="checkbox"/>

- s. Enter **app1RG** as Resource Group name and **None** as Resource Group Template, Move the **VT-Medrec-1** virtual target to **Selected targets** then click on **Next**.

Create Domain Partition: Resource Group

A resource group needs to be created within a partition before you can deploy applications or resources. The resource group can optionally extend a resource group template specified at the domain level.

* Resource Group Name **app1RG**

Resource Group Template **None**

Targets for the Resource Group Select a target for the resource group from the list of available targets. If the partition has a default target specified, the resource group will implicitly inherit that target.

Available Targets	Selected Targets
VT-Medrec-1	VT-Medrec-1

- t. Verify the configuration and click on **Create**.
u. Check the box near **dp1** and click on **Control -> Start**. Once you notice the message “**Partition state after the operation is RUNNING**” then Click on Close.

Domain Partitions

Domain partitions are the building blocks of WebLogic server multi-tenancy (MT). Multi-tenancy permits multiple client organizations to share a domain, improving efficiency and reducing operation costs. Before creating a domain partition, you must first create one or more virtual targets. Look at the Getting Started topics for more information.

► Getting Started with Multi-Tenancy

Hide Pie Chart

Name	Status	OTD Partition	Realm	Default Targets	Available Targets
dp1	Down (1)			VT-Medrec-1	VT-Medrec-1

Status

Control ▾

Start

Down (1)

Shutdown(1)

Domain Partitions 1 of 1



v. Click on the Domain Partition **dp1**.

Name	Status	State	OTD Partition	Realm	Default Targets	Available Targets
dp1		Running			VT-Medrec-1	VT-Medrec-1

w. Click on **Domain Partition -> Administration -> Resource Group**.

The screenshot shows the Oracle Enterprise Manager interface for Fusion Middleware Control 12c. The top navigation bar includes "WebLogic Domain" and "weblogic". The main content area is for the domain partition "dp1". The left sidebar has sections for Monitoring, Resource Groups, Deployment, and Administration. The "Administration" section is currently selected, with its sub-menu expanded. The sub-menu items include Home, General, JDBC and JTA Usage, Resource Groups (which is highlighted with a red box), Load Balancer Configuration, Resource Overrides, Resource Sharing, Coherence Caches, Notes, Pending Messages, and Current Messages. The "General" section shows the State as Running and Default Targets as VT-Medrec-1. The "JDBC and JTA Usage" section shows Open JDBC Connections at 0, JDBC Connection Creates (per minute) at 0.00, Active Transactions at 0, Transaction Commits (per minute) at 0.00, and Transaction Rollbacks (per minute) at 0.00. The "Resource Usage" section shows CPU Usage (%) as Unavailable and Open Files as Unavailable.

- x. Click on Resource Group **app1RG**.
- y. Creation of Datasource.
 - i. Select the **Services** tab.
 - ii. Choose JDBC tab, click on **Create > Generic Data Source**.

The screenshot shows the Oracle Enterprise Manager interface for a WebLogic Domain named 'weblogic'. The top navigation bar includes 'WebLogic Domain' and 'weblogic'. Below the navigation is a toolbar with 'Domain Partition' (dp1), 'Start Up', 'Shut Down', 'Auto Refresh' (Off), and a date/time stamp 'Nov 5, 2015 2:44:29 AM PST'. The main content area is titled 'Resource Group : app1RG'. The 'Services' tab is selected, indicated by a red box. Under the 'JDBC' tab, a dropdown menu shows 'Generic Data Source' highlighted with a red box. Other options in the dropdown include 'GridLink Data Source' and 'Multi Data Source'. The main table displays columns for 'Name', 'JNDI Name', 'Type', and 'Targets'. The status bar at the bottom right shows 'JDBC Data Sources 0 of 0'.

- iii. Enter **MedRecGlobalDataSourceXA** as Data Source Name and **jdbc/MedRecGlobalDataSourceXA** as JNDI Name, and then click on Select.

The screenshot shows the 'Create a JDBC Data Source: Data Source Properties' step of a wizard. The top navigation bar shows 'weblogic'. Below it is a progress bar with five steps: 'Data Source Properties' (selected), 'Connection Properties', 'Transaction Properties', 'Select Targets', and 'Review'. The main form is titled 'Create a JDBC Data Source: Data Source Properties'. It includes fields for 'Data Source Name' (MedRecGlobalDataSourceXA), 'Scope' (Resource group "app1RG" in domain partition "dp1"), 'Type' (Generic), 'Database Type' (Oracle), 'Driver Class Name' (oracle.jdbc.OracleDriver), 'JNDI Name' (jdbc/MedRecGlobalDataSourceXA), and a 'Select...' button for the driver class. At the bottom are 'Back', 'Step 1 of 5', 'Next', and 'Cancel' buttons.


- iv. Select **Oracle** as Database Type and “**Oracle’s Driver (Thin XA) for service connections; Versions: Any**” as JDBC Driver then click on OK.



- v. Click on **Next**.
vi. Click on **Generate URL and Properties** and Enter the following:

Host Name:	localhost
Listen Port:	1521
Database Name:	pdborcl
User Name:	medrec1
Password:	medrec1
Confirm Password	medrec1

Click OK.



vii. Click on **Test Database Connection** to verify the connection. Click **Next**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. A modal dialog titled "Confirmation" is displayed, stating "Connection test succeeded." with an "OK" button. The main page is titled "Create a JDBC Data Source: Connection" and contains "Database Connection Information". The "Driver Class" is set to "oracle.jdbc.xa.client.OracleXADataSource". The "Database URL" is "jdbc:oracle:thin:@//localhost:1521/pdborcl". The "Password" and "Confirm Password" fields both contain "*****". The "SQL ISVALID" field shows "Test Database Connection" (which is also highlighted with a red box). Below the form, there is a "Properties" section and a URL "localhost:7001/em/faces/as-emas_createDS_taskflow/as/jdbc/createDSStep2#".

viii. Leave Default on **Transaction Options** and click on **Next**.

ix. Verify the configuration and click on **Create**.

z. Adding User to Default Realm.

i. Click on **Weblogic Domain -> Security -> Users and Groups**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. On the left, under "base_domain", it says "JDBC Data Source 'MedRecGlobalDataSourceXA' has been created successfully. All changes have been saved." In the center, the "Resource Group : app1RG" page is shown. The "Services" tab is selected, and the "JDBC" sub-tab is active. A table lists a single entry: "Name" is "MedRecGlobalDataSourceXA" and "JNDI Name" is "jdbc/MedRecGlobalDataSourceXA". A context menu is open over this row, with "Users and Groups" highlighted (and also highlighted with a red box). On the right, the navigation bar shows "Security" (also highlighted with a red box) under the "WebLogic Domain" dropdown. The bottom right corner of the screen shows the URL "Target Sitemap".

- ii. In **Users** tab, click on **Create**.

Users and Groups

This page displays information about the users and groups that have been configured in the selected security realm in this WebLogic Server domain.

Select a Realm: myrealm

Default Realm for This WebLogic Domain: true

Users Groups

Create Delete Detach

Name	Description	Provider
LCMUser	This is the default service account ...	DefaultAuthenticator
OracleSystemUser	Oracle application software syste...	DefaultAuthenticator
weblogic	This user is the default administrator.	DefaultAuthenticator

Columns Hidden: 1

Users 3 of 3

- iii. Enter the following then click on **Create**.

Name:	administrator
Description:	Medrec Admin
Provider:	Default Authenticator
Password:	administrator123
Confirm Password:	administrator123

aa. Configuring Mail Session.

- Click on **Weblogic Domain ->Environment ->Domain Partition**.
- Click on Domain Partition **dp1**.
- Click on **Domain Partition -> Other Services -> Mail Sessions**.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

WebLogic Domain: weblogic

dp1

Domain Partition Start Up Shut Down

Nov 5, 2015 7:09:41 AM PST

Monit

- Home
- Monitoring
- Diagnostics
- Control
- Logs

Resou

- Deployments
- JDBC Data Sources
- Messaging
- Coherence Caches

Deplo

- Web Services
- Other Services**
- Administration
- Security
- System MBean Browser
- Target Sitemap

General

State: Running

Default Targets: VT-Medrec-1

Available Targets: VT-Medrec-1

JDBC and JTA Usage

Open JDBC Connections: 0

JDBC Connection Creates (per minute): 0.00

Active Transactions: 0

Work Manager

Requests (per minute): 6.41

Pending Requests: 0

Transaction Commits (per minute): 0.00

Transaction Rollbacks (per minute): 0.00

Resource Usage

CPU Usage (%): Unavailable

Open Files: Unavailable

Persistent Stores

Mail Sessions

Foreign JNDI Providers

Current Messages: 0

iv. Click on **Create**.

v. Enter the following and click on **Next**.

Name: MedRecMailSession
Scope: Leave as default
JNDI Name: mail/MedRecMailSession

The screenshot shows the 'Create a Mail Session: General Configuration' page. The 'Name' field contains 'MedRecMailSession'. The 'Scope' dropdown shows 'Domain Partition Resource Group' with 'app1RG in partition dp1' selected. The 'JNDI Name' field contains 'mail/MedRecMailSession'. The 'Next' button is highlighted with a red box.

vi. Click on **Create**.

bb. Configuring JMS Server.

i. Click on **Domain Partition** -> **Messaging** -> **JMS Servers**.

The screenshot shows the 'Domain Partition' section of the Oracle Enterprise Manager. The 'Messaging' option under 'Domain Partition' is selected and highlighted with a red box. A tooltip message 'as been created successfully. All changes have been activated.' is displayed above the 'JMS Servers' link. The 'JMS Servers' link is also highlighted with a red box.

- ii. Click on **Create**. Enter **MedRecJMSServer** as Name then click on **Create a Store** -> **File Store**.

JMS servers act as management containers for the queues and topics in JMS modules that are targeted to them. A JMS server's primary responsibility for its destinations is to maintain information on what persistent store is used for any persistent messages that arrive on the destinations, and to maintain the states of durable subscribers created on the destinations.

Use this page to define the general configuration parameters for this JMS server.

* Name

Scope Domain Partition Resource Group

Persistent Store

- iii. Enter **MedRec-fs** as Name then click on **Next**. Click on **Create**.
 iv. In **JMS Server: General Setting**, Select the newly created file store as persistent store then click on **Next**.

JMS servers act as management containers for the queues and topics in JMS modules that are targeted to them. A JMS server's primary responsibility for its destinations is to maintain information on what persistent store is used for any persistent messages that arrive on the destinations, and to maintain the states of durable subscribers created on the destinations.

Use this page to define the general configuration parameters for this JMS server.

* Name

Scope Domain Partition Resource Group

Persistent Store

- v. Click on **Create**.
- cc. Configure JMS Module.
- Click on **Domain Partition -> Messaging -> JMS Resources and Modules**.

The screenshot shows the Oracle Enterprise Manager interface for a WebLogic Domain named 'weblogic'. The left sidebar shows a tree structure with 'dp1' selected. Under 'dp1', the 'Domain Partition' menu is open, and 'Messaging' is highlighted with a red box. A sub-menu for 'Messaging' is displayed, with 'JMS Resources and Modules' also highlighted with a red box. To the right, a table titled 'JMS Resources and Modules' shows one entry: 'app1RG'. At the bottom of the table, it says 'JMS Servers 1 of 1'. A yellow box highlights a message: 'JMS module has been created successfully. All changes have been activated.'

- Under the **JMS Modules** tab, click on **Create**.

The screenshot shows the same Oracle Enterprise Manager interface for domain partition 'dp1'. The 'JMS Modules' tab is selected, indicated by a red box around the tab name. A red box also highlights the 'Create' button in the top navigation bar. Below the tabs, there is a message: 'To configure and manage JMS modules, use the [WebLogic Server Administration Console](#)'. The main content area shows a table for 'JMS Modules'. The table has columns: Name, Resource Group, Queues, Topics, Connection Factories, Distributed Queues, Distributed Topics, Foreign Servers, Quotas, and Hand. A note at the bottom of the table says 'The table is empty'. At the bottom of the page, it says 'Columns Hidden 2' and 'JMS Modules 0 of 0'.

- iii. Enter **MedRecModule** as Name then click on **Next**. Click on **Create**.
- iv. Under **JMS Modules** tab, click on **MedRecModule**.

JMS Resources and Modules

To configure and manage JMS modules, use the [WebLogic Server Administration Console](#).

Name	Resource Group	Queues	Topics	Connection Factories	Distributed Queues	Distributed Topics	Foreign Servers	Quotas	Handle
MedRecModule	app1RG	0	0	0	0	0	0	0	

Columns Hidden 2 JMS Modules 1 of 1

- v. Under **Subdeployment** tab, click on **Create**.

JMS Module: MedRecModule

To configure and manage this JMS module, use the [WebLogic Server Administration Console](#).

Name	Resources	Targets
The table is empty		

- vi. Enter **MedRecJMS** as Name and Select the box near **MedRecJMSServer** then click on **Create**.

Create a Subdeployment

Subdeployment Name **MedRecJMS**

Select targets for this subdeployment.

JMS Servers

Select Name
MedRecJMSServer

SAF Agents

Select Name
No data to display

Create **Cancel**

- vii. Under **General** tab, click on **Create**.

JMS Module: MedRecModule

To configure and manage this JMS module, use the [WebLogic Server Administration Console](#).

General Subdeployments Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: MedRecModule
Scope: Resource group "app1RG" in domain partition "dp1"
Descriptor File Name: partitions/dp1/jms/medrecmodule-jms.xml

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

Create **Delete** **Detach**

- viii. Select box near **Connection Factory** then click on **Next**.

Create a JMS System Module Resource: Resource Type

Choose the type of JMS resource that you would like to create.

- ▲ Connection Factory
 - Connection Factory
- ▲ Destination
 - Destination Key
 - Quota

Connection Factory

A connection factory defines configuration parameters that are used to create connections for WebLogic JMS clients. A client's connection factory must be hosted on the same server or cluster as the client's destinations.

- ix. Leave Default in **JMS System Module** Page then click on **Next**.
 x. Enter **MedRecConnectionFactory/com.oracle.medrec.jms.connectionFactory** as Name/JNDI Name respectively then click on **Next**. Click on **Create**.

Create a Connection Factory: Properties

Specify the properties that you would like to identify your new JMS resource.

Resource Type	Connection Factory
* Name	<input type="text" value="MedRecConnectionFactory"/>
JNDI Name	<input type="text" value="com.oracle.medrec.jms.connectionFactory"/>
Notes	

<p>The global JNDI name used to look up a connection factory within a clustered JNDI namespace.</p>

- xi. Under General tab, Click on **Create**.
- xii. Select **Uniform Distributed Queue** then click on **Next**.

Create a JMS System Module Resource: Resource Type

Choose the type of JMS resource that you would like to create.

Resource Type

- Connection Factory
 - Connection Factory
- Destination
 - Destination Key
 - Quota
 - JMS Template
- Queue
 - JMS Queue
 - Uniform Distributed Queue
- Topic
 - JMS Topic
 - Uniform Distributed Topic

Uniform Distributed Queue

A uniform distributed topic is a logical topic that references a set of automatically generated JMS topic instances, each hosted on a different JMS server.

Note: depending on the type of resource selected, you will be prompted to enter basic information for the new JMS resource to be created in next step. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and SAF import destinations, you can also proceed to "Targets" step for selecting the appropriate targeting policy. For untargetable resources, like destination keys, quotas, templates, SAF error handling, and remote SAF context, the "Targets" step will be skipped.

xiii. Click on **Next**.

xiv. Enter the following and click on **Next**.

Name: PatientNotificationQueue

JNDI Name: com.oracle.medrec.jms.PatientNotificationQueue

Create a Uniform Distributed Queue: Properties

Specify the properties that you would like to identify your new JMS resource.

Properties

Resource Type	Uniform Distributed Queue
* Name	PatientNotificationQueue
Notes	<p>The name used to bind a virtual destination to the JNDI tree. Applications can use the JNDI name to look up the virtual destination.</p>
JNDI Name	com.oracle.medrec.jms.PatientNotificationQueue
Template	(None)

- xv. Click on **Create**. Click on **PatientNotificationQueue**, Under **Targeting**, Select **Subdeployment targeting as Targeting Policy** and **MedRecJMS** as **Subdeployment** then click on **Apply**.

The screenshot shows the Oracle Enterprise Manager interface for configuring a JMS resource. The top navigation bar includes Configuration, Monitoring, Notes, General, Advanced Configuration, Delivery Failure, Delivery Overrides, Logging, and Thresholds and Quotas. The General tab is selected. In the main content area, there is a 'Reset Delivery Count On Forward' checkbox. Below it, the 'Targeting' section is expanded, showing two radio buttons: 'Subdeployment targeting' (selected) and 'Default to the parent module's target'. Under 'Subdeployment', a dropdown menu is open, with 'MedRecJMS' selected.

Note: You must restart domain partition before going to deploy Medrec Application.

- Click on Change Center -> View Restart Checklist.

The screenshot shows the Oracle Enterprise Manager interface with a context menu open over a domain partition named 'dp1'. The menu items include Edit Sessions, Lock & Edit, View Change List, View & Resolve Conflicts, Release Configuration, Activate Changes, Undo All Changes, and a redboxed 'View Restart Checklist'. Other menu items like Console and Help are also visible. The main pane shows a confirmation message: 'Settings updated successfully. All changes have been activated. There are 1 or more item(s) that must be effect. Use the "View Restart Checklist" menu in Change Center to view the details.' Below this, the 'Uniform Distributed Queue: PatientNotificationQueue' configuration page is shown, with the General tab selected. The configuration details include Name: PatientNotificationQueue and Scope: Resource group "app1RG" in domain partition "dp1".

b. Select the box near to dp1 then click on Restart.

Restart Checklist			
This page lists servers, domain partitions, system components, and other resources that must be restarted for configuration changes to take effect. To restart, select the resource you would like to restart and click Restart button.			
Name	Resource Type	Targets	Status of Last Action
dp1	Domain Partition		START (TASK COMPLETED)

c. On Confirmation Screen, Click on Restart.

dd. Deployment of Medrec Application.

i. Click on **WebLogic Domain -> Environment -> Resource Groups**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The left pane displays the configuration for a Uniform Distributed Queue named 'PatientNotificationQueue'. The right pane shows the navigation menu under 'Environment'.

Left Panel (Configuration):

- General tab selected.
- Fields: Name (PatientNotificationQueue), Scope (Resource g), JNDI Name (com.oracle), Template (None).
- Description: "Use this page to define the general configuration parameters for the Uniform Distributed Queue members."

Right Panel (Navigation Menu):

- WebLogic Domain: weblogic
- Environment (selected):
 - Servers
 - Server Templates
 - Clusters
 - Machines
 - Domain Partitions
 - OTD Runtimes
 - Resource Groups** (selected)
 - Resource Group Templates
 - Partition Work Managers
 - Resource Consumption Managers
 - Virtual Hosts
 - Virtual Targets
 - Migratable Targets
- Deployments
- JDBC Data Sources
- Messaging
- Cross Component Wiring
- Web Services
- Other Services
- Administration
- Refresh WebLogic Domain
- Security
- System MBean Browser
- WebLogic Server Administration Console
- Target Sitemap

- ii. Click on Resource Group **app1RG**, click on **Deployments** tab.
- iii. Click on **Deployment -> Deploy**.

The screenshot shows the Oracle Enterprise Manager interface for a WebLogic Domain. The top navigation bar includes 'WebLogic Domain' and 'weblogic'. The main title is 'Resource Group : app1RG'. Below it, there are tabs: General, **Deployments** (which is selected), Services, Targets, Monitoring, Control, and Notes. A message box states 'This page displays a list of Java EE applications and standalone application modules that have been deployed to this resource group.' Below this, there are filter options: View, Show All, Deployment (with 'Deploy' highlighted), Override, and Control. A table header shows columns: Name, Status, State, Health, and Type. A note below the table says 'No deployments found. Select a deployment target to view existing applications, resource adapters, and libraries.' At the bottom right of the table area, it says 'Deployments 0 of 0'. A context menu is open over the 'Deployment' dropdown, with 'Deploy' highlighted.


- iv. Select “Archive or exploded directory is on the server where Enterprise Manager is running” then click on **Browse**. Specify the location of **medrec.ear** from **/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2** then click on **OK**.

The screenshot shows the 'Deploy Java EE Application: Select Archive' wizard, Step 1 of 4. It has four tabs: Select Archive (selected), Select Target, Application Attributes, and Deployment Settings. The 'Scope' section indicates the scope is 'Resource group "app1RG" in domain partition "dp1"'. The 'Archive or Exploded Directory' section contains a note about deploying Java EE archives, Web Modules (WAR files), EJB Modules (EJB JAR files), Resource Adapter Modules (RAR files), Coherence Archives (GAR files), JDBC Modules, JMS Modules, and library files (Jar files). It also notes that an exploded archive can be deployed if present on the server. There are two radio button options: 'Archive is on the machine where this Web browser is running.' (unchecked) and 'Archive or exploded directory is on the server where Enterprise Manager is running.' (checked). The input field for the archive path is '/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2/medrec.ear', and the 'Browse...' button next to it is highlighted. On the right side of the screen, there is a vertical sidebar with various links and a scroll bar.

- v. Click on **Next** then click on **Deploy**. Click on Close.
- vi. Deploy **physician.ear** file similarly from the **/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2** location.
- vii. Deploy **chat.war** file similarly from the **/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2** location.

Accessing Medrec Application in Domain Partition dp1

- i. Go to Firefox and type the URL: <http://localhost:7101/dp1/medrec/>
- ii. Click on Getting Started.



- iii. Under Patient, Click on **I'm New Here**
- iv. Enter the following or any other data then click on Submit.

Email:	weblogic@oracle.com
Password:	welcome1
Confirm Password:	welcome1
First Name:	Ankit
Last Name:	Pandey
Gender:	Male
DOB:	Jun 23, 1988
SSN:	123456788

Note: Make sure you not use 123456789 as SSN Number.

- v. Click on **Getting Started** again on Medrec Home Page.
- vi. Under Administrator, click on Login.
- vii. Enter **administrator/administrator123** as username and password then click on Sign In.

The image shows a login interface titled "Administrator". It features a central message "Please sign in." Below it are two input fields: "Username" containing "administrator" and "Password" containing a series of dots. A blue "Sign In" button is positioned to the right of the password field. Both the "Username" and "Password" fields are highlighted with a red border.

- viii. Under **Pending Requests**, click on Go.
- ix. Click on the Email Id, and then click on Approve.
- x. Click on Logout. Click on Logout again.
- xi. You can login as weblogic@oracle.com/welcome1 as username/password as Patient.
- xii. You can view your record summary, and you can also have interaction with physician.



Patient look up and view your visit and prescription history and edit your profile information.

The Patient application allows patients to log in, edit their profile information, or request that their profile be added to the system. Patients can also view prior medical records of visits with their physician.

Configuration of Medrec Application in Domain Partition 2

In the next step we are creating the below configuration for Medrec application in domain partition dp2. We are using the same Medrec applications and same JNDI name for the Datasources, connection factory and Distributed queue but we will connect to different database. So there are two benefits of Multitenancy.

- In a domain, you can deploy the same application in two different domain partitions and there will be no JNDI conflict. You do not have to make any changes in application.
- In single domain, you can have same application deployed in two different domain partitions and connected to two databases. So both the application will have different Set of Users in our case or different set of Application Specific Data.

Virtual Target: VT-Medrec-2

Domain Partition: dp2

Resource Group app2RG

app1RG:

Datasource:	MedRec2GlobalDataSourceXA, jdbc/MedRecGlobalDataSourceXA
Mail Session:	MedRecMailSession, mail/MedRecMailSession
Persistence Store:	MedRec2-fs
JMS Server:	MedRec2JMSServer
JMS Module:	MedRec2Module
MedRecModule:	
Subdeployment:	MedRec2JMS
Connection Factory:	MedRec2ConnectionFactory, com.oracle.medrec.jms.connectionFactory
Distributed Queue:	PatientNotificationQueue com.oracle.medrec.jms.PatientNotificationQueue
Applications:	medrec.ear physician.ear chat.war


The Scripts MedrecInDP2.sh creates the Virtual Target, Domain Partition, Resource Group, JDBC Datasource, JMS Server, JMS Module, Distributed Queue and Connection Factory then deploys the medrec.ear, physician.ear and chat.war.

- a. Open a new tab.
- b. cd /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2
- c. ./Medrec2DB.sh (It creates the required user medrec2 in pdb2 and populates the sample data.)
- d. ./MedrecInDP2.sh
- e. Go back to Fusion Middleware Control <http://localhost:7001/em>.
- f. Verify the creation of the following resources.
 - i. Click on **WebLogic Domain ->Environment ->Virtual Target**. Here we have **dp2** as **URI Prefix** for the Virtual Target **VT-Medrec-2**.
 - ii. Click on **WebLogic Domain ->Environment ->Domain Partition**.
 - iii. Click on Domain Partition **dp2** then Select **Domain Partition -> Administration -> Resource Groups**.
 - iv. Click on Resource group **app2RG**.
 - v. In the “**Services**” and “**Deployments**” tab, you can verify the creation of above System Resources here.

Accessing Medrec Application in Domain Partition dp2

While accessing the application we need to use the Virtual Target URI. As domain partition dp2 is targeted to Virtual Target VT-Medrec-2, which has /dp2 as URI, we need to add it in URL for the accessing the application.

- a. In Firefox, type the URL: <http://localhost:7101/dp2/medrec/>



- b. As both this application has exactly same JNDI name used within application, JNDI name of Datasource, JMS connection factory, mail sessions, Distributed Queue.
- c. Click on Getting Started!
- d. Under **Patient**, Click on Login, Try to login with weblogic@oracle.com/welcome1. You will not be able to login. As both Medrec application is connected to different database. So in Multitenant WebLogic Server, you can deploy exactly same application with same configuration but with different database and there will be no JNDI conflict in domain.

Configuration of Day Trader application in domain partition 3

Here we will create the below configuration through WLST to Run Day Trader Application on Domain Partition dp3.

Virtual Target: VT-daytrader

Domain Partition: dp3

Resource Group app3RG

app1RG:

Datasource:

Name:	jdbc/datasources/TradeDataSource,
JNDI Name:	jdbc/datasources/TradeDataSource
Name:	jdbc/datasources/NoTxTradeDataSource
JNDI Name:	jdbc/datasources/NoTxTradeDataSource

Persistence Store: MyFileStore

JMS Server: MyJMServer

JMS Module: MyJMSModule

MyJMSModule:

Subdeployment: MySubdeployment

Connection Factory:

Name:	jms/myQueueConnectionFactory,
JNDI Name:	jms/myQueueConnectionFactory
Name:	jms/myTopicConnectionFactory
JNDI Name:	jms/myTopicConnectionFactory

Distributed Queue:

Name:	jms/TradeBrokerQueue
JNDI Name:	jms/TradeBrokerQueue

Distributed Topic:

Name:	jms/TradeStreamerTopic
JNDI Name:	jms/TradeStreamerTopic

Applications: web-3.0.0.war

This DayTraderInDP3.sh creates the Virtual Target, Domain Partition, Resource Group, JDBC Datasource, JMS Server, JMS Module, Distributed Queue and Connection Factory then deploys the web-3.0.0.war.

- a. cd/ u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab2
- b. ./DayTrader3DB.sh (It creates the required user for pdborcl database.)
- c. ./DayTraderInDP3.sh
- d. Go back to Fusion Middleware Control <http://localhost:7001/em>
- e. Verify the creation of the following resources.
 - i. Click on **WebLogic Domain ->Environment ->Virtual Target**. Here we have **dp3** as **URI Prefix** for the Virtual Target **VT-daytrader**.
 - ii. Click on **WebLogic Domain ->Environment ->Domain Partition**.
 - iii. Click on Domain Partition to **dp3** then Select **Domain Partition -> Administration -> Resource Groups**.
 - iv. Click on Resource group **app3RG**.
 - v. In **Services** and **Deployments** tab, you can verify the creation of above System Resources here.

Access Day Trader Application in Domain Partition dp3

- a. Go to Firefox and type the URL: <http://localhost:7101/dp3/daytrader/>
- b. Click on **Configuration** tab, click on “**Re-populate Day Trader Database**”. It creates the 500 users in the database and also populates some sample data.

Benchmark Configuration Tools	Description
Reset DayTrader (to be done before each run)	Reset the DayTrader runtime to a clean starting point by logging off all users, removing new registrations and other general cleanup. For consistent results this URL should be run before each Trade run.
Configure DayTrader run-time parameters	This link provides an interface to set configuration parameters that control DayTrader run-time characteristics such as using EJBs or JDBC. This link also provides utilities such as setting the UID and Password for a remote or protected database when using JDBC.
(Re)-create DayTrader Database Tables and Indexes	This link is used to (a) initially create or (b) drop and re-create the DayTrader tables. A DayTrader database should exist before doing this action , the existing DayTrader tables, if any, are dropped, then new tables and indexes are created. Please stop and re-start the Daytrader application (or your application server) after this action and then use the "Repopulate DayTrader Database" link below to repopulate the new database tables.
(Re)-populate DayTrader Database	This link is used to initially populate or re-populate the DayTrader database with fictitious users (uid:0, uid:1, ...) and stocks (s:0, s:1, ...). First all existing users and stocks are deleted (if any). The database is then populated with a new set of DayTrader users and stocks. This option does not drop and recreate the Daytrader db tables.

Copyright 2006, Apache Software Foundation. All Rights Reserved

POWERED BY
APACHE GERONIMO

- c. Choose following Options and leave other defaults then click on **Update Config.**


Run Time Mode: Full EJB 3
JPA Layer: Hibernate
Order Processing Mode: Synchronous



DAYTRADER
PERFORMANCE BENCHMARKING

Home	Trading & Portfolios	Configuration	Primitives	FAQ
Run-Time Mode	Run Time Mode determines server implementation of the TradeServices to use in the DayTrader application Enterprise Java Beans including Session, Entity and Message beans or Direct mode which uses direct database and JMS access. See DayTrader FAQ for details.			
<input checked="" type="radio"/> Full EJB3 <input type="radio"/> Direct (JDBC) <input type="radio"/> Session (EJB3) To Direct				
JPA Layer	JPA Layer determines what kind of JPA Implementation Daytrader EJB classes use. Typically, Apache Geronimo uses OpenJPA, and RedHat JBoss 5 uses Hibernate.			
<input type="radio"/> OpenJPA <input checked="" type="radio"/> Hibernate				
Order-Processing Mode	Order Processing Mode determines the mode for completing stock purchase and sell operations. Synchronous mode completes the order immediately. Asynchronous_2-Phase performs a 2-phase commit over the EJB Entity/DB and MDB/JMS transactions. See DayTrader FAQ for details.			
<input type="radio"/> Synchronous <input type="radio"/> Asynchronous_2-Phase				
Scenario Workload Mix	This setting determines the runtime workload mix of DayTrader operations when driving the benchmark through TradeScenarioServlet. See DayTrader FAQ for details.			
<input type="radio"/> Standard <input checked="" type="radio"/> High-Volume				
WebInterface				

- d. Once it is done, go to terminal.
- e. ./correctDB.sh (This application has some issue, so to solve it we are removing some data from database)
- f. Close the tab.
- g. Click on **Trading & Portfolios** tab, Enter uid:0/xxx as username/password then click on **Login**.



The screenshot shows a Firefox browser window with the following details:

- Address Bar:** Firefox, DayTrader, 127.0.0.1:7101/dp3/daytrader/
- Title Bar:** Oracle Technology Ne..., Applications, Admin Console, Developer Producti..., Technical Innovat...
- DayTrader Logo:** PERFORMANCE BENCHMARKING
- Navigation Bar:** Home, Trading & Portfolios, Configuration, Primitives, FAQ
- Header:** DayTrader Login
- Content:**
 - Log in:** Username: uid:0, Password: [redacted], Log in button
 - Text:** First time user? Please Register, Register With DayTrader
 - Footer:** DayTrader Login, DayTrader
- Page Bottom:** Copyright 2006, Apache Software Foundation. All Rights Reserved, POWERED BY APACHE GERONIMO

- h. Click on **Quotes/Trade**, Click on buy to purchase a share.

The screenshot shows the DayTrader application interface. At the top, there is a navigation bar with links for Home, Trading & Portfolios, Configuration, Primitives, and FAQ. Below the navigation bar, a red header bar displays "DayTrader Home", "DayTrader", and "Logoff". The main content area has several sections: "Welcome uid:0", "User Statistics" (including account ID, account creation date, created, total logins, and session created), "Account Summary" (including cash balance, number of holdings, total of holdings, sum of cash/holdings, and opening balance), and a "Market Summary 2015-11-05" table. The Market Summary table contains three parts: "DayTrader Stock Index (TSIA)" with a value of 101.54 (-1.00%), "Trading Volume" with a value of 21350.0, and two tables for "Top Gainers" and "Top Losers" with their respective stock symbols, prices, and changes. The "Top Gainers" table includes rows for s:100 through s:104. The "Top Losers" table includes rows for s:199 through s:196. A copyright notice at the bottom left states "Copyright 2006, Apache Software Foundation. All Rights Reserved". A "POWERED BY APACHE GERONIMO" logo is at the bottom right.

Market Summary 2015-11-05		
DayTrader Stock Index (TSIA)	101.54 (-1.00%)	
Trading Volume	21350.0	
Top Gainers	symbol	price
	s:100	207.86
	s:101	188
	s:102	100.19
	s:103	154.34
	s:104	105.06
Top Losers	symbol	price
	s:199	74.08
	s:198	157.41
	s:197	77.96
	s:196	47

- i. Click on **Portfolio**, Verify the Order then click on Sell.
j. Again click on Portfolio, to verify the Sell of share.
k. Click on **Log off**.

You can create many domain partitions in WebLogic 12.2.1. Your application does not require any specific application development. Your application which is working in previous version of WebLogic 12c, you can deploy them in multitenant environment without modifying the application. Daytrader application is developed by IBM which we deployed in domain partition dp3. So you can also easily deployed application build on different platform to WebLogic Server.

LAB 3: SECURITY ISOLATION

Overview

A security realm comprises mechanism for protecting WebLogic resources. Each security realm consists of a set of configured security providers, users, groups, security roles, and security policies. You use realms to configure authentication, authorization, role mapping, credential mapping, auditing and other services.

WebLogic Server traditionally supports multiple realms in a domain configuration, but only one realm—typically referred to as the “default realm” or “admin realm”—can be active at any given time.

In contrast, WebLogic Server MT supports multiple active realms and allows each partition to execute against a different realm.

This means that a partition can have unique security providers, users, groups, security roles and security policies. Resources and applications in the domain partition are available to only to users within the domain partition’s security realm. Other tenants cannot see or access the resources or applications.

Note: Partition can share a security realm, with consequent loss of independence isolation. In particular if you do not specify a realm when you create a partition, the default realm is shared with the partition and there is no security isolation between the partition and the domain.


In this Lab, first we will create a new security realm then we will assign the security realms to a partition dp1. So we will have two security realms in our domain one which we created and one is default security realm. Domain partition dp1 will have new security realm and other domain partitions will have default security realm. Default security realm has a user administrator with password administrator123. And new security realm will have user administrator with password welcome1. So Medrec application deployed in dp1 can be used by users of new security realm. You will not be able to login as an Admin in Medrec Application with default security realm user (administrator/administrator123).

In this lab we are going to perform the following operations:

- Creation of New Security Realm.
- Assigning a new Security realm to Domain Partition.
- Medrec application deployed in two different domain partitions which are using two different security realms in single domain.

Creating a New Security Realm

- i. Go to Firefox and type the WebLogic Admin Console URL:
<http://localhost:7001/console>.
- ii. Enter **weblogic/welcome1** as username/password then click on Login.



- iii. Under Domain Structure, click on **Security Realms**.

A screenshot of the Oracle WebLogic Server Administration Console 12c home page. The left sidebar shows a 'Domain Structure' tree with nodes like 'base_domain', 'Environment', 'Deployments', 'Services', and 'Security Realms'. The 'Security Realms' node is highlighted with a red box. The main content area is titled 'Home Page' and contains sections for 'Information and Resources', 'Helpful Tools' (with links to 'Configure applications', 'Configure GridLink for RAC Data Source', etc.), and 'General Information' (with links to 'Common Administration Task Descriptions', 'Read the documentation', etc.). The top navigation bar includes 'Home', 'Log Out', 'Preferences', 'Record', 'Help', and a search bar. The status bar at the bottom indicates 'Welcome, weblogic' and 'Connected to: base_domain'.

- iv. Click on **New**.
- v. Enter **mynewrealm** as Name; check the box for “**Create default providers within new realm**” and “**Ignore Deploy Credential Mapping**” then click on **OK**.

Create a New Realm

Realm Properties

The following properties will be used to identify your new realm.

* Indicates required fields

What would you like to name your new realm?

* Name:

Valid security realms must include a number of providers, each of which is responsible for some aspect of the overall security framework. You can use either the WebLogic Server supplied providers or your own custom providers.

Create default providers within this new realm

To avoid overwriting new credential mapping information with old information in a weblogic-ra.xml deployment descriptor file, check the Ignore Deploy Credential Mapping setting below.

Ignore Deploy Credential Mapping

- vi. Click on **mynewrealm**.
- vii. Click on **Users and Groups -> Users** tab.

Settings for mynewrealm

Configuration **Users and Groups** Credential Mappings Providers Migration

Users Groups

This page displays information about each user that has been configured in this security realm.

Customize this table

Users (Filtered - More Columns Exist)

	Name	Description	Provider
There are no items to display			

New Delete Showing 0 to 0 of 0 Previous | Next

- viii. Click on New.
 - ix. Enter the following then click on **OK**.
- | | |
|-------------------|--------------------------|
| Name: | administrator |
| Description: | Domain Partition 2 users |
| Provider: | Default Authenticator |
| Password: | welcome1 |
| Confirm Password: | welcome1 |

Create a New User

OK Cancel

User Properties

The following properties will be used to identify your new User.

* Indicates required fields

What would you like to name your new User?

* Name: **administrator**

How would you like to describe the new User?

Description: **Domain Partition 2 users**

Please choose a provider for the user.

Provider: **DefaultAuthenticator**

The password is associated with the login name for the new User.

* Password: *********

* Confirm Password: *********

OK Cancel

Assign the mynewrealm security realm to domain partition dp1.

- i. Click on **Domain Partitions**, then on **Control** tab.
- ii. Check the box near dp1 and click on **Shutdown ->Force Shutdown Now**.

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a navigation tree under 'Domain Structure' with 'Domain Partitions' selected. The main area is titled 'Summary of Domain Partitions' and shows a table of domain partitions (dp1, dp2, dp3). The 'Shutdown' column has a dropdown menu open for dp1, with 'Force Shutdown Now' highlighted. Other options in the dropdown include 'When work completes' and 'Cancel Shutdown'.

Name	Default Target	Status	Status of Last Action
dp1	VT-Medrec-1	RUNNING	TASK COMPLETED
dp2	VT-Medrec-2	RUNNING	TASK COMPLETED
dp3	VT-daytrader	RUNNING	TASK COMPLETED

- iii. Once domain partition shutdown, click on dp1.
- iv. In Configuration-> General tab, Under Use Realm, select **mynewrealm** then click on **Save**.

The screenshot shows the 'Settings for dp1' configuration page. At the top, there are two tabs: 'Configuration' (highlighted with a red box) and 'Resource Groups', followed by other tabs like 'Deployments', 'Services', etc. Below that, there are sub-tabs: 'General' (highlighted with a red box), 'Available Targets', 'File Systems', 'JTA', 'Concurrency', and 'Partition Work Manager'. Under 'General', there's a 'Resource Management' section with a 'Save' button highlighted with a red box. The main content area is titled 'Select Default Targets:' and shows two lists: 'Available' (empty) and 'Chosen' (containing 'VT-Medrec-1'). A note on the right says 'Select de These ta that does'. At the bottom, there's a 'Use Realm:' dropdown set to 'mynewrealm' (highlighted with a red box), and a 'Primary Identity Domain:' input field containing 'idd_dp1'.

- v. Click on **Domain Partitions**, then on **Control** tab.
- vi. Select the box near dp1 and click on **Start**.

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a navigation tree under 'Domain Structure' for 'base_domain' with 'Domain Partitions' selected. A red box highlights this selection. On the right, the 'Control' tab of the 'Summary of Domain Partitions' page is active. It displays a table of domain partitions:

	Name	Default Target(s)	State	Status of Last Action
<input checked="" type="checkbox"/>	dp1	VT-Medrec-1	SHUTDOWN	TASK COMPLETED
<input type="checkbox"/>	dp2	VT-Medrec-2	RUNNING	TASK COMPLETED
<input type="checkbox"/>	dp3	VT-daytrader	RUNNING	TASK COMPLETED

Verified that we have two security realms in different domain partition in single domain

- i. Go to Firefox and type the URL: <http://localhost:7101/dp1/medrec/index.xhtml>
- ii. Under Administrator, click on Login.
- iii. Login with old security realm credential that is administrator/administrator123.
- iv. You must get “Incorrect username or password!”
- v. Login with new security realm credential that is administrator/welcome1.
- vi. Click on Logout. Click on Logout again.
- vii. Go to Firefox and type the URL: <http://localhost:7101/dp2/medrec/index.xhtml>
- viii. Under Administrator, click on Login.
- ix. Login with new security realm credential that is administrator/welcome1.
- x. You must get “Incorrect username or password!”
- xi. Login with old security realm credential that is administrator/administrato123.
- xii. Click on Logout. Click on Logout again.

Here we learned how you can have two security realms in a domain. So one of your domain partitions can use default security realm and other can use custom security realm created by you in same domain.

LAB 4: EXPORT/IMPORT DOMAIN PARTITION

Overview

Exporting and importing partitions let WLS system administrators easily move partitions from one domain to another, including the applications that are deployed to the partition. This feature is useful for replicating partitions across the domains and for moving domains from a development to a testing then production environment.

Exporting a domain partition creates a partition backup and stores it in an archived format. You can export a domain partition from source domain with its entire configuration and data. With few configuration changes, you can then import the partition archive into another instance of multi-tenant WLS (the target domain). You might need to update any domain dependencies, such as targets and security realms, and optionally update other attributes in the partition configuration to make it valid.

When a partition is exported from the source domain it is packaged in a partition archive. Included in the partition archive is:

- The partition configuration.
- Any resource group contained in the partitions.
- Any resource group templates referred to by those resource groups.
- The contents of the file system, <partition-file-system>/config directory.
- Optionally, application binaries and configuration for applications deployed to the partition.

No application runtime state or application-specific runtime configuration is included in the partition archive. Examples of what would not be exported are JMS messages in queues, users in an embedded LDAP realm.

In this Lab, We will create a Non-JRF domain dev_domain and configure it with all required resources for Medrec application. You will remove domain partition dp1 from base_domain. As this domain partition is targeted to Virtual Target VT-Medrec-1 and we are going to import a new domain partition on this Virtual target. So we need to remove this domain partition dp1 for this Lab2.

We are going to learn the following:

- Exporting a domain partition from a Non-JRF domain dev_domain and importing it to a Restricted JRF domain base_domain.

Note: To simplify import/export both domains contain Virtual Target with the same name. In our case, base_domain and dev_domain has VT-Medrec-1 as Virtual Target. It is possible to make import/export without that restriction. To import partition and bind it to virtual target of different name, you should modify settings inside associated “*-attributes.JSON” file

Stop and remove domain partition dp1 from base_domain.

- In Fusion Middleware Control <http://localhost:7001/em>, Click on **WebLogic Domain -> Environment -> Domain Partition**.
- Check the **box** near **dp1** then click on **Control -> Stop->Force Stop Now**. On the Confirmation Screen Click on **OK**. Once you see the message "**Partition state after the operation is SHUTDOWN**" then click on **Close**.

Name	Status	OTD Partition	Realm	Default Targets	Available Targets
dp1	Up (3)	dp1	When work completes	VT-Medrec-1	VT-Medrec-1
dp2	Running	dp2	Force stop now	VT-Medrec-2	VT-Medrec-2
dp3	Running	dp3		VT-daytrader	VT-daytrader

- c. Check the box near **dp1** and make it highlighted then click on **Delete**. In Delete Domain Partition Screen, click on OK.

The screenshot shows the Oracle Enterprise Manager interface for a WebLogic Domain named 'base_domain'. The 'Domain Partitions' section is displayed. Two pie charts are shown: one for 'Status' (Up 2, Down 1) and one for 'State' (Running 2, Shutdown 1). Below the charts is a table of domain partitions. The row for 'dp1' is selected and has a red box around its 'Name' column. The 'Delete' button in the toolbar above the table is also highlighted with a red box. The table columns are: Name, Status, State, OTD Partition, Realm, Default Targets, and Available Targets. The data in the table is:

Name	Status	State	OTD Partition	Realm	Default Targets	Available Targets
dp1		Shutdown		mynewrealm	VT-Medrec-1	VT-Medrec-1
dp2		Running			VT-Medrec-2	VT-Medrec-2

- d. Go to Firefox and type the URL: <http://localhost:7101/dp1/medrec/>
e. Confirm that page return “Error 404—Not Found”.


The screenshot shows a Firefox browser window with the following details:

- Address bar: localhost:7101/dp1/medrec/ (highlighted with a red box)
- Page title: Error 404--Not Found
- Text content: "Error 404--Not Found" (highlighted with a red box)
- Text below: "From RFC 2068 Hypertext Transfer Protocol -- HTTP/1.1:"
- Section: "10.4.5 404 Not Found"
- Description: "The server has not found anything matching the Request-URI. No indication is given of whether the condition is temporary or permanent."
- Text at the bottom: "If the server does not wish to make this information available to the client, the status code 403 (Forbidden) can be used instead. The 410 (Gone) status code SHOULD be used if the server knows, through some internally configurable mechanism, that an old resource is permanently unavailable and has no forwarding address."

Create a new dev single server (Admin Server) domain


We are going to create a domain which contains only Admin Server, as the previous domain base_domain is created with RESTRICTED-JRF template. But this domain will be created by default template that is with basic template.

- a. Open a new tab.
- b. cd /u01/wins/wls1221/oracle_common/common/bin/
- c. ./config.sh
- d. Select “Create a new domain” and Enter “/u01/wins/wls1221/user_projects/domains/dev_domain” as Domain Location then click on **Next**.



- e. Leave Default on Templates then click on **Next**.
- f. Enter **weblogic/welcome1** as Name/Password in Administrator Account then click on **Next**.
- g. Leave default on Domain Mode and JDK then click on **Next**.
- h. Check the box near to Administration Server then click on **Next**.

- i. In Administration Server, Enter 9001 as Listen Port then click on **Next**.



- j. Click on **Create** then click on **Next**. Click on **Finish**.

Configure domain for Medrec Application.

In Lab 2, you configure the domain using Fusion Middleware console, but here we are going to configure domain using Weblogic Admin Console. The operation related to Multitenancy, we can also perform using WebLogic Admin Console.

- cd /u01/wls/wls1221/user_projects/domains/dev_domain/
- ./startWebLogic.sh
- In Tab, Click on Terminal -> Set Title, Enter **dev_admin** as Title then Click on OK.
- Go to Firefox and type the WebLogic Admin Console URL:
<http://localhost:9001/console>.
- Enter **weblogic/welcome1** as **Username/Password** then click on Login.
- Creation of Virtual Target.
 - Click on **Environment -> Virtual Targets**.



- ii. Click on New.
- iii. Enter the following then click on **OK**.

Name:	VT-Medrec-1 (Both Virtual Target Name will be same)
Target:	Admin Server
URI Prefix:	/devDP

Home >Summary of Virtual Targets

Create a New Virtual Target

Virtual Target Properties

The following properties will be used to identify your new virtual target.

What would you like to name your new virtual target?

Name:

Select one managed server or cluster on which you would like to deploy this virtual target

Target:

Enter one or more hostnames, each on separate lines within the text box.

Host Names:

Enter an URI prefix starting with a / (forward slash).

URI Prefix:

OK **Cancel**

- g. Creation of Domain Partition.
- i. Click on **Domain Partition -> New**.

ORACLE WebLogic Server Administration Console 12c

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- + dev_domain
 - Domain Partitions **(highlighted)**
 - Environment
 - Servers
 - Clusters
 - Coherence Clusters
 - Resource Groups
 - Resource Group Templates
 - Machines
 - Virtual Hosts
 - Virtual Targets
 - Work Managers
 - Concurrent Templates
 - Resource Management

How do I...

- Create Domain Partitions
- Configure Domain Partition General Settings
- Export partitions
- Import partitions

System Status

Health of Running Servers

Home >Summary of Virtual Targets >Summary of Domain Partitions

Summary of Domain Partitions

Configuration Control

Domain partitions are an administrative and runtime slice of a WebLogic domain that is dedicated to running application instances and related resources for a tenant.

This page summarizes the domain partitions that have been configured in the current WebLogic Server domain.

Customize this table

Domain Partitions (Filtered - More Columns Exist)

New	Delete	Import	Export	Showing 0 to 0 of 0 Previous Next
<input type="checkbox"/> Name	Resource Groups	Default Target(s)	State	
There are no items to display				

New **Delete** **Import** **Export** Showing 0 to 0 of 0 Previous | Next

- ii. Enter **Medrec-Dev** as Name and **unchecked** the box for **Default Resource Group**. Click on **Next**.
- iii. Check the box for **VT-Medrec-1** then click on **Next**.
- iv. In Default Targets, Move **VT-Medrec-1** to Chosen. Click on **Finish**.

Create a New Domain Partition

Domain Partition Configuration

The following properties will be used to configure your new domain partition.

Default Targets:

Available:	Chosen:
[Empty]	<input checked="" type="checkbox"/> VT-Medrec-1

Security: Not assigned
Realm:

Partition File System

- v. In **Domain Partition -> Control tab**, check the box near Medrec-Dev and click on Start.

Summary of Domain Partitions

Control

This page lists the state of the domain partitions in this WebLogic Server domain.

Domain Partitions

<input checked="" type="checkbox"/>	Name	Default Target(s)	State	Status of Last Action
<input checked="" type="checkbox"/>	Medrec-Dev	VT-Medrec-1	SHUTDOWN	None

Showing 1 to 1 of 1 Previous | Next

Start **Resume** **Suspend** **Shutdown**

Start **Resume** **Suspend** **Shutdown**

h. Creation of Resource Group

- i. Click on domain partition **Medrec-Dev**.
- ii. Click on **Resource Groups -> Configuration tab** then click on New.

This page summarizes the resource groups of a domain partition that have been configured in the current WebLogic Server domain.

Name	Resource Group Template	Effective Targets	State	Notes
There are no items to display				

- iii. Enter **appRG** as Name, Leave others as default then click on **OK**.

Note: We have created script through which you can create the remaining resources, you need to run the file **MedrecInMedrec-Dev.sh** inside **/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab4**, and then you can directly go to **Exporting the domain partition** section.

i. Creation of Data Source.

- i. Click on **dev_domain -> Services -> Data Sources** then click on **New-> Generic Data Sources**.

A JDBC data source is an object bound to the JNDI tree that provides database connectivity through a pool of JDBC connections. Applications can look up a data source on the JNDI tree and then borrow a database connection from a data source.

Type	JNDI Name	Targets	Scope	Domain Partitions
There are no items to display				

ii. Enter the following and click on **Next**.

Name: MedRecGlobalDataSourceXA
JNDI Name: jdbc/MedRecGlobalDataSourceXA
Scope: appRG in Medrec-Dev
Database Type: Oracle

Create a New JDBC Data Source

Back | **Next** | Finish | Cancel

JDBC Data Source Properties

The following properties will be used to identify your new JDBC data source.

* Indicates required fields

What would you like to name your new JDBC data source?

* Name: **MedRecGlobalDataSourceXA**

What scope do you want to create your data source in ?

Scope: **appRG in Medrec-Dev**

What JNDI name would you like to assign to your new JDBC Data Source?

JNDI Name: **jdbc/MedRecGlobalDataSourceXA**

What database type would you like to select?

Database Type: **Oracle**

iii. Select “**Oracle’s Driver (Thin XA) for Service connections; Version: Any**” then click on **Next**.

iv. In Transaction Options, click on **Next**.

v. Enter the following and click on **Next**.

Database Name: pdborcl
Host Name: localhost
Port: 1521
Database User Name: medrec1
Password: medrec1

Create a New JDBC Data Source

Back | **Next** | Finish | Cancel

Connection Properties

Define Connection Properties..

What is the name of the database you would like to connect to?

Database Name: pdborcl

What is the name or IP address of the database server?

Host Name: localhost

What is the port on the database server used to connect to the database?

Port: 1521

What database account user name do you want to use to create database connections?

Database User Name: medrec1

What is the database account password to use to create database connections?

Password: •••••

Confirm Password: •••••|

- vi. Click on **Test Configuration** and verify the connectivity.
vii. Click on **Next** then Click on **Finish**.

j. Creation of JMS Server.

- i. Click on **Services -> Messaging -> JMS Servers**.
ii. Click on **New**.

ORACLE WebLogic Server Administration Console 12c

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- dev_domain
 - Domain Partitions
 - Environment
 - Deployments
 - Services
 - Messaging
 - JMS Servers
 - Store-and-Forward Agents
 - JMS Modules
 - Path Services
 - Bridges
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers

How do I...

- Configure JMS servers
- Configure JMS system modules

Welcome, weblogic | Connected to: dev_domain

Home >Summary of Virtual Targets >Summary of Domain Partitions >Medrec-Dev >Summary of JDBC Data Sources >Summary of JMS Servers

Summary of JMS Servers

JMS servers act as management containers for the queues and topics in JMS modules that are targeted to them. This page summarizes the JMS servers that have been created in the current WebLogic Server domain.

Customize this table

JMS Servers (Filtered - More Columns Exist)

<input type="checkbox"/>	Name	Persistent Store	Target	Current Target	Health	Scope	Domain Partitions
There are no items to display							

New Delete Showing 0 to 0 of 0 Previous | Next

<input type="checkbox"/>	Name	Persistent Store	Target	Current Target	Health	Scope	Domain Partitions
Showing 0 to 0 of 0 Previous Next							

New Delete Showing 0 to 0 of 0 Previous | Next

iii. Enter the following and click on **Next**.

Name: DevJMServer
Scope: appRG in Medrec-Dev

Create a New JMS Server

Back Next Finish Cancel

JMS Server Properties

The following properties will be used to identify your new JMS Server.
* Indicates required fields

What would you like to name your new JMS Server?

* Name: **DevJMServer**

Would you like this new JMS Bridge Destination to be restricted to a specific resource group template or resource group ?

Scope: **appRG in Medrec-Dev**

Back **Next** Finish Cancel

iv. Click on **Create a New Store**.

v. Select “File Store” as Type then click on **Next**.

vi. Enter “MedrecDev-fs” as Name and “appRG in Medrec-Dev” as Scope then click on **Next**. Click on **Finish**.

Create a New JMS Server

Back Next Finish Cancel

File Store Properties

The following properties will be used to identify your new file store.
* Indicates required fields

What would you like to name your new file store?

* Name: **MedrecDev-fs**

What scope do you want to create your jms file store in ?

Scope: **appRG in Medrec-Dev**

The pathname to the directory on the file system where the file store is kept. This directory must exist on your system, so be sure to create it before completing this tab.

Directory:

Back **Next** Finish Cancel

vii. Select “**MedrecDev-fs**” as Persistent Store then click on **Next**.



viii. Click on **Finish**.


k. Creation of JMS Module.

i. Click on **Services -> Messaging -> JMS Modules** then click on **New**.

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar has a 'Domain Structure' tree with nodes like 'dev_domain', 'Domain Partitions', 'Environment', 'Deployments', 'Services', 'Messaging', 'JMS Servers', 'Store-and-Forward Agents', 'JMS Modules' (which is highlighted with a red box), 'Path Services', 'Bridges', 'Data Sources', 'Persistent Stores', and 'Foreign JNDI Providers'. A 'How do I...' section at the bottom lists 'Configure JMS system modules' and 'Configure resources for JMS system modules'. The main content area is titled 'Summary of JMS Modules'. It contains a brief description of JMS system resources and a table titled 'JMS Modules'. The table has columns for 'Name' (with a sorting arrow icon), 'Type', 'Scope', and 'Domain Partitions'. A note below the table says 'There are no items to display'. At the bottom of the table are 'New' and 'Delete' buttons, along with navigation links for 'Showing 0 to 0 of 0 Previous | Next'.

ii. Enter **DevJMSModule** as Name and “**appRG in Medrec-Dev**” then click on **Next**.

- iii. Check the box for “Would you like to add resources to this JMS system module” then click on **Finish**.



- I. Creation of Subdeployment.
i. Select **Subdeployments** tab then click on New.

	Name	Resources	Targets
There are no items to display			

- ii. Enter **DevMedrecJMS** as Name then click on **Next**.
iii. Select **DevJMSServer** as Target then click on **Finish**.

- m. Creation of Connection Factory.
- Click on Configuration tab then click on New.

Settings for DevJMSModule

Configuration	Subdeployments	Security	Notes																								
This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.																											
Name:	DevJMSModule	The name of this JMS system module. More Info...																									
Scope:	appRG in Medrec-Dev	Specifies if the JMS system module is accessible within the domain, a partition, or a resource group template. More Info...																									
Descriptor File Name:	partitions/Medrec-Dev/jms/devjmsmodule-jms.xml	The name of the JMS module descriptor file. More Info...																									
This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.																											
<p>Customize this table</p> <p>Summary of Resources</p> <table border="1"> <thead> <tr> <th>New</th> <th>Delete</th> <th colspan="4">Showing 0 to 0 of 0 Previous Next</th> </tr> <tr> <th><input type="checkbox"/></th> <th>Name </th> <th>Type</th> <th>JNDI Name</th> <th>Subdeployment</th> <th>Targets</th> </tr> </thead> <tbody> <tr> <td colspan="6">There are no items to display</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>New</th> <th>Delete</th> <th colspan="4">Showing 0 to 0 of 0 Previous Next</th> </tr> </thead> </table>				New	Delete	Showing 0 to 0 of 0 Previous Next				<input type="checkbox"/>	Name	Type	JNDI Name	Subdeployment	Targets	There are no items to display						New	Delete	Showing 0 to 0 of 0 Previous Next			
New	Delete	Showing 0 to 0 of 0 Previous Next																									
<input type="checkbox"/>	Name	Type	JNDI Name	Subdeployment	Targets																						
There are no items to display																											
New	Delete	Showing 0 to 0 of 0 Previous Next																									

- Select the box for Connection Factory then click on **Next**.
 - Enter **DevMedRecConnectionFactory** as Name and **com.oracle.medrec.jms.connectionFactory** and leave other default then click on **Next**.
 - Click on **Finish**.
- n. Creation of Distributed Queue.
- Click on New.
 - Select the box for Distributed Queue then click on **Next**.
 - Enter **PatientNotificationQueue** as Name and **com.oracle.medrec.jms.PatientNotificationQueue** as JNDI Name and leave other default then click on **Next**.

- iv. Click on **Advanced Targeting**, Select DevMedrecJMS as Subdeployments and DevJMSServer as Targets then click on **Finish**.

Create a New JMS System Module Resource

Back | Next | **Finish** | Cancel

The following properties will be used to target your new JMS system module resource

Use this page to select a subdeployment to assign this system module resource. A subdeployment is a mechanism by which JMS resources are grouped and targeted to a server instance, cluster, or SAF agent. If necessary, you can create a new subdeployment by clicking the **Create a New Subdeployment** button. You can also reconfigure subdeployment targets later by using the parent module's subdeployment management page.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

Subdeployments: **DevMedrecJMS** ▾ Create a New Subdeployment

What targets do you want to assign to this subdeployment?

Targets: **DevJMSServer** ▾

Back | Next | **Finish** | Cancel

- o. Creation of Mail Session.
i. Click on **Services -> Mail Sessions**.



- ii. Click on **New**.
iii. Enter the following then click on **Next**.
- | | |
|------------|------------------------|
| Name: | MedRecMailSession |
| JNDI Name: | mail/MedRecMailSession |
| Scope: | appRG in Medrec-Dev |

Create a New Mail Session

Back **Next** Finish Cancel

Mail Session Properties

The following property will be used to identify your new mail session.

* Indicates required fields

What would you like to name your new mail session?

* Name: **MedRecMailSession**


* JNDI Name: **mail/MedRecMailSession**

What scope do you want to create your mail session in ?

Scope: **appRG in Medrec-Dev**

- iv. Click on **Finish**.
- p. Deployments of Application
- Click on **Deployments** then on **Install**.
 - Select the medrec.ear application from the Path /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab4/ then click on **Next**.

- iii. Select “**Install this deployment as an application**” and “**appRG in Medrec-Dev**” as Scope then click on **Next**. Click on **Finish**.



- iv. Click on **Install** then Select the physician.ear application from the Path /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab4/ then click on **Next**.
- v. Select “**Install this deployment as an application**” and “**appRG in Medrec-Dev**” as Scope then click on **Next**. Click on **Finish**.
- vi. Click on **Install** then Select the chat.war application from the Path /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab4/ then click on **Next**.
- vii. Select “**Install this deployment as an application**” and “**appRG in Medrec-Dev**” as Scope then click on **Next**. Click on **Finish**.
- viii. Go to Firefox and type the URL: <http://localhost:9001/devDP/medrec/> and confirm the execution of application.

Exporting the domain partition

- Go back to admin console <http://localhost:9001/console/> of dev_domain.
- Click on **Domain Partition**, and then check the box near to “**Medrec-Dev**” then click on Export.

Name	Resource Groups	Default Target(s)	State
Medrec-Dev	appRG	VT-Medrec-1	RUNNING

- Select the box for “**Include Application Bits**” and enter **/home/oracle/Desktop** as Path then click on **OK**.

OK | Cancel

Export a Domain Partition

Select or enter the directory where the domain partition archive should be placed. Each domain partition should be located in its own directory. The domain partition archive will be overwritten if it already exists. Other files in the directory may be overwritten as well.

Domain: Medrec-Dev
Partition Name:

Do you want to include the installed applications in the exported ZIP file?

Include Application Bits

What is the full path to the key file you want to use to encrypt attributes in the partition archive?

Full path to the Key File: [Path Field]

Where do you want the domain partition archive to be placed ?

Path: /home/oracle/Desktop

- Go to Desktop and Verify the Creation of **Medrec-Dev-attributes.json** and **Medrec-Dev.zip** file.

Importing the domain partition

- Go back to EM console of base_domain. Go to Firefox and type the WebLogic Admin Console URL: <http://localhost:7001/em>.
- Enter **weblogic/welcome1** as Username/Password and click on Login.
- Click on **WebLogic Domain-> Environment ->Domain Partition**.
- Click on Import. Click on **Browse** button, Select the file **Medrec-Dev.zip** from **/home/oracle/Desktop** directory then click on **OK**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The top navigation bar includes 'WebLogic Domain' and 'weblogic'. The main content area is titled 'base_domain'. Under 'Domain Partitions', there is a pie chart showing 'Up (2)' and 'Running (2)'. Below the chart is a table with columns: Name, Status, State, OTD Partition, Realm, Default Targets, and Available Targets. Two rows are listed: dp2 (Status Up, State Running, Default Targets VT-Medrec-2, Available Targets VT-Medrec-2) and dp3 (Status Up, State Running, Default Targets VT-daytrader, Available Targets VT-daytrader). A red box highlights the 'Import' button in the toolbar above the table. The status bar at the bottom right indicates 'Nov 5, 2015 9:32:21 PM PST'.

The screenshot shows the 'Import Domain Partition' dialog box. It contains instructions: 'Use this dialog to import a partition archive into the domain. The archive was previously generated by exporting a partition.' Below this is a text input field labeled 'Import domain partition from zip file' containing the path '/home/oracle/Desktop/Medrec-Dev.zip', which is also highlighted with a red box. To the right of this input field is a 'Browse...' button. There are two checkboxes: 'Overwrite existing resource group templates' (unchecked) and 'Override domain partition name (optional)' followed by a text input field. Below these is another text input field for 'Full path to the key file used to decrypt attributes (optional)'. At the bottom right are 'OK' and 'Cancel' buttons, with 'OK' also highlighted with a red box.

- e. Initially it will have State “**Unknown**”. Wait for 1 or 2 minute, click on Refresh icon to get the current state.
- f. Once the status for **Medrec-Dev** domain partition is **Shutdown**, check the box, near Medrec-Dev then click on **Control -> Start**. Click on **Close**. Click on the Refresh icon to get the current state.

Domain Partitions

Domain partitions are the building blocks of WebLogic server multi-tenancy (MT). Multi-tenancy permits multiple client organizations to share a domain, improving efficiency and reducing operation costs. Before creating a domain partition, you must first create one or more virtual targets. Look at the Getting Started topics for more information.

► Getting Started with Multi-Tenancy

Hide Pie Chart

Name	Status	State	OTD Partition	Realm	Default Targets	Available Targets
dp2	Up	Running			VT-Medrec-2	VT-Medrec-2
dp3	Up	Running			VT-daytrader	VT-daytrader
Medrec-Dev	Up	Running			VT-Medrec-1	VT-Medrec-1

- g. Go to Firefox and type the URL: <http://localhost:7101/dp1/medrec/>
- h. Click on “**Getting Started!**” Under Administrator, click on Login.
- i. Enter **administrator/administrator123** as Username/Password then click on Sign in.
- j. Click on Logout. Click on Logout again.

Note: As we have VT-Medrec-1 as Virtual target in both the domains `base_domain` and `dev_domain`. In `base_domain`, we have added administrator user to default security realm. So as this domain partition becomes part of this domain. It also uses the default security realm. Here you are accessing the application using `/dp1` in the URL because, we have Virtual target VT-Medrec-1 has `/dp1` as URI, So Virtual target definition do not change during import.

- k. Come back to tab **dev_admin**.
- l. Stop the Weblogic Server running in `dev_domain`, by pressing **Ctrl +C** in tab in which Admin Server is running. Close the Tab.

LAB 5: RESOURCE CONSUMPTION MANAGEMENT

Overview

When applications that are deployed to multiple collocated Domain Partitions, access shared resources (low level resources such as CPU, network, storage) two key problems are likely to be faced:

- Contention and unfairness during allocation: Multiple request for a Shared resources results in contention and interference. Abnormal resource consumption requests may happen due to benign reasons (high traffic-genuine or DDoS), misbehaving, buggy applications or malicious code. These requests could overload the capacity of shared resources, thereby preventing another consumer's access to the resource.
- Variable performance leading to potential Service Level Agreement (SLA) violations: From a cloud operations perspective, performance for different collocated consumers.

It is therefore critical to manage and isolate access to shared resources in the WebLogic application Server by domain partition to ensure fairness in allocation, prevent contention/interferences of access to shared resources and to provide consistent performance for multiple co resident tenants. The Resource Consumption Management (RCM) feature in WebLogic 12.2.1 Multitenancy allows WebLogic System administrator to specify resource consumption management policies (allows the specification of constraints, recourse actions and notification) on shared resources such as CPU, Heap, File and Network. You can create resource manager based on the following parameter:

- Retained Heap
- CPU Time
- Open File Descriptor

You need to provide the value for below action, as it reaches to that value. It will trigger the following action:

- Notify:** Inform administrator that a threshold has been crossed.
Slow: Reduce Partition ability to consume more resources.
Stop: Initiate the shutdown sequence for the offending partition.


In this lab first we create a resource manager based on the Heap size then we specify the values with respective actions. So as following values reaches that action get triggered. We will use sample application through which we can modify the value of Heap size and we will see the action associated.

In this lab we are going to perform the following operations:

- Enabling RCM by adding extra arguments in Server Java Arguments.
- Creating Resource manager on the basis of Heap Size.
- Assign Resource manager to a Domain Partition.
- Running an example to understand the functioning of RCM.

Enabling RCM by adding extra arguments in Server JAVA_OPTION Arguments


- Go to Firefox and type the Fusion Middleware Control Console URL:
<http://localhost:7001/em>
- Click on **WebLogic Domain -> Control -> Clusters.**



The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The left sidebar has 'Domain' selected. Under 'Control', 'Clusters' is highlighted and selected. A tooltip explains multi-tenancy (MT) and virtual targets. The main panel shows a pie chart indicating 3 clusters are running. Below it is a table with columns TD Partition, Realm, Default Targets, and Available Targets. The table data is as follows:

TD Partition	Realm	Default Targets	Available Targets
		VT-Medrec-2	VT-Medrec-2
		VT-daytrader	VT-daytrader
		VT-Medrec-1	VT-Medrec-1

- Check the boxes near app-cluster then click on **Control -> Shutdown ->Force Shutdown Now.** Click on **Forcibly Shutdown Servers.**




The screenshot shows the 'Clusters (Control)' page. The 'Control' dropdown is open, showing options: Start, Resume, Suspend, Shutdown, and Restart SSL. The 'Shutdown' option is selected, and its submenu is open, showing 'When work completes' and 'Force Shutdown Now'. The 'app-cluster' row is selected in the table. The table columns are Name, Cluster Type, Servers, Cluster Messaging Mode, Default Load Algorithm, and Replication Type. The data for the app-cluster is: Name (app-cluster), Cluster Type (Dynamic), Servers (2), Cluster Messaging Mode (Unicast), Default Load Algorithm (Round Robin), and Replication Type ((None)).

- d. Open a new tab.
- e. cd /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab5
- f. cp setDomainEnv.sh /u01/wins/wls1221/user_projects/domains/base_domain/bin/
- g. In above command we have modified the JAVA_OPTIONS as specified below.
JAVA_OPTIONS="-XX:+UnlockCommercialFeatures -XX:+ResourceManagement -XX:+UseG1GC \${JAVA_OPTIONS} \${JAVA_PROPERTIES}"
- h. cd /u01/wins/wls1221/user_projects/domains/base_domain/bin/
- i. ./setDomainEnv.sh
- j. Go back to Fusion middleware control then click on **WebLogic Domain > Control -> Clusters**.
- k. Check the box near to app-cluster-1 to make it highlighted and then click on **Control -> Start -> Start Servers**.
- l. tail -f /u01/wins/wls1221/user_projects/domains/base_domain/servers/app-cluster-1/logs/app-cluster-1.log
- m. In this tab, Click on Enter Terminal -> Set Title and app-cluster-1 then click on **OK**.
We will use these logs to monitor resource consumption manager lab.

Creating a Resource Manager and Configuring Resource Manager for a domain partition

- a. Go to FMW control <http://localhost:7001/em>
 - b. Enter weblogic/welcome1 as Username/Password then click on Login.
 - c. Click on **WebLogic Domain->Environment -> Resource Consumption Managers**.
 - d. Click on **Add Resource Manager** and Enter the following value then click on **OK**
- | | |
|-------------------|--------------|
| Resource Manager: | smallHeap |
| Policy Type: | HeapRetained |
| Shutdown: | 400 |
| Slow: | 250 |
| Notify: | 200 |



Associate the Resource Manager with Medrec-Dev domain partition.


- Click on **WebLogic Domain -> Environment->Domain Partition** then click on **Medrec-Dev**.
- Click on **Domain Partition ->Administration -> Resource Sharing**.

The screenshot shows the Oracle Enterprise Manager interface for a 'Medrec-Dev' domain. The left sidebar has sections for Monitoring, Resource, Deployment, and Administration. Under 'Administration', the 'Resource Sharing' option is highlighted with a red box. The main panel displays 'JDBC and JTA Usage' and 'Resource Usage' metrics, with 'Resource Sharing' listed under 'General'.

- Under **Resource Manager Configuration**, and Select “**Use a Resource Manager configured for the domain**” and choose “**smallHeap**” then click on **Save**.

The screenshot shows the 'Partition Work Manager Configuration' and 'Resource Manager Configuration' pages for the 'Medrec-Dev' partition. In the 'Partition Work Manager Configuration', the 'No Partition Work Manager' option is selected. In the 'Resource Manager Configuration', the 'Use a resource manager configured for the domain: smallHeap' option is selected and highlighted with a red box. Both pages have 'Save' and 'Revert' buttons at the top right.

- d. Click on **Start Up** near Domain partition. Click on Close.



- e. Open a new tab.
- f. cd /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab5
- g. ./DeployHeap.sh
- h. Close the tab.
- i. Go back to Firefox and type the URL: <http://localhost:7101/dp1/heapApp/>
- j. Enter 160 in **Allocate Heap** then click on Submit then observe the logs of app-cluster-1 managed server. After that no Warning message should be observed in the log as we didn't cross the boundary of any RCM action.

- k. Enter 50 in **Allocate Heap** then click on Submit then observe the logs of app-cluster-1 managed server. We will cross the first ("Notify") boundary of RCM actions. So we should see associated log message.

```
####<Nov 5, 2015 10:12:23 PM PST> <Notice> <RCM> <localhost.localdomain> <app-cluster-1> <Thread-73> <weblogic> <> <f11a4b64-f694-4af6-8b28-7f32a9f96d47-0000003c> <1446790343249> <[Notifying Quota Reached For Partition: Medrec-Dev] [severity-value: 32] [rid: 0] [Previous Usage: 207153216] [partition-id: cd3147a2-5e49-4731-bad1-94689b69cd5b] [Resource Name: com.oracle.weblogic.rcm.framework.base.HeapRetainedResourceAttributes] [Current Usage: 215825984] [partition-name: Medrec-Dev]> <BEA-2165799> <Resource Consumption Management Notification Message: Given quota has been reached for the partition and a notify action has been executed.>
```


- l. Enter 50 in **Allocate Heap** then click on Submit then observe the logs of app-cluster-1 managed server. We crossed the second limit ("Slow") so the associated message should be seen in the log.

```
####<Nov 5, 2015 10:14:04 PM PST> <Notice> <RCM> <localhost.localdomain> <app-cluster-1> <Thread-72> <weblogic> <> <f11a4b64-f694-4af6-8b28-7f32a9f96d47-0000003d> <1446790444011> <[Slow Action Quota Reached For Partition: Medrec-Dev] [Current Usage: 299741448] [severity-value: 32] [Previous Usage : 298576032] [Was Required action to Slow the Partition is executed?: true] [Resource Name: com.oracle.weblogic.rcm.framework.base.HeapRetainedResourceAttributes] [partition-id: cd3147a2-5e49-4731-bad1-94689b69cd5b] [partition-name: Medrec-Dev] [rid: 0]> <BEA-2165800> <Resource Consumption Management Slow Message: Given quota has been reached for the partition and a slow action has been executed.>
```

- m. Enter 150 in **Allocate Heap** then click on Submit then observe the logs of app-cluster-1 managed server. This will exceed the limit of memory allowed to be used by that partition. So to prevent other partitions from suffering of lack of memory WebLogic will shutdown the partition.

```
####<Nov 5, 2015 10:15:15 PM PST> <Notice> <RCM> <localhost.localdomain> <app-cluster-1> <Thread-74> <weblogic> <> <f11a4b64-f694-4af6-8b28-7f32a9f96d47-0000003e> <1446790515227> <[severity-value: 32] [Proposed Usage: 459764600] [rid: 0] [partition-id: cd3147a2-5e49-4731-bad1-94689b69cd5b] [Shutdown Action Quota Reached For Partition: Medrec-Dev] [Resource Name: com.oracle.weblogic.rcm.framework.base.HeapRetainedResourceAttributes] [Current Usage: 442240104] [partition-name: Medrec-Dev]> <BEA-2165801> <Resource Consumption Management Shutdown Message: Given quota has been reached for the partition and a shutdown action has been executed.>
```

- n. Refresh the page, <http://localhost:7101/dp1/heapApp/> which return 404 and confirm shutdown of the domain partition Medrec-dev in managed server 1.



From RFC 2068 Hypertext Transfer Protocol -- HTTP/1.1:

10.4.5 404 Not Found

The server has not found anything matching the Request-URI. No indication is given of whether the condition is temporary or permanent.

If the server does not wish to make this information available to the client, the status code 403 (Forbidden) can be used instead. The 410 (Gone) status code SHOULD be used if the server knows, through some internally configurable mechanism, that an old resource is permanently unavailable and has no forwarding address.

Note: As this domain partition is target to virtual target which is target at cluster which consists of two managed servers. So this domain partition stopped working on managed server 1, but if you access the application on managed server 2, you still will be able to access the application in this domain partition. If similar things happen in managed server 2 and domain partition shutdown on managed server 2 as well, then domain partition will be shutdown.

LAB 6: OTD INTEGRATION AND RESOURCE MIGRATION

Overview

This lab describes how Oracle Traffic Director can front end a WLS MT Deployment topology for a large enterprise, providing an integrated, end to end administration experience for the server life cycle, and partition management.

For this lab, we installed OTD in Collocated mode. We create one domain otd_domain for OTD instance then we show how to register an OTD instance in WebLogic Domain base_domain. Then we show how you can create partition front ended by OTD.

Oracle Traffic Director has an administration plug in which is responsible for handling life cycle events and automatically configuring Oracle Traffic Director with the corresponding configuration

When you create a WLS MT partition, a corresponding Oracle Traffic Director partition is created for you. The Oracle Traffic Director partition is simply a grouping with the same name as the partition and the resource group. The life cycle of an Oracle Traffic Director partition and its corresponding artifacts are linked to the life cycle of the partition.

The Oracle Traffic Director console provided a partition table with the list of Oracle Traffic Director Partitions to identify the Oracle Traffic director artifacts that are mapped to partitions and resource groups.

Oracle Traffic Director Artifacts map to WebLogic Server MT artifacts as follows:


- Each cluster maps to an origin server pool.
- The hostnames of a virtual target that is associated with the partitions and/or resource groups maps to a virtual server.
- Each partition or resource group maps to a route within the virtual server corresponding to the hostname of the virtual target.

In this lab, we are going to perform the below operations.


- We create an OTD domain; in that domain we create a machine and OTD configuration.
- We register that OTD Runtime instance inside the WebLogic domain.
- We create a domain partition front ended by OTD.
- We deploy a simple application to verify the OTD integration with domain partition.
- We migrate a resource group from one cluster to other cluster.

Create OTD Restricted JRF Domain


- a. Open a new tab.
- b. cd /u01/wins/wls1221/oracle_common/common/bin/
- c. ./config.sh
- d. Select “Create a new domain” and enter “**/u01/wins/wls1221/user_projects/domains/otd_domain**” as Domain Location then Click on Next.




- e. Enter “**Oracle Traffic Director- Restricted JRF**” Template as it also selects other required template then Click on Next.




- f. Enter “/u01/wins/wls1221/user_projects/applications/otd_domain” as Application Location then Click on Next.




- g. Enter “**weblogic/welcome1**” as **Username/Password** then Click on Next.
- h. Leave Default in **Domain Mode and JDK** then Click on Next.
- i. In **Advanced Configuration**, Select the box near **Administration Server** then Click on Next.



- j. Change Listen port to **8001** then click on Next.



- k. Click on **Create**.
- l. Click on **Next** then Click on **Finish**.
- m. cd /u01/wins/wls1221/user_projects/domains/otd_domain/
- n. ./startWebLogic.sh
- o. In terminal, Click on **Terminal -> Set Title**. Enter **otd_admin** as Title then click on OK.



```
oracle@localhost:/u01/wins/wls1221/user_projects/domains/otd_domain
File Edit View Search Terminal Help
2015-11-05 01:40:58.5
' for queue: 'weblogi
"cache-factory-config
2015-11-05 01:40:58.5
' for queue: 'weblogi
"cache-factory-build
2015-11-05 01:40:58.5
' for queue: 'weblogi
"/custom-mbeans.xml"
Oracle Coherence Vers
Grid Edition: Develo
Copyright (c) 2000, 2
2015-11-05 01:40:58.7
4. 132x43
d: '3' for queue: 'weblogic.kernel.default (seti-tuning)', member=n/a): Loaded FMW commons version:
12.2.1-0-0-SNAPSHOT b60603
1. 80x24
2. 80x43
3. 132x24
es. All rights reserved.

2.2.1.0.0 <Info> (thread=[STANDBY] ExecuteThrea


```

- p. Open a New tab.
- q. cd /u01/wins/wls1221/user_projects/domains/otd_domain/
- r. vi nodemanager/nodemanager.properties
- s. Change Listen Port to 5557 then save the file and close it.

```
#Node manager properties
#Thu Nov 05 01:39:36 PST 2015
DomainsFile=/u01/wins/wls1221/user_projects/domains/otd_domain/nodemanager/nodemanager.domains
LogLimit=0
PropertiesVersion=12.2.1
AuthenticationEnabled=true
NodeManagerHome=/u01/wins/wls1221/user_projects/domains/otd_domain/nodemanager
JavaHome=/u01/java/jdk1.8.0_60
LogLevel=INFO
DomainsFileEnabled=true
StartScriptName=startWebLogic.sh
ListenAddress=localhost
NativeVersionEnabled=true
ListenPort=5557
LogIostderr=true
SecureListener=true
LogCount=1
StopScriptEnabled=false
QuitEnabled=false
LogAppend=true
StateCheckInterval=500
CrashRecoveryEnabled=false
StartScriptEnabled=true
LogFile=/u01/wins/wls1221/user_projects/domains/otd_domain/nodemanager/nodemanager.log
LogFormatter=weblogic.nodemanager.server.LogFormatter
ListenBacklog=50
```

- t. bin/startNodeManager.sh
- u. In tab, Click on **Terminal -> Set Title**. Enter **otd_nm** as Title then click on OK.

- v. Go to Firefox and type the Fusion Middleware Control URL <http://localhost:8001/em> .
w. Enter “weblogic/welcome1” as Username/Password then click on Login.



- x. Create a Machine.
i. Click on **WebLogic Domain ->Environment ->Machines**.

Server	Machine	State
		Running

- ii. Click on Create, Enter “**otd_machine**” as Name and “**Unix**” as Machine OS then Click on Next.


The screenshot shows the Oracle Enterprise Manager interface for creating a machine. The top navigation bar says "ORACLE Enterprise Manager Fusion Middleware Control 12c" and "weblogic". Below it, a progress bar shows "otd_domain" with three steps: "Machine Identity" (selected), "Node Manager Properties", and "Review". The main content area is titled "Create a Machine: Machine Identity". It contains fields for "Name" (set to "otd_machine") and "Machine OS" (set to "Unix"). At the bottom right are buttons for "Back", "Step 1 of 3", "Next" (highlighted with a red box), "Create", and "Cancel".

- iii. Change Listen Port to **5557** then Click on Next.

The screenshot shows the Oracle Enterprise Manager interface for creating a machine, Step 2 of 3. The progress bar shows "otd_domain" with "Machine Identity" selected. The main content area is titled "Create a Machine: Node Manager Properties". It includes a note about configuring Node Manager for Managed Servers. Below are fields for "Node Manager Type" (set to "SSL") and "Listen Address" (set to "localhost"). The "Listen Port" field is highlighted with a red box and contains the value "5557". At the bottom right are buttons for "Back", "Step 2 of 3", "Next" (highlighted with a red box), "Create", and "Cancel".

- iv. Click on **Create**.


- y. Create an OTD Configuration.
- Click on **WebLogic Domain -> Administration -> OTD Configurations**.



- Click on Create.
- Enter "mt" as Name and "HTTP" as Origin Server Type then click on Next.

The screenshot shows the 'New Configuration Wizard' with the 'General' step selected. The 'Create Configuration: General' page has a progress bar at the top. The 'Name' field contains 'mt' and the 'Origin Server Type' radio button is selected for 'HTTP'. There is a note about configuration names and a help link. The 'Next' button is highlighted with a red box.

- Leave Default in "Create Configuration: Listener" then click on Next.
- Leave Default in "Create Configuration: Server Pool" then click on Next.
- Select the "otd_machine" then click on Next.



- vii. Click on “Create Configuration”.
- viii. Check the box near “mt” to make it highlighted and then click on **Start Instances**. Click on Close.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

WebLogic Domain ▾ weblogic ▾ ...

Nov 5, 2015 2:00:12 AM PST

otd_domain ⓘ

WebLogic Domain ▾

i Information

Successfully created configuration "mt".

Successfully created instance(s) of configuration "mt" on machine(s) "otd_machine".
All changes have been activated.

Oracle Traffic Director Configurations

This page displays all the Oracle Traffic Director configurations. A configuration is a collection of elements that determine the run-time behavior of an Oracle Traffic Director instance. Click on 'Delete' to delete the selected configuration.

Configuration Name	Target Full Name
mt	/Domain_otd_domain/otd_domain/mt

Create... Duplicate Delete... Stop Instances Start Instances



Note: Go to Firefox and type the URL <http://localhost:8080/> to verify that server is listening.

The screenshot shows a Firefox browser window with the address bar set to 'localhost:8080'. The main content area displays a red-bordered 'Service Unavailable' header followed by the message 'The server is too busy to respond to your request. Please try again later.'

Registering an OTD Runtime Instance

- i. Go to base domain Fusion Middleware Control Console <http://localhost:7001/em>.
- ii. Enter weblogic/welcome1 as User Name/Password then click on Login.
- iii. Click on **Weblogic Domain -> Environment -> OTD Runtimes**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The left sidebar is expanded to show 'base_domain'. Under 'WebLogic Domain', the 'Environment' link is highlighted with a red box. In the main content area, a message box says 'All changes have been activated.' Below it, the 'OTD Runtimes' link is also highlighted with a red box. A table on the right lists one entry:

ID	Replication Type	Multicast Address	Multicast Port
1	(None)	239.192.0.0	7001

At the bottom right of the table, it says 'Clusters 1 of 1'.

iv. Click on **Register Runtime**.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The top navigation bar includes 'ORACLE Enterprise Manager' and 'Fusion Middleware Control 12c'. Below it, there's a breadcrumb trail: 'base_domain' > 'WebLogic Domain'. The main content area is titled 'OTD Runtimes'. A sub-header below it states: 'Oracle Traffic Director can be used to front-end domain partitions created in this WebLogic domain. Oracle Traffic Director can be installed within this same domain or in a separate domain. OTD runtimes need to be registered with this WebLogic domain before they can be used.' A red box highlights the 'Register Runtime' button in the top right of the table header. The table has columns: Name, OTD Configuration Name, Admin Server Host, Admin Server Port, Username, and OTD Domain Name. A message at the bottom of the table says: 'No Oracle Traffic Director runtimes have been registered in this WebLogic domain.'

v. Enter the following and then click on OK.

Runtime Name:	otd_runtime
OTD Configuration Name:	mt
Admin Server Host:	localhost
Admin Server Port:	8001
Username:	weblogic
Password:	welcome1
OTD Domain Name:	otd_domain

The screenshot shows the 'Register Runtime' dialog box. The title bar says 'Register Runtime'. The instructions inside say: 'An OTD configuration will be used to front-end domain partitions. Provide the OTD configuration name and connection information (host, port and credentials) for the WebLogic Admin Server where this configuration is located.' There are six input fields, each with a red box highlighting it: 'Runtime Name' (value: otd_runtime), 'OTD Configuration Name' (value: mt), 'Admin Server Host' (value: localhost), 'Admin Server Port' (value: 8001), 'Username' (value: weblogic), and 'OTD Domain Name' (value: otd_domain). At the bottom right are 'OK' and 'Cancel' buttons, with 'OK' also having a red box.

Creating Domain Partition front ended by OTD

- a. Click on **WebLogic Domain -> Environment ->Virtual Targets**.
- b. Click on Create.
- c. Enter **VT-1** as Name and **/dp4** as Uri Prefix then click on Add to Enter **localhost** as Host Name then click on Next.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

base_domain

General Targets

Create Virtual Target: General

Name * VT-1

Uri Prefix /dp4

Hosts

Specify the host name(s) that will be used for front-end access. If you are not using Oracle Traffic Director (OTD) to load balance connections for a domain partition, specify the actual host name(s) of the WebLogic server cluster or managed server. If you are using OTD to load balance connections for a domain partition, specify the host name(s) of the OTD administration server.

+ Add X Delete

Host Name

localhost

Advanced Options

Back Step 1 of 2 **Next** Cancel

- d. Select “app-cluster” as Cluster then click on **Create**.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

base_domain

General Targets

Create Virtual Target: Targets

Choose a server or cluster to be associated with this virtual target.

Cluster app-cluster

Server

Logging Configuration

Log File Name

Notes

Notes

Back Step 2 of 2 **Create** Cancel

- e. Click on **WebLogic Domain -> Environment -> Domain Partition**.
- f. Click on **Create**.

- g. Enter **dp4** as name and Check the box for “**Use OTD for load balancing**” and select “**otd_runtime**” then click on Next.

Create Domain Partition: General

Use this page to specify general attributes for this domain partition.

* Name: dp4

Security Realm: None

Primary Identity Domain:

Load Balancer Configuration

If you wish to use a load balancer to front-end this domain partition, choose an Oracle Traffic Director runtime from the list of registered runtimes shown below. If you wish to register a new OTD runtime, please use the Environment->OTD Runtimes menu item on the WebLogic Domain menu.

Use OTD for load balancing

OTD Runtime: otd_runtime

- h. Check the box for “VT-1” as shown below then click on Next.

Create Domain Partition: Available Targets

Select the virtual targets that will be available for this domain partition to use. Note that virtual targets can only be used by one partition; so, only available virtual targets are listed below.

Select	Virtual Target	Set as Default
<input checked="" type="checkbox"/>	VT-1	<input checked="" type="checkbox"/>

- i. Enter **app4RG** as Resource Group Name and Move **VT-1** to **Selected Targets** then click on Next.

Create Domain Partition: Resource Group

A resource group needs to be created within a partition before you can deploy applications or resources. The resource group can optionally extend a resource group template specified at the domain level.

* Resource Group Name: app4RG

Resource Group Template: None

Targets for the Resource Group: Select a target for the resource group from the list of available targets. If the partition has a default target specified, the resource group will implicitly inherit that target.

Available Targets	Selected Targets
	VT-1

- j. Review the Configuration then click on **Create**.
k. Check box near to **dp4** and click on **Control -> Start**. Click on Close.

base_domain

Status **State**

Control ▾

- Start
- Stop
- Restart
- Import
- Export

Name	Status	OTD Partition	Realm	Default Targets	Available Targets
dp2	Up			VT-Medrec-2	VT-Medrec-2
dp3	Up	Running		VT-daytrader	VT-daytrader
dp4	Down	Shutdown	dp4	VT-1	VT-1
Medrec-Dev	Up	Running		VT-Medrec-1	VT-Medrec-1

Deploying simple application to test OTD integration with weblogic

Here we are going to deploy heapApp.war which we used in Lab5. We will access that application through **load balancer** now.

- a. Click on dp4.
- b. Click on **Domain Partition -> Administration -> Resource Groups**.
- c. Click on Resource Group **app4RG**.
- d. Click on **Deployments** tab, and then click on **Deployment -> Deploy**.

The screenshot shows the Oracle Enterprise Manager interface for a WebLogic Domain. The top navigation bar includes 'WebLogic Domain' and 'weblogic'. Below the navigation is a toolbar with icons for Start Up and Shut Down, and a date/time stamp of 'Nov 5, 2015 11:32:49 PM PST'. The main content area is titled 'Resource Group : app4RG'. At the top of this section, there are tabs: General, Deployments (which is highlighted with a red box), Services, Targets, Monitoring, Control, and Notes. Below the tabs, a message states 'This page displays a list of Java EE applications and standalone application modules that have been deployed to this resource group.' Underneath this message is a table header with columns: Name, Status, State, Health, and Type. A tooltip for the 'Name' column indicates 'No deployments found. Select a deployment plan or redeploy an existing application, resource adapters, and libraries.' To the left of the table, there is a 'View' dropdown, a 'Show All' checkbox, and a 'Deployment' dropdown menu with options: Deploy (highlighted with a red box), Redeploy, Undeploy, and Fetch Deployment Plan. A status message at the bottom right says 'Deployments 0 of 0'.

- e. Select “**Archive or exploded directory is on the server where Enterprise Manager is running**” then click on **Browse**. Select the file **heapApp.war** from **/u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab6/** location then click on **OK**.

ORACLE® Enterprise Manager Fusion Middleware Control 12c

weblogic ▾

dp4

Select Archive Select Target Application Attributes Deployment Settings

Deploy Java EE Application: Select Archive

Back Step 1 of 4 Next Cancel

Scope
The scope that this application will be deployed to : Resource group "app4RG" in domain partition "dp4"

Archive or Exploded Directory
Java EE archives, Web Modules (WAR files), EJB Modules (EJB JAR files), Resource Adapter Modules (RAR files), Coherence Archives (GAR files), JDBC Modules, JMS Modules, and library files (Jar files) can be deployed. You can also deploy an exploded archive that is present on the server where Enterprise Manager is running.

Archive is on the machine where this Web browser is running.
 Archive or exploded directory is on the server where Enterprise Manager is running.

Browse... No file selected. /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/Lab6/heapApp.war Browse...

Deployment Plan
The deployment plan is a file that contains the deployment settings for an application. You can use a previously saved deployment plan for this application. Later in the deployment process, you can optionally edit the deployment plan and save it for a future deployment of this application. If you

Use app Met take App Fra If yc con Cor If yc con MD con you or th Adm

- f. Click on **Next** then click on **Deploy**. Click on **Close**.
- g. Go to Firefox and type the URL <http://localhost:8080/dp4/heapApp/>.




Total Heap in Use = 0 MB

Allocate Heap : MB

Migration Resource Group from one Cluster to other Cluster

Now we are going to migrate Resource Group app4RG from app-cluster to another cluster. As the application deployed in app4RG are front ended by OTD, when you migrate your resource group on other cluster. WebLogic automatically detect the server setting and you can access the application continuously without doing any manual configuration.



- When you click on **migrate** the following actions performs:
- Migrate API is called
- Resource Group starts on new hosts
- Sessions are replicated to new hosts.
- New origin server pool added to the OTD Configuration
 - Old pool used for sticky request to old pool only
 - New pool used for all new requests.
- Graceful shutdown called on resource group on original hosts.
- Virtual target configuration updated with new cluster only.

So using the same URL, you can access the application.

- a. Go back to Fusion middleware control console <http://localhost:7001/em>
- b. Create a new Cluster.
 - i. Click on **WebLogic Domain -> Environment -> Clusters**.
 - ii. Click on **Create -> Dynamic Cluster**.
 - iii. Enter **new-cluster** as Name then click on Next.
 - iv. Enter 1 as Dynamic Cluster Size then click on Next.
 - v. Select the box for "**Use a single machine for all dynamic servers**" and choose "**machine**" as Selected Machine then click on Next.
 - vi. Enter 9100 and 10101 as **Base Listen Port** and **SSL Base Listen Port** Respectively then click on Next.
 - vii. Review the Configuration then click on **Create**.
 - viii. Click on **WebLogic Domain -> Control -> Clusters**.
 - ix. Check the box near **new-cluster** to make it highlighted and then click on **Control -> Start -> Start Servers**.

Note: Before going to next step, wait till managed server in new-cluster get started, you can monitor the progress in base_nm tab.

- c. Migration of Resource Group.
 - i. Click on **WebLogic Domain -> Environment -> Resource Groups..**
 - ii. Check the box near to app4RG to make it highlighted and then click on Migrate. Select **new-cluster** as New Target then click on Migrate. In Confirmation window, click on Migrate.
 - iii. Once you notice "**Migrating resource group "app4RG" – Completed successfully**" message then click on Close.

The screenshot shows the Oracle Enterprise Manager interface for Fusion Middleware Control 12c. The main window displays a 'Resource Group Migration' dialog. On the left, a sidebar lists resource groups: app2RG, app3RG, app4RG (highlighted with a red box), and appRG. The migration dialog shows the following details:

- Resource Group:** app4RG
- Virtual Target:** VT-1
- Current Target:** app-cluster (Cluster)
- New Target:** new-cluster (Dynamic cluster) (highlighted with a red box)

A confirmation dialog box is overlaid on the main window, stating:

Confirmation

Migrating resource group "app4RG" - Completed Successfully


The virtual target "VT-1", to which this resource group is targeted to, has been migrated from "app-cluster (Cluster)" to "new-cluster (Dynamic cluster)"

Buttons in the confirmation dialog include **Close**, **Migrate** (highlighted with a red box), and **Cancel**.


At the bottom of the main window, status bars show "Rows Selected 1" and "Resource Groups 4 of 4".

Access Application through OTD

- Go to Firefox and type the URL <http://localhost:8080/dp4/heapApp>



- As the Resource group migrated from app-cluster to new-cluster. But still you are able to access the application through same URL. Load balancer is redirecting all requests to new cluster. new-cluster-1 is running on 9101 port and app-cluster-1 is running on 7101.



Error 404--Not Found

From RFC 2068 *Hypertext Transfer Protocol -- HTTP/1.1*:

10.4.5 404 Not Found

The server has not found anything matching the Request-URI. No indication is given of whether the condition is temporary or permanent.

If the server does not wish to make this information available to the client, the status code 403 (Forbidden) can be used instead. The 410 (Gone) status code SHOULD be used if the server knows, through some internally configurable mechanism, that an old resource is permanently unavailable and has no forwarding address.

So you can successfully migrate the resource group from one cluster to another cluster without affecting the front end of your application.

CLEANING AND RESETTING

Cleaning up Environment

- a. Go back to Fusion Middleware Control <http://localhost:7001/em>
- b. Click on WebLogic Domain -> Control -> Cluster.
- c. Check the boxes near to both the cluster then click on Control -> Shutdown -> Force Shutdown now. Click on Forcibly Shutdown Servers.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control 12c interface. The title bar reads "ORACLE Enterprise Manager Fusion Middleware Control 12c". The main navigation bar includes "WebLogic Domain" and "weblogic". The date and time "Nov 6, 2015 12:17:02 AM PST" are displayed. The current page is "/Domain_base_domain/base_domain > Clusters (Control)". The main content area is titled "Clusters (Control)" and shows a status pie chart with a green circle labeled "Up (2)". Below the chart is a table with columns: Name, Cluster Type, Servers, Cluster Messaging Mode, Default Load Algorithm, and Replication Type. Two clusters are listed: "app-cluster" and "new-cluster". The "app-cluster" row has a red box around its name. The "Control" dropdown menu for "app-cluster" is open, with the "Shutdown" option highlighted. A sub-menu for "Shutdown" is shown with two options: "When work completes" and "Force Shutdown Now", with "Force Shutdown Now" also highlighted by a red box. At the bottom of the table, there are statistics: "Rows Selected 2", "Columns Hidden 32", and "Clusters 2 of 2".

- d. Press CTRL + C on Tab title with otd_admin, otd_nm, base_nm, base_admin, dev_admin, app-cluster-1.
- e. Open a new terminal.
- f. cd /u01/content/weblogic-innovation-seminars/WInS_Demos/MT-Workshop/CleanUp/
- g. ./CleanEnvironment.sh