

## TP3 - NP Properties and Polynomial Reductions

Here is Lucas Sauvage's ACT TP3 assignment.

### Answers

#### PART 1

##### Q1

**Definition of a NP algorithm** L is said to be NP if there exists a polynomial Q and a polynomial-time algorithm A with two inputs and Boolean output such that :

$$L = \{u \mid \exists c, A(c, u) = \text{True}, |c| \leq Q(|u|)\}$$

**Certification** A certificate is a series of choices that serves as a proof (in polynomial time) that an instance u is true, i.e. belongs to the language L.

In this TP, the certification is an assignment function which specifies for each object i, the bag j it goes into.

**How to implement certification ?** Given an array arr and a set of bags j. arr[i] indicates which bag item at index i go in.

To check if the array's a validation of the algorithm, we can go through the array and sum all the items weight.

If the sum exceed the total capacity, the verification's false, otherwise it's true.

**Certificate size** As the certificate corresponds to the affectation of all items into bags, the array size is n :  $\text{aff} : [1..n] \rightarrow [1..k]$

Each entry in the array indicates the bag number for the corresponding item. To encode a bag number, we need approximately  $\log_2(k)$  bits.

Therefore, the total size of the certificate is  $|c| = n * \log_2(k)$

**Is the size of certificates polynomially bounded ?** First, we need to approximately calculate |u| size (input size). As  $x_i$  is the weight of the item i, c the capacity of the bag and k the number of bags, the size of the inputs is (to encode n, we need  $\log_2(n)$  size):

$$|u| = \sum_{i=1}^n \log_2(x_i) + \log_2(c) + \log_2(k)$$

As  $|c| = n * \log_2(k)$ ,  $|u|$  contains *at least*  $n$  (because there is  $n$  inputs). Moreover,  $|u|$  contains also  $\log_2(k)$  (for the size of the bags), so there's always a polynom  $Q$  such that :  $|c| \geq Q(|u|)$

**Verification algorithm** Determine whether this algorithm runs in  $O(n^k)$  for  $k \in \mathbb{N}^*$ .

We iterate  $j$  from 1 to  $k+1$  which runs in  $O(k)$ . The sum runs in  $O(\text{len}(x)) \Leftrightarrow O(n)$ .

The total complexity of this algorithm is  $O(k) * O(n) \Leftrightarrow O(kn)$  which is polynomial.

## Q2

**Q2.1 - Randomly generating a certificate** Since each object is assigned independently to a random bag between 1 and  $k$ , the probability of generating any particular certificate is  $(1/k)^n$ .

Therefore, the algorithm generates certificates uniformly.

**Q2.2 - Outline of a nondeterministic polynomial algorithm for the problem** To create the outline of the problem, we need to decompose it into steps : - With an input of an instance  $u$ , we generate a certificate - We check if the certificate is correct - We return True or False regarding the result of the previous step

With  $A$  as the polynomial-time algorithm with two inputs and Boolean output, an outline would be :

**[Instance  $u$ ]  $\Rightarrow$  [Certificate  $c$  generated randomly (for now I guess)]  $\Rightarrow$  [Verify  $A(u, c)$ ]  $\Rightarrow$  [Returns True or False]**

## Q3 - $NP \subset EXPTIME$

**EXPTIME Definition** In computational complexity theory, the complexity class EXPTIME (sometimes called EXP or DEXPTIME) is the set of all decision problems that are solvable by a deterministic Turing machine in exponential time, i.e., in  $O(2^{p(n)})$  time, where  $p(n)$  is a polynomial function of  $n$ .

See Wikipedia

**Q3.1 - Certificate values for n and k fixed** For  $k$  and  $n$  fixed, the certificate can take  $k^n$  values. Indeed, for each value of  $\text{aff}[i]$ , there's  $k$  possibilities and the length of  $\text{aff}$  is  $n$ . That's  $k * k * \dots * k$   $n$  times so  $k^n$ .

**Q3.2 - Enumeration of all certificates** To define an order, I suggest to start from the lowest one, i.e.  $[1, 1, \dots, 1]$ ,  $n$  times.

Then we add 1 to the first digit, until reaching  $k$ . Then we reset the digit and move to the second and so on and so forth.

The maximum certificate will be reached at the end of the algorithm, and it's  $[k, k, \dots, k]$ ,  $n$  times.

This allows an enumeration of all possible certificates without forgetting one.

**Q3.3 - The British Museum algorithm** The British Museum algorithm is a general approach to find a solution by checking all possibilities one by one, beginning with the smallest.

An algorithm would be :

- Generate minimal certificate
- While not  $[k, k, \dots, k]$ ,  $n$  times :
  - Verify if the certificate is a solution
  - If not : Next certificate
- If none certificate is a solution, returns False

## Q4

For this question, I didn't understand what the teacher meant by ". I assume it's a **txt** file formatted as follows :

```
10 # number of items
4 5 8 9 2 1 2 4 3 10 # list of item's weight
7 # the capacity
```

## PART 2

### Q1

Partition Input :

$n$  : items number

$x_1, \dots, x_n$  : the items

Output :

Yes if

$$\exists J \subset [1..n] \mid \sum_{i \in J} x_i = (\sum_{i=1}^n x_i)/2$$

No otherwise

To reduce *Partition* into *BinPack*, we need to first compute the sum of all items in the list. Let's call this sum  $S$ .

Then we need to set the number of bags ( $k$ ) to 2, and the capacity for each bag  $S/2$ .

**Correctness of reduction Yes for BinPack => Yes for Partition :**

Let's consider a set of items whose sum is equal to  $S$  (i.e.  $S = \sum_{i=1}^n x_i$ ). "Yes" means we can put items in two bags of capacity  $c$  then we found a subset whose sum is equal to  $\frac{\sum}{2} \Leftrightarrow \frac{S}{2}$ . (Each bag represent a subset) Let  $k = 2$ . An instance of BinPack is :  $(x_{i1}, \dots, x_{ik})$  goes in bag 1 and  $(x_{ik+1}, \dots, x_{in})$  goes in bag 2 Let  $J = (x_1, \dots, x_k)$ , the list of items placed in bag 1. Since every item is placed in one of the two bags :  $\sum_{i \in J} x_i + \sum_{i \notin J} x_i = \sum_{i=1}^n x_i = S$  Because both bags respect the same capacity we have  $\sum_{i \in J} x_i \leq S/2$  and  $\sum_{i \notin J} x_i \leq S/2$  so necessarily  $\sum_{i \in J} x_i = S/2$  Therefore,  $J$  is a valid subset for Partition, so

**Yes for Partition => Yes for BinPack :**

Let  $c$  the capacity for each bag on the BinPack instance. If there exists a subset  $J = (x_1, \dots, x_k)$  such that  $\sum_{i=1}^k x_i = S/2$ , then we have  $\sum_{i \in J} x_i$  in bag 1 and  $\sum_{i \notin J} x_i$  in bag 2. Therefore,  $\sum_{i \in J} x_i = \sum_{i \notin J} x_i = \frac{S}{2} = c$  which implies that Yes for Partition equals Yes for BinPack. This transformation only requires to compute  $S = \sum_{i=1}^n x_i$  which is  $O(n)$  which is polynomial.

## Q1.2

If Partition can be reduced to BinPack, it proves that  $Partition \leq_P BinPack$  and it means that each instance of Partition can be transformed into a BinPack instance in polynomial time.

As Partition is NP-Complete, we can assert that BinPack is, at least, as much as harder, which makes it NP-Hard.

Moreover, check a certificate takes polynomial time, so  $BinPack \in NP$ .

As  $BinPack \in NP$  and  $BinPack \in NP - Hard$ , **BinPack is NP-complete !**

### Q1.3

There is a unique case where we can reduce *BinPack* into *Partition*, and it's when  $k = 2$ . So, theoretically there's a reduction, but for only one case so it's not relevant.

### Q2

Partition is a special case of Sum, with  $c = \frac{\sum x_i}{2}$ , i.e. exactly half of the total sum. Therefore, any instance of Partition can be transformed into an instance of Sum, which gives :  $Sum \leq_P Partition$

To reduce Sum into Partition (i.e.  $([x_1, \dots, x_n], c)$ ) we need to first compute the sum of the items  $S = \sum_{i=1}^n x_i$ . If  $S < 2c$ , it means we need to "complete" the list to reach  $2c$ . To reach  $2c$  we need to add an item of weight equals to  $2c - S$ .

The instance  $([x_1, \dots, x_n, x_{n+1}], c)$  is then an instance to Partition.

Sum instance :  $([x_1, \dots, x_n], c) \parallel$  Partition instance :  $([x_1, \dots, x_n])$

#### **Yes for Sum => Yes for Partition**

Let's assume that  $J \subseteq [1..n]$  with  $\sum_{i \in J} x_i = c$

In Partition, the total sum is equals to  $2c$ , so half of it is  $c$ .

Take subset  $J$  as a instance to Partition computes a sum equals to half the total sum.

#### **Yes for Partition => Yes for Sum**

Let's assume that  $J' \subseteq [1..n]$  with  $\sum_{i \in J'} x_i = c$

If  $x_{n+1} \in J'$  then the sum of all the others items equals  $c - x_{n+1} = c - (2c - S) = S - c$ . The other half is then equals to  $c$ , and the sum of a subset is equals to  $c$

#### Q4

As we have  $Sum \leq_P Partition$  and  $Partition \leq_P BinPack$ , we obviously have  $Sum \leq_P BinPack$

(reduction in reduction.py)

#### Q5

To reduce *BinPackDiff* into *BinPack* we need to get the maximum capacity ( $c_{max}$ ) of the bags for *BinPackDiff*.

Then, we go through all bags (of capacity  $c_i$ ) and add an artificial item  $c_{max} - c_i$ .

Therefore, we can assume each bag has the same capacity and then reduce it to *BinPack*.

### PART 3

#### Q1

Let assume that *BinPackOpt1* is P and returns the minimal  $k_{min}$  needed.

To compute *BinPack* instance  $[(x_1, \dots, x_n), c, k]$  we compute *BinPackOpt1* $[(x_1, \dots, x_n), c]$ . *BinPack* then computes “yes” or “no”, which is polynomial, so it implies that *BinPack*  $\in P$ . It's the same for *BinPackOpt2*.

But we already know that *BinPack* is  $\in NP$  (even in *NP-complete*) so this would implies that  $P = NP$  which can't be true. It means that *BinPackOpt* (1 or 2) is at least *NP-Hard*.

#### Q2

Let's assume that *BinPack* is in  $P$ . To show that *BinPackOpt1* is also in  $P$  we need to prove there exists a reduction from *BinPackOpt1* to *BinPack*, i.e.  $BinPackOpt1 \leq_P BinPack$ .

We need to transform an instance of *BinPackOpt1* (i.e.  $[(x_1, \dots, x_n), c]$ ) into *BinPack*. That means we have to find the  $k_{min}$  such that *BinPack* $[(x_1, \dots, x_n), c, k_{min}]$  returns True.

Now that we've found a reduction, if *BinPack* is  $P$ , then *BinPackOpt1* is  $P$  and  $BinPackOpt1 \leq_P BinPack$

### Q3

It's the same as above. If we find a reduction from *BinPackOpt2* into *BinPack*, then *BinPackOpt2* is *P*.

To do so, we need to first find the  $k_{min}$  (same as above). Then we need to compute *BinPack* with the  $k_{min}$  and find the first instance where *BinPack* returns "Yes".