.PJX Table Structure for Visual FoxPro for Windows

(left section)

| | eld structure | Applies to | | | | | | | | |
|-----------|---------------|--|--------|------|--------------|---------|------|-------|--------|-------|
| Field | Type | Width Description | Header | Form | Visual Class | Program | Menu | Query | Report | Label |
| NAME | М | 4 Memo contains file name | Х | x | Х | x | X | Х | Х | X |
| TYPE | С | 1 The type is identified by the following characters: H Header K Form V Visual Class Library P Program M Menu Q Query R Report B Label L Library F Format d Database D Free Table t Associated Table I Index x File T Text File Z Application i Icon | X | X | х | X | X | х | х | X |
| ID | N | 10 Identifies current user of project | Х | х | Х | х | х | х | х | х |
| TIMESTAMP | N | 10 Specifies the last time the object was changed | Х | Х | X | х | X | Х | Х | Х |
| OUTFILE | М | 4 Memo contains location of .MPR when it's generated. " <source/> " indicates that the .MPR is stored in the same directory as the .MPX. " <project>" indicates that the .MPR is stored in the same directory as the .PJX.</project> | | | | | X | | | |
| HOMEDIR | М | 4 Memo contains the home directory | Х | х | | | Х | | | |
| EXCLUDE | L | Indicates whether the file is excluded from the application that is built from the project | | Х | Х | х | X | х | х | х |
| MAINPROG | L | 1 Indicates whether the file is designated as the project's main program | | Х | | х | Х | Х | | |

| | Fi | eld s | tructure | Applies to | | | | | | | | |
|-----------|------------------------|-------|---|--------------------|--------------|---------|------|-------|--------|-------|---|--|
| Field | Type Width Description | | Header | Form | Visual Class | Program | Menu | Query | Report | Label | | |
| SAVECODE | L | 1 | Indicates whether .MPR is not deleted when a menu is generated | Х | | | | | | | | |
| DEBUG | L | 1 | Indicates whether debug information is stored in the generated application | Х | | | | | | | | |
| ENCRYPT | L | 1 | Indicates whether the application is encrypted | Х | | | x | X | x | | | |
| NOLOGO | L | 1 | Indicates whether the application displays the FoxPro introduction screen | Х | | | | | | | | |
| CMNTSTYLE | N | 1 | Indicates which characters are used to create boxes around comments in .MPR. If the value is 0, comments are surrounded by line characters for viewing in FoxFont. If the value is not 0, comments are surrounded by asterisks. | х | | | | | | | | |
| OBJREV | N | 5 | Specifies the object code version | X PJX file version | Х | Х | Х | х | Х | | | |
| DEVINFO | М | 4 | Memo contains developer information (stored in binary) from the Project Information dialog box | Х | | | | | | | | |
| SYMBOLS | М | 4 | Reserved | | | | | | | | | |
| OBJECT | М | 4 | Reserved | | | | | | | | | |
| CKVAL | N | 6 | Reserved | | | | | | | | | |
| CPID | N | 5 | Specifies the code page associated with the file | | | | х | | х | | | |
| OSTYPE | С | 4 | Not applicable to Visual FoxPro 6.0 for Windows | | | | | | | | | |
| OSCREATOR | С | 4 | Not applicable to Visual FoxPro 6.0 for Windows | | | | | | | | | |
| COMMENTS | М | 4 | Memo contains description from the Edit Description dialog box | | х | х | Х | Х | Х | Х | Х | |
| RESERVED1 | М | 4 | Reserved | | | | | | | | | |
| RESERVED2 | М | 4 | Reserved | | | | | | | | | |

| Field structure | | | | Applies to | | | | | | | |
|------------------------------|---|---|--|------------|------|--------------|---------|------|-------|--------|-------|
| Field Type Width Description | | | | Header | Form | Visual Class | Program | Menu | Query | Report | Label |
| SCCDATA | М | | C structure used by Visual FoxPro to enable Source Code control | Х | X | Х | X | x | X | x | Х |
| LOCAL | L | | Specifies whether the project is Source Code-controlled (.F.) or not | Х | X | х | х | х | х | х | х |
| KEY | С | | Designates sort key for the Project Manager | Х | х | Х | х | х | х | х | х |
| USER | М | 4 | Memo is reserved for user | Х | х | Х | х | Х | х | Х | х |