

# Parallel Programming


## Distributed Memory Programming with MPI (1)

Slides adapted from the lecture notes by Peter Pacheco

# Roadmap

- Writing your first MPI program.
- Using the common MPI functions.
- The Trapezoidal Rule in MPI.
- Collective communication.
- MPI derived datatypes.
- Performance evaluation of MPI programs.
- Parallel sorting.
- Safety in MPI programs.

# A distributed memory system



# Hello World!

```
#include <stdio.h>
```

```
int main(void) {  
    printf("hello, world\n");  
  
    return 0;  
}
```

# Identifying MPI processes

- Common practice to identify processes by nonnegative integer ranks.
- $p$  processes are numbered  $0, 1, 2, \dots, p-1$

# Our first MPI program

```
1 #include <stdio.h>
2 #include <string.h> /* For strlen */
3 #include <mpi.h>    /* For MPI functions, etc */
4
5 const int MAX_STRING = 100;
6
7 int main(void) {
8     char    greeting[MAX_STRING];
9     int     comm_sz; /* Number of processes */
10    int     my_rank; /* My process rank */
11
12    MPI_Init(NULL, NULL);
13    MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);
14    MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
15
16    if (my_rank != 0) {
17        sprintf(greeting, "Greetings from process %d of %d!",
18                my_rank, comm_sz);
19        MPI_Send(greeting, strlen(greeting)+1, MPI_CHAR, 0, 0,
20                 MPI_COMM_WORLD);
21    } else {
22        printf("Greetings from process %d of %d!\n", my_rank, comm_sz);
23        for (int q = 1; q < comm_sz; q++) {
24            MPI_Recv(greeting, MAX_STRING, MPI_CHAR, q,
25                    0, MPI_COMM_WORLD, MPI_STATUS_IGNORE);
26            printf("%s\n", greeting);
27        }
28    }
29
30    MPI_Finalize();
31    return 0;
32 } /* main */
```

# Compilation

*wrapper script to compile*

*source file*

`mpicc -g -Wall -o mpi_hello mpi_hello.c`

*produce debugging information*

*turns on all warnings*

*create this executable file name (as opposed to default a.out)*

# Execution

`mpiexec -n <number of processes> <executable>`

---

`mpiexec -n 1 ./mpi_hello`

 *run with 1 process*

`mpiexec -n 4 ./mpi_hello`

 *run with 4 processes*



# Execution

```
mpiexec -n 1 ./mpi_hello
```

Greetings from process 0 of 1 !

```
mpiexec -n 4 ./mpi_hello
```

Greetings from process 0 of 4 !

Greetings from process 1 of 4 !

Greetings from process 2 of 4 !

Greetings from process 3 of 4 !

# MPI Programs

- Written in C.
  - Has main.
  - Uses `stdio.h`, `string.h`, etc.
- Need to add `mpi.h` header file.
- Identifiers defined by MPI start with “MPI\_”.
- First letter following underscore is uppercase.
  - For function names and MPI-defined types.
  - Helps to avoid confusion.

# MPI Components

- MPI\_Init

- Tells MPI to do all the necessary setup.

```
int MPI_Init(  
    int*      argc_p  /* in/out */,  
    char***   argv_p  /* in/out */);
```

- MPI\_Finalize

- Tells MPI we're done, so clean up anything allocated for this program.

```
int MPI_Finalize(void);
```

# Basic Outline

```
. . .  
#include <mpi.h>  
  
. . .  
int main(int argc, char* argv[]) {  
    . . .  
    /* No MPI calls before this */  
    MPI_Init(&argc, &argv);  
    . . .  
    MPI_Finalize();  
    /* No MPI calls after this */  
    . . .  
    return 0;  
}
```

# Communicators

- A collection of processes that can send messages to each other.
- MPI\_Init defines a communicator that consists of all the processes created when the program is started.
- Called **MPI\_COMM\_WORLD**.

# Communicators

```
int MPI_Comm_size(  
    MPI_Comm comm      /* in */,  
    int* comm_sz_p     /* out */);
```

  
*number of processes in the communicator*

```
int MPI_Comm_rank(  
    MPI_Comm comm      /* in */,  
    int* my_rank_p     /* out */);
```

  
*my rank*  
*(the process making this call)*

# SPMD

- Single-Program Multiple-Data
- We compile one program.
- Process 0 does something different.
  - Receives messages and prints them while the other processes do the work.
- The **if-else** construct makes our program SPMD.

# Communication

```
int MPI_Send(  
  
    void*          msg_buf_p      /* in */,  
    int            msg_size       /* in */,  
    MPI_Datatype   msg_type       /* in */,  
    int            dest           /* in */,  
    int            tag            /* in */,  
    MPI_Comm       communicator   /* in */);
```



# Data types

MPI datatype	C datatype
MPI_CHAR	signed char
MPI_SHORT	signed short int
MPI_INT	signed int
MPI_LONG	signed long int
MPI_LONG_LONG	signed long long int
MPI_UNSIGNED_CHAR	unsigned char
MPI_UNSIGNED_SHORT	unsigned short int
MPI_UNSIGNED	unsigned int
MPI_UNSIGNED_LONG	unsigned long int
MPI_FLOAT	float
MPI_DOUBLE	double
MPI_LONG_DOUBLE	long double
MPI_BYTE	
MPI_PACKED	

# Communication

```
int MPI_Recv(  
    void*          msg_buf_p      /* out */,  
    int           buf_size        /* in  */,  
    MPI_Datatype   buf_type       /* in  */,  
    int           source          /* in  */,  
    int           tag             /* in  */,  
  
    MPI_Comm       communicator    /* in  */,  
    MPI_Status*    status_p       /* out */);
```

# Message matching

```
MPI_Send(send_buf_p, send_buf_sz, send_type, dest, send_tag,  
send_comm);
```

*MPI\_Send*

*src = q*



*MPI\_Recv*


*dest = r*

```
MPI_Recv(recv_buf_p, recv_buf_sz, recv_type, src, recv_tag,  
recv_comm, &status);
```

# Receiving messages

- A receiver can get a message without knowing:
  - the amount of data in the message,
  - the sender of the message,
  - or the tag of the message.

```
MPI_Recv(result, result_sz, result_type,  
        MPI_ANY_SOURCE,  
        MPI_ANY_TAG,  
        comm,  
        MPI_STATUS_IGNORE);
```



# status\_p argument

```
MPI_Recv(recv_buf_p, recv_buf_sz, recv_type, src, recv_tag,  
recv_comm, &status);
```

**MPI\_Status\***



**MPI\_Status status;**

**status.MPI\_SOURCE**

**status.MPI\_TAG**

*MPI\_SOURCE*

*MPI\_TAG*

*MPI\_ERROR*

# How much data am I receiving?


```
int MPI_Get_count(  
    MPI_Status* status_p /* in */,  
    MPI_Datatype type /* in */,  
    int* count_p /* out */);
```



# Issues with send and receive

- Exact behavior is determined by the MPI implementation.
- MPI\_Send may behave differently with regard to buffer size, cutoffs and blocking.
- MPI\_Recv always blocks until a matching message is received.
- Know your implementation; don't make assumptions!







# TRAPEZOIDAL RULE IN MPI



# The Trapezoidal Rule



(a)



(b)

# The Trapezoidal Rule


$$\text{Area of one trapezoid} = \frac{h}{2}[f(x_i) + f(x_{i+1})]$$

$$h = \frac{b - a}{n}$$

$$x_0 = a, x_1 = a + h, x_2 = a + 2h, \dots, x_{n-1} = a + (n - 1)h, x_n = b$$

$$\text{Sum of trapezoid areas} = h[f(x_0)/2 + f(x_1) + f(x_2) + \dots + f(x_{n-1}) + f(x_n)/2]$$

# One trapezoid



# Pseudo-code for a serial program

```
/* Input:  a, b, n */  
h = (b-a)/n;  
approx = (f(a) + f(b))/2.0;  
for (i = 1; i <= n-1; i++) {  
    x_i = a + i*h;  
    approx += f(x_i);  
}  
approx = h*approx;
```


# Parallelizing the Trapezoidal Rule

1. Partition problem solution into tasks.
2. Identify communication channels between tasks.
3. Aggregate tasks into composite tasks.
4. Map composite tasks to cores.

# Parallel pseudo-code

```
1  Get a, b, n;
2  h = (b-a)/n;
3  local_n = n/comm_sz;
4  local_a = a + my_rank*local_n*h;
5  local_b = local_a + local_n*h;
6  local_integral = Trap(local_a, local_b, local_n, h);
7  if (my_rank != 0)
8      Send local_integral to process 0;
9  else /* my_rank == 0 */
10     total_integral = local_integral;
11     for (proc = 1; proc < comm_sz; proc++) {
12         Receive local_integral from proc;
13         total_integral += local_integral;
14     }
15 }
16 if (my_rank == 0)
17     print result;
```

# Tasks and communications for Trapezoidal Rule



# First version (1)

```
1  int main(void) {
2      int my_rank, comm_sz, n = 1024, local_n;
3      double a = 0.0, b = 3.0, h, local_a, local_b;
4      double local_int, total_int;
5      int source;
6
7      MPI_Init(NULL, NULL);
8      MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
9      MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);
10
11     h = (b-a)/n;          /* h is the same for all processes */
12     local_n = n/comm_sz;  /* So is the number of trapezoids */
13
14     local_a = a + my_rank*local_n*h;
15     local_b = local_a + local_n*h;
16     local_int = Trap(local_a, local_b, local_n, h);
17
18     if (my_rank != 0) {
19         MPI_Send(&local_int, 1, MPI_DOUBLE, 0, 0,
20                 MPI_COMM_WORLD);
```



# First version (2)

```
21 } else {
22     total_int = local_int;
23     for (source = 1; source < comm_sz; source++) {
24         MPI_Recv(&local_int, 1, MPI_DOUBLE, source, 0,
25             MPI_COMM_WORLD, MPI_STATUS_IGNORE);
26         total_int += local_int;
27     }
28 }
29
30 if (my_rank == 0) {
31     printf("With n = %d trapezoids, our estimate\n", n);
32     printf("of the integral from %f to %f = %.15e\n",
33         a, b, total_int);
34 }
35 MPI_Finalize();
36 return 0;
37 } /* main */
```

# First version (3)

```
1  double Trap(  
2      double left_endpt  /* in */,  
3      double right_endpt /* in */,  
4      int    trap_count  /* in */,  
5      double base_len    /* in */) {  
6      double estimate, x;  
7      int i;  
8  
9      estimate = (f(left_endpt) + f(right_endpt))/2.0;  
10     for (i = 1; i <= trap_count-1; i++) {  
11         x = left_endpt + i*base_len;  
12         estimate += f(x);  
13     }  
14     estimate = estimate*base_len;  
15  
16     return estimate;  
17 } /* Trap */
```

# Dealing with I/O

```
#include <stdio.h>
```

```
#include <mpi.h>
```

```
int main(void) {  
    int my_rank, comm_sz;
```

```
    MPI_Init(NULL, NULL);
```

```
    MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);
```

```
    MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
```

```
    printf("Proc %d of %d > Does anyone have a toothpick?\n",  
           my_rank, comm_sz);
```

```
    MPI_Finalize();
```

```
    return 0;
```


```
} /* main */
```

*Each process just  
prints a message.*

# Running with 6 processes

```
Proc 0 of 6 > Does anyone have a toothpick?  
Proc 1 of 6 > Does anyone have a toothpick?  
Proc 2 of 6 > Does anyone have a toothpick?  
Proc 4 of 6 > Does anyone have a toothpick?  
Proc 3 of 6 > Does anyone have a toothpick?  
Proc 5 of 6 > Does anyone have a toothpick?
```

*unpredictable output*



# Input

- Most MPI implementations only allow process 0 in MPI\_COMM\_WORLD access to **stdin**.
- Process 0 must read the data (scanf) and send to the other processes.

```
. . .  
MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);  
MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);  
  
Get_data(my_rank, comm_sz, &a, &b, &n);  
  
h = (b-a)/n;  
. . .
```

# Function for reading user input

```
void Get_input(  
    int      my_rank    /* in */,  
    int      comm_sz    /* in */,  
    double*  a_p        /* out */,  
    double*  b_p        /* out */,  
    int*     n_p        /* out */) {  
    int dest;  
  
    if (my_rank == 0) {  
        printf("Enter a, b, and n\n");  
        scanf("%lf %lf %d", a_p, b_p, n_p);  
        for (dest = 1; dest < comm_sz; dest++) {  
            MPI_Send(a_p, 1, MPI_DOUBLE, dest, 0, MPI_COMM_WORLD);  
            MPI_Send(b_p, 1, MPI_DOUBLE, dest, 0, MPI_COMM_WORLD);  
            MPI_Send(n_p, 1, MPI_INT, dest, 0, MPI_COMM_WORLD);  
        }  
    } else { /* my_rank != 0 */  
        MPI_Recv(a_p, 1, MPI_DOUBLE, 0, 0, MPI_COMM_WORLD,  
            MPI_STATUS_IGNORE);  
        MPI_Recv(b_p, 1, MPI_DOUBLE, 0, 0, MPI_COMM_WORLD,  
            MPI_STATUS_IGNORE);  
        MPI_Recv(n_p, 1, MPI_INT, 0, 0, MPI_COMM_WORLD,  
            MPI_STATUS_IGNORE);  
    }  
} /* Get_input */
```