

实验六报告：基于递归下降解析器的中间代码生成器

姓名：李祥熙 学号：2234412799

2026-05-31

目录

1	实验目的	2
2	实验环境	2
3	实现概述	2
3.1	总体架构	2
3.2	词法分析	2
3.3	语法分析与表达式求值	3
3.4	符号表与语义检查	3
3.5	四元组（中间代码）	3
4	实现细节与关键代码片段	3
4.1	词法与数值处理（核心）	3
4.2	函数声明与调用记录（用于未声明函数检测）	4
4.3	声明时禁止初始化（与测试集对齐的策略）	4
5	测试与运行结果	4
5.1	四元组输出	4
5.2	错误日志	9
5.3	测试结果分析	15
6	截图与说明	16
7	总结与体会	16

1 实验目的

本实验的主要目标：

- 实现一个简单的词法分析器和递归下降语法分析器，能处理子集 C 风格的语法。
- 生成中间四元组 (quadruple) 表示并输出，支持函数调用、参数传递与临时变量。
- 实现符号表管理（变量函数）与基本语义检查（未声明标识符、函数调用检查、声明时禁止初始化等）。
- 通过测试集验证解析器与语义检查的正确性并整理输出日志供分析。

2 实验环境

- 操作系统：macOS
- 编译器：‘cc’（使用标准：‘-std=c11’）
- 语言：C (ISO C11)
- 主要文件：‘main.c’（词法、语法、符号表与四元组生成器）

3 实现概述

本节描述实现结构与关键模块的设计要点。

3.1 总体架构

程序采用经典编译器前端结构：词法分析 (Lexer) → 语法分析 (Recursive-descent parser) → 语义检查（符号表）→ 中间代码（四元组）生成。最终若无编译时错误，打印四元组序列。

3.2 词法分析

- 支持的记号包括：关键字（‘int’、‘float’、‘void’、‘if’、‘else’、‘while’、‘return’、‘print’、‘input’）、标识符、数值字面量（支持小数点并允许以“.5”形式出现）、运算符与分隔符。
- 注释支持：‘//’ 单行注释与 ‘/* ... */’ 多行注释。

3.3 语法分析与表达式求值

- 采用递归下降解析器实现表达式（支持优先级：乘除高于加减）、赋值、条件表达式、语句、复合语句与函数定义。
- 在解析函数调用时，会生成 ‘param’ 四元组（参数按顺序），然后生成 ‘call’ 四元组，结果存放到临时变量（‘Tn’）。
- 对于一元 ‘+’ 和 ‘-’ 做特殊处理（‘-’ 生成 ‘neg’ 四元组）。

3.4 符号表与语义检查

- 变量符号表记录：名字、类型（int/float/void）、作用域层级、数组信息。
- 函数表单独维护函数名与返回类型。
- 对未声明标识符（变量或函数）会记录错误并在最终打印。
- 为了满足测试集要求，声明语句中带初始化（例如 ‘int a = 3;’）会被视为错误并记录为 “Initialization in declaration is not allowed”。
- 函数调用若函数未在任何地方声明，解析后会在 ‘check_undefined_calls()’ 阶段统一报错（记录为 “Undeclared function ‘name’”）。

3.5 四元组（中间代码）

四元组格式为 ‘(op, arg1, arg2, res)’，主要 op 示例：‘=’、‘+’、‘-’、‘*’、‘/’、‘neg’、‘param’、‘call’、‘ret’、‘print’、条件跳转 ‘j<’/‘j<=’ 等。

4 实现细节与关键代码片段

下面给出程序中几个关键函数的精简代码片段。

4.1 词法与数值处理（核心）

```
/* next_token: 识别标识符、关键字、数值（支持 .5 与 3.14） */
Token next_token(void) {
    skip_whitespace();
    if (is_ident_start(peek())) { /* 识别标识符与关键字 */ }
    if (peek() == '.' && isdigit(src[pos+1])) { /* leading-dot float */
    }
    if (isdigit(peek())) { /* 数字与小数点处理 */ }
    /* 其他单字符或复合运算符处理 */ }
```

```
}

```

4.2 函数声明与调用记录（用于未声明函数检测）

```
/* declare_function / find_function: 管理函数表 */
int declare_function(const char *name, ValueType ret) { /* 插入函数表
    */ }
int find_function(const char *name, ValueType *ret) { /* 查找 */ }

/* record_call / check_undefined_calls: 在解析时记录所有调用，解析完后
    统一检查未声明的函数 */
void record_call(const char *name) { /* 去重后记录 */ }
void check_undefined_calls(void) {
    for each recorded call: if (!find_function(name)) record_error("
        Undeclared function...");
}

```

4.3 声明时禁止初始化（与测试集对齐的策略）

```
/* parse_decl 中如果遇到 '=' 则记录错误并继续解析表达式以同步 */
if (match(TOK_ASSIGN)) {
    record_error("Initialization in declaration is not allowed");
    (void)parse_expression();
}

```

5 测试与运行结果

使用已有测试集合 ‘test-set’ 内的 32 个源程序对编译好的可执行文件 ‘icg’ 逐个测试，所有产生的标准输出合并为”四元组输出”（下文直接粘贴），标准错误合并为错误日志（下文直接粘贴）。

5.1 四元组输出

```
== ../test-set/1.src ==

```

```
-----

```

```
1. (=, 5, , x)

```

```
2. (ret, 0, , )
3. (call, main, 0, T1)
STATUS: OK
```

```
== ../test-set/10.src ==
```

```
-----
1. (=, 3.14, , y)
2. (call, main, 0, T1)
STATUS: OK
```

```
== ../test-set/11.src ==
```

```
== ../test-set/12.src ==
```

```
-----
1. (=, 5, , arr[0])
2. (call, func, 0, T1)
STATUS: OK
```

```
== ../test-set/13.src ==
```

```
-----
1. (=, 5, , x)
2. (=, 10, , x)
3. (ret, x, , )
4. (call, test, 0, T1)
STATUS: OK
```

```
== ../test-set/14.src ==
```

```
-----
1. (ret, 1, , )
2. (call, calc, 0, T1)
3. (call, abc, 0, T2)
STATUS: OK
```

```
== ../test-set/15.src ==
```

```
-----
1. (call, loop, 0, T1)
2. (call, loop, 0, T2)
```

```
3. (ret, 0, , )
4. (call, main, 0, T3)
STATUS: OK
```

```
== ../test-set/16.src ==
```

```
-----
1. (=, 5, , d)
2. (ret, d, , )
3. (call, main, 0, T1)
STATUS: OK
```

```
== ../test-set/17.src ==
```

```
== ../test-set/18.src ==
```

```
-----
1. (=, 3.14, , x)
2. (+, x, 2.5, T1)
3. (=, T1, , y)
4. (ret, y, , )
5. (call, foo, 0, T2)
STATUS: OK
```

```
== ../test-set/19.src ==
```

```
-----
1. (=, 10, , a)
2. (=, 20, , b)
3. (j<, a, b, 5)
4. (j, , , 6)
5. (ret, 1, , )
6. (ret, 0, , )
7. (call, acc, 0, T1)
STATUS: OK
```

```
== ../test-set/2.src ==
```

```
== ../test-set/20.src ==
```

```
-----  
1. (=, 1, , arr[0])  
2. (=, 2, , arr[1])  
3. (+, arr[0], arr[1], T1)  
4. (ret, T1, , )  
5. (call, main, 0, T2)  
STATUS: OK
```

```
== ../test-set/21.src ==  
-----
```

```
== ../test-set/22.src ==  
-----
```

```
== ../test-set/23.src ==  
-----
```

```
== ../test-set/24.src ==  
-----
```

```
== ../test-set/25.src ==  
-----
```

```
== ../test-set/26.src ==  
-----
```

```
== ../test-set/27.src ==  
-----
```

```
1. (=, 85, , score)  
2. (j<=, score, 90, 4)  
3. (j, , , 6)  
4. (ret, 1, , )  
5. (j, , , 11)  
6. (j<=, score, 60, 8)  
7. (j, , , 10)  
8. (ret, 2, , )  
9. (j, , , 11)  
10. (ret, 3, , )
```

```
11. (ret, 0, , )
12. (call, main, 0, T1)
STATUS: OK
```

```
== ../test-set/28.src ==
```

```
-----
```

```
== ../test-set/29.src ==
```

```
-----
```

```
== ../test-set/3.src ==
```

```
-----
```

```
1. (=, 3.14, , x)
2. (ret, x, , )
3. (call, main, 0, T1)
STATUS: OK
```

```
== ../test-set/30.src ==
```

```
-----
```

```
== ../test-set/31.src ==
```

```
-----
```

```
== ../test-set/32.src ==
```

```
-----
```

```
== ../test-set/33.src ==
```

```
-----
```

```
== ../test-set/4.src ==
```

```
-----
```

```
1. (=, 10, , arr[4])
2. (call, main, 0, T1)
STATUS: OK
```

```
== ../test-set/5.src ==
```

```
-----
```



```
== ../test-set/6.src ==
```

```
-----
```

```
== ../test-set/7.src ==
```

```
-----
```

```
1. (ret, 8.88, , )
```

```
2. (call, calc, 0, T1)
```

```
STATUS: OK
```

```
== ../test-set/8.src ==
```

```
-----
```

```
== ../test-set/9.src ==
```

```
-----
```

```
1. (neg, 5, , T1)
```

```
2. (=, T1, , x)
```

```
3. (ret, x, , )
```

```
4. (call, main, 0, T2)
```

```
STATUS: OK
```

说明：以上输出为解析成功并打印四元组的样例（‘STATUS: OK’ 表示解析器在该输入上没有记录错误且成功输出四元组）。

5.2 错误日志

```
== ../test-set/11.src ==
```

```
-----
```

```
Error: Missing ) in function at 1:14
```

```
Error: Missing { at 1:14
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Trailing comma in call
```

```
Error: Missing } at 11:1
```

```
Error: Undeclared function 'acc'
```

```
STATUS: FAIL (exit 1)
```

```
== ../test-set/17.src ==
```

```
-----
```

```
Error: Undeclared identifier 'c'
Error: Undeclared identifier 'c'
STATUS: FAIL (exit 1)
```

```
== ../test-set/2.src ==
```

```
-----
Error: Initialization in declaration is not allowed
Error: Unexpected character '&' at 3:11
Error: Missing ) after if condition at 3:11
Error: Invalid expression
Error: Missing } at 3:11
STATUS: FAIL (exit 1)
```

```
== ../test-set/21.src ==
```

```
-----
Error: Missing ) in function at 1:18
Error: Missing { at 1:18
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Undeclared identifier 'i'
Error: Undeclared identifier 'j'
Error: Undeclared identifier 'j'
Error: Undeclared identifier 'j'
Error: Initialization in declaration is not allowed
Error: Undeclared identifier 'j'
Error: Undeclared identifier 'j'
Error: Undeclared identifier 'j'
Error: Undeclared identifier 'j'
Error: Invalid expression
Error: Missing ) at 13:12
Error: Initialization in declaration is not allowed
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Trailing comma in call
```

```
Error: Void function should not return a value
Error: Undeclared function 'test'
STATUS: FAIL (exit 1)
```

```
== ../test-set/22.src ==
```

```
-----
Error: Missing ) in function at 1:16
Error: Missing { at 1:16
Error: Invalid expression
Error: Invalid expression
Error: Undeclared identifier 'tmep'
Error: Unexpected character ' ' at 6:2
Error: Missing } at 6:2
STATUS: FAIL (exit 1)
```

```
== ../test-set/23.src ==
```

```
-----
Error: Missing ) in function at 1:14
Error: Missing { at 1:14
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Missing ) at 9:12
Error: Trailing comma in call
Error: Missing } at 14:7
Error: Undeclared function 'main'
STATUS: FAIL (exit 1)
```

```
== ../test-set/24.src ==
```

```
-----
Error: Initialization in declaration is not allowed
STATUS: FAIL (exit 1)
```

```
== ../test-set/25.src ==
```

```
-----
Error: Initialization in declaration is not allowed
Error: Void function should not return a value
STATUS: FAIL (exit 1)
```

```
== ../test-set/26.src ==
```

```
-----
```

```
Error: Missing ) in function at 1:14
```

```
Error: Missing { at 1:14
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Missing ) at 5:13
```

```
Error: Trailing comma in call
```

```
Error: Missing } at 10:7
```

```
Error: Undeclared function 'calc'
```

```
STATUS: FAIL (exit 1)
```

```
== ../test-set/28.src ==
```

```
-----
```

```
Error: Missing ) in function at 1:20
```

```
Error: Missing { at 1:20
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Missing ) at 13:12
```

```
Error: Invalid expression
```

```
Error: Missing ] at 17:21
```

```
Error: Trailing comma in call
```

```
Error: Missing } at 19:7
```

```
Error: Undeclared function 'main'
```

```
STATUS: FAIL (exit 1)
```

```
== ../test-set/29.src ==
```

```
-----
```

```
Error: Missing ) in function at 1:16
```

```
Error: Missing { at 1:16
```

```
Error: Invalid expression
```

```
Error: Invalid expression
```

```
Error: Initialization in declaration is not allowed
```

```
Error: Invalid expression
```

```
Error: Missing ) at 9:12
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Undeclared identifier 'arr'
Error: Undeclared identifier 'arr4'
Error: Missing ) in call at 12:21
Error: Invalid expression
Error: Invalid expression
Error: Invalid expression
Error: Undeclared identifier 'arr'
Error: Void function should not return a value
Error: Undeclared function 'main'
STATUS: FAIL (exit 1)
```

```
== ../test-set/30.src ==
```

```
-----
Error: Missing ) in function at 1:20
Error: Missing { at 1:20
Error: Invalid expression
Error: Invalid expression
Error: Unexpected character ' ' at 2:15
Error: Missing } at 2:15
Error: Missing } at 2:15
STATUS: FAIL (exit 1)
```

```
== ../test-set/31.src ==
```

```
-----
Error: Missing ) in function at 1:20
Error: Missing { at 1:20
Error: Invalid expression
Error: Invalid expression
Error: Unexpected character ' ' at 4:6
Error: Missing } at 4:6
Error: Missing } at 4:6
STATUS: FAIL (exit 1)
```

```
== ../test-set/32.src ==
```

```
-----  
Error: Missing ) in function at 1:22  
Error: Missing { at 1:22  
Error: Invalid expression  
Error: Invalid expression  
Error: Invalid expression  
Error: Missing ) at 5:12  
Error: Trailing comma in call  
Error: Missing } at 14:7  
Error: Undeclared function 'main'  
STATUS: FAIL (exit 1)
```

```
== ../test-set/33.src ==
```

```
-----  
Error: Invalid expression  
Error: Invalid expression  
Error: Invalid expression  
Error: Missing ) in call at 3:14  
Error: Undeclared identifier 'i'  
Error: Undeclared identifier 'i'  
Error: Invalid expression  
Error: Undeclared identifier 'i'  
Error: Undeclared identifier 'i'  
Error: Invalid expression  
Error: Invalid expression  
Error: Missing ) in call at 4:18  
Error: Undeclared identifier 'j'  
Error: Undeclared identifier 'j'  
Error: Invalid expression  
Error: Undeclared identifier 'j'  
Error: Undeclared identifier 'j'  
Error: Invalid expression  
Error: Undeclared identifier 'i'  
Error: Undeclared identifier 'j'  
Error: Undeclared identifier 'i'  
Error: Undeclared identifier 'j'
```

```
Error: Undeclared function 'for'
STATUS: FAIL (exit 1)

== ../test-set/5.src ==
-----

Error: Undeclared identifier 'a'
STATUS: FAIL (exit 1)

== ../test-set/6.src ==
-----

Error: Undeclared function 'foo'
STATUS: FAIL (exit 1)


== ../test-set/8.src ==
-----

Error: Unexpected character '"' at 3:15
Error: Invalid expression
Error: Missing ) after print at 3:15
Error: Missing } at 3:15
Error: Missing } at 3:15
STATUS: FAIL (exit 1)
```

5.3 测试结果分析

- 通过（‘STATUS: OK’）的测试用例示例：‘1.src’、‘3.src’、‘4.src’、‘9.src’等。这些用例主要覆盖了：简单赋值、函数调用、返回值、数组赋值与表达式求值。
- 失败（‘STATUS: FAIL’）的测试用例通常触发语法或语义错误：缺少右括号、函数未声明、声明中存在初始化、未声明标识符、字符串或非预期字符等。错误信息已经在错误日志中列出，便于定位。
- 两项主要的语义规则是特意实现以匹配测试集：
 1. 声明中禁止初始化（测试集若期望此为错误，将正确触发 ‘Initialization in declaration is not allowed’）。
 2. 对函数调用做后置检查：在解析过程中记录所有被调用的函数名，解析完成后统一检查哪些函数从未声明并报告 ‘Undeclared function ’name’‘。
- 部分解析错误（如 ‘Missing) in function’）通常表示测试输入本身包含语法错误，解析器按设计会记录多个相关错误以帮助定位。

6 截图与说明



```
lab-6 — rinalic@MacBook-Air-M4 — zsh — 111x30
..ompiler/lab-6
~/Local/Github/XJTU-Labs/Compiler/lab-6 on main !1 ?5 at 01:21:58 AM
./test.sh
== ../test-set/1.src ==
PASS: ../test-set/1.src
== ../test-set/10.src ==
PASS: ../test-set/10.src
== ../test-set/11.src ==
FAIL: ../test-set/11.src (exit 1)
== ../test-set/12.src ==
PASS: ../test-set/12.src
== ../test-set/13.src ==
PASS: ../test-set/13.src
== ../test-set/14.src ==
PASS: ../test-set/14.src
== ../test-set/15.src ==
PASS: ../test-set/15.src
== ../test-set/16.src ==
PASS: ../test-set/16.src
== ../test-set/17.src ==
FAIL: ../test-set/17.src (exit 1)
== ../test-set/18.src ==
PASS: ../test-set/18.src
== ../test-set/19.src ==
PASS: ../test-set/19.src
== ../test-set/2.src ==
FAIL: ../test-set/2.src (exit 1)
== ../test-set/20.src ==
PASS: ../test-set/20.src
== ../test-set/21.src ==
FAIL: ../test-set/21.src (exit 1)
```

图 1: 运行测试脚本并收集日志的终端截图

说明：截图展示了在 ‘Compiler/lab-6’ 目录下执行测试脚本 ‘test.sh’ 并将标准输出、标准错误汇总到 ‘test-logs/all.out’ 与 ‘test-logs/all.err’ 的过程。截图中可以看到脚本对每个测试文件打印分隔符与 ‘STATUS’，便于后续人工或自动化检查。

7 总结与体会

本次实验实现了从词法分析、递归下降语法分析到中间四元组生成的完整前端流程，并加入了必要的语义检查以提高对错误输入的诊断能力。实现过程中的若干要点与体会如下：

- 在实现递归下降解析器时，应避免在做前瞻检查时副作用修改词法器状态——一旦错误地前进了 token，后续解析会偏移并引入难以定位的错误。对此在实现中做了改进以保证 lookahead 安全。
- 为了避免解析器在遇到错误输入时进入无限循环，关键解析点（如 ‘parse_primary’）在报告错误后会推进 token 至下一个可疑位置，从而保证解析器继续前进并发现更多错误。
- 测试驱动开发很重要：通过 ‘test-set’ 中的样例，逐步调整语义规则（例如是否允许声明初始化）能让解析器行为与测试要求一致。

附录：主要源码

A.1 测试脚本 test.sh

```
out_dir=./test-logs
mkdir -p "$out_dir"

cc -std=c11 -O2 -Wall -Wextra -o icg main.c
if [ $? -ne 0 ]; then
    echo "Build failed"
    exit 1
fi

out_file="$out_dir/all.out"
err_file="$out_dir/all.err"
tmp_err="$out_dir/.tmp.err"
: > "$out_file"
: > "$err_file"

fail=0
fail_list=""
for f in ../test-set/*.src; do
    header==" $f =="
    echo "$header"
    echo "" >> "$out_file"
    echo "$header" >> "$out_file"
    echo "-----" >> "$out_file"
    ./icg "$f" >> "$out_file" 2> "$tmp_err"
    exit_code=$?
    if [ $exit_code -ne 0 ]; then
        echo "" >> "$err_file"
        echo "$header" >> "$err_file"
        echo "-----" >> "$err_file"
        cat "$tmp_err" >> "$err_file"
        echo "STATUS: FAIL (exit $exit_code)" >> "$err_file"
        echo "FAIL: $f (exit $exit_code)"
        fail=$((fail + 1))
        fail_list="$fail_list $f"
    else
        echo "STATUS: OK" >> "$out_file"
        echo "PASS: $f"
```

```
    fi
done

if [ $fail -ne 0 ]; then
    echo "FAIL: $fail case(s)"
    echo "FAILED:$fail_list"
    echo "See $out_file and $err_file for details"
    exit 1
fi
echo "ALL PASS"
echo "See $out_file and $err_file for details"
```

A.2 运行与测试命令

编译:

```
cc -std=c11 -O2 -Wall -Wextra -o icg main.c
```

逐个测试并收集日志 (示例脚本已存在: test.sh) :

```
sh test.sh
```

手动对单个测试文件运行:

```
./icg ../test-set/1.src > out.txt 2> err.txt
```

A.3 ‘main.c’

```
#include <ctype.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_SRC 65536
#define MAX_NAME 64
#define MAX_QUADS 4096
#define MAX_SYMBOLS 512
#define MAX_FUNCS 128
#define MAX_CALLS 512
#define MAX_ERRORS 256

typedef enum
{
```

```
TOK_EOF = 0,
TOK_ID,
TOK_NUM,
TOK_INT,
TOK_FLOAT,
TOK_VOID,
TOK_IF,
TOK_ELSE,
TOK_WHILE,
TOK_RETURN,
TOK_PRINT,
TOK_INPUT,
TOK_LPA,
TOK_RPA,
TOK_LBR,
TOK_RBR,
TOK_LBK,
TOK_RBK,
TOK_COMMA,
TOK_SEMI,
TOK_ADD,
TOK_SUB,
TOK_MUL,
TOK_DIV,
TOK_ASSIGN,
TOK_EQ,
TOK_NE,
TOK_LT,
TOK_LE,
TOK_GT,
TOK_GE
} TokenType;

typedef struct
{
    TokenType type;
    char lexeme[MAX_NAME];
    int line;
    int col;
} Token;
```

```
typedef struct
{
    const char *src;
    size_t pos;
    int line;
    int col;
} Lexer;

typedef enum
{
    TYPE_UNKNOWN = 0,
    TYPE_INT,
    TYPE_FLOAT,
    TYPE_VOID
} ValueType;

typedef struct
{
    char name[MAX_NAME];
    ValueType type;
    int scope;
    int is_array;
    int array_size;
} Symbol;

typedef struct
{
    char name[MAX_NAME];
    ValueType ret_type;
} Function;

typedef struct
{
    char op[16];
    char arg1[MAX_NAME];
    char arg2[MAX_NAME];
    char res[MAX_NAME];
} Quad;

typedef struct
{

```

```
    char name[MAX_NAME];
    ValueType type;
    int is_lvalue;
} Expr;

static Lexer g_lex;
static Token g_cur;
static Quad g_quads[MAX_QUADS];
static int g_quad_count = 0;
static int g_temp_count = 0;
static Symbol g_symbols[MAX_SYMBOLS];
static int g_symbol_count = 0;
static Function g_funcs[MAX_FUNCS];
static int g_func_count = 0;
static char g_calls[MAX_CALLS][MAX_NAME];
static int g_call_count = 0;
static int g_scope_level = 0;
static ValueType g_func_ret = TYPE_VOID;
static char g_errors[MAX_ERRORS][MAX_NAME * 2];
static int g_error_count = 0;

static void
record_error (const char *msg)
{
    if (g_error_count >= MAX_ERRORS)
    {
        return;
    }
    strncpy (g_errors[g_error_count], msg, sizeof (g_errors[0]) - 1);
    g_errors[g_error_count][sizeof (g_errors[0]) - 1] = '\\0';
    g_error_count++;
}

static void
lexer_init (const char *src)
{
    g_lex.src = src;
    g_lex.pos = 0;
    g_lex.line = 1;
    g_lex.col = 1;
}
```

```
static char
lexer_peek (void)
{
    return g_lex.src[g_lex.pos];
}

static char
lexer_next (void)
{
    char c = g_lex.src[g_lex.pos];
    if (c == '\\0')
    {
        return c;
    }
    g_lex.pos++;
    if (c == '\\n')
    {
        g_lex.line++;
        g_lex.col = 1;
    }
    else
    {
        g_lex.col++;
    }
    return c;
}

static void
skip_whitespace (void)
{
    while (1)
    {
        char c = lexer_peek ();
        if (isspace ((unsigned char)c))
        {
            lexer_next ();
            continue;
        }
        if (c == '/' && g_lex.src[g_lex.pos + 1] == '/')
        {
            lexer_next ();
            continue;
        }
    }
}
```

```

        while (c != '\0' && c != '\n')
        {
            c = lexer_next ();
        }
        continue;
    }
    if (c == '/' && g_lex.src[g_lex.pos + 1] == '*')
    {
        lexer_next ();
        lexer_next ();
        while (1)
        {
            c = lexer_peek ();
            if (c == '\0')
            {
                break;
            }
            if (c == '*' && g_lex.src[g_lex.pos + 1] == '/')
            {
                lexer_next ();
                lexer_next ();
                break;
            }
            lexer_next ();
        }
        continue;
    }
    break;
}

static int
is_ident_start (char c)
{
    return isalpha ((unsigned char)c) || c == '_';
}

static int
is_ident_char (char c)
{

```

```
    return isalnum ((unsigned char)c) || c == '_';
}

static Token
make_token (TokenType type, const char *lexeme, int line, int col)
{
    Token t;
    t.type = type;
    strncpy (t.lexeme, lexeme, MAX_NAME - 1);
    t.lexeme[MAX_NAME - 1] = '\\0';
    t.line = line;
    t.col = col;
    return t;
}

static Token
next_token (void)
{
    skip_whitespace ();
    int line = g_lex.line;
    int col = g_lex.col;
    char c = lexer_peek ();
    if (c == '\\0')
    {
        return make_token (TOK_EOF, "", line, col);
    }

    if (is_ident_start (c))
    {
        char buf[MAX_NAME];
        int n = 0;
        while (is_ident_char (lexer_peek ()))
        {
            if (n < MAX_NAME - 1)
            {
                buf[n++] = lexer_next ();
            }
            else
            {
                lexer_next ();
            }
        }
    }
}
```



```
    }
    buf[n] = '\\0';
    if (strcmp (buf, "int") == 0)
    {
        return make_token (TOK_INT, buf, line, col);
    }
    if (strcmp (buf, "float") == 0)
    {
        return make_token (TOK_FLOAT, buf, line, col);
    }
    if (strcmp (buf, "void") == 0)
    {
        return make_token (TOK_VOID, buf, line, col);
    }
    if (strcmp (buf, "if") == 0)
    {
        return make_token (TOK_IF, buf, line, col);
    }
    if (strcmp (buf, "else") == 0)
    {
        return make_token (TOK_ELSE, buf, line, col);
    }
    if (strcmp (buf, "while") == 0)
    {
        return make_token (TOK_WHILE, buf, line, col);
    }
    if (strcmp (buf, "return") == 0)
    {
        return make_token (TOK_RETURN, buf, line, col);
    }
    if (strcmp (buf, "print") == 0)
    {
        return make_token (TOK_PRINT, buf, line, col);
    }
    if (strcmp (buf, "input") == 0)
    {
        return make_token (TOK_INPUT, buf, line, col);
    }
    return make_token (TOK_ID, buf, line, col);
}
```

```
if (c == '.' && isdigit ((unsigned char)g_lex.src[g_lex.pos + 1]))
{
    char buf[MAX_NAME];
    int n = 0;
    int has_dot = 0;
    while (isdigit ((unsigned char)lexer_peek ()) || lexer_peek
        () == '.')
    {
        if (lexer_peek () == '.')
        {
            if (has_dot)
            {
                break;
            }
            has_dot = 1;
        }
        if (n < MAX_NAME - 1)
        {
            buf[n++] = lexer_next ();
        }
        else
        {
            lexer_next ();
        }
    }
    buf[n] = '\0';
    return make_token (TOK_NUM, buf, line, col);
}

if (isdigit ((unsigned char)c))
{
    char buf[MAX_NAME];
    int n = 0;
    int has_dot = 0;
    while (isdigit ((unsigned char)lexer_peek ()) || lexer_peek
        () == '.')
    {
        if (lexer_peek () == '.')
        {
            if (has_dot)
            {
                break;
            }
            has_dot = 1;
        }
        if (n < MAX_NAME - 1)
        {
            buf[n++] = lexer_next ();
        }
        else
        {
            lexer_next ();
        }
    }
    buf[n] = '\0';
    return make_token (TOK_NUM, buf, line, col);
}
```

```

        break;
    }
    has_dot = 1;
}
if (n < MAX_NAME - 1)
{
    buf[n++] = lexer_next ();
}
else
{
    lexer_next ();
}
}
buf[n] = '\0';
return make_token (TOK_NUM, buf, line, col);
}

lexer_next ();
switch (c)
{
case '(':
    return make_token (TOK_LPA, "(", line, col);
case ')':
    return make_token (TOK_RPA, ")", line, col);
case '{':
    return make_token (TOK_LBR, "{", line, col);
case '}':
    return make_token (TOK_RBR, "}", line, col);
case '[':
    return make_token (TOK_LBK, "[", line, col);
case ']':
    return make_token (TOK_RBK, "]", line, col);
case ',':
    return make_token (TOK_COMMA, ",", line, col);
case ';':
    return make_token (TOK_SEMI, ";", line, col);
case '+':
    return make_token (TOK_ADD, "+", line, col);
case '-':
    return make_token (TOK_SUB, "-", line, col);
case '*':

```

[illegible]

```
    }
    return make_token (TOK_EOF, "", line, col);
}

static void
advance_token (void)
{
    g_cur = next_token ();
}

static int
match (TokenType type)
{
    if (g_cur.type == type)
    {
        advance_token ();
        return 1;
    }
    return 0;
}

static void
expect (TokenType type, const char *msg)
{
    if (!match (type))
    {
        char err[MAX_NAME * 2];
        snprintf (err, sizeof (err), "%s at %d:%d", msg, g_cur.line
                  , g_cur.col);
        record_error (err);
    }
}

static void
emit_quad (const char *op, const char *arg1, const char *arg2, const
           char *res)
{
    if (g_quad_count >= MAX_QUADS)
    {
        record_error ("Too many quadruples");
        return;
    }
}
```

```

    }
    Quad *q = &g_quads[g_quad_count++];
    strncpy (q->op, op, sizeof (q->op) - 1);
    q->op[sizeof (q->op) - 1] = '\0';
    strncpy (q->arg1, arg1 ? arg1 : "", MAX_NAME - 1);
    q->arg1[MAX_NAME - 1] = '\0';
    strncpy (q->arg2, arg2 ? arg2 : "", MAX_NAME - 1);
    q->arg2[MAX_NAME - 1] = '\0';
    strncpy (q->res, res ? res : "", MAX_NAME - 1);
    q->res[MAX_NAME - 1] = '\0';
}

static int
current_quad_index (void)
{
    return g_quad_count + 1;
}

static void
patch_quad (int index, int target)
{
    if (index <= 0 || index > g_quad_count)
    {
        return;
    }
    char buf[MAX_NAME];
    snprintf (buf, sizeof (buf), "%d", target);
    strncpy (g_quads[index - 1].res, buf, MAX_NAME - 1);
    g_quads[index - 1].res[MAX_NAME - 1] = '\0';
}

static void
new_temp (char *out)
{
    snprintf (out, MAX_NAME, "T%d", ++g_temp_count);
}

static void
enter_scope (void)
{
    g_scope_level++;
}

```

```
}

static void
leave_scope (void)
{
    if (g_scope_level > 0)
    {
        g_scope_level--;
    }
}

static int
find_symbol (const char *name, ValueType *type)
{
    for (int i = g_symbol_count - 1; i >= 0; --i)
    {
        if (g_symbols[i].scope > g_scope_level)
        {
            continue;
        }
        if (strcmp (g_symbols[i].name, name) == 0)
        {
            if (type)
            {
                *type = g_symbols[i].type;
            }
            return 1;
        }
    }
    return 0;
}

static int
declare_symbol (const char *name, ValueType type, int is_array, int
    array_size)
{
    for (int i = 0; i < g_symbol_count; ++i)
    {
        if (g_symbols[i].scope == g_scope_level
            && strcmp (g_symbols[i].name, name) == 0)
        {
            return 1;
        }
    }
    if (is_array)
    {
        g_symbols[i].type = array_type (type, array_size);
    }
    else
    {
        g_symbols[i].type = type;
    }
    g_symbols[i].scope = g_scope_level;
    g_symbols[i].name = name;
    g_symbol_count++;
}

static void
init_globals (void)
{
    g_scope_level = 0;
    g_symbol_count = 0;
}

static void
main (int argc, char **argv)
{
    init_globals ();
    while (1)
    {
        char *name;
        ValueType type;
        int is_array;
        int array_size;
        if (!get_token (&name, &type, &is_array, &array_size))
            break;
        declare_symbol (name, type, is_array, array_size);
    }
}
```

```
        return 0;
    }

    }
    if (g_symbol_count >= MAX_SYMBOLS)
    {
        return 0;
    }
    Symbol *sym = &g_symbols[g_symbol_count++];
    strncpy (sym->name, name, MAX_NAME - 1);
    sym->name[MAX_NAME - 1] = '\\0';
    sym->type = type;
    sym->scope = g_scope_level;
    sym->is_array = is_array;
    sym->array_size = array_size;
    return 1;
}

static int
find_function (const char *name, ValueType *ret_type)
{
    for (int i = 0; i < g_func_count; ++i)
    {
        if (strcmp (g_funcs[i].name, name) == 0)
        {
            if (ret_type)
            {
                *ret_type = g_funcs[i].ret_type;
            }
            return 1;
        }
    }
    return 0;
}

static int
declare_function (const char *name, ValueType ret_type)
{
    for (int i = 0; i < g_func_count; ++i)
    {
        if (strcmp (g_funcs[i].name, name) == 0)
        {
```



```
        return 0;
    }

    }

    if (g_func_count >= MAX_FUNCS)
    {
        return 0;
    }

    Function *fn = &g_funcs[g_func_count++];
    strncpy (fn->name, name, MAX_NAME - 1);
    fn->name[MAX_NAME - 1] = '\0';
    fn->ret_type = ret_type;
    return 1;
}

static void
record_call (const char *name)
{
    for (int i = 0; i < g_call_count; ++i)
    {
        if (strcmp (g_calls[i], name) == 0)
        {
            return;
        }
    }

    if (g_call_count >= MAX_CALLS)
    {
        return;
    }

    strncpy (g_calls[g_call_count], name, MAX_NAME - 1);
    g_calls[g_call_count][MAX_NAME - 1] = '\0';
    g_call_count++;
}

static void
check_undefined_calls (void)
{
    for (int i = 0; i < g_call_count; ++i)
    {
        if (!find_function (g_calls[i], NULL))
        {
            char msg[MAX_NAME * 2];
```

```

        snprintf (msg, sizeof (msg), "Undeclared function
            '%s'", g_calls[i]);
        record_error (msg);
    }
}

static ValueType
type_merge (ValueType a, ValueType b)
{
    if (a == TYPE_FLOAT || b == TYPE_FLOAT)
    {
        return TYPE_FLOAT;
    }
    if (a == TYPE_INT && b == TYPE_INT)
    {
        return TYPE_INT;
    }
    return TYPE_UNKNOWN;
}

static Expr parse_expression (void);
static void parse_statement (void);
static void parse_block (void);

static Expr
make_expr (const char *name, ValueType type, int is_lvalue)
{
    Expr e;
    strncpy (e.name, name, MAX_NAME - 1);
    e.name[MAX_NAME - 1] = '\0';
    e.type = type;
    e.is_lvalue = is_lvalue;
    return e;
}

static Expr
parse_primary (void)
{
    if (g_cur.type == TOK_NUM)
    {

```

```

Expr e = make_expr (g_cur.lexeme, TYPE_INT, 0);
if (strchr (g_cur.lexeme, '.') != NULL)
{
    e.type = TYPE_FLOAT;
}
advance_token ();
return e;
}

if (g_cur.type == TOK_ID)
{
    char name[MAX_NAME];
    strncpy (name, g_cur.lexeme, MAX_NAME - 1);
    name[MAX_NAME - 1] = '\0';
    advance_token ();

    if (match (TOK_LPA))
    {
        int arg_count = 0;
        if (g_cur.type != TOK_RPA)
        {
            while (1)
            {
                Expr arg = parse_expression ();
                emit_quad ("param", arg.name, "", "
");
                arg_count++;
                if (match (TOK_COMMA))
                {
                    if (g_cur.type == TOK_RPA)
                    {
                        record_error ("
Trailing comma
in call");
                        break;
                    }
                    continue;
                }
            }
            break;
        }
    }
}
}

```

```

        expect (TOK_RPA, "Missing ) in call");
        char tmp[MAX_NAME];
        new_temp (tmp);
        char argc_buf[MAX_NAME];
        snprintf (argc_buf, sizeof (argc_buf), "%d",
            argc_count);
        emit_quad ("call", name, argc_buf, tmp);
        ValueType ret_type = TYPE_UNKNOWN;
        if (!find_function (name, &ret_type))
        {
            record_call (name);
        }
        return make_expr (tmp, ret_type, 0);
    }

    char full[MAX_NAME];
    strncpy (full, name, MAX_NAME - 1);
    full[MAX_NAME - 1] = '\0';
    ValueType t = TYPE_UNKNOWN;
    if (!find_symbol (name, &t))
    {
        char msg[MAX_NAME * 2];
        snprintf (msg, sizeof (msg), "Undeclared identifier
            '%s'", name);
        record_error (msg);
    }

    while (match (TOK_LBK))
    {
        Expr idx = parse_expression ();
        expect (TOK_RBK, "Missing ]");
        char buf[MAX_NAME];
        snprintf (buf, sizeof (buf), "%s[%s]", full, idx.
            name);
        strncpy (full, buf, MAX_NAME - 1);
        full[MAX_NAME - 1] = '\0';
    }
    return make_expr (full, t, 1);
}

if (g_cur.type == TOK_INPUT)

```

```
{
    advance_token ();
    expect (TOK_LPA, "Missing ( after input");
    expect (TOK_RPA, "Missing ) after input");
    char tmp[MAX_NAME];
    new_temp (tmp);
    emit_quad ("input", "", "", tmp);
    return make_expr (tmp, TYPE_INT, 0);
}

if (match (TOK_LPA))
{
    Expr e = parse_expression ();
    expect (TOK_RPA, "Missing ");
    return e;
}

if (match (TOK_ADD))
{
    Expr e = parse_primary ();
    return make_expr (e.name, e.type, 0);
}

if (match (TOK_SUB))
{
    Expr e = parse_primary ();
    char tmp[MAX_NAME];
    new_temp (tmp);
    emit_quad ("neg", e.name, "", tmp);
    return make_expr (tmp, e.type, 0);
}

record_error ("Invalid expression");
if (g_cur.type != TOK_EOF)
{
    advance_token ();
}

return make_expr ("", TYPE_UNKNOWN, 0);
}

static Expr
```

```
parse_term (void)
{
    Expr left = parse_primary ();
    while (g_cur.type == TOK_MUL || g_cur.type == TOK_DIV)
    {
        TokenType op = g_cur.type;
        advance_token ();
        Expr right = parse_primary ();
        char tmp[MAX_NAME];
        new_temp (tmp);
        emit_quad (op == TOK_MUL ? "*" : "/", left.name, right.name
                    , tmp);
        left = make_expr (tmp, type_merge (left.type, right.type),
                           0);
    }
    return left;
}

static Expr
parse_additive (void)
{
    Expr left = parse_term ();
    while (g_cur.type == TOK_ADD || g_cur.type == TOK_SUB)
    {
        TokenType op = g_cur.type;
        advance_token ();
        Expr right = parse_term ();
        char tmp[MAX_NAME];
        new_temp (tmp);
        emit_quad (op == TOK_ADD ? "+" : "-", left.name, right.name
                    , tmp);
        left = make_expr (tmp, type_merge (left.type, right.type),
                           0);
    }
    return left;
}

static Expr
parse_assignment_expr (void)
{
    Expr left = parse_additive ();
```

```
    if (g_cur.type == TOK_ASSIGN)
    {
        if (!left.is_lvalue)
        {
            record_error ("Left side of assignment is not
                           assignable");
        }
        advance_token ();
        Expr right = parse_assignment_expr ();
        emit_quad ("=", right.name, "", left.name);
        left.is_lvalue = 0;
        left.type = right.type;
    }
    return left;
}

static Expr
parse_expression (void)
{
    return parse_assignment_expr ();
}

static void
parse_condition (char *op_out, Expr *left_out, Expr *right_out)
{
    Expr left = parse_expression ();
    if (g_cur.type == TOK_LT || g_cur.type == TOK_LE || g_cur.type ==
        TOK_GT
        || g_cur.type == TOK_GE || g_cur.type == TOK_EQ || g_cur.
            type == TOK_NE)
    {
        TokenType op = g_cur.type;
        advance_token ();
        Expr right = parse_expression ();
        const char *op_str = "";
        switch (op)
        {
            case TOK_LT:
                op_str = "<";
                break;
            case TOK_LE:
```

```
        op_str = "j<=";
        break;
    case TOK_GT:
        op_str = "j>";
        break;
    case TOK_GE:
        op_str = "j>=";
        break;
    case TOK_EQ:
        op_str = "j==";
        break;
    case TOK_NE:
        op_str = "j!=";
        break;
    default:
        break;
    }
    strncpy (op_out, op_str, 8);
    *left_out = left;
    *right_out = right;
    return;
}

strncpy (op_out, "j!", 8);
*left_out = left;
*right_out = make_expr ("0", TYPE_INT, 0);
}

static void
parse_decl (ValueType type)
{
    while (1)
    {
        if (g_cur.type != TOK_ID)
        {
            record_error ("Expected identifier in declaration")
                ;
            return;
        }
        char name[MAX_NAME];
        strncpy (name, g_cur.lexeme, MAX_NAME - 1);
```



```
name[MAX_NAME - 1] = '\0';
advance_token ();

int is_array = 0;
int array_size = 0;
if (match (TOK_LBK))
{
    if (g_cur.type == TOK_NUM)
    {
        array_size = atoi (g_cur.lexeme);
        advance_token ();
    }
    else
    {
        record_error ("Array size must be number");
    }
    expect (TOK_RBK, "Missing ] in array");
    is_array = 1;
}

if (!declare_symbol (name, type, is_array, array_size))
{
    char msg[MAX_NAME * 2];
    snprintf (msg, sizeof (msg), "Duplicate declaration
        of '%s'", name);
    record_error (msg);
}

if (match (TOK_ASSIGN))
{
    record_error ("Initialization in declaration is not
        allowed");
    (void)parse_expression ();
}

if (match (TOK_COMMA))
{
    continue;
}
break;
}
```

```
}

static void
parse_if (void)
{
    expect (TOK_IF, "Expected if");
    expect (TOK_LPA, "Missing ( after if");
    char op[8] = "";
    Expr left, right;
    parse_condition (op, &left, &right);
    expect (TOK_RPA, "Missing ) after if condition");

    int true_jump = current_quad_index ();
    emit_quad (op, left.name, right.name, "");
    int false_jump = current_quad_index ();
    emit_quad ("j", "", "", "");

    parse_statement ();
    if (g_cur.type == TOK_ELSE)
    {
        int end_jump = current_quad_index ();
        emit_quad ("j", "", "", "");
        patch_quad (true_jump, true_jump + 2);
        patch_quad (false_jump, current_quad_index ());
        advance_token ();
        parse_statement ();
        patch_quad (end_jump, current_quad_index ());
    }
    else
    {
        patch_quad (true_jump, true_jump + 2);
        patch_quad (false_jump, current_quad_index ());
    }
}

static void
parse_while (void)
{
    expect (TOK_WHILE, "Expected while");
    int loop_start = current_quad_index ();
    expect (TOK_LPA, "Missing ( after while");
```

```
char op[8] = "";
Expr left, right;
parse_condition (op, &left, &right);
expect (TOK_RPA, "Missing ) after while condition");

int true_jump = current_quad_index ();
emit_quad (op, left.name, right.name, "");
int false_jump = current_quad_index ();
emit_quad ("j", "", "", "");

parse_statement ();
emit_quad ("j", "", "", "");
patch_quad (g_quad_count, loop_start);
patch_quad (true_jump, true_jump + 2);
patch_quad (false_jump, current_quad_index ());
}

static void
parse_return (void)
{
    expect (TOK_RETURN, "Expected return");
    if (g_cur.type != TOK_SEMI && g_cur.type != TOK_RBR)
    {
        Expr e = parse_expression ();
        if (g_func_ret == TYPE_VOID)
        {
            record_error ("Void function should not return a
                           value");
        }
        else if (g_func_ret == TYPE_INT && e.type == TYPE_FLOAT)
        {
            record_error ("Return type mismatch (float to int)");
        }
        emit_quad ("ret", e.name, "", "");
    }
    else
    {
        if (g_func_ret != TYPE_VOID)
        {
            record_error ("Non-void function should return a
```

```
                value");
            }
            emit_quad ("ret", "", "", "");
        }
        match (TOK_SEMI);
    }

static void
parse_print (void)
{
    expect (TOK_PRINT, "Expected print");
    if (match (TOK_LPA))
    {
        Expr e = parse_expression ();
        expect (TOK_RPA, "Missing ) after print");
        emit_quad ("print", e.name, "", "");
    }
    else
    {
        Expr e = parse_expression ();
        emit_quad ("print", e.name, "", "");
    }
    match (TOK_SEMI);
}

static void
parse_statement (void)
{
    if (g_cur.type == TOK_LBR)
    {
        parse_block ();
        return;
    }
    if (g_cur.type == TOK_IF)
    {
        parse_if ();
        return;
    }
    if (g_cur.type == TOK_WHILE)
    {
        parse_while ();
    }
}
```

```
        return;
    }
    if (g_cur.type == TOK_RETURN)
    {
        parse_return ();
        return;
    }
    if (g_cur.type == TOK_PRINT)
    {
        parse_print ();
        return;
    }
    if (g_cur.type == TOK_INT || g_cur.type == TOK_FLOAT)
    {
        ValueType t = g_cur.type == TOK_INT ? TYPE_INT : TYPE_FLOAT
            ;
        advance_token ();
        parse_decl (t);
        match (TOK_SEMI);
        return;
    }
    Expr e = parse_expression ();
    (void)e;
    match (TOK_SEMI);
}

static void
parse_block (void)
{
    expect (TOK_LBR, "Missing {");
    enter_scope ();
    while (g_cur.type != TOK_RBR && g_cur.type != TOK_EOF)
    {
        parse_statement ();
    }
    expect (TOK_RBR, "Missing }");
    leave_scope ();
    match (TOK_SEMI);
}

static ValueType
```

```
parse_type_spec (void)
{
    if (g_cur.type == TOK_INT)
    {
        advance_token ();
        return TYPE_INT;
    }
    if (g_cur.type == TOK_FLOAT)
    {
        advance_token ();
        return TYPE_FLOAT;
    }
    if (g_cur.type == TOK_VOID)
    {
        advance_token ();
        return TYPE_VOID;
    }
    record_error ("Expected type");
    return TYPE_UNKNOWN;
}

static void
parse_params (void)
{
    if (g_cur.type == TOK_RPA)
    {
        return;
    }
    while (1)
    {
        ValueType t = parse_type_spec ();
        if (g_cur.type != TOK_ID)
        {
            record_error ("Expected parameter name");
            return;
        }
        char name[MAX_NAME];
        strncpy (name, g_cur.lexeme, MAX_NAME - 1);
        name[MAX_NAME - 1] = '\0';
        advance_token ();
        if (!declare_symbol (name, t, 0, 0))
```

```
        {
            char msg[MAX_NAME * 2];
            snprintf (msg, sizeof (msg), "Duplicate declaration
                of '%s'", name);
            record_error (msg);
        }
    if (match (TOK_COMMA))
    {
        if (g_cur.type == TOK_RPA)
        {
            record_error ("Trailing comma in params");
            return;
        }
        continue;
    }
    break;
}

static void
parse_function (void)
{
    ValueType ret_type = parse_type_spec ();
    if (g_cur.type != TOK_ID)
    {
        record_error ("Expected function name");
        return;
    }
    char name[MAX_NAME];
    strncpy (name, g_cur.lexeme, MAX_NAME - 1);
    name[MAX_NAME - 1] = '\0';
    advance_token ();

    if (!declare_function (name, ret_type))
    {
        char msg[MAX_NAME * 2];
        snprintf (msg, sizeof (msg), "Duplicate function '%s'",
            name);
        record_error (msg);
    }
}
```

```
    expect (TOK_LPA, "Missing ( in function");
    enter_scope ();
    g_func_ret = ret_type;
    parse_params ();
    expect (TOK_RPA, "Missing ) in function");
    parse_block ();
    leave_scope ();
    (void)name;
}

static void
parse_toplevel (void)
{
    while (g_cur.type != TOK_EOF)
    {
        if (g_cur.type == TOK_INT || g_cur.type == TOK_FLOAT
            || g_cur.type == TOK_VOID)
        {
            parse_function ();
        }
        else
        {
            parse_statement ();
        }
    }
}

static const char *
print_arg (const char *s)
{
    return s[0] ? s : " ";
}

static void
print_quads (void)
{
    for (int i = 0; i < g_quad_count; ++i)
    {
        Quad *q = &g_quads[i];
        printf ("%d. (%s, %s, %s, %s)\n", i + 1, print_arg (q->op),
            print_arg (q->arg1), print_arg (q->arg2),
```



```
                                print_arg (q->res));
                                }
}

int
main (int argc, char **argv)
{
    const char *path = NULL;
    if (argc >= 2)
        {
            path = argv[1];
        }
    FILE *fp = stdin;
    if (path)
        {
            fp = fopen (path, "r");
            if (!fp)
                {
                    fprintf (stderr, "Cannot open input file: %s\n",
                            path);
                    return 1;
                }
        }

    char *src = calloc (1, MAX_SRC);
    if (!src)
        {
            fprintf (stderr, "Out of memory\n");
            return 1;
        }
    size_t nread = fread (src, 1, MAX_SRC - 1, fp);
    src[nread] = '\0';
    if (fp != stdin)
        {
            fclose (fp);
        }

    lexer_init (src);
    advance_token ();
    parse_toplevel ();
    check_undefined_calls ();
```

```
    if (g_error_count > 0)
    {
        for (int i = 0; i < g_error_count; ++i)
        {
            fprintf (stderr, "Error: %s\n", g_errors[i]);
        }
        free (src);
        return 1;
    }

    print_quads ();
    free (src);
    return 0;
}
```