



UNIVERSITY OF AMSTERDAM



Optimization with Constraint Learning LAB

Part I

Speakers: Ilker Birbil & Donato Maragno

University of Amsterdam

February 8, 2023



Agenda



UNIVERSITY OF AMSTERDAM



- Introduction to mathematical optimization
- Introduction to Constraint Learning
- Chemotherapy case study
- Embedding Decision trees
- Embedding Neural networks
- Trust region constraints
- Hands-on tutorial


Mathematical Optimization

An optimization problem seeks to find the best (smallest or largest) value of a quantity given certain limits to the problem.

It can be expressed as a **minimization** (or maximization) of a quantity subject to a set of **constraints**.

Some examples:

- Travelling salesperson problem: minimize distance s.t. each city visited exactly once
- Diet problem: minimize cost s.t. nutrient requirements
- knapsack problem: maximize the value of objects in the knapsack s.t. capacity constraints




Mathematical Optimization

The general form of an optimization model is:

$$\min_{x \in \mathbb{R}^n} f(x_1, \dots, x_n) \rightarrow \textit{Objective function}$$

$$\textit{subject to } g_i(x_1, \dots, x_n) \leq 0, i = 1, \dots, m \rightarrow \textit{Constraints}$$

where x_1, \dots, x_n are the decision variables and the goal is to find a value for each of them such that the constraints are satisfied and the objective value is minimized.



Mathematical Optimization



UNIVERSITY OF AMSTERDAM





The general form of an optimization model is:

$$\min_{x \in \mathbb{R}^n} f(x_1, \dots, x_n) \rightarrow \text{Objective function}$$

subject to $g_i(x_1, \dots, x_n) \leq 0, i = 1, \dots, m \rightarrow \text{Constraints}$

where x_1, \dots, x_n are the decision variables and the goal is to find a value for each of them such that the constraints are satisfied and the objective value is minimized.



[source](#)

Mixed-Integer Optimization (MIO)

Powerful tool that allows us to optimize a given objective subject to various constraints.

Many real-life optimization problems contain one or more constraints or objectives for which **there are no explicit formulae**.

Mixed-Integer Optimization (MIO)

Powerful tool that allows us to optimize a given objective subject to various constraints.

Many real-life optimization problems contain one or more constraints or objectives for which **there are no explicit formulae**.

Machine Learning (ML)

Data is available and machine learning models can be used to **learn the constraints**.


Constraint Learning

x Decision variables
 w Contextual variables
 y Predicted outcomes

Constraint Learning

x Decision variables
 w Contextual variables
 y Predicted outcomes

$$D = \{(\bar{x}_i, \bar{w}_i, \bar{y}_i)\}_{i=1}^N \longrightarrow$$



Constraint Learning


\mathbf{x} Decision variables
 \mathbf{w} Contextual variables
 \mathbf{y} Predicted outcomes

$$\min_{\mathbf{x} \in \mathbb{R}^n, \mathbf{y} \in \mathbb{R}^k} f(\mathbf{x}, \mathbf{w}, \mathbf{y})$$

$$\text{s.t. } g(\mathbf{x}, \mathbf{w}, \mathbf{y}) \leq 0$$

$$\mathbf{y} = \hat{\mathbf{h}}_{\mathcal{D}}(\mathbf{x}, \mathbf{w})$$

$$D = \{(\bar{\mathbf{x}}_i, \bar{\mathbf{w}}_i, \bar{\mathbf{y}}_i)\}_{i=1}^N \longrightarrow$$



Constraint Learning


\mathbf{x} Decision variables
 \mathbf{w} Contextual variables
 \mathbf{y} Predicted outcomes

$$\min_{\mathbf{x} \in \mathbb{R}^n, \mathbf{y} \in \mathbb{R}^k} f(\mathbf{x}, \mathbf{w}, \mathbf{y})$$

$$\text{s.t. } g(\mathbf{x}, \mathbf{w}, \mathbf{y}) \leq 0$$

$$\mathbf{y} = \hat{\mathbf{h}}_{\mathcal{D}}(\mathbf{x}, \mathbf{w})$$

$$D = \{(\bar{\mathbf{x}}_i, \bar{\mathbf{w}}_i, \bar{\mathbf{y}}_i)\}_{i=1}^N \longrightarrow$$



Constraint Learning


\mathbf{x} Decision variables
 \mathbf{w} Contextual variables
 \mathbf{y} Predicted outcomes

$$\min_{\mathbf{x} \in \mathbb{R}^n, \mathbf{y} \in \mathbb{R}^k} f(\mathbf{x}, \mathbf{w}, \mathbf{y})$$

$$\text{s.t. } g(\mathbf{x}, \mathbf{w}, \mathbf{y}) \leq 0$$

$$\mathbf{y} = \hat{\mathbf{h}}_{\mathcal{D}}(\mathbf{x}, \mathbf{w})$$

$$D = \{(\bar{\mathbf{x}}_i, \bar{\mathbf{w}}_i, \bar{\mathbf{y}}_i)\}_{i=1}^N \longrightarrow$$



Chemotherapy Case Study

In this case study, we extend the work of [Bertsimas et al. \(2016\)](#)* in the design of chemotherapy regimens for advanced gastric cancer. Given a new study cohort and study characteristics, we would like to optimize a chemotherapy regimen to **maximize the cohort's survival subject to constraint on different types of toxicity**.

$\mathbf{x}_b^d = \mathbb{I}(\text{drug } d \text{ is administered}),$
 $\mathbf{x}_a^d = \text{average daily dose of drug } d,$
 $\mathbf{x}_i^d = \text{maximum instantaneous dose of drug } d.$

$$\begin{aligned} \min_{\mathbf{x}, \mathbf{y}} \quad & y_{OS} \\ \text{s.t.} \quad & y_i \leq \tau_i, & i \in \mathcal{Y}_C, \\ & y_i = \hat{h}_i(\mathbf{x}, \mathbf{w}), & i \in \mathcal{Y}_C, \\ & y_{OS} = \hat{h}_{OS}(\mathbf{x}, \mathbf{w}), \\ & \sum_d \mathbf{x}_b^d \leq 3, \\ & \mathbf{x}_b \in \{0, 1\}^d, \\ & \mathbf{x} \in \mathcal{X}(\mathbf{w}). \end{aligned}$$

(*) Bertsimas D, O'Hair A, Relyea S, Silberholz J (2016) An analytics approach to designing combination chemotherapy regimens for cancer. Management Science 62(5):1511–1531, ISSN 15265501

Chemotherapy Case Study

In this case study, we extend the work of [Bertsimas et al. \(2016\)](#)* in the design of chemotherapy regimens for advanced gastric cancer. Given a new study cohort and study characteristics, we would like to optimize a chemotherapy regimen to **maximize the cohort's survival subject to constraint on different types of toxicity**.

$\mathbf{x}_b^d = \mathbb{I}(\text{drug } d \text{ is administered}),$
 $\mathbf{x}_a^d = \text{average daily dose of drug } d,$
 $\mathbf{x}_i^d = \text{maximum instantaneous dose of drug } d.$

$$\begin{aligned} \min_{\mathbf{x}, \mathbf{y}} \quad & y_{OS} \\ \text{s.t.} \quad & y_i \leq \tau_i, & i \in \mathcal{Y}_C, \\ & y_i = \hat{h}_i(\mathbf{x}(\mathbf{w})), & i \in \mathcal{Y}_C, \\ & y_{OS} = \hat{h}_{OS}(\mathbf{x}, \mathbf{w}), \\ & \sum_d \mathbf{x}_b^d \leq 3, \\ & \mathbf{x}_b \in \{0, 1\}^d, \\ & \mathbf{x} \in \mathcal{X}(\mathbf{w}). \end{aligned}$$

Cohort contextual variables

- Gender
- Age
- primary site breakdown
- ecog score
- ...

(*) Bertsimas D, O'Hair A, Relyea S, Silberholz J (2016) An analytics approach to designing combination chemotherapy regimens for cancer. Management Science 62(5):1511–1531, ISSN 15265501

Chemotherapy Case Study

In this case study, we extend the work of [Bertsimas et al. \(2016\)](#)* in the design of chemotherapy regimens for advanced gastric cancer. Given a new study cohort and study characteristics, we would like to optimize a chemotherapy regimen to **maximize the cohort's survival subject to constraint on different types of toxicity**.

$\mathbf{x}_b^d = \mathbb{I}(\text{drug } d \text{ is administered}),$
 $\mathbf{x}_a^d = \text{average daily dose of drug } d,$
 $\mathbf{x}_i^d = \text{maximum instantaneous dose of drug } d.$

Overall Survival

$$\begin{aligned} \min_{\mathbf{x}, \mathbf{y}} \quad & y_{OS} \\ \text{s.t.} \quad & y_i \leq \tau_i, & i \in \mathcal{Y}_C, \\ & y_i = \hat{h}_i(\mathbf{x}, \mathbf{w}), & i \in \mathcal{Y}_C, \\ & y_{OS} = \hat{h}_{OS}(\mathbf{x}, \mathbf{w}), \\ & \sum_d \mathbf{x}_b^d \leq 3, \\ & \mathbf{x}_b \in \{0, 1\}^d, \\ & \mathbf{x} \in \mathcal{X}(\mathbf{w}). \end{aligned}$$

Cohort contextual variables

- Gender
- Age
- primary site breakdown
- ecog score
- ...

(*) Bertsimas D, O'Hair A, Relyea S, Silberholz J (2016) An analytics approach to designing combination chemotherapy regimens for cancer. Management Science 62(5):1511–1531, ISSN 15265501

Chemotherapy Case Study

In this case study, we extend the work of [Bertsimas et al. \(2016\)](#)* in the design of chemotherapy regimens for advanced gastric cancer. Given a new study cohort and study characteristics, we would like to optimize a chemotherapy regimen to **maximize the cohort's survival subject to constraint on different types of toxicity**.

$\mathbf{x}_b^d = \mathbb{I}(\text{drug } d \text{ is administered}),$
 $\mathbf{x}_a^d = \text{average daily dose of drug } d,$
 $\mathbf{x}_i^d = \text{maximum instantaneous dose of drug } d.$

Overall Survival

$$\begin{aligned} \min_{\mathbf{x}, \mathbf{y}} \quad & y_{OS} \\ \text{s.t.} \quad & y_i \leq \tau_i, \quad i \in \mathcal{Y}_C, \\ & y_i = \hat{h}_i(\mathbf{x}, \mathbf{w}), \quad i \in \mathcal{Y}_C, \\ & y_{OS} = \hat{h}_{OS}(\mathbf{x}, \mathbf{w}), \\ & \sum_d \mathbf{x}_b^d \leq 3, \\ & \mathbf{x}_b \in \{0, 1\}^d, \\ & \mathbf{x} \in \mathcal{X}(\mathbf{w}). \end{aligned}$$

Toxicities


- Grade 3/4 constitutional
- Infection
- Neurological
- Grade 4 blood
- ...

Cohort contextual variables


- Gender
- Age
- primary site breakdown
- ecog score
- ...

(*) Bertsimas D, O'Hair A, Relyea S, Silberholz J (2016) An analytics approach to designing combination chemotherapy regimens for cancer. Management Science 62(5):1511–1531, ISSN 15265501

Embedding Decision Trees



Embedding Decision Trees




Conceptual model

$$\begin{cases} \min_x & f(x) \\ \text{s.t.} & g(x) \leq 0 \end{cases}$$

P_3 $\begin{cases} A_1^T x \leq b_1 \\ A_2^T x \leq b_2 \end{cases}$

Embedding Decision Trees



Conceptual model


$$\begin{cases} \min_x & f(x) \\ \text{s.t.} & g(x) \leq 0 \end{cases}$$

P_6 $\begin{cases} A_1^T x \geq b_1 \\ A_5^T x \leq b_5 \end{cases}$

Embedding Neural Networks

ReLU activation function


$$y_1^2 = \max \{0, \beta_{01}^2 + \boldsymbol{\beta}_1^{2T} \mathbf{y}^1\}$$



Embedding Neural Networks

ReLU activation function

$$y_1^2 = \max \left\{ 0, \beta_{01}^2 + \boldsymbol{\beta}_1^{2T} \mathbf{y}^1 \right\}$$





$y = \max\{0, x\}$ can also be written as:



$$\begin{cases} y \geq x, \\ y \leq x - M_L(1 - z), \\ y \leq M_U z, \\ y \geq 0, \\ z \in \{0, 1\}, \end{cases}$$

where $M_L < 0$ is a lower bound on all possible values of x , and $M_U > 0$ is an upper bound.

Trust region constraints





Trust region constraints




Trust region constraints



UNIVERSITY OF AMSTERDAM





Trust region constraints



Trust region constraints

$$CH(\mathbf{x}) = \left\{ \mathbf{x} \mid \mathbf{x} = \sum_i^N \lambda_i \bar{\mathbf{x}}_i, \sum_i^N \lambda_i = 1, \lambda_i \geq 0, i = 1, \dots, N \right\}$$







Trust region constraints



UNIVERSITY OF AMSTERDAM



$$CH(\mathbf{x}) = \left\{ \mathbf{x} \mid \mathbf{x} = \sum_i^N \lambda_i \bar{\mathbf{x}}_i, \sum_i^N \lambda_i = 1, \lambda_i \geq 0, i = 1, \dots, N \right\}$$



OptiCL

A Python Package for

Optimization with Constraint Learning

<https://github.com/hwiberg/OptiCL>



UNIVERSITY OF AMSTERDAM



OptiCL

A Python Package for

Optimization with Constraint Learning

<https://github.com/hwiberg/OptiCL>



Hands-on tutorial on the



diet problem

Thank you!

Q&A



CONTACT ME

d.maragno@uva.nl



github.com/donato-maragno



[@MaragnoDonato](https://twitter.com/MaragnoDonato)



linkedin.com/in/donato-maragno

