

# Complexity - Exercise 2

Oren Roth

December 10, 2017

## Question 1

Let  $M$  be the TM which decide  $A$  and  $p(n)$  a polynomial, which for any input with size  $n$ ,  $M$  runs at most  $p(n)$  steps with oracle access to inputs with length at most  $n - 1$ . We will describe  $M'$  that will use only  $n * p(n)$  space for any input of size  $n$  and decide  $A$ . This will show  $A \in PSPACE$ .

Given  $x \in \Sigma^*$ ,  $M'$  will save  $n$  slots with size  $p(n)$  each.  $M'$  runs as follows:

- Copy  $x$  to the first slot
- run  $M$  on the input in slot 1. When oracle request is asked copy the input for the oracle to the next slot and runs  $M$  on it.
- Continue the same process when oracle request is asked copy the input for the oracle to the next slot and runs  $M$  on it and so on.
- When  $M$  answer on input of slot  $i > 1$ , clear slot  $i$  and return the answer to  $M$  on slot  $i - 1$  that asked the question to the oracle and continue the run of  $M$  on slot  $i - 1$ .
- When answer of  $M$  appears on slot 1,  $M'$  return the same.

First notice that any calls for oracle is shrink the input by one, so we will use at most  $n$  slots, because each slot is with size  $p(n)$ ,  $M'$  uses  $poly(n)$  space. Moreover as  $M$  need  $p(n)$  time for an input in size  $n$ , it for sure use at most  $p(n)$  space for inputs in size  $\leq n$ , in each slot we run on inputs with size  $\leq$  to  $n$  and hence each slot as sufficient space for running  $M$ .

If all the calls for the oracle are correct  $M'$  is just simulating  $M$  on slot 1 and hence  $L(M') = L(M)$ . Assume that all the calls for the oracle in input  $y$  with  $|y| < k$  are simulating correctly by  $M'$  and let  $y$  be input for the oracle with  $|y| = k$ , for this we will open new slot and run  $M$  on  $y$ , with every oracle call on inputs in size at most  $k - 1$  which by the induction assumption we know  $M'$  simulate correctly and hence,  $M'$  on  $y$  will answer exactly as  $M$  on  $y$ .

## Question 2

Assume  $NP = CO - NP$ , we will show  $PH \subseteq NP$  and hence  $PH = NP$ .

$$PH = \bigcup_{i=0}^{\infty} \Sigma_i^P$$

We will show by induction on  $i$  that  $\Sigma_i^P \subseteq NP$

### Question 3

### Question 4

a.

b.

$SAT$  is a special case of boolean formula, so as we showed in 1, iff  $x \in SAT$  there is a witness for it, a interpretation for it  $a$  with:

$$(x, a) \in FVAL$$

Because the witness tape is just like a normal tape we can run the algorithm from section a, and determine  $x \in SAT$  iff  $\exists a$  s.t.  $(x, a) \in FVAL$ .

c.

**Claim 0.1**  $G$  is not bipartite graph  $\iff$  there is a cycle of odd length in  $G$

We will show that  $BIPARTITE \in CO - NL$  and by theorem we showed in class ( $NL = CO - NL$ ) we will conclude  $BIPARTITE \in NL$ . Let us show  $\overline{BIPARTITE} \in NL$  by describe  $M$  non deterministic TM which decide  $\overline{BIPARTITE}$ .

$M$  will receive as an witness the odd cycle in  $G$  (by our claim we know there exist iff  $G \in \overline{BIPARTITE}$ ) and just check that this cycle exists in  $G$ .

$M$  will accept  $\iff$  there is such witness  $\iff G \in \overline{BIPARTITE}$ .

**Proof of claim** ( $\Leftarrow$ ) Let  $C = \{v_1, v_2, \dots, v_{2n+1}\}$  be a cycle of odd length, by contradiction assume  $G = (V \cup E)$  is bipartite with  $V = L \cup R$  division of  $V$  to two disjoint sets as promised. WLOG assume  $v_1 \in L$  so  $v_2 \in R$ ,  $v_3 \in L$  and so on (there is edge between those vertices so they have to be in different sets), we conclude all the odd vertices are in  $L$  but there is edge between  $v_{2n+1}$  to  $v_1$  and we arrive to contradiction.

( $\Rightarrow$ ) Let be

■

### Question 5