inovativno · zanesljivo · globalno
DAFRA
Kontakt tehnologija

DAFRA D.O.O,
Cesta ob železnici 3, 3310 Žalec

Phone. 386 713 32 30

Company / customer	RRI
Project description	08/2024| RRI
Job number	/
Commission	DAFRA D.O.O., Egasi d.o.o.

Project name	RRI
Responsible for project	Dejan Rožič
Last EPLAN version used	2024.0.3
Manufacturing date	08.2024
Type	Machine board
Place of installation	DAFRA
Power supply	5G2.5, 3G2.5
Input lead	3x230/1x230
Control voltage	24V DC
Special customer regulations	

Created on	30. 05. 2024		
Edit date	9. 07. 2025	by (short name)	DEJAN
Number of pages	105		

SAFETY REGULATIONS

DAFRA D.O.O,

Cesta ob železnici 3, 3310 Žalec

inovativno · zanesljivo · globalno
DAFRA
Kontakt tehnologija

GENERAL SAFETY REGULATIONS

DANGER !

During plant operation certain items are under dangerous voltage!
Non-observance of safety instructions can result in death, serious injuries or material damage.

Only specialist personnel may carry out transport, installation and commissioning work.

The applicable valid standards as well as the national and / or company-specific accident prevention regulations are to observed.

The following safety instructions are to be observed:

The erection, commissioning, troubleshooting as well as repair of the plant may only be carried out by qualified personnel that is familiar with the corresponding operating instructions.

Mounting of the devices has to be effected in accordance with the valid standards, state and local regulations.
Proper grounding and conductor dimensioning as well as proper short-circuit proofing have to be ensured.
These measures serve to ensure the safety of the plant and of the operating personnel.

Before carrying out safety checks, maintenance work and repair measures ensure that all the power supplies are switched off, are secured against being switched on unintentionally and are marked correspondingly.

Only test devices that are in a technically perfect condition and are suitable for the respective measurement may be used to carry out measurements!

The instructions specified in the respective operating instructions are to be followed strictly!
It is mandatory that hazard, warning and safety instructions be observed!

All doors and covers are to be kept closed during the plant operation.
If cooling devices are installed in the plant, ensure that these systems operate trouble-free.
These include the regular cleaning of the filters, in as far as they exist.

Parts list

F01_002

Device tag Placement	Quantity QU	Designation	Type number Order number	Manufacturer Supplier	Part number Function text	Pos.
=L1+MP-?X1	0					
=L1+MP-?X2	0					
=L1+MP-?X3	0					
=LIN1+OMA1-32M2 =LIN1+OMA1/32	0					
=LIN1+OMA1-33M3 =LIN1+OMA1/33.0	0					
=LIN1+OMA1-29U2 =LIN1+OMA1/29.a.8	1				HBM.ClipX	
=LIN1+OMA1-31U3 =LIN1+OMA1/31.2	1				Teltonika.RUT241 router	
=LIN1+OMA1-1X1 =LIN1+OMA1/33.0	0					
=LIN1+OMA1-2X2 =LIN1+OMA1/2.0;=LIN1+OMA1/33.1	0				Hlajenje ele. omare	
=LIN1+OMA1-3X3 =LIN1+OMA1/3.a.0;=LIN1+OMA1/33.3	0				48VDC	
=LIN1+OMA1-4X4 =LIN1+OMA1/4.0;=LIN1+OMA1/33.3	0				24V DC	
=LIN1+OMA1-5X5 =LIN1+OMA1/5.0;=LIN1+OMA1/33.3	0				0V DC	
=LIN1+OMA1-6X12 =LIN1+OMA1/33.3	0					
=LIN1+OMA1-12X13 =LIN1+OMA1/33.0	0					
=LIN1+OMA1-21X15 =LIN1+OMA1/21.0;=LIN1+OMA1/33.2	0				PLC sponke	
=LIN1+OMA1-6XP1 =LIN1+OMA1/6.1	0					
=LIN1+OMA1-6XP2 =LIN1+OMA1/6.2	0					
=LIN1+FIELD-6M1 =LIN1+OMA1/6.a.1	0				Actuator	

Parts list

F01_002

Device tag Placement	Quantity QU	Designation	Type number Order number	Manufacturer Supplier	Part number Function text	Pos.
=LIN1+FIELD-6M2 =LIN1+OMA1/6.a.4	0				Actuator	
=LIN1+FIELD-6M3 =LIN1+OMA1/6.b.1	0				=	
=LIN1+FIELD-6M4 =LIN1+OMA1/6.b.4	0				=	
=LIN1+FIELD-6M5 =LIN1+OMA1/6.c.1	0				=	
=LIN1+FIELD-30R1 =LIN1+OMA1/30.a.1	0				RTD1	
=LIN1+FIELD-30R2 =LIN1+OMA1/30.a.3	0				RTD2	
=LIN1+FIELD-30R3 =LIN1+OMA1/30.a.6	0				RTD3	
=LIN1+FIELD-30R4 =LIN1+OMA1/30.a.8	0				RTD4	
=LIN1+FIELD-21U1 =LIN1+OMA1/21.3	0					
=LIN1+FIELD-31U2 =LIN1+OMA1/31.0	1				Lenovo.PC PC - lenovo	
=LIN1+OMA1-1S1 =LIN1+OMA1/1.1	1	Main switch, 3 pole + N, 63 A, STOP function, Lockable in the 0 (Off) position, flush mounting	P3-63/EA/SVB-SW/N 012771	ETN ETN	ETN.P3-63/EA/SVB-SW/N Glavno stikalo 63A Main Switch 63A	
=LIN1+OMA1-29T1 =LIN1+OMA1/29.a.2	1 Piece	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP	BM40IE 1-BM40IE	HBM HBM	HBM.BM40IE	
=LIN1+OMA1-29T2 =LIN1+OMA1/29.a.2	1 Piece	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP	BM40IE 1-BM40IE	HBM HBM	HBM.BM40IE	
=LIN1+OMA1-29T3 =LIN1+OMA1/29.b.2	1 Piece	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP	BM40IE 1-BM40IE	HBM HBM	HBM.BM40IE	
=LIN1+OMA1-29T4 =LIN1+OMA1/29.b.2	1 Piece	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP	BM40IE 1-BM40IE	HBM HBM	HBM.BM40IE	
=LIN1+OMA1-29T5 =LIN1+OMA1/29.c.2	1 Piece	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP	BM40IE 1-BM40IE	HBM HBM	HBM.BM40IE	
=LIN1+OMA1-10FC1 =LIN1+OMA1/10.1	1 piece	Current monitoring equipment MICO BASIC 5.2/3.6 ELEC AUX CIRCUIT, 8 CHANNELS (IN: 24VDC OUT: 5x24V/2ADC 3x24V/6ADC)	9000-41068-0200600 9000-41068-0200600	MURR	MURR.9000-41068-0200600	
=LIN1+OMA1-11KF1 =LIN1+OMA1/11.0	1 Piece	TREE 8TX METALL - UNMANAGED SWITCH - 8 PORTS	8 port unmanaged switch 58171	MURR	MURR.58171	

Parts list

F01_002

Device tag Placement	Quantity QU	Designation	Type number Order number	Manufacturer Supplier	Part number Function text	Pos.
=LIN1+OMA1-11XF1 =LIN1+OMA1/11.6	1 Piece	Connector (special) MSDD INSTALLATION SOCKET RJ45 CAT5e BU/BU	4000-73000-0010000 4000-73000-0010000	MURR	MURR.4000-73000-0010000	
=LIN1+OMA1-11XF2 =LIN1+OMA1/11.7	1 Piece	Connector (special) MSDD INSTALLATION SOCKET RJ45 CAT5e BU/BU	4000-73000-0010000 4000-73000-0010000	MURR	MURR.4000-73000-0010000	
=LIN1+OMA1-1F1 =LIN1+OMA1/1.1	1 KOS piece	Inštalacijski odklopnik, karak. C, 10A, 10kA, 3-polni Miniature Circuit Breaker (MCB) C10/3, 10kA	BM017310-- BM017310--	SCHR SCHR	SCHR.BM017310--	
=LIN1+OMA1-1F2 =LIN1+OMA1/1.3	1 KOS piece	Inštalacijski odklopnik, karak. C, 2A, 3-polni, 10kA Miniature Circuit Breaker (MCB) C2/3, 10kA	BM017302-- BM017302--	SCHR SCHR	SCHR.BM017302--	
=LIN1+OMA1-6F8 =LIN1+OMA1/6.1	1 kos piece	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA Miniature Circuit Breaker (MCB) C6/1, 10kA	BM017106-- BM017106--	SCHR	SCHR.BM017106--	
=LIN1+OMA1-6F9 =LIN1+OMA1/6.2	1 kos piece	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA Miniature Circuit Breaker (MCB) C6/1, 10kA	BM017106-- BM017106--	SCHR	SCHR.BM017106--	
=LIN1+OMA1-2M1 =LIN1+OMA1/2.1	1 KOS piece	Ventilator s filtrom 230V, 11W, 109x109x62mm, IP54, 16m3/h Filter Ventilator 109x109x62mm (25m³/h), IP54	IUKNF1523A IUKNF1523A	SCHR SCHR	SCHR.IUKNF1523A Hlajenje ele. omare Cooling Cabinet	
=LIN1+OMA1-N =LIN1+OMA1/1.1	0 KOS piece	N-sponka za 15 odvodov, montaža na DIN letev, izolirana Insulated neutral terminal, 15 outgoings terminals	IK021038I- IK021038I-	SCHR SCHR	SCHR.IK021038I- N BusBar	
=LIN1+OMA1-PE =LIN1+OMA1/1.2	0 KOS piece	PE-sponka za 15 odvodov, montaža na DIN letev, izolirana Insulated PE terminal, 15 outgoings terminals	IK021039I- IK021039I-	SCHR SCHR	SCHR.IK021039I- PE BusBar	
=LIN1+OMA1-2Q1 =LIN1+OMA1/2.1	1 KOS piece	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P Motor Protection Circuit Breaker, 3-pole, 0.63-1.0A	BE501000-- BE501000--	SCHR SCHR	SCHR.BE501000--	
=LIN1+OMA1-2Q1 =LIN1+OMA1/2.1	1 KOS piece	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja Auxiliary contact front, 1NO+1NC	BE082882-- BE082882--	SCHR SCHR	SCHR.BE082882--	
=LIN1+OMA1-3Q2 =LIN1+OMA1/3.1	1 KOS piece	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P Motor Protection Circuit Breaker, 3-pole, 0.63-1.0A	BE501000-- BE501000--	SCHR SCHR	SCHR.BE501000--	
=LIN1+OMA1-3Q2 =LIN1+OMA1/3.1	1 KOS piece	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja Auxiliary contact front, 1NO+1NC	BE082882-- BE082882--	SCHR SCHR	SCHR.BE082882--	
=LIN1+OMA1-2S2 =LIN1+OMA1/2.1	1 KOS piece	Termostat za ventilator, 0 - 60° C, 1 delovni kontakt Ventilation thermostat 1 NO switch, blue, 0°-60°C	IUK08566-- IUK08566--	SCHR SCHR	SCHR.IUK08566-- Termostat 0-60	
=LIN1+OMA1-1U1 =LIN1+OMA1/1.3	1	UR6P3052 | Rele, nadzor zaporedja faz, 3-fazni, 2 preklopna kontakta	UR6P3052 UR6P3052	SCHR SCHR	SCH.UR6P3052	
=LIN1+OMA1-6XP1 =LIN1+OMA1/6.1	1 KOS piece	Vtičnica za montažo na letev s LED signalizacijo Rail mountable socket, with LED and screw connection	BZ325003-- BZ325003--	SCHR SCHR	SCHR.BZ325003--	
=LIN1+OMA1-6XP2 =LIN1+OMA1/6.2	1 KOS piece	Vtičnica za montažo na letev s LED signalizacijo Rail mountable socket, with LED and screw connection	BZ325003-- BZ325003--	SCHR SCHR	SCHR.BZ325003--	
=LIN1+OMA1-1H1 =LIN1+OMA1/1.2	1 Piece	Red complete pilot light Ø22 plain lens with integral LED 230...240V	XB4BVM4 XB4BVM4	SE SE	SE.XB4BVM4	

1.a 1.c

Parts list

F01_002

Device tag Placement	Quantity QU	Designation	Type number Order number	Manufacturer Supplier	Part number Function text	Pos.
=LIN1+OMA1-1H2 =LIN1+OMA1/1.2	1 Piece	Red complete pilot light Ø22 plain lens with integral LED 230...240V	XB4BVM4 XB4BVM4	SE SE	SE.XB4BVM4	
=LIN1+OMA1-1H3 =LIN1+OMA1/1.3	1 Piece	Red complete pilot light Ø22 plain lens with integral LED 230...240V	XB4BVM4 XB4BVM4	SE SE	SE.XB4BVM4	
=LIN1+OMA1-1K1 =LIN1+OMA1/1.7	1	Contactor TeSys LC1-D - 3P - AC-3 440V 38 A, Coil 230 V AC Coil 230 V AC	LC1-D 3P 38A LC1D38P7	SE SE	SE.LC1D38P7	
=LIN1+OMA1-3K2 =LIN1+OMA1/3.b.4	1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A	RSL1AB4BD RSL1AB4BD	SE SE	SE.RSL1AB4BD POWER ENABLE M1	
=LIN1+OMA1-3K2 =LIN1+OMA1/3.b.4	1	Screw socket equipped with LED and protection circuit, 12-24 V	RSLZVA1 RSLZVA1	SE SE	SE.RSLZVA1 =	
=LIN1+OMA1-3K3 =LIN1+OMA1/3.b.5	1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A	RSL1AB4BD RSL1AB4BD	SE SE	SE.RSL1AB4BD POWER ENABLE M2	
=LIN1+OMA1-3K3 =LIN1+OMA1/3.b.5	1	Screw socket equipped with LED and protection circuit, 12-24 V	RSLZVA1 RSLZVA1	SE SE	SE.RSLZVA1 =	
=LIN1+OMA1-3K4 =LIN1+OMA1/3.b.6	1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A	RSL1AB4BD RSL1AB4BD	SE SE	SE.RSL1AB4BD POWER ENABLE M3	
=LIN1+OMA1-3K4 =LIN1+OMA1/3.b.6	1	Screw socket equipped with LED and protection circuit, 12-24 V	RSLZVA1 RSLZVA1	SE SE	SE.RSLZVA1 =	
=LIN1+OMA1-3K5 =LIN1+OMA1/3.b.7	1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A	RSL1AB4BD RSL1AB4BD	SE SE	SE.RSL1AB4BD POWER ENABLE M4	
=LIN1+OMA1-3K5 =LIN1+OMA1/3.b.7	1	Screw socket equipped with LED and protection circuit, 12-24 V	RSLZVA1 RSLZVA1	SE SE	SE.RSLZVA1 =	
=LIN1+OMA1-3K6 =LIN1+OMA1/3.b.8	1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A	RSL1AB4BD RSL1AB4BD	SE SE	SE.RSL1AB4BD POWER ENABLE M5	
=LIN1+OMA1-3K6 =LIN1+OMA1/3.b.8	1	Screw socket equipped with LED and protection circuit, 12-24 V	RSLZVA1 RSLZVA1	SE SE	SE.RSLZVA1 =	
=LIN1+OMA1-17A1 =LIN1+OMA1/17.4	1	CPU 1215C, DC/DC/DC, 14DI/10DO/2AI/2AO SIMATIC, S7-1200	6ES7215-1AG40-0XB0 6ES7215-1AG40-0XB0	SIE SIE	SIE.6ES7215-1AG40-0XB0	
=LIN1+OMA1-18A2 =LIN1+OMA1/18.0	1 piece	S7-1200, ANALOG INPUT SM 1231 TC, 4 AI SIMATIC, S7-1200	6ES7231-5QD32-0XB0 6ES7231-5QD32-0XB0	SIE	SIE.6ES7231-5QD32-0XB0	
=LIN1+OMA1-18A3 =LIN1+OMA1/18.a.3	1	DIGITAL I/O SM 1223, 16DI/16DO SIMATIC, S7-1200	6ES7223-1BL32-0XB0 6ES7223-1BL32-0XB0	SIE SIE	SIE.6ES7223-1BL32-0XB0	
=LIN1+OMA1-18A4 =LIN1+OMA1/18.b.1	1	S7-1200, ANALOG INPUT SM 1231 RTD, 4 AI SIMATIC, S7-1200	6ES7231-5PD32-0XB0 6ES7231-5PD32-0XB0	SIE SIE	SIE.6ES7231-5PD32-0XB0	
=LIN1+OMA1-15K7 =LIN1+OMA1/15.2	1	SIMATIC HMI KTP700 BASIC SIMATIC, HMI	6AV2123-2GB03-0AX0 6AV2123-2GB03-0AX0	SIE SIE	SIE.6AV2123-2GB03-0AX0	

1.b

1.d

Parts list

F01_002

Device tag Placement	Quantity QU	Designation	Type number Order number	Manufacturer Supplier	Part number Function text	Pos.
=LIN1+FIELD-20A1 =LIN1+OMA1/20.2	1	SIMATIC HMI KTP700 BASIC SIMATIC, HMI	6AV2123-2GB03-0AX0 6AV2123-2GB03-0AX0	SIE SIE	SIE.6AV2123-2GB03-0AX0	
=LIN1+OMA1-3F3 =LIN1+OMA1/3.a.2	1 Piece	Fuse terminal Fuse terminal, Screw connection, Fuse isolator, for screwable cross-connection, One end without connection,	WSI 6 1011000000	WEI	WEI.1011000000 Screw connection, 6 mm², 250 V, 6.3 A, G-Si. 5 x 20, dark beige	
=LIN1+OMA1-3F4 =LIN1+OMA1/3.a.2	1 Piece	Fuse terminal Fuse terminal, Screw connection, Fuse isolator, for screwable cross-connection, One end without connection,	WSI 6 1011000000	WEI	WEI.1011000000 Screw connection, 6 mm², 250 V, 6.3 A, G-Si. 5 x 20, dark beige	
=LIN1+OMA1-3F5 =LIN1+OMA1/3.a.2	1 Piece	Fuse terminal Fuse terminal, Screw connection, Fuse isolator, for screwable cross-connection, One end without connection,	WSI 6 1011000000	WEI	WEI.1011000000 Screw connection, 6 mm², 250 V, 6.3 A, G-Si. 5 x 20, dark beige	
=LIN1+OMA1-3F6 =LIN1+OMA1/3.a.3	1 Piece	Fuse terminal Fuse terminal, Screw connection, Fuse isolator, for screwable cross-connection, One end without connection,	WSI 6 1011000000	WEI	WEI.1011000000 Screw connection, 6 mm², 250 V, 6.3 A, G-Si. 5 x 20, dark beige	
=LIN1+OMA1-3F7 =LIN1+OMA1/3.a.3	1 Piece	Fuse terminal Fuse terminal, Screw connection, Fuse isolator, for screwable cross-connection, One end without connection,	WSI 6 1011000000	WEI	WEI.1011000000 Screw connection, 6 mm², 250 V, 6.3 A, G-Si. 5 x 20, dark beige	
=LIN1+OMA1-26K8 =LIN1+OMA1/26.1	1 Piece	Relay module Relay module, 24 V DC +/-20 %, Green LED, Free-wheeling diode, Reverse polarity protection, 1 CO contact (AgNi) , 250 V AC, 8 A, Screw connection	TRS 24VDC 2CO 1123490000	WEI	WEI.1123490000	
=LIN1+OMA1-3TB1 =LIN1+OMA1/3.0	1 piece	Continuous current supply Power supply, 120 W, 5 A at 55 °C	PRO ECO3 120W 24V 5A 1469530000	WEI	WEI.1469530000	
=LIN1+OMA1-3TB2 =LIN1+OMA1/3.a.1	1 piece	Continuous current supply Power supply, 240 W, 5 A at 55 °C	PRO ECO 240W 48V 5A 1469590000	WEI	WEI.1469590000	
=LIN1+OMA1-3V1 =LIN1+OMA1/3.a.2	1 Piece	Solid-state relais Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3	TOS 24VDC/24VDC 4A 1275100000	WEI	WEI.1275100000 V DC, 4 A, Screw connection	
=LIN1+OMA1-3V2 =LIN1+OMA1/3.a.2	1 Piece	Solid-state relais Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3	TOS 24VDC/24VDC 4A 1275100000	WEI	WEI.1275100000 V DC, 4 A, Screw connection	
=LIN1+OMA1-3V3 =LIN1+OMA1/3.a.2	1 Piece	Solid-state relais Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3	TOS 24VDC/24VDC 4A 1275100000	WEI	WEI.1275100000 V DC, 4 A, Screw connection	
=LIN1+OMA1-3V4 =LIN1+OMA1/3.a.3	1 Piece	Solid-state relais Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3	TOS 24VDC/24VDC 4A 1275100000	WEI	WEI.1275100000 V DC, 4 A, Screw connection	
=LIN1+OMA1-3V5 =LIN1+OMA1/3.a.3	1 Piece	Solid-state relais Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3	TOS 24VDC/24VDC 4A 1275100000	WEI	WEI.1275100000 V DC, 4 A, Screw connection	
=LIN1+OMA1-1X1 =LIN1+OMA1/1.0	2 Piece	End bracket End bracket, Wemid, dark beige, Rail: TS 35, when screwed in	WEW 35/2 1061200000	WEI	WEI.1061200000 Dovodne sponke	

Summarized parts list

F02_002

Order number	Quantity	Designation	Type number	Supplier	Unit price	Total price
	0					0,00
6ES7215-1AG40-0XB0	1	CPU 1215C, DC/DC/DC, 14DI/10DO/2AI/2AO	6ES7215-1AG40-0XB0	SIE	0,00	0,00
6ES7231-5QD32-0XB0	1	S7-1200, ANALOG INPUT SM 1231 TC, 4 AI	6ES7231-5QD32-0XB0		0,00	0,00
6ES7223-1BL32-0XB0	1	DIGITAL I/O SM 1223, 16DI/16DO	6ES7223-1BL32-0XB0	SIE	0,00	0,00
6ES7231-5PD32-0XB0	1	S7-1200, ANALOG INPUT SM 1231 RTD, 4 AI	6ES7231-5PD32-0XB0	SIE	0,00	0,00
BM017310--	1	Inštalacijski odklopnik, karak. C, 10A, 10kA, 3-polni Miniature Circuit Breaker (MCB) C10/3, 10kA	BM017310--	SCHR	0,00	0,00
BM017302--	1	Inštalacijski odklopnik, karak. C, 2A, 3-polni, 10kA Miniature Circuit Breaker (MCB) C2/3, 10kA	BM017302--	SCHR	0,00	0,00
1011000000	5	Fuse terminal	WSI 6		0,00	0,00
BM017106--	2	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA Miniature Circuit Breaker (MCB) C6/1, 10kA	BM017106--		0,00	0,00
9000-41068-0200600	1	Current monitoring equipment	9000-41068-0200600		0,00	0,00
XB4BVM4	3	Red complete pilot light Ø22 plain lens with integral LED 230...240V	XB4BVM4	SE	0,00	0,00
LC1D38P7	1	Contactor TeSys LC1-D - 3P - AC-3 440V 38 A, Coil 230 V AC	LC1-D 3P 38A	SE	0,00	0,00
RSL1AB4BD	5	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A	RSL1AB4BD	SE	0,00	0,00
RSLZVA1	5	Screw socket equipped with LED and protection circuit, 12-24 V	RSLZVA1	SE	0,00	0,00
6AV2123-2GB03-0AX0	2	SIMATIC HMI KTP700 BASIC	6AV2123-2GB03-0AX0	SIE	0,00	0,00
1123490000	1	Relay module	TRS 24VDC 2CO		0,00	0,00
58171	1	TREE 8TX METALL - UNMANAGED SWITCH - 8 PORTS	8 port unmanaged switch		0,00	0,00
IUKNF1523A	1	Ventilator s filtrom 230V, 11W, 109x109x62mm, IP54, 16m3/h Filter Ventilator 109x109x62mm (25m³/h), IP54	IUKNF1523A	SCHR	0,00	0,00
IK021038I-	0	N-sponka za 15 odvodov, montaža na DIN letev, izolirana Insulated neutral terminal, 15 outgoings terminals	IK021038I-	SCHR	0,00	0,00
IK021039I-	0	PE-sponka za 15 odvodov, montaža na DIN letev, izolirana Insulated PE terminal, 15 outgoings terminals	IK021039I-	SCHR	0,00	0,00
BE501000--	2	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P Motor Protection Circuit Breaker, 3-pole, 0.63-1.0A	BE501000--	SCHR	0,00	0,00
BE082882--	2	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja Auxiliary contact front, 1NO+1NC	BE082882--	SCHR	0,00	0,00
012771	1	Main switch, 3 pole + N, 63 A, STOP function, Lockable in the 0 (Off) position, flush mounting	P3-63/EA/SVB-SW/N	ETN	0,00	0,00
IUK08566--	1	Termostat za ventilator, 0 - 60° C, 1 delovni kontakt Ventilation thermostat 1 NO switch, blue, 0°-60°C	IUK08566--	SCHR	0,00	0,00
1-BM40IE	5	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP	BM40IE	HBM	0,00	0,00
1469530000	1	Continuous current supply	PRO ECO3 120W 24V 5A		0,00	0,00
1469590000	1	Continuous current supply	PRO ECO 240W 48V 5A		0,00	0,00
UR6P3052	1	UR6P3052 | Rele, nadzor zaporedja faz, 3-fazni, 2 preklopna kontakta	UR6P3052	SCHR	0,00	0,00

Summarized parts list

F02_002

Order number	Quantity	Designation	Type number	Supplier	Unit price	Total price
	1				0,00	0,00
	1				0,00	0,00
1275100000	5	Solid-state relais	TOS 24VDC/24VDC 4A		0,00	0,00
1061200000	2	End bracket	WEW 35/2		0,00	0,00
4000-73000-0010000	2	Connector (special)	4000-73000-0010000		0,00	0,00
BZ325003--	2	Vtičnica za montažo na letev s LED signalizacijo Rail mountable socket, with LED and screw connection	BZ325003--	SCHR	0,00	0,00
	1				0,00	0,00

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.
Preveril	Vodja projektive		
Mail	dejan.rozic@dafra-kt.si		08/2024| RRI
Verzija eplan	2024.0.3		

Sumarna kosovnica

= Dokumentacija
+ Summarized_partList

/

Cable name 6W1
Cable type UNITRONIC® LiYCY 15x0,34 mm²
Free conductors 2

Cable parts LAPP.0034515
Order number 0034515

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-6X12:2:2				
	=LIN1+OMA1-6X12:8:4				
	=LIN1+OMA1-6X12:14:4				
	=LIN1+OMA1-6X12:12:4				
	=LIN1+OMA1-6X12:10:4				
	=LIN1+OMA1-6X12:15:2				
	=LIN1+OMA1-6X12:13:2				
	=LIN1+OMA1-6X12:11:2				
	=LIN1+OMA1-6X12:6:1				
	=LIN1+OMA1-6X12:4:1				
	=LIN1+OMA1-6X12:1:4				
	=LIN1+OMA1-6X12:3:3				
	=LIN1+OMA1-6X12:9:2				
	=LIN1+OMA1-6X12:7:3				
	=LIN1+OMA1-6X12:5:3				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+FIELD-6M1:1	FIELD
				=LIN1+FIELD-6M1:2	FIELD
				=LIN1+FIELD-6M1:3	FIELD
				=LIN1+FIELD-6M1:4	FIELD
				=LIN1+FIELD-6M1:5	FIELD
				=LIN1+FIELD-6M1:6	FIELD
				=LIN1+FIELD-6M1:7	FIELD
				=LIN1+FIELD-6M1:8	FIELD
				=LIN1+FIELD-6M1:9	FIELD
				=LIN1+FIELD-6M1:10	FIELD
				=LIN1+FIELD-6M1:11	FIELD
				=LIN1+FIELD-6M1:12	FIELD
				=LIN1+FIELD-6M1:15	FIELD
				=LIN1+FIELD-6M1:14	FIELD
				=LIN1+FIELD-6M1:13	FIELD

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija
Odgovoren Dejan Rožič 13. 08. 2025
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si
Verzija eplan 2024.0.3
DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 6W2
Cable type UNITRONIC® LiYCY 15x0,34 mm²
Free conductors 2

Cable parts LAPP.0034515
Order number 0034515

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-6X12:17:2				
	=LIN1+OMA1-6X12:24:4				
	=LIN1+OMA1-6X12:30:4				
	=LIN1+OMA1-6X12:28:4				
	=LIN1+OMA1-6X12:26:4				
	=LIN1+OMA1-6X12:31:2				
	=LIN1+OMA1-6X12:29:2				
	=LIN1+OMA1-6X12:27:2				
	=LIN1+OMA1-6X12:21:2				
	=LIN1+OMA1-6X12:19:2				
	=LIN1+OMA1-6X12:16:4				
	=LIN1+OMA1-6X12:18:4				
	=LIN1+OMA1-6X12:25:2				
	=LIN1+OMA1-6X12:22:4				
	=LIN1+OMA1-6X12:20:4				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+FIELD-6M2:1	FIELD
				=LIN1+FIELD-6M2:2	FIELD
				=LIN1+FIELD-6M2:3	FIELD
				=LIN1+FIELD-6M2:4	FIELD
				=LIN1+FIELD-6M2:5	FIELD
				=LIN1+FIELD-6M2:6	FIELD
				=LIN1+FIELD-6M2:7	FIELD
				=LIN1+FIELD-6M2:8	FIELD
				=LIN1+FIELD-6M2:9	FIELD
				=LIN1+FIELD-6M2:10	FIELD
				=LIN1+FIELD-6M2:11	FIELD
				=LIN1+FIELD-6M2:12	FIELD
				=LIN1+FIELD-6M2:15	FIELD
				=LIN1+FIELD-6M2:14	FIELD
				=LIN1+FIELD-6M2:13	FIELD

5 7

Cable name 6W3
Cable type UNITRONIC® LiYCY 15x0,34 mm²
Free conductors 2

Cable parts LAPP.0034515
Order number 0034515

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-6X12:33:2				
	=LIN1+OMA1-6X12:40:4				
	=LIN1+OMA1-6X12:46:4				
	=LIN1+OMA1-6X12:44:4				
	=LIN1+OMA1-6X12:42:4				
	=LIN1+OMA1-6X12:47:2				
	=LIN1+OMA1-6X12:45:2				
	=LIN1+OMA1-6X12:43:2				
	=LIN1+OMA1-6X12:37:2				
	=LIN1+OMA1-6X12:35:2				
	=LIN1+OMA1-6X12:32:4				
	=LIN1+OMA1-6X12:34:4				
	=LIN1+OMA1-6X12:41:2				
	=LIN1+OMA1-6X12:38:4				
	=LIN1+OMA1-6X12:36:4				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+FIELD-6M3:1	FIELD
				=LIN1+FIELD-6M3:2	FIELD
				=LIN1+FIELD-6M3:3	FIELD
				=LIN1+FIELD-6M3:4	FIELD
				=LIN1+FIELD-6M3:5	FIELD
				=LIN1+FIELD-6M3:6	FIELD
				=LIN1+FIELD-6M3:7	FIELD
				=LIN1+FIELD-6M3:8	FIELD
				=LIN1+FIELD-6M3:9	FIELD
				=LIN1+FIELD-6M3:10	FIELD
				=LIN1+FIELD-6M3:11	FIELD
				=LIN1+FIELD-6M3:12	FIELD
				=LIN1+FIELD-6M3:15	FIELD
				=LIN1+FIELD-6M3:14	FIELD
				=LIN1+FIELD-6M3:13	FIELD

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 6W4
Cable type UNITRONIC® LiYCY 15x0,34 mm²
Free conductors 2

Cable parts LAPP.0034515
Order number 0034515

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-6X12:49:2				
	=LIN1+OMA1-6X12:56:4				
	=LIN1+OMA1-6X12:62:4				
	=LIN1+OMA1-6X12:60:4				
	=LIN1+OMA1-6X12:58:4				
	=LIN1+OMA1-6X12:63:2				
	=LIN1+OMA1-6X12:61:2				
	=LIN1+OMA1-6X12:59:2				
	=LIN1+OMA1-6X12:53:2				
	=LIN1+OMA1-6X12:51:2				
	=LIN1+OMA1-6X12:48:4				
	=LIN1+OMA1-6X12:50:4				
	=LIN1+OMA1-6X12:57:2				
	=LIN1+OMA1-6X12:54:4				
	=LIN1+OMA1-6X12:52:4				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+FIELD-6M4:1	FIELD
				=LIN1+FIELD-6M4:2	FIELD
				=LIN1+FIELD-6M4:3	FIELD
				=LIN1+FIELD-6M4:4	FIELD
				=LIN1+FIELD-6M4:5	FIELD
				=LIN1+FIELD-6M4:6	FIELD
				=LIN1+FIELD-6M4:7	FIELD
				=LIN1+FIELD-6M4:8	FIELD
				=LIN1+FIELD-6M4:9	FIELD
				=LIN1+FIELD-6M4:10	FIELD
				=LIN1+FIELD-6M4:11	FIELD
				=LIN1+FIELD-6M4:12	FIELD
				=LIN1+FIELD-6M4:15	FIELD
				=LIN1+FIELD-6M4:14	FIELD
				=LIN1+FIELD-6M4:13	FIELD

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 6W5
Cable type UNITRONIC® LiYCY 15x0,34 mm²
Free conductors 2

Cable parts LAPP.0034515
Order number 0034515

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-6X12:65:2				
	=LIN1+OMA1-6X12:72:4				
	=LIN1+OMA1-6X12:78:4				
	=LIN1+OMA1-6X12:76:4				
	=LIN1+OMA1-6X12:74:4				
	=LIN1+OMA1-6X12:79:2				
	=LIN1+OMA1-6X12:77:2				
	=LIN1+OMA1-6X12:75:2				
	=LIN1+OMA1-6X12:69:2				
	=LIN1+OMA1-6X12:67:2				
	=LIN1+OMA1-6X12:64:4				
	=LIN1+OMA1-6X12:66:4				
	=LIN1+OMA1-6X12:73:2				
	=LIN1+OMA1-6X12:70:4				
	=LIN1+OMA1-6X12:68:4				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+FIELD-6M5:1	FIELD
				=LIN1+FIELD-6M5:2	FIELD
				=LIN1+FIELD-6M5:3	FIELD
				=LIN1+FIELD-6M5:4	FIELD
				=LIN1+FIELD-6M5:5	FIELD
				=LIN1+FIELD-6M5:6	FIELD
				=LIN1+FIELD-6M5:7	FIELD
				=LIN1+FIELD-6M5:8	FIELD
				=LIN1+FIELD-6M5:9	FIELD
				=LIN1+FIELD-6M5:10	FIELD
				=LIN1+FIELD-6M5:11	FIELD
				=LIN1+FIELD-6M5:12	FIELD
				=LIN1+FIELD-6M5:15	FIELD
				=LIN1+FIELD-6M5:14	FIELD
				=LIN1+FIELD-6M5:13	FIELD

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 11W6
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors

Cable parts LAPP.2170891
Order number 2170891

F09_004

Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-11KF1:X1:2	PLC KOMUNIKACIJA			



Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+OMA1-17A1:X1P1 R	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.
Preveril	Vodja projektive		
Mail	dejan.rozic@dafra-kt.si		08/2024| RRI
Verzija eplan	2024.0.3		

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 11W7
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors

Cable parts LAPP.2170891
Order number 2170891

F09_004

Location designation	Source	Function text source	Stopper	L1 [mm]	Part number



Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				NG-LIN1+OMA1-11KF1:X2:1	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija
Odgovoren Dejan Rožič 13. 08. 2025
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si
Verzija eplan 2024.0.3
DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 11W8
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors 4

Cable parts LAPP.2170891
Order number 2170891

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 11W9
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors 4

Cable parts LAPP.2170891
Order number 2170891

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 11W10
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors

Cable parts LAPP.2170891
Order number 2170891

F09_004

Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-11KF1:X5:1	NC			



Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+OMA1-29T1:X6:1-8	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025	
Preveril	Vodja projektive		
Mail	dejan.rozic@dafra-kt.si		
Verzija eplan	2024.0.3		

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 11W11
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors 4

Cable parts LAPP.2170891
Order number 2170891

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-11KF1:X6:1				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
			=LIN1+OMA1-11XF1:X1:IN:1-8		

14 16

Cable name 11W12
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors

Cable parts LAPP.2170891
Order number 2170891

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-11KF1:X7:1	NC			

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+OMA1-11XF2:X1:IN:1-8	

Cable name 11W13
Cable type ETHERLINE® PN Cat.5e Y 4x22 mm²
Free conductors

Cable parts LAPP.2170891
Order number 2170891

F09_004

Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-11KF1:X8:1	NC			



Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+OMA1-31U3-LAN:2	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.
Preveril	Vodja projektive		
Mail	dejan.rozic@dafra-kt.si		08/2024| RRI
Verzija eplan	2024.0.3		

Diagram kablov

= Dokumentacija
+ Cable_Diagram
/

Cable name 12W14
Cable type
Free conductors



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-21X15:1:2				
	=LIN1+OMA1-21X15:2:4				
	=LIN1+OMA1-21X15:3:2				

Cable parts
Order number

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+PLC-32X1:1	
				=LIN1+PLC-32X1:3	
				=LIN1+PLC-32X1:4	

F09_004

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 12W15
Cable type
Free conductors



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-21X15:4:4				
	=LIN1+OMA1-21X15:5:2				
	=LIN1+OMA1-21X15:6:4				

Cable parts
Order number

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+PLC-32X2:1	
				=LIN1+PLC-32X2:3	
				=LIN1+PLC-32X2:4	

F09_004

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 12W16
Cable type
Free conductors



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-21X15:1:2				
	=LIN1+OMA1-21X15:2:4				
	=LIN1+OMA1-21X15:4:4				
	=LIN1+OMA1-21X15:3:2				
	=LIN1+OMA1-21X15:6:4				
	=LIN1+OMA1-21X15:5:2				

Cable parts
Order number

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+PLC-32X3:1	
				=LIN1+PLC-32X3:2	
				=LIN1+PLC-32X3:4	
				=LIN1+PLC-32X3:3	
				=LIN1+PLC-32X3:6	
				=LIN1+PLC-32X3:5	

F09_004

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 20W21
Cable type 7G0,5 mm²
Free conductors 1

Cable parts 7G075
Order number

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
	=LIN1+OMA1-12X13:17:1				
	=LIN1+OMA1-12X13:18:1				
	=LIN1+OMA1-12X13:19:1				

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
				=LIN1+FIELD-20A1:-X80:1	FIELD
				=LIN1+FIELD-20A1:-X80:2	FIELD
				=LIN1+FIELD-20A1:FE	FIELD

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 30W22
Cable type SAC-5P- 5,0-PUR/M12FS
Free conductors

Cable parts PXC.1669848
Order number 1669848

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
FIELD	=LIN1+FIELD-30XC1:1	RTD1			
FIELD	=LIN1+FIELD-30XC1:3	=			
FIELD	=LIN1+FIELD-30XC1:2	=			
FIELD	=LIN1+FIELD-30XC1:4	=			

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
			RTD1	=LIN1+OMA1-18A4:-X10:5	
			=	=LIN1+OMA1-18A4:-X10:7	
			=	=LIN1+OMA1-18A4:-X10:6	
			=	=LIN1+OMA1-18A4:-X10:4	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 30W23
Cable type SAC-5P- 5,0-PUR/M12FS
Free conductors

Cable parts PXC.1669848
Order number 1669848

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
FIELD	=LIN1+FIELD-30XC2:1	RTD2			
FIELD	=LIN1+FIELD-30XC2:3	=			
FIELD	=LIN1+FIELD-30XC2:2	=			
FIELD	=LIN1+FIELD-30XC2:4	=			

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
			RTD2	=LIN1+OMA1-18A4:-X11:5	
			=	=LIN1+OMA1-18A4:-X11:7	
			=	=LIN1+OMA1-18A4:-X11:6	
			=	=LIN1+OMA1-18A4:-X11:4	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 30W24
Cable type SAC-5P- 5,0-PUR/M12FS
Free conductors

Cable parts PXC.1669848
Order number 1669848

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
FIELD	=LIN1+FIELD-30XC3:1	RTD3			
FIELD	=LIN1+FIELD-30XC3:3	=			
FIELD	=LIN1+FIELD-30XC3:2	=			
FIELD	=LIN1+FIELD-30XC3:4	=			

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
			RTD3	=LIN1+OMA1-18A4:-X12:5	
			=	=LIN1+OMA1-18A4:-X12:7	
			=	=LIN1+OMA1-18A4:-X12:6	
			=	=LIN1+OMA1-18A4:-X12:4	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Diagram kablov

= Dokumentacija
+ Cable_Diagram

/

Cable name 30W25
Cable type SAC-5P- 5,0-PUR/M12FS
Free conductors

Cable parts PXC.1669848
Order number 1669848

F09_004



Location designation	Source	Function text source	Stopper	L1 [mm]	Part number
FIELD	=LIN1+FIELD-30XC4:1	RTD4			
FIELD	=LIN1+FIELD-30XC4:3	=			
FIELD	=LIN1+FIELD-30XC4:2	=			
FIELD	=LIN1+FIELD-30XC4:4	=			

Part number	L2 [mm]	Stopper	Function text target	Target	Location designation
			RTD4	=LIN1+OMA1-18A4:-X13:5	
			=	=LIN1+OMA1-18A4:-X13:7	
			=	=LIN1+OMA1-18A4:-X13:6	
			=	=LIN1+OMA1-18A4:-X13:4	

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.
Preveril	Vodja projektive		
Mail	dejan.rozic@dafra-kt.si		08/2024| RRI
Verzija eplan	2024.0.3		

Diagram kablov

= Dokumentacija
+ Cable_Diagram
/

Cable overview

F10_002

Cable type	Cable description	Device tag	Conductors	Cross-section	Length	Function text
UNITRONIC® LiYCY		6W1	15	0,34	5	Actuator cable M1
		6W2	15	0,34	5	Actuator cable M2
		6W3	15	0,34	5	Actuator cable M3
		6W4	15	0,34	5	Actuator cable M4
		6W5	15	0,34	5	Actuator cable M1
ETHERLINE® PN Cat.5e Y	ETHERLINE Y CAT5 2X2XAWG22	11W6	4	22		PLC KOMUNIKACIJA
	ETHERLINE Y CAT5 2X2XAWG22	11W7	4	22		NC
	ETHERLINE Y CAT5 2X2XAWG22	11W8	4	22		HMI KOMUNIKACIJA
	ETHERLINE Y CAT5 2X2XAWG22	11W9	4	22		NC
	ETHERLINE Y CAT5 2X2XAWG22	11W10	4	22		=
	ETHERLINE Y CAT5 2X2XAWG22	11W11	4	22		FREKVENČNIK
	ETHERLINE Y CAT5 2X2XAWG22	11W12	4	22		NC
	ETHERLINE Y CAT5 2X2XAWG22	11W13	4	22		=
		12W14				
		12W15				
		12W16				
		20W21	7G	0,5		
SAC-5P- 5,0-PUR/M12FS		30W22				RTD1
		30W23				RTD2
		30W24				RTD3
		30W25				RTD4

Terminal diagram

F13_005

Strip

=LIN1+OMA1-1X1

Dovodne sponke

Page	Function text	Potential	External targets	Wiring	Wiring	Internal targets	Function text
/1.1		L1	+F33A-X1	BK	BK	-1S1	Glavno stikalo 63A Main Switch 63A
/1.1		L2	+F33A-X1	BK	BK	-1S1	
/1.1		L3	+F33A-X1	BK	BK	-1S1	
/1.1		N	+F33A-X1	BU	BU	-N	
/1.1		PE	+F33A-X1	GNYE	GNYE	-PE	



Strip

=LIN1+OMA1-2X2

Hlajenje ele. omare

Page	Function text	Potential	External targets	Wiring	Wiring	Internal targets	Function text
/2.1	Hlajenje ele. omare Cooling Cabinet	L1	-2M1	BK	BK	-2S2	Termostat 0-60
/2.2	=	N	-2M1	BU	BU	-N	
/2.2					GNYE	-PE	



Strip

=LIN1+OMA1-3X3

48VDC

Page	Function text	Potential	External targets	Wiring	Wiring	Internal targets	Function text
/3.a.2		L;L	-3K2 -3V1	BU BU	BU	-3F3	
/3.a.2		L;L	-3K3 -3V2	BU BU	BU	-3F4	
/3.a.2		L;L	-3K4 -3V3	BU BU	BU	-3F5	
/3.a.3		L;L	-3K5 -3V4	BU BU	BU	-3F6	
/3.a.3		L;L	-3K6 -3V5	BU BU	BU	-3F7	
/3.a.7		PE	-3V5	GNYE	GNYE	-3TB2	
/3.a.7		PE	-6X12	GNYE			
/3.a.7		PE	-6X12	GNYE			
/3.a.8		PE	-6X12	GNYE			
/3.a.8		PE	-6X12	GNYE			
/3.a.8		PE	-6X12	GNYE			



DAFRA Kontakt tehnologija
inovativno · zanesljivo · globalno
Odgovoren
Preveril
Dejan Rožič
Vodja projektive
Mail
dejan.rozic@dafra-kt.si
Verzija eplan
2024.0.3
13. 08. 2025
DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Terminal diagram

F13_005

Strip

=LIN1+OMA1-3X3

48VDC

Page	Function text	Potential	External targets	Wiring		Wiring	Internal targets	Function text
/3.a.8					12	GNYE	-3TB2	

Strip

=LIN1+OMA1-4X4

24V DC

Page	Function text	Potential	External targets	Wiring		Wiring	Internal targets	Function text
/4.1		L+	-10FC1	BU	1			
/4.1					2	BU	-11KF1	
/4.1					3			
/4.2					4	BU	-3V1	
/4.2		L+	-29T2	BU	5			

Strip

=LIN1+OMA1-5X5

0V DC

Page	Function text	Potential	External targets	Wiring		Wiring	Internal targets	Function text
/5.1		L-	-3TB1	BUWH	1	BUWH	-17A1	
/5.1		L-	-10FC1	BUWH	2	BUWH	-17A1	
/5.1		L-	-21X15	BUWH	3	BUWH	-17A1	
/5.2		L-	-21X15	BUWH	4	BUWH	-18A2	
/5.2					5	BUWH	-18A3	
/5.2					6	BUWH	-12X13	
/5.2					7	BUWH	-11KF1	
/5.2					8	BUWH	-26K8	
/5.3	POWER ENABLE M1	L-	-3K2	BUWH	9	BUWH	-6X12	
/5.3		L-	-29T2	BUWH	10	BUWH	-6X12	-6X12
/5.3					11	BUWH	-6X12	-6X12

3.a

Terminal diagram

F13_005

Strip

=LIN1+OMA1-6X12

Page	Function text	Potential	External targets	Wiring		Wiring		Internal targets	Function text
/6.a.1		L	+FIELD-6M1	6W1	GYPK	1	BU	-3K2	
/6.a.1			-29T1			2	WH 6W1	+FIELD-6M1	
/6.a.1		L	+FIELD-6M1	6W1	RDBU	3			
/6.a.1						4	VT 6W1	+FIELD-6M1	
/6.a.2		PE	+FIELD-6M1	6W1	WHGN	5	GNYE	-3X3	
/6.a.2		L-	-5X5		BUWH	6	BK 6W1	+FIELD-6M1	
/6.a.2		PE	+FIELD-6M1	6W1	BNGN	7			
/6.a.3		L-	+FIELD-6M1	6W1	BN	8	BUWH	-5X5	
/6.a.3		L-	-5X5		BUWH	9	WHYE 6W1	+FIELD-6M1	
/6.a.3		L	+FIELD-6M1	6W1	GY	10	BU	-21X15	M1 GO POS1
/6.a.3	M1 IN POS1	L	-21X15		BU	11	RD 6W1	+FIELD-6M1	
/6.a.3		L	+FIELD-6M1	6W1	YE	12	BU	-21X15	M1 GO POS2
/6.a.3	M1 IN POS2	L	-21X15		BU	13	BU 6W1	+FIELD-6M1	
/6.a.3		L	+FIELD-6M1	6W1	GN	14	BU	-21X15	M1 HOMMING
/6.a.3	M1 HOMMED	L	-21X15		BU	15	PK 6W1	+FIELD-6M1	
/6.a.5		L	+FIELD-6M2	6W2	GYPK	16	BU	-3K3	
/6.a.5						17	WH 6W2	+FIELD-6M2	
/6.a.5		L	+FIELD-6M2	6W2	RDBU	18			
/6.a.5						19	VT 6W2	+FIELD-6M2	
/6.a.5		PE	+FIELD-6M2	6W2	WHGN	20	GNYE	-3X3	
/6.a.5		L-	-5X5		BUWH	21	BK 6W2	+FIELD-6M2	
/6.a.5		PE	+FIELD-6M2	6W2	BNGN	22			
/6.a.5						23			
/6.a.6		L-	+FIELD-6M2	6W2	BN	24			
/6.a.6		L-	-5X5		BUWH	25	WHYE 6W2	+FIELD-6M2	
/6.a.6		L	+FIELD-6M2	6W2	GY	26	BU	-21X15	M2 GO POS1
/6.a.6	M2 IN POS1	L	-21X15		BU	27	RD 6W2	+FIELD-6M2	
/6.a.6		L	+FIELD-6M2	6W2	YE	28	BU	-21X15	M2 GO POS2
/6.a.6	M2 IN POS2	L	-21X15		BU	29	BU 6W2	+FIELD-6M2	
/6.a.7		L	+FIELD-6M2	6W2	GN	30	BU	-21X15	M2 HOMMING
/6.a.7	M2 HOMMED	L	-21X15		BU	31	PK 6W2	+FIELD-6M2	
/6.b.1		L	+FIELD-6M3	6W3	GYPK	32	BU	-3K4	
/6.b.1						33	WH 6W3	+FIELD-6M3	
/6.b.1		L	+FIELD-6M3	6W3	RDBU	34			
/6.b.1						35	VT 6W3	+FIELD-6M3	

DAFRA Kontakt tehnologija
inovativno · zanesljivo · globalno
Odgovoren Dejan Rožič
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si
Verzija eplan 2024.0.3
13. 08. 2025
DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Terminal diagram =LIN1+OMA1-6X12

/

= Dokumentacija
+ Terminal_Diagram

3.c

Terminal diagram

F13_005

Strip

=LIN1+OMA1-6X12

Page	Function text	Potential	External targets			Wiring			Internal targets		Function text
/6.b.2		PE	+FIELD-6M3	6W3	WHGN	36	GNYE		-3X3		
/6.b.2		L-	-5X5		BUWH	37	BK	6W3	+FIELD-6M3		
/6.b.2		PE	+FIELD-6M3	6W3	BNGN	38					
/6.b.2						39					
/6.b.3		L-	+FIELD-6M3	6W3	BN	40					
/6.b.3		L-	-5X5		BUWH	41	WHYE	6W3	+FIELD-6M3		
/6.b.3		L	+FIELD-6M3	6W3	GY	42	BU		-21X15		M3 GO POS1
/6.b.3	M3 IN POS1	L	-21X15		BU	43	RD	6W3	+FIELD-6M3		
/6.b.3		L	+FIELD-6M3	6W3	YE	44	BU		-21X15		M3 GO POS2
/6.b.3	M3 IN POS2	L	-21X15		BU	45	BU	6W3	+FIELD-6M3		
/6.b.3		L	+FIELD-6M3	6W3	GN	46	BU		-21X15		M3 HOMMING
/6.b.3	M3 HOMMED	L	-21X15		BU	47	PK	6W3	+FIELD-6M3		
/6.b.5		L	+FIELD-6M4	6W4	GYPK	48	BU		-3K5		
/6.b.5						49	WH	6W4	+FIELD-6M4		
/6.b.5		L	+FIELD-6M4	6W4	RDBU	50					
/6.b.5						51	VT	6W4	+FIELD-6M4		
/6.b.5		PE	+FIELD-6M4	6W4	WHGN	52	GNYE		-3X3		
/6.b.5		L-	-5X5		BUWH	53	BK	6W4	+FIELD-6M4		
/6.b.5		PE	+FIELD-6M4	6W4	BNGN	54					
/6.b.5						55					
/6.b.6		L-	+FIELD-6M4	6W4	BN	56					
/6.b.6		L-	-5X5		BUWH	57	WHYE	6W4	+FIELD-6M4		
/6.b.6		L	+FIELD-6M4	6W4	GY	58	BU		-21X15		M4 GO POS1
/6.b.6	M4 IN POS1	L	-21X15		BU	59	RD	6W4	+FIELD-6M4		
/6.b.6		L	+FIELD-6M4	6W4	YE	60	BU		-21X15		M4 GO POS2
/6.b.6	M4 IN POS2	L	-21X15		BU	61	BU	6W4	+FIELD-6M4		
/6.b.7		L	+FIELD-6M4	6W4	GN	62	BU		-21X15		M4 HOMMING
/6.b.7	M4 HOMMED	L	-21X15		BU	63	PK	6W4	+FIELD-6M4		
/6.c.1		L	+FIELD-6M5	6W5	GYPK	64	BU		-3K6		
/6.c.1						65	WH	6W5	+FIELD-6M5		
/6.c.1		L	+FIELD-6M5	6W5	RDBU	66					
/6.c.1						67	VT	6W5	+FIELD-6M5		
/6.c.2		PE	+FIELD-6M5	6W5	WHGN	68	GNYE		-3X3		
/6.c.2		L-	-5X5		BUWH	69	BK	6W5	+FIELD-6M5		
/6.c.2		PE	+FIELD-6M5	6W5	BNGN	70					

Odgovoren Dejan Rožič
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si
Verzija eplan 2024.0.3
13. 08. 2025
DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

Terminal diagram

F13_005

Strip

=LIN1+OMA1-6X12

Page	Function text	Potential	External targets	Wiring			Wiring		Internal targets	Function text
/6.c.2						71				
/6.c.3		L-	+FIELD-6M5	6W5	BN	72				
/6.c.3		L-	-5X5		BUWH	73	WHYE	6W5	+FIELD-6M5	
/6.c.3		L	+FIELD-6M5	6W5	GY	74	BU		-21X15	M5 GO POS1
/6.c.3	M5 IN POS1	L	-21X15		BU	75	RD	6W5	+FIELD-6M5	
/6.c.3		L	+FIELD-6M5	6W5	YE	76	BU		-21X15	M5 GO POS2
/6.c.3	M5 IN POS2	L	-21X15		BU	77	BU	6W5	+FIELD-6M5	
/6.c.3		L	+FIELD-6M5	6W5	GN	78	BU		-21X15	M5 HOMMING
/6.c.3	M5 HOMMED	L	-21X15		BU	79	PK	6W5	+FIELD-6M5	

Strip

=LIN1+OMA1-12X13

Page	Function text	Potential	External targets	Wiring			Wiring		Internal targets	Function text
/20.6		L+	-10FC1	BU		17	1	20W21	+FIELD-20A1	
/20.6		L-	-5X5	BUWH		18	2	20W21	+FIELD-20A1	
/20.6		PE	-PE	GNYE		19	PE	20W21	+FIELD-20A1	

Strip

=LIN1+OMA1-21X15

PLC sponke

Page	Function text	Potential	External targets	Wiring			Wiring		Internal targets	Function text
/21.1	Trigger		-17A1			17				
/24.b.1	M1 IN POS1	L	-18A3	BU		33	BU		-6X12	
/24.c.1	M2 IN POS2	L	-18A3	BU		37	BU		-6X12	

DAFRA
Kontakt tehnologija
inovativno · zanesljivo · globalno

Odgovoren Dejan Rožič
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si
Verzija eplan 2024.0.3
13. 08. 2025

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Terminal diagram =LIN1+OMA1-6X12 =LIN1+OMA1-12X13 =LIN1+OMA1-21X15

/

= Dokumentacija
+ Terminal_Diagram

Terminal diagram

F13_005

Strip

=LIN1+OMA1-21X15

PLC sponke

Page	Function text	Potential	External targets	Wiring		Wiring	Internal targets	Function text
/24.d.1	M3 HOMMED	L	-18A3	BU	41	BU	-6X12	
/24.e.1	M5 IN POS1	L	-18A3	BU	45	BU	-6X12	
/27.1	POWER ENABLE M4	L	-3K5	BU	57	BU	-17A1	POWER ENABLE M4
/27.a.1		L	-6X12	BU	59	BU	-18A3	M1 GO POS1
/27.b.1		L	-6X12	BU	63	BU	-18A3	M2 GO POS2
/27.c.1		L	-6X12	BU	67	BU	-18A3	M3 HOMMING
/27.d.1		L	-6X12	BU	71	BU	-18A3	M5 GO POS1
/24.c.3		L	-18A3	BU	38	BU	-6X12	
/24.b.3	M1 IN POS2	L	-18A3	BU	34	BU	-6X12	
/24.d.3	M4 IN POS1	L	-18A3	BU	42	BU	-6X12	
/24.e.3	M5 IN POS2	L	-18A3	BU	46	BU	-6X12	
/27.3	POWER ENABLE M5	L	-3K6	BU	58	BU	-17A1	POWER ENABLE M5
/27.a.3		L	-6X12	BU	60	BU	-18A3	M1 GO POS2
/27.b.3		L	-6X12	BU	64	BU	-18A3	M2 HOMMING
/27.c.3		L	-6X12	BU	68	BU	-18A3	M4 GO POS1
/27.d.3		L	-6X12	BU	72	BU	-18A3	M5 GO POS2
/21.3			-17A1		18		+FIELD-21X1	Trigger
/24.c.5	M3 IN POS1	L	-18A3	BU	39	BU	-6X12	
/24.b.5	M1 HOMMED	L	-18A3	BU	35	BU	-6X12	
/24.d.5	M4 IN POS2	L	-18A3	BU	43	BU	-6X12	
/24.e.5	M5 HOMMED	L	-18A3	BU	47	BU	-6X12	
/27.a.5		L	-6X12	BU	61	BU	-18A3	M1 HOMMING
/27.b.6		L	-6X12	BU	65	BU	-18A3	M3 GO POS1
/27.c.6		L	-6X12	BU	69	BU	-18A3	M4 GO POS2
/27.d.6		L	-6X12	BU	73	BU	-18A3	M5 HOMMING
/21.5			-17A1		19		+FIELD-21X1	Trigger
/24.c.8	M3 IN POS2	L	-18A3	BU	40	BU	-6X12	
/24.b.8	M2 IN POS1	L	-18A3	BU	36	BU	-6X12	
/24.d.8	M4 HOMMED	L	-18A3	BU	44	BU	-6X12	
/24.e.8			-18A3		48			
/27.a.8		L	-6X12	BU	62	BU	-18A3	M2 GO POS1
/27.b.8		L	-6X12	BU	66	BU	-18A3	M3 GO POS2
/27.c.8		L	-6X12	BU	70	BU	-18A3	M4 HOMMING

Odgovoren Dejan Rožič
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si

Verzija eplan 2024.0.3
13. 08. 2025
DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI
Terminal diagram =LIN1+OMA1-21X15
/
= Dokumentacija
+ Terminal_Diagram
Page 3.e
Page 37 / 105
3.f

Terminal diagram

F13_005

Strip

=LIN1+OMA1-21X15

PLC sponke

Page	Function text	Potential	External targets	Wiring		Wiring	Internal targets	Function text
/27.d.8							-18A3	
/21.8			-17A1				+FIELD-21X1	Trigger
/22.1			-17A1					
/22.3			-17A1					
/22.5			-17A1					
/22.8	EGASI PWR OK	L	-17A1	BU		BU	-3V5	
/23.1			-17A1					
/23.3			-17A1					
/23.5			-17A1					
/23.8			-17A1					
/24.1			-17A1					
/24.3	AKD1 - status		-17A1					
/24.5								
/24.8								
/25.1						BU	-17A1	Sistem feedback OK
/25.3							-17A1	
/25.5							-17A1	
/25.8							-17A1	
/26.1		L	-26K8	BU		BU	-17A1	
/26.3	POWER ENABLE M1	L	-3K2	BU		BU	-17A1	POWER ENABLE M1
/26.5	POWER ENABLE M2	L	-3K3	BU		BU	-17A1	POWER ENABLE M2
/26.8	POWER ENABLE M3	L	-3K4	BU		BU	-17A1	POWER ENABLE M3
/28.2			-17A1					
/28.5			-17A1					
/29.2			-17A1					
/29.5			-17A1					
/12.0			+PLC-32X3	12W16	BK			
			+PLC-32X1	12W14	BK			
/12.1		L-;L-	+PLC-32X3	12W16	BN			
			+PLC-32X1	12W14	BN	BUWH	-5X5	
/12.1			+PLC-32X3	12W16	GY			
			+PLC-32X1	12W14	GY			
/12.1			+PLC-32X3	12W16	BU			
			+PLC-32X2	12W15	BK			
/12.2		L-;L-	+PLC-32X3	12W16	RD			
			+PLC-32X2	12W15	BN	BUWH	-5X5	
/12.2		L;L	+PLC-32X3	12W16	OG			
			+PLC-32X2	12W15	BU			
/12.3								
/12.4								
/12.4								

Odgovoren: Dejan Rožič
Preveril: Vodja projektive
Mail: dejan.rozic@dafra-kt.si
Verzija eplan: 2024.0.3

13. 08. 2025

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Terminal diagram =LIN1+OMA1-21X15

= Dokumentacija

+ Terminal_Diagram

3.f

Terminal diagram

F13_005

Strip

=LIN1+OMA1-21X15

PLC sponke

Page	Function text	Potential	External targets	Wiring	Internal targets	Function text
/12.4						
/12.4						
/12.4						
/12.5						
/12.5						
/12.5						
/12.5						



DAFRA Kontakt tehnologija
inovativno · zanesljivo · globalno

Odgovoren: Dejan Rožič
Preveril: Vodja projektive
Mail: dejan.rozic@dafra-kt.si
Verzija eplan: 2024.0.3

13. 08. 2025

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Terminal diagram =LIN1+OMA1-21X15

+Plug_Diagram/104

= Dokumentacija
+ Terminal_Diagram

Page 3.g
Page 39 / 105

Plug diagram

F22_001

Function text								Cable name / Cable type	Target designation	Connection point	Plug designation	Jumper	Device connection point	Target designation	Connection point	Cable name / Cable type					Page / column
											Strip designation =LIN1+OMA1-6XP1										
											1			-6F8	2						/6.1
											2										/6.1
											3										/6.1

Plug diagram

F22_001

Strip designation

=LIN1+OMA1-6XP2

Function text	Cable name	Cable type	Target designation	Connection point	Plug designation	Jumper	Device connection point	Target designation	Connection point	Cable name	Cable type	Page / column
					1			-6F9	2			/6.2
					2			-N	8			/6.2
					3			-PE	12			/6.2

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Plug diagram =LIN1+OMA1-6XP2

= Dokumentacija

+ Plug_Diagram

/

Plug diagram

F22_001

Function text								30W22	Cable name	Strip designation =LIN1+FIELD-30XC1 RTD1							Cable name					Page / column
								SAC-5P- 5,0-PUR/M12FS	Cable type	Target designation	Connection point	Plug designation	Jumper	Device connection point	Target designation	Connection point	Cable type					
RTD1								BN		+OMA1-18A4	-X10:5	1			-30R1							+OMA1/30.a.1
=								WH		+OMA1-18A4	-X10:6	2			-30R1							+OMA1/30.a.1
=								BU		+OMA1-18A4	-X10:7	3			-30R1							+OMA1/30.a.1
=								BK		+OMA1-18A4	-X10:4	4		PIW24	-30R1							+OMA1/30.a.1

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Plug diagram =LIN1+FIELD-30XC1

= Dokumentacija
+ Plug_Diagram

/

Plug diagram

F22_001

Function text								30W23	Cable name	Strip designation =LIN1+FIELD-30XC2 RTD2							Cable name						Page / column
								SAC-5P- 5,0-PUR/M12FS	Cable type	Target designation	Connection point	Plug designation	Jumper	Device connection point	Target designation	Connection point	Cable type						
RTD2								BN		+OMA1-18A4	-X11:5	1			-30R2								+OMA1/30.a.3
=								WH		+OMA1-18A4	-X11:6	2			-30R2								+OMA1/30.a.4
=								BU		+OMA1-18A4	-X11:7	3			-30R2								+OMA1/30.a.4
=								BK		+OMA1-18A4	-X11:4	4		PIW26	-30R2								+OMA1/30.a.4

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Plug diagram =LIN1+FIELD-30XC2

= Dokumentacija
+ Plug_Diagram

/

Plug diagram

F22_001

Function text								30W24	Cable name	Strip designation =LIN1+FIELD-30XC3 RTD3							Cable name					Page / column
								SAC-5P- 5,0-PUR/M12FS	Cable type	Target designation	Connection point	Plug designation	Jumper	Device connection point	Target designation	Connection point	Cable type					
RTD3								BN		+OMA1-18A4	-X12:5	1			-30R3							+OMA1/30.a.6
=								WH		+OMA1-18A4	-X12:6	2			-30R3							+OMA1/30.a.6
=								BU		+OMA1-18A4	-X12:7	3			-30R3							+OMA1/30.a.6
=								BK		+OMA1-18A4	-X12:4	4		PIW28	-30R3							+OMA1/30.a.6

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Plug diagram =LIN1+FIELD-30XC3

= Dokumentacija
+ Plug_Diagram

/

Plug diagram

F22_001

Function text								30W25	Cable name	Strip designation =LIN1+FIELD-30XC4 RTD4							Cable name						Page / column
								SAC-5P- 5,0-PUR/M12FS	Cable type	Target designation	Connection point	Plug designation	Jumper	Device connection point	Target designation	Connection point	Cable type						
RTD4								BN		+OMA1-18A4	-X13:5	1			-30R4								+OMA1/30.a.8
=								WH		+OMA1-18A4	-X13:6	2			-30R4								+OMA1/30.a.8
=								BU		+OMA1-18A4	-X13:7	3			-30R4								+OMA1/30.a.9
=								BK		+OMA1-18A4	-X13:4	4		PIW30	-30R4								+OMA1/30.a.9

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Plug diagram =LIN1+FIELD-30XC4

= Dokumentacija
+ Plug_Diagram

/

Plug overview

F23_002

Plug designation	Function text	Plug					Page of plug diagram
		first	last	Total PE	Total N	Total number	
=L1+MP-?X1				0	0	0	
=L1+MP-?X2				0	0	0	
=L1+MP-?X3				0	0	0	
=LIN1+OMA1-6XP1		1	3	0	0	3	=Dokumentacija+Plug_Diagram/104
=LIN1+OMA1-6XP2		1	3	0	0	3	=Dokumentacija+Plug_Diagram/105
=LIN1+FIELD-30XC1	RTD1	1	4	0	0	4	=Dokumentacija+Plug_Diagram/106
=LIN1+FIELD-30XC2	RTD2	1	4	0	0	4	=Dokumentacija+Plug_Diagram/107
=LIN1+FIELD-30XC3	RTD3	1	4	0	0	4	=Dokumentacija+Plug_Diagram/108
=LIN1+FIELD-30XC4	RTD4	1	4	0	0	4	=Dokumentacija+Plug_Diagram/109

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Plug overview : =L1+MP-?X1 - =LIN1+FIELD-30XC4

= Dokumentacija
+ Plug_Overview

/

Terminal-strip overview

F14_002

Terminal strip	Function text	Terminals					Terminal diagram page
		first	last	Total PE	Total N	Total number	
=LIN1+OMA1-1X1	Dovodne sponke	1	PE	1	0	5	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-2X2	Hlajenje ele. omare	1	PE	1	1	3	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-3X3	48VDC	1	12	0	0	12	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-4X4	24V DC	1	5	0	0	5	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-5X5	0V DC	1	11	0	0	11	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-6X12		1	79	0	0	80	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-12X13		17	19	0	0	6	=Dokumentacija+Terminal_Diagram/3
=LIN1+OMA1-21X15	PLC sponke	17	16	0	0	81	=Dokumentacija+Terminal_Diagram/3

Table of contents

F06_002

Table of contents

F06_002

Table of contents

F06_002

Table of contents

F06_002



=Dokumentacija+TOC/1.c

2

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	Dovod
	Preveril	Vodja projektive		08/2024| RRI	
	Mail	dejan.rozic@dafra-kt.si			
	Verzija eplan	2024.0.3			

= LIN1
+ OMA1
/
Page 1
Page 52 / 105

Hlajenje ele. omare
Cooling Cabinet

1 3

2.8 / L1
2.8 / L2
2.8 / L3

L1 / 3.a.0
L2 / 3.a.0
L3 / 3.a.0

-3Q2
0.5A

2 4 6 13 21
14 22
I> I> I>
1 3 5

-PE:9

PE
2,5 mm²

-3TB1
L1(+) L2(-) L3 PE

1469530000
PRO ECO3 120W 24V 5A

+ + - - 13 14

10.3 / DC1_COM
/ DC2_OK

L+ 2,5
L+ 2,5
L- 2,5 mm²

NAPAJANJE
MURR VAROVALKE

Napajanje 24V DC
Power Supply 24V DC

L01+ / 10.0
L02+ /

Distribucija 0V
Distribution 0V

DC_0V_FEED / 5.1

ALARM DC1

2

3.a

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	220V AC / 24V DC	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/	Page 3
	Verzija eplan	2024.0.3					Page 54 / 105

3.9 / L1
3.9 / L2
3.9 / L3

L1 / 6.0
L2 / 6.0
L3 / 6.0

-N:9 -PE:10

-3F3
B4
1
2

4.9 / 48VDC_OK
/ 48VDC_OK

-3TB2
L(+) N(-) PE
1469590000
PRO ECO 240W 48V 5A
+ + - - 13 14

L 1 mm²
M 1 mm²

VCC_48V_L / 3.c.0
VCC_48V_M / 3.c.0

-3X3 = 48VDC
-3X3 1 6 7 8 9 10 11 12

3.c.8 / M1_PWR_STATUS
3.c.8 / M2_PWR_STATUS
3.c.8 / M3_PWR_STATUS
3.c.8 / M4_PWR_STATUS
3.c.8 / M5_PWR_STATUS

A1
-2V1
-2V2
-2V3
-2V4
-2V5

M 0,5 mm²
PWR_M1_M / 6.a.2
PWR_M2_M / 6.a.5
PWR_M3_M / 6.b.2
PWR_M4_M / 6.b.5
PWR_M5_M / 6.c.2

L 0,5 mm²
egasi_PWR_M1_48V / 22.1
egasi_PWR_M2_48V / 22.3
egasi_PWR_M3_48V / 22.5
egasi_PWR_M4_48V / 22.8
egasi_PWR_M5_48V / 23.1

4.9 / egasi_PWR_OK

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.
08/2024| RRI

220V AC / 48V DC

= LIN1
+ OMA1
/



3.a

3.c

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	EGASI actuator POWER enable		= LIN1
	Preveril	Vodja projektive					+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					Page 3.b
							Page 56 / 105



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	48V FUSE Motors	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3				Page	3.c
						Page	57 / 105

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	24V periferija	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/ Page 4
	Verzija eplan	2024.0.3					Page 58 / 105



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DISTRIBUCIJA 0V	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 5
	Verzija eplan	2024.0.3				Page 59 / 105

inovativno • zanesljivo • globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	230V Vtičnice	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/ Page 6
	Verzija eplan	2024.0.3					Page 60 / 105



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	EGASI M1, M2	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 6.a
	Verzija eplan	2024.0.3				Page 61 / 105



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	EGASI M3, M4	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					Page 6.b
							Page 62 / 105



DAFRA Kontakt tehnologija (inovativno · zanesljivo · globalno)	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	EGASI M5	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3				Page	6.c
						Page	63 / 105

0	1	2	3	4	5	6	7	8	9

3.8 / L01+

NAPAKA IZHODA

DC1_COM / 3.0

-10FC1
IN: 24 V DC
OUT: 24 V DC / 5x2 A , 3x6 A

MURR ELEKTRONIK
stay connected
9000-41068-0200600

+24V
ON
14

+24V

Logic

GND/0V
bridging contact

GND

OUT1 1A
OUT2 1A
OUT3 2A
OUT4 2A
OUT5 2A
OUT6 4A
OUT7 4A
OUT8 4A

L+ 1,5 PLC_DI_L+ / 19.0
L+ 1,5 PLC_AQ_L+ / 19.0
L+ 1,5 PLC_DQ_L+ / 19.0
L+ 1,5 PLC_TC_L+ / 19.0
L+ 1,5 DC24V / 4.0
L+ 1 PLC_L+ / 19.0
1215C PLC, DI/DQ, AI
L+ 1,5 HMI_L+ / 20.0
L+ 1,5 X1_24V /

5.9 / DC-_b

DC-_b /

VARNOST
KANAL1 + KANAL 2

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	24V - VAROVALKE	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/ Page 10
	Verzija eplan	2024.0.3					Page 64 / 105

4.9 / S_OUT2_b

5.9 / F_DC_-

-PE:13

-11KF1

V+ V- V+ V- F.G.

UB2 0V UB1 0V FE

P2 P1

11.8 / 58186_X6

11.8 / 58186_X7

-11XF1

X1:IN 1-8

RJ45

X1:OUT 1-8

MURR ELEKTRONIK

stay connected

4000-73000-0010000

4000-73000-0010000

-11XF2

X1:IN 1-8

RJ45

X1:OUT 1-8

MURR ELEKTRONIK

stay connected

4000-73000-0010000

4000-73000-0010000

PC_COM / 31.1

MURR ELEKTRONIK

stay connected

8 port unmanaged switch 58171

RJ45 PORT 1 X1 1

RJ45 PORT 2 X2 1

RJ45 PORT 3 X3 1

RJ45 PORT 4 X4 1

RJ45 PORT 5 X5 1

RJ45 PORT 6 X6 1

RJ45 PORT 7 X7 1

RJ45 PORT 8 X8 1

-11W6 WH 22AWG

-11W7 WH 22AWG

-11W8

-11W9

-11W10 WH 22AWG

-11W11

-11W12 WH 22AWG

-11W13 WH 22AWG

ROUTER_COM / 31.3

PROGRAMING PORT

58186_X7 / 11.7

PC PORT

58186_X6 / 11.6

KOLLMORGEN AKD

58186_X5 / 29.a.0

HMI PROFINET

58186_X4 /

AKD1_profinet / 14.1

S7 1215C P1 - PROFINET

58186_X1 / 14.1

PLC KOMUNIKACIJA

NC

HMI KOMUNIKACIJA

NC

NC

FREKVENČNIK

NC

NC

10

12



11

14

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	IO	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		Page 12
	Verzija eplan	2024.0.3				/	Page 66 / 105



inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Profinet mreža

= LIN1
+ OMA1
/

0	1	2	3	4	5	6	7	8	9

-15K7



inovativno • zanesljivo • globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	HMI	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					

0	1	2	3	4	5	6	7	8	9

0	1	2	3	4	5	6	7	8	9

-17A1

/19.2
/21.1
/22.1
/23.1
/24.1
/24.3
/28.2
/29.2
/25.1
/26.1
/27.1

SIE.6ES7215-1AG40-0XB0

S7-1200
CPU 1215C DC/DC/DC

SIEMENS



						X1 P1 R PN		/14.2		
						X1 P2 R PN		/14.3		
				-X10:1 L+		-X11:1 2M		/19.4		
			/19.2	-X10:2 M		PQW4 -X11:2 AQ 0		/28.2	-21X7:74	
			/19.2	-X10:3 FE		PQW6 -X11:3 AQ 1		/28.5	-21X7:75	
			/19.3	-X10:4 L+						
			/19.3	-X10:5 M		-X11:4 3M		/19.4		
			/19.3	-X10:6 1M		PIW4 -X11:5 AI 0		/29.2	-21X7:76	
Trigger		-xSystemTrigger	/21.1	-X10:7 DI a.0	I1.6	PIW6 -X11:6 AI 1		/29.5	-21X7:77	
		-i_xEncoder_A	/21.3	-X10:8 DI a.1	I1.7					
		-i_xEncoder_B	/21.5	-X10:9 DI a.2	I2.0	-X12:1 4L+		/19.4		
		-i_xEncoder_Z	/21.8	-X10:10 DI a.3	I2.1	-X12:2 4M		/19.4		
		-3V1	/22.1	-X10:11 DI a.4	I2.2	Q1.2 -X12:3 DQ a.0		/25.1	-xSystemOK	Sistem feedback OK
		-3V2	/22.3	-X10:12 DI a.5	I2.3	Q1.3 -X12:4 DQ a.1		/25.3	-21X7:49	
		-3V3	/22.5	-X10:13 DI a.6	I2.4	Q1.4 -X12:5 DQ a.2		/25.5	-21X7:50	
	EGASI PWR OK	-3V4	/22.8	-X10:14 DI a.7	I2.5	Q1.5 -X12:6 DQ a.3		/25.8	-21X7:51	
		-3V5	/23.1	-X10:15 DI b.0	I2.6	Q1.6 -X12:7 DQ a.4		/26.1	-26K8:+A1	
		-21X7:25	/23.3	-X10:16 DI b.1	I2.7	Q1.7 -X12:8 DQ a.5		/26.3	-q_xMotor1_PWR_EN	POWER ENABLE M1
	i_xDoubleFeed	-23B3:3	/23.5	-X10:17 DI b.2	I3.0	Q2.0 -X12:9 DQ a.6		/26.5	-q_xMotor2_PWR_EN	POWER ENABLE M2
	i_xSmallFeed	-23B2:3	/23.8	-X10:18 DI b.3	I3.1	Q2.1 -X12:10 DQ a.7		/26.8	-q_xMotor3_PWR_EN	POWER ENABLE M3
	i_xShapeSensor_1	-24B1:3	/24.1	-X10:19 DI b.4	I3.2	Q2.2 -X12:11 DQ b.0		/27.1	-q_xMotor5_PWR_EN	POWER ENABLE M4
	i_xShapeSensor_2	-24B2:3	/24.3	-X10:20 DI b.5	I3.3	Q2.3 -X12:12 DQ b.1		/27.3	-3K6:A1	POWER ENABLE M5

6ES7215-1AG40-0XB0

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	PLC	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 17
	Verzija eplan	2024.0.3				Page 70 / 105

-18A2
/19.5

Siemens
6ES7231-5QD32-0XB0



			X10:1 L+	/19.5	
			X10:2 M	/19.6	
			X10:3 FE	/19.6	
+	0	PIW8	X10:4 AI 0+	/30.1	TEMP. ORODJA
-	0		X10:5 AI 0-	/30.1	
+	1	PIW10	X10:6 AI 1+	/30.3	TEMP. ORODJA
-	1		X10:7 AI 1-	/30.3	
			X11:1 n.c.		
			X11:2 n.c.		
			X11:3 n.c.		
+	2	PIW12	X11:4 AI 2+	/30.5	TEMP. OKOLICE
-	2		X11:5 AI 2-	/30.5	
+	3	PIW14	X11:6 AI 3+	/30.7	
-	3		X11:7 AI 3-	/30.7	

SIEMENS

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

AI

= LIN1
+ OMA1
/
Page 18
Page 71 / 105

0	1	2	3	4	5	6	7	8	9

-18A3
/19.7
/24.b.1
/24.c.1
/24.d.1
/24.e.1
/27.a.1
/27.b.1
/27.c.1
/27.d.1
SIE.6ES7223-1BL32-0XB0

S7-1200 SIEMENS
SM1223 DI 16x24VDC / DO 16x24VDC

		/19.8	-X10:1 L+				-X12:1 n.c.		
		/19.8	-X10:2 M				-X12:2 n.c.		
		/19.8	-X10:3 1M				-X12:3 n.c.		
M1 IN POS1	+FIELD-6M1:8	/24.b.1	-X10:4 DI a.0	I4.0		Q2.4	-X12:4 DQ a.0	/27.a.1	+FIELD-6M1:5	M1 GO POS1
M1 IN POS2	-i_xEncoder_A	/24.b.3	-X10:5 DI a.1	I4.1		Q2.5	-X12:5 DQ a.1	/27.a.3	-q_xMotor1_PWR_EN	M1 GO POS2
M1 HOMMED	-i_xEncoder_B	/24.b.5	-X10:6 DI a.2	I4.2		Q2.6	-X12:6 DQ a.2	/27.a.5	-q_xMotor2_PWR_EN	M1 HOMMING
M2 IN POS1	-i_xEncoder_Z	/24.b.8	-X10:7 DI a.3	I4.3		Q2.7	-X12:7 DQ a.3	/27.a.8	-q_xMotor3_PWR_EN	M2 GO POS1
M2 IN POS2	+FIELD-6M2:7	/24.c.1	-X10:8 DI a.4	I4.4		Q3.0	-X12:8 DQ a.4	/27.b.1	+FIELD-6M2:4	M2 GO POS2
	-i_xEncoder_A	/24.c.3	-X10:9 DI a.5	I4.5		Q3.1	-X12:9 DQ a.5	/27.b.3	-q_xMotor1_PWR_EN	M2 HOMMING
M3 IN POS1	-i_xEncoder_B	/24.c.5	-X10:10 DI a.6	I4.6		Q3.2	-X12:10 DQ a.6	/27.b.6	-q_xMotor2_PWR_EN	M3 GO POS1
M3 IN POS2	-i_xEncoder_Z	/24.c.8	-X10:11 DI a.7	I4.7		Q3.3	-X12:11 DQ a.7	/27.b.8	-q_xMotor3_PWR_EN	M3 GO POS2
		/19.8	-X11:1 FE				-X13:1 n.c.			
			-X11:2 n.c.				-X13:2 n.c.			
		/19.8	-X11:3 2M				-X13:3 n.c.			
M3 HOMMED	+FIELD-6M3:6	/24.d.1	-X11:4 DI b.0	I5.0		Q3.4	-X13:4 DQ b.0	/27.c.1	+FIELD-6M3:3	M3 HOMMING
M4 IN POS1	-i_xEncoder_A	/24.d.3	-X11:5 DI b.1	I5.1		Q3.5	-X13:5 DQ b.1	/27.c.3	-q_xMotor1_PWR_EN	M4 GO POS1
M4 IN POS2	-i_xEncoder_B	/24.d.5	-X11:6 DI b.2	I5.2		Q3.6	-X13:6 DQ b.2	/27.c.6	-q_xMotor2_PWR_EN	M4 GO POS2
M4 HOMMED	-i_xEncoder_Z	/24.d.8	-X11:7 DI b.3	I5.3		Q3.7	-X13:7 DQ b.3	/27.c.8	-q_xMotor3_PWR_EN	M4 HOMMING
M5 IN POS1	+FIELD-6M5:8	/24.e.1	-X11:8 DI b.4	I5.4		Q4.0	-X13:8 DQ b.4	/27.d.1	+FIELD-6M5:5	M5 GO POS1
M5 IN POS2	-i_xEncoder_A	/24.e.3	-X11:9 DI b.5	I5.5		Q4.1	-X13:9 DQ b.5	/27.d.3	-q_xMotor1_PWR_EN	M5 GO POS2
M5 HOMMED	-i_xEncoder_B	/24.e.5	-X11:10 DI b.6	I5.6		Q4.2	-X13:10 DQ b.6	/27.d.6	-q_xMotor2_PWR_EN	M5 HOMMING
	-i_xEncoder_Z	/24.e.8	-X11:11 DI b.7	I5.7		Q4.3	-X13:11 DQ b.7	/27.d.8	-q_xMotor3_PWR_EN	

6ES7223-1BL32-0XB0

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	di	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 18.a
	Verzija eplan	2024.0.3				Page 72 / 105

0	1	2	3	4	5	6	7	8	9

-18A4
/19.6
/30.a.1
SIE.6ES7231-5PD32-0XB0

S7-1200
SM 1231 RTD 4 x 16 Bit

SIEMENS



6ES7231-5PD32-0XB0

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	AI RTD		= LIN1
	Preveril	Vodja projektive					+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					Page 18.b
							Page 73 / 105

0	1	2	3	4	5	6	7	8	9



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	PLC napajanje	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 19
	Verzija eplan	2024.0.3				Page 74 / 105

+FIELD

-20A1



-X80 1 L+ 2 M FE

-20W18
7G0,5
1 0,75
2 0,75
PE 0,75

-21X7 13 14 15

10.8 / HMI_L+

5.9 / HMI_M

1.3 / HMI_PE

19

21

inovativno • zanesljivo • globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	HMI napajanje	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3				Page 20
						Page 75 / 105

+FIELD

-21U1
Enkoder 1000PPR

A B Z

-21X1 1 2 3

Trig_L+ / 12.1

-21X7 16 17 18 19

-X10	7	8	9	10
	DI a.0	DI a.1	DI a.2	DI a.3
	-17A1			
	/17.4	/17.4	/17.4	/17.4
	I1.6	I1.7	I2.0	I2.1
	-xSystemTrigger	-i_xEncoder_A	-i_xEncoder_B	-i_xEncoder_Z
	Trigger			

-21X7 = PLC sponke

Trigger

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

DI

= LIN1
+ OMA1
/


3.a.8
egasi_PWR_M1_48V
3.a.8
egasi_PWR_M2_48V
3.a.8
egasi_PWR_M3_48V
3.a.8
egasi_PWR_M4_48V
-21X7
20
21
22
23
-X10
11
12
13
14
DI a.4
-17A1
/17.4
I2.2
-3V1
DI a.5
/17.4
I2.3
-3V2
DI a.6
/17.4
I2.4
-3V3
DI a.7
/17.4
I2.5
-3V4
EGASI PWR OK
EGASI PWR OK



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DI	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					Page 23 / Page 78 / 105



DAFRA Kontakt tehnologija (inovativno · zanesljivo · globalno)	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DI	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3				Page	24
						Page	79 / 105

0	1	2	3	4	5	6	7	8	9

inovativno · zanesljivo · globalno
DAFRA
Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

empty

= LIN1
+ OMA1

/



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DI / M1/M2	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 24.b
	Verzija eplan	2024.0.3					Page 81 / 105



inovativno · zanesljivo · globalno
DAFRA
Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

DI M3/M3

= LIN1
+ OMA1
/


6.b.3
M3_HOM
6.b.6
M4_inPOS1
6.b.6
M4_inPOS2
6.b.7
M4_HOM
L
0,5 mm²
-21X7
40
41
42
43
-X11
4
5
6
7
DI b.0
-18A3
/18.a.3
I5.0
+FIELD-6M3:6
M3 HOMMED
DI b.1
/18.a.3
I5.1
-i_xEncoder_A
M4 IN POS1
DI b.2
/18.a.3
I5.2
-i_xEncoder_B
M4 IN POS2
DI b.3
/18.a.3
I5.3
-i_xEncoder_Z
M4 HOMMED
M3 HOMMED
M4 IN POS1
M4 IN POS2
M4 HOMMED

24.c

24.e



M5 IN POS1

M5 IN POS2

M5 HOMMED

24.d

24.f

0	1	2	3	4	5	6	7	8	9

inovativno · zanesljivo · globalno
DAFRA
Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

Outputs

= LIN1
+ OMA1

/



Sistem feedback OK

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DQ	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					


-26K8:+A1
Q1.6
/17.6
-17A1
DQ a.4
-X12 7
-21X7 52
L
0,5 mm²
+A1
-26K8
-A2
5.9 / M_R-
POWER ENABLE M1
-q_xMotor1_PWR_EN
Q1.7
/17.6
DQ a.5
8
53
L
0,5 mm²
3.b.4 / M1_PWR
POWER ENABLE M2
-q_xMotor2_PWR_EN
Q2.0
/17.6
DQ a.6
9
54
L
0,5 mm²
3.b.5 / M2_PWR
POWER ENABLE M3
-q_xMotor3_PWR_EN
Q2.1
/17.6
DQ a.7
10
55
L
0,5 mm²
3.b.6 / M3_PWR
M_R- / 27.0
14 (NO)
12 (NC)
11 (COM)
24 (NO)
22 (NC)
21 (COM)

0	1	2	3	4	5	6	7	8	9

POWER ENABLE M4
-q_xMotor5_PWR_EN
Q2.2
/17.6
-17A1
DQ b.0
-X12 11

-21X7 56
L
0,5 mm²

3.b.7 / M4_PWR

POWER ENABLE M5
-3K6:A1
Q2.3
/17.6

DQ b.1
12

57
L
0,5 mm²

3.b.8 / M5_PWR

26.9 / M_R- → M_R- /

26 27.a

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DQ	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					

Page 27
Page 88 / 105



M1 GO POS1 M1 GO POS2 M1 HOMMING M2 GO POS1

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	DQ	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3					



M2 GO POS2

M2 HOMMING

M3 GO POS1

M3 GO POS2

27.a

27.c



M3 HOMMING M4 GO POS1 M4 GO POS2 M4 HOMMING

27.b 27.d



M5 GO POS1 M5 GO POS2 M5 HOMMING

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija

Odgovoren	Dejan Rožič	13. 08. 2025
Preveril	Vodja projektive	
Mail	dejan.rozic@dafra-kt.si	
Verzija eplan	2024.0.3	

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

DQ

= LIN1
+ OMA1
/

0	1	2	3	4	5	6	7	8	9





27.d

28.a

0	1	2	3	4	5	6	7	8	9

0	1	2	3	4	5	6	7	8	9

28.a

29.a

0	1	2	3	4	5	6	7	8	9

4.9 / HBM_L+

5.9 / HBM_M

1.4 / HBM_PE

11.8 / 58186_X5

HBM_L+ / 29.b.0

HBM_M / 29.b.0

HBM_PE / 29.b.0

29.a.6 / 58186_X5_1

-29T1

X2 24V 0V DO1 DO2 DI1 DI2 0I Sync CxB X CxA PE

Spg.-vers. | Spg.-vers. / Digital Out GND | Digital Out 1 | Digital Out 2 | Digital In 1 | Digital In 2 | Digital In GND | ClipX-Bus B (RS485-) | ClipX-BUS GND | ClipX-Bus A (RS485+)

X1 1-8 ETHERNET — IP-Address: xxx.xxx.x.x

X6 1-8 P1 — IP-Address: xxx.xxx.x.x

X7 1-8 P2 — IP-Address: xxx.xxx.x.x

Profinet

SYS

RUN SF MS

ERR BF NS

Electrical voltage source

U

X3 AO AO_GND PE — Analog Out | Analog Out GND

X4 Pt100 TEDS S 4 1 2´ 2 3´ 3 PE AI I IN U IN — Measuring signal - | Measuring signal + | Sensor line - | Bridge supply voltage - | Sensor line + | Bridge supply voltage + | Outer shield | Cable shield

HBM ClipX BM40IE

M1_AQ+ / 6.a.1

M1_AQ- /

-29U2

24V 0V

-29X1:1 -29X1:2

-29X2:2 (I) X4 (AI_GND)

29.a.9 / 58186_X5_1

58186_X5_2 / 29.b.0

-29T2

X2 24V 0V DO1 DO2 DI1 DI2 0I Sync CxB X CxA PE

Spg.-vers. | Spg.-vers. / Digital Out GND | Digital Out 1 | Digital Out 2 | Digital In 1 | Digital In 2 | Digital In GND | ClipX-Bus B (RS485-) | ClipX-BUS GND | ClipX-Bus A (RS485+)

X1 2 ETHERNET — IP-Address: xxx.xxx.x.x

X6 2 P1 — IP-Address: xxx.xxx.x.x

X7 2 P2 — IP-Address: xxx.xxx.x.x

Profinet

SYS

RUN SF MS

ERR BF NS

Electrical voltage source

U

X3 AO AO_GND PE — Analog Out | Analog Out GND

X4 Pt100 TEDS S 4 1 2´ 2 3´ 3 PE AI I IN U IN — Measuring signal - | Measuring signal + | Sensor line - | Bridge supply voltage - | Sensor line + | Bridge supply voltage + | Outer shield | Cable shield

HBM ClipX BM40IE

M2_AQ+ /

M2_AQ- /

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	hbm	= LIN1
	Preveril	Vodja projektive				+ OMA1
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI	/	Page 29.a
	Verzija eplan	2024.0.3				Page 96 / 105

0	1	2	3	4	5	6	7	8	9

29.a.9 / HBM_L+
29.a.9 / HBM_M
29.a.9 / HBM_PE
29.a.9 / 58186_X5_2

HBM_L+ / 29.c.0
HBM_M / 29.c.0
HBM_PE / 29.c.0
58186_X5_3 / 29.b.6

-29T3

X2: 24V, 0V, DO1, DO2, DI1, DI2, 0I, Sync, CxB, X, CxA, PE
Spg.-vers., Spg.-vers. / Digital Out GND, Digital Out 1, Digital Out 2, Digital In 1, Digital In 2, Digital In GND, ClipX-Bus B (RS485-), ClipX-BUS GND, ClipX-Bus A (RS485+)

X1 2 ETHERNET — IP-Address: xxx.xxx.x.x
X6 2 P1 — IP-Address: xxx.xxx.x.x
X7 2 P2 — IP-Address: xxx.xxx.x.x
Profinet

SYS
RUN SF MS
ERR BF NS

Electrical voltage source
U

X3: AO, AO_GND, PE
Analog Out, Analog Out GND

X4: Pt100, TEDS, S, 4, 1, 2´, 2, 3´, 3, PE, AI, I IN, U IN
Measuring signal -, Measuring signal +, Sensor line -, Bridge supply voltage -, Sensor line +, Bridge supply voltage +, Outer shield, Cable shield

HBM
ClipX
BM40IE

M3_AQ+ /
M3_AQ-

29.b.9 / 58186_X5_3
58186_X5_4 / 29.c.0

-29T4

X2: 24V, 0V, DO1, DO2, DI1, DI2, 0I, Sync, CxB, X, CxA, PE
Spg.-vers., Spg.-vers. / Digital Out GND, Digital Out 1, Digital Out 2, Digital In 1, Digital In 2, Digital In GND, ClipX-Bus B (RS485-), ClipX-BUS GND, ClipX-Bus A (RS485+)

X1 2 ETHERNET — IP-Address: xxx.xxx.x.x
X6 2 P1 — IP-Address: xxx.xxx.x.x
X7 2 P2 — IP-Address: xxx.xxx.x.x
Profinet

SYS
RUN SF MS
ERR BF NS

Electrical voltage source
U

X3: AO, AO_GND, PE
Analog Out, Analog Out GND

X4: Pt100, TEDS, S, 4, 1, 2´, 2, 3´, 3, PE, AI, I IN, U IN
Measuring signal -, Measuring signal +, Sensor line -, Bridge supply voltage -, Sensor line +, Bridge supply voltage +, Outer shield, Cable shield

HBM
ClipX
BM40IE

M4_AQ+ /
M4_AQ-

29.a
29.c

29.b.9 / HBM_L+

29.b.9 / HBM_M

29.b.9 / HBM_PE

29.b.9 / 58186_X5_4

-29T5

X2: 24V (Spg.-vers.), 0V (Spg.-vers. / Digital Out GND), DO1 (Digital Out 1), DO2 (Digital Out 2), DI1 (Digital In 1), DI2 (Digital In 2), 0I (Digital In GND), Sync, CxB (ClipX-Bus B (RS485-)), X (ClipX-BUS GND), CxA (ClipX-Bus A (RS485+)), PE

X1 2 ETHERNET — IP-Address: xxx.xxx.x.x

X6 2 P1 — IP-Address: xxx.xxx.x.x

X7 2 P2 — IP-Address: xxx.xxx.x.x

Profinet

SYS

RUN SF MS

ERR BF NS

Electrical voltage source

U

X3: AO (Analog Out), AO_GND (Analog Out GND), PE

X4: Pt100, TEDS, S, 4 (Measuring signal -), 1 (Measuring signal +), 2´ (Sensor line -), 2 (Bridge supply voltage -), 3´ (Sensor line +), 3 (Bridge supply voltage +), PE (Outer shield), AI (Cable shield), I IN, U IN

HBM ClipX BM40IE

M5_AQ+ /

M5_AQ- /

inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	hbm	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/
	Verzija eplan	2024.0.3				Page	29.c
						Page	98 / 105



TEMP. ORODJA

TEMP. ORODJA

TEMP. OKOLICE

29.c

30.a

+FIELD



RTD1 RTD2 RTD3 RTD4

DAFRA Kontakt tehnologija (inovativno · zanesljivo · globalno)	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	RTD	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/	Page 30.a
	Verzija eplan	2024.0.3					Page 100 / 105



inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	PC & Router komunikacija	= LIN1	
	Preveril	Vodja projektive				+ OMA1	
	Mail	dejan.rozic@dafra-kt.si		08/2024| RRI		/ Page 31
	Verzija eplan	2024.0.3					Page 101 / 105

Enclosure legend

=LIN1+OMA1-32M2		
Item number	Device tag	Type number
1	1S1	P3-63/EA/SVB-SW/N
4	1H1	XB4BVM4
5	1H2	XB4BVM4
6	1H3	XB4BVM4
7	2M1	IUKNF1523A
8	11XF1	4000-73000-0010000
9	11XF2	4000-73000-0010000
10	31U3	









inovativno · zanesljivo · globalno DAFRA Kontakt tehnologija	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	OMARA1 - dimenzije ele. omare - WSA1008260		= LIN1
	Preveril	Vodja projektive		08/2024| RRI		+ OMA1
	Mail	dejan.rozic@dafra-kt.si				/	Page 32
	Verzija eplan	2024.0.3					Page 102 / 105



WSA1008260

DAFRA Kontakt tehnologija (inovativno · zanesljivo · globalno)	Odgovoren	Dejan Rožič	13. 08. 2025	DAFRA D.O.O., Egasi d.o.o.	OMARA1 - montažna plošča - WSA1008260	= LIN1	
	Preveril	Vodja projektive		08/2024| RRI		+ OMA1
	Mail	dejan.rozic@dafra-kt.si				/	Page 33
	Verzija eplan	2024.0.3					Page 103 / 105

Enclosure legend

=LIN1+OMA1-33M3		
Item number	Device tag	Type number
1	17A1	6ES7215-1AG40-0XB0
2	18A2	6ES7231-5QD32-0XB0
3	1F1	BM017310--
4	1F2	BM017302--
6	10FC1	9000-41068-0200600
8	26K8	TRS 24VDC 2CO
11	11KF1	8 port unmanaged switch
12	2Q1	BE501000--
14	3TB1	PRO ECO3 120W 24V 5A
15	1U1	UR6P3052
16	1X1	
17	2X2	
18	4X4	
19	5X5	
20	20X7	
22	21X8	
24	2S2	IUK08566--
28	6F9	BM017106--
29	6F10	BM017106--
30	3Q2	BE501000--
32	1K1	LC1-D 3P 38A
33	18A3	6ES7223-1BL32-0XB0
34	18A4	6ES7231-5PD32-0XB0
40	3K2	RSL1AB4BD
41	3K3	RSL1AB4BD
42	3K4	RSL1AB4BD
43	3K5	RSL1AB4BD
44	3K6	RSL1AB4BD
45	29T1	BM40IE
46	29T2	BM40IE
47	29T3	BM40IE
48	29T4	BM40IE
49	29T5	BM40IE
50	3TB2	PRO ECO 240W 48V 5A
51	3V1	TOS 24VDC/24VDC 4A
52	3V2	TOS 24VDC/24VDC 4A
53	3V3	TOS 24VDC/24VDC 4A
54	3V4	TOS 24VDC/24VDC 4A
55	3V5	TOS 24VDC/24VDC 4A
56	3X3	
57	6X6	
58	6XP1	BZ325003--
59	6XP4	BZ325003--
60	3F3	BM018104--

inovativno · zanesljivo · globalno
DAFRA Kontakt tehnologija
Odgovoren Dejan Rožič 13. 08. 2025
Preveril Vodja projektive
Mail dejan.rozic@dafra-kt.si
Verzija eplan 2024.0.3

DAFRA D.O.O., Egasi d.o.o.

08/2024| RRI

OMARA1 - montažna plošča - WSA1008260

= LIN1
+ OMA1
/

Enclosure legend

Item number	Device tag	Type number	Part number	Manufacturer	Function text
1	17A1	6ES7215-1AG40-0XB0	SIE.6ES7215-1AG40-0XB0	SIE	
2	18A2	6ES7231-5QD32-0XB0	SIE.6ES7231-5QD32-0XB0	SIE	
3	1F1	BM017310--	SCHR.BM017310--	SCHR	
4	1F2	BM017302--	SCHR.BM017302--	SCHR	
6	10FC1	9000-41068-0200600	MURR.9000-41068-0200600	MURR	
8	26K8	TRS 24VDC 2CO	WEI.1123490000	WEI	
11	11KF1	8 port unmanaged switch	MURR.58171	MURR	
12	2Q1	BE501000--	SCHR.BE501000--	SCHR	
14	3TB1	PRO ECO3 120W 24V 5A	WEI.1469530000	WEI	
15	1U1	UR6P3052	SCH.UR6P3052	SCHR	
16	1X1				
17	2X2				
18	4X4				
19	5X5				
20	12X13				
22	21X15				
24	2S2	IUK08566--	SCHR.IUK08566--	SCHR	Termostat 0-60
28	6F8	BM017106--	SCHR.BM017106--	SCHR	
29	6F9	BM017106--	SCHR.BM017106--	SCHR	
30	3Q2	BE501000--	SCHR.BE501000--	SCHR	
32	1K1	LC1-D 3P 38A	SE.LC1D38P7	SE	
33	18A3	6ES7223-1BL32-0XB0	SIE.6ES7223-1BL32-0XB0	SIE	
34	18A4	6ES7231-5PD32-0XB0	SIE.6ES7231-5PD32-0XB0	SIE	
40	3K2	RSL1AB4BD	SE.RSL1AB4BD	SE	POWER ENABLE M1
41	3K3	RSL1AB4BD	SE.RSL1AB4BD	SE	POWER ENABLE M2
42	3K4	RSL1AB4BD	SE.RSL1AB4BD	SE	POWER ENABLE M3
43	3K5	RSL1AB4BD	SE.RSL1AB4BD	SE	POWER ENABLE M4
44	3K6	RSL1AB4BD	SE.RSL1AB4BD	SE	POWER ENABLE M5
45	29T1	BM40IE	HBM.BM40IE	HBM	
46	29T2	BM40IE	HBM.BM40IE	HBM	
47	29T3	BM40IE	HBM.BM40IE	HBM	
48	29T4	BM40IE	HBM.BM40IE	HBM	
49	29T5	BM40IE	HBM.BM40IE	HBM	
50	3TB2	PRO ECO 240W 48V 5A	WEI.1469590000	WEI	
51	3V1	TOS 24VDC/24VDC 4A	WEI.1275100000	WEI	
52	3V2	TOS 24VDC/24VDC 4A	WEI.1275100000	WEI	
53	3V3	TOS 24VDC/24VDC 4A	WEI.1275100000	WEI	
54	3V4	TOS 24VDC/24VDC 4A	WEI.1275100000	WEI	
55	3V5	TOS 24VDC/24VDC 4A	WEI.1275100000	WEI	
56	3X3				
57	6X12				
58	6XP1	BZ325003--	SCHR.BZ325003--	SCHR	
59	6XP2	BZ325003--	SCHR.BZ325003--	SCHR	

=+

Properties

Trade	Electrical engineering

References

Multi-line	=+	=LIN1+OMA1/11.9

W2

Properties

Trade	Electrical engineering
Function text (automatic)	i_xSmallFeed
Cable type	PUR
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	0.34
Cable length with unit	5 m

Part properties

Parts: TUR.6625504 Variant: 1

Part type	Component
Order number	6625504
Designation 1	Actuator and Sensor Cable, PUR
Description	Actuator and Sensor Cable, PUR, Connection Cable, Female M12, straight, 4-pin, Cable length: 5.0 m, Sheath material: PUR, Sheath color: black, Qualified for drag chain use, Resistant to weld splatter, Resistant to chemicals, UV radiation and oils, Flame retardant, Free from halogen, silicone, PVC and LABS, Particularly resistant to abrasion, Approval: cULus, RoHS conform, Protection class IP67
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Multi-line	W2	=LIN1+OMA1/23.8

W3

Properties

Trade	Electrical engineering
Function text (automatic)	i_xShapeSensor_1
Cable type	PUR
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	0.34
Cable length with unit	5 m

Part properties

Parts: TUR.6625504 Variant: 1

Part type	Component
Order number	6625504
Designation 1	Actuator and Sensor Cable, PUR
Description	Actuator and Sensor Cable, PUR, Connection Cable, Female M12, straight, 4-pin, Cable length: 5.0 m, Sheath material: PUR, Sheath color: black, Qualified for drag chain use, Resistant to weld splatter, Resistant to chemicals, UV radiation and oils, Flame retardant, Free from halogen, silicone, PVC and LABS, Particularly resistant to abrasion, Approval: cULus, RoHS conform, Protection class IP67
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Multi-line	W3	=LIN1+OMA1/24.0

W4

Properties

Trade	Electrical engineering
Function text (automatic)	i_xShapeSensor_2
Cable type	PUR
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	0.34
Cable length with unit	5 m

Part properties

Parts: TUR.6625504 Variant: 1

Part type	Component
Order number	6625504
Designation 1	Actuator and Sensor Cable, PUR
Description	Actuator and Sensor Cable, PUR, Connection Cable, Female M12, straight, 4-pin, Cable length: 5.0 m, Sheath material: PUR, Sheath color: black, Qualified for drag chain use, Resistant to weld splatter, Resistant to chemicals, UV radiation and oils, Flame retardant, Free from halogen, silicone, PVC and LABS, Particularly resistant to abrasion, Approval: cULus, RoHS conform, Protection class IP67
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Multi-line	W4	=LIN1+OMA1/24.3

W5

Properties

Trade	Electrical engineering
Function text (automatic)	i_xDoubleFeed
Cable type	PUR
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	0.34
Cable length with unit	5 m

Part properties

Parts: TUR.6625504 Variant: 1

Part type	Component
Order number	6625504
Designation 1	Actuator and Sensor Cable, PUR
Description	Actuator and Sensor Cable, PUR, Connection Cable, Female M12, straight, 4-pin, Cable length: 5.0 m, Sheath material: PUR, Sheath color: black, Qualified for drag chain use, Resistant to weld splatter, Resistant to chemicals, UV radiation and oils, Flame retardant, Free from halogen, silicone, PVC and LABS, Particularly resistant to abrasion, Approval: cULus, RoHS conform, Protection class IP67
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Multi-line	W5	=LIN1+OMA1/23.5

6W1

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator cable M1
Cable type	UNITRONIC® LiYCY
Cable: No. of conductors	15
Cable: Conductor cross-section / diameter	0,34
Cable length with unit	5 m

Part properties

Parts: LAPP.0034515 Variant: 1

Part type	Component
Order number	0034515
Designation 1	Data communication systems
Designation 2	UNITRONIC LiYCY 15x0,34
Manufacturer	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	6W1	=LIN1+OMA1/6.a.1
	6W1	=LIN1+OMA1/6.a.1

6W2

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator cable M2
Cable type	UNITRONIC® LiYCY
Cable: No. of conductors	15
Cable: Conductor cross-section / diameter	0,34
Cable length with unit	5 m

Part properties

Parts: LAPP.0034515 Variant: 1

Part type	Component
Order number	0034515
Designation 1	Data communication systems
Designation 2	UNITRONIC LiYCY 15x0,34
Manufacturer	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	6W2	=LIN1+OMA1/6.a.4
	6W2	=LIN1+OMA1/6.a.4

6W3

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator cable M3
Cable type	UNITRONIC® LiYCY
Cable: No. of conductors	15
Cable: Conductor cross-section / diameter	0,34
Cable length with unit	5 m

Part properties

Parts: LAPP.0034515 Variant: 1

Part type	Component
Order number	0034515
Designation 1	Data communication systems
Designation 2	UNITRONIC LiYCY 15x0,34
Manufacturer	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	6W3	=LIN1+OMA1/6.b.1
	6W3	=LIN1+OMA1/6.b.1

6W4

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator cable M4
Cable type	UNITRONIC® LiYCY
Cable: No. of conductors	15
Cable: Conductor cross-section / diameter	0,34
Cable length with unit	5 m

Part properties

Parts: LAPP.0034515 Variant: 1

Part type	Component
Order number	0034515
Designation 1	Data communication systems
Designation 2	UNITRONIC LiYCY 15x0,34
Manufacturer	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	6W4	=LIN1+OMA1/6.b.4
	6W4	=LIN1+OMA1/6.b.4

6W5

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator cable M1
Cable type	UNITRONIC® LiYCY
Cable: No. of conductors	15
Cable: Conductor cross-section / diameter	0,34
Cable length with unit	5 m

Part properties

Parts: LAPP.0034515 Variant: 1

Part type	Component
Order number	0034515
Designation 1	Data communication systems
Designation 2	UNITRONIC LiYCY 15x0,34
Manufacturer	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	6W5	=LIN1+OMA1/6.c.1
	6W5	=LIN1+OMA1/6.c.1

11W6

Properties

Trade	Electrical engineering
Function text (automatic)	PLC KOMUNIKACIJA
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W6	=LIN1+OMA1/11.0

11W7

Properties

Trade	Electrical engineering
Function text (automatic)	NC
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W7	=LIN1+OMA1/11.2

11W8

Properties

Trade	Electrical engineering
Function text (automatic)	HMI KOMUNIKACIJA
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W8	=LIN1+OMA1/11.3

11W9

Properties

Trade	Electrical engineering
Function text (automatic)	NC
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W9	=LIN1+OMA1/11.4

11W10

Properties

Trade	Electrical engineering
Function text (automatic)	NC
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W10	=LIN1+OMA1/11.5

11W11

Properties

Trade	Electrical engineering
Function text (automatic)	FREKVENČNIK
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W11	=LIN1+OMA1/11.6

11W12

Properties

Trade	Electrical engineering
Function text (automatic)	NC
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W12	=LIN1+OMA1/11.7

11W13

Properties

Trade	Electrical engineering
Function text (automatic)	NC
Cable type	ETHERLINE® PN Cat.5e Y
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	22

Part properties

Parts: LAPP.2170891 Variant: 1

Part type	Component
Order number	2170891
Designation 1	Profinet 2pair cabling Cat.5/5e PVC fixed 2X2X22AWG
Description	Data Communication Systems For ETHERNET-Technology / Accessories for Industrial networking / LAN-cables for industrial cabling
Manufacturer	LAPP
Supplier	LAPP
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	11W13	=LIN1+OMA1/11.8

12W14

Properties

Trade	Electrical engineering
Function text (automatic)	Triger from PLC
Cable length with unit	5 m

Part properties

Parts: Variant:

Part type	Undefined

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	12W14	=LIN1+OMA1/12.0

12W15

Properties

Trade	Electrical engineering
Function text (automatic)	Feedback to Machine
Cable length with unit	5 m

Part properties

Parts: Variant:

Part type	Undefined

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	12W15	=LIN1+OMA1/12.1

12W16

Properties

Trade	Electrical engineering
Function text (automatic)	Reserve
Cable type	PUR
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	0.34
Cable length with unit	5 m

Part properties

Parts: TUR.6625504 Variant: 1

Part type	Component
Order number	6625504
Designation 1	Actuator and Sensor Cable, PUR
Description	Actuator and Sensor Cable, PUR, Connection Cable, Female M12, straight, 4-pin, Cable length: 5.0 m, Sheath material: PUR, Sheath color: black, Qualified for drag chain use, Resistant to weld splatter, Resistant to chemicals, UV radiation and oils, Flame retardant, Free from halogen, silicone, PVC and LABS, Particularly resistant to abrasion, Approval: cULus, RoHS conform, Protection class IP67
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Multi-line	12W16	=LIN1+OMA1/12.2

12W17

Properties

Trade	Electrical engineering
Function text (automatic)	Reserve
Cable type	PUR
Cable: No. of conductors	4
Cable: Conductor cross-section / diameter	0.34
Cable length with unit	5 m

Part properties

Parts: TUR.6625504 Variant: 1

Part type	Component
Order number	6625504
Designation 1	Actuator and Sensor Cable, PUR
Description	Actuator and Sensor Cable, PUR, Connection Cable, Female M12, straight, 4-pin, Cable length: 5.0 m, Sheath material: PUR, Sheath color: black, Qualified for drag chain use, Resistant to weld splatter, Resistant to chemicals, UV radiation and oils, Flame retardant, Free from halogen, silicone, PVC and LABS, Particularly resistant to abrasion, Approval: cULus, RoHS conform, Protection class IP67
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Multi-line	12W17	=LIN1+OMA1/12.3

20W18

Properties

Trade	Electrical engineering
Cable: No. of conductors	7G
Cable: Conductor cross-section / diameter	0,5

Part properties

Parts: 7G075 Variant: 1

Part type	Component
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	20W18	=LIN1+OMA1/20.5

30W23

Properties

Trade	Electrical engineering
Function text (automatic)	RTD1
Cable type	SAC-5P- 5,0-PUR/M12FS

Part properties

Parts: PXC.1669848 Variant: 1

Part type	Component
Order number	1669848
Designation 1	Sensor/actuator cable
Description	Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 5 m
Manufacturer	Phoenix Contact
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,18 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	30W23	=LIN1+OMA1/30.a.0

30W24

Properties

Trade	Electrical engineering
Function text (automatic)	RTD2
Cable type	SAC-5P- 5,0-PUR/M12FS

Part properties

Parts: PXC.1669848 Variant: 1

Part type	Component
Order number	1669848
Designation 1	Sensor/actuator cable
Description	Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 5 m
Manufacturer	Phoenix Contact
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,18 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	30W24	=LIN1+OMA1/30.a.3

30W25

Properties

Trade	Electrical engineering
Function text (automatic)	RTD3
Cable type	SAC-5P- 5,0-PUR/M12FS

Part properties

Parts: PXC.1669848 Variant: 1

Part type	Component
Order number	1669848
Designation 1	Sensor/actuator cable
Description	Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 5 m
Manufacturer	Phoenix Contact
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,18 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	30W25	=LIN1+OMA1/30.a.5

30W26

Properties

Trade	Electrical engineering
Function text (automatic)	RTD4
Cable type	SAC-5P- 5,0-PUR/M12FS

Part properties

Parts: PXC.1669848 Variant: 1

Part type	Component
Order number	1669848
Designation 1	Sensor/actuator cable
Description	Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 5 m
Manufacturer	Phoenix Contact
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,18 kg

References

Cable diagram	Cable diagram	
Cable overview	Cable overview	
Multi-line	30W26	=LIN1+OMA1/30.a.8

=LIN1+OMA1-17A1

Properties

Trade	Electrical engineering

Part properties

Parts: SIE.6ES7215-1AG40-0XB0 Variant: 1

Part type	Component
Order number	6ES7215-1AG40-0XB0
Designation 1	CPU 1215C, DC/DC/DC, 14DI/10DO/2AI/2AO
Designation 2	SIMATIC, S7-1200
Designation 3	Central processing unit
Description	SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/DC, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC/ 10 DO 24 V DC/ 0.5A/ 2 AI 0-10 V DC, 2 AO 0-20 mA DC, Power supply: DC 20.4-28.8V DC, Program/data memory 125 KB
Manufacturer	Siemens
Supplier	Siemens
Height	100,00 mm
Width	130,00 mm
Depth	75,00 mm
Weight	0,45 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Overview	=LIN1+OMA1-17A1	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1	=LIN1+OMA1/19.2
Single-line	=LIN1+OMA1-17A1	=LIN1+OMA1/14.1
Multi-line	=LIN1+OMA1-17A1:1	=LIN1+OMA1/19.2
Overview	=LIN1+OMA1-17A1:1	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:2	=LIN1+OMA1/19.2
Overview	=LIN1+OMA1-17A1:2	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:3	=LIN1+OMA1/19.2
Overview	=LIN1+OMA1-17A1:3	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:4	=LIN1+OMA1/19.3
Overview	=LIN1+OMA1-17A1:4	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:5	=LIN1+OMA1/19.3
Overview	=LIN1+OMA1-17A1:5	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:6	=LIN1+OMA1/19.3
Overview	=LIN1+OMA1-17A1:6	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:7	=LIN1+OMA1/21.1
Overview	=LIN1+OMA1-17A1:7	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:8	=LIN1+OMA1/21.3
Overview	=LIN1+OMA1-17A1:8	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:9	=LIN1+OMA1/21.5
Overview	=LIN1+OMA1-17A1:9	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:10	=LIN1+OMA1/21.8
Overview	=LIN1+OMA1-17A1:10	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:11	=LIN1+OMA1/22.1

=LIN1+OMA1-17A1

Overview	=LIN1+OMA1-17A1:11	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:12	=LIN1+OMA1/22.3
Overview	=LIN1+OMA1-17A1:12	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:13	=LIN1+OMA1/22.5
Overview	=LIN1+OMA1-17A1:13	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:14	=LIN1+OMA1/22.8
Overview	=LIN1+OMA1-17A1:14	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:15	=LIN1+OMA1/23.1
Overview	=LIN1+OMA1-17A1:15	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:16	=LIN1+OMA1/23.3
Overview	=LIN1+OMA1-17A1:16	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:17	=LIN1+OMA1/23.5
Overview	=LIN1+OMA1-17A1:17	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:18	=LIN1+OMA1/23.8
Overview	=LIN1+OMA1-17A1:18	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:19	=LIN1+OMA1/24.1
Overview	=LIN1+OMA1-17A1:19	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:20	=LIN1+OMA1/24.3
Overview	=LIN1+OMA1-17A1:20	=LIN1+OMA1/17.4
Multi-line	=LIN1+OMA1-17A1:1	=LIN1+OMA1/19.4
Overview	=LIN1+OMA1-17A1:1	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:2	=LIN1+OMA1/28.2
Overview	=LIN1+OMA1-17A1:2	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:3	=LIN1+OMA1/28.5
Overview	=LIN1+OMA1-17A1:3	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:4	=LIN1+OMA1/19.4
Overview	=LIN1+OMA1-17A1:4	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:5	=LIN1+OMA1/29.2
Overview	=LIN1+OMA1-17A1:5	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:6	=LIN1+OMA1/29.5
Overview	=LIN1+OMA1-17A1:6	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:1	=LIN1+OMA1/19.4
Overview	=LIN1+OMA1-17A1:1	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:2	=LIN1+OMA1/19.4
Overview	=LIN1+OMA1-17A1:2	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:3	=LIN1+OMA1/25.1
Overview	=LIN1+OMA1-17A1:3	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:4	=LIN1+OMA1/25.3
Overview	=LIN1+OMA1-17A1:4	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:5	=LIN1+OMA1/25.5
Overview	=LIN1+OMA1-17A1:5	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:6	=LIN1+OMA1/25.8
Overview	=LIN1+OMA1-17A1:6	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:7	=LIN1+OMA1/26.1
Overview	=LIN1+OMA1-17A1:7	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:8	=LIN1+OMA1/26.3
Overview	=LIN1+OMA1-17A1:8	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:9	=LIN1+OMA1/26.5

=LIN1+OMA1-17A1

Overview	=LIN1+OMA1-17A1:9	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:10	=LIN1+OMA1/26.8
Overview	=LIN1+OMA1-17A1:10	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:11	=LIN1+OMA1/27.1
Overview	=LIN1+OMA1-17A1:11	=LIN1+OMA1/17.6
Multi-line	=LIN1+OMA1-17A1:12	=LIN1+OMA1/27.3
Overview	=LIN1+OMA1-17A1:12	=LIN1+OMA1/17.6
	=LIN1+OMA1-17A1	=LIN1+OMA1/17.6
Single-line	=LIN1+OMA1-17A1	=LIN1+OMA1/14.2
Overview	=LIN1+OMA1-17A1	=LIN1+OMA1/17.6
Single-line	=LIN1+OMA1-17A1	=LIN1+OMA1/14.3
Panel layout	=LIN1+OMA1-17A1	=LIN1+OMA1/33.0

=LIN1+OMA1-18A2

Properties

Trade	Electrical engineering

Part properties

Parts: SIE.6ES7231-5QD32-0XB0 Variant: 1

Part type	Component
Order number	6ES7231-5QD32-0XB0
Designation 1	S7-1200, ANALOG INPUT SM 1231 TC, 4 AI
Designation 2	SIMATIC, S7-1200
Description	SIMATIC S7-1200, Analog input, SM 1231 TC, 4 AI thermocouples
Manufacturer	Siemens
Height	100,00 mm
Width	45,00 mm
Depth	75,00 mm
Weight	0,17 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Overview	=LIN1+OMA1-18A2	=LIN1+OMA1/18.0
Multi-line	=LIN1+OMA1-18A2	=LIN1+OMA1/19.5
	=LIN1+OMA1-18A2:1	=LIN1+OMA1/19.5
Overview	=LIN1+OMA1-18A2:1	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:2	=LIN1+OMA1/19.6
Overview	=LIN1+OMA1-18A2:2	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:3	=LIN1+OMA1/19.6
Overview	=LIN1+OMA1-18A2:3	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:4	=LIN1+OMA1/30.1
Overview	=LIN1+OMA1-18A2:4	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:5	=LIN1+OMA1/30.1
Overview	=LIN1+OMA1-18A2:5	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:6	=LIN1+OMA1/30.3
Overview	=LIN1+OMA1-18A2:6	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:7	=LIN1+OMA1/30.3
Overview	=LIN1+OMA1-18A2:7	=LIN1+OMA1/18.1
	=LIN1+OMA1-18A2:1	=LIN1+OMA1/18.1
	=LIN1+OMA1-18A2:2	=LIN1+OMA1/18.1
	=LIN1+OMA1-18A2:3	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:4	=LIN1+OMA1/30.5
Overview	=LIN1+OMA1-18A2:4	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:5	=LIN1+OMA1/30.5
Overview	=LIN1+OMA1-18A2:5	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:6	=LIN1+OMA1/30.7
Overview	=LIN1+OMA1-18A2:6	=LIN1+OMA1/18.1
Multi-line	=LIN1+OMA1-18A2:7	=LIN1+OMA1/30.7
Overview	=LIN1+OMA1-18A2:7	=LIN1+OMA1/18.1
Panel layout	=LIN1+OMA1-18A2	=LIN1+OMA1/33.1

=LIN1+OMA1-18A3

Properties

Trade	Electrical engineering

Part properties

Parts: SIE.6ES7223-1BL32-0XB0 Variant: 1

Part type	Component
Order number	6ES7223-1BL32-0XB0
Designation 1	DIGITAL I/O SM 1223, 16DI/16DO
Designation 2	SIMATIC, S7-1200
Designation 3	Digital module input/output
Description	SIMATIC S7-1200, Digital I/O SM 1223, 16 DI/16 DO, 16 DI 24 V DC, Sink/Source, 16 DO, transistor 0.5 A
Manufacturer	Siemens
Supplier	Siemens
Height	100,00 mm
Width	70,00 mm
Depth	75,00 mm
Weight	0,31 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Overview	=LIN1+OMA1-18A3	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3	=LIN1+OMA1/19.7
	=LIN1+OMA1-18A3:1	=LIN1+OMA1/19.8
Overview	=LIN1+OMA1-18A3:1	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:2	=LIN1+OMA1/19.8
Overview	=LIN1+OMA1-18A3:2	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:3	=LIN1+OMA1/19.8
Overview	=LIN1+OMA1-18A3:3	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:4	=LIN1+OMA1/24.b.1
Overview	=LIN1+OMA1-18A3:4	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:5	=LIN1+OMA1/24.b.3
Overview	=LIN1+OMA1-18A3:5	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:6	=LIN1+OMA1/24.b.5
Overview	=LIN1+OMA1-18A3:6	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:7	=LIN1+OMA1/24.b.8
Overview	=LIN1+OMA1-18A3:7	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:8	=LIN1+OMA1/24.c.1
Overview	=LIN1+OMA1-18A3:8	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:9	=LIN1+OMA1/24.c.3
Overview	=LIN1+OMA1-18A3:9	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:10	=LIN1+OMA1/24.c.5
Overview	=LIN1+OMA1-18A3:10	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:11	=LIN1+OMA1/24.c.8
Overview	=LIN1+OMA1-18A3:11	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:1	=LIN1+OMA1/19.8
Overview	=LIN1+OMA1-18A3:1	=LIN1+OMA1/18.a.3

=LIN1+OMA1-18A3

Multi-line	=LIN1+OMA1-18A3:3	=LIN1+OMA1/19.8
Overview	=LIN1+OMA1-18A3:3	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:4	=LIN1+OMA1/24.d.1
Overview	=LIN1+OMA1-18A3:4	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:5	=LIN1+OMA1/24.d.3
Overview	=LIN1+OMA1-18A3:5	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:6	=LIN1+OMA1/24.d.5
Overview	=LIN1+OMA1-18A3:6	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:7	=LIN1+OMA1/24.d.8
Overview	=LIN1+OMA1-18A3:7	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:8	=LIN1+OMA1/24.e.1
Overview	=LIN1+OMA1-18A3:8	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:9	=LIN1+OMA1/24.e.3
Overview	=LIN1+OMA1-18A3:9	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:10	=LIN1+OMA1/24.e.5
Overview	=LIN1+OMA1-18A3:10	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:11	=LIN1+OMA1/24.e.8
Overview	=LIN1+OMA1-18A3:11	=LIN1+OMA1/18.a.3
Multi-line	=LIN1+OMA1-18A3:4	=LIN1+OMA1/27.a.1
Overview	=LIN1+OMA1-18A3:4	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:5	=LIN1+OMA1/27.a.3
Overview	=LIN1+OMA1-18A3:5	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:6	=LIN1+OMA1/27.a.5
Overview	=LIN1+OMA1-18A3:6	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:7	=LIN1+OMA1/27.a.8
Overview	=LIN1+OMA1-18A3:7	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:8	=LIN1+OMA1/27.b.1
Overview	=LIN1+OMA1-18A3:8	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:9	=LIN1+OMA1/27.b.3
Overview	=LIN1+OMA1-18A3:9	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:10	=LIN1+OMA1/27.b.6
Overview	=LIN1+OMA1-18A3:10	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:11	=LIN1+OMA1/27.b.8
Overview	=LIN1+OMA1-18A3:11	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:4	=LIN1+OMA1/27.c.1
Overview	=LIN1+OMA1-18A3:4	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:5	=LIN1+OMA1/27.c.3
Overview	=LIN1+OMA1-18A3:5	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:6	=LIN1+OMA1/27.c.6
Overview	=LIN1+OMA1-18A3:6	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:7	=LIN1+OMA1/27.c.8
Overview	=LIN1+OMA1-18A3:7	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:8	=LIN1+OMA1/27.d.1
Overview	=LIN1+OMA1-18A3:8	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:9	=LIN1+OMA1/27.d.3
Overview	=LIN1+OMA1-18A3:9	=LIN1+OMA1/18.a.5
Multi-line	=LIN1+OMA1-18A3:10	=LIN1+OMA1/27.d.6
Overview	=LIN1+OMA1-18A3:10	=LIN1+OMA1/18.a.5

=LIN1+OMA1-18A3

Multi-line	=LIN1+OMA1-18A3:11	=LIN1+OMA1/27.d.8
Overview	=LIN1+OMA1-18A3:11	=LIN1+OMA1/18.a.5
Panel layout	=LIN1+OMA1-18A3	=LIN1+OMA1/33.2

=LIN1+OMA1-18A4

Properties

Trade	Electrical engineering

Part properties

Parts: SIE.6ES7231-5PD32-0XB0 Variant: 1

Part type	Component
Order number	6ES7231-5PD32-0XB0
Designation 1	S7-1200, ANALOG INPUT SM 1231 RTD, 4 AI
Designation 2	SIMATIC, S7-1200
Designation 3	Analog module input
Description	SIMATIC S7-1200, Analog input, SM 1231 RTD, 4xAI RTD m odule
Manufacturer	Siemens
Supplier	Siemens
Height	100,00 mm
Width	45,00 mm
Depth	75,00 mm
Weight	0,21 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Overview	=LIN1+OMA1-18A4	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4	=LIN1+OMA1/19.6
	=LIN1+OMA1-18A4:1	=LIN1+OMA1/19.6
Overview	=LIN1+OMA1-18A4:1	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:2	=LIN1+OMA1/19.7
Overview	=LIN1+OMA1-18A4:2	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:3	=LIN1+OMA1/19.7
Overview	=LIN1+OMA1-18A4:3	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:4	=LIN1+OMA1/30.a.1
Overview	=LIN1+OMA1-18A4:4	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:5	=LIN1+OMA1/30.a.1
Overview	=LIN1+OMA1-18A4:5	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:6	=LIN1+OMA1/30.a.1
Overview	=LIN1+OMA1-18A4:6	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:7	=LIN1+OMA1/30.a.1
Overview	=LIN1+OMA1-18A4:7	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:4	=LIN1+OMA1/30.a.4
Overview	=LIN1+OMA1-18A4:4	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:5	=LIN1+OMA1/30.a.3
Overview	=LIN1+OMA1-18A4:5	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:6	=LIN1+OMA1/30.a.4
Overview	=LIN1+OMA1-18A4:6	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:7	=LIN1+OMA1/30.a.4
Overview	=LIN1+OMA1-18A4:7	=LIN1+OMA1/18.b.1
Multi-line	=LIN1+OMA1-18A4:4	=LIN1+OMA1/30.a.6
Overview	=LIN1+OMA1-18A4:4	=LIN1+OMA1/18.b.4

=LIN1+OMA1-18A4

Multi-line	=LIN1+OMA1-18A4:5	=LIN1+OMA1/30.a.6
Overview	=LIN1+OMA1-18A4:5	=LIN1+OMA1/18.b.4
Multi-line	=LIN1+OMA1-18A4:6	=LIN1+OMA1/30.a.6
Overview	=LIN1+OMA1-18A4:6	=LIN1+OMA1/18.b.4
Multi-line	=LIN1+OMA1-18A4:7	=LIN1+OMA1/30.a.6
Overview	=LIN1+OMA1-18A4:7	=LIN1+OMA1/18.b.4
Multi-line	=LIN1+OMA1-18A4:4	=LIN1+OMA1/30.a.9
Overview	=LIN1+OMA1-18A4:4	=LIN1+OMA1/18.b.4
Multi-line	=LIN1+OMA1-18A4:5	=LIN1+OMA1/30.a.8
Overview	=LIN1+OMA1-18A4:5	=LIN1+OMA1/18.b.4
Multi-line	=LIN1+OMA1-18A4:6	=LIN1+OMA1/30.a.8
Overview	=LIN1+OMA1-18A4:6	=LIN1+OMA1/18.b.4
Multi-line	=LIN1+OMA1-18A4:7	=LIN1+OMA1/30.a.9
Overview	=LIN1+OMA1-18A4:7	=LIN1+OMA1/18.b.4
Panel layout	=LIN1+OMA1-18A4	=LIN1+OMA1/33.1

=LIN1+OMA1-23B2

Properties

Trade	Electrical engineering
Function text (automatic)	i_xSmallFeed

Part properties

Parts: Variant:

Part type	Undefined

References

Multi-line	=LIN1+OMA1-23B2:1;3;2	=LIN1+OMA1/23.8

=LIN1+OMA1-23B3

Properties

Trade	Electrical engineering
Function text (automatic)	i_xDoubleFeed

Part properties

Parts: Variant:

Part type	Undefined

References

Multi-line	=LIN1+OMA1-23B3:1;3;2	=LIN1+OMA1/23.5

=LIN1+OMA1-24B1

Properties	
Trade	Electrical engineering
Function text (automatic)	i_xShapeSensor_1

Part properties	
Parts:	Variant:
Part type	Undefined

References		
Multi-line	=LIN1+OMA1-24B1:1;3;2	=LIN1+OMA1/24.1

=LIN1+OMA1-24B2

Properties	
Trade	Electrical engineering
Function text (automatic)	i_xShapeSensor_2

Part properties	
Parts:	Variant:
Part type	Undefined

References		
Multi-line	=LIN1+OMA1-24B2:1;3;2	=LIN1+OMA1/24.3

=LIN1+OMA1-1F1

Properties

Trade	Electrical engineering
Technical characteristics	C10

Part properties

Parts: SCHR.BM017310-- Variant: 1

Part type	Component
Order number	BM017310--
Designation 1	Inštalacijski odklopnik, karak. C, 10A, 10kA, 3-polni
Description	Inštalacijski odklopnik, karak. C, 10A, 10kA, 3-polni serija B MS0, standard za izdelek EN 60898,EN 60947-2
Manufacturer	Schrack
Supplier	Schrack
Height	80,00 mm
Width	53,10 mm
Depth	74,90 mm
Weight	0,37 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1F1:2;1;4;3;6;5	=LIN1+OMA1/1.1
Panel layout	=LIN1+OMA1-1F1	=LIN1+OMA1/33.0

=LIN1+OMA1-1F2

Properties

Trade	Electrical engineering
Technical characteristics	C2

Part properties

Parts: SCHR.BM017302-- Variant: 1

Part type	Component
Order number	BM017302--
Designation 1	Inštalacijski odklopnik, karak. C, 2A, 3-polni, 10kA
Description	Inštalacijski odklopnik, karak. C, 2A, 3-polni, 10kA serija BM S0, standard za izdelek EN 60898,EN 60947-2
Manufacturer	Schrack
Supplier	Schrack
Height	80,00 mm
Width	53,10 mm
Depth	74,90 mm
Weight	0,37 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1F2:2;1;4;3;6;5	=LIN1+OMA1/1.3
Panel layout	=LIN1+OMA1-1F2	=LIN1+OMA1/33.1

=LIN1+OMA1-3F3

Properties

Trade	Electrical engineering
Technical characteristics	B4

Part properties

Parts: SCHR.BM018104-- Variant: 1

Part type	Component
Order number	BM018104--
Designation 1	Inštalacijski odklopnik, karak. B, 4A, 1-polni, 10kA
Description	Inštalacijski odklopnik, karak. B, 4A, 1-polni, 10kA serija BM S0, standard za izdelek EN 60898,EN 60947-2
Manufacturer	Schrack
Supplier	Schrack
Height	80,00 mm
Width	17,70 mm
Depth	74,90 mm
Weight	0,12 kg

References

Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3F3:1;2	=LIN1+OMA1/3.a.1
Panel layout	=LIN1+OMA1-3F3	=LIN1+OMA1/33.1

=LIN1+OMA1-3F9

Properties

Trade	Electrical engineering

Part properties

Parts: LUETZE.716406 Variant: 1

Part type	Undefined

References

Multi-line	=LIN1+OMA1-3F9	=LIN1+OMA1/3.c.0
	=LIN1+OMA1-3F9:1	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3F9:2	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3F9:3	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3F9:4	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3F9:5	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3F9:6	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3F9:7	=LIN1+OMA1/3.c.1
Panel layout	=LIN1+OMA1-3F9	=LIN1+OMA1/33.3

=LIN1+OMA1-3F10

Properties

Trade	Electrical engineering

Part properties

Parts: LUETZE.716406 Variant: 1

Part type	Undefined

References

Multi-line	=LIN1+OMA1-3F10	=LIN1+OMA1/3.c.2
	=LIN1+OMA1-3F10:1	=LIN1+OMA1/3.c.2
	=LIN1+OMA1-3F10:2	=LIN1+OMA1/3.c.3
	=LIN1+OMA1-3F10:3	=LIN1+OMA1/3.c.3
	=LIN1+OMA1-3F10:4	=LIN1+OMA1/3.c.3
	=LIN1+OMA1-3F10:5	=LIN1+OMA1/3.c.3
	=LIN1+OMA1-3F10:6	=LIN1+OMA1/3.c.2
	=LIN1+OMA1-3F10:7	=LIN1+OMA1/3.c.2
Panel layout	=LIN1+OMA1-3F10	=LIN1+OMA1/33.3

=LIN1+OMA1-3F11

Properties

Trade	Electrical engineering

Part properties

Parts: LUETZE.716406 Variant: 1

Part type	Undefined

References

Multi-line	=LIN1+OMA1-3F11	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3F11:1	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3F11:2	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3F11:3	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3F11:4	=LIN1+OMA1/3.c.5
	=LIN1+OMA1-3F11:5	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3F11:6	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3F11:7	=LIN1+OMA1/3.c.4
Panel layout	=LIN1+OMA1-3F11	=LIN1+OMA1/33.3

=LIN1+OMA1-3F12

Properties

Trade	Electrical engineering

Part properties

Parts: LUETZE.716406 Variant: 1

Part type	Undefined

References

Multi-line	=LIN1+OMA1-3F12	=LIN1+OMA1/3.c.5
	=LIN1+OMA1-3F12:1	=LIN1+OMA1/3.c.5
	=LIN1+OMA1-3F12:2	=LIN1+OMA1/3.c.6
	=LIN1+OMA1-3F12:3	=LIN1+OMA1/3.c.6
	=LIN1+OMA1-3F12:4	=LIN1+OMA1/3.c.6
	=LIN1+OMA1-3F12:5	=LIN1+OMA1/3.c.6
	=LIN1+OMA1-3F12:6	=LIN1+OMA1/3.c.6
	=LIN1+OMA1-3F12:7	=LIN1+OMA1/3.c.5
Panel layout	=LIN1+OMA1-3F12	=LIN1+OMA1/33.3

=LIN1+OMA1-3F13

Properties

Trade	Electrical engineering

Part properties

Parts: LUETZE.716406 Variant: 1

Part type	Undefined

References

Multi-line	=LIN1+OMA1-3F13	=LIN1+OMA1/3.c.7
	=LIN1+OMA1-3F13:1	=LIN1+OMA1/3.c.7
	=LIN1+OMA1-3F13:2	=LIN1+OMA1/3.c.8
	=LIN1+OMA1-3F13:3	=LIN1+OMA1/3.c.8
	=LIN1+OMA1-3F13:4	=LIN1+OMA1/3.c.8
	=LIN1+OMA1-3F13:5	=LIN1+OMA1/3.c.8
	=LIN1+OMA1-3F13:6	=LIN1+OMA1/3.c.7
	=LIN1+OMA1-3F13:7	=LIN1+OMA1/3.c.7
Panel layout	=LIN1+OMA1-3F13	=LIN1+OMA1/33.3

=LIN1+OMA1-6F9

Properties

Trade	Electrical engineering

Part properties

Parts: SCHR.BM017106-- Variant: 1

Part type	Component
Order number	BM017106--
Designation 1	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA
Description	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA serija BM S0, standard za izdelek EN 60898,EN 60947-2
Manufacturer	Schrack
Height	80,00 mm
Width	17,70 mm
Depth	74,90 mm
Weight	0,12 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-6F9:1;2	=LIN1+OMA1/6.1
Panel layout	=LIN1+OMA1-6F9	=LIN1+OMA1/33.1

=LIN1+OMA1-6F10

Properties

Trade	Electrical engineering

Part properties

Parts: SCHR.BM017106-- Variant: 1

Part type	Component
Order number	BM017106--
Designation 1	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA
Description	Inštalacijski odklopnik, karak. C, 6A, 1-polni, 10kA serija BM S0, standard za izdelek EN 60898,EN 60947-2
Manufacturer	Schrack
Height	80,00 mm
Width	17,70 mm
Depth	74,90 mm
Weight	0,12 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-6F10:1;2	=LIN1+OMA1/6.2
Panel layout	=LIN1+OMA1-6F10	=LIN1+OMA1/33.1

=LIN1+OMA1-10FC1

Properties

Trade	Electrical engineering
Technical characteristics	IN: 24 V DC OUT: 24 V DC / 5x2 A , 3x6 A

Part properties

Parts: MURR.9000-41068-0200600 Variant: 1

Part type	Component
Order number	9000-41068-0200600
Designation 1	Current monitoring equipment
Designation 2	MICO BASIC 5.2/3.6 ELEC AUX CIRCUIT, 8 CHANNELS (IN: 24VDC OUT: 5x24V/2ADC 3x24V/6ADC)
Description	MICO BASIC 5.2/3.6 8 channels Current adjustment 5× 2 A; 3× 6 A More information may be found on https://www.murrelektronik.com or in the technical datasheet
Height	90,00 mm
Width	70,00 mm
Depth	80,00 mm
Weight	0,16 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-10FC1	=LIN1+OMA1/10.1
	=LIN1+OMA1-10FC1:14	=LIN1+OMA1/10.3
	=LIN1+OMA1-10FC1:ON	=LIN1+OMA1/10.2
	=LIN1+OMA1-10FC1:OUT1	=LIN1+OMA1/10.2
	=LIN1+OMA1-10FC1:OUT2	=LIN1+OMA1/10.3
	=LIN1+OMA1-10FC1:OUT3	=LIN1+OMA1/10.3
	=LIN1+OMA1-10FC1:OUT4	=LIN1+OMA1/10.4
	=LIN1+OMA1-10FC1:OUT5	=LIN1+OMA1/10.4
	=LIN1+OMA1-10FC1:OUT6	=LIN1+OMA1/10.5
	=LIN1+OMA1-10FC1:OUT7	=LIN1+OMA1/10.5
	=LIN1+OMA1-10FC1:OUT8	=LIN1+OMA1/10.6
	=LIN1+OMA1-10FC1:+24V	=LIN1+OMA1/10.2
	=LIN1+OMA1-10FC1:GND	=LIN1+OMA1/10.2
Panel layout	=LIN1+OMA1-10FC1	=LIN1+OMA1/33.3

=LIN1+OMA1-1H1

Properties

Trade	Electrical engineering
Technical characteristics	L1

Part properties

Parts: SE.XB4BVM4 Variant: 1

Part type	Component
Order number	XB4BVM4
Designation 1	Red complete pilot light Ø22 plain lens with integral LED 230. ..240V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	47,00 mm
Width	30,00 mm
Depth	54,00 mm
Weight	0,08 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1H1:X1;X2	=LIN1+OMA1/1.2
Panel layout	=LIN1+OMA1-1H1	=LIN1+OMA1/32.7

=LIN1+OMA1-1H2

Properties

Trade	Electrical engineering
Technical characteristics	L2

Part properties

Parts: SE.XB4BVM4 Variant: 1

Part type	Component
Order number	XB4BVM4
Designation 1	Red complete pilot light Ø22 plain lens with integral LED 230. ..240V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	47,00 mm
Width	30,00 mm
Depth	54,00 mm
Weight	0,08 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1H2:X1;X2	=LIN1+OMA1/1.2
Panel layout	=LIN1+OMA1-1H2	=LIN1+OMA1/32.7

=LIN1+OMA1-1H3

Properties

Trade	Electrical engineering
Technical characteristics	L3

Part properties

Parts: SE.XB4BVM4 Variant: 1

Part type	Component
Order number	XB4BVM4
Designation 1	Red complete pilot light Ø22 plain lens with integral LED 230. ..240V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	47,00 mm
Width	30,00 mm
Depth	54,00 mm
Weight	0,08 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1H3:X1;X2	=LIN1+OMA1/1.3
Panel layout	=LIN1+OMA1-1H3	=LIN1+OMA1/32.7

=LIN1+OMA1-1K1

Properties

Trade	Electrical engineering
Technical characteristics	230VAC

Part properties

Parts: SE.LC1D38P7 Variant: 1

Part type	Component
Order number	LC1D38P7
Designation 1	Contactor TeSys LC1-D - 3P - AC-3 440V 38 A, Coil 230 V AC
Designation 2	Coil 230 V AC
Description	Contactor TeSys LC1-D - 3P - AC-3 440V 38 A, Coil 230 V AC
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	85,00 mm
Width	45,00 mm
Depth	90,00 mm
Weight	0,38 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1K1:A1;A2	=LIN1+OMA1/1.7
	=LIN1+OMA1-1K1:1/L1;2/T1	=LIN1+OMA1/1.7
	=LIN1+OMA1-1K1:3/L2;4/T2	=LIN1+OMA1/1.7
	=LIN1+OMA1-1K1:5/L3;6/T3	=LIN1+OMA1/1.8
Panel layout	=LIN1+OMA1-1K1	=LIN1+OMA1/33.2

=LIN1+OMA1-3K2

Properties

Trade	Electrical engineering
Function text (automatic)	POWER ENABLE M1
Technical characteristics	24 VDC

Part properties

Parts: SE.RSL1AB4BD Variant: 1

Part type	Component
Order number	RSL1AB4BD
Designation 1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Description	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	28,00 mm
Width	5,00 mm
Depth	18,50 mm
Weight	0,01 kg

Parts: SE.RSLZVA1 Variant: 1

Part type	Component
Order number	RSLZVA1
Designation 1	Screw socket equipped with LED and protection circuit, 12-24 V
Description	Screw socket equipped with LED and protection circuit, 12-24 V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	78,60 mm
Width	6,20 mm
Depth	101,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3K2:A1;A2	=LIN1+OMA1/3.b.4
	=LIN1+OMA1-3K2:13;14	=LIN1+OMA1/3.b.1
Panel layout	=LIN1+OMA1-3K2	=LIN1+OMA1/33.4

=LIN1+OMA1-3K3

Properties

Trade	Electrical engineering
Function text (automatic)	POWER ENABLE M2
Technical characteristics	24 VDC

Part properties

Parts: SE.RSL1AB4BD Variant: 1

Part type	Component
Order number	RSL1AB4BD
Designation 1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Description	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	28,00 mm
Width	5,00 mm
Depth	18,50 mm
Weight	0,01 kg

Parts: SE.RSLZVA1 Variant: 1

Part type	Component
Order number	RSLZVA1
Designation 1	Screw socket equipped with LED and protection circuit, 12-24 V
Description	Screw socket equipped with LED and protection circuit, 12-24 V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	78,60 mm
Width	6,20 mm
Depth	101,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3K3:A1;A2	=LIN1+OMA1/3.b.5
	=LIN1+OMA1-3K3:13;14	=LIN1+OMA1/3.b.1
Panel layout	=LIN1+OMA1-3K3	=LIN1+OMA1/33.4

=LIN1+OMA1-3K4

Properties

Trade	Electrical engineering
Function text (automatic)	POWER ENABLE M3
Technical characteristics	24 VDC

Part properties

Parts: SE.RSL1AB4BD Variant: 1

Part type	Component
Order number	RSL1AB4BD
Designation 1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Description	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	28,00 mm
Width	5,00 mm
Depth	18,50 mm
Weight	0,01 kg

Parts: SE.RSLZVA1 Variant: 1

Part type	Component
Order number	RSLZVA1
Designation 1	Screw socket equipped with LED and protection circuit, 12-24 V
Description	Screw socket equipped with LED and protection circuit, 12-24 V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	78,60 mm
Width	6,20 mm
Depth	101,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3K4:A1;A2	=LIN1+OMA1/3.b.6
	=LIN1+OMA1-3K4:13;14	=LIN1+OMA1/3.b.1
Panel layout	=LIN1+OMA1-3K4	=LIN1+OMA1/33.4

=LIN1+OMA1-3K5

Properties

Trade	Electrical engineering
Function text (automatic)	POWER ENABLE M4
Technical characteristics	24 VDC

Part properties

Parts: SE.RSL1AB4BD Variant: 1

Part type	Component
Order number	RSL1AB4BD
Designation 1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Description	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	28,00 mm
Width	5,00 mm
Depth	18,50 mm
Weight	0,01 kg

Parts: SE.RSLZVA1 Variant: 1

Part type	Component
Order number	RSLZVA1
Designation 1	Screw socket equipped with LED and protection circuit, 12-24 V
Description	Screw socket equipped with LED and protection circuit, 12-24 V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	78,60 mm
Width	6,20 mm
Depth	101,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3K5:A1;A2	=LIN1+OMA1/3.b.7
	=LIN1+OMA1-3K5:13;14	=LIN1+OMA1/3.b.2
Panel layout	=LIN1+OMA1-3K5	=LIN1+OMA1/33.4

=LIN1+OMA1-3K6

Properties

Trade	Electrical engineering
Function text (automatic)	POWER ENABLE M5
Technical characteristics	24 VDC

Part properties

Parts: SE.RSL1AB4BD Variant: 1

Part type	Component
Order number	RSL1AB4BD
Designation 1	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Description	Slim interface plug-in relay - Zelio RSL - 1 C/O standard - 24 V DC - 6 A
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	28,00 mm
Width	5,00 mm
Depth	18,50 mm
Weight	0,01 kg

Parts: SE.RSLZVA1 Variant: 1

Part type	Component
Order number	RSLZVA1
Designation 1	Screw socket equipped with LED and protection circuit, 12-24 V
Description	Screw socket equipped with LED and protection circuit, 12-24 V
Manufacturer	Schneider Electric
Supplier	Schneider Electric
Height	78,60 mm
Width	6,20 mm
Depth	101,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3K6:A1;A2	=LIN1+OMA1/3.b.8
	=LIN1+OMA1-3K6:13;14	=LIN1+OMA1/3.b.2
Panel layout	=LIN1+OMA1-3K6	=LIN1+OMA1/33.4

=LIN1+OMA1-15K7

Properties

Trade	Electrical engineering

Part properties

Parts: SIE.6AV2123-2GB03-0AX0 Variant: 1

Part type	Component
Order number	6AV2123-2GB03-0AX0
Designation 1	SIMATIC HMI KTP700 BASIC
Designation 2	SIMATIC, HMI
Designation 3	Basic Panel
Description	SIMATIC HMI, KTP700 Basic, Basic Panel, Key/touch operation, 7″ TFT display, 65536 colors, PROFINET interface, configurable from WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD
Manufacturer	Siemens
Supplier	Siemens
Height	158,00 mm
Width	214,00 mm
Depth	39,00 mm
Weight	0,98 kg

References

Parts list	Parts list	
Multi-line	=LIN1+OMA1-15K7	=LIN1+OMA1/15.2
Single-line	=LIN1+OMA1-15K7	=LIN1+OMA1/14.7
Multi-line	=LIN1+OMA1-15K7:1	=LIN1+OMA1/15.5
	=LIN1+OMA1-15K7:2	=LIN1+OMA1/15.6
	=LIN1+OMA1-15K7	=LIN1+OMA1/15.6
Single-line	=LIN1+OMA1-15K7	=LIN1+OMA1/14.7

=LIN1+OMA1-26K8

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1123490000 Variant: 1

Part type	Component
Order number	1123490000
Designation 1	Relay module
Designation 2	Relay module, 24 V DC +/-20 %, Green LED, Free-wheeling diode, Reverse polarity protection, 2 CO contact (AgNi) , 250 V AC, 8 A, Screw connection
Description	Assembly of plug-in relay and plug-in socket. Control circuit and load circuit are electrically isolated.
Height	89,60 mm
Width	12,80 mm
Depth	87,80 mm
Weight	0,06 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-26K8:+A1;-A2	=LIN1+OMA1/26.1
Panel layout	=LIN1+OMA1-26K8	=LIN1+OMA1/33.2

=LIN1+OMA1-11KF1

Properties

Trade	Electrical engineering

Part properties

Parts: MURR.58171 Variant: 1

Part type	Component
Order number	58171
Designation 1	TREE 8TX METALL - UNMANAGED SWITCH - 8 PORTS
Description	Further information is available at http://www.murrelektronik.de
Height	90,00 mm
Width	45,00 mm
Depth	78,00 mm
Weight	0,27 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-11KF1	=LIN1+OMA1/11.0
	=LIN1+OMA1-11KF1:F.G.	=LIN1+OMA1/11.1
	=LIN1+OMA1-11KF1:V+	=LIN1+OMA1/11.1
	=LIN1+OMA1-11KF1:V-	=LIN1+OMA1/11.1
	=LIN1+OMA1-11KF1:V+	=LIN1+OMA1/11.0
	=LIN1+OMA1-11KF1:V-	=LIN1+OMA1/11.0
Single-line	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.1
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.2
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.3
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.4
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.5
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.6
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.7
	=LIN1+OMA1-11KF1:1	=LIN1+OMA1/11.9
Panel layout	=LIN1+OMA1-11KF1	=LIN1+OMA1/33.4

=LIN1+OMA1-2M1

Properties

Trade	Electrical engineering
Function text (automatic)	Hlajenje ele. omare

Part properties

Parts: SCHR.IUKNF1523A Variant: 1

Part type	Component
Order number	IUKNF1523A
Designation 1	Ventilator s filtrom 230V, 11W, 109x109x62mm, IP54, 16m3/h
Description	Ventilator s filtrom 230V, 11W, 109x109x62mm, IP54, 16m3/h
Manufacturer	Schrack
Supplier	Schrack
Height	109,00 mm
Width	109,00 mm
Depth	62,00 mm
Weight	0,55 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-2M1	=LIN1+OMA1/2.1
Panel layout	=LIN1+OMA1-2M1	=LIN1+OMA1/32.7

=LIN1+OMA1-32M2

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Panel layout	=LIN1+OMA1-32M2	=LIN1+OMA1/32

=LIN1+OMA1-33M3

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Panel layout	=LIN1+OMA1-33M3	=LIN1+OMA1/33.0

=LIN1+OMA1-N

Properties

Trade	Electrical engineering
Function text (automatic)	N BusBar

Part properties

Parts: Variant:

Part type	Undefined

Parts: SCHR.IK021038I- Variant: 1

Part type	Component
Order number	IK021038I-
Designation 1	N-sponka za 15 odvodov, montaža na DIN letev, izolirana
Description	N-sponka za 15 odvodov, montaža na DIN letev, izolirana
Manufacturer	Schrack
Supplier	Schrack
Height	20,00 mm
Width	100,00 mm
Depth	90,00 mm
Weight	0,06 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Multi-line	=LIN1+OMA1-N	=LIN1+OMA1/1.1
	=LIN1+OMA1-N:1	=LIN1+OMA1/1.1
	=LIN1+OMA1-N:2	=LIN1+OMA1/1.2
	=LIN1+OMA1-N:3	=LIN1+OMA1/1.4
	=LIN1+OMA1-N:4	=LIN1+OMA1/1.7
	=LIN1+OMA1-N:5	=LIN1+OMA1/2.2
	=LIN1+OMA1-N:7	=LIN1+OMA1/6.1
	=LIN1+OMA1-N:8	=LIN1+OMA1/6.2
	=LIN1+OMA1-N:9	=LIN1+OMA1/3.a.1

=LIN1+OMA1-PE

Properties

Trade	Electrical engineering
Function text (automatic)	PE BusBar

Part properties

Parts: Variant:

Part type	Undefined

Parts: SCHR.IK021039I- Variant: 1

Part type	Component
Order number	IK021039I-
Designation 1	PE-sponka za 15 odvodov, montaža na DIN letev, izolirana
Description	PE-sponka za 15 odvodov, montaža na DIN letev, izolirana
Manufacturer	Schrack
Supplier	Schrack
Height	20,00 mm
Width	100,00 mm
Depth	90,00 mm
Weight	0,06 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Multi-line	=LIN1+OMA1-PE	=LIN1+OMA1/1.2
	=LIN1+OMA1-PE:1	=LIN1+OMA1/1.1
	=LIN1+OMA1-PE:2	=LIN1+OMA1/1.2
	=LIN1+OMA1-PE:3	=LIN1+OMA1/1.3
	=LIN1+OMA1-PE:4	=LIN1+OMA1/1.3
	=LIN1+OMA1-PE:5	=LIN1+OMA1/1.3
	=LIN1+OMA1-PE:6	=LIN1+OMA1/1.4
	=LIN1+OMA1-PE:7	=LIN1+OMA1/1.4
	=LIN1+OMA1-PE:8	=LIN1+OMA1/2.2
	=LIN1+OMA1-PE:9	=LIN1+OMA1/3.1
	=LIN1+OMA1-PE:10	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-PE:11	=LIN1+OMA1/6.1
	=LIN1+OMA1-PE:12	=LIN1+OMA1/6.2
	=LIN1+OMA1-PE:13	=LIN1+OMA1/11.1

=LIN1+OMA1-2Q1

Properties

Trade	Electrical engineering
Technical characteristics	0.5A

Part properties

Parts: SCHR.BE082882-- Variant: 1

Part type	Component
Order number	BE082882--
Designation 1	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja
Description	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja
Manufacturer	Schrack
Supplier	Schrack
Height	68,00 mm
Width	70,00 mm
Depth	76,00 mm
Weight	0,02 kg

Parts: SCHR.BE501000-- Variant: 1

Part type	Component
Order number	BE501000--
Designation 1	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P
Description	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P Velikost BE5, Naprava Razred 10
Manufacturer	Schrack
Supplier	Schrack
Height	93,00 mm
Width	45,00 mm
Depth	76,00 mm
Weight	0,30 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-2Q1:2;1;4;3;6;5	=LIN1+OMA1/2.1
Panel layout	=LIN1+OMA1-2Q1	=LIN1+OMA1/33.2

=LIN1+OMA1-3Q2

Properties

Trade	Electrical engineering
Technical characteristics	0.5A

Part properties

Parts: SCHR.BE082882-- Variant: 1

Part type	Component
Order number	BE082882--
Designation 1	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja
Description	Pomožni kontakt MZS BE5, 1Z in 1O, čelna vgradnja
Manufacturer	Schrack
Supplier	Schrack
Height	68,00 mm
Width	70,00 mm
Depth	76,00 mm
Weight	0,02 kg

Parts: SCHR.BE501000-- Variant: 1

Part type	Component
Order number	BE501000--
Designation 1	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P
Description	Motorsko zaščitno stikalo BE5 0,63-1,0A / 3P Velikost BE5, Naprava Razred 10
Manufacturer	Schrack
Supplier	Schrack
Height	93,00 mm
Width	45,00 mm
Depth	76,00 mm
Weight	0,30 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3Q2:2;1;4;3;6;5	=LIN1+OMA1/3.1
Panel layout	=LIN1+OMA1-3Q2	=LIN1+OMA1/33.1

=LIN1+OMA1-1S1

Properties

Trade	Electrical engineering
Function text (automatic)	Glavno stikalo 63A

Part properties

Parts: ETN.P3-63/EA/SVB-SW/N Variant: 1

Part type	Component
Order number	012771
Designation 1	Main switch, 3 pole + N, 63 A, STOP function, Lockable in th e 0 (Off) position, flush mounting
Description	Main switch/switch-disconnector on-off according to IEC/ EN 60947-3, 690V/63A, degree of protection Front IP65, han dle black with black locking collar lockable with 3 padlocks, switch-disconnectors P3 have a very compact and robust d esign. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off. D esign general: insulating material-surface mounting enclosure, flush mounting, rear mounting, IVS service distribution board mounting
Manufacturer	Eaton
Supplier	Eaton
Height	102,00 mm
Width	90,00 mm
Depth	128,00 mm
Weight	0,50 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1S1:1;2	=LIN1+OMA1/1.1
	=LIN1+OMA1-1S1:3;4	=LIN1+OMA1/1.1
	=LIN1+OMA1-1S1:5;6	=LIN1+OMA1/1.1
	=LIN1+OMA1-1S1:N1;N2	=LIN1+OMA1/1.1
Panel layout	=LIN1+OMA1-1S1	=LIN1+OMA1/32.7

=LIN1+OMA1-2S2

Properties

Trade	Electrical engineering
Function text (automatic)	Termostat 0-60
Technical characteristics	tERMOSTAT

Part properties

Parts: SCHR.IUK08566-- Variant: 1

Part type	Component
Order number	IUK08566--
Designation 1	Termostat za ventilator, 0 – 60° C, 1 delovni kontakt
Description	Termostat za ventilator, 0 – 60° C, 1 delovni kontakt
Manufacturer	Schrack
Supplier	Schrack
Height	64,00 mm
Width	46,00 mm
Depth	37,00 mm
Weight	0,05 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-2S2:1;2	=LIN1+OMA1/2.1
Panel layout	=LIN1+OMA1-2S2	=LIN1+OMA1/33.1

=LIN1+OMA1-29T1

Properties

Trade	Electrical engineering

Part properties

Parts: HBM.BM40IE Variant: 1

Part type	Component
Order number	1-BM40IE
Designation 1	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP
Description	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP Four individually configurable strain gauge full or half bridges (4.8kHz TF). Potentiometric sensors, Pt100 voltage / current input, 4 TEDS (0-wire) sensor detection 2 x RJ45 connector
Height	132,60 mm
Width	25,00 mm
Depth	111,70 mm
Weight	0,00 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-29T1	=LIN1+OMA1/29.a.2
Single-line	=LIN1+OMA1-29T1:1-8	=LIN1+OMA1/29.a.5
Multi-line	=LIN1+OMA1-29T1:0I	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:0V	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:24V	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:CxA	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:CxB	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:DI1	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:DI2	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:DO1	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:DO2	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:PE	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:Sync	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:X	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:AO	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:AO_GND	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:PE	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:1	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:2	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:2´	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:3	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:3´	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:4	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:AI	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:I IN	=LIN1+OMA1/29.a.6
	=LIN1+OMA1-29T1:PE	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T1:Pt100	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T1:S	=LIN1+OMA1/29.a.4

=LIN1+OMA1-29T1

Multi-line	=LIN1+OMA1-29T1:TEDS	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T1:U IN	=LIN1+OMA1/29.a.6
Single-line	=LIN1+OMA1-29T1:1-8	=LIN1+OMA1/29.a.6
	=LIN1+OMA1-29T1:1-8	=LIN1+OMA1/29.a.7
Panel layout	=LIN1+OMA1-29T1	=LIN1+OMA1/33.3

=LIN1+OMA1-29T2

Properties

Trade	Electrical engineering

Part properties

Parts: HBM.BM40IE Variant: 1

Part type	Component
Order number	1-BM40IE
Designation 1	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP
Description	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP Four individually configurable strain gauge full or half bridges (4.8kHz TF). Potentiometric sensors, Pt100 voltage / current input, 4 TEDS (0-wire) sensor detection 2 x RJ45 connector
Height	132,60 mm
Width	25,00 mm
Depth	111,70 mm
Weight	0,00 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-29T2	=LIN1+OMA1/29.a.2
Single-line	=LIN1+OMA1-29T2:2	=LIN1+OMA1/29.a.5
Multi-line	=LIN1+OMA1-29T2:0I	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:0V	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:24V	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:CxA	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:CxB	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:DI1	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:DI2	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:DO1	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:DO2	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:PE	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:Sync	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:X	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:AO	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:AO_GND	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:PE	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:1	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:2	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:2´	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:3	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:3´	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:4	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:AI	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:I IN	=LIN1+OMA1/29.a.6
	=LIN1+OMA1-29T2:PE	=LIN1+OMA1/29.a.5
	=LIN1+OMA1-29T2:Pt100	=LIN1+OMA1/29.a.3
	=LIN1+OMA1-29T2:S	=LIN1+OMA1/29.a.4

=LIN1+OMA1-29T2

Multi-line	=LIN1+OMA1-29T2:TEDS	=LIN1+OMA1/29.a.4
	=LIN1+OMA1-29T2:U IN	=LIN1+OMA1/29.a.6
Single-line	=LIN1+OMA1-29T2:2	=LIN1+OMA1/29.a.6
	=LIN1+OMA1-29T2:2	=LIN1+OMA1/29.a.7
Panel layout	=LIN1+OMA1-29T2	=LIN1+OMA1/33.3

=LIN1+OMA1-29T3

Properties

Trade	Electrical engineering

Part properties

Parts: HBM.BM40IE Variant: 1

Part type	Component
Order number	1-BM40IE
Designation 1	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP
Description	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP Four individually configurable strain gauge full or half bridges (4.8kHz TF). Potentiometric sensors, Pt100 voltage / current input, 4 TEDS (0-wire) sensor detection 2 x RJ45 connector
Height	132,60 mm
Width	25,00 mm
Depth	111,70 mm
Weight	0,00 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-29T3	=LIN1+OMA1/29.b.2
Single-line	=LIN1+OMA1-29T3:2	=LIN1+OMA1/29.b.5
Multi-line	=LIN1+OMA1-29T3:0I	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:0V	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:24V	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:CxA	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:CxB	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:DI1	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:DI2	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:DO1	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:DO2	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:PE	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:Sync	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:X	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:AO	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:AO_GND	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:PE	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:1	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:2	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:2´	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:3	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:3´	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:4	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:AI	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:I IN	=LIN1+OMA1/29.b.6
	=LIN1+OMA1-29T3:PE	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T3:Pt100	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T3:S	=LIN1+OMA1/29.b.4

=LIN1+OMA1-29T3

Multi-line	=LIN1+OMA1-29T3:TEDS	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T3:U IN	=LIN1+OMA1/29.b.6
Single-line	=LIN1+OMA1-29T3:2	=LIN1+OMA1/29.b.6
	=LIN1+OMA1-29T3:2	=LIN1+OMA1/29.b.7
Panel layout	=LIN1+OMA1-29T3	=LIN1+OMA1/33.4

=LIN1+OMA1-29T4

Properties

Trade	Electrical engineering

Part properties

Parts: HBM.BM40IE Variant: 1

Part type	Component
Order number	1-BM40IE
Designation 1	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP
Description	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP Four individually configurable strain gauge full or half bridges (4.8kHz TF). Potentiometric sensors, Pt100 voltage / current input, 4 TEDS (0-wire) sensor detection 2 x RJ45 connector
Height	132,60 mm
Width	25,00 mm
Depth	111,70 mm
Weight	0,00 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-29T4	=LIN1+OMA1/29.b.2
Single-line	=LIN1+OMA1-29T4:2	=LIN1+OMA1/29.b.5
Multi-line	=LIN1+OMA1-29T4:0I	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:0V	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:24V	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:CxA	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:CxB	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:DI1	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:DI2	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:DO1	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:DO2	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:PE	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:Sync	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:X	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:AO	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:AO_GND	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:PE	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:1	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:2	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:2´	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:3	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:3´	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:4	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:AI	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:I IN	=LIN1+OMA1/29.b.6
	=LIN1+OMA1-29T4:PE	=LIN1+OMA1/29.b.5
	=LIN1+OMA1-29T4:Pt100	=LIN1+OMA1/29.b.3
	=LIN1+OMA1-29T4:S	=LIN1+OMA1/29.b.4

=LIN1+OMA1-29T4

Multi-line	=LIN1+OMA1-29T4:TEDS	=LIN1+OMA1/29.b.4
	=LIN1+OMA1-29T4:U IN	=LIN1+OMA1/29.b.6
Single-line	=LIN1+OMA1-29T4:2	=LIN1+OMA1/29.b.6
	=LIN1+OMA1-29T4:2	=LIN1+OMA1/29.b.7
Panel layout	=LIN1+OMA1-29T4	=LIN1+OMA1/33.4

=LIN1+OMA1-29T5

Properties

Trade	Electrical engineering

Part properties

Parts: HBM.BM40IE Variant: 1

Part type	Component
Order number	1-BM40IE
Designation 1	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP
Description	BM40IE measuring amplifier PROFINET, EtherCAT, Ethernet/IP Four individually configurable strain gauge full or half bridges (4.8kHz TF). Potentiometric sensors, Pt100 voltage / current input, 4 TEDS (0-wire) sensor detection 2 x RJ45 connector
Height	132,60 mm
Width	25,00 mm
Depth	111,70 mm
Weight	0,00 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-29T5	=LIN1+OMA1/29.c.2
Single-line	=LIN1+OMA1-29T5:2	=LIN1+OMA1/29.c.5
Multi-line	=LIN1+OMA1-29T5:0I	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:0V	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:24V	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:CxA	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:CxB	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:DI1	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:DI2	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:DO1	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:DO2	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:PE	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:Sync	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:X	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:AO	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:AO_GND	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:PE	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:1	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:2	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:2´	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:3	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:3´	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:4	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:AI	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:I IN	=LIN1+OMA1/29.c.6
	=LIN1+OMA1-29T5:PE	=LIN1+OMA1/29.c.5
	=LIN1+OMA1-29T5:Pt100	=LIN1+OMA1/29.c.3
	=LIN1+OMA1-29T5:S	=LIN1+OMA1/29.c.4

=LIN1+OMA1-29T5

Multi-line	=LIN1+OMA1-29T5:TEDS	=LIN1+OMA1/29.c.4
	=LIN1+OMA1-29T5:U IN	=LIN1+OMA1/29.c.6
Single-line	=LIN1+OMA1-29T5:2	=LIN1+OMA1/29.c.6
	=LIN1+OMA1-29T5:2	=LIN1+OMA1/29.c.7
Panel layout	=LIN1+OMA1-29T5	=LIN1+OMA1/33.4

=LIN1+OMA1-3TB1

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1469530000 Variant: 1

Part type	Component
Order number	1469530000
Designation 1	Continuous current supply
Designation 2	Power supply, 120 W, 5 A at 55 ° C
Description	Power supply unit for providing DC voltage.
Height	125,00 mm
Width	40,00 mm
Depth	109,00 mm
Weight	0,68 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3TB1	=LIN1+OMA1/3.0
	=LIN1+OMA1-3TB1:13	=LIN1+OMA1/3.2
	=LIN1+OMA1-3TB1:14	=LIN1+OMA1/3.2
	=LIN1+OMA1-3TB1:+	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:+	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:-	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:-	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:L1(+)	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:L2(-)	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:L3	=LIN1+OMA1/3.1
	=LIN1+OMA1-3TB1:PE	=LIN1+OMA1/3.1
Panel layout	=LIN1+OMA1-3TB1	=LIN1+OMA1/33.2

=LIN1+OMA1-3TB2

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1469590000 Variant: 1

Part type	Component
Order number	1469590000
Designation 1	Continuous current supply
Designation 2	Power supply, 240 W, 5 A at 55 ° C
Description	Power supply unit for providing DC voltage.
Height	125,00 mm
Width	60,00 mm
Depth	109,00 mm
Weight	1,01 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3TB2	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:13	=LIN1+OMA1/3.a.2
	=LIN1+OMA1-3TB2:14	=LIN1+OMA1/3.a.2
	=LIN1+OMA1-3TB2:+	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:+	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:-	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:-	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:L(+)	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:N(-)	=LIN1+OMA1/3.a.1
	=LIN1+OMA1-3TB2:PE	=LIN1+OMA1/3.a.1
Panel layout	=LIN1+OMA1-3TB2	=LIN1+OMA1/33.3

=LIN1+OMA1-1U1

Properties

Trade	Electrical engineering

Part properties

Parts: SCH.UR6P3052 Variant: 1

Part type	Component
Order number	UR6P3052
Designation 1	UR6P3052 | Rele, nadzor zaporedja faz, 3-fazni, 2 preklopna kontakta
Description	UR6P3052 - Rele, nadzor zaporedja faz, 3-fazni, 2 preklopna kontakta
Manufacturer	Schrack
Supplier	Schrack
Height	129,00 mm
Width	29,00 mm
Depth	92,00 mm
Weight	0,00 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1U1	=LIN1+OMA1/1.3
	=LIN1+OMA1-1U1:L1	=LIN1+OMA1/1.3
	=LIN1+OMA1-1U1:L2	=LIN1+OMA1/1.3
	=LIN1+OMA1-1U1:L3	=LIN1+OMA1/1.4
	=LIN1+OMA1-1U1:N	=LIN1+OMA1/1.4
	=LIN1+OMA1-1U1:PE	=LIN1+OMA1/1.4
Panel layout	=LIN1+OMA1-1U1	=LIN1+OMA1/33.2

=LIN1+OMA1-29U2

Properties

Trade	Electrical engineering

Part properties

Parts: HBM.ClipX Variant: 1

Part type	Component
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Multi-line	=LIN1+OMA1-29U2	=LIN1+OMA1/29.a.8

=LIN1+OMA1-29U2-29X1

Properties	
Trade	Electrical engineering

References		
Multi-line	=LIN1+OMA1-29U2-29X1:1	=LIN1+OMA1/29.a.8
	=LIN1+OMA1-29U2-29X1:2	=LIN1+OMA1/29.a.8

=LIN1+OMA1-29U2-29X2

Properties	
Trade	Electrical engineering

References		
Multi-line	=LIN1+OMA1-29U2-29X2:2	=LIN1+OMA1/29.a.8
	=LIN1+OMA1-29U2-29X2:X4	=LIN1+OMA1/29.a.9

=LIN1+OMA1-31U3

Properties	
Trade	Electrical engineering
Function text (automatic)	router
Technical characteristics	Teltonika router

Part properties	
Parts: Teltonika.RUT241 Variant: 1	
Part type	Component
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References		
Parts list	Parts list	
Summarized parts list	Summarized parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-31U3	=LIN1+OMA1/31.2
Panel layout	=LIN1+OMA1-31U3	=LIN1+OMA1/32.7

=LIN1+OMA1-31U3-LAN

Properties	
Trade	Electrical engineering

References		
Multi-line	=LIN1+OMA1-31U3-LAN:2	=LIN1+OMA1/31.3

=LIN1+OMA1-31U3-WAN

Properties	
Trade	Electrical engineering

References		
Multi-line	=LIN1+OMA1-31U3-WAN:1	=LIN1+OMA1/31.2

=LIN1+OMA1-3V1

Properties	
Trade	Electrical engineering

Part properties	
Parts: WEI.1275100000 Variant: 1	
Part type	Component
Order number	1275100000
Designation 1	Solid-state relais
Designation 2	Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3...33 V DC, 4 A, Screw connection
Description	Solid-state relay for switching and amplifying digital signals. The relay operates wear-free and noiselessly. Control circuit and load circuit are electrically isolated.
Height	74,43 mm
Width	6,10 mm
Depth	55,00 mm
Weight	0,02 kg
Parts: WEI.8950930000 Variant: 1	
Part type	Undefined

References		
Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3V1:A1;A2	=LIN1+OMA1/3.a.2
Panel layout	=LIN1+OMA1-3V1	=LIN1+OMA1/33.4

=LIN1+OMA1-3V2

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1275100000 Variant: 1

Part type	Component
Order number	1275100000
Designation 1	Solid-state relais
Designation 2	Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3...33 V DC, 4 A, Screw connection
Description	Solid-state relay for switching and amplifying digital signals. The relay operates wear-free and noiselessly. Control circuit and load circuit are electrically isolated.
Height	74,43 mm
Width	6,10 mm
Depth	55,00 mm
Weight	0,02 kg

Parts: WEI.8950930000 Variant: 1

Part type	Undefined

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3V2:A1;A2	=LIN1+OMA1/3.a.2
Panel layout	=LIN1+OMA1-3V2	=LIN1+OMA1/33.4

=LIN1+OMA1-3V3

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1275100000 Variant: 1

Part type	Component
Order number	1275100000
Designation 1	Solid-state relais
Designation 2	Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3...33 V DC, 4 A, Screw connection
Description	Solid-state relay for switching and amplifying digital signals. The relay operates wear-free and noiselessly. Control circuit and load circuit are electrically isolated.
Height	74,43 mm
Width	6,10 mm
Depth	55,00 mm
Weight	0,02 kg

Parts: WEI.8950930000 Variant: 1

Part type	Undefined

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3V3:A1;A2	=LIN1+OMA1/3.a.2
Panel layout	=LIN1+OMA1-3V3	=LIN1+OMA1/33.4

=LIN1+OMA1-3V4

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1275100000 Variant: 1

Part type	Component
Order number	1275100000
Designation 1	Solid-state relais
Designation 2	Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3...33 V DC, 4 A, Screw connection
Description	Solid-state relay for switching and amplifying digital signals. The relay operates wear-free and noiselessly. Control circuit and load circuit are electrically isolated.
Height	74,43 mm
Width	6,10 mm
Depth	55,00 mm
Weight	0,02 kg

Parts: WEI.8950930000 Variant: 1

Part type	Undefined

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3V4:A1;A2	=LIN1+OMA1/3.a.3
Panel layout	=LIN1+OMA1-3V4	=LIN1+OMA1/33.4

=LIN1+OMA1-3V5

Properties

Trade	Electrical engineering

Part properties

Parts: WEI.1275100000 Variant: 1

Part type	Component
Order number	1275100000
Designation 1	Solid-state relais
Designation 2	Solid-state relais, 24 V DC +/-20 %, Varistor, Reverse polarity protection , 1 NO contact (MOS-FET), 3...33 V DC, 4 A, Screw connection
Description	Solid-state relay for switching and amplifying digital signals. The relay operates wear-free and noiselessly. Control circuit and load circuit are electrically isolated.
Height	74,43 mm
Width	6,10 mm
Depth	55,00 mm
Weight	0,02 kg

Parts: WEI.8950930000 Variant: 1

Part type	Undefined

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3V5:A1;A2	=LIN1+OMA1/3.a.3
Panel layout	=LIN1+OMA1-3V5	=LIN1+OMA1/33.4

=LIN1+OMA1-1X1

Properties

Trade	Electrical engineering
Function text (automatic)	Dovodne sponke

Part properties

Parts: Variant:

Part type	Undefined

Parts: WEI.1010000000 Variant: 1

Part type	Component
Order number	1010000000
Designation 1	PE terminal
Designation 2	PE terminal, Screw connection, 2.5 mm², 800 V, Number of c onnections: 2, Number of levels: 1, Green/yellow
Description	Terminal block for connecting protective earth conductors to the mounting base (earth). Hardened steel withstands the mechanical forces, tin-coated copper ensures top conductivit y.
Height	60,00 mm
Width	5,10 mm
Depth	46,50 mm
Weight	0,02 kg

Parts: WEI.1020000000 Variant: 1

Part type	Component
Order number	1020000000
Designation 1	Feed-through terminal block
Designation 2	Feed-through terminal block, Screw connection, 2.5 mm², 80 0 V, 24 A, Number of connections: 2
Description	Terminal block for connecting or joining conductors with per manently secure contact. Hardened steel withstands the mec hanical forces, tin-coated copper ensures top conductivity.
Height	60,00 mm
Width	5,10 mm
Depth	46,25 mm
Weight	0,01 kg

Parts: WEI.1061200000 Variant: 1

Part type	Component
Order number	1061200000
Designation 1	End bracket
Designation 2	End bracket, Wemid, dark beige, Rail: TS 35, when screwed in
Description	The end bracket ensures a permanently secure fit on the mo unting rail and prevents slipping. The end bracket has marking options for group markers and the option of receiving test pl ugs.
Height	56,10 mm
Width	8,00 mm
Depth	46,50 mm
Weight	0,01 kg

References

Parts list	Parts list
Summarized parts list	Summarized parts list

=LIN1+OMA1-1X1

Terminal diagram	Terminal diagram	
Terminal-strip overview	Terminal-strip overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-1X1	=LIN1+OMA1/1.0
	=LIN1+OMA1-1X1:1:1;2	=LIN1+OMA1/1.1
	=LIN1+OMA1-1X1:2:1;2	=LIN1+OMA1/1.1
	=LIN1+OMA1-1X1:3:1;2	=LIN1+OMA1/1.1
	=LIN1+OMA1-1X1:4:1;2	=LIN1+OMA1/1.1
	=LIN1+OMA1-1X1:PE:1;2	=LIN1+OMA1/1.1
Panel layout	=LIN1+OMA1-1X1	=LIN1+OMA1/33.0

=LIN1+OMA1-2X2

Properties

Trade	Electrical engineering
Function text (automatic)	Hlajenje ele. omare

Part properties

Parts: Variant:

Part type	Undefined

Parts: WEI.1010000000 Variant: 1

Part type	Component
Order number	1010000000
Designation 1	PE terminal
Designation 2	PE terminal, Screw connection, 2.5 mm², 800 V, Number of c onnections: 2, Number of levels: 1, Green/yellow
Description	Terminal block for connecting protective earth conductors to the mounting base (earth). Hardened steel withstands the mechanical forces, tin-coated copper ensures top conductivit y.
Height	60,00 mm
Width	5,10 mm
Depth	46,50 mm
Weight	0,02 kg

Parts: WEI.1020000000 Variant: 1

Part type	Component
Order number	1020000000
Designation 1	Feed-through terminal block
Designation 2	Feed-through terminal block, Screw connection, 2.5 mm², 80 0 V, 24 A, Number of connections: 2
Description	Terminal block for connecting or joining conductors with per manently secure contact. Hardened steel withstands the mec hanical forces, tin-coated copper ensures top conductivity.
Height	60,00 mm
Width	5,10 mm
Depth	46,25 mm
Weight	0,01 kg

Parts: WEI.1020080000 Variant: 1

Part type	Component
Order number	1020080000
Designation 1	Feed-through terminal block
Designation 2	Feed-through terminal block, Screw connection, 2.5 mm², 80 0 V, 24 A, Number of connections: 2
Description	Terminal block for connecting or joining conductors with per manently secure contact. Hardened steel withstands the mec hanical forces, tin-coated copper ensures top conductivity.
Height	60,00 mm
Width	5,10 mm
Depth	46,25 mm
Weight	0,01 kg

References

Terminal diagram	Terminal diagram
Terminal-strip overview	Terminal-strip overview

=LIN1+OMA1-2X2

Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-2X2	=LIN1+OMA1/2.0
	=LIN1+OMA1-2X2:1:1;2	=LIN1+OMA1/2.1
	=LIN1+OMA1-2X2:N2:1;2	=LIN1+OMA1/2.2
	=LIN1+OMA1-2X2:PE:1;2	=LIN1+OMA1/2.2
Panel layout	=LIN1+OMA1-2X2	=LIN1+OMA1/33.1

=LIN1+OMA1-3X3

Properties

Trade	Electrical engineering
Function text (automatic)	48VDC

Part properties

Parts: Variant:

Part type	Undefined

Parts: WEI.1020000000 Variant: 1

Part type	Component
Order number	1020000000
Designation 1	Feed-through terminal block
Designation 2	Feed-through terminal block, Screw connection, 2.5 mm², 80 0 V, 24 A, Number of connections: 2
Description	Terminal block for connecting or joining conductors with per manently secure contact. Hardened steel withstands the mec hanical forces, tin-coated copper ensures top conductivity.
Height	60,00 mm
Width	5,10 mm
Depth	46,25 mm
Weight	0,01 kg

References

Terminal diagram	Terminal diagram	
Terminal-strip overview	Terminal-strip overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-3X3	=LIN1+OMA1/3.a.6
	=LIN1+OMA1-3X3:1:1;2	=LIN1+OMA1/3.a.7
	=LIN1+OMA1-3X3:6:1;2	=LIN1+OMA1/3.a.7
	=LIN1+OMA1-3X3:7:1;2	=LIN1+OMA1/3.a.7
	=LIN1+OMA1-3X3:8:1;2	=LIN1+OMA1/3.a.7
	=LIN1+OMA1-3X3:9:1;2	=LIN1+OMA1/3.a.8
	=LIN1+OMA1-3X3:10:1;2	=LIN1+OMA1/3.a.8
	=LIN1+OMA1-3X3:11:1;2	=LIN1+OMA1/3.a.8
	=LIN1+OMA1-3X3:12:1;2	=LIN1+OMA1/3.a.8
Panel layout	=LIN1+OMA1-3X3	=LIN1+OMA1/33.2

=LIN1+OMA1-3X3_1

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Multi-line	=LIN1+OMA1-3X3_1:1	=LIN1+OMA1/3.c.1
	=LIN1+OMA1-3X3_1:2	=LIN1+OMA1/3.c.2
	=LIN1+OMA1-3X3_1:3	=LIN1+OMA1/3.c.4
	=LIN1+OMA1-3X3_1:4	=LIN1+OMA1/3.c.6
	=LIN1+OMA1-3X3_1:5	=LIN1+OMA1/3.c.7

=LIN1+OMA1-4X4

Properties

Trade	Electrical engineering
Function text (automatic)	24V DC

Part properties

Parts: Variant:

Part type	Undefined

Parts: WEI.1020000000 Variant: 1

Part type	Component
Order number	1020000000
Designation 1	Feed-through terminal block
Designation 2	Feed-through terminal block, Screw connection, 2.5 mm², 800 V, 24 A, Number of connections: 2
Description	Terminal block for connecting or joining conductors with permanently secure contact. Hardened steel withstands the mechanical forces, tin-coated copper ensures top conductivity.
Height	60,00 mm
Width	5,10 mm
Depth	46,25 mm
Weight	0,01 kg

References

Terminal diagram	Terminal diagram	
Terminal-strip overview	Terminal-strip overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-4X4	=LIN1+OMA1/4.0
	=LIN1+OMA1-4X4:1:1;2	=LIN1+OMA1/4.1
	=LIN1+OMA1-4X4:2:1;2	=LIN1+OMA1/4.1
	=LIN1+OMA1-4X4:3:1;2	=LIN1+OMA1/4.1
	=LIN1+OMA1-4X4:4:1;2	=LIN1+OMA1/4.2
	=LIN1+OMA1-4X4:5:1;2	=LIN1+OMA1/4.2
Panel layout	=LIN1+OMA1-4X4	=LIN1+OMA1/33.1

=LIN1+OMA1-5X5

Properties

Trade	Electrical engineering
Function text (automatic)	0V DC

Part properties

Parts: Variant:

Part type	Undefined

Parts: WEI.1020000000 Variant: 1

Part type	Component
Order number	1020000000
Designation 1	Feed-through terminal block
Designation 2	Feed-through terminal block, Screw connection, 2.5 mm², 800 V, 24 A, Number of connections: 2
Description	Terminal block for connecting or joining conductors with permanently secure contact. Hardened steel withstands the mechanical forces, tin-coated copper ensures top conductivity.
Height	60,00 mm
Width	5,10 mm
Depth	46,25 mm
Weight	0,01 kg

References

Terminal diagram	Terminal diagram	
Terminal-strip overview	Terminal-strip overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-5X5	=LIN1+OMA1/5.0
	=LIN1+OMA1-5X5:1:1;2	=LIN1+OMA1/5.1
	=LIN1+OMA1-5X5:2:1;2	=LIN1+OMA1/5.1
	=LIN1+OMA1-5X5:3:1;2	=LIN1+OMA1/5.1
	=LIN1+OMA1-5X5:4:1;2	=LIN1+OMA1/5.2
	=LIN1+OMA1-5X5:5:1;2	=LIN1+OMA1/5.2
	=LIN1+OMA1-5X5:6:1;2	=LIN1+OMA1/5.2
	=LIN1+OMA1-5X5:7:1;2	=LIN1+OMA1/5.2
	=LIN1+OMA1-5X5:8:1;2	=LIN1+OMA1/5.2
	=LIN1+OMA1-5X5:9:1;2	=LIN1+OMA1/5.3
	=LIN1+OMA1-5X5:10:1;2	=LIN1+OMA1/5.3
	=LIN1+OMA1-5X5:11:1;2	=LIN1+OMA1/5.3
Panel layout	=LIN1+OMA1-5X5	=LIN1+OMA1/33.2

=LIN1+OMA1-6X6

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

Parts: PXC.3208511 Variant: 1

Part type	Component
Order number	3208511
Designation 1	Double-level terminal block
Description	Double-level terminal block, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Connection type: Push-in connection, Width: 3.5 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15
Manufacturer	Phoenix Contact
Supplier	Phoenix Contact
Height	65,40 mm
Width	3,50 mm
Depth	41,10 mm
Weight	0,01 kg

References

Parts list	Parts list	
Terminal diagram	Terminal diagram	
Terminal-strip overview	Terminal-strip overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-6X6:1:1;4	=LIN1+OMA1/6.a.1
	=LIN1+OMA1-6X6:2:2;3	=LIN1+OMA1/6.a.1
	=LIN1+OMA1-6X6:3:2;3	=LIN1+OMA1/6.a.1
	=LIN1+OMA1-6X6:4:1;4	=LIN1+OMA1/6.a.1
	=LIN1+OMA1-6X6:5:2;3	=LIN1+OMA1/6.a.2
	=LIN1+OMA1-6X6:6:1;4	=LIN1+OMA1/6.a.2
	=LIN1+OMA1-6X6:7:2;3	=LIN1+OMA1/6.a.2
	=LIN1+OMA1-6X6:8:1;4	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:9:2;3	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:10:1;4	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:11:2;3	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:12:1;4	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:13:2;3	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:14:1;4	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:15:2;3	=LIN1+OMA1/6.a.3
	=LIN1+OMA1-6X6:16:1;4	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:17:2;3	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:18:1;4	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:19:2;3	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:20:1;4	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:21:2;3	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:22:1;4	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:23:2;3	=LIN1+OMA1/6.a.5
	=LIN1+OMA1-6X6:24:1;4	=LIN1+OMA1/6.a.6

=LIN1+OMA1-6X6

Multi-line	=LIN1+OMA1-6X6:25:2;3	=LIN1+OMA1/6.a.6
	=LIN1+OMA1-6X6:26:1;4	=LIN1+OMA1/6.a.6
	=LIN1+OMA1-6X6:27:2;3	=LIN1+OMA1/6.a.6
	=LIN1+OMA1-6X6:28:1;4	=LIN1+OMA1/6.a.6
	=LIN1+OMA1-6X6:29:2;3	=LIN1+OMA1/6.a.6
	=LIN1+OMA1-6X6:30:1;4	=LIN1+OMA1/6.a.7
	=LIN1+OMA1-6X6:31:2;3	=LIN1+OMA1/6.a.7
	=LIN1+OMA1-6X6:32:1;4	=LIN1+OMA1/6.b.1
	=LIN1+OMA1-6X6:33:2;3	=LIN1+OMA1/6.b.1
	=LIN1+OMA1-6X6:34:1;4	=LIN1+OMA1/6.b.1
	=LIN1+OMA1-6X6:35:2;3	=LIN1+OMA1/6.b.1
	=LIN1+OMA1-6X6:36:1;4	=LIN1+OMA1/6.b.2
	=LIN1+OMA1-6X6:37:2;3	=LIN1+OMA1/6.b.2
	=LIN1+OMA1-6X6:38:1;4	=LIN1+OMA1/6.b.2
	=LIN1+OMA1-6X6:39:2;3	=LIN1+OMA1/6.b.2
	=LIN1+OMA1-6X6:40:1;4	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:41:2;3	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:42:1;4	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:43:2;3	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:44:1;4	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:45:2;3	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:46:1;4	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:47:2;3	=LIN1+OMA1/6.b.3
	=LIN1+OMA1-6X6:48:1;4	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:49:2;3	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:50:1;4	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:51:2;3	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:52:1;4	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:53:2;3	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:54:1;4	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:55:2;3	=LIN1+OMA1/6.b.5
	=LIN1+OMA1-6X6:56:1;4	=LIN1+OMA1/6.b.6
	=LIN1+OMA1-6X6:57:2;3	=LIN1+OMA1/6.b.6
	=LIN1+OMA1-6X6:58:1;4	=LIN1+OMA1/6.b.6
	=LIN1+OMA1-6X6:59:2;3	=LIN1+OMA1/6.b.6
	=LIN1+OMA1-6X6:60:1;4	=LIN1+OMA1/6.b.6
	=LIN1+OMA1-6X6:61:2;3	=LIN1+OMA1/6.b.6
	=LIN1+OMA1-6X6:62:1;4	=LIN1+OMA1/6.b.7
	=LIN1+OMA1-6X6:63:2;3	=LIN1+OMA1/6.b.7
	=LIN1+OMA1-6X6:64:1;4	=LIN1+OMA1/6.c.1
	=LIN1+OMA1-6X6:65:2;3	=LIN1+OMA1/6.c.1
	=LIN1+OMA1-6X6:66:1;4	=LIN1+OMA1/6.c.1
	=LIN1+OMA1-6X6:67:2;3	=LIN1+OMA1/6.c.1
	=LIN1+OMA1-6X6:68:1;4	=LIN1+OMA1/6.c.2
	=LIN1+OMA1-6X6:69:2;3	=LIN1+OMA1/6.c.2
	=LIN1+OMA1-6X6:70:1;4	=LIN1+OMA1/6.c.2
	=LIN1+OMA1-6X6:71:2;3	=LIN1+OMA1/6.c.2
	=LIN1+OMA1-6X6:72:1;4	=LIN1+OMA1/6.c.3

=LIN1+OMA1-6X6

Multi-line	=LIN1+OMA1-6X6:73:2;3	=LIN1+OMA1/6.c.3
	=LIN1+OMA1-6X6:74:1;4	=LIN1+OMA1/6.c.3
	=LIN1+OMA1-6X6:75:2;3	=LIN1+OMA1/6.c.3
	=LIN1+OMA1-6X6:76:1;4	=LIN1+OMA1/6.c.3
	=LIN1+OMA1-6X6:77:2;3	=LIN1+OMA1/6.c.3
	=LIN1+OMA1-6X6:78:1;4	=LIN1+OMA1/6.c.3
	=LIN1+OMA1-6X6:79:2;3	=LIN1+OMA1/6.c.3
Panel layout	=LIN1+OMA1-6X6	=LIN1+OMA1/33.2

=LIN1+OMA1-21X7

Properties

Trade	Electrical engineering
Function text (automatic)	PLC sponke

Part properties

Parts: Variant:

Part type	Undefined

Parts: WEI.1021500000 Variant: 1

Part type	Component
Order number	1021500000
Designation 1	Multi-tier modular terminal
Designation 2	Multi-tier modular terminal, Screw connection, 2.5 mm², 400 V, 24 A, Number of levels: 2, dark beige
Description	Terminal block with several levels for connecting or joining c onductors with permanently secure contact. Hardened steel withstands the mechanical forces, tin-coated copper ensure s top conductivity. Space-saving design.
Height	69,07 mm
Width	5,10 mm
Depth	62,25 mm
Weight	0,01 kg

References

Terminal diagram	Terminal diagram	
Terminal-strip overview	Terminal-strip overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-21X7	=LIN1+OMA1/21.0
	=LIN1+OMA1-21X7:1:1;2	=LIN1+OMA1/12.0
	=LIN1+OMA1-21X7:2:3;4	=LIN1+OMA1/12.1
	=LIN1+OMA1-21X7:3:1;2	=LIN1+OMA1/12.1
	=LIN1+OMA1-21X7:4:3;4	=LIN1+OMA1/12.1
	=LIN1+OMA1-21X7:5:1;2	=LIN1+OMA1/12.2
	=LIN1+OMA1-21X7:6:3;4	=LIN1+OMA1/12.2
	=LIN1+OMA1-21X7:7:1;2	=LIN1+OMA1/12.2
	=LIN1+OMA1-21X7:8:3;4	=LIN1+OMA1/12.3
	=LIN1+OMA1-21X7:9:1;2	=LIN1+OMA1/12.3
	=LIN1+OMA1-21X7:10:3;4	=LIN1+OMA1/12.3
	=LIN1+OMA1-21X7:11:1;2	=LIN1+OMA1/12.4
	=LIN1+OMA1-21X7:12:3;4	=LIN1+OMA1/12.4
	=LIN1+OMA1-21X7:13:1;2	=LIN1+OMA1/20.6
	=LIN1+OMA1-21X7:14:3;4	=LIN1+OMA1/20.6
	=LIN1+OMA1-21X7:15:1;2	=LIN1+OMA1/20.6
	=LIN1+OMA1-21X7:16:1;2	=LIN1+OMA1/21.1
	=LIN1+OMA1-21X7:17:3;4	=LIN1+OMA1/21.3
	=LIN1+OMA1-21X7:18:1;2	=LIN1+OMA1/21.5
	=LIN1+OMA1-21X7:19:3;4	=LIN1+OMA1/21.8
	=LIN1+OMA1-21X7:20:1;2	=LIN1+OMA1/22.1
	=LIN1+OMA1-21X7:21:3;4	=LIN1+OMA1/22.3
	=LIN1+OMA1-21X7:22:1;2	=LIN1+OMA1/22.5

=LIN1+OMA1-21X7

Multi-line	=LIN1+OMA1-21X7:23:3;4	=LIN1+OMA1/22.8
	=LIN1+OMA1-21X7:24:1;2	=LIN1+OMA1/23.1
	=LIN1+OMA1-21X7:25:3;4	=LIN1+OMA1/23.3
	=LIN1+OMA1-21X7:26:1;2	=LIN1+OMA1/23.5
	=LIN1+OMA1-21X7:27:3;4	=LIN1+OMA1/23.8
	=LIN1+OMA1-21X7:28:1;2	=LIN1+OMA1/24.1
	=LIN1+OMA1-21X7:29:3;4	=LIN1+OMA1/24.3
	=LIN1+OMA1-21X7:30:1;2	=LIN1+OMA1/24.5
	=LIN1+OMA1-21X7:31:3;4	=LIN1+OMA1/24.8
	=LIN1+OMA1-21X7:32:3;4	=LIN1+OMA1/24.b.1
	=LIN1+OMA1-21X7:33:3;4	=LIN1+OMA1/24.b.3
	=LIN1+OMA1-21X7:34:3;4	=LIN1+OMA1/24.b.5
	=LIN1+OMA1-21X7:35:3;4	=LIN1+OMA1/24.b.8
	=LIN1+OMA1-21X7:36:3;4	=LIN1+OMA1/24.c.1
	=LIN1+OMA1-21X7:37:1;2	=LIN1+OMA1/24.c.3
	=LIN1+OMA1-21X7:38:1;2	=LIN1+OMA1/24.c.5
	=LIN1+OMA1-21X7:39:3;4	=LIN1+OMA1/24.c.8
	=LIN1+OMA1-21X7:40:1;2	=LIN1+OMA1/24.d.1
	=LIN1+OMA1-21X7:41:3;4	=LIN1+OMA1/24.d.3
	=LIN1+OMA1-21X7:42:3;4	=LIN1+OMA1/24.d.5
	=LIN1+OMA1-21X7:43:1;2	=LIN1+OMA1/24.d.8
	=LIN1+OMA1-21X7:44:1;2	=LIN1+OMA1/24.e.1
	=LIN1+OMA1-21X7:45:1;2	=LIN1+OMA1/24.e.3
	=LIN1+OMA1-21X7:46:1;2	=LIN1+OMA1/24.e.5
	=LIN1+OMA1-21X7:47:1;2	=LIN1+OMA1/24.e.8
	=LIN1+OMA1-21X7:48:1;2	=LIN1+OMA1/25.1
	=LIN1+OMA1-21X7:49:3;4	=LIN1+OMA1/25.3
	=LIN1+OMA1-21X7:50:1;2	=LIN1+OMA1/25.5
	=LIN1+OMA1-21X7:51:3;4	=LIN1+OMA1/25.8
	=LIN1+OMA1-21X7:52:1;2	=LIN1+OMA1/26.1
	=LIN1+OMA1-21X7:53:3;4	=LIN1+OMA1/26.3
	=LIN1+OMA1-21X7:54:1;2	=LIN1+OMA1/26.5
	=LIN1+OMA1-21X7:55:3;4	=LIN1+OMA1/26.8
	=LIN1+OMA1-21X7:56:3;4	=LIN1+OMA1/27.1
	=LIN1+OMA1-21X7:57:1;2	=LIN1+OMA1/27.3
	=LIN1+OMA1-21X7:58:1;2	=LIN1+OMA1/27.a.1
	=LIN1+OMA1-21X7:59:3;4	=LIN1+OMA1/27.a.3
	=LIN1+OMA1-21X7:60:1;2	=LIN1+OMA1/27.a.5
	=LIN1+OMA1-21X7:61:3;4	=LIN1+OMA1/27.a.8
	=LIN1+OMA1-21X7:62:3;4	=LIN1+OMA1/27.b.1
	=LIN1+OMA1-21X7:63:1;2	=LIN1+OMA1/27.b.3
	=LIN1+OMA1-21X7:64:3;4	=LIN1+OMA1/27.b.6
	=LIN1+OMA1-21X7:65:1;2	=LIN1+OMA1/27.b.8
	=LIN1+OMA1-21X7:66:1;2	=LIN1+OMA1/27.c.1
	=LIN1+OMA1-21X7:67:3;4	=LIN1+OMA1/27.c.3
	=LIN1+OMA1-21X7:68:1;2	=LIN1+OMA1/27.c.6
	=LIN1+OMA1-21X7:69:3;4	=LIN1+OMA1/27.c.8
	=LIN1+OMA1-21X7:70:3;4	=LIN1+OMA1/27.d.1

=LIN1+OMA1-21X7

Multi-line	=LIN1+OMA1-21X7:71:1;2	=LIN1+OMA1/27.d.3
	=LIN1+OMA1-21X7:72:3;4	=LIN1+OMA1/27.d.6
	=LIN1+OMA1-21X7:73:1;2	=LIN1+OMA1/27.d.8
	=LIN1+OMA1-21X7:74:1;2	=LIN1+OMA1/28.2
	=LIN1+OMA1-21X7:75:3;4	=LIN1+OMA1/28.5
	=LIN1+OMA1-21X7:76:1;2	=LIN1+OMA1/29.2
	=LIN1+OMA1-21X7:77:3;4	=LIN1+OMA1/29.5
Panel layout	=LIN1+OMA1-21X7	=LIN1+OMA1/33.0

=LIN1+OMA1-210X7

Properties

Trade	Electrical engineering
Function text (automatic)	i_xDoubleFeed

Part properties

Parts: PXC.3208511 Variant: 1

Part type	Component
Order number	3208511
Designation 1	Double-level terminal block
Description	Double-level terminal block, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Connection type: Push-in connection, Width: 3.5 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15
Manufacturer	Phoenix Contact
Supplier	Phoenix Contact
Height	65,40 mm
Width	3,50 mm
Depth	41,10 mm
Weight	0,01 kg

References

Multi-line	=LIN1+OMA1-210X7:1:1;4	=LIN1+OMA1/23.5
	=LIN1+OMA1-210X7:2:2;3	=LIN1+OMA1/23.6
	=LIN1+OMA1-210X7:3:1;4	=LIN1+OMA1/23.6
	=LIN1+OMA1-210X7:4:2;3	=LIN1+OMA1/23.6
	=LIN1+OMA1-210X7:5:1;4	=LIN1+OMA1/23.8
	=LIN1+OMA1-210X7:6:2;3	=LIN1+OMA1/23.8
	=LIN1+OMA1-210X7:7:1;4	=LIN1+OMA1/23.8
	=LIN1+OMA1-210X7:8:2;3	=LIN1+OMA1/23.9
	=LIN1+OMA1-210X7:9:1;4	=LIN1+OMA1/24.1
	=LIN1+OMA1-210X7:10:2;3	=LIN1+OMA1/24.1
	=LIN1+OMA1-210X7:11:1;4	=LIN1+OMA1/24.1
	=LIN1+OMA1-210X7:12:2;3	=LIN1+OMA1/24.1
	=LIN1+OMA1-210X7:13:1;4	=LIN1+OMA1/24.3
	=LIN1+OMA1-210X7:14:2;3	=LIN1+OMA1/24.3
	=LIN1+OMA1-210X7:15:1;4	=LIN1+OMA1/24.4
	=LIN1+OMA1-210X7:16:2;3	=LIN1+OMA1/24.4

=LIN1+OMA1-11XF1

Properties

Trade	Electrical engineering

Part properties

Parts: MURR.4000-73000-0010000 Variant: 1

Part type	Component
Order number	4000-73000-0010000
Designation 1	Connector (special)
Designation 2	MSDD INSTALLATION SOCKET RJ45 CAT5e BU/BU
Description	Pass-through 1x RJ45, 8-pole metal, CAT5e (female/female) More information may be found on https://www.murrelektronik.com or in the technical datasheet
Height	29,50 mm
Width	29,50 mm
Depth	29,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-11XF1	=LIN1+OMA1/11.6
	=LIN1+OMA1-11XF1:1.-8.;1-8	=LIN1+OMA1/11.6
	=LIN1+OMA1-11XF1:1.-8.;1-8	=LIN1+OMA1/11.6
Panel layout	=LIN1+OMA1-11XF1	=LIN1+OMA1/32.7

=LIN1+OMA1-11XF2

Properties

Trade	Electrical engineering

Part properties

Parts: MURR.4000-73000-0010000 Variant: 1

Part type	Component
Order number	4000-73000-0010000
Designation 1	Connector (special)
Designation 2	MSDD INSTALLATION SOCKET RJ45 CAT5e BU/BU
Description	Pass-through 1x RJ45, 8-pole metal, CAT5e (female/female) More information may be found on https://www.murrelektronik.com or in the technical datasheet
Height	29,50 mm
Width	29,50 mm
Depth	29,00 mm
Weight	0,02 kg

References

Parts list	Parts list	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-11XF2	=LIN1+OMA1/11.7
	=LIN1+OMA1-11XF2:1.-8.;1-8	=LIN1+OMA1/11.8
	=LIN1+OMA1-11XF2:1.-8.;1-8	=LIN1+OMA1/11.8
Panel layout	=LIN1+OMA1-11XF2	=LIN1+OMA1/32.7

=LIN1+OMA1-6XP1

Properties

Trade	Electrical engineering

Part properties

Parts: SCHR.BZ325003-- Variant: 1

Part type	Component
Order number	BZ325003--
Designation 1	Vtičnica za montažo na letev s LED signalizacijo
Description	Vtičnica za montažo na letev s LED signalizacijo
Manufacturer	Schrack
Supplier	Schrack
Height	62,00 mm
Width	44,00 mm
Depth	74,00 mm
Weight	0,13 kg

References

Parts list	Parts list	
Plug diagram	Plug diagram	
Plug overview	Plug overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-6XP1:1:1	=LIN1+OMA1/6.1
Panel layout	=LIN1+OMA1-6XP1	=LIN1+OMA1/33.2

=LIN1+OMA1-6XP2

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Overview	=LIN1+OMA1-6XP2:2:1	=LIN1+OMA1/6.1

=LIN1+OMA1-6XP3

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Overview	=LIN1+OMA1-6XP3:3:1	=LIN1+OMA1/6.1

=LIN1+OMA1-6XP4

Properties

Trade	Electrical engineering

Part properties

Parts: SCHR.BZ325003-- Variant: 1

Part type	Component
Order number	BZ325003--
Designation 1	Vtičnica za montažo na letev s LED signalizacijo
Description	Vtičnica za montažo na letev s LED signalizacijo
Manufacturer	Schrack
Supplier	Schrack
Height	62,00 mm
Width	44,00 mm
Depth	74,00 mm
Weight	0,13 kg

References

Parts list	Parts list	
Plug diagram	Plug diagram	
Plug overview	Plug overview	
Panel layout caption	Panel layout caption	
Multi-line	=LIN1+OMA1-6XP4:1:1	=LIN1+OMA1/6.2
Panel layout	=LIN1+OMA1-6XP4	=LIN1+OMA1/33.2

=LIN1+OMA1-6XP5

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Multi-line	=LIN1+OMA1-6XP5:2:1	=LIN1+OMA1/6.2

=LIN1+OMA1-6XP6

Properties

Trade	Electrical engineering

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Multi-line	=LIN1+OMA1-6XP6:3:1	=LIN1+OMA1/6.2

=LIN1+FIELD-20A1

Properties

Trade	Electrical engineering

Part properties

Parts: SIE.6AV2123-2GB03-0AX0 Variant: 1

Part type	Component
Order number	6AV2123-2GB03-0AX0
Designation 1	SIMATIC HMI KTP700 BASIC
Designation 2	SIMATIC, HMI
Designation 3	Basic Panel
Description	SIMATIC HMI, KTP700 Basic, Basic Panel, Key/touch operation, 7″ TFT display, 65536 colors, PROFINET interface, configurable from WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD
Manufacturer	Siemens
Supplier	Siemens
Height	158,00 mm
Width	214,00 mm
Depth	39,00 mm
Weight	0,98 kg

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-20A1	=LIN1+OMA1/20.2
	=LIN1+FIELD-20A1:1	=LIN1+OMA1/20.6
	=LIN1+FIELD-20A1:2	=LIN1+OMA1/20.6
	=LIN1+FIELD-20A1	=LIN1+OMA1/20.6

=LIN1+FIELD-6M1

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator
Technical characteristics	Egasi

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-6M1	=LIN1+OMA1/6.a.1
	=LIN1+FIELD-6M1:1	=LIN1+OMA1/6.a.1
	=LIN1+FIELD-6M1:2	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:3	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:4	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:5	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:6	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:7	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:8	=LIN1+OMA1/6.a.3
	=LIN1+FIELD-6M1:9	=LIN1+OMA1/6.a.2
	=LIN1+FIELD-6M1:10	=LIN1+OMA1/6.a.1
	=LIN1+FIELD-6M1:11	=LIN1+OMA1/6.a.1
	=LIN1+FIELD-6M1:12	=LIN1+OMA1/6.a.1
	=LIN1+FIELD-6M1:13	=LIN1+OMA1/6.a.2
	=LIN1+FIELD-6M1:14	=LIN1+OMA1/6.a.2
	=LIN1+FIELD-6M1:15	=LIN1+OMA1/6.a.3

=LIN1+FIELD-6M2

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator
Technical characteristics	Egasi

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-6M2	=LIN1+OMA1/6.a.4
	=LIN1+FIELD-6M2:1	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:2	=LIN1+OMA1/6.a.6
	=LIN1+FIELD-6M2:3	=LIN1+OMA1/6.a.7
	=LIN1+FIELD-6M2:4	=LIN1+OMA1/6.a.6
	=LIN1+FIELD-6M2:5	=LIN1+OMA1/6.a.6
	=LIN1+FIELD-6M2:6	=LIN1+OMA1/6.a.7
	=LIN1+FIELD-6M2:7	=LIN1+OMA1/6.a.6
	=LIN1+FIELD-6M2:8	=LIN1+OMA1/6.a.6
	=LIN1+FIELD-6M2:9	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:10	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:11	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:12	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:13	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:14	=LIN1+OMA1/6.a.5
	=LIN1+FIELD-6M2:15	=LIN1+OMA1/6.a.6

=LIN1+FIELD-6M3

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator
Technical characteristics	Egasi

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-6M3	=LIN1+OMA1/6.b.1
	=LIN1+FIELD-6M3:1	=LIN1+OMA1/6.b.1
	=LIN1+FIELD-6M3:2	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:3	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:4	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:5	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:6	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:7	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:8	=LIN1+OMA1/6.b.3
	=LIN1+FIELD-6M3:9	=LIN1+OMA1/6.b.2
	=LIN1+FIELD-6M3:10	=LIN1+OMA1/6.b.1
	=LIN1+FIELD-6M3:11	=LIN1+OMA1/6.b.1
	=LIN1+FIELD-6M3:12	=LIN1+OMA1/6.b.1
	=LIN1+FIELD-6M3:13	=LIN1+OMA1/6.b.2
	=LIN1+FIELD-6M3:14	=LIN1+OMA1/6.b.2
	=LIN1+FIELD-6M3:15	=LIN1+OMA1/6.b.3

=LIN1+FIELD-6M4

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator
Technical characteristics	Egasi

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-6M4	=LIN1+OMA1/6.b.4
	=LIN1+FIELD-6M4:1	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:2	=LIN1+OMA1/6.b.6
	=LIN1+FIELD-6M4:3	=LIN1+OMA1/6.b.7
	=LIN1+FIELD-6M4:4	=LIN1+OMA1/6.b.6
	=LIN1+FIELD-6M4:5	=LIN1+OMA1/6.b.6
	=LIN1+FIELD-6M4:6	=LIN1+OMA1/6.b.7
	=LIN1+FIELD-6M4:7	=LIN1+OMA1/6.b.6
	=LIN1+FIELD-6M4:8	=LIN1+OMA1/6.b.6
	=LIN1+FIELD-6M4:9	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:10	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:11	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:12	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:13	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:14	=LIN1+OMA1/6.b.5
	=LIN1+FIELD-6M4:15	=LIN1+OMA1/6.b.6

=LIN1+FIELD-6M5

Properties

Trade	Electrical engineering
Function text (automatic)	Actuator
Technical characteristics	Egasi

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-6M5	=LIN1+OMA1/6.c.1
	=LIN1+FIELD-6M5:1	=LIN1+OMA1/6.c.1
	=LIN1+FIELD-6M5:2	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:3	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:4	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:5	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:6	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:7	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:8	=LIN1+OMA1/6.c.3
	=LIN1+FIELD-6M5:9	=LIN1+OMA1/6.c.2
	=LIN1+FIELD-6M5:10	=LIN1+OMA1/6.c.1
	=LIN1+FIELD-6M5:11	=LIN1+OMA1/6.c.1
	=LIN1+FIELD-6M5:12	=LIN1+OMA1/6.c.1
	=LIN1+FIELD-6M5:13	=LIN1+OMA1/6.c.2
	=LIN1+FIELD-6M5:14	=LIN1+OMA1/6.c.2
	=LIN1+FIELD-6M5:15	=LIN1+OMA1/6.c.3

=LIN1+FIELD-30R1

Properties

Trade	Electrical engineering
Function text (automatic)	RTD1

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-30R1	=LIN1+OMA1/30.a.1

=LIN1+FIELD-30R2

Properties

Trade	Electrical engineering
Function text (automatic)	RTD2

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-30R2	=LIN1+OMA1/30.a.3

=LIN1+FIELD-30R3

Properties

Trade	Electrical engineering
Function text (automatic)	RTD3

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-30R3	=LIN1+OMA1/30.a.6

=LIN1+FIELD-30R4

Properties

Trade	Electrical engineering
Function text (automatic)	RTD4

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-30R4	=LIN1+OMA1/30.a.8

=LIN1+FIELD-21U1

Properties

Trade	Electrical engineering
Technical characteristics	Enkoder 1000PPR

Part properties

Parts: Variant:

Part type	Undefined

References

Parts list	Parts list	
Multi-line	=LIN1+FIELD-21U1	=LIN1+OMA1/21.3
	=LIN1+FIELD-21U1:A	=LIN1+OMA1/21.3
	=LIN1+FIELD-21U1:B	=LIN1+OMA1/21.5
	=LIN1+FIELD-21U1:Z	=LIN1+OMA1/21.8

=LIN1+FIELD-31U2

Properties

Trade	Electrical engineering
Function text (automatic)	PC - lenovo
Technical characteristics	PC lenovo

Part properties

Parts: Lenovo.PC Variant: 1

Part type	Component
Height	0,00 mm
Width	0,00 mm
Depth	0,00 mm
Weight	0,00 kg

References

Parts list	Parts list	
Summarized parts list	Summarized parts list	
Multi-line	=LIN1+FIELD-31U2	=LIN1+OMA1/31.0

=LIN1+FIELD-31U2-LAN

Properties

Trade	Electrical engineering

References

Multi-line	=LIN1+FIELD-31U2-LAN:2	=LIN1+OMA1/31.1

=LIN1+FIELD-30XC1

Properties

Trade	Electrical engineering
Function text (automatic)	RTD1

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Plug overview	Plug overview	
Multi-line	=LIN1+FIELD-30XC1:1	=LIN1+OMA1/30.a.1
	=LIN1+FIELD-30XC1:2	=LIN1+OMA1/30.a.1
	=LIN1+FIELD-30XC1:3	=LIN1+OMA1/30.a.1
	=LIN1+FIELD-30XC1:4	=LIN1+OMA1/30.a.1

=LIN1+FIELD-30XC2

Properties

Trade	Electrical engineering
Function text (automatic)	RTD2

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Plug overview	Plug overview	
Multi-line	=LIN1+FIELD-30XC2:1	=LIN1+OMA1/30.a.3
	=LIN1+FIELD-30XC2:2	=LIN1+OMA1/30.a.4
	=LIN1+FIELD-30XC2:3	=LIN1+OMA1/30.a.4
	=LIN1+FIELD-30XC2:4	=LIN1+OMA1/30.a.4

=LIN1+FIELD-30XC3

Properties

Trade	Electrical engineering
Function text (automatic)	RTD3

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Plug overview	Plug overview	
Multi-line	=LIN1+FIELD-30XC3:1	=LIN1+OMA1/30.a.6
	=LIN1+FIELD-30XC3:2	=LIN1+OMA1/30.a.6
	=LIN1+FIELD-30XC3:3	=LIN1+OMA1/30.a.6
	=LIN1+FIELD-30XC3:4	=LIN1+OMA1/30.a.6

=LIN1+FIELD-30XC4

Properties

Trade	Electrical engineering
Function text (automatic)	RTD4

Part properties

Parts: Variant:

Part type	Undefined

References

Plug diagram	Plug diagram	
Plug overview	Plug overview	
Multi-line	=LIN1+FIELD-30XC4:1	=LIN1+OMA1/30.a.8
	=LIN1+FIELD-30XC4:2	=LIN1+OMA1/30.a.8
	=LIN1+FIELD-30XC4:3	=LIN1+OMA1/30.a.9
	=LIN1+FIELD-30XC4:4	=LIN1+OMA1/30.a.9