

— CONTR@LS · BI-LEVEL

LDLL-E2/MSP/W

Occupancy Sensor | Indoor | PIR | Eclipse-II | 1-Pin

Compact indoor PIR occupancy sensor designed for fixture integration. Eclipse-II series with 1-pin audio jack connection. Low-profile design for linear and strip luminaire applications.

TECHNICAL SPECIFICATIONS

Detection Technology	Passive Infrared (PIR)	IP Rating	IP65
Input Voltage	10-15Vdc	Certification	UL Listed
Max Mounting Height	10FT (3m)	Connector	1-Pin Audio Jack
Detection Range	Fixed	Commissioning	N/A
Hold Time	Factory Set	Operating Temp	-20°C to +50°C
Daylight Harvesting	No	Finish	White
Stand-by Dimming	N/A	DLC / NLC	No (Standalone)

FEATURES

- Passive infrared motion detection
- Compact Eclipse-II form factor
- Low-profile fixture integration
- Automatic on/off switching
- Sealed optical lens
- IP65 rated for damp locations
- 1-pin audio jack plug-and-play
- No external commissioning required
- Compatible with low-voltage drivers
- Maintenance-free operation

COMPATIBLE LUMINAIRE FAMILIES

lampar@RCH (UFO High Bay)

select@RCH (Strips & Wraps)

LV3P (Vapor Tight)

ORDERING INFORMATION

SKU	LDLL-E2/MSP/W
UPC	819313024289
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	contr@LS
Platform	Bi-Level
Manufacturer	Archipelago Lighting Group

PIR

DETECTION

10FT

MAX HEIGHT

IP65

IP RATING

10-15Vdc

INPUT VOLTAGE

UL

CERTIFICATION

Bi-Level

PLATFORM