



— CONSTANT · MID-POWER · J-BOX QUICK INSTALL

CRC6-EM24/JBS/W

MPN · BLD-CRC6-EM24-W

⚠ INFERRED SPECS — PENDING VERIFICATION

Quick-Install J-Box Emergency LED Driver — 6" Single-Cover White

24W constant-power emergency LED driver with integrated 6" round junction-box mount and single-aperture white cover. Designed for rapid remote deployment in occupied buildings. White cover for standard ceiling finishes.

KEY FEATURES

- Universal 120 VAC input — one driver, every building voltage
- Operating range 41°F to 122°F
- Constant brightness for 90 min — no dimming as battery drains
- Self-protecting battery — overcharge / over-discharge / short-circuit
- Test switch with red LED status indicator
- UL 924 listed for code-compliant emergency egress
- 5-year limited warranty on driver and battery
- CSA C22.2 No.141 + CEC Title 20 compliant

PERFORMANCE

Emergency Output Power	24 W
Emergency Runtime	90 min
Output Type	Constant power
Recharge Time	24 hours
Battery Type	LiFePO4
Battery Charging Current	0–250 mA

CONSTRUCTION

J-Box Compatibility	6" round/octagonal
Cover Finish	White
Operating Temperature	41°F to 122°F
Storage Temperature	158°F max
Location Rating	Dry, damp
Warranty	5-year limited

ELECTRICAL

Input Voltage	120 VAC
Input Frequency	50 / 60 Hz
Input Current	200 mA max
Input Power	12 W max
Output Voltage	DC 190 V
Output Power	24 W max

COMPLIANCE

Safety Listings	UL 924 · CSA C22.2 No.141
Energy Compliance	CEC Title 20
Installation Listing	UL listed for J-Box install
Compatibility	plano RCH series

INSTALLATION

Mounting Type	J-Box integrated (6" white cover)
Test Switch	Test switch with indicator light
Wire Type	UL 2464, 24 AWG, 300 V, 80°C
Wire Length	550 mm (21.65")
Installation	Quick-install (no fixture removal)
Power Factor	>0.50

COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

plano RCH

See full Application Quick Guide for sensor & controller pairings.

ORDERING INFORMATION

CRC6-EM24/JBS/W

Standard 24 W driver

Vendor MPN

BLD-CRC6-EM24-W (BillDa)

24W

OUTPUT POWER

90 min

EGRESS RUNTIME

120 VAC

INPUT

6" J-Box

QUICK-INSTALL

White

COVER FINISH

UL 924

LISTED