



— CONSTANT · MID-POWER · J-BOX QUICK INSTALL

## CRCU-EM24/JBM

MPN · BLD-CRCU-EM24

⚠ INFERRED SPECS — PENDING VERIFICATION

### Quick-Install J-Box Emergency LED Driver — Universal Mount

24W constant-power emergency LED driver with integrated junction-box mount. Designed for rapid remote deployment in occupied buildings and ceiling-mount emergency-lighting applications. Eliminates complex wiring and reduces labor cost vs. discrete driver + battery + J-Box assemblies.

#### KEY FEATURES

- Universal 120 VAC input — one driver, every building voltage
- Operating range 41°F to 122°F
- Constant brightness for 90 min — no dimming as battery drains
- Self-protecting battery — overcharge / over-discharge / short-circuit
- Test switch with red LED status indicator
- UL 924 listed for code-compliant emergency egress
- 5-year limited warranty on driver and battery
- CSA C22.2 No.141 + CEC Title 20 compliant

#### PERFORMANCE

|                          |                |
|--------------------------|----------------|
| Emergency Output Power   | 24 W           |
| Emergency Runtime        | 90 min         |
| Output Type              | Constant power |
| Recharge Time            | 24 hours       |
| Battery Type             | LiFePO4        |
| Battery Charging Current | 0–250 mA       |

#### CONSTRUCTION

|                       |                                |
|-----------------------|--------------------------------|
| J-Box Compatibil...   | 4", 5", 6", 7" round/octagonal |
| Max. Application      | 200 W                          |
| Operating Temperature | 41°F to 122°F                  |
| Storage Temperature   | 158°F max                      |
| Location Rating       | Dry, damp                      |
| Warranty              | 5-year limited                 |

#### ELECTRICAL

|                 |            |
|-----------------|------------|
| Input Voltage   | 120 VAC    |
| Input Frequency | 50 / 60 Hz |
| Input Current   | 200 mA max |
| Input Power     | 12 W max   |
| Output Voltage  | DC 190 V   |
| Output Power    | 24 W max   |

#### COMPLIANCE

|                      |                             |
|----------------------|-----------------------------|
| Safety Listings      | UL 924 · CSA C22.2 No.141   |
| Energy Compliance    | CEC Title 20                |
| Installation Listing | UL listed for J-Box install |
| Compatibility        | plano RCH series            |

#### INSTALLATION

|                |                                    |
|----------------|------------------------------------|
| Mounting Ty... | J-Box integrated (universal cover) |
| Test Switch    | Test switch with indicator light   |
| Wire Type      | UL 2464, 24 AWG, 300 V, 80°C       |
| Wire Length    | 550 mm (21.65")                    |
| Installation   | Quick-install (no fixture removal) |
| Power Factor   | >0.50                              |

#### COMPATIBILITY · CONSTANT APPLICATION QUICK GUIDE

plano RCH

See full Application Quick Guide for sensor & controller pairings.

#### ORDERING INFORMATION

|               |                        |
|---------------|------------------------|
| CRCU-EM24/JBM | Standard 24 W driver   |
| Vendor MPN    | BLD-CRCU-EM24 (BillDa) |

24W  
OUTPUT POWER

90 min  
EGRESS RUNTIME

120 VAC  
INPUT

J-Box  
QUICK-INSTALL

plano RCH  
COMPATIBLE

UL 924  
LISTED