

```

subroutine adummy
c,,,,, cliché storage set up here

```

```

cliche param
parameter (lzx=34, jrx=60, lzx2=lzx-2 )
parameter ( ltbw=2*lzx-1 )
parameter (kxp=(lzx-2)*(jrx-2), lbw=lzx-1 )
parameter (nplt=3000, nps=100 )
parameter (lxpf=4*(lzx-2),nfourxf=150)
parameter (lxpg=2*lzx2)
parameter (ksim=51)
endcliche
cliche fstor
use param
common/fun/f1(lzx,jrx),f2(lzx,jrx),f3(lzx,jrx),f4(lzx,jrx)
c ,f5(lzx,jrx),f7(lzx,jrx),
c g1(lzx,jrx),g2(lzx,jrx),g3(lzx,jrx),g4(lzx,jrx)
c ,swg1,swg2,swg3,swg4

```

```

common/equil/b(lzx,jrx),rho(lzx,jrx),qub(lzx,jrx),r(lzx,jrx)
c ,phi(lzx,jrx),yyy(lzx,jrx),xxx(lzx,jrx),qv(lzx,jrx)
common/pertur/xloo(kxp),xlo(kxp),xlo1(kxp)
c ,xroo(kxp),xro(kxp),xro1(kxp)
endcliche

```

```

cliche matrix
use param
common/coeff/a1(kxp,9),a2(kxp,9),a3(kxp,9),b1(kxp,3)
c ,rhs1(kxp),rhs2(kxp)
c,,,,,unnamed common for dynamic memory expansion
common ww(1), ww(1)
endcliche

```

```

cliche const
use param
common/title/aname(5)
common/con/gam1,gam2,lx,jx,mm,lxjp,kxx,nmax,lmax,lsw,lhbw
c ,fac1,fac2,bias,du,dv,dt,ndlag,ex0,b0,rho0,ex1,f11,f1zx,fj1
c ,fjrx,kplot,npm,fps1,fz,fu,fv,azm,apsim,u0,v0,amass
c ,fourpl,omegst,omegr,omegexb,flr,sf6,sf8,kplotm,kzs,zedge
c ,cpuo,cio,syso,valfk,xu,xv,n,pi,vw,pslw,dvin,dvout
common/contm/
c psi0rel,psi1rel,psi2rel,z1rel,z2rel,z3rel,z0rel,nslosh,bmg
c ,ncenter,pslosh,pcenter,rp,ztrans,ltrans,bm,ltran,ztran,rp1
c ,bcen,pring,epsp,phicen,phiplg,kin,xpot,ypot,wpot,pfudge,rpx
c ,phice,phipl,betslsh,betcent,z0,z1,z2,z3,z4,psi1,psi2,psi0
c ,betcone,betslse,psloshe,pcentee,bmax,alsi,bm1,psls1,cold
c ,p2wide,psi3rel,psi3,p1max,bv0,bv3,bv4,bceng,psloshin,psloshen
c ,nsloshin,pxp1,pxp2,p3a,p3b,p3c,p3d,psim,pe10,ael,be1,cel
c ,psi0erel,psi0e,psime,p2ewide,wp2e,p2floor,p1floor,p2flag
c ,fring, long, no3d, no1d, dphi
common/mesh/psi(jrx),z(lzx),u(lzx),v(jrx),dpsi(jrx),dz(lzx)
c ,vpsi(jrx),uuz(lzx),vpsi1(jrx),uuzh(lzx)
common/graf/ xrtime(nplt),xrspz(lzx,nps),xrsppsi(jrx,2*nps)
c ,time(nplt),xflute(lzx,nps)
common/curvco/cr,lb,rw,beta0,delrho,stable,en0,cee,r0,
c echarg,omeg1,omeg2,er1,basang,zol,dtnel,p0,omeg0
c ,omana1,omana2,groana,theta0
common/tmcon/h12(lzx),h1(lzx),h34(lzx),abp(lzx),bbp(lzx)
c ,cbp(lzx),abf(lzx),bbf(lzx),cbf(lzx),hp3(jrx),hp12(jrx)

```

```

c ,htrans(izx),abq(izx),bbq(izx),cbq(izx),h56(izx),abr(izx)
c ,bbr(izx),cbr(izx),betring,hp0(jrx),hpm(jrx),hpm0(jrx),hflr(jrx)
c ,commun/tmfield/bvac(izx),dbvdz(izx),d2bvdz2(izx),dp1dpsi(jrx)
c ,p1(jrx),p1k(ksim,jrx),hpk12(ksim),hpk0(ksim),deli1(ksim)
c ,deli2(ksim),deli3(ksim),deli4(ksim),rzz(izx,jrx),dbdpsi(izx,jrx)
c ,phi1(izx),phi2(izx),pperp(izx,jrx),ppar(izx,jrx),dflute3(izx)
c ,qubv(izx,jrx),p2(jrx),dp2dpsi(jrx),dflute1(izx),dflute2(izx)
c ,flute1(jrx),flute2(jrx),flute3(jrx),p2k(ksim,jrx),deli5(ksim)
c ,pperps(izx,jrx),errprp(izx,jrx),errprl(izx2,jrx-1)
c ,pperp0(izx,jrx),epsi(izx,jrx),omeg1wkb(jrx),omeg2wkb(jrx)
c ,gamwkb(jrx),dflute4(izx),rhoave(jrx),xxxave(jrx),yyyave(jrx)
c ,p2t(jrx),dp2dpst(jrx),p3(jrx),dp3dpsi(jrx),hpkm(ksim)
c ,hpkme(ksim),droave(jrx),droterm(izx)
c ,common/forced/nfour,nfourx,nfourmax,nfourp,jfour,ixp,iocv

real lb,ltrans,ltran,nslosh,ncenter,nsloshin
endcliche

return
end

```

c..... the main routine

c..... notice of 4/8/82, this version runs correctly for lsw=1, and  
c..... runs correctly for lsw=-1 ,

c.....5/12/82, flora runs testcase 1 , 0 beta, 0 pressure, homogeneous  
c..... plasma, correctly,

c..... flora1 transforms variables z,psi to u,v which are always equally  
c..... spaced, transformation:  $z=au*u**xu$ , and  $psi=apsi*v**xv$ , where  
c.....  $zmax=umax$ ,  $psimax=vmax$ , and  $fz*zmax=fu*umax$ ,  $fpsi*psimax=fv*vmax$  ,  
c.....  $fz$ ,  $fu$ ,  $fpsi$ ,  $fv$ , input,  $xu=\ln fz / \ln fu$ ,  $xv=\ln fpsi / \ln fv$  ,  
c.....  $au=umax**(-xx+1)$  ,  $apsi=vmax**(-yy+1)$  ,

c..... flora2 solves test case 2 , rotating rigid rotor stability, ref:  
c..... freidberg and pearlstein, phys fluids 21(7) july 1978 1207

c.....flora4 includes background constant density, enbar ( as does flora3 ),  
c..... and kzs switch which when set to zero, generates initial perturbations  
c..... independent of z in random spatial generator (ex0=1.) ,

c..... flora5  
c..... is vectorized version of flora4,(calls rightvec instead of  
c..... right ), also has timing routine from b. langdon (requires  
c..... bzohar loaded as a binary ),  
c..... insert cliché storage here

c..... flora7 is mod. flora5, with psi stretching function  
c..... exactly centered in amat. (flora5 used linear interpolation  
c..... to get  $vpsi(j+1/2)$ ). Also revised diagnostic plots included.

c.....flora12 is flora11 (rigid rotor with corrected equil. and  
c..... corrected curvature terms (flora10)) with fourier mode analyses  
c..... added ( using cpft and rpft) and data for zed post processing.  
c.....additional input data: jfour (v index at which xr is analyzed in  
c.....z ), nfourp ( analyze xr every nfour'th time step ),nfourmax

```

c..... (number of times the buffer is read to the history file), note
c..... xr is extended a factor of 4 to look like a periodic full wave
c..... for cpft. If jfour is input 0, code sets it to jx/4 ,
c
c.....flora13 is flora12 with curvature driven flute mode equilibrium
c.....(equilrot replaced by equilcur, rigidcon replaced by curvecon )

c.....floralm, tandem mirror equilibrium
c
c.....flortm1, tandem mirror equilibrium, with 3-d plot of equilib,
c      quantities added. ( uses tv80 and graflib )

c.....flortex, tandem mirror equilb, with corrections to flortm1. In-
c..... put switches swg1, swg2, swg3, swg4 added,

c.....flortm2, like flortex with revised electron ring, a la D'ippolito
c.....(e-ring pperp in b field only, and additional term in curvature
c..... drive ),

c.....flortm3, like flortm2 with corrections to pressure normalization,
c..... and additional diagnostics, ( 3-d plots of curvature drive-e ring
c..... term, and perp. pressure balance check ) , also 3-d plots of
c..... pparallel pressure check, and e-psi ( $=-d\phi/d\psi$  ) , Phi2 modified
c..... to  $= 1.-(\psi/\psi_3)**ypot$  ,

c.....flortm4, modified plasma pperp with addition of p3(j) to give
c..... a positive slope near the center,

c.....flortm5, modified p1 in flortm4 to be two functions, pe1 and
c..... pe2, joined at psime with equal slope and value, pe1=ae1+be1*(
c..... psi/psime)+ce1*(psi/psime)**2, and pe2=.5*(1-tanh((psi-psi0e)/p2ewide))
c
c..... flortm6, modified flortm5 as follows: for p2(psi)le. to p2flag ( an
c..... input value), p2 set to p2floor (an input value) and p1 set to
c..... p1floor (an input value). Long-thin ering option added. This modifies
c..... the dependence of ering pperp to look longer (by changing abf, bbf, cbf)
c..... if long ( an input value ) = 1, otherwise leaves pperp of ring un-
c..... changed. Plot output options, no1d=1, prevents graflib plots, no3d=1
c..... prevents tv80lib 3d plots.
c

```

```

      use param
      use fstor
      use matrix
      use const

```

```

      data tim/1.e6/
      integer tallyb(2000b)
      common / q8iocs/iocf(10:15)
      common/pic100/npete
      data itally/1/

```

```

c.....call link call here
      call link('unit59=terminal,unit2=(inflt6,open),unit3=(output,
c create) //')

```

```

      if(itally.gt.0) then
      do 200 ii=1,15
200   if(iocf(ii).eq.0)go to 210
      ii=0

```

```

210  loctally=11
    loctally=14
    if(loctally,eq,0)go to 299
    call timer(loctally,'ztally00',tallyb,2000b,florativ,1)
299  itally=-1
    endif
    isw=1
    if(izx.gt,jrx)isw=-1
    jtbw=.5*(1+isw)*itbw+.5*(1-isw)*(2*jrx-1)
    ihbw=.5*(1+isw)*ibw+.5*(1-isw)*(jrx-1)
    nn=jtbw*kxp
    nn1=jtbw+kxp
    call memory(ww,nn-1)
    call memory(ww1(nn),nn1)
    namelist/noplot/no1d,no3d
    call ddi(noplot,2,0,1)
    if(no1d,ne,1)call pstart(dev,4rplot,1,'box u21$',1)
c    npete=1
    if(no1d,ne,1)call p100
    call input
    call inputtm
c    call rigidecon
c    call curvecon
    call grid
    call constant
    call tmcon2
    call equiltm
c    call equilrot
c    call equilcur
    call fltoll
    call amat
    call comat(ww,jtbw)
    call initial
c.....special version for testing fourier analysis and zed file
c..... maker
    call fourplay
    call fourier
    call mymove(xrol(1),xro(1),kxx)
    call mymove(xiol(1),xio(1),kxx)
c    call mymove(xroo(1),xro(1),kxx)
c    call mymove(xioo(1),xio(1),kxx)
    call banfac(kxp,ihbw,ww,1,-(kxp-1))
    t=0.
    do 100 n=1,nmax
    t=t+dt
    time(n)=t
    fac1=-1./dt
    fac2=1./dt
    do 90 l=0,lmax
    call rightvec
    call zmovewrd(ww1(nn),rhs1,kxx)
    call bansol(kxp,ihbw,ww,1,-(kxp-1),ww1(nn))
    do 10 j=2,jx-1
    kp=1+izxp*(j-2)
    call zmovewrd(xrol,ww1(nn),kxx)
10  continue
    call zmovewrd(ww1(nn),rhs2,kxx)
    call bansol(kxp,ihbw,ww,1,-(kxp-1),ww1(nn))
    do 20 j=2,jx-1
    kp=1+kxp*(j-2)

```

```

      call zmovevrd(xiol,ww1(nn),kxx)
20  continue
      fac1=-.5/dt
90  fac2=.5/dt
      call zmovevrd(xloo,xio,kxx)
      call zmovevrd(xio,xiol,kxx)
      call zmovevrd(xroo,xro,kxx)
      call zmovevrd(xro,xrol,kxx)
c,.... time array
      xrtime(n)=xro(kplot)
      if(mod(n,ndiag).eq.0)call diagno
      if(mod(n,nfourp).eq.0)call fourier
100 continue
      call clsdsk(locv,0)
      call timeused(lcp,lo,lsy)
      cpuo=lcp*tim
      cio=lo*tim
      syso=lsy*tim
      if(nold.ne.1)
c call picsher
      call close(100)
      if(no3d.eq.1)go to 300
      call keep80(1,3)
      call fr80id
      call threed
      call plote
300 continue
      call timend
      call exit(1)
      end
      subroutine constant

c,.... insert storage cliché here
      use param
      use fstor
      use matrix
      use const

      gam1=.25*(3*bias+1)
      gam2=.25*(1-bias)
      ip=.5*(ix-2)
      jp=.5*(jx-2)
      kp1=ip-1+(jp-2)*(ix-2)
      kp2=jp-1+(jx-2)*(ip-2)
      kplot=.5*(1+isw)*kp1+.5*(1-isw)*kp2
      if(kplotm.ne.0)kplot=kplotm
      return
      end

      subroutine curvecon

c,.... calculates constants necessary for curvature driven
c,.... flute mode case.

c,.... insert storage clichés here
      use param
      use const
      real klbsq

```

```

c..... input for curvature driven flute case
      data echarg/4.8e-10/, en0/1.00e+12/, b0/1.e4/, amass/'3.34e-24/
      c , ceo/3.e10/, stable/,4/, fourpi/12.56637/, pi/3.1415926/
      c , delrho/.05/, dtrel/,02/, xm/3.8317/, theta0/1.570796/
      namelist/curve/b0,beta0,delrho,stable,en0,echarg,lb,rw,xm
      c ,zol,dtrel,theta0
      call ddi(curve,2,3,1)
      if(nold.ne.1) call ddo(curve,100,0,1)
      zmax=zol*lb
      p0=beta0*b0**2*.5
      psimax=rw**2*b0*.5
      omeg0sq=b0**2/(en0*amass*lb**2)
      omeg0=sqrt(omeg0sq)
      ag1=1.-2.*delrho/xm**2
      klbsq=0.
      if(kzs.ne.0)klbsq=(pi/(2.*zol))**2
      delomeg=0.
      if(sf8.ne.0)
1 delomeg=stable*((beta0/xm**2-klbsq/mm**2)/(ag1*sf8)+1.-sf6*ag1/
2 sf8)*omeg0sq
      omeg1=omeg0+sqrt(delomeg)
      omeg2=omeg1-2*sqrt(delomeg)
      dt=dtrel/omeg1
      en1=2.*en0*delrho/rw**2
      u(ix)=zmax
      v(jx)=psimax
      du=u(ix)/(ix-1,5)
      dv=v(jx)/(jx-1,5)
      besarg=(xm/rw)
c..... calculate analytic growth rate
      tsf6=tan(theta0*.5)*sf6
      radical=((ag1*mm*tsf6)**2*(omeg1+omeg2)**2-4.*((omeg1*omeg2*ag1
      c *sf8+omeg0sq*beta0/xm**2)*mm**2-klbsq*omeg0sq))
      if(radical.lt.0)go to 5
      root=sqrt(radical)
      omana1=ag1*tsf6*mm*(omeg1+omeg2)*.5+root*.5
      omana2=omana1-root
      groana=0.
      return
5 continue
      omana1=ag1*tsf6*mm*(omeg1+omeg2)*.5
      groana=sqrt(-radical)*.5
      omana2=0.
      return
      end
      subroutine inputtm

c..... calculates grid quantities needed by sub. grid
c..... in floratm version

c..... insert storage cliches here
      use param
      use const
      real klbsq

c.....glossary of input parameters
c      psi0rel..value of psi (in relative units) where plasma pperp
c      profile is half the maximum.
c      p2wide..parameter inversely proportional to "ramp width" of p2
c      psi0erel..realitive value of psi where ering pperp (pe2) is half

```

```

c      the maximum
c      p2ewide,,parameter inversely proportional to "ramp width" of pe2
c      psi1rel,,lower limit of psi where pring =0,
c      psi2,,upper limit of psi where pring=0.
c      z0rel,,axial center of plug
c      z1rel,,axial position of plug inward mirror
c      z2rel,,axial position of plug outboard mirror
c      z3rel,,inner axial position where pring=0,
c      z4rel,,outer axial position where pring=0,
c      nslosh,,peak sloshing ion number density
c      ncenter,,peak center cell ion density
c      betslsh,,peak sloshing ion beta-perp w.r.t. bvac(z0)
c      betcent,,peak center cell ion beta-perp w.r.t. bvac(z=0)
c      betslse,,peak sloshing electron beta-perp w.r.t. bvac(z0)
c      betcene,,peak center cell electron beta-perp w.r.t. bvac(z=0)
c      betring,,peak electron ring beta perp w.r.t. bvac(z0)
c      rp,,plug vacuum mirror ratio
c      ztrans,,begining of center cell transition region
c      ltrans,,transition length
c      bmg,,vacuum mirror peak (approx.) in gauss
c      bceng,,center cell bmax in gauss
c      epsp,,minimum pressure, below which b=bvac
c      phicen,,center cell potential relative to plug ion t perp
c      phiplg,,plug potential relative to plug ion t perp
c      kin,,number of points i n sismsons rule quadratures
c      xpot,,exponent coefficient in center cell potential
c      wpot,,exponent coefficient in plug potential
c      ypot,,power of polynomial in potential psi dependence
c      pxp1,,power of polynomial in e ring pperp(psi) (p1(psi))
c      pxp2,,power of polynomial in e ring pperp(psi) (p1(psi))
c      zmax,,axial end of system in cm.
c      pe10= e ring pperp at psi=0.
c      p2flag,,value of p2 at which p2 is set constant
c      p2floor... constant used in conjunction with p2flag
c      p1floor...constnt for p1 used in conjunction with p2flag

c..... input for tandem mirror equilb.
      data echarg/4.8e-10/, en0/1.00e+12/, b0/1.e4/, amass/3.34e-24/
c      , cee/3.e10/, stable/.4/, fourpi/12.56637/, pi/3.1415926/
c      , xpot/1./, ypot/2./, wpot/2./, kin/5/psi1rel/2./, psi2rel/1.5/
c      , psi0rel/.50/, zmax/100./, z1rel/.5/, z2rel/1./, z0rel/.75/
c      , z3rel/.625/, z4rel/.875/, ztrans/.4/, ltrans/.05/, p2ewide/.1/
c      , bmg/1.e4/, bceng/1.e3/, nsloshin/2.e13/, ncenter/1.e13/,
c      , betslsh/.25/, betcent/.10/, rp/4./, epsp/1.e-6/, rp1/2./
c      , phicen/.1/, phiplg/.1/, betcene/.1/, betslse/.1/
c      , dt/1.e-5/, pfudge/0./, cold/1.e-5/, betring/0./, psi3rel/1.05/
c      , pxp1/2./, pxp2/2./, safe/.9/, pe10/0./, psi0erel/.5/, p2ewide/.2/
c      , p2floor/0./, p1floor/0./, p2flag/1.e-3/, fring/.9/, long/1/, no3d/0/
c      , no1d/0/, dphi/0./
      namelist/curve/echarg, lb, rw, xm, rw1
c      , zmax, dt, theta0, pfudge
c      , psi0rel, z1rel, z2rel, z0rel, nsloshin, cold, z3rel, z4rel
c      , ncenter, betslsh, betcent, rp, ztrans, ltrans, bmg, rp1
c      , bceng, epsp, phicen, phiplg, kin, xpot, ypot, wpot, betcene, betslse
c      , betring, psi1rel, psi2rel, p2ewide, psi3rel, pxp1, pxp2, safe, pe10
c      , p2ewide, psi0erel, p2floor, p2flag, p1floor, fring, long, dphi
      call ddi(curve, 2, 3, 1)
      if(no1d.ne.1)then
      call pframe
      call p100

```

```

        call ddo(curve,100,0,1)
        end if
c.....transform input z into physical units
        z0=z0rel*zmax
        z1=z1rel*zmax
        z2=z2rel*zmax
        z3=z3rel*zmax
        z4=z4rel*zmax
        ztran=ztrans*zmax
        ltran=ltrans*zmax
        bm=bmg/sqrt(4.*pi)
        bcen=bceng/sqrt(4.*pi)
c..... generate zmax, psimax, u(ix),v(jx), du, dv
        asq=.25/((2.*rp)**(2./3.)-1.)*(z2-z1)**2
        argt1=+(z1-ztran)/ltran
        bv0=bm*(1./(1.+(z0-z1)**2/asq)**1.5+1./(1.+(z0-z2)**2/asq)
c **1.5)
        bmax=bm*(1.+1./(1.+(z1-z2)**2/asq)**1.5) +bcen*.5*
c (1.-tanh(argt1))
        bv4=bm*(1./(1.+(z1)**2/asq)**1.5+1./(1.+(z2)**2/asq)**1.5)
        psimax=rw**2*bmax*.5
        psiw=rw1**2*bmax*.5
        psi0=psimax*psi0rel
        psi0e=psimax*psi0erel
        psi3=psimax*psi3rel
        psi1=psimax*psi1rel
        psi2=psimax*psi2rel
        v(jx)=psimax
        u(ix)=zmax
        du=u(ix)/(ix-1.5)
        dv=v(jx)/(jx-1.5)
c.....transform input constants from relative to physical units
        pmag0=(bv0)**2*.5
        pmag1=(bv4+bcen)**2*.5
        psloshin=(betslsh)*pmag0
        pcenter=(betcent)*pmag1
        psloshen=betslse*pmag0
        pcentee=betcene*pmag1
        pring=betring*pmag0
        phice=phicen*psloshin/(nsloshin*echarg)
        phipl=phiplg*psloshin/(nsloshin*echarg)
c.....calculate maximum p1(psi)
        psidif=psi2-psi1
        p1max=(pxp1*psidif/((pxp1+pxp2)*psi1))**pxp1*(pxp2*psidif/
c ((pxp1+pxp2)*psi2))**pxp2
c.....check that kin is not too big
        ksimp=ksim
        if(kin.gt.ksimp)then
            kin=ksimp
            write(59,200)kin
200    format('kin initially too large, reduced to',i4)
            end if
c..... check that kin is odd for simpsons quadratures
        kch=mod(kin,2)
        if (kch.eq.0)then
            kin=kin-1
            write(59,201)kin
201    format('kin initially even, changed to',i4)
            end if
c..... adjust epsp to accomodate zero pressure case

```



```

      epsp=epsp*(1.e-4+psloshin+pcenter)/(1.e-8*epsp+psloshin+pcenter)
c.....check that bcen and betcen are physically consistent
      asq=.25/((2.*rp)**(2./3.)-1.)*(z2-z1)**2
      bv0=bm*(1./(1.+(z0-z1)**2/asq)**1.5+1./(1.+(z0-z2)**2/asq)
      c**1.5)
      argt3=(z3-ztran)/ltran
      bv3=bm*(1./(1.+(z3-z1)**2/asq)**1.5+1./(1.+(z3-z2)**2/asq)
      c**1.5)+bcen*.5*(1.-tanh(argt3))
      rpx=bmax/(bv0)
      rp3=bv3/bv0
      afac=(rp*(1.-1./rp**2))**2/bm**2
      afac1=(rp*(1.-1./rp3**2))**2/bm**2
      tcon6=pring/((1.-1./rp3**2)**2)
      tmin=afac*(bcen+bv4)**2
      if(tmin.le.betcent+betcene)then
      bcen1=sqrt((betcent+betcene)/afac)-bv4
      tmine=tmin-betcene
      write(59,210)bcen1,tmine
210  format('initial central cell beta and b are inconsistent for',
c ' equilibrium',/'either increase bcen to more than',e14.6/
c 'or decrease betcent to less than',e14.6/'use namelist',
c ' data format')
      namelist/better/betcent,bcen
      read(59,better)
      pcenter=betcent*pmag0
      end if
c..... check plug ion beta and e ring beta
      tmin1=afac*bv0**2
      if (tmin1.le.(betslsh+betslse))then
      tbetsl=tmin1-betslse
      tbetr=(-betslsh+tmin1)
      delbet=betslsh+betslse-tmin1
      write(59,220)delbet,tbetsl,tbetr
      namelist/fix/betslsh,betslse
220  format('the sum of (betslsh+betslse) is too large by',
c e14.6/'either decrease betslsh to',e14.6/'or decrease
c betslse to',e14.6/'or something (use namelist data format)')
      read(59,fix)
      psloshin=betslsh*pmag0
      psloshen=betslse*pmag0
      end if

c..... check betring in plug
      if(tcon6.ge.(safe*.5*bv0**2))then
      ratio=safe*.5*bv0**2/tcon6
      pring=pring*ratio
      ratinv=1./ratio
      write(59,231)ratinv,pring
231  format('pring was too large by a factor ('e14.6,') , and was',
c ' reduced to ',e14.6 )
      end if

c..... check that rp1 is less than rpx
      if(rp1.ge.rpx)then
      rp1t=rp1
      rp1=.5*rpx
      write(59,230)rp1t,rpx,rp1
230  format('rp1 ('e12.6,') was larger than rpx ('e12.6,') , and was',
c ' reduced to ',e12.6 )
      end if

```

```

end
subroutine tmcon2

c..... calculates equilibrium quantities for tandem mirror

c..... insert storage cliches here
use param
use const
real klbsq

c..... calculate heaveside step functions h12, h1, h34
call bcast(h12(1),0.,ix)
call bcast(h1(1),0.,ix)
call bcast(h34(1),0.,ix)
call bcast(htrans(1),0.,ix)
do 2 i=1,ix
  if(z(i).ge.z1.and.z(i).le.z2)h12(i)=1.
  if(z(i).le.z1)h1(i)=1.
  if(z(i).ge.ztran)htrans(i)=1.
2  if(z(i).ge.z3.and.z(i).le.z4)h34(i)=1.

  psim=psi0*(1.-p2wide)
  psime=psi0*(1.-p2ewide)
c..... calculate heaveside step functions hp0(j), hp3(j) and hp12(j)
call bcast(hp12(1),0.,jx)
call bcast(hp3(1),0.,jx)
call bcast(hp0(1),0.,jx)
call bcast(hpm(1),0.,jx)
call bcast(hpme(1),0.,jx)
do 4 j=1,jx
  if(psi(j).le.psi0)hp0(j)=1.
  if(psi(j).le.psi3)hp3(j)=1.
  if(psi(j).le.psim)hpm(j)=1.
  if(psi(j).le.psime)hpme(j)=1.
4  if(psi(j).ge.psi1.and.psi(j).le.psi2)hp12(j)=1.

c..... calculate vacuum b field (bvac) and derivatives dbv/dz, d2bv/dz2
asq=.25/((2.*rp)**(2./3.)-1.)*(z2-z1)**2
bv0=bm*(1./((1.+(z0-z1)**2/asq)**1.5+1./((1.+(z0-z2)**2/asq)
c**1.5)
do 5 i=1,ix
  eb1=(z(i)-z1)/asq
  eb2=(z(i)-z2)/asq
  fb1=sqrt(1.+eb1*(z(i)-z1))
  fb2=sqrt(1.+eb2*(z(i)-z2))
  argt=(z(i)-ztran)/ltran
  dbvdz(i)=-3*bm*(eb1/fb1**5+eb2/fb2**5)-bcen*.5**1
c tanh(argt)**2)/ltran
  d2bvdz2(i)=-3*bm*(1./(asq*fb1**5)+1./(asq*fb2**5)-eb1**2*5/
c fb1**7-eb2**2*5/fb2**7)+bcen*tanh(argt)*(1.-tanh(argt)**2)/
c ltran**2
5  bvac(i)=bm*(1./fb1**3+1./fb2**3)+bcen*.5*(1.-tanh(argt))
  argt3=(z3-ztran)/ltran
  bv3=bm*(1./((1.+(z3-z1)**2/asq)**1.5+1./((1.+(z3-z2)**2/asq)
c**1.5)+bcen*.5*(1.-tanh(argt3))
  rp3=bv3/(1+bv0)
  bm1=rp1*(bv0)
  alsit=((1.-1./rp1**2)/(1.-1./rp3**2)*(rp1/rp3))**2
  alsi=alsit+.5*(1.-alsit)*pfudge

```

```

c.....calculate heaveside function h56(i) for second component of
c..... sloshing pperp
      do 10 i=1,ix
        eb2=(z(i)-z2)/asq
        if(z(i).gt.z1.and.z(i).lt.z2.and.bm1.ge.bvac(i))
          c h56(i)=1.
10      continue

c..... calculate pressure coeff, including electron ring (pr)
      con1=1./((1.-1./rpx**2)**2*bmax**4)
      con2=con1*(-2*bmax**2)
      con3=-.5*con2*bmax**2
      con4=pring/((1.-1./rp3**2)**2*bv3**4)
      con5=con4*(-2*bv3**2)
      con6=-.5*con5*bv3**2
      don1=1./((1.-1./rp1**2)**2*bm1**4)
      don2=don1*(-2*bm1**2)
      don3=-.5*don2*bm1**2

c..... calculate constants for p3 pressure component
      data p30/.01/
      wp2=p2wide*.5*psi0
      wp2e=p2ewide*.5*psi0e
      wp3=wp2/psim
      psi0r=psi0/psim
      p3b=p30
      p3c=.5*(1.-(tanh(2.))**2)/wp3-p3b*p2wide*(2.-p2wide)
      c *.5/p2wide
      p3d=-(p3b+2.*p3c*psi0r)/(3.*psi0r**2)
      p3a=-(p3b*psi0r+p3c*psi0r**2+p3d*psi0r**3)

c.....calculate constants for pe1
      g2p=-.5*(1.-(tanh(-2.))**2)/wp2e
      g2f=.5*(1.-tanh(-2.))
      ae1=pe10
      ce1=psime*g2p-g2f+ae1
      be1=2.*(g2f-ae1)-psime*g2p

c.....readjust peak plug pressure for sloshing
      rtemp=(bm1/bmax)**2
      rpxi2=1./rpx**2
      ter1=(rtemp-rpxi2)**2
      ter2=(1.-rpxi2)**2
      bstr2=bmax**2*(-ter1+alsi*rtemp*ter2)/(-ter1+alsi*ter2)
      pfloat=((con1-don1*alsi)*bstr2**2+(con2-don2*alsi)*bstr2
      c +con3-don3*alsi)*(1.+p3a)
      pslosh=psloshin/pfloat
      psloshe=psloshen/pfloat
      nslosh=nsloshin/pfloat
      psls1=pslosh+psloshe
      pcon1=pcenter+pcentee
      do 6 i=1,ix
        eon1=con1-don1*alsi*h56(i)
        eon2=con2-don2*alsi*h56(i)
        eon3=con3-don3*alsi*h56(i)
        abf(i)=con4*h34(i)
        bbf(i)=con5*h34(i)
        cbf(i)=con6*h34(i)

      abp(i)=eon1*(psls1*h12(i)+pcon1*h1(i))
      bbp(i)=eon2*(psls1*h12(i)+pcon1*h1(i))
      cbp(i)=eon3*(psls1*h12(i)+pcon1*h1(i))

```

```

abr(i)=eon1*(nslosh*h12(i)+ncenter*h1(i))
bbr(i)=eon2*(nslosh*h12(i)+ncenter*h1(i))
cbr(i)=eon3*(nslosh*h12(i)+ncenter*h1(i))

abq(i)=eon1*(pslosh*h12(i)+pcenter*h1(i))
bbq(i)=eon2*(pslosh*h12(i)+pcenter*h1(i))
6   cbq(i)=eon3*(pslosh*h12(i)+pcenter*h1(i))
c..... constants for ering pperp(b) long-thin
    if(long.eq.0)go to 21
    bstr=bmax*fring
    faccb=1./(bmax**2-bstr**2)**2
    do 20 i=1,ix
        if(bvac(i).ge.bstr)then
            abf(i)=-pring*faccb*h12(i)
            bbf(i)=2.*pring*faccb*h12(i)*bstr**2
            cbf(i)=pring*bmax**2*(bmax**2-2.*bstr**2)*faccb*h12(i)
        else
            cbf(i)=pring*h12(i)
            bbf(i)=0.
            abf(i)=0.
        end if
20   continue
21   continue
    return
    end

subroutine equiltn

c.....equilibrium for tandem mirror electron ring plug

c.....insert storage cliches here
    use param
    use const
    use fstor

    data epsb/1.e-2/, p30/.01/
c..... loop 10, calculate p2 p1 and b and dp2/dpsi and dp1/dpsi
    wp2=p2wide*.5*psi0
    psibar=-be1*.5/ce1
    p1max=ae1+be1*psibar+ce1*psibar**2

    do 10 j=1,jx
        psir=psi(j)/psim
        psire=psi(j)/psime
        pe1=(ae1+be1*psire+ce1*psire**2)*hpme(j)
        pe2=.5*(1.-tanh((psi(j)-psi0e)/wp2e))*(1.-hpme(j))
        p1(j)=(pe1+pe2)/p1max
        dp1dpsi(j)=(be1+2.*ce1*psire)/(psime*p1max)*hpme(j)-.5*(1.-tanh
c ((psi(j)-psi0e)/wp2e)**2)/(wp2e*p1max)*(1.-hpme(j))
        p2t(j)=(1.-tanh((psi(j)-psi0)/wp2))*.5
        dp2dpst(j)=-.5*(1.-tanh((psi(j)-psi0)/wp2)**2)/wp2
        p3(j)=(p3a+p3b*psir+p3c*psir**2+p3d*psir**3)*hp0(j)
        dp3dpsi(j)=(p3b+2.*p3c*psir+3.*p3d*psir**2)*hp0(j)/psim
        p2(j)=p2t(j)+p3(j)
        dp2dpsi(j)=dp2dpst(j)+dp3dpsi(j)
        hflr(j)=1.

c..... set p2 and p3 constant at large psi
    if (p2(j).le.p2flag)then

```

```

p2(j)=p2floor
p1(j)=p1floor
dp2dpsi(j)=0.
dp1dpsi(j)=0.
hflr(j)=0.
end if
if((p2(j)).lt.epsp)go to 50
do 11 i=1,ix
if(abp(i).eq.0)then
b(i,j)=bvac(i)
go to 11
end if
u1=p2(j)*abp(i)+p1(j)*abf(i)
u2=p2(j)*bbp(i)+.5+p1(j)*bbf(i)
t1=-u2*.5/u1
u3=p2(j)*cbp(i)-bvac(i)**2*.5+p1(j)*cbf(i)
radic=sqrt(t1**2-u3/u1)
bsq1=t1+radic
bsq2=t1-radic
bsq=bsq1
if(t1.gt.radic)bsq=bsq2
b(i,j)=sqrt(bsq)
11 continue
go to 10
c.... b=bvac if p2.lt.epsp
50 do 51 i=1,ix
51 b(i,j)=bvac(i)
10 continue

c.....loop 15, calculate phi, the electric potential
do 15 i=1,ix
arg1=((z(i)-z1)/(z1-z0))**2*(-xpot)*(1.-h1(i))
arg2=wpot*((z(i)-z0)/(z0-z1))**2
15 phi1(i)=phice*exp(arg1)+phipl/cosh(arg2)
c....special phi1 for high mm rotation mode test
do 17 i=1,ix
phi1(i)=phice*(1.-dphi*(1.-h1(i)))
17 continue
do 16 j=2,jx
phi2(j)=(1.-(psi(j)*hp3(j)/psi3)**ypot)*hp3(j)
16 continue
c....loop 20,calculate pperp, ppar and db/dpsi
ppt=1./((1.-1./rp1**2)**2
dter1=(-8./3-4.*(bmax/bm1)**3/3.+4.*(bmax/bm1))/bm1
dter2=-alsi*ppt*dter1*psis1
do 20 i=1,ix
do 20 j=1,jx
if(dter2.eq.0.)dter2=0.
b2=b(i,j)**2
b4=b2**2
dter3=dter2*h56(i)
dter=(4.*abp(i)*bmax**2/3.+2.*bbp(i))*bmax+dter3
ppart=(-abp(i)/3.*b4-bbp(i)*b2+cbp(i)+dter*b(i,j))
ppert=(abp(i)*b4+bbp(i)*b2+cbp(i))
pperte=(abq(i)*b4+bbq(i)*b2+cbq(i))
pperp(i,j)=p2(j)*ppert
ppar(i,j)=p2(j)*ppart
qub(i,j)=(b2+ppar(i,j)-pperp(i,j))/b(i,j)
rho(i,j)=amass*(p2(j)**.5*(abr(i)*b4+bbr(i)*b2+cbr(i))+
c ncenter*col d)

```

```

    fac=b(i,j)*(1.+2.*p1(j)*(2.*abf(i)*b2+bbf(i)))
    fac1=dp1dpsi(j)*(abf(i)*b4+bbf(i)*b2+cbf(i))
    fac2=dp2dpsi(j)*(abp(i)*b4+bbp(i)*b2+cbp(i))
    fac3=p2(j)*(2.*abp(i)*b2+bbp(i))+p1(j)*(2.*abf(i)*b2+bbf(i))
    dbdpsi(i,j)=-(fac1+fac2)/(b(i,j)*(1.+fac3*2.))
    dp2db=b(i,j)*(abp(i)*b2*2.+bbp(i))*2.
    dp2dbe=b(i,j)*(abq(i)*b2*2.+bbq(i))*2.
    dp3db=dp2db-4.*abp(i)*b(i,j)**3/3.-2.*bbp(i)*b(i,j)
c +dter
    qubv(i,j)=(-dp2dpsi(j)*(pperp+ppart)-p2(j)*dp3db*dbdpsi(i,j))
    pharg=psi(j)*hp3(j)
    dphidpsi=phi1(i)*ypot*(pharg/psi3)**(ypot-1.)/
c (-psi3)*hp3(j)
    epsi(i,j)=-dphidpsi
    dpdpsi=pperp*dp2dpsi(j)+p2(j)*dp2dbe*dbdpsi(i,j)
    omegci=echarg*b(i,j)/(amass*cee)
    unit=1./(sqrt(4.*pi))
    omegstr=-unit*b(i,j)*dpdpsi/(omegci*rho(i,j))
    omeggb=unit*pperp*p2(j)*dbdpsi(i,j)/(omegci*rho(i,j))
    omegexb=-cee*dphidpsi
    xxx(i,j)=hflr(j)*rho(i,j)*(omeggb-omegstr+2.*omegexb)*sf6
    yyy(i,j)=-hflr(j)*rho(i,j)*(omegexb+omeggb)*(omegexb-omegstr)*sf8
    ppertr=(abf(i)*b4+bbf(i)*b2+cbf(i))
    pperpsi(i,j)=pperp(i,j)+p1(j)*ppertr
    pperpe(i,j)=p1(j)*ppertr
20    continue

c.....check for negative pressure, and terminate prob. if necessary
    do 25 j=1,jx
    do 25 i=1,ix
        if(pperp(i,j).lt.0.or.pperpe(i,j).lt.0.)then
            write(59,101)
101        format('problem terminated due to negative pressure' )
            call exit(1)
            end if
25    continue

c....calculate diagnostic on perpendicular pressure balance
    do 80 i=1,ix
    do 80 j=i,jx
        errprp(i,j)=(b(i,j)**2-bvac(i)**2+2.*pperpsi(i,j))/bvac(i)**2
80    continue
c....calculate diagnostic on parallel pressure balance
    do 81 j=2,jx
    do 81 i=2,ix-1
        delb=b(i+1,j)-b(i-1,j)
        if(abs(delb).lt.epsb)then
            abar=-abp(i)*5./3.
            bbar=-3.*bbp(i)
            dter3=dter2*h56(i)
            dter4=(4.*abp(i)*bmax**2/3.+2.*bbp(i))*bmax+dter3
            dbar=dter4*2.
            factor=-(abar*b(i,j)**4+bbar*b(i,j)**2+cbp(i)+dbar*b(i,j))
        else
            factor=(ppar(i+1,j)*b(i+1,j)-ppar(i-1,j)*b(i-1,j))
        c /delb
        end if
81    errprl(i-1,j-1)=(pperp(i,j)-2.*ppar(i,j)+factor)/bvac(i)**2*2

c.....cal. r and rzz*r

```

```

do 40 i=1,ix
sum1=0,
sum2=0,
sum3=0,
sum4=0,
sum5=0,
do 40 j=2,jx
dps=dpsi(j)
psib=psi(j-1)
if(j.eq.2)then
dps=psi(2)
psib=0,
end if
if(i.gt.2)go to 31
call bcast(hpk0(1),0,,kin)
call bcast(hpk12(1),0,,kin)
call bcast(hpkm(1),0,,kin)
call bcast(hpkme(1),0,,kin)
do 29 k=1,kin
psik=psib+dps*(k-1)/(kin-1)
if(psi(k).lt.psi0)hpk0(k)=1,
if(psi(k).lt.psim)hpkm(k)=1,
if(psi(k).lt.psime)hpkme(k)=1,
if(psi(k).lt.psi2.and,psik.gt,psi1)hpk12(k)=1,
29 continue
c..... cal. p1 (p1k) at intermediate points in dps1 interval
do 30 k=1,kin
psik=psib+dps*(k-1)/(kin-1)
psikr=psik/psim
psikre=psik/psime
p1ek=(a01+b01*psikre+c01*psikre**2)*hpkme(k)
p2ek=.5*(1.-tanh((psik-psi0e1)/wp2e1))*(1.-hpkme(k))
p1k(k,j)=(p1ek+p2ek)/p1max
p3k=(p3a+p3b*psikr+p3c*psikr**2+p3d*psikr**3)*hpk0(k)
p2k(k,j)=(1.-tanh((psik-psi0)/wp21))*0.5 +p3k
30 continue
31 continue
do 32 k=1,kin
if(p2k(k,j).le,p2flag)then
p2k(k,j)=p2floor
p1k(k,j)=p1floor
end if
if((p2k(k,j)).le,eps,or,abp(i).eq.0) then
bk=bvac(i)
else
u1=p2k(k,j)*abp(i)+p1k(k,j)*abf(i)
u2=p2k(k,j)*bbp(i)+p1k(k,j)*bbf(i)+.5
t1=-u2*.5/u1
u3=p2k(k,j)*cbp(i)+p1k(k,j)*cbf(i)-bvac(i)**2*.5
radic=sqrt(t1**2-u3/u1)
bsq1=t1+radic
bsq2=t1-radic
bsq=bsq1
if(t1.gt,radic)bsq=bsq2
bk=sqrt(bsq)
end if
capf=1.+2.*p1k(k,j)*(2.*abf(i)*bk**2+bbf(i))+2.*p2k(k,j)*
c (2.*abp(i)*bk**2+bbp(i))
deli1(k)=1./bk
deli2(k)=1./(bk**3*capf)

```

```

        del13(k)=del12(k)/(capf*bk**2)
        del14(k)=p1k(k,j)/(capf*bk)**3
        del15(k)=p2k(k,j)/(capf*bk)**3
32      continue
        call simps(del11,dcapi1,kin,dps)
        call simps(del12,dcapi2,kin,dps)
        call simps(del13,dcapi3,kin,dps)
c      call simps(del14,dcapi4,kin,dps)
        call simps(del15,dcapi5,kin,dps)
        capi1=dcapi1+sum1
        capi2=dcapi2+sum2
        capi3=dcapi3+sum3
        capi4=dcapi4+sum4
        capi5=dcapi5+sum5
        r(1,j)=sqrt(2,*capi1)
        vv1=(bvac(1)*dbvdz(1))**2
        vv2=bvac(1)*d2bvdz2(1)+dbvdz(1)**2
        rzz(1,j)=-vv1*capi2**2/r(1,j)**3+3,*vv1*capi3/r(1,j)
c      -vv2*capi2/r(1,j)+8,*bvac(1)**2*(abf(1)*capi4+abp(1)*
c      capi5)/r(1,j)
        sum1=+capi1
        sum2=capi2
        sum3=capi3
        sum4=capi4
        sum5=capi5
40      continue
c      ....,set r(1,1)=r(1,2)
        do 41 i=1,ix
41      r(1,1)=r(1,2)
c      calculate diagnostic quantities flute1, flute2 and flute3
        do 60 j=2,jx-1
            is=2
            if(mod(ix-2,2).eq.0)is=3
            do 61 i=is,ix-1
                ia=i-is+1
                eterm=dp2dpsi(j)*(abp(1)*b(1,j)**4+bbp(1)*b(1,j)**2+cbp(1))
c      +p2(j)*(4*abp(1)*b(1,j)**3+2*bbp(1)*b(1,j))*dbdpsi(i,j)
                rterm=0.
                if(dp2dpsi(j).ne.0.)
c      rterm=dp2dpsi(j)*(abr(1)*b(1,j)**4+bbr(1)*b(1,j)**2+br(1))
c      /(2,*p2(j)**.5)
c      +p2(j)**.5*(4*abr(1)*b(1,j)**3+2*bbr(1)*b(1,j))*dbdpsi(i,j)
                droterm(ia)=rterm*amass/b(1,j)**2/uuz(i)
                ringj=dp1dpsi(j)*(abf(1)*b(1,j)**4+bbf(1)*b(1,j)**2+cbf(1))
c      +p1(j)*(4*abf(1)*b(1,j)**3+2*bbf(1)*b(1,j))*dbdpsi(i,j)
                dflute1(ia)=+rzz(1,j)*qubv(1,j)/(r(1,j)*b(1,j)**2)/uuz(i)
c      +eterm*ringj/b(1,j)**3/uuz(i)
                dflute2(ia)=yyy(1,j)/(r(1,j)*b(1,j)
c      )**2*b(1,j)/uuz(i)
                dflute3(ia)=rho(1,j)/(r(1,j)*b(1,j)**2*b(1,j)/uuz(i)
                dflute4(ia)=xxx(1,j)/(r(1,j)*b(1,j)**2*b(1,j)/uuz(i)
61      continue
        call simps(dflute1,ans1,ia,du)
        call simps(dflute2,ans2,ia,du)
        call simps(dflute3,ans3,ia,du)
        call simps(dflute4,ans4,ia,du)
        call simps(droterm,ans5,ia,du)
        flute1(j)=ans1*(ia-1)
        flute2(j)=(ans2*(mm**2-1)+ans1)*(ia-1)
        flute3(j)=-ans1/ans3

```



```

        rhoave(j)=ans3*(ia-1)
        xxxave(j)=ans4*(ia-1)
        yyyave(j)=ans2*(ia-1)
        droave(j)=ans5*(ia-1)
60    continue

        grow=0.
        growmax=0.
        do 62 j=2,jx-1
            if(flute3(j).gt.0)grow=grow+flute3(j)
            growmax=amax1(growmax,flute3(j))
62    continue
        write(59,102)grow,growmax
102    format('grow=',e14.6,3x,'growmax=',e14.6)
c..... local growth rate for high mm. (wkb approx. )
        do 70 j=2,jx-1
            omegwkb=mm*.5*xxxave(j)/rhoave(j)
            trad=.25*mm**2*(xxxave(j)**2+4.*rhoave(j)*yyyave(j))
c -rhoave(j)**2*flute3(j)-droave(j)*yyyave(j)
            if(trad.le.0.)then
                gamwkb(j)=sqrt(-trad)/rhoave(j)
                omeg1wkb(j)=omegwkb
                omeg2wkb(j)=0.
            else
                omeg1wkb(j)=omegwkb +sqrt(trad)/rhoave(j)
                omeg2wkb(j)=omegwkb-sqrt(trad)/rhoave(j)
            end if
70    continue
        return
        end
        subroutine simps(fin,fout,knn,df)
c..... simpsons rule quadratures. knn must be odd
        dimension fin(1)
        nse=(knn-1)/2
        se=ssum(nse,fin(2),2)
        nso=nse-1
        so=ssum(nso,fin(3),2)
        fout=df/(3.*(knn-1))*(fin(1)+fin(knn)+4.*se+2.*so)
        return
        end
        subroutine equilcur

c.....equilibrium for curvature driven flute mode case.

c.....insert storage cliches here.
        use param
        use const
        use fstor

        do 10 i=1,ix
            do 10 j=1,jx
c..... special b(i,j) to test b.c. on flute test case
                b(i,j)=b0
                r(i,j)=sqrt(2*psi(j)/b(i,j))
                rho(i,j)=(en0-en1*r(i,j)**2*.5)*amass
                xxx(i,j)=rho(i,j)*(omeg1+omeg2)*sf6
                yyy(i,j)=rho(i,j)*(-omeg1*omeg2)*sf8
                qub(i,j)=b(i,j)
                qv(i,j)=p0/psi(jx)
10    continue

```

```

        return
    end
    subroutine equil
c.....special case equilibrium, 0 beta, 0 pressure, rho=const.
c.....test case 1
c.....set up 1/4/82 by r, freis
c.....insert cliché storage here
    use param
    use matrix
    use const
    use fstor

    data rho0/1.e12/,b0/1.e4/,azm/1./,apsim/1./

    do 10 j=1,jx
    do 10 i=1,ix
        uz=uuz(i)
        rho(i,j)=rho0
        b(i,j)=b0
        r(i,j)=sqrt(2.*abs(psi(j))/b0)
        xxx(i,j)=0.
        yyy(i,j)=0.
        qub(i,j)=b0
10    continue
    return
    end
    subroutine equilrot

c..... sets up equilibrium for rigid rotor, test case 2 .
c.....flora3 adds cold plasma halo to equilibrium density
c..... insert cliché storage here
    use param
    use const
    use fstor

    psi0=b0*1.0sq*.5/sqrt(fourpi)
    omegr=ratrod*omegst*(1.-enbar/en0)
    foursq=sqrt(fourpi)
    do 5 i=1,ix
        uz=uuz(i)
        do 5 j=1,jx
            fac=exp(psi(j)/psi0)/sqrt(beta0)
            b(i,j)=b0*sqrt(fac**2-1.)/(fac*foursq)
            rho(i,j)=en0*amass/(beta0*fac**2)+enbar*amass
            beta=1/fac**2
            arg1=fac+sqrt(fac**2-1.)
            acosh=alog(arg1)
            r(i,j)=r0*sqrt(-cr+acosh)
            qub(i,j)=b(i,j)
            omegstr=omegst*(1.-enbar*amass/rho(i,j))
            entest=enbar*amass
            if(entest.ge.rho(i,j))omegstr=0.
            omegexb=(1.+ratrod)*omegstr
            omeggb=+beta*omegstr*.5/(1.-beta)
            xxx(i,j)=rho(i,j)*(2.*omegexb+omeggb-omegst)
            yyy(i,j)=-rho(i,j)*(omegexb+omeggb)*(omegexb-omegst)
            xxx(i,j)=xxx(i,j)*flr

```

```

      yyy(i,j)=yyy(i,j)*flr
5      continue
      do 30 i=1,ix
      do 30 j=2,jx-1
      qv(i,j)=.5*(qub(i,j+1)*b(i,j+1)-qub(i,j-1)*b(i,j-1))
30      continue
      return
      end
      subroutine initial

c.....set up initial displacement vectors, xro and xio
c..... test case 1, cos(kz) in z, flat in psi
c..... set up 1/4/82 by r. freis

c.....insert cliché storage here
      use param
      use fstor
      use matrix
      use const

      data pi/3.1415926/

      rbf=1,
      do 10 j=2,jx-1
      r1=ranf(b1)
      r2=ranf(b1)
      r3=ranf(b1)
      r4=ranf(b1)
      do 10 i=2,ix-1
      if(kzs.eq.0)then
      rbf=1./(r(i,j)*b(i,j))
      else
      r1=ranf(b1)
      r2=ranf(b1)
      r3=ranf(b1)
      r4=ranf(b1)
      endif
5      continue
      k1=i-1+(j-2)*(ix-2)
      k2=j-1+(jx-2)*(i-2)
      k=.5*(1+isw)*k1+.5*(1-isw)*k2
      xro(k)=ex0*rbf*(r1+r2-1.)+ex1*cos(.5*pi*(z(i))/zedge)
      xio(k)=ex0*rbf*(r3+r4-1.)+ex1*cos(.5*pi*z(i)/zedge)
c      xio(k)=cos(theta0)*xro(k)
10      continue
      do 20 j=2,jx-1
      r1=ranf(b1)
      r2=ranf(b1)
      r3=ranf(b1)
      r4=ranf(b1)
      do 20 i=2,ix-1
      if(kzs.eq.0)then
      rbf=1./(r(i,j)*b(i,j))
      else
      r1=ranf(b1)
      r2=ranf(b1)
      r3=ranf(b1)
      r4=ranf(b1)
      endif
15      continue

```

```

      k1=i-1+(j-2)*(ix-2)
      k2=j-1+(jx-2)*(i-2)
      k=.5*(1+isw)*k1+.5*(1-isw)*k2
      xroo(k)=ex0*rbf*(r1+r2-1.)+ex1*cos(.5*pi*(z(i))/zedge)
      xloo(k)=ex0*rbf*(r3+r4-1.)+ex1*cos(.5*pi*(z(i))/zedge)
c      xloo(k)=cos(theta0)*xroo(k)
20  continue
      return
      end

      subroutine input
c.....insert storage cliches here
      use param
      use const
      use fstor

c..... boundary conditions are set as follows:
c.....      at z=z0 (i=1), f11=-1, implies x=0,
c.....      f11=1, implies slope=0,
c.....      at z=zmax (i=ix), fizx=-1, implies x=0
c.....      fizx=1, implies slope=0,
c.....      at psi=psi0 (j=1), fj1=-1, implies x=0,
c.....      fj1=1, implies slope=0,
c.....      at psi=psi0 (j=jx), fjrx=-1, implies x=0,
c.....      fjrx=1, implies slope=0,
c.....      data mm/4/, bias/.5/ lmax/2/, nmax/5/, dv/1./, du/1./
c      ,ndiag/100/, f11/1./, fizx/1./, fj1/1./, fjrx/1./, flr/1./
c      ,sf6/1./, sf8/1./, kplotm/0/, kzs/1/, swg1/1./, swg2/1./
c      , swg3/1./, swg4/1./

c.....,forced data loaded for testing fourier analyses and zed file
c.....,maker
      data jfour/1/,nfourp/1/,nfourmax/5/
      namelist/nw1/aname,mm, bias, lmax, nmax,ndiag
c      ,f11,fizx,fj1,fjrx,ex0,ex1,fpsi,fu,fv,fz
c      ,kplotm,kzs,jfour,nfourp,nfourmax,sf6,sf8,swg1,swg2,swg3,swg4

      call ddi(nw1,2,3,1)
      if(nold.ne.1)call ddo(nw1,100,0,1)
      jx=jrx
      kxx=kxp
      ix=izx
      return
      end

      subroutine grid

c..... relates physical grid z,psi to computational grid u,v (equally
c..... spaced ). uses input fpsi, fv, fz, fu and azm, apsim .

c.....,insert cliché storage here
      use param
      use const

      xv=alog(fpsi)/alog(fv)
      xu=alog(fz)/alog(fu)
      zzp=0.
      pslp=0.
      do 5 i=1,ix
5      u(i)=u0+du*(i-1.5)

```

```

u(1)=-u(1)
azm=u(ix)**(1,-xu)
do 10 i=1,ix
uuz(i)=u(i)**(1,-xu)/(xu*azm)
z(i)=azm*u(i)**xu

uuzh(i)=(u(i)+.5*du)**(1,-xu)/(xu*azm)
dz(i)=z(i)-zzp
zzp=z(i)
10 continue
zedge=azm*.5*(u(ix)**xu+u(ix-1)**xu)
do 15 j=1,jx
v(j)=v0+(j-1.5)*dv
15 continue
v(1)=-v(1)
apsim=v(jx)**(1,-xv)
do 20 j=1,jx
vpsi(j)=v(j)**(1,-xv)/(apsim*xv)
vpsih(j)=(v(j)+.5*dv)**(1,-xv)/(apsim*xv)
psi(j)=apsim*v(j)**xv
dpsi(j)=psi(j)-psip
psip=psi(j)
20 continue
c..... calculates v at plasma edge
vw=(psiw/apsim)**(1,-xv)
dvin=(vw-v(jx-1))/dv
dvout=(v(jx)-vw)/dv
return
end
subroutine fltol1
c.....calculates the fl to fl1 functions needed to generate the a and
c..... b matrices , uses the equilibrium quantities r, rho, b, etc.
c..... insert cliché storage here

use param
use fstor
use matrix
use const

m2=mm**2
du2=du**2
do 10 i=1,ix
do 10 j=2,jx
r2=r(i,j)**2
uz=uuz(i)
bb=b(i,j)
vp=vpsi(j)
r4=r2**2
f1(i,j)=rho(i,j)*bb*r4
f2t=(1.-m2)*rho(i,j)/bb+r2*vp*(rho(i,j+1)-rho(i,j-1))/(2.*dv)
f2(i,j)=f2t/vp
f3(i,j)=mm*xxx(i,j)*r4*bb
f4(i,j)=(1.-m2)*mm*xxx(i,j)/bb
f5(i,j)=-m2*yyy(i,j)*r4*bb
f7(i,j)=(1.-m2)*(1.-m2)*yyy(i,j)/(bb*vp)
g4(i,j)=qub(i,j)*r(i,j)**2
g3(i,j)=r(i,j)*b(i,j)
g2(i,j)=qub(i,j)/(r(i,j)*b(i,j))**2
dppdpsi=dp2dpsi(j)*(abp(i)*b(i,j)**4+bbp(i)*b(i,j)**2+cbp(i))
c +p2(j)*(4*abp(i)*b(i,j)**3+2*bbp(i)*b(i,j))*dbdpsi(i,j)

```

```

      dpdpdpsi=dp1dpsi(j)*(abf(i)*b(i,j)**4+bbf(i)*b(i,j)**2+cbf(i))
c      +p1(j)*(4*abf(i)*b(i,j)**3+2*bbf(i)*b(i,j))*dbdpsi(i,j)
      g1(i,j)=+(mm*uuz(i)**2*r(i,j)*rzz(i,j)
c      *qubv(i,j)+dppdpsi*dpdpdpsi*r(i,j)/b(i,j))
      g1(i,j)=g1(i,j)*swg1
      g2(i,j)=g2(i,j)*swg2
      g3(i,j)=g3(i,j)*swg3
      g4(i,j)=g4(i,j)*swg4
c      .... special g1 to test b.c. on flute test case
c      g1(i,j)=-(mm*uuz(i)**2*r(i,j)*r(i,j)/lb**2
c      c*qv(i,j)

```

```

10      continue
c      .... fill in edge values
      do 20 i=1,ix
        f1(i,1)=-f1(i,2)
        f2(i,1)=f2(i,2)
        f3(i,1)=-f3(i,2)
        f4(i,1)=f4(i,2)
        f5(i,1)=-f5(i,2)
        f7(i,1)=f7(i,2)
        g4(i,1)=-g4(i,2)
20      continue
      return
      end

```

subroutine amat

```

c      .... calculates the matrix coefficients for a1, a2, a3, b1, b2
c      .... in the equation  $a1*x(n+1)=a2*x(n)+a3*x(n-1)+b1*y(n)+b2*y(n-1)$  .
c      .... uses f1 to f11 from subroutine fltol1 and equilibrium quantities.
c      .... cliche storage here

```

```

      use param
      use fstor
      use matrix
      use const

```

```

      data unit/1./

```

```

      gam3=-gam2
      du2=du**2
      dt2=dt**2
      dv2=dv**2
      dvt=2.*dv
      m2=mm**2
      jx=jrx
      ix=izx
      do 10 i=2,ix-1
      do 10 j=2,jx-1
        k1=i-1+(j-2)*(ix-2)
        k2=j-1+(jx-2)*(i-2)
        k=.5*(1+isw)*k1+.5*(1-isw)*k2
        r2=r(i,j)**2
        vp=vpsi(j)
        uz=uuz(i)
        bijmh=(b(i,j)+b(i,j-1))*0.5

```

```

b1jph=(b(i,j)+b(i,j+1))*5
b1p1jph=(b(i+1,j+1)+b(i+1,j))*5
b1p1jmh=(b(i+1,j-1)+b(i+1,j))*5
b1m1jph=(b(i-1,j+1)+b(i-1,j))*5
b1m1jmh=(b(i-1,j-1)+b(i-1,j))*5
g41phjph=(g4(i+1,j+1)+g4(i,j)+g4(i+1,j)+g4(i,j+1))*25*uu zh(i)
g41phjmh=(g4(i+1,j-1)+g4(i,j)+g4(i+1,j)+g4(i,j-1))*25*uu zh(i)
g41mhjph=(g4(i-1,j+1)+g4(i,j)+g4(i-1,j)+g4(i,j+1))*25*uu zh(i)
g41mhjmh=(g4(i-1,j-1)+g4(i,j)+g4(i-1,j)+g4(i,j-1))*25*uu zh(i)
g21phj=(g2(i+1,j)+g2(i,j))*5*uu zh(i)
g21mhj=(g2(i-1,j)+g2(i,j))*5*uu zh(i-1)
g31phj=(g3(i+1,j)+g3(i,j))*5*uu zh(i)
g31mhj=(g3(i-1,j)+g3(i,j))*5*uu zh(i-1)

f11jph=(f1(i,j)+f1(i,j+1))*5*vpsih(j)
f11jmh=(f1(i,j)+f1(i,j-1))*5*vpsih(j-1)
f51jph=(f5(i,j)+f5(i,j+1))*5*vpsih(j)
f51jmh=(f5(i,j)+f5(i,j-1))*5*vpsih(j-1)

if(j.gt.2)go to 60
f11jmh=0.
f61jmh=0.
60 continue
uzbar=-uu z(i)*r(i,j)/(du2*dv2)
a1(k,1)=-gam1*b1m1jmh*g41mhjmh*b1jmh*uzbar*vpsih(j-1)
c *r(i-1,j-1)
a2(k,1)=-gam2*b1m1jmh*g41mhjmh*b1jmh*uzbar*vpsih(j-1)
c *r(i-1,j-1)
a3(k,1)=-gam3*b1m1jmh*g41mhjmh*b1jmh*uzbar*vpsih(j-1)
c *r(i-1,j-1)

a1(k,2)=-f11jmh/((dt*dv)**2)+gam1*(f51jmh/dv2+b1jmh**2*uzbar
c *vpsih(j-1)*r(i,j-1)*(g41mhjmh+g41phjmh))
a2(k,2)=-f11jmh/((dt*dv)**2)+gam2*(f51jmh/dv2+b1jmh**2*uzbar
c *vpsih(j-1)*r(i,j-1)*(g41mhjmh+g41phjmh))
a3(k,2)=-f11jmh/((dt*dv)**2)+gam3*(f51jmh/dv2+b1jmh**2*uzbar
c *vpsih(j-1)*r(i,j-1)*(g41mhjmh+g41phjmh))

a1(k,3)=-gam1*b1p1jmh*g41phjmh*b1jmh*uzbar*vpsih(j-1)*r(i+1,j-1)
a2(k,3)=-gam2*b1p1jmh*g41phjmh*b1jmh*uzbar*vpsih(j-1)*r(i+1,j-1)
a3(k,3)=-gam3*b1p1jmh*g41phjmh*b1jmh*uzbar*vpsih(j-1)*r(i+1,j-1)
a1(k,4)=gam1*((b1m1jmh*g41mhjmh*vpsih(j-1)*b1jmh+b1m1jph*g41mhjph
c *vpsih(j)*b1jph)*uzbar*r(i-1,j)+mm**2*b(i,j)*uzbar*
c g21mhj*g3(i-1,j)*dv2/vpsi(j))
a2(k,4)=gam2*((b1m1jmh*g41mhjmh*vpsih(j-1)*b1jmh+b1m1jph*g41mhjph
c *vpsih(j)*b1jph)*uzbar*r(i-1,j)+mm**2*b(i,j)*uzbar*
c g21mhj*g3(i-1,j)*dv2/vpsi(j))
a3(k,4)=gam3*((b1m1jmh*g41mhjmh*vpsih(j-1)*b1jmh+b1m1jph*g41mhjph
c *vpsih(j)*b1jph)*uzbar*r(i-1,j)+mm**2*b(i,j)*uzbar*
c g21mhj*g3(i-1,j)*dv2/vpsi(j))

a1(k,5)=((f11jph+f11jmh)/dv2-f2(i,j))/dt2+gam1*(-(f51jph+f51jmh
c /dv2+f7(i,j)+g1(i,j)+(-b1jmh**2*(g41mhjmh+g41phjmh)*vpsih(j-1)
c -b1jph**2*(g41mhjph+g41phjph)*vpsih(j))*r(i,j)*uzbar-
c mm**2*b(i,j)*uzbar*(g21mhj+g21phj)*g3(i,j)*dv2/vpsi(j))
a2(k,5)=((f11jph+f11jmh)/dv2-f2(i,j))/dt2+gam2*(-(f51jph+f51jmh
c /dv2+f7(i,j)+g1(i,j)+(-b1jmh**2*(g41mhjmh+g41phjmh)*vpsih(j-1)
c -b1jph**2*(g41mhjph+g41phjph)*vpsih(j))*r(i,j)*uzbar-
c mm**2*b(i,j)*uzbar*(g21mhj+g21phj)*g3(i,j)*dv2/vpsi(j))

```

```

a3(k,5)=(f1ijph+f1ijmh)/dv2-f2(i,j)/dt2+gam3*(-(f5ijph+f5ijmh
c )/dv2+f7(i,j)+g1(i,j)+(-bijmh**2*(g4imhjmh+g4iphjmh)*vpsih(j-1)
c -bijph**2*(g4imhjph+g4iphjph)*vpsih(j))*r(i,j)*uzbar-
c mm**2*b(i,j)*uzbar*(g2imhj+g2iphj)*g3(i,j)*dv2/vpsih(j))

a1(k,6)=gam1*((bip1jmh*g4iphjmh*bijmh*vpsih(j-1)+bip1jph*g4iphjph
c *bijph*vpsih(j))*uzbar*r(i+1,j)+mm**2*b(i,j)*uzbar*
c g2iphj*g3(i+1,j)*dv2/vpsih(j))
a2(k,6)=gam2*((bip1jmh*g4iphjmh*bijmh*vpsih(j-1)+bip1jph*g4iphjph
c *bijph*vpsih(j))*uzbar*r(i+1,j)+mm**2*b(i,j)*uzbar*
c g2iphj*g3(i+1,j)*dv2/vpsih(j))
a3(k,6)=gam3*((bip1jmh*g4iphjmh*bijmh*vpsih(j-1)+bip1jph*g4iphjph
c *bijph*vpsih(j))*uzbar*r(i+1,j)+mm**2*b(i,j)*uzbar*
c g2iphj*g3(i+1,j)*dv2/vpsih(j))

a1(k,7)=gam1*(-bim1jph*g4imhjph*bijph*vpsih(j)*uzbar*r(i-1,j+1))
a2(k,7)=gam2*(-bim1jph*g4imhjph*bijph*vpsih(j)*uzbar*r(i-1,j+1))
a3(k,7)=gam3*(-bim1jph*g4imhjph*bijph*vpsih(j)*uzbar*r(i-1,j+1))
a1(k,8)=-f1ijph/(dt2*dv2)+gam1*(f5ijph/dv2+(bijph**2*(g4imhjph
c +g4iphjph)*vpsih(j))*r(i,j+1)*uzbar)
a2(k,8)=-f1ijph/(dt2*dv2)+gam2*(f5ijph/dv2+(bijph**2*(g4imhjph
c +g4iphjph)*vpsih(j))*r(i,j+1)*uzbar)
a3(k,8)=-f1ijph/(dt2*dv2)+gam3*(f5ijph/dv2+(bijph**2*(g4imhjph
c +g4iphjph)*vpsih(j))*r(i,j+1)*uzbar)
a1(k,9)=gam1*(-bip1jph*g4iphjph*bijph*vpsih(j)*uzbar*r(i+1,j+1))
a2(k,9)=gam2*(-bip1jph*g4iphjph*bijph*vpsih(j)*uzbar*r(i+1,j+1))
a3(k,9)=gam3*(-bip1jph*g4iphjph*bijph*vpsih(j)*uzbar*r(i+1,j+1))
c.....b1 array for rhs
f3ijmh=(f3(i,j)+f3(i,j-1))*0.5*vpsih(j-1)
f3ijph=(f3(i,j)+f3(i,j+1))*0.5*vpsih(j)
denom=1./(dv2)
b1(k,1)=f3ijmh*denom
b1(k,3)=f3ijph*denom
b1(k,2)=-(f3ijmh+f3ijph-f4(i,j)*dv2/vp)*denom
10 continue
c.....correct coefficients on boundaries
sf1=sign(unit,f1)
sfj=sign(unit,fj)
sfjrx=sign(unit,fjrx)
sfizx=sign(unit,fizx)
c..... set corners to 0
k1i=ix-2
k1j=1+(ix-3)*(jx-2)
k1=.5*(1+isw)*k1i+.5*(1-isw)*k1j
fac1=-1.
if(sfj1.eq.1.and.sfizx.eq.1)fac1=r(ix-1,2)*b(ix-1,2)/
c (r(ix,2)*b(ix,2))
a1(k1,5)=a1(k1,5)+fac1*a1(k1,3)
a2(k1,5)=a2(k1,5)+fac1*a2(k1,3)
a3(k1,5)=a3(k1,5)+fac1*a3(k1,3)
a1(k1,3)=0.
a2(k1,3)=0.
a3(k1,3)=0.
k2i=1+(ix-2)*(jx-3)
k2j=jx-2
k2=.5*(1+isw)*k2i+.5*(1-isw)*k2j
fac3=-dvout/dvin
if(sfjrx.eq.1.and.sf1.eq.1)fac3=r(2,jx-1)*b(2,jx-1)/
c (r(1,jx-1)*b(1,jx-1))
a1(k2,5)=a1(k2,5)+fac3*a1(k2,7)

```



```

      a2(k2,5)=a2(k2,5)+fac3*a2(k2,7)
      a3(k2,5)=a3(k2,5)+fac3*a3(k2,7)
      a1(k2,7)=0.
      a2(k2,7)=0.
      a3(k2,7)=0.
      fac2=-1.
      if(sfj1.eq.1.and.sfi1.eq.1)fac2=r(2,2)*b(2,2)/(r(1,2)*b(1,2))
      a1(1,5)=a1(1,5)+fac2*a1(1,1)
      a2(1,5)=a2(1,5)+fac2*a2(1,1)
      a3(1,5)=a3(1,5)+fac2*a3(1,1)
      a1(1,1)=0.
      a2(1,1)=0.
      a3(1,1)=0.
      fac4=-dvout/dvin
      if(sfjrx.eq.1.and.sfizx.eq.1)fac4=r(ix-1,jx-1)*b(ix-1,jx-1)/
c (r(ix,jx-1)*b(ix,jx-1))
      a1(kxp,5)=a1(kxp,5)+fac4*a1(kxp,9)
      a2(kxp,5)=a2(kxp,5)+fac4*a2(kxp,9)
      a3(kxp,5)=a3(kxp,5)+fac4*a3(kxp,9)
      a1(kxp,9)=0.
      a2(kxp,9)=0.
      a3(kxp,9)=0.
      i=2
      do 11 j=2,jx-1
      if(sfi1.eq.1.)sfi1=r(2,j)*b(2,j)/(r(1,j)*b(1,j))
      k1=i-1+(j-2)*(ix-2)
      k2=j-1+(jx-2)*(i-2)
      k=.5*(1+isw)*k1+.5*(1-isw)*k2
      do 11 m=2,8,3
      a1(k,m)=a1(k,m)+sfi1*a1(k,m-1)
      a2(k,m)=a2(k,m)+sfi1*a2(k,m-1)
      a3(k,m)=a3(k,m)+sfi1*a3(k,m-1)
11  continue
13  continue
      i=ix-1
      do 12 j=2,jx-1
      if(sfizx.eq.1.)sfizx=r(ix-1,j)*b(ix-1,j)/(r(ix,j)*b(ix,j))
      k1=i-1+(j-2)*(ix-2)
      k2=j-1+(jx-2)*(i-2)
      k=.5*(1+isw)*k1+.5*(1-isw)*k2
      do 12 m=2,8,3
      a1(k,m)=a1(k,m)+sfizx*a1(k,m+1)
      a2(k,m)=a2(k,m)+sfizx*a2(k,m+1)
      a3(k,m)=a3(k,m)+sfizx*a3(k,m+1)
12  continue
20  continue
      i=2
      do 21 j=2,jx-1
      k1=i-1+(j-2)*(ix-2)
      k2=j-1+(jx-2)*(i-2)
      k=.5*(1+isw)*k1+.5*(1-isw)*k2
      do 21 m=1,7,3
      a1(k,m)=0.
      a2(k,m)=0.
      a3(k,m)=0.
21  continue
      i=ix-1
      do 22 j=2,jx-1
      k1=i-1+(j-2)*(ix-2)
      k2=j-1+(jx-2)*(i-2)

```

```

      k=.5*(1+isw)*k1+.5*(1-isw)*k2
      do 22 m=3,9,3
        a1(k,m)=0.
        a2(k,m)=0.
        a3(k,m)=0.
22      continue
        j=2
        do 31 i=2,ix-1
          k1=i-1+(j-2)*(ix-2)
          k2=j-1+(jx-2)*(i-2)
          k=.5*(1+isw)*k1+.5*(1-isw)*k2
          do 30 m=4,6
            a1(k,m)=a1(k,m)+sfj1*a1(k,m-3)
            a2(k,m)=a2(k,m)+sfj1*a2(k,m-3)
            a3(k,m)=a3(k,m)+sfj1*a3(k,m-3)
30          continue
            b1(k,2)=b1(k,2)+sfj1*b1(k,1)
31          continue
32          continue
            j=jx-1
            fac5=sfjrx
            if(sfjrx.eq.-1) fac5=fac5*dvout/dvin
            do 35 i=2,ix-1
              k1=i-1+(j-2)*(ix-2)
              k2=j-1+(jx-2)*(i-2)
              k=.5*(1+isw)*k1+.5*(1-isw)*k2
              do 34 m=4,6
                a1(k,m)=a1(k,m)+fac5*a1(k,m+3)
                a2(k,m)=a2(k,m)+fac5*a2(k,m+3)
                a3(k,m)=a3(k,m)+fac5*a3(k,m+3)
34              continue
                b1(k,2)=b1(k,2)+fac5*b1(k,3)
35              continue
40              continue
                j=2
                do 45 i=2,ix-1
                  k1=i-1+(j-2)*(ix-2)
                  k2=j-1+(jx-2)*(i-2)
                  k=.5*(1+isw)*k1+.5*(1-isw)*k2
                  do 44 m=4,6
                    a1(k,m-3)=0.
                    a2(k,m-3)=0.
                    a3(k,m-3)=0.
44                  continue
                    b1(k,1)=0.
45                  continue
                    j=jx-1
                    do 48 i=2,ix-1
                      k1=i-1+(j-2)*(ix-2)
                      k2=j-1+(jx-2)*(i-2)
                      k=.5*(1+isw)*k1+.5*(1-isw)*k2
                      do 47 m=4,6
                        a1(k,m+3)=0.
                        a3(k,m+3)=0.
                        a2(k,m+3)=0.
47                      continue
                        b1(k,3)=0.
48                      continue
                      return
                    end

```

```

      subroutine comat(abar,nd)

c.....transforms the elements of the a1(k,m) array into into the
c..... elements of the compressed column matrix abar which will be
c..... operated upon by banfac and bansol.

c..... insert storage cliches here
      use param
      use fstor
      use matrix
      use const

      dimension abar(kxp,1)

      kxx=kxp
      len=nd*kxp
      call bcast(abar(1,1),0.,len)
      do 10 k=1,kxx
      do 10 m=1,9
        lp1=m+((m-1)/3)*(ihbw-4)
        lp2=1+mod(m-1,3)*(ihbw-1)+(m-1)/3
        lp=.5*(1+isw)*lp1+.5*(1-isw)*lp2
        abar(k,lp)=a1(k,m)
10    continue
      return
      end

      subroutine right

c..... calculates right hand side vector for both equations.
c..... rhs1(k)=2*a2*xr(n)-a2*xr(n-1)+b1*(xi(1)-xi(n-1)) , and
c..... rhs2(k)=2*a3*xi(n)-a2*xi(n-1)+b1*(xr(1)-xr(n-1)) .

c..... insert cliches for storage here
      use param
      use fstor
      use matrix
      use const

      do 10 j=2,jx-1
      do 10 i=2,ix-1
        k1=i-1+(j-2)*(ix-2)
        k2=j-1+(jx-2)*(i-2)
        k=.5*(1+isw)*k1+.5*(1-isw)*k2
        t1=0.
        t2=0.
        t3=0.
        tt1=0.
        tt2=0.
        tt3=0.
      do 5 m=1,9
        ip=i-2+m-((m-1)/3)*3
        jp=j-1+(m-1)/3
        if(jp.eq.1.or.jp.eq.jrx.or.ip.eq.1.or.ip.eq.izx)go to 5
        kp1=ip-1+(ix-2)*(jp-2)
        kp2=jp-1+(jx-2)*(ip-2)
        kp=.5*(1+isw)*kp1+.5*(1-isw)*kp2
        t1=t1+a2(k,m)*xroo(kp)

```

```

      t2=t2+a3(k,m)*xro(kp)
      tt1=tt1+a2(k,m)*xioo(kp)
      tt2=tt2+a3(k,m)*xio(kp)
5    continue
      do 5 mn=1,3
      jq=j-2+mn
      if(jq.eq.1 or jq.eq.jrx)go to 6
      kq1=i-1+(ix-2)*(jq-2)
      kq2=jq-1+(jx-2)*(i-2)
      kq=.5*(1+isw)*kq1+.5*(1-isw)*kq2
      t3=t3+b1(k,mn)*(xiol(kq)-xioo(kq))
      tt3=tt3+b1(k,mn)*(xrol(kq)-xroo(kq))
6    continue
      rhs1(k)=(2.*t2-t1+fac1*tt3)
      rhs2(k)=2.*tt2-tt1+fac2*tt3
10   continue
      return
      end
      subroutine rightvec

```

c..... calculates right hand side vector for both equations,  
 c..... rhs1(k)=2\*a2\*xr(n)-a2\*xr(n-1)+b1\*(xi(1)-xi(n-1)) , and  
 c..... rhs2(k)=2\*a3\*xi(n)-a2\*xi(n-1)+b1\*(xr(1)-xr(n-1)) .

c..... insert cliches for storage here

```

      use param
      use fstor
      use matrix
      use const

      call scal(kxx,0.,rhs1,1)
      call scal(kxx,0.,rhs2,1)
      do 100 m=1,9
      mdel=(m-1)/3
      m1=m-1
      koff1=-mdel*5+m+(mdel-1)*ix
      koff2=(m-((mdel+1)*3-1))*jx+1-2*m1+7*mdel
      koff=.5*(1+isw)*koff1+.5*(1-isw)*koff2
      do 110 k=1,kxx
      rhs1(k)=rhs1(k)+2.*a3(k,m)*xro(k+koff)-a2(k,m)*xroo(k+koff)
110  rhs2(k)=rhs2(k)+2.*a3(k,m)*xio(k+koff)-a2(k,m)*xioo(k+koff)
      if(m.eq.2.or.m.eq.5.or.m.eq.8)go to 119
      go to 100
119  continue
      do 120 k=1,kxx
      mbar=m-1-(m/4)*2
      rhs1(k)=rhs1(k)+fac1*b1(k,mbar)*(xiol(k+koff)-xioo(k+koff))
120  rhs2(k)=rhs2(k)+fac2*b1(k,mbar)*(xrol(k+koff)-xroo(k+koff))
100  continue
      return
      end
      subroutine rigidcon

```

c..... special constants needed for rigid rotor equilibrium.

c..... storage cliché here

```

      use param
      use const

```

c..... input for rigid rotor