

The Learning Point

Main Page: The Complete Index at a Glance	Mathematics	Computer Science	Physics
Electrical Science and Engineering	An Introduction to Graphics and Solid Modelling		
Test Preparations	Ace the Programming Interviews		
CoursePlex: Online Open Classes from Coursera, Udacity, etc			About

[Computer Science](#) >

Algorithms: Dynamic Programming - Longest Common Sub-sequence with C Program Source Code

Quick Links to Various Sections on the Main Page

Place a 10 persone. [Sign Up](#) per vedere cosa piace ai tuoi amici.

To go through the C program / source-code, scroll down to of this page

Longest Common Subsequence

A subsequence of a given sequence is the given sequence with just some elements left out (order should be from left-to-right, not necessarily consecutive).. A common sequence of two sequences X and Y, is a subsequence of both X and Y. A longest common subsequence is the one with maximum length. For example, if $X = \{A, B, C, B, D, A, B\}$ and $Y = \{B, D, C, A, B, A\}$ then the longest common subsequence is of length 4 and they are $\{B, C, B, A\}$ and $\{B, D, A, B\}$.

Finding the longest common subsequence has applications in areas like biology. The longest subsequence (LCS) problem has an optimal substructure property. Thus, the dynamic programming method can be used to solve this problem.

Theorem used - Let $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$ be sequences, and let $Z = \langle z_1, z_2, \dots, z_k \rangle$ be any LCS of X and Y .

1. If $x_m = y_n$, then $z_k = x_m = y_n$ and Z_{k-1} is an LCS of X_{m-1} and Y_{n-1} .
2. If $x_m \neq y_n$, then $z_k = x_m$ implies that Z is an LCS of X_{m-1} and Y.
3. If $x_m \neq y_n$, then $z_k = y_n$ implies that Z is an LCS of X and Y_{n-1} .

Complete Tutorial with Examples:

0

These are Quick Links to sections of the Main Page

Longest Common Subsequence

A subsequence of a given sequence is the given sequence with just some elements left out (order should be from left-to-right, not necessarily consecutive).. A common sequence of two sequences X and Y, is a subsequence of both X and Y. A longest common subsequence is the one with maximum length. For example, if $X = \{A, B, C, B, D, A, B\}$ and $Y = \{B, D, C, A, B, A\}$ then the longest common subsequence is of length 4 and they are $\{B, C, B, A\}$ and $\{B, D, A, B\}$.

Finding the longest common subsequence has applications in areas like biology. The longest subsequence (LCS) problem has an optimal substructure property. Thus, dynamic programming method can be used to solve this problem.

Theorem used - Let $X = \langle x_1, x_2, \dots, x_m \rangle$ and $Y = \langle y_1, y_2, \dots, y_n \rangle$ be sequences, and let $Z = \langle z_1, z_2, \dots, z_k \rangle$ be any LCS of X and Y.

1. If $x_m = y_n$, then $z_k = x_m = y_n$ and Z_{k-1} is an LCS of X_{m-1} and Y_{n-1} .
2. If $x_m = y_n$, then $z_k = x_m$ implies that Z is an LCS of X_{m-1} and Y.
3. If $x_m = y_n$, then $z_k = y_n$ implies that Z is an LCS of X and Y_{n-1} .

Algorithm:

S, T are two strings for which we have to find the longest common sub sequence. Input the two sequences. Now print the longest common subsequence using **LongestCommonSubsequence** function.

LongestCommonSubsequence function : This function takes the two sequences (**S, T**) as arguments and returns the longest common subsequence found.

Store the length of both the subsequences. **Slength** = strlen(S), **Tlength** = strlen(T).

We will start with the index from 1 for our convenience (avoids handling special cases for

C Program Source Code for the Longest Common Subsequence problem

```
#include<stdio.h>
#include<string.h>
#define maxn 100100
int max(int a,int b)
{
    return a>b?a:b;
}
int LongestCommonSubsequence(char S[],char T[])
{
    int Slength = strlen(S);
    int Tlength = strlen(T);
    /* Starting the index from 1 for our convinience (avoids handling special cases for negative indices) */
    int iter,jter;
    for(iter=Slength;iter>=1;iter--)
    {
        S[iter] = S[iter-1];
    }
    for(iter=Tlength;iter>=1;iter--)
    {
        T[iter] = T[iter-1];
    }
    int common[Slength+1][Tlength+1];
    /* common[i][j] represents length of the longest common sequence in S[1..i], T[1..j] */
    /* Recurrence: common[i][j] = common[i-1][j-1] + 1 if S[i]==T[j]
                    = max(common[i-1][j],common[i][j-1]) otherwise
    */
    /*common[0][i]=0, for all i because there are no characters from string S*/
    for(iter=0;iter<=Tlength;iter++)
    {
        common[0][iter]=0;
    }
    /*common[i][0]=0, for all i because there are no characters from string T*/
```

```

        for(iter=0;iter<=Slength;iter++)
        {
            common[iter][0]=0;
        }
        for(iter=1;iter<=Slength;iter++)
        {
            for(jter=1;jter<=Tlength;jter++)
            {
                if(S[iter] == T[jter] )
                {
                    common[iter][jter] = common[iter-1][jter-1] + 1;
                }
                else
                {
                    common[iter][jter] = max(common[iter][jter-1],common[iter-1][jter]);
                }
            }
        }
        return common[Slength][Tlength];
    }

int main()
{
    char S[maxn],T[maxn];/* S,T are two strings for which we have to find the longest common sub sequence. */
    scanf("%s%s",S,T);
    printf("%d\n",LongestCommonSubsequence(S,T));
}

```

Rough notes about the Algorithm implemented in the code above:

S,T are two strings for which we have to find the longest common sub sequence. Input the two sequences. Now print the

LongestCommonSubsequence function : This function takes the two sequences (S, T) as arguments and returns the

Store the length of both the subsequences. Slength = strlen(S), Tlength = strlen(T). We will Start with the index from 0. Declare **common[Slength][Tlength]**. Where, common[i][j] represents length of the longest common sequence in S[1..i], T[1..j]. If there are no characters from string S, common[0][i]=0 for all i or if there are no characters from string T, common[i][0]=0 for all i.

Recurrence: for i=1 to Slength
 for j=1 to Tlength
 common[i][j] = common[i-1][j-1] + 1, if S[i]=T[j]. Else, common[i][j] = max(common[i-1][j],common[i][j-1]).

Return **common[Slength][Tlength]**.

Related Tutorials (common examples of Dynamic Programming):

<u>Integer Knapsack problem</u>	An elementary problem, often used to introduce the concept of dynamic programming.
<u>Matrix Chain Multiplication</u>	Given a long chain of matrices of various sizes, how do you parenthesize them for the purpose of multiplication - how do you chose which ones to start multiplying first?
<u>Longest Common Subsequence</u>	Given two strings, find the longest common sub sequence between them.

Some Important Data Structures and Algorithms, at a glance:

Arrays : Popular			
------------------	--	--	--


Sorting and Searching Algorithms			
Bubble Sort	Insertion Sort	Selection Sort	Shell Sort
Merge Sort	Quick Sort	Heap Sort	Binary Search Algorithm
Basic Data Structures and Operations on them			
Stacks	Queues	Single Linked List	Double Linked List
Circular Linked List	1.		

Tree Data Structures			
Binary Search Trees	Heaps	Height Balanced Trees	
Graphs and Graph Algorithms			
Depth First Search	Breadth First Search	Minimum Spanning Trees: Kruskal Algorithm	Minimum Spanning Trees: Prim's Algorithm
Dijkstra Algorithm for Shortest Paths	Floyd Warshall Algorithm for Shortest Paths	Bellman Ford Algorithm	
Popular Algorithms in Dynamic Programming			
Dynamic Programming	Integer Knapsack problem	Matrix Chain Multiplication	Longest Common Subsequence
Greedy Algorithms			
Elementary cases : Fractional Knapsack Problem, Task Scheduling	Data Compression using Huffman Trees		


Consigli

Registrazione


Crea un account o [accedi](#) per vedere cosa consigliano i tuoi amici.



Functional Programming – A General Overview – The Learning Point
 3 people recommended this.



The Learning Point
 70 people recommended this.



Arrays and Sorting: Merge Sort (with C Program source code) – The Learning Point
 17 people recommended this.

Plug-in sociale di Facebook




<http://www.thelearningpoint.net/computer-science/algorithms-dynamic-programming---longest-common-subsequence>

Pagina 4 di 5


Like

Send


10 people like this. [Sign Up](#) to see what your friends



Recommend this on Google



Add a comment...



Om Bachchan · Amity School of Engineering & Technology

The input to this problem is a pair of strings of letters A = a1... am possible. The rules are as follows:

- For a cost of 3 you can delete any letter.
- For a cost of 4 you can insert a letter in any position.
- For a cost of 5 you can replace any letter by any other letter.

For example, you can convert A = abcabc to B = abacab via the fol which at cost of 3 can be converted to ababc, which at cost of 3 ca abacb, which at cost of 4 can be converted to abacab. Thus the tot the cheapest possible conversion.

I/O description. Input: the two strings on separate consecutive lin.

Reply · 1 · Like · October 24 at 7:48am

Facebook social plugin