Software Release Standard - (SRLS)

Software Release Standard - (SRLS)

OOF® Origin Open Foundation®

Independent Methodological Authority

Architecture: SLGA™ — Software Lifecycle Governance Architecture

Category: Governance & Enforcement

Subcategory: Software Release Governance

Type: Parent Standard

Governed Space: Software Release Governance

Standard ID: SLGA-SRLS-07

Origin ID: OOF-SLGA-SRLS

Version: 1.0

Status: Canonical Parent Standard

Effective Date: 13.10.2026

Compatibility: Human-Developed, AI-Assisted, Automated, and Autonomous

AI-Readable: Yes

Authority: OOF® — OriginOpen® Foundation

Protection: OOF® Methodological Intellectual Property

Canonical Language: English

Architecture: SLGA™ — Software Lifecycle Governance Architecture

Category: Governance & Enforcement

Subcategory: Software Lifecycle Governance

Governed Space: Software Release Governance

Architecture: SLGA™ — Software Lifecycle Governance Architecture

Parent Standard: Software Release Standard (SRLS)

Category: Governance & Enforcement

Subcategory: Software Lifecycle Governance

Governed Space: Software Release Governance

Version: 1.0

Status: Canonical · Open Standard

Effective Date: 13.10.2026

Authority: OOF® — OriginOpen® Foundation

Canonical Language: English (UCL™)

Architecture: SLGA™ — Software Lifecycle Governance Architecture

Parent Standard: SRLS — Software Release Standard

Category: Governance & Enforcement

Subcategory: Software Lifecycle Governance

Type: Core Module

Governed Space: Software Release Candidate Governance

Module ID: SLGA-SRLS-RCMM-01

Origin ID: OOF-SLGA-SRLS-RCMM

Version: 1.0

Status: Canonical Open

Effective Date: 13.10.2026

Compatibility: Methodology OS — Modular Compatibility

GIE-Compatible: Yes

AI-Readable: Yes

Authority: OOF® — OriginOpen® Foundation

Protection: Protected Methodological Work

Canonical Language: English

Version: ### 7\. Scope

Version: A candidate identifier must refer to a sufficiently defined candidate state

Version: ### 43\. Evidence Integrity

Version: ### 62\. Minimum Implementation Framework

Version: ### 69\. Practical Applications

Architecture: SLGA™ — Software Lifecycle Governance Architecture

Parent Standard: SRLS — Software Release Standard

Category: Governance & Enforcement

Subcategory: Software Lifecycle Governance

Type: Core Module

Governed Space: Software Release Readiness Governance

Module ID: SLGA-SRLS-RRM-02

Origin ID: OOF-SLGA-SRLS-RRM

Version: 1.0

Status: Canonical Open

Effective Date: 13.10.2026

Compatibility: Methodology OS — Modular Compatibility

GIE-Compatible: Yes

AI-Readable: Yes

Authority: OOF® — OriginOpen® Foundation

Protection: Protected Methodological Work

Canonical Language: English

Canonical Definition

RRM — Release Readiness Module is the Core Module within SRLS that governs how an identifiable software release candidate is assessed against applicable requirements, quality, security, dependency, configuration, evidence, and release-specific conditions to determine whether its readiness for release authorization is sufficiently established.

RRM establishes the methodological conditions under which a software

release candidate may be recognized as ready, not ready, conditionally ready, evidence-limited, conflicted, or undetermined within an explicitly defined release scope.

It governs the relationship between the exact release candidate, applicable

readiness criteria, supporting lifecycle assessments, unresolved findings, exceptions, restrictions, and the resulting readiness determination.

RRM ensures that successful builds, completed development tasks, passing tests, automated pipeline results, or agent-generated readiness declarations cannot independently establish software release readiness.

The module preserves the distinction between technical verification results

and the broader governance conditions required to support a release decision.

It also ensures that readiness conclusions remain bound to the candidate identity, assessment boundary, evidence, and conditions under which they were established.

RRM does not independently grant release authorization or deployment permission.

Its principal governed output is the Software Release Readiness Profile.

Build Success ≠ Release Readiness.

Testing Success ≠ Sufficient Release Verification.

Release Conditions Assessed ≠ Release Conditions Satisfied.

Release Readiness Established ≠ Release Authorization Granted.

Release Readiness Valid Previously ≠ Release Readiness Valid After

Material Change.

Operational Role

RRM governs the evidence-supported assessment of software release readiness.

Its operational role is to establish:

• Release candidate identity

- Readiness assessment identity
- Assessment purpose
- Assessment scope and boundary
- Applicable release criteria
- Requirements alignment
- Quality condition references
- Security condition references
- Dependency condition references
- Configuration condition references
- Artifact integrity references
- Test coverage relevance
- Unresolved defects
- Unresolved vulnerabilities
- Release restrictions
- Evidence provenance
- Evidence sufficiency
- Evidence applicability
- Evidence conflicts
- Readiness uncertainty
- Condition status
- Exception applicability
- Material finding assessment
- Readiness classification
- Reassessment triggers
- Readiness validity boundaries
- Authorization handoff

RRM evaluates the applicability of findings established by responsible

lifecycle standards.

It does not replace their underlying technical assessments, independently certify software safety, or authorize the release.

Operational Question

How can an identifiable software release candidate be assessed for release readiness when requirements, quality, security, dependencies, configurations, testing evidence, unresolved findings, and automated development results may differ in completeness, reliability, and applicability, while ensuring that unknown conditions, exceptions, material changes, and authorization boundaries remain explicitly governed?

Position in Architecture Governance Flow

SLGA™ Governance Flow

Software Requirements → Software Creation → Software Dependencies →

Software Configuration → Software Quality → Software Security → Software Release → Software Deployment → Software Change Management → Software Retirement

Cross-cutting:

Software Lifecycle Control

SRLS Core Module Flow

RCMM — Release Candidate Management Module

2. RRM — Release Readiness Module 3. RAM — Release Authorization Module 4. RRMM — Release Record Management Module 5. RWM — Release Withdrawal Module

RRM occupies the second Core Module position within SRLS.

It receives the Software Release Candidate Profile established by RCMM.

It evaluates the candidate against applicable release conditions and

supporting lifecycle governance references.

Its output establishes the readiness state submitted to RAM for release

authorization consideration.

RRM does not convert a readiness determination into an authorization decision.

Software Release Candidate Profile → Readiness Assessment Scope →

Applicable Release Criteria → Requirements Alignment → Quality & Security Conditions → Dependency & Configuration Conditions → Evidence Sufficiency → Unresolved Findings → Exception Assessment → Readiness Classification → Software Release Readiness Profile → RAM Authorization Handoff

• Governed Space

Software Release Readiness Governance

This governed space concerns the evidence-supported determination of

whether an identifiable software release candidate satisfies the applicable conditions for consideration under release authorization governance.

It includes:

• Readiness assessment identity

• Candidate association

• Assessment scope

• Readiness criteria

• Requirements alignment

• Quality findings

• Security findings

• Dependency conditions

• Configuration conditions

• Artifact integrity conditions

• Evidence sufficiency

• Unresolved findings

• Materiality

• Exceptions and restrictions

• Readiness classification

• Validity boundaries

• Reassessment

• Authorization handoff

RRM does not independently govern release authorization, deployment authorization, production operation, or general authority legitimacy.

Governed Object

The primary Governed Object is:

A Software Release Readiness State representing the evidence-supported

relationship between an identifiable release candidate, applicable readiness criteria, relevant lifecycle findings, unresolved conditions, exceptions, restrictions, and the resulting readiness determination within defined assessment boundaries.

The governed state must preserve:

Release Candidate ID

Readiness Assessment ID

Assessment Purpose

Assessment Boundary

Applicable Readiness Criteria

Requirements Alignment State

Quality Condition State

Security Condition State

Dependency Condition State

Configuration Condition State

Artifact Integrity State

Evidence Sufficiency State

Unresolved Findings

Exception References

Readiness Classification

Validity Conditions

Reassessment Requirement

Version

Scope

RRM governs:

• Release readiness assessment establishment

• Candidate-specific readiness criteria

• Requirements alignment review

• Quality and security condition integration

• Dependency and configuration condition integration

• Artifact integrity references

• Test evidence applicability

• Unresolved finding assessment

• Evidence sufficiency

• Condition classification

• Exception and restriction treatment

• Readiness determination

• Readiness validity

• Reassessment

• Authorization handoff

RRM does not independently perform software development, testing, security remediation, release approval, or deployment.

Foundational Governance Principles 8.1 Readiness Principle

Build Success ≠ Release Readiness. 8.2 Verification Principle

Testing Success ≠ Sufficient Release Verification. 8.3 Requirements Principle

Implemented Behavior ≠ Approved Software Requirements. 8.4 Evidence Principle

Readiness Evidence Available ≠ Readiness Evidence Sufficient. 8.5 Condition Principle

Release Conditions Assessed ≠ Release Conditions Satisfied. 8.6 Uncertainty Principle

Unknown Release Condition ≠ Satisfied Release Condition. 8.7 Exception Principle

Release Exception Approved ≠ Underlying Condition Satisfied. 8.8 Authorization Principle

Release Readiness Established ≠ Release Authorization Granted. 8.9 Candidate Identity Principle

Readiness Established for One Candidate ≠ Readiness Established for

Another Candidate. 8.10 Continuity Principle

Release Readiness Valid Previously ≠ Release Readiness Valid After

Material Change.

Readiness Assessment Identity

Every governed readiness assessment must establish:

Readiness Assessment ID

Release Candidate ID

Software Product ID

Assessment Purpose

Assessment Scope

Assessment Boundary

Applicable Criteria Reference

Assessment Time

Evidence References

Assessment Classification

Version

Assessment Identity Principle

Readiness Assessment Recorded ≠ Readiness Assessment Applicable to the

Current Candidate.

The assessment must remain associated with the exact candidate state evaluated.

Readiness Assessment Purpose

The assessment purpose establishes why release readiness is being evaluated.

Relevant purposes include:

Initial Release Readiness

Maintenance Release Readiness

Security Patch Readiness

Emergency Release Readiness

Candidate Reassessment

Restricted Release Readiness

Post-Change Readiness Review

The assessment purpose does not independently determine which mandatory conditions may be omitted.

Purpose Integrity

Emergency Release Purpose ≠ Automatic Exemption From Mandatory Release

Conditions.

Readiness Assessment Boundary

The assessment boundary defines the conditions covered by the readiness

determination.

Relevant dimensions include:

Candidate Artifact Boundary

Functional Scope Boundary

Requirements Boundary

Quality Boundary

Security Boundary

Dependency Boundary

Configuration Boundary

Platform Boundary

Evidence Boundary

Temporal Boundary

Boundary Integrity

Readiness Established Within a Limited Boundary ≠ Readiness Established for Every Software Use or Environment.

Applicable Release Criteria

RRM identifies the criteria governing readiness for the particular

candidate and release context.

Relevant elements include:

Criterion ID

Criterion Purpose

Criterion Source

Criterion Applicability

Required Evidence

Acceptance Condition

Mandatory or Conditional Status

Exception Eligibility

Assessment Result

Unresolved Condition

Readiness criteria must be identifiable before their satisfaction is asserted.

Criteria Integrity

Release Criteria Documented ≠ Release Criteria Satisfied.

Criteria must not be retroactively weakened merely to convert an unfavorable readiness result into a favorable one.

Requirements Alignment Assessment

RRM evaluates whether relevant findings support alignment between the

proposed release and applicable software requirements.

Relevant elements include:

Requirements Baseline Reference

Release Scope

Implemented Functionality References

Requirements Traceability

Known Requirements Deviations

Unapproved Functionality Findings

Unimplemented Mandatory Requirements

Requirements Evidence

RRM uses SRS and relevant lifecycle evidence rather than independently

redefining approved requirements.

Requirements Alignment Principle

Software Functionality Working ≠ Software Functionality Authorized by

Requirements.

Quality Condition Assessment

RRM evaluates release-relevant quality findings established through SQS.

Relevant elements include:

Quality Requirements Reference

Quality Criteria

Test Coverage Findings

Test Execution Results

Defect Classification

Unresolved Defects

Quality Limitations

Quality Assessment Validity

A favorable quality assessment must remain associated with the candidate and conditions actually evaluated.

Quality Integrity

Quality Tests Passed ≠ All Material Quality Conditions Satisfied.

Security Condition Assessment

RRM evaluates release-relevant security findings established through SSS.

Relevant elements include:

Security Requirements

Security Testing Findings

Vulnerability Status

Exposure Conditions

Security Remediation References

Unresolved Security Findings

Security Restrictions

Security Evidence Validity

Security findings must not be concealed or treated as resolved merely because the release pipeline completed.

Security Integrity

Security Scan Completed ≠ Software Security Conditions Satisfied.

Dependency Condition Assessment

RRM evaluates the release implications of dependency conditions established

through SDS.

Relevant elements include:

Dependency Baseline Reference

Dependency Acceptance State

Critical Dependency Findings

Dependency Compatibility

Dependency Restrictions

Dependency Risk Findings

Unresolved Dependency Conditions

Dependency Change References

RRM does not independently authorize dependency introduction.

Dependency Integrity

Dependency Installed Successfully ≠ Dependency Acceptable for Release.

Configuration Condition Assessment

RRM evaluates relevant configuration findings established through SCFS.

Relevant elements include:

Configuration Baseline ID

Build Identity

Artifact Version Identity

Configuration Consistency

Build Reproducibility Findings

Artifact Equivalence Findings

Configuration Exceptions

Unresolved Configuration Conditions

Configuration Integrity

Configuration Baseline Recorded ≠ Release Candidate Configuration

Verified.

Artifact Integrity Assessment

RRM evaluates whether available artifact identity and integrity findings

remain applicable to the candidate.

Relevant elements include:

Release Candidate ID

Artifact Identity Reference

Build Artifact Reference

Artifact Integrity Evidence

Artifact Modification History

Artifact Comparison Findings

Unresolved Identity Conflicts

RRM consumes relevant RCMM and SCFS findings.

Artifact Integrity Principle

Artifact Integrity Evidence Available ≠ Every Constituent Artifact

Verified.

Test Coverage Relevance

RRM evaluates whether available test coverage is relevant to the release candidate and its applicable requirements and risks.

Relevant elements include:

Tested Requirements

Tested Components

Tested Configurations

Tested Interfaces

Tested Conditions

Untested Areas

Known Coverage Limitations

Candidate Applicability

RRM does not prescribe a universal test coverage percentage.

Coverage Principle

High Test Coverage ≠ Sufficient Coverage of Critical Software Behavior.

Test Result Applicability

RRM must determine whether available test results apply to the candidate being assessed.

Relevant elements include:

Tested Artifact ID

Current Candidate ID

Test Environment

Test Configuration

Test Execution Time

Relevant Dependency State

Material Changes Since Testing

Evidence Applicability

Test Applicability Principle

Tests Passed on a Previous Build ≠ Tests Passed on the Current Release

Candidate.

Unresolved Defect Assessment

RRM preserves release-relevant unresolved defects and their implications.

Relevant elements include:

Defect ID

Affected Component

Severity

Operational Significance

Requirements Impact

Known Workaround

Resolution Status

Release Restriction

Supporting Evidence

A defect may be technically unresolved without automatically prohibiting every release, provided applicable mandatory conditions and exception rules are respected.

Defect Assessment Principle

Defect Classified as Low Severity ≠ Defect Immaterial to Every Release

Context.

Unresolved Vulnerability Assessment

RRM evaluates the release implications of unresolved security

vulnerabilities.

Relevant elements include:

Vulnerability Reference

Affected Artifact

Exposure Context

Severity

Exploitability Findings

Potential Consequences

Mitigation State

Applicable Release Restrictions

Security Assessment Reference

Vulnerability Principle

Vulnerability Documented ≠ Vulnerability Risk Resolved.

Cross-Condition Consistency

RRM evaluates whether findings from different lifecycle domains remain

mutually consistent.

Relevant conflicts may include:

Requirements–Implementation Conflict

Build–Configuration Conflict

Dependency–Security Conflict

Quality–Security Conflict

Artifact–Evidence Conflict

Scope–Testing Conflict

Assessment–Candidate Identity Conflict

Material conflicts must remain visible until appropriately resolved.

Consistency Principle

Individual Assessments Passed ≠ Combined Release Conditions Consistent.

Release Readiness Evidence

RRM may use:

Requirements Traceability Records

Software Creation Records

Software Release Candidate Profile

Dependency Governance Profiles

Configuration Baselines

Build Records

Artifact Integrity Records

Quality Assessment Records

Test Coverage Records

Defect Records

Security Assessment Records

Vulnerability Records

Exception Decisions

Relevant Change Records

Evidence must be relevant to the specific candidate and readiness criteria.

Evidence Provenance

Readiness evidence must preserve:

Evidence ID

Evidence Source

Evidence Origin

Assessment or Collection Method

Referenced Candidate

Referenced Artifact

Relevant Configuration

Evidence Time

Evidence Content

Known Limitations

Version

Evidence Provenance Principle

Readiness Evidence Recorded ≠ Readiness Evidence Authentic or Applicable.

Evidence Sufficiency

Evidence sufficiency concerns whether the available evidence adequately

supports the applicable release readiness conditions.

Relevant dimensions include:

Requirements Coverage

Quality Evidence Coverage

Security Evidence Coverage

Dependency Evidence Coverage

Configuration Evidence Coverage

Artifact Identity Coverage

Evidence Reliability

Evidence Freshness

Evidence Consistency

Assessment Boundary Coverage

Evidence Sufficiency Principle

Large Volume of Test Evidence ≠ Sufficient Release Readiness Evidence.

Evidence Freshness

RRM evaluates whether evidence remains applicable to the current release

candidate and relevant conditions.

Relevant elements include:

Evidence Generation Time

Candidate Creation Time

Candidate Modification Time

Assessment Time

Configuration Changes

Dependency Changes

Relevant Security Changes

Evidence Validity Conditions

Freshness Principle

Evidence Previously Valid ≠ Evidence Currently Applicable.

Missing and Conflicting Evidence

RRM must preserve evidence gaps and conflicts affecting readiness.

Relevant conditions include:

Missing Requirements Evidence

Missing Quality Evidence

Missing Security Evidence

Missing Dependency Evidence

Missing Configuration Evidence

Missing Artifact Identity Evidence

Conflicting Test Results

Contradictory Assessment Findings

Unresolved Evidence Applicability

Evidence Gap Principle

Required Evidence Missing ≠ Applicable Condition Satisfied.

Readiness Condition States

Each applicable readiness condition must retain a distinguishable condition state.

The SLGA™ condition model includes:

Satisfied

Not Satisfied

Unknown

Not Applicable

Exception

A condition classified as Not Applicable requires an established basis for

inapplicability.

An Exception requires an applicable exception basis and must remain distinguishable from Satisfied.

Unknown must not be treated as Satisfied merely because no failure has been observed.

Condition State Integrity

Unknown ≠ Satisfied.

Not Applicable ≠ Not Assessed.

Exception ≠ Satisfied.

No Known Failure ≠ Positive Evidence of Readiness.

Material Finding Assessment

RRM evaluates whether unresolved findings materially affect release

readiness.

Relevant dimensions include:

Affected Requirement

Affected Functionality

Affected Artifact

Operational Criticality

Security Consequence

Quality Consequence

Dependency Consequence

Configuration Consequence

Evidence Uncertainty

Applicable Release Restriction

Materiality must be assessed within the actual release context.

Materiality Principle

Finding Minor in Technical Size ≠ Finding Immaterial to Release Readiness.

Release Readiness Exceptions

RRM governs the readiness implications of exceptions established under

applicable governance rules.

Relevant elements include:

Exception ID

Affected Criterion

Exception Reason

Exception Eligibility

Authority Reference

Exception Scope

Applicable Restrictions

Validity Period

Residual Uncertainty

Required Follow-Up

RRM does not independently create general authority to override mandatory requirements.

Exception Integrity

Exception Approved ≠ Underlying Release Condition Satisfied.

An exception cannot override a non-exceptionable mandatory condition.

Conditional Readiness

Conditional readiness may be established only where applicable rules permit readiness to be qualified by explicit conditions or restrictions.

Relevant elements include:

Conditional Readiness Basis

Applicable Criteria

Satisfied Conditions

Excepted Conditions

Restrictions

Unresolved Limitations

Evidence Basis

Authorization Implications

Conditional readiness must not conceal an unresolved mandatory prohibition.

Conditional Readiness Principle

Conditional Readiness ≠ Unrestricted Release Readiness.

Readiness Classification

RRM may classify readiness states as:

Assessment Not Initiated

Assessment Pending

Criteria Incomplete

Evidence Collection Pending

Evidence-Limited

Conditions Under Review

Readiness Established

Conditional Readiness Established

Readiness Not Established

Mandatory Condition Not Satisfied

Exception Review Required

Material Finding Unresolved

Conflicted

Unknown

Reassessment Required

Readiness Superseded

Assessment Closed

These are release readiness classifications, not release authorization decisions.

Classification Integrity

Readiness Established ≠ Release Authorized.

A readiness determination must be transferred to the appropriate release authorization mechanism.

Readiness Validity Conditions

Every established readiness conclusion must remain associated with its applicable validity conditions.

Relevant elements include:

Release Candidate Identity

Assessment Scope

Artifact Baseline

Configuration Baseline

Dependency Baseline

Requirements Baseline

Quality Assessment References

Security Assessment References

Evidence Applicability

Relevant Time Conditions

Known Restrictions

Validity Principle

Readiness Established Under One Set of Conditions ≠ Readiness Established

Under Materially Different Conditions.

Readiness Reassessment

RRM governs the need to reassess readiness when relevant conditions change.

Reassessment triggers may include:

Candidate Artifact Change

Requirements Change

Configuration Change

Dependency Change

New Quality Finding

New Security Finding

Test Evidence Invalidated

Previously Unknown Condition Identified

Exception Expiration

Assessment Boundary Change

Material Evidence Conflict

Reassessment may be targeted to affected conditions where sufficient evidence establishes that unaffected findings remain applicable.

Reassessment Principle

Readiness Reassessment Triggered ≠ Previous Readiness Automatically

Reconfirmed.

Software Release Readiness Profile

The principal governed output is the:

Software Release Readiness Profile

It establishes the evidence-supported readiness state of an identifiable

release candidate.

The profile preserves:

• Candidate identity

• Assessment identity

• Assessment purpose and scope

• Applicable readiness criteria

• Requirements alignment

• Quality condition state

• Security condition state

• Dependency condition state

• Configuration condition state

• Artifact integrity references

• Evidence sufficiency

• Unresolved findings

• Exceptions and restrictions

• Readiness classification

• Validity conditions

• Reassessment requirements

• Authorization handoff

Minimum Profile Fields

At minimum:

Software Release Readiness Profile ID

Readiness Assessment ID

Release Candidate ID

Software Product ID

Candidate Revision

Assessment Purpose

Assessment Boundary

Applicable Readiness Criteria

Requirements Baseline Reference

Requirements Alignment State

Quality Assessment Reference

Quality Condition State

Security Assessment Reference

Security Condition State

Dependency Baseline Reference

Dependency Condition State

Configuration Baseline Reference

Configuration Condition State

Artifact Integrity Reference

Test Coverage Reference

Unresolved Defect Register

Unresolved Vulnerability Register

Material Finding Register

Evidence Provenance

Evidence Sufficiency

Evidence Freshness

Missing Evidence

Evidence Conflicts

Condition State Register

Exception References

Release Restrictions

Readiness Classification

Validity Conditions

Reassessment Requirement

Authorization Handoff Status

Effective Time

Version

Minimum Implementation Framework

A minimum operational RRM implementation should contain eight governed layers. Layer 1 — Candidate and Assessment Identity

Establish the exact release candidate, assessment identity, purpose, scope,

and boundaries. Layer 2 — Applicable Readiness Criteria

Identify the release conditions, mandatory requirements, acceptance

criteria, and permitted exception rules. Layer 3 — Requirements and Quality Assessment

Evaluate applicable requirements alignment, quality findings, test

coverage, and unresolved defects. Layer 4 — Security, Dependency and Configuration Assessment

Evaluate security findings, dependency conditions, configuration

consistency, and relevant artifact integrity evidence. Layer 5 — Evidence and Condition Assessment

Determine evidence provenance, sufficiency, freshness, applicability,

conflicts, and individual condition states. Layer 6 — Material Findings and Exceptions

Evaluate unresolved findings, materiality, restrictions, and valid

exception conditions. Layer 7 — Readiness Classification and Validity

Establish the readiness determination and preserve the conditions under

which it remains applicable. Layer 8 — Governed Output and Authorization Handoff

Produce the Software Release Readiness Profile and transfer the governed

readiness state to RAM.

Minimum Decision States

At minimum:

Assessment Not Initiated

Candidate Identified

Assessment Boundary Established

Readiness Criteria Identified

Criteria Applicability Pending

Requirements Assessment Pending

Quality Assessment Pending

Security Assessment Pending

Dependency Assessment Pending

Configuration Assessment Pending

Evidence Review Pending

Evidence Sufficient

Evidence Insufficient

Evidence Conflicted

Condition Satisfied

Condition Not Satisfied

Condition Unknown

Condition Not Applicable

Condition Exception

Material Finding Identified

Exception Review Required

Readiness Not Established

Conditional Readiness Established

Readiness Established

Reassessment Required

Readiness Superseded

Authorization Handoff Completed

Unknown

Minimum Evidence Path

Where release readiness cannot be sufficiently established:

Software Release Candidate Profile → Assessment Scope → Applicable Release

Criteria → Requirements Evidence → Quality Evidence → Security Evidence → Dependency Evidence → Configuration Evidence → Artifact Integrity Evidence → Evidence Sufficiency Review → Condition Classification → Missing / Conflicted / Unknown / Not Satisfied Condition → Materiality Assessment → Evidence Acquisition / Corrective Handoff / Exception Review → Targeted Reassessment → Readiness Classification → Software Release Readiness Profile → RAM Authorization Handoff

Missing evidence must not be replaced by assumed readiness.

Minimum Reassessment Framework

Current Software Release Readiness Profile → New Candidate or Lifecycle

Event → Material Change Identification → Candidate Identity Review → Requirements Applicability Review → Quality Evidence Review → Security Evidence Review → Dependency Condition Review → Configuration Condition Review → Evidence Sufficiency Review → Exception Validity Review → Condition State Update → Readiness Reclassification → Historical State Preservation → Profile Update → Authorization Handoff Update

Reassessment must distinguish:

Candidate Changed

Requirements Changed

Quality Conditions Changed

Security Conditions Changed

Dependencies Changed

Configuration Changed

Evidence Changed

Exception Conditions Changed

Previous Readiness Still Supported

Readiness Reassessment Required

Readiness No Longer Established

Governance Requirements

A conforming RRM implementation must satisfy the following requirements. Assessment Identity and Criteria

• Identify the release candidate being assessed

• Establish the readiness assessment identity

• Define assessment purpose

• Define assessment scope

• Preserve assessment boundaries

• Identify applicable release criteria

• Distinguish mandatory and conditional criteria

• Preserve criterion applicability

• Identify permitted exception conditions

• Prevent incomplete criteria from automatically establishing

readiness.

Requirements and Quality

• Preserve applicable requirements references

• Evaluate release scope alignment

• Identify material requirements deviations

• Preserve quality assessment references

• Evaluate relevant test coverage

• Preserve unresolved defects

• Assess defect materiality

• Prevent build success from replacing quality assessment

• Prevent passing tests from automatically establishing requirements

alignment.

Security, Dependencies and Configuration

• Preserve security assessment references

• Evaluate unresolved security findings

• Preserve relevant vulnerability conditions

• Preserve dependency baseline references

• Evaluate dependency acceptance conditions

• Identify unresolved dependency restrictions

• Preserve configuration baseline references

• Evaluate configuration consistency

• Preserve artifact integrity references

• Prevent successful dependency installation from establishing

• Prevent configuration declarations from replacing configuration

dependency acceptance. evidence.

Evidence Governance

• Preserve readiness evidence provenance

• Preserve evidence applicability to the exact candidate

• Evaluate evidence sufficiency

• Evaluate evidence freshness

• Identify missing evidence

• Preserve conflicting evidence

• Preserve relevant uncertainty

• Prevent historical evidence from automatically applying after

• Prevent evidence volume from replacing evidence relevance

• Prevent absent findings from being represented as positive evidence

material candidate changes. of readiness.

Conditions and Exceptions

Classify applicable conditions as Satisfied, Not Satisfied, Unknown,

Not Applicable, or Exception. 42. Preserve the basis for Not Applicable conditions. 43. Preserve the basis and authority references for exceptions. 44. Identify non-exceptionable mandatory conditions. 45. Preserve unresolved mandatory failures. 46. Assess material findings. 47. Preserve release restrictions. 48. Prevent Unknown from being treated as Satisfied. 49. Prevent Exception from being treated as Satisfied. 50. Prevent conditional readiness from being represented as unrestricted readiness.

Readiness Classification and Continuity

• Establish an evidence-supported readiness classification

• Preserve readiness validity conditions

• Bind readiness to the assessed candidate identity

• Preserve assessment limitations

• Identify material reassessment triggers

• Reassess affected conditions when required

• Preserve historical readiness states

• Preserve superseding readiness conclusions

• Prevent readiness for one candidate from automatically transferring

• Prevent readiness classification from becoming release authorization

to another.

Architecture Boundaries

• Maintain RCMM candidate identification boundaries

• Maintain SRS requirements governance boundaries

• Maintain SDS dependency governance boundaries

• Maintain SCFS configuration governance boundaries

• Maintain SQS quality governance boundaries

• Maintain SSS security governance boundaries

• Maintain RAM release authorization boundaries

• Maintain SCMS change governance boundaries

• Maintain SLCS lifecycle control boundaries

• Produce a Software Release Readiness Profile

Governance Logic

Canonical RRM logic:

Release Candidate Identity → Readiness Assessment Purpose → Assessment

Boundary → Applicable Release Criteria → Requirements Alignment → Quality Condition Assessment → Security Condition Assessment → Dependency Condition Assessment → Configuration Condition Assessment → Artifact Integrity Review → Test Evidence Applicability → Unresolved Findings → Evidence Provenance → Evidence Sufficiency → Evidence Freshness → Condition State Classification → Materiality Assessment → Exception & Restriction Review → Readiness Determination → Validity Condition Establishment → Software Release Readiness Profile → RAM Authorization Handoff

A readiness determination must not override unresolved mandatory conditions or create release authority.

Governance Outputs

RRM may produce:

Software Release Readiness Profile

Readiness Assessment Identity

Assessment Purpose Record

Assessment Boundary

Release Criteria Register

Requirements Alignment Assessment

Quality Condition Assessment

Security Condition Assessment

Dependency Condition Assessment

Configuration Condition Assessment

Artifact Integrity Assessment Reference

Test Coverage Applicability Record

Unresolved Defect Register

Unresolved Vulnerability Register

Material Finding Assessment

Readiness Evidence Register

Evidence Provenance Record

Evidence Sufficiency State

Evidence Freshness Assessment

Missing Evidence Record

Evidence Conflict Record

Condition State Register

Exception Reference

Release Restriction Record

Readiness Classification

Readiness Validity Conditions

Reassessment Requirement

Historical Readiness Reference

Authorization Handoff

Version

Practical Applications Autonomous Software Factories

Evaluating whether AI-generated software candidates satisfy release

requirements rather than relying solely on automated build and test success. Enterprise Release Management

Establishing consistent release readiness conditions across development

teams, software products, and delivery environments. Continuous Delivery Pipelines

Separating pipeline execution success from evidence-supported release

readiness. Security Patch Releases

Assessing whether emergency software updates satisfy applicable release

conditions while preserving unresolved risks and restrictions. Critical Infrastructure Software

Evaluating release readiness where software defects, configuration changes, or security vulnerabilities may affect essential operational functions. AI-Assisted Software Maintenance

Reassessing readiness after AI agents modify existing software,

dependencies, configurations, or implementation behavior.

• Use Case 1 — An AI Agent Produces Software That Passes Every Test but

Contains an Unauthorized Function

An organization authorizes an autonomous AI development system to create a

financial reporting application.

The approved requirements define data collection, calculation, and report

generation functions.

During development, an AI agent introduces an automatic refund function

that was not included in the approved requirements.

Another agent generates tests for the implemented application.

All tests pass.

The automated pipeline reports:

Build Successful — Tests Passed — Release Ready.

The application is submitted for release authorization.

RRM evaluates:

Release Candidate Identity → Requirements Alignment → Test Coverage →

Quality Findings → Evidence Sufficiency → Readiness Classification

The assessment identifies:

• The release candidate is identifiable

• The application builds successfully

• Automated tests pass

• The additional refund function is outside the approved requirements

• Test success establishes that the implemented function behaves as

• Requirements alignment remains unresolved for the proposed release

tested, not that its inclusion was authorized.

The appropriate readiness classification is:

Readiness Not Established — Material Requirements Deviation.

The critical distinctions are:

Testing Success ≠ Requirements Alignment.

Implemented Functionality ≠ Authorized Functionality.

Automated Pipeline Success ≠ Release Readiness.

The result: RRM prevents a known requirements deviation from being

concealed behind successful automated testing.

RRM does not guarantee detection of every hidden function. It requires identified deviations and evidence limitations to remain explicit in the readiness determination.

Use Case 2 — A Critical Security Vulnerability Remains Unresolved

Before Release

A software company prepares a new version of an enterprise application.

The candidate has passed functional tests and satisfies its principal

performance requirements.

A security assessment identifies a vulnerability affecting an externally

accessible interface.

The development team records the vulnerability but does not complete remediation.

The release pipeline nevertheless reports that all required build and functional test stages have completed successfully.

The organization proposes to release the software because the application

is technically functional.

RRM evaluates:

Candidate Identity → Security Findings → Vulnerability Materiality →

Applicable Security Criteria → Evidence Sufficiency → Exception Eligibility → Readiness Classification

The assessment identifies:

• Functional quality conditions are supported

• A material security finding remains unresolved

• Technical functionality does not resolve the security condition

• Applicable release criteria must determine whether release is

• The vulnerability cannot be treated as satisfied merely because it has

prohibited, restricted, or eligible for a legitimate exception. been documented.

Where the applicable mandatory security condition prohibits release, the readiness classification is:

Readiness Not Established — Mandatory Security Condition Not Satisfied.

The critical distinctions are:

Functional Readiness ≠ Security Readiness.

Vulnerability Documented ≠ Vulnerability Resolved.

Exception Requested ≠ Exception Authorized.

The result: RRM preserves the security condition as an independent

release readiness requirement and prevents unrelated technical success from overriding it.

• Use Case 3 — Previously Valid Test Evidence Is Reused After a

Dependency Change

An organization completes release readiness assessment for a software

candidate.

Requirements alignment, quality findings, and security conditions are supported by relevant evidence.

Before authorization, an automated maintenance process updates a critical

external dependency.

The candidate retains the same visible version label.

The development pipeline does not rerun all affected tests.

Instead, it reuses the earlier readiness report.

RRM evaluates:

Original Candidate → Dependency Change → Artifact Applicability → Previous

Evidence → Affected Conditions → Reassessment Requirement → Updated Readiness State

The assessment identifies:

• Previous readiness evidence applied to the earlier candidate state

• A material dependency change occurred

• The unchanged version label does not establish artifact equivalence

• Previous test and security evidence may no longer cover the modified

• Targeted reassessment is required for affected conditions

• Unaffected findings may be retained only where their continued

candidate. applicability is sufficiently supported.

The appropriate classification is:

Reassessment Required — Previous Readiness Not Automatically Applicable.

The critical distinctions are:

Version Equality ≠ Artifact Equivalence.

Evidence Previously Valid ≠ Evidence Currently Applicable.

Previous Readiness ≠ Continuing Readiness.

The result: RRM prevents historical readiness evidence from being

automatically transferred to materially changed software.

Critical Distinctions

Build Success ≠ Release Readiness.

Testing Success ≠ Sufficient Release Verification.

Implemented Behavior ≠ Approved Software Requirements.

Readiness Evidence Available ≠ Readiness Evidence Sufficient.

Release Conditions Assessed ≠ Release Conditions Satisfied.

Unknown Release Condition ≠ Satisfied Release Condition.

Release Exception Approved ≠ Underlying Condition Satisfied.

Release Readiness Established ≠ Release Authorization Granted.

Readiness Established for One Candidate ≠ Readiness Established for

Another Candidate.

Readiness Assessment Recorded ≠ Readiness Assessment Applicable to the

Current Candidate.

Emergency Release Purpose ≠ Automatic Exemption From Mandatory Release

Conditions.

Readiness Established Within a Limited Boundary ≠ Readiness Established for Every Software Use or Environment.

Software Functionality Working ≠ Software Functionality Authorized by

Requirements.

Quality Tests Passed ≠ All Material Quality Conditions Satisfied.

Security Scan Completed ≠ Software Security Conditions Satisfied.

Dependency Installed Successfully ≠ Dependency Acceptable for Release.

Configuration Baseline Recorded ≠ Release Candidate Configuration

Verified.

High Test Coverage ≠ Sufficient Coverage of Critical Software Behavior.

Tests Passed on a Previous Build ≠ Tests Passed on the Current Release

Candidate.

Defect Classified as Low Severity ≠ Defect Immaterial to Every Release

Context.

Vulnerability Documented ≠ Vulnerability Risk Resolved.

Individual Assessments Passed ≠ Combined Release Conditions Consistent.

Readiness Evidence Recorded ≠ Readiness Evidence Authentic or Applicable.

Large Volume of Test Evidence ≠ Sufficient Release Readiness Evidence.

Evidence Previously Valid ≠ Evidence Currently Applicable.

Required Evidence Missing ≠ Applicable Condition Satisfied.

Not Applicable ≠ Not Assessed.

Exception ≠ Satisfied.

No Known Failure ≠ Positive Evidence of Readiness.

Finding Minor in Technical Size ≠ Finding Immaterial to Release Readiness.

Conditional Readiness ≠ Unrestricted Release Readiness.

Readiness Established Under One Set of Conditions ≠ Readiness Established

Under Materially Different Conditions.

Readiness Reassessment Triggered ≠ Previous Readiness Automatically

Reconfirmed.

Cross-Architecture Boundary

RRM may consume governed evidence from:

SRS — Software Requirements Standard

SCS — Software Creation Standard

SDS — Software Dependency Standard

SCFS — Software Configuration Standard

SQS — Software Quality Standard

SSS — Software Security Standard

SCMS — Software Change Management Standard

SLCS — Software Lifecycle Control Standard

Within SRLS, RRM receives the candidate identity and composition established by:

RCMM — Release Candidate Management Module

RRM provides the readiness determination to:

RAM — Release Authorization Module

Relevant decisions and evidence may subsequently be preserved through:

RRMM — Release Record Management Module

Material changes or invalidated release conditions may also become relevant to:

RWM — Release Withdrawal Module

RRM does not replace the substantive governance mechanisms responsible for requirements, quality, security, dependencies, configuration, or software changes.

Its role is to determine whether their relevant findings sufficiently support release readiness for the identified candidate.

Cross-Architecture Mechanism Principle

An operational mechanism may produce inputs for multiple governance architectures, but it belongs only to the architecture whose governed domain includes that mechanism itself. Other architectures govern only its domain-specific relevance or consequences.

RRM may consume software test results, vulnerability assessments, dependency records, configuration evidence, and requirements traceability.

It governs the release readiness implications of those findings.

It does not independently redefine their underlying assessment methods or assume the authority of the mechanisms that produced them.

Canonical Boundary

RRM governs how identifiable software release candidates are assessed against applicable requirements, quality, security, dependency, configuration, artifact integrity, evidence, and release-specific conditions to establish an evidence-supported readiness determination within explicit assessment and validity boundaries.

It does not independently create software requirements, execute testing, remediate vulnerabilities, authorize software release, authorize deployment, or certify that software is free from defects or harmful behavior.

Its principal governed output is the Software Release Readiness Profile.

Canonical Closing Statement

Software release readiness cannot be established merely because

development is complete, a build succeeds, or automated tests report success.

A software candidate may perform its tested functions correctly while containing behavior that was never authorized.

It may satisfy quality requirements while retaining unresolved security vulnerabilities.

It may be supported by extensive test evidence that applies to an earlier build rather than the artifact currently proposed for release.

And it may receive a favorable automated readiness report while material dependency, configuration, or requirements conditions remain unknown.

The absence of a detected failure is not evidence that every applicable release condition has been satisfied.

RRM establishes the methodological boundary between technical results and

evidence-supported release readiness.

It requires the exact candidate to be identified, the applicable criteria

to be established, the relevant lifecycle findings to be assessed, and unresolved conditions to remain visible.

It preserves the distinction between satisfied conditions, unsatisfied

conditions, unknown conditions, legitimate inapplicability, and explicitly governed exceptions.

It also ensures that readiness remains associated with the software artifact and conditions actually assessed.

A readiness conclusion is not permanent merely because it was valid when first established.

When software changes, dependencies change, configurations change, or new evidence emerges, the continued applicability of the readiness conclusion must be reassessed.

RRM establishes a fundamental release governance requirement: software

must not be represented as ready for authorization unless the applicable release conditions are sufficiently supported by relevant evidence and unresolved limitations remain explicitly governed.

This requirement applies regardless of whether software is developed by humans, automated pipelines, AI coding assistants, or autonomous software factories.

The actor may change.

The development process may accelerate.

The volume of automated testing may increase.

The requirement for evidence-supported release readiness remains.

RRM transforms release readiness from a technical success indicator into a

governed assessment state — ensuring that software is not considered ready merely because it works, but because the conditions required to justify its release have been sufficiently established.

Modul 3

RAM — Release Authorization Module

Architecture

SLGA™ — Software Lifecycle Governance Architecture

Parent Standard

SRLS — Software Release Standard

Category

Governance & Enforcement

Subcategory

Software Lifecycle Governance

Type

Core Module

Governed Space

Software Release Authorization Governance

Module ID

SLGA-SRLS-RAM-03

Origin ID

OOF-SLGA-SRLS-RAM

Version

1.0

Status

Canonical Open

Effective Date

10.2026

Compatibility

Methodology OS — Modular Compatibility

GIE-Compatible

Yes

AI-Readable

Yes

Authority

OOF® — OriginOpen® Foundation

Protection

Protected Methodological Work

Canonical Language

English

1. Canonical Definition

RAM — Release Authorization Module is the Core Module within SRLS that governs how software release authorization decisions are established, evaluated, granted, restricted, denied, suspended, and reassessed in relation to an identifiable release candidate, its established readiness state, applicable authority, authorization conditions, and defined release boundaries.

RAM establishes the methodological conditions under which a software

release candidate may receive legitimate authorization for release following the assessment of applicable readiness conclusions, decision authority, authorization scope, unresolved restrictions, exceptions, and supporting evidence.

It governs the relationship between the software artifact proposed for

release, the authority permitted to authorize its release, the conditions under which authorization may be exercised, and the continuing applicability of the resulting decision.

RAM distinguishes technical release capability from legitimate release

authority, readiness assessment from authorization, and authorization of a software release from permission to deploy that release into a particular operational environment.

The module applies to release decisions performed by humans,

organizational processes, automated pipelines, delegated AI systems, and autonomous software agents.

It does not assume that human approval is universally required.

It requires that the authority governing a release decision remain identifiable, applicable, bounded, and sufficiently supported regardless of the actor executing the decision.

Its principal governed output is the Software Release Authorization Profile.

Release Readiness Established ≠ Release Authorization Granted.

Technical Release Capability ≠ Legitimate Release Authority.

Development Authority ≠ Release Authorization Authority.

Automated Approval Executed ≠ Authorization Legitimacy Established.

Release Authorization ≠ Deployment Authorization.

2. Operational Role

RAM governs the establishment and continued applicability of software

release authorization decisions.

Its operational role is to establish:

• Release authorization identity

• Release candidate association

• Readiness assessment reference

• Authorization purpose

• Authorization scope

• Authorization boundary

• Applicable authority reference

• Authorized decision actor

• Delegation conditions

• Authorization prerequisites

• Mandatory readiness conditions

• Exception applicability

• Decision evidence

• Decision traceability

• Authorization restrictions

• Authorization validity period

• Authorization classification

• Authorization execution

• Authorization continuity

• Material change detection

• Reauthorization triggers

• Suspension and revocation references

• Release record handoff

• Deployment governance boundary

RAM does not independently establish general organizational authority, conduct software testing, certify release readiness, or execute deployment.

3. Operational Question

How can software release authorization be established and maintained as a legitimate, evidence-supported, candidate-specific, and bounded governance decision when release processes may be executed by humans, organizations, automated systems, or autonomous AI agents, while ensuring that technical capability, delegated authority, readiness conclusions, exceptions, restrictions, and material changes remain explicitly distinguishable?

4. Position in Architecture Governance Flow

SLGA™ Governance Flow

Software Requirements → Software Creation → Software Dependencies →

Software Configuration → Software Quality → Software Security → Software Release → Software Deployment → Software Change Management → Software Retirement

Cross-cutting:

Software Lifecycle Control

SRLS Core Module Flow

RCMM — Release Candidate Management Module

RRM — Release Readiness Module

RAM — Release Authorization Module

RRMM — Release Record Management Module

RWM — Release Withdrawal Module

RAM occupies the third Core Module position within SRLS.

It receives the identifiable candidate established by RCMM and the

readiness determination established by RRM.

RAM evaluates whether the applicable release authorization prerequisites

and authority conditions have been sufficiently established.

Its authorization decision remains bound to the candidate identity,

readiness conditions, authorization scope, and applicable restrictions.

Software Release Candidate Profile → Software Release Readiness Profile

→ Authorization Purpose → Authority Reference → Authorization Scope → Authorization Prerequisites → Decision Evidence → Exception & Restriction Review → Authorization Decision → Validity Conditions → Software Release Authorization Profile → Release Record Handoff

5. Governed Space

Software Release Authorization Governance

This governed space concerns the legitimate authorization of identifiable

software releases under applicable readiness, authority, evidence, and lifecycle conditions.

It includes:

• Authorization identity

• Candidate-specific authorization

• Readiness prerequisite verification

• Authority references

• Delegation applicability

• Authorization scope

• Authorization conditions

• Decision actor identification

• Authorization evidence

• Exceptions and restrictions

• Decision classification

• Authorization validity

• Reauthorization requirements

• Suspension and revocation references

• Historical authorization continuity

• Release record handoff

RAM does not independently govern deployment execution, operational acceptance, general authority creation, or organization-wide accountability assignment.

6. Governed Object

The primary Governed Object is:

A Software Release Authorization State representing the

evidence-supported relationship between an identifiable software release candidate, its readiness determination, applicable release authority, authorization prerequisites, decision actor, scope, restrictions, validity conditions, and resulting authorization decision.

The governed state must preserve:

Software Product ID

Release Candidate ID

Release Authorization ID

Readiness Assessment Reference

Authorization Purpose

Authority Reference

Decision Actor Reference

Authorization Scope

Authorization Boundary

Authorization Prerequisites

Exception References

Restrictions

Decision Evidence

Authorization Classification

Validity Conditions

Reauthorization Requirement

Historical Authorization Reference

Version

7. Scope

RAM governs:

• Release authorization requests

• Candidate and readiness association

• Applicable release authority

• Decision actor eligibility

• Delegation references

• Authorization scope and boundaries

• Authorization prerequisites

• Decision evidence

• Exceptions and restrictions

• Authorization classifications

• Decision validity

• Reauthorization triggers

• Suspension and revocation references

• Historical authorization continuity

• Release record handoff

RAM does not independently determine whether an organization possesses legitimate authority to create a delegation, nor does it replace the mechanisms responsible for validating the underlying readiness conditions.

8. Foundational Governance Principles

8.1 Authorization Legitimacy Principle

Technical Release Capability ≠ Legitimate Release Authority.

8.2 Readiness–Authorization Separation Principle

Release Readiness Established ≠ Release Authorization Granted.

8.3 Actor Independence Principle

Human Approval ≠ Automatically Legitimate Approval.

8.4 Delegation Principle

Task Authority ≠ Constituent Action Authority.

8.5 Candidate Specificity Principle

Authorization for One Release Candidate ≠ Authorization for Every Candidate.

8.6 Scope Integrity Principle

Release Authorization Granted Within a Defined Scope ≠ Unrestricted Release Authority.

8.7 Evidence Principle

Authorization Record Available ≠ Authorization Legitimacy Established.

8.8 Exception Principle

Exception Approved ≠ Mandatory Authorization Condition Satisfied.

8.9 Continuity Principle

Authorization Previously Valid ≠ Authorization Continuously Applicable.

8.10 Deployment Boundary Principle

Release Authorization ≠ Deployment Authorization.

9. Release Authorization Identity

Every governed authorization decision must establish:

Release Authorization ID

Software Product ID

Release Candidate ID

Readiness Assessment ID

Authorization Purpose

Authorization Scope

Authority Reference

Decision Actor Reference

Decision Time

Authorization Classification

Version

10. Authorization Identity Principle

Release Approval Recorded ≠ Release Authorization Identity Sufficiently

Established.

The authorization must remain associated with the exact candidate and decision context to which it applies.

11. Authorization Purpose

The authorization purpose establishes the intended release decision.

Relevant purposes include:

Initial Software Release

Maintenance Release

Security Patch Release

Emergency Release

Restricted Release

Release Reauthorization

Release Authorization Reassessment

Purpose classification does not independently establish authority or eligibility.

12. Purpose Integrity

Emergency Release Purpose ≠ Unlimited Emergency Release Authority.

13. Authorization Request

A release authorization request must identify:

Authorization Request ID

Requesting Actor

Software Product

Release Candidate

Readiness Assessment

Requested Release Scope

Requested Authorization Type

Supporting Evidence

Known Restrictions

Requested Decision Time

The requesting actor does not automatically possess decision authority.

14. Request Integrity

Release Authorization Requested ≠ Release Authorization Permitted.

15. Release Candidate Association

RAM must associate authorization with an identifiable release candidate.

Relevant elements include:

Release Candidate ID

Candidate Revision

Artifact Baseline

Configuration Baseline

Dependency Baseline

Candidate Composition Reference

Candidate Classification

Candidate Evidence Reference

The candidate identity is established through RCMM.

16. Candidate Association Principle

Release Candidate Name Matches ≠ Authorized Artifact Identity Matches.

17. Readiness Assessment Association

RAM must reference the applicable readiness determination established through RRM.

Relevant elements include:

Readiness Assessment ID

Readiness Classification

Assessment Boundary

Applicable Release Criteria

Unresolved Findings

Exceptions

Restrictions

Validity Conditions

Reassessment Requirements

18. Readiness Association Principle

Readiness Profile Attached ≠ Readiness Profile Applicable to the Current

Candidate.

19. Applicable Release Authority

RAM identifies the authority under which a release decision may legitimately be made.

Relevant elements include:

Authority Reference

Authority Source

Authority Holder

Authorized Decision Function

Authority Scope

Authority Conditions

Authority Limitations

Authority Validity

Authority Status

General authority legitimacy remains governed by the applicable authority

architecture, including GOA™.

20. Authority Principle

Authority Claimed ≠ Authority Established.

21. Decision Actor Identification

RAM identifies the actor executing the authorization decision.

Possible actors include:

Authorized Human

Authorized Organizational Function

Automated Approval System

Delegated AI Agent

Autonomous Software Governance Agent

Hybrid Human–Machine Decision Process

Actor identity must remain distinguishable from the authority under which the actor operates.

22. Actor Identity Principle

Decision Actor Identified ≠ Decision Actor Authorized.

23. Delegated Release Authority

Where release authorization is delegated, RAM must preserve:

Delegation Reference

Delegating Authority

Receiving Actor

Delegated Release Function

Delegation Scope

Permitted Candidate Categories

Applicable Conditions

Delegation Limitations

Delegation Validity

Revocation Reference

Delegation must not exceed the authority legitimately available to the delegating actor.

24. Delegation Integrity

Authority to Develop Software ≠ Authority to Authorize Its Release.

25. Automated Release Authorization

Automated release authorization may be used where legitimate authority and applicable decision conditions have been established.

Relevant elements include:

Automated Decision System ID

Authorization Policy Reference

Delegated Authority Reference

Permitted Decision Scope

Required Readiness State

Mandatory Conditions

Exception Restrictions

Decision Evidence

Decision Traceability

Human Intervention Conditions

Automation must not convert technical pipeline completion into authorization by default.

26. Automation Principle

Automated Approval Rule Executed ≠ Legitimate Authorization

Established.

27. Autonomous Agent Authorization

Where autonomous AI agents execute release authorization decisions, RAM must preserve:

Agent Identity Reference

Agent Authority Reference

Delegated Release Function

Permitted Release Scope

Candidate Eligibility

Decision Constraints

Tool Execution References

Decision Evidence

Escalation Conditions

Override Conditions

Authorization Event

Agent authority must remain bounded by the specific release decision and its constituent actions.

28. Autonomous Authority Principle

Agent Authorized to Complete a Release Workflow ≠ Agent Authorized to

Approve Every Release Within That Workflow.

29. Authorization Scope

Authorization scope defines the permitted release action.

Relevant dimensions include:

Software Product Scope

Release Candidate Scope

Artifact Scope

Version Scope

Distribution Scope

Recipient Scope

Release Channel Scope

Temporal Scope

Operational Restrictions

Authority Scope

30. Scope Integrity

Authorization Granted for One Release Channel ≠ Authorization Granted

for Every Distribution Channel.

31. Authorization Boundary

The authorization boundary establishes the limits within which the decision applies.

Relevant boundaries include:

Candidate Identity Boundary

Artifact Composition Boundary

Configuration Boundary

Dependency Boundary

Readiness Boundary

Authority Boundary

Distribution Boundary

Temporal Boundary

Evidence Boundary

Exception Boundary

32. Boundary Integrity

Release Authorization Within a Defined Boundary ≠ Authorization Outside That Boundary.

33. Authorization Prerequisites

RAM identifies the conditions required before authorization may be granted.

Relevant prerequisites include:

Candidate Identity Established

Applicable Readiness State Established

Mandatory Release Conditions Satisfied

Applicable Exceptions Valid

Authorization Authority Established

Decision Actor Eligible

Authorization Scope Defined

Evidence Sufficient

Material Conflicts Resolved

Restrictions Preserved

34. Prerequisite Principle

Authorization Prerequisites Listed ≠ Authorization Prerequisites

Satisfied.

35. Mandatory Authorization Conditions

Mandatory authorization conditions must remain distinguishable from optional or exceptionable conditions.

Relevant elements include:

Condition ID

Condition Source

Condition Purpose

Condition Applicability

Condition Status

Evidence Reference

Exception Eligibility

Decision Consequence

A mandatory condition that is not satisfied cannot be silently converted into an authorized state.

36. Mandatory Condition Principle

Mandatory Condition Not Satisfied ≠ Authorization Permitted by

Default.

37. Readiness Classification Review

RAM evaluates whether the RRM readiness classification permits

authorization consideration.

Relevant classifications include:

Readiness Established

Conditional Readiness Established

Readiness Not Established

Evidence-Limited

Conflicted

Unknown

Reassessment Required

Only classifications compatible with the applicable authorization

conditions may support a favorable decision.

38. Readiness Review Principle

Conditional Readiness ≠ Automatic Conditional Release Authorization.

39. Authorization Evidence

RAM may use:

Software Release Candidate Profile

Software Release Readiness Profile

Authority Governance References

Delegation Records

Authorization Policy References

Applicable Exception Decisions

Release Restrictions

Candidate Identity Evidence

Decision Actor Records

Decision Execution Records

Relevant Change Records

Evidence must remain applicable to the authorization decision.

40. Evidence Provenance

Authorization evidence must preserve:

Evidence ID

Evidence Source

Evidence Origin

Evidence Type

Referenced Candidate

Referenced Readiness Assessment

Referenced Authority

Evidence Time

Decision Relevance

Known Limitations

Version

41. Evidence Integrity

Authorization Evidence Recorded ≠ Authorization Evidence Sufficient.

42. Authorization Evidence Sufficiency

Evidence sufficiency concerns whether the available evidence adequately

supports the proposed authorization decision.

Relevant dimensions include:

Candidate Identity Coverage

Readiness Applicability

Authority Validity

Decision Actor Eligibility

Delegation Applicability

Authorization Scope

Mandatory Condition Coverage

Exception Validity

Evidence Consistency

Evidence Freshness

43. Evidence Sufficiency Principle

Release Approval Supported by Some Evidence ≠ Release Authorization

Sufficiently Supported.

44. Authority Validity Assessment

RAM must evaluate whether the referenced authority remains applicable.

Relevant elements include:

Authority Status

Authority Scope

Authority Conditions

Authority Expiration

Delegation Status

Revocation Status

Applicable Restrictions

Decision Time

45. Authority Validity Principle

Authority Valid Previously ≠ Authority Valid at the Time of Release

Authorization.

46. Authorization Condition States

Applicable authorization conditions must preserve the SLGA™ condition model:

Satisfied

Not Satisfied

Unknown

Not Applicable

Exception

A favorable authorization decision requires the applicable decision rules

to be met.

Unknown must not be treated as Satisfied.

Not Applicable requires a supported basis.

Exception requires a legitimate exception basis and must remain distinguishable from satisfaction.

47. Condition State Integrity

Unknown ≠ Satisfied.

Not Applicable ≠ Not Assessed.

Exception ≠ Satisfied.

Condition Not Satisfied ≠ Condition Waived.

48. Authorization Exceptions

RAM governs the release authorization implications of applicable

exceptions.

Relevant elements include:

Exception ID

Affected Condition

Exception Basis

Exception Authority Reference

Exception Scope

Exception Validity

Residual Risk Reference

Required Restrictions

Exception Evidence

Reassessment Requirement

An exception may permit a restricted decision only where the applicable governance rules allow it.

49. Exception Integrity

Exception Granted for One Condition ≠ Exception Granted for Every

Authorization Condition.

50. Authorization Restrictions

RAM preserves restrictions affecting the release authorization decision.

Relevant restrictions may include:

Limited Release Scope

Restricted Distribution Channel

Restricted Recipient Group

Restricted Candidate Configuration

Defined Validity Period

Mandatory Monitoring Reference

Required Follow-Up Assessment

Exception-Specific Restriction

Restrictions must remain associated with the authorization state.

51. Restriction Principle

Restricted Release Authorization ≠ Unrestricted Release Authorization.

52. Authorization Decision

RAM establishes an explicit decision concerning the identified release

candidate.

Relevant decision elements include:

Decision ID

Candidate ID

Readiness Reference

Authority Reference

Decision Actor

Decision Scope

Decision Conditions

Decision Evidence

Decision Time

Decision Classification

Restrictions

Validity Conditions

The decision must not exceed the applicable authority or readiness boundaries.

53. Decision Integrity

Approval Action Completed ≠ Legitimate Release Authorization Decision

Established.

54. Authorization Classification

RAM may classify authorization states as:

Authorization Not Requested

Authorization Requested

Authorization Review Pending

Authority Verification Pending

Readiness Prerequisite Pending

Evidence-Limited

Conflicted

Unknown

Authorization Denied

Authorization Granted

Restricted Authorization Granted

Authorization Deferred

Reauthorization Required

Authorization Suspended

Authorization Revoked

Authorization Expired

Authorization Superseded

Authorization Closed

These classifications must remain distinguishable from release readiness and deployment states.

55. Classification Integrity

Authorization Granted ≠ Software Deployed.

Authorization Denied ≠ Release Candidate Deleted.

Authorization Suspended ≠ Authorization Revoked.

56. Authorization Validity Conditions

Every authorization decision must preserve its applicable validity conditions.

Relevant elements include:

Authorized Candidate Identity

Authorized Artifact Baseline

Authorized Configuration

Authorized Dependency Context

Readiness Assessment Reference

Authority Validity

Decision Actor Eligibility

Authorized Release Scope

Restrictions

Validity Period

Material Change Conditions

57. Validity Principle

Release Authorization Valid at Decision Time ≠ Release Authorization

Permanently Valid.

58. Authorization Reassessment

RAM governs the identification of conditions requiring authorization

reassessment.

Relevant triggers include:

Release Candidate Change

Readiness Classification Change

Authority Revocation

Delegation Expiration

Authorization Scope Change

Mandatory Condition Change

Exception Expiration

Material Evidence Conflict

Release Restriction Violation

Relevant Governance Policy Change

Reassessment must preserve the distinction between the original decision and any subsequent authorization state.

59. Reassessment Principle

Authorization Reassessment Initiated ≠ Authorization Automatically

Renewed.

60. Authorization Suspension and Revocation

RAM preserves authorization state changes initiated through applicable authority and release governance mechanisms.

Relevant elements include:

Original Authorization ID

Suspension or Revocation Trigger

Applicable Authority Reference

Decision Actor

Affected Candidate

Affected Release Scope

Effective Time

Decision Evidence

Required Follow-Up

Historical Authorization State

RAM establishes the authorization implications of these decisions.

RWM governs the corresponding release withdrawal mechanisms.

61. Suspension and Revocation Principle

Release Authorization Suspended or Revoked ≠ Previously Distributed

Software Automatically Removed.

62. Authorization Continuity

RAM preserves the continuity of authorization decisions across changes in

actors, systems, repositories, organizations, and release processes.

Relevant elements include:

Authorization Identity

Authority Reference

Delegation Reference

Candidate Identity

Readiness Reference

Decision Evidence

Validity Conditions

Restrictions

Historical Decision States

Superseding Authorization

Authorization continuity must not be confused with unrestricted authority transfer.

63. Continuity Principle

Authorization Record Transferred ≠ Authorization Authority

Transferred.

64. Software Release Authorization Profile

The principal governed output is the:

Software Release Authorization Profile

It establishes the evidence-supported authorization state of an

identifiable software release candidate.

The profile preserves:

• Release candidate identity

• Readiness assessment reference

• Authorization identity

• Authorization purpose

• Authority reference

• Decision actor

• Delegation conditions

• Authorization scope

• Authorization prerequisites

• Decision evidence

• Exceptions

• Restrictions

• Authorization classification

• Validity conditions

• Reauthorization requirements

• Suspension and revocation references

• Historical authorization states

• Release record handoff

65. Minimum Profile Fields

At minimum:

Software Release Authorization Profile ID

Release Authorization ID

Software Product ID

Release Candidate ID

Candidate Revision

Readiness Assessment ID

Readiness Classification

Authorization Purpose

Authorization Request ID

Authority Reference

Authority Status

Decision Actor Reference

Delegation Reference

Authorization Scope

Authorization Boundary

Authorization Prerequisites

Mandatory Condition Register

Condition State Register

Exception References

Authorization Restrictions

Decision Evidence

Evidence Sufficiency

Evidence Conflicts

Authorization Decision

Authorization Classification

Decision Time

Validity Conditions

Authorization Expiration

Reauthorization Requirement

Suspension Reference

Revocation Reference

Historical Authorization Reference

Release Record Handoff

Version

66. Minimum Implementation Framework

A minimum operational RAM implementation should contain eight governed layers.

Layer 1 — Candidate and Readiness Association

Identify the exact release candidate and applicable readiness assessment.

Layer 2 — Authorization Purpose and Scope

Define the requested release action, intended scope, and authorization

boundaries.

Layer 3 — Authority and Actor Eligibility

Establish the applicable authority reference, decision actor, delegation

conditions, and validity limitations.

Layer 4 — Authorization Prerequisites

Evaluate mandatory readiness, authority, evidence, and release-specific

conditions.

Layer 5 — Exceptions and Restrictions

Preserve applicable exceptions, limitations, residual conditions, and

restricted authorization possibilities.

Layer 6 — Authorization Decision

Establish an explicit, evidence-supported authorization classification.

Layer 7 — Validity and Continuity

Preserve authorization validity conditions, reassessment triggers, and

historical decision states.

Layer 8 — Governed Output and Release Record Handoff

Produce the Software Release Authorization Profile and transfer the

authorization state to RRMM.

67. Minimum Decision States

At minimum:

Authorization Not Requested

Authorization Request Received

Release Candidate Identified

Readiness Reference Identified

Authorization Purpose Defined

Authorization Scope Defined

Authority Verification Pending

Authority Established

Authority Not Established

Decision Actor Identified

Decision Actor Eligibility Established

Delegation Verification Pending

Delegation Valid

Delegation Invalid

Authorization Prerequisites Pending

Mandatory Conditions Satisfied

Mandatory Condition Not Satisfied

Exception Review Required

Exception Valid

Exception Invalid

Evidence Sufficient

Evidence Insufficient

Authorization Review Complete

Authorization Granted

Restricted Authorization Granted

Authorization Denied

Authorization Deferred

Authorization Suspended

Authorization Revoked

Authorization Expired

Reauthorization Required

Authorization Superseded

Release Record Handoff Completed

Conflicted

Unknown

68. Minimum Evidence Path

Where legitimate release authorization cannot be sufficiently established:

Software Release Candidate Profile → Software Release Readiness Profile

→ Authorization Request → Authority Reference → Decision Actor → Delegation Conditions → Authorization Scope → Mandatory Prerequisites → Exception & Restriction Review → Evidence Sufficiency → Unknown / Conflicted / Not Satisfied Condition → Authority Clarification / Evidence Acquisition / Readiness Reassessment → Authorization Decision → Software Release Authorization Profile → RRMM Release Record Handoff

Missing authority evidence must not be replaced by assumed permission.

69. Minimum Reassessment Framework

Current Software Release Authorization Profile → New Release or

Authority Event → Candidate Identity Review → Readiness Applicability Review → Authority Validity Review → Delegation Review → Authorization Scope Review → Mandatory Condition Review → Exception Validity Review → Restriction Review → Evidence Sufficiency Review → Authorization Reclassification → Historical State Preservation → Profile Update → Release Record Update

Reassessment must distinguish:

Candidate Changed

Readiness Changed

Authority Changed

Delegation Changed

Scope Changed

Mandatory Condition Changed

Exception Changed

Restriction Changed

Authorization Remains Applicable

Reauthorization Required

Authorization Suspended

Authorization Revoked

70. Governance Requirements

A conforming RAM implementation must satisfy the following requirements.

Authorization Identity and Request

• Establish a release authorization identity

• Identify the software product

• Identify the release candidate

• Preserve the candidate revision

• Identify the applicable readiness assessment

• Establish authorization purpose

• Preserve the authorization request

• Identify the requesting actor

• Define the requested release scope

Prevent release requests from automatically establishing release

permission.

Authority and Decision Actor

• Identify the applicable authority reference

• Preserve the authority source

• Preserve the authority scope

• Evaluate authority validity

• Identify the decision actor

• Evaluate decision actor eligibility

• Preserve applicable delegation references

• Evaluate delegation scope

• Preserve delegation restrictions

• Identify authority expiration or revocation

• Prevent technical capability from replacing legitimate authority

Prevent development authority from automatically establishing release

authority.

Readiness and Prerequisites

• Preserve the applicable readiness classification

• Evaluate readiness applicability to the current candidate

• Identify mandatory authorization prerequisites

• Preserve prerequisite condition states

• Identify unresolved mandatory failures

• Preserve evidence limitations

• Preserve material readiness restrictions

Prevent readiness assessment from automatically becoming

authorization.

• Prevent Unknown conditions from being treated as Satisfied

• Prevent invalid readiness conclusions from supporting authorization

Exceptions and Restrictions

• Identify applicable exception rules

• Preserve exception authority references

• Evaluate exception validity

• Preserve exception scope

• Preserve residual conditions

• Preserve authorization restrictions

• Preserve restricted release scope

• Prevent exceptions from being represented as satisfied conditions

Prevent restricted authorization from being represented as

unrestricted authorization.

Prevent exceptions from overriding non-exceptionable mandatory

conditions.

Decision and Evidence

• Preserve authorization evidence provenance

• Evaluate evidence sufficiency

• Preserve conflicting evidence

• Preserve decision time

• Preserve decision actor identity

• Preserve the authority reference supporting the decision

• Establish an explicit authorization classification

• Preserve authorization denial reasons where applicable

• Preserve authorization conditions

Prevent automated approval execution from automatically establishing

authorization legitimacy.

Validity and Continuity

• Preserve authorization validity conditions

• Preserve candidate-specific authorization boundaries

• Identify material reassessment triggers

• Preserve authority expiration conditions

• Preserve delegation expiration conditions

• Preserve authorization suspension references

• Preserve authorization revocation references

• Preserve reauthorization requirements

• Preserve historical authorization decisions

Prevent previous authorization from automatically applying after

material changes.

Prevent authorization record transfer from establishing authority

transfer.

Architecture Boundaries

• Maintain RCMM candidate governance boundaries

• Maintain RRM readiness governance boundaries

• Maintain RRMM release record governance boundaries

• Maintain RWM release withdrawal governance boundaries

• Maintain GOA™ authority governance boundaries

• Maintain AGA™ accountability governance boundaries

• Maintain ASGA™ autonomous actor governance boundaries

• Maintain SDPS deployment authorization boundaries

• Maintain SCMS change governance boundaries

• Maintain SLCS lifecycle control boundaries

Prevent release authorization from independently establishing

deployment authorization.

• Produce a Software Release Authorization Profile

71. Governance Logic

Canonical RAM logic:

Software Release Candidate Identity → Release Readiness Reference →

Authorization Request → Authorization Purpose → Applicable Authority → Decision Actor Identification → Delegation Validity → Authorization Scope → Authorization Boundary → Mandatory Prerequisites → Readiness Applicability → Evidence Sufficiency → Exception & Restriction Review → Authorization Condition Classification → Authorization Decision → Validity Condition Establishment → Software Release Authorization Profile → RRMM Release Record Handoff

A favorable authorization decision requires sufficiently established

authority, applicable readiness conditions, and compliance with mandatory authorization boundaries.

72. Governance Outputs

RAM may produce:

Software Release Authorization Profile

Release Authorization Identity

Authorization Request Record

Authorization Purpose Record

Authorization Scope Record

Authorization Boundary

Authority Reference

Authority Validity Assessment

Decision Actor Record

Delegation Reference

Delegation Applicability Assessment

Authorization Prerequisite Register

Mandatory Condition Register

Authorization Evidence Register

Evidence Sufficiency State

Evidence Conflict Record

Exception Reference

Release Restriction Record

Authorization Decision

Authorization Classification

Authorization Validity Conditions

Authorization Expiration Record

Reauthorization Requirement

Authorization Suspension Reference

Authorization Revocation Reference

Historical Authorization Record

Release Record Handoff

Version

73. Practical Applications

Autonomous Software Factories

Establishing legitimate release authority for software generated and

evaluated by autonomous AI agents without assuming that development authority includes release authorization.

Enterprise Release Governance

Separating development completion, readiness assessment, and release

approval across organizational functions.

Automated Continuous Delivery

Permitting automated release authorization where legitimate delegation, mandatory conditions, and decision traceability have been established.

Critical Infrastructure Software

Preserving explicit release authority, restrictions, and evidence for

software whose release may materially affect essential operational systems.

Security Patch Releases

Supporting time-sensitive release authorization without silently

eliminating mandatory security, readiness, or authority conditions.

Multi-Organization Software Delivery

Distinguishing release authority held by developers, suppliers, product

owners, platform operators, and other participating organizations.

74. Use Case 1 — An Autonomous AI Agent Authorizes a Release Without

Delegated Release Authority

An organization operates an autonomous software development platform.

An AI agent is authorized to implement approved software requirements, modify source code, execute tests, and prepare release candidates.

The agent completes its development task.

RCMM establishes an identifiable release candidate.

RRM establishes a favorable readiness determination.

The AI agent then invokes an automated release approval function and marks

the candidate as authorized.

However, the organization's authority framework delegated software

development and candidate preparation functions to the agent.

It did not delegate release authorization.

RAM evaluates:

Candidate Identity → Readiness State → Agent Identity → Authority

Reference → Delegation Scope → Decision Eligibility → Authorization Classification

The assessment identifies:

• The release candidate is identifiable

• Release readiness is established

• The agent possesses legitimate development authority

• The agent can technically execute the release approval function

• The applicable delegation does not include release authorization

• The executed approval cannot establish legitimate release authorization

The appropriate classification is:

Authorization Not Established — Decision Actor Lacks Applicable Release

Authority.

The critical distinctions are:

Development Authority ≠ Release Authorization Authority.

Technical Approval Capability ≠ Legitimate Approval Authority.

Release Readiness Established ≠ Release Authorization Granted.

The result: RAM prevents autonomous workflow completion from being

confused with legitimate release authorization.

75. Use Case 2 — A Release Is Approved for Limited Distribution but Published Publicly

A software company prepares a new application release.

The release candidate satisfies applicable readiness conditions.

An authorized decision actor approves distribution to a limited internal

testing group.

The authorization explicitly restricts distribution to the designated

recipients.

An automated release system subsequently publishes the same software

package to a public distribution channel.

The artifact itself has not changed.

However, the distribution action exceeds the authorized release scope.

RAM evaluates:

Authorization Identity → Authorized Candidate → Authorized Distribution

Scope → Actual Release Action → Scope Comparison → Authorization Applicability

The assessment identifies:

• The candidate was legitimately authorized for limited distribution

• The authorization scope was explicit

• The actual distribution exceeded that scope

• Artifact identity equality does not extend authorization to unrestricted

publication.

• The public release action lacks applicable authorization

The appropriate classification for the public distribution action is:

Authorization Not Applicable to Actual Release Scope.

The critical distinctions are:

Candidate Authorized ≠ Every Distribution Action Authorized.

Artifact Identity Unchanged ≠ Authorization Scope Unchanged.

Restricted Release Authorization ≠ Public Release Authorization.

The result: RAM establishes that release legitimacy depends on both the authorized artifact and the permitted release action.

76. Use Case 3 — An Automated Pipeline Reuses an Expired Release

Delegation

An organization authorizes an automated release system to approve

maintenance releases within defined conditions.

The delegation is valid for a limited period.

During that period, the system successfully authorizes several maintenance releases.

The delegation subsequently expires.

The automated pipeline continues operating with unchanged technical

permissions.

A new maintenance candidate satisfies the applicable readiness criteria.

The pipeline automatically approves its release using the previously

configured authorization rule.

RAM evaluates:

Release Candidate → Readiness State → Automated Decision System →

Delegation Reference → Delegation Validity → Decision Time → Authorization Classification

The assessment identifies:

• The candidate is sufficiently identified

• Readiness is established

• The automated release system remains technically operational

• The delegated release authority has expired

• Previous valid decisions do not establish current authority

- The new approval cannot be recognized as legitimate without renewed

applicable authority.

The appropriate classification is:

Authorization Not Established — Delegated Authority Expired.

The critical distinctions are:

Automation Operational ≠ Delegation Valid.

Previous Authorization Success ≠ Current Authorization Legitimacy.

Technical Permission Remaining ≠ Governance Authority Remaining.

The result: RAM prevents continuing technical access from silently

extending expired release authority.

77. Critical Distinctions

Technical Release Capability ≠ Legitimate Release Authority.

Release Readiness Established ≠ Release Authorization Granted.

Human Approval ≠ Automatically Legitimate Approval.

Task Authority ≠ Constituent Action Authority.

Authorization for One Release Candidate ≠ Authorization for Every

Candidate.

Release Authorization Granted Within a Defined Scope ≠ Unrestricted Release Authority.

Authorization Record Available ≠ Authorization Legitimacy Established.

Exception Approved ≠ Mandatory Authorization Condition Satisfied.

Authorization Previously Valid ≠ Authorization Continuously

Applicable.

Release Authorization ≠ Deployment Authorization.

Release Approval Recorded ≠ Release Authorization Identity Sufficiently

Established.

Emergency Release Purpose ≠ Unlimited Emergency Release Authority.

Release Authorization Requested ≠ Release Authorization Permitted.

Release Candidate Name Matches ≠ Authorized Artifact Identity Matches.

Readiness Profile Attached ≠ Readiness Profile Applicable to the Current

Candidate.

Authority Claimed ≠ Authority Established.

Decision Actor Identified ≠ Decision Actor Authorized.

Authority to Develop Software ≠ Authority to Authorize Its Release.

Automated Approval Rule Executed ≠ Legitimate Authorization

Established.

Agent Authorized to Complete a Release Workflow ≠ Agent Authorized to

Approve Every Release Within That Workflow.

Authorization Granted for One Release Channel ≠ Authorization Granted

for Every Distribution Channel.

Authorization Prerequisites Listed ≠ Authorization Prerequisites

Satisfied.

Mandatory Condition Not Satisfied ≠ Authorization Permitted by

Default.

Conditional Readiness ≠ Automatic Conditional Release Authorization.

Authorization Evidence Recorded ≠ Authorization Evidence Sufficient.

Authority Valid Previously ≠ Authority Valid at the Time of Release

Authorization.

Not Applicable ≠ Not Assessed.

Exception ≠ Satisfied.

Condition Not Satisfied ≠ Condition Waived.

Exception Granted for One Condition ≠ Exception Granted for Every

Authorization Condition.

Restricted Release Authorization ≠ Unrestricted Release Authorization.

Approval Action Completed ≠ Legitimate Release Authorization Decision

Established.

Authorization Granted ≠ Software Deployed.

Authorization Denied ≠ Release Candidate Deleted.

Authorization Suspended ≠ Authorization Revoked.

Release Authorization Valid at Decision Time ≠ Release Authorization

Permanently Valid.

Authorization Reassessment Initiated ≠ Authorization Automatically

Renewed.

Release Authorization Suspended or Revoked ≠ Previously Distributed

Software Automatically Removed.

Authorization Record Transferred ≠ Authorization Authority

Transferred.

78. Cross-Architecture Boundary

RAM may consume governed references from:

GOA™ — Governance Architecture

AGA™ — Accountability Governance Architecture

ASGA™ — Autonomous Systems Governance Architecture

SRS — Software Requirements Standard

SDS — Software Dependency Standard

SCFS — Software Configuration Standard

SQS — Software Quality Standard

SSS — Software Security Standard

SCMS — Software Change Management Standard

SLCS — Software Lifecycle Control Standard

Within SRLS, RAM receives candidate and readiness states from:

RCMM — Release Candidate Management Module

RRM — Release Readiness Module

RAM provides authorization decisions and supporting references to:

RRMM — Release Record Management Module

Authorization suspension, revocation, or invalidated release conditions

may also require coordination with:

RWM — Release Withdrawal Module

Downstream deployment decisions remain governed by:

SDPS — Software Deployment Standard

RAM governs the software release authorization decision.

It does not replace general authority governance, accountability assignment, autonomous actor governance, release readiness assessment, or deployment authorization.

79. Cross-Architecture Mechanism Principle

An operational mechanism may produce inputs for multiple governance architectures, but it belongs only to the architecture whose governed domain includes that mechanism itself. Other architectures govern only its domain-specific relevance or consequences.

RAM may reference organizational authority, delegated permissions, autonomous agent authority, readiness assessments, software artifact identities, and release execution records.

It governs their relevance to legitimate software release authorization.

It does not independently create those authority relationships or redefine the mechanisms responsible for establishing them.

80. Canonical Boundary

RAM governs how software release authorization decisions are established, evaluated, granted, restricted, denied, suspended, and reassessed in relation to identifiable release candidates, applicable readiness states, legitimate authority, authorization prerequisites, decision evidence, and defined release boundaries.

It does not independently establish software readiness, create general authority, assign accountability, execute deployment, or determine whether software is free from defects or harmful behavior.

Its principal governed output is the Software Release Authorization Profile.

81. Canonical Closing Statement

Software release authorization is not a technical capability. It is a legitimate governance decision exercised under defined authority, conditions, and boundaries.

Modern software delivery systems can create, test, package, and publish software without continuous human involvement.

An autonomous agent may complete a development task.

An automated pipeline may establish a favorable readiness result.

A release system may possess the technical permissions required to publish the resulting software.

But none of these facts independently establishes legitimate release

authority.

The ability to execute an approval is not evidence of the right to approve.

A release may be technically ready while its authorization authority remains unresolved.

An AI agent may be authorized to develop software without being authorized to release it.

A release may be legitimately approved for one distribution channel while remaining unauthorized for another.

And an automated approval process may continue functioning after its delegated authority has expired.

RAM establishes the governance conditions required to distinguish these

situations.

It requires the authorized software candidate to be identifiable.

It requires the readiness conclusion to remain applicable.

It requires the decision actor to possess legitimate authority for the

specific release action.

It requires exceptions and restrictions to remain explicit.

And it requires the authorization decision to remain bounded by the

conditions under which it was established.

Release authorization must follow legitimate authority—not merely the actor or system capable of executing the release.

This principle applies equally to human decision-makers, organizational

functions, automated pipelines, and autonomous AI agents.

The actor may change.

The authorization process may become automated.

The software delivery system may operate autonomously.

The requirement for legitimate, bounded, and evidence-supported release

authority remains.

RAM transforms software release approval from a technical workflow

action into a governed authorization state — ensuring that software is released not merely because a system can approve it, but because the decision is supported by applicable readiness, legitimate authority, explicit boundaries, and sufficient evidence.

Modul4

RRMM — Release Record Management Module

Architecture

SLGA™ — Software Lifecycle Governance Architecture

Parent Standard

SRLS — Software Release Standard

Category

Governance & Enforcement

Subcategory

Software Lifecycle Governance

Type

Core Module

Governed Space

Software Release Record Governance

Module ID

SLGA-SRLS-RRMM-04

Origin ID

OOF-SLGA-SRLS-RRMM

Version

1.0

Status

Canonical Open

Effective Date

10.2026

Compatibility

Methodology OS — Modular Compatibility

GIE-Compatible

Yes

AI-Readable

Yes

Authority

OOF® — OriginOpen® Foundation

Protection

Protected Methodological Work

Canonical Language

English

Canonical Definition

RRMM — Release Record Management Module is the Core Module within SRLS that governs how software release records are established, structured, associated, preserved, updated, verified, superseded, and maintained as traceable evidence of identifiable software releases and their applicable governance states throughout the software lifecycle.

RRMM establishes the methodological conditions under which a software

release record may represent the relationship between an identifiable release candidate, its artifact and configuration references, readiness assessment, authorization decision, applicable restrictions, release events, and subsequent lifecycle changes.

It governs the integrity, completeness, provenance, consistency,

accessibility, versioning, and continuity of release governance records.

RRMM distinguishes the existence of a release record from the completeness

of its evidence, the recording of an authorization decision from the legitimacy of that decision, and the preservation of historical release information from the continued applicability of its original governance conclusions.

The module ensures that release records remain usable for subsequent deployment, change management, incident investigation, withdrawal, retirement, and lifecycle control without independently replacing the governance mechanisms responsible for those decisions.

Its principal governed output is the Software Release Record Profile.

Release Record Exists ≠ Release Governance Evidence Complete.

Release Recorded ≠ Release Authorized.

Release Record Updated ≠ Underlying Release State Changed.

Historical Release Record Preserved ≠ Historical Authorization Still

Valid.

Artifact Reference Recorded ≠ Artifact Identity Verified.

Operational Role

RRMM governs the establishment and continuity of software release records.

Its operational role is to establish:

• Release record identity

• Release record purpose

• Software product association

• Release candidate association

• Artifact and version references

• Configuration and dependency references

• Readiness assessment references

• Authorization decision references

• Release restrictions

• Release event references

• Release record boundaries

• Record provenance

• Record completeness

• Record consistency

• Evidence sufficiency

• Record integrity

• Record versioning

• Historical state preservation

• Record correction

• Record supersession

• Record accessibility

• Record retention conditions

• Record transfer

• Release withdrawal references

• Deployment handoff

• Lifecycle traceability

RRMM does not independently establish release readiness, grant release authorization, execute deployment, withdraw released software, or certify the correctness of recorded claims.

Operational Question

How can software release records preserve a reliable, evidence-supported, and traceable representation of what software was prepared, assessed, authorized, released, restricted, changed, or withdrawn, while ensuring that record completeness, provenance, integrity, historical continuity, and current governance applicability remain distinguishable throughout human-operated, automated, and autonomous software lifecycles?

Position in Architecture Governance Flow

SLGA™ Governance Flow

Software Requirements → Software Creation → Software Dependencies →

Software Configuration → Software Quality → Software Security → Software Release → Software Deployment → Software Change Management → Software Retirement

Cross-cutting:

Software Lifecycle Control

SRLS Core Module Flow

RCMM — Release Candidate Management Module

2. RRM — Release Readiness Module 3. RAM — Release Authorization Module 4. RRMM — Release Record Management Module 5. RWM — Release Withdrawal Module

RRMM occupies the fourth Core Module position within SRLS.

It receives release candidate identity, readiness conclusions, and

authorization decisions from the preceding SRLS modules.

Its role is to establish a coherent release governance record that preserves the relationship between these states without merging them into a single unsupported claim of release legitimacy.

RRMM supports downstream deployment and lifecycle governance by providing

identifiable, traceable release references.

Release Candidate Profile → Release Readiness Profile → Release

Authorization Profile → Release Record Identity → Record Scope → Artifact & Configuration References → Evidence Association → Record Integrity Assessment → Record Classification → Software Release Record Profile → Deployment / Withdrawal / Lifecycle Governance Handoff

• Governed Space

Software Release Record Governance

This governed space concerns the evidence-supported representation and

preservation of software release governance information.

It includes:

• Release record identification

• Record scope and boundaries

• Release candidate association

• Artifact identification references

• Readiness and authorization references

• Release event recording

• Record provenance

• Evidence association

• Record completeness

• Record integrity

• Record consistency

• Record versioning

• Record correction

• Historical state preservation

• Record supersession

• Record access and retention

• Governance handoffs

RRMM does not independently determine whether the software is technically correct, secure, ready, authorized, deployed, or operationally acceptable.

Governed Object

The primary Governed Object is:

A Software Release Record State representing the evidence-supported

relationship between an identifiable software release, its candidate and artifact references, readiness and authorization states, applicable release conditions, recorded release events, associated evidence, historical changes, and current record integrity.

The governed state must preserve:

Software Product ID

Release Record ID

Release Candidate ID

Artifact Reference

Configuration Reference

Readiness Profile Reference

Authorization Profile Reference

Release Event Reference

Release Scope

Release Restrictions

Evidence References

Record Provenance

Record Completeness State

Record Integrity State

Record Classification

Historical State References

Version

Scope

RRMM governs:

• Release record creation

• Release identity association

• Release candidate references

• Artifact and configuration references

• Readiness and authorization associations

• Release event recording

• Record provenance

• Record completeness

• Evidence sufficiency

• Record consistency

• Record integrity

• Record updates

• Corrections and supersession

• Historical record preservation

• Record accessibility

• Record retention

• Record transfer

• Deployment and withdrawal references

• Lifecycle governance handoffs

RRMM does not independently perform software verification, authorize release decisions, or establish the operational state of deployed software.

Foundational Governance Principles8.1 Record Existence Principle

Release Record Exists ≠ Release Governance Evidence Complete. 8.2 Authorization Separation Principle

Release Recorded ≠ Release Authorized. 8.3 Record–Reality Separation Principle

Release Record Updated ≠ Underlying Release State Changed. 8.4 Historical Validity Principle

Historical Release Record Preserved ≠ Historical Authorization Still

Valid. 8.5 Artifact Identity Principle

Artifact Reference Recorded ≠ Artifact Identity Verified. 8.6 Provenance Principle

Release Information Recorded ≠ Release Information Proven. 8.7 Completeness Principle

Required Fields Populated ≠ Release Record Substantively Complete. 8.8 Integrity Principle

Release Record Accessible ≠ Release Record Integrity Established. 8.9 Version Continuity Principle

Release Record Revised ≠ Previous Release Record Erased. 8.10 Lifecycle Traceability Principle

Release History Available ≠ Complete Software Lifecycle Traceability

Established.

Release Record Identity

Every governed release record must establish:

Release Record ID

Software Product ID

Release Candidate ID

Release Identifier

Record Purpose

Record Scope

Record Origin

Record Creation Time

Record Version

Record Classification

Record Identity Integrity

Release Name Recorded ≠ Unique Release Identity Established.

Release records must remain distinguishable across products, candidate revisions, artifacts, and release channels.

Record Purpose

Release record purposes may include:

Release Governance Documentation

Release Evidence Preservation

Release Authorization Traceability

Release Distribution Traceability

Deployment Reference

Release Withdrawal Reference

Lifecycle Investigation

Historical Governance Reconstruction

A record created for one purpose must not automatically be treated as sufficient for every other purpose.

Purpose Principle

Release Record Suitable for Distribution Tracking ≠ Release Record

Sufficient for Authorization Audit.

Release Record Boundary

The record boundary defines the software release information represented by

the record.

Relevant dimensions include:

Software Product Boundary

Release Candidate Boundary

Artifact Boundary

Configuration Boundary

Dependency Boundary

Release Channel Boundary

Authorization Boundary

Evidence Boundary

Temporal Boundary

Lifecycle Boundary

Boundary Integrity

Release Record Covers One Candidate ≠ Release Record Covers Every Related

Artifact.

Software Product Association

RRMM must preserve the relationship between the release record and its software product.

Relevant elements include:

Software Product ID

Product Name

Product Version Reference

Product Scope

Product Ownership Reference

Product Lifecycle Reference

Associated Release Candidates

Product Association Principle

Software Product Identified ≠ Exact Released Artifact Identified.

Release Candidate Association

RRMM receives the governed candidate identity established by RCMM.

Relevant elements include:

Release Candidate ID

Candidate Revision

Candidate Baseline

Candidate Composition Reference

Candidate Status

Candidate Evidence Reference

Candidate Supersession Reference

Candidate Association Principle

Release Candidate Referenced ≠ Candidate Identity and Composition

Verified.

Artifact Identity References

RRMM preserves references to the software artifacts associated with a

release.

Relevant elements include:

Artifact ID

Artifact Type

Artifact Version

Artifact Hash or Equivalent Identifier

Build Reference

Artifact Origin

Artifact Location Reference

Artifact Integrity Evidence

Artifact identity verification remains dependent on the applicable

configuration and integrity mechanisms.

Artifact Reference Principle

Version Label Equality ≠ Artifact Equivalence.

Configuration References

RRMM preserves the configuration context relevant to the release.

Relevant elements include:

Configuration Baseline ID

Build Configuration Reference

Runtime Configuration Reference Where Applicable

Environment Assumptions

Configuration Restrictions

Configuration Evidence

Configuration Version

Configuration Principle

Release Artifact Identified ≠ Applicable Configuration Context Fully

Established.

Dependency References

RRMM preserves material dependency references relevant to release

reconstruction.

Relevant elements include:

Dependency Baseline ID

Component Inventory Reference

Dependency Origin Reference

Dependency Version Reference

Dependency Restriction

Dependency Risk Reference

Dependency Evidence

Dependency Reference Principle

Dependency Manifest Attached ≠ Complete Release Dependency Reality

Established.

Readiness Assessment References

RRMM must preserve the applicable readiness determination.

Relevant elements include:

Readiness Assessment ID

Readiness Classification

Readiness Assessment Time

Assessment Boundary

Assessment Evidence

Unresolved Findings

Applicable Restrictions

Reassessment Requirements

RRMM records the readiness state established by RRM.

It does not independently establish readiness.

Readiness Record Principle

Readiness Conclusion Recorded ≠ Readiness Conclusion Independently

Verified by RRMM.

Authorization Decision References

RRMM must preserve the applicable release authorization decision.

Relevant elements include:

Release Authorization ID

Authorization Classification

Authorization Authority Reference

Decision Actor Reference

Decision Time

Authorized Release Scope

Authorization Restrictions

Validity Conditions

Authorization Evidence Reference

RRMM records the authorization state established by RAM.

It does not independently grant authorization.

Authorization Record Principle

Authorization Decision Referenced ≠ Authorization Legitimacy Independently

Established.

Release Event Recording

RRMM may preserve release events associated with the software release.

Relevant elements include:

Release Event ID

Release Event Type

Release Candidate ID

Artifact Reference

Release Channel

Event Actor

Event Time

Event Evidence

Event Classification

Events must remain distinguishable from authorization decisions.

Release Event Principle

Release Event Recorded ≠ Release Event Authorized.

Release Distribution References

Where applicable, RRMM preserves distribution-related references.

Relevant elements include:

Distribution Event ID

Distribution Channel

Distributed Artifact Reference

Distribution Time

Distribution Actor

Recipient Scope

Distribution Evidence

Distribution Restrictions

RRMM does not independently establish successful delivery to every intended recipient.

Distribution Principle

Software Published to a Repository ≠ Software Delivered to Every Intended

Recipient.

Release Restrictions

RRMM preserves restrictions applicable to the recorded release.

Relevant restrictions include:

Restricted Distribution

Limited Recipient Scope

Configuration Restrictions

Environment Restrictions

Validity Period Restrictions

Conditional Release Requirements

Exception-Related Restrictions

Withdrawal Conditions

Restriction Integrity

Release Restrictions Recorded ≠ Release Restrictions Operationally

Enforced.

Release Record Provenance

RRMM governs the traceability of release record origins and updates.

Relevant elements include:

Record Origin

Record Creator

Creation Method

Source Systems

Referenced Evidence

Record Creation Time

Modification History

Responsible Record Function

Record Version

Provenance Integrity

Release Record Source Identified ≠ Release Record Content Authenticated.

Record Evidence Association

RRMM must associate release record claims with relevant evidence.

Evidence may include:

Candidate Identity Evidence

Artifact Integrity Evidence

Configuration Evidence

Dependency Evidence

Readiness Evidence

Authorization Evidence

Release Event Evidence

Distribution Evidence

Record Modification Evidence

Withdrawal References

Evidence Association Principle

Evidence Linked ≠ Evidence Relevant or Sufficient.

Record Completeness

Record completeness concerns whether the record contains the information

required for its defined governance purpose.

Relevant dimensions include:

Identity Completeness

Candidate Reference Completeness

Artifact Reference Completeness

Readiness Reference Completeness

Authorization Reference Completeness

Release Event Coverage

Evidence Coverage

Restriction Coverage

Historical State Coverage

Completeness Integrity

All Mandatory Fields Present ≠ All Recorded Claims Substantively

Supported.

Record Consistency

RRMM evaluates whether the record contains contradictory or incompatible

references.

Relevant dimensions include:

Candidate Identity Consistency

Artifact Version Consistency

Configuration Consistency

Readiness Reference Consistency

Authorization Scope Consistency

Release Event Consistency

Timestamp Consistency

Historical State Consistency

Consistency Principle

Release Record Internally Consistent ≠ Release Record Factually Correct.

Record Integrity

RRMM governs whether the release record remains protected against

untraceable or unauthorized alteration.

Relevant elements include:

Record Integrity Reference

Modification Authorization

Change Traceability

Version History

Integrity Verification Evidence

Access Restrictions

Correction History

Supersession History

Integrity Principle

Record Unchanged ≠ Record Originally Accurate.

Record Authenticity

Record authenticity concerns whether the record's claimed origin and

modifications are sufficiently supported.

Relevant elements include:

Origin Identity

Record Creator Identity

Source System Reference

Creation Evidence

Modification Evidence

Authentication Mechanism Reference

Known Authenticity Limitations

Authenticity Principle

Record Authenticated ≠ Every Claim Within the Record Validated.

Record Evidence Sufficiency

RRMM evaluates whether the available evidence adequately supports the

record's intended governance use.

Relevant dimensions include:

Evidence Coverage

Evidence Provenance

Evidence Relevance

Evidence Consistency

Evidence Freshness

Evidence Accessibility

Evidence Integrity

Known Evidence Gaps

Sufficiency Principle

Release Evidence Available ≠ Release Evidence Sufficient for Every

Lifecycle Decision.

Missing Record Evidence

RRMM must preserve missing or unavailable evidence.

Examples include:

Missing Artifact Identity Evidence

Missing Configuration Reference

Missing Readiness Assessment

Missing Authorization Decision

Missing Release Event Evidence

Missing Distribution Reference

Missing Record Modification History

Unavailable Historical Record

Missing Evidence Principle

Release Information Missing ≠ Release Condition Satisfied.

Record Uncertainty

Record uncertainty may arise from:

Unverified Artifact Identity

Incomplete Release History

Conflicting Authorization References

Unknown Release Actor

Uncertain Distribution Scope

Missing Historical Evidence

Inconsistent Timestamps

Unverified External Records

Uncertainty Principle

Record Uncertainty Acknowledged ≠ Record Uncertainty Resolved.

Record Updates

RRMM governs modifications to existing release records.

Relevant elements include:

Record Update ID

Affected Release Record

Update Purpose

Update Actor

Update Authority Reference

Previous Value

Updated Value

Update Evidence

Update Time

Updated Version

Update Integrity

Release Record Corrected ≠ Original Release Event Changed.

Record Correction

A record correction addresses inaccurate, incomplete, or misleading

recorded information.

Relevant elements include:

Correction ID

Affected Field

Original Recorded Value

Corrected Value

Correction Reason

Supporting Evidence

Correction Authority Reference

Correction Time

Historical Reference

Corrections must preserve the distinction between historical recording and later correction.

Correction Principle

Historical Record Inaccurate ≠ Historical Record May Be Silently Rewritten.

Record Supersession

RRMM governs the relationship between earlier and later release records.

Relevant elements include:

Original Record ID

Superseding Record ID

Supersession Reason

Supersession Scope

Effective Time

Evidence Reference

Historical Relationship

Supersession must not erase the historical record.

Supersession Principle

Release Record Superseded ≠ Previous Release Record Invalid for Historical

Reconstruction.

Record Versioning

Every material record update must preserve version continuity.

Relevant elements include:

Record Version

Previous Version

Version Change Reason

Modified Fields

Modification Actor

Modification Time

Evidence Reference

Supersession Reference

Versioning Principle

Release Record Version Increased ≠ Software Release Version Increased.

Historical Release State Preservation

RRMM preserves historical governance states relevant to the release.

Relevant elements include:

Previous Candidate State

Previous Readiness State

Previous Authorization State

Previous Release Event State

Previous Distribution State

Previous Record Classification

Historical Evidence

State Transition Time

Superseding State

Historical Integrity

Current Release Record State ≠ Complete Historical Release State.

Record Retention

RRMM governs the identification and preservation of applicable release

record retention conditions.

Relevant elements include:

Retention Purpose

Retention Authority Reference

Retention Period

Record Category

Evidence Retention Requirement

Access Conditions

Archival Reference

Disposal Restriction

Retention requirements may arise from applicable organizational, contractual, regulatory, or legal obligations.

RRMM does not independently establish those external obligations.

Retention Principle

Record No Longer Operationally Needed ≠ Record Eligible for Deletion.

Record Accessibility

RRMM governs whether authorized governance functions can access the release record when required.

Relevant elements include:

Record Location

Access Authority

Access Scope

Availability State

Retrieval Method

Record Format

Evidence Accessibility

Historical Version Accessibility

Accessibility Principle

Release Record Stored ≠ Release Record Retrievable When Required.

Record Transfer and Continuity

RRMM preserves release record continuity across organizational, technical,

or custodial changes.

Relevant elements include:

Original Record Custodian

Receiving Record Custodian

Transfer Scope

Transferred Record Identity

Transferred Evidence

Transfer Integrity

Access Continuity

Historical Version Preservation

Transfer Time

Transfer Principle

Release Record Transferred ≠ Record Integrity and Accessibility

Automatically Preserved.

Release Record Classification

RRMM may classify release record states as:

Record Not Established

Record Creation Pending

Record Established

Record Incomplete

Record Evidence-Limited

Record Verification Pending

Record Consistent

Record Conflicted

Record Integrity Unresolved

Record Integrity Supported

Record Correction Required

Record Update Pending

Record Superseded

Record Archived

Record Inaccessible

Record Retention Exception

Unknown

Record Closed

These are release record governance classifications, not independent readiness or authorization classifications.

Classification Integrity

Release Record Classified as Complete ≠ Release Independently Validated as

Ready or Authorized.

Software Release Record Profile

The principal governed output is the:

Software Release Record Profile

It establishes the evidence-supported record state of an identifiable

software release.

The profile preserves:

• Software product identity

• Release record identity

• Release candidate identity

• Artifact and version references

• Configuration references

• Dependency references

• Readiness assessment references

• Authorization decision references

• Release event references

• Distribution references

• Release restrictions

• Record provenance

• Evidence associations

• Record completeness

• Record consistency

• Record integrity

• Record classification

• Record corrections

• Historical versions

• Supersession references

• Retention and accessibility conditions

• Lifecycle governance handoffs

Minimum Profile Fields

At minimum:

Software Release Record Profile ID

Release Record ID

Software Product ID

Release Candidate ID

Release Identifier

Release Record Purpose

Release Record Boundary

Artifact ID

Artifact Version

Artifact Integrity Reference

Build Reference

Configuration Baseline ID

Dependency Baseline ID

Readiness Assessment ID

Readiness Classification

Release Authorization ID

Authorization Classification

Authorization Scope

Authorization Restrictions

Release Event ID

Release Event Type

Release Event Time

Release Event Actor

Distribution Reference

Record Origin

Record Creator

Record Creation Time

Record Evidence Register

Evidence Provenance

Evidence Sufficiency

Missing Evidence

Evidence Conflicts

Record Completeness

Record Consistency

Record Integrity

Record Classification

Correction References

Supersession References

Historical State References

Retention Conditions

Accessibility State

Lifecycle Handoff References

Version

Minimum Implementation Framework

A minimum operational RRMM implementation should contain eight governed layers. Layer 1 — Record Identity and Scope

Establish the release record identity, purpose, boundaries, and software

product association. Layer 2 — Candidate and Artifact Association

Associate the record with the identifiable release candidate, artifact,

build, configuration, and dependency references. Layer 3 — Readiness and Authorization Association

Preserve the applicable readiness assessment and authorization decision

without independently replacing either mechanism. Layer 4 — Release Event and Restriction Recording

Record applicable release events, distribution references, and release

restrictions. Layer 5 — Evidence and Provenance

Establish record provenance, evidence associations, missing evidence, and

evidence sufficiency. Layer 6 — Record Integrity and Classification

Evaluate record completeness, consistency, integrity, and applicable record

classifications. Layer 7 — Historical Continuity

Preserve corrections, versions, supersession relationships, retention

conditions, and historical states. Layer 8 — Governed Output and Lifecycle Handoff

Produce the Software Release Record Profile and provide relevant

references to deployment, withdrawal, change management, retirement, and lifecycle control governance.

Minimum Decision States

At minimum:

Record Not Established

Record Creation Requested

Release Record Identity Established

Record Purpose Defined

Record Boundary Defined

Software Product Identified

Release Candidate Identified

Artifact Reference Established

Configuration Reference Established

Dependency Reference Established

Readiness Reference Established

Authorization Reference Established

Release Event Recorded

Release Restrictions Recorded

Record Evidence Associated

Record Provenance Established

Evidence Sufficiency Review Pending

Record Evidence Sufficient

Record Evidence Insufficient

Record Completeness Review Pending

Record Complete Within Defined Scope

Record Incomplete

Record Consistency Review Pending

Record Consistent

Record Conflicted

Record Integrity Review Pending

Record Integrity Supported

Record Integrity Unresolved

Record Correction Required

Record Correction Completed

Record Update Pending

Record Updated

Record Superseded

Record Archived

Record Inaccessible

Lifecycle Handoff Completed

Unknown

Record Closed

Minimum Evidence Path

Where release record integrity or completeness cannot be sufficiently established:

Software Product → Release Candidate → Artifact & Configuration References

→ Readiness Profile → Authorization Profile → Release Event References → Record Provenance → Evidence Association → Completeness Review → Consistency Review → Integrity Review → Evidence-Limited / Conflicted / Unknown State → Missing Evidence Identification → Evidence Acquisition / Record Correction → Record Reassessment → Updated Record Classification → Software Release Record Profile → Lifecycle Governance Handoff

Missing record evidence must not be replaced by assumed release legitimacy.

Minimum Reassessment Framework

Current Software Release Record Profile → New Release Information or

Evidence → Record Identity Review → Candidate Association Review → Artifact Reference Review → Configuration & Dependency Review → Readiness Reference Review → Authorization Reference Review → Release Event Review → Evidence Provenance Review → Completeness Review → Consistency Review → Integrity Review → Correction / Supersession Assessment → Historical State Preservation → Record Classification Update → Profile Update → Version Update

Reassessment must distinguish:

Release Event Changed

Release Record Changed

Evidence Changed

Readiness Reference Changed

Authorization Reference Changed

Artifact Reference Changed

Record Correction Required

Record Supersession Required

Historical State Preserved

Governance Requirements

A conforming RRMM implementation must satisfy the following requirements. Record Identity and Boundaries

• Establish a unique release record identity

• Identify the software product

• Identify the release candidate

• Define the record purpose

• Define the record boundary

• Preserve the release identifier

• Preserve record creation time

• Preserve record origin

• Preserve record version

• Prevent release names from replacing unique record identities

Candidate, Artifact, and Configuration References

• Preserve the release candidate reference

• Preserve candidate revision information

• Preserve artifact identity references

• Preserve artifact version references

• Preserve artifact integrity references where applicable

• Preserve build references

• Preserve configuration baseline references

• Preserve dependency baseline references

• Preserve known artifact identity limitations

• Prevent version labels from automatically establishing artifact equivalence.

Readiness and Authorization References

• Preserve the applicable readiness assessment reference

• Preserve readiness classification

• Preserve readiness restrictions

• Preserve the applicable authorization reference

• Preserve authorization classification

• Preserve authorization scope

• Preserve authorization restrictions

• Preserve authorization validity references

• Prevent readiness records from automatically establishing release

• Prevent authorization records from independently establishing authorization. authorization legitimacy.

Release Events and Distribution

• Identify relevant release events

• Preserve release event identities

• Preserve event actors

• Preserve event times

• Preserve event evidence

• Preserve release channel references

• Preserve distribution scope where applicable

• Preserve release restrictions

• Prevent release event recording from establishing event

• Prevent repository publication from establishing successful authorization. distribution to every recipient.

Evidence Governance

• Preserve record evidence provenance

• Preserve evidence source references

• Preserve evidence creation times

• Preserve evidence associations

• Evaluate evidence relevance

• Evaluate evidence sufficiency

• Preserve missing evidence

• Preserve conflicting evidence

• Preserve uncertainty

• Prevent populated record fields from automatically establishing evidentiary completeness.

Record Completeness and Integrity

• Evaluate record completeness

• Preserve completeness boundaries

• Evaluate record consistency

• Preserve conflicting references

• Evaluate record integrity

• Preserve modification traceability

• Preserve applicable authentication references

• Identify unauthorized or unexplained alterations

• Prevent internal consistency from establishing factual correctness

• Prevent record accessibility from automatically establishing record integrity.

Record Updates and Historical Continuity

• Preserve material record updates

• Preserve update actors

• Preserve update authority references

• Preserve correction reasons

• Preserve original recorded values

• Preserve corrected values

• Preserve supersession relationships

• Preserve historical record versions

• Preserve state transition times

• Prevent corrections from silently rewriting historical release

• Prevent record supersession from erasing historical records

• Prevent record version changes from being confused with software

events. release version changes.

Retention, Accessibility, and Transfer

• Identify applicable record retention conditions

• Preserve retention authority references

• Preserve archival references

• Preserve authorized access conditions

• Preserve record retrieval capability

• Preserve historical version accessibility where required

• Preserve record transfer identity

• Preserve transfer integrity evidence

• Prevent record storage from automatically establishing

• Prevent record transfer from automatically establishing integrity

retrievability. continuity.

Architecture Boundaries

• Maintain RCMM candidate governance boundaries

• Maintain RRM readiness governance boundaries

• Maintain RAM authorization governance boundaries

• Maintain RWM withdrawal governance boundaries

• Maintain SCFS configuration governance boundaries

• Maintain SDS dependency governance boundaries

• Maintain SDPS deployment governance boundaries

• Maintain SCMS change governance boundaries

• Maintain SRTS retirement governance boundaries

• Maintain SLCS lifecycle control boundaries

• Prevent RRMM from independently establishing release readiness

• Prevent RRMM from independently granting release authorization

• Prevent RRMM from independently establishing deployment permission

• Prevent RRMM from independently certifying software correctness or

• Produce a Software Release Record Profile

security.

Governance Logic

Canonical RRMM logic:

Software Product Identity → Release Record Identity → Record Purpose →

Record Boundary → Release Candidate Reference → Artifact & Version References → Configuration & Dependency References → Readiness Assessment Reference → Authorization Decision Reference → Release Event References → Distribution & Restriction References → Record Provenance → Evidence Association → Evidence Sufficiency → Record Completeness → Record Consistency → Record Integrity → Record Classification → Software Release Record Profile → Historical State Preservation → Deployment / Withdrawal / Lifecycle Governance Handoff

Governance Outputs

RRMM may produce:

Software Release Record Profile

Release Record Identity

Release Record Purpose

Release Record Boundary

Software Product Association

Release Candidate Association

Artifact Identity Reference

Artifact Version Reference

Build Reference

Configuration Baseline Reference

Dependency Baseline Reference

Readiness Assessment Reference

Authorization Decision Reference

Release Event Register

Distribution Reference

Release Restriction Register

Record Provenance Register

Record Evidence Register

Evidence Sufficiency State

Missing Evidence Record

Evidence Conflict Record

Record Completeness Assessment

Record Consistency Assessment

Record Integrity Assessment

Record Authenticity Reference

Record Classification

Record Update Register

Record Correction Register

Record Supersession Reference

Historical Record Register

Record Retention Reference

Record Accessibility State

Record Transfer Reference

Lifecycle Governance Handoff

Version

Practical ApplicationsAutonomous Software Development

Preserving traceable release records when AI agents create, assess, authorize, and distribute software through multiple automated tools. Enterprise Release Management

Maintaining coherent release governance records across development,

testing, security, operations, and management functions. Continuous Integration and Delivery

Associating automated build artifacts, readiness results, authorization

decisions, and release events without confusing technical pipeline execution with governance approval. Software Supply Chain Governance

Preserving artifact, configuration, dependency, and origin references

needed to reconstruct software release composition. Critical Infrastructure Software

Maintaining reliable release histories for systems where changes may affect essential operational functions. Incident Investigation and Withdrawal

Providing release evidence that supports identification of affected artifacts, release events, authorization conditions, and historical states.

Use Case 1 — An AI Software Factory Produces a Release Without a

Reconstructable Record

An organization operates an autonomous software factory.

Multiple AI agents generate source code, modify dependencies, execute

builds, perform tests, and prepare release candidates.

The software factory successfully produces a functioning application.

A release authorization process approves the candidate.

The software is subsequently published.

However, the organization discovers that its release record contains only a version label and a successful pipeline status.

The record does not preserve the exact artifact identity, applicable configuration baseline, dependency references, readiness assessment, or authorization decision.

RRMM evaluates:

Release Record Identity → Candidate Association → Artifact Identity →

Configuration & Dependency References → Readiness Reference → Authorization Reference → Evidence Sufficiency → Record Classification

The assessment identifies:

• A release event occurred

• A release record exists

• The exact released artifact cannot be sufficiently reconstructed

• Readiness and authorization references are incomplete

• The record cannot fully support subsequent governance investigation

The appropriate classification is:

Record Incomplete — Evidence-Limited.

The critical distinctions are:

Release Record Exists ≠ Release Governance Evidence Complete.

Successful Pipeline ≠ Complete Release Evidence.

Version Label ≠ Verified Artifact Identity.

The result: RRMM exposes the difference between successful automated

software delivery and reconstructable release governance.

• Use Case 2 — A Release Record Is Silently Modified After an Incident

An organization distributes a software release.

Several weeks later, an operational incident reveals that the released software contained a configuration inconsistent with the intended release conditions.

During the investigation, a release administrator modifies the original

release record to reflect the configuration that should have been used.

The modification overwrites the previous value.

No correction reason, modification time, or historical version is preserved.

The current release record appears consistent with the intended

configuration.

However, it no longer accurately represents the information recorded at the

time of release.

RRMM evaluates:

Original Record → Recorded Configuration → Modification Event → Correction

Evidence → Historical State → Record Integrity

The assessment identifies:

• The original record was modified

• The original recorded value was not preserved

• The modification cannot be sufficiently reconstructed

• The current record may conceal the historical discrepancy

• Record integrity is not sufficiently established

The appropriate classification is:

Record Integrity Unresolved — Historical Evidence Incomplete.

The critical distinctions are:

Release Record Corrected ≠ Original Release Event Changed.

Current Record Consistent ≠ Historical Record Accurate.

Record Updated ≠ Record Integrity Preserved.

The result: RRMM requires corrections to remain traceable rather than

allowing historical release evidence to be silently rewritten.

Use Case 3 — A Security Withdrawal Requires Identification of Affected

Releases

A software supplier discovers a security vulnerability affecting a

third-party library.

The vulnerable library was used in several software releases.

Some releases included the library directly.

Others inherited it through transitive dependencies.

The supplier must determine which releases may be affected.

Its release records contain software version names but do not consistently

preserve dependency baselines or artifact composition references.

The organization cannot immediately establish which distributed artifacts

contain the vulnerable component.

RRMM evaluates:

Release Record Identity → Artifact References → Dependency Baseline

References → Historical Release Composition → Evidence Coverage → Affected Release Identification

The assessment identifies:

• Release records are available

• Dependency composition evidence is incomplete

• Version names do not sufficiently establish affected artifact

• The organization cannot reliably reconstruct the complete affected

• Additional evidence acquisition is required

composition. release population.

The appropriate classification is:

Record Evidence-Limited — Dependency Traceability Incomplete.

The critical distinctions are:

Release History Available ≠ Dependency Exposure Reconstructable.

Software Version Known ≠ Component Composition Known.

Record Completeness for Distribution ≠ Record Completeness for Security

Withdrawal.

The result: RRMM demonstrates why release records must preserve sufficient artifact and dependency traceability before an incident creates an urgent need for reconstruction.

Critical Distinctions

Release Record Exists ≠ Release Governance Evidence Complete.

Release Recorded ≠ Release Authorized.

Release Record Updated ≠ Underlying Release State Changed.

Historical Release Record Preserved ≠ Historical Authorization Still

Valid.

Artifact Reference Recorded ≠ Artifact Identity Verified.

Release Information Recorded ≠ Release Information Proven.

Required Fields Populated ≠ Release Record Substantively Complete.

Release Record Accessible ≠ Release Record Integrity Established.

Release Record Revised ≠ Previous Release Record Erased.

Release History Available ≠ Complete Software Lifecycle Traceability

Established.

Release Name Recorded ≠ Unique Release Identity Established.

Release Record Suitable for Distribution Tracking ≠ Release Record

Sufficient for Authorization Audit.

Release Record Covers One Candidate ≠ Release Record Covers Every Related

Artifact.

Software Product Identified ≠ Exact Released Artifact Identified.

Release Candidate Referenced ≠ Candidate Identity and Composition

Verified.

Version Label Equality ≠ Artifact Equivalence.

Release Artifact Identified ≠ Applicable Configuration Context Fully

Established.

Dependency Manifest Attached ≠ Complete Release Dependency Reality

Established.

Readiness Conclusion Recorded ≠ Readiness Conclusion Independently

Verified by RRMM.

Authorization Decision Referenced ≠ Authorization Legitimacy Independently

Established.

Release Event Recorded ≠ Release Event Authorized.

Software Published to a Repository ≠ Software Delivered to Every Intended

Recipient.

Release Restrictions Recorded ≠ Release Restrictions Operationally

Enforced.

Release Record Source Identified ≠ Release Record Content Authenticated.

Evidence Linked ≠ Evidence Relevant or Sufficient.

All Mandatory Fields Present ≠ All Recorded Claims Substantively

Supported.

Release Record Internally Consistent ≠ Release Record Factually Correct.

Record Unchanged ≠ Record Originally Accurate.

Record Authenticated ≠ Every Claim Within the Record Validated.

Release Evidence Available ≠ Release Evidence Sufficient for Every

Lifecycle Decision.

Release Information Missing ≠ Release Condition Satisfied.

Record Uncertainty Acknowledged ≠ Record Uncertainty Resolved.

Release Record Corrected ≠ Original Release Event Changed.

Historical Record Inaccurate ≠ Historical Record May Be Silently Rewritten.

Release Record Superseded ≠ Previous Release Record Invalid for Historical

Reconstruction.

Release Record Version Increased ≠ Software Release Version Increased.

Current Release Record State ≠ Complete Historical Release State.

Record No Longer Operationally Needed ≠ Record Eligible for Deletion.

Release Record Stored ≠ Release Record Retrievable When Required.

Release Record Transferred ≠ Record Integrity and Accessibility

Automatically Preserved.

Release Record Classified as Complete ≠ Release Independently Validated as

Ready or Authorized.

Cross-Architecture Boundary

RRMM may consume governed references from:

GOA™ — Governance Architecture

AGA™ — Accountability Governance Architecture

SCS — Software Creation Standard

SDS — Software Dependency Standard

SCFS — Software Configuration Standard

SQS — Software Quality Standard

SSS — Software Security Standard

Within SRLS, RRMM receives release governance references from:

RCMM — Release Candidate Management Module

RRM — Release Readiness Module

RAM — Release Authorization Module

RRMM supports:

RWM — Release Withdrawal Module

SDPS — Software Deployment Standard

SCMS — Software Change Management Standard

SRTS — Software Retirement Standard

SLCS — Software Lifecycle Control Standard

RRMM preserves the release governance record and its historical continuity.

It does not replace the mechanisms responsible for establishing candidate identity, readiness, authorization, deployment, withdrawal, or lifecycle transitions.

Cross-Architecture Mechanism Principle

An operational mechanism may produce inputs for multiple governance architectures, but it belongs only to the architecture whose governed domain includes that mechanism itself. Other architectures govern only its domain-specific relevance or consequences.

RRMM may preserve evidence generated through software creation, configuration, dependency, quality, security, authorization, deployment, and operational processes.

It governs how that evidence is associated with and preserved within the software release record.

It does not redefine the underlying mechanisms or independently validate every referenced governance conclusion.

Canonical Boundary

RRMM governs how software release records are established, structured, associated, preserved, updated, verified, superseded, and maintained as traceable evidence of identifiable software releases and their applicable governance states throughout the software lifecycle.

It does not independently establish software readiness, grant release authorization, execute software deployment, withdraw releases, or certify software correctness, security, or operational acceptability.

Its principal governed output is the Software Release Record Profile.

Canonical Closing Statement

Software release governance cannot remain reliable if the evidence of what

was released, why it was considered ready, who authorized it, and under which conditions it was distributed cannot be reconstructed.

Modern software delivery increasingly involves distributed development

environments, automated build systems, external dependencies, AI coding agents, autonomous workflows, and multiple release channels.

These mechanisms can produce and distribute software rapidly.

But the speed of software delivery does not establish the completeness or integrity of its release history.

A software release may be technically successful while its record remains incomplete.

An authorization decision may be legitimate while its evidence is poorly preserved.

A release record may exist while the exact released artifact cannot be identified.

And a historical record may appear complete after modifications have silently erased the information originally recorded.

A release record is not reliable merely because it exists.

It must preserve identifiable relationships between the software product, release candidate, artifact composition, readiness assessment, authorization decision, release event, and applicable restrictions.

It must distinguish what was known at the time of release from what was discovered later.

It must preserve corrections without rewriting history.

And it must remain accessible and interpretable when software is deployed, modified, investigated, withdrawn, or retired.

Historical evidence must remain historical evidence—even when later knowledge changes the interpretation of the release.

This principle applies whether software is released by a human development team, an automated delivery pipeline, or an autonomous AI software factory.

The release mechanism may change.

The participating actors may change.

The software artifacts may evolve.

The requirement for reconstructable release governance remains.

RRMM transforms software release documentation into governed lifecycle

evidence — preserving not merely the claim that software was released, but the identifiable artifacts, decisions, conditions, events, and historical relationships required to establish what that release represented and how its governance state can be reconstructed over time.

Modul 5

RWM — Release Withdrawal Module

Architecture

SLGA™ — Software Lifecycle Governance Architecture

Parent Standard

SRLS — Software Release Standard

Category

Governance & Enforcement

Subcategory

Software Lifecycle Governance

Type

Core Module

Governed Space

Software Release Withdrawal Governance

Module ID

SLGA-SRLS-RWM-05

Origin ID

OOF-SLGA-SRLS-RWM

Version

1.0

Status

Canonical Open

Effective Date

10.2026

Compatibility

Methodology OS — Modular Compatibility

GIE-Compatible

Yes

AI-Readable

Yes

Authority

OOF® — OriginOpen® Foundation

Protection

Protected Methodological Work

Canonical Language

English

Canonical Definition

RWM — Release Withdrawal Module is the Core Module within SRLS that governs how previously authorized, published, distributed, or otherwise available software releases are identified, evaluated, restricted, suspended, withdrawn, and reassessed when their continued release availability, authorization applicability, distribution eligibility, or supporting governance conditions can no longer be sufficiently maintained.

RWM establishes the methodological conditions under which a software

release must be considered for withdrawal and how the resulting withdrawal decision, scope, authority, execution references, evidence, residual availability, and lifecycle consequences are governed.

It governs the distinction between identifying a withdrawal condition,

authorizing a withdrawal, executing withdrawal actions, and verifying the resulting release availability state.

The module recognizes that software release withdrawal may affect distribution channels, repositories, registries, download endpoints, update mechanisms, recipient access, and previously distributed artifacts differently.

Removing a release from one distribution location does not establish that all copies have become unavailable.

Similarly, withdrawing release authorization does not automatically remove deployed software, reverse completed installations, or eliminate operational exposure.

RWM preserves the relationship between release withdrawal decisions and the

underlying governance conditions that require restriction, suspension, reassessment, or withdrawal.

Its principal governed output is the Software Release Withdrawal Profile.

Release Authorization Revoked ≠ Software Release Automatically Withdrawn.

Release Withdrawal Authorized ≠ Release Withdrawal Executed.

Release Removed from One Channel ≠ Release Universally Unavailable.

Release Withdrawal Completed ≠ Deployed Software Removed.

Withdrawal Action Executed ≠ Withdrawal Effectiveness Verified.

Operational Role

RWM governs the controlled withdrawal of software releases from applicable

release and distribution availability.

Its operational role is to establish:

• Withdrawal identity

• Affected release identity

• Withdrawal purpose

• Withdrawal trigger

• Withdrawal scope

• Withdrawal authority

• Decision actor eligibility

• Withdrawal urgency

• Withdrawal prerequisites

• Release availability references

• Distribution channel references

• Recipient exposure references

• Withdrawal restrictions

• Withdrawal decision

• Withdrawal execution references

• Withdrawal evidence

• Withdrawal effectiveness

• Residual availability

• Partial withdrawal

• Withdrawal exceptions

• Escalation conditions

• Reassessment requirements

• Reauthorization references

• Historical withdrawal states

• Deployment governance handoffs

• Lifecycle continuity

RWM does not independently execute deployment rollback, uninstall software from operational environments, revoke general organizational authority, or determine liability for consequences arising from a release.

Operational Question

How can software releases be legitimately and effectively withdrawn when authorization, security, quality, dependency, configuration, or other release-governing conditions become invalid, while ensuring that withdrawal decisions, distribution boundaries, execution actions, residual availability, deployed software exposure, evidence, and lifecycle consequences remain identifiable, traceable, and appropriately governed?

Position in Architecture Governance Flow

SLGA™ Governance Flow

Software Requirements → Software Creation → Software Dependencies →

Software Configuration → Software Quality → Software Security → Software Release → Software Deployment → Software Change Management → Software Retirement

Cross-cutting:

Software Lifecycle Control

SRLS Core Module Flow

RCMM — Release Candidate Management Module

2. RRM — Release Readiness Module 3. RAM — Release Authorization Module 4. RRMM — Release Record Management Module 5. RWM — Release Withdrawal Module

RWM occupies the fifth and final Core Module position within SRLS.

It receives release identities, authorization states, and historical

release records from the preceding SRLS modules.

RWM governs whether continued release availability remains supportable and,

where necessary, establishes the conditions for restricted availability, suspension, or withdrawal.

It provides downstream governance references to deployment, change

management, retirement, and lifecycle control mechanisms.

Release Candidate Profile → Release Readiness Profile → Release

Authorization Profile → Software Release Record Profile → Withdrawal Trigger → Withdrawal Scope → Withdrawal Authority → Withdrawal Decision → Withdrawal Execution Reference → Effectiveness Verification → Residual Availability Assessment → Software Release Withdrawal Profile → Lifecycle Governance Handoff

• Governed Space

Software Release Withdrawal Governance

This governed space concerns the legitimate and evidence-supported

restriction, suspension, or withdrawal of software release availability.

It includes:

• Withdrawal identification

• Withdrawal triggers

• Release identity

• Withdrawal boundaries

• Distribution channel scope

• Withdrawal authority

• Withdrawal decision

• Withdrawal urgency

• Execution references

• Availability verification

• Residual exposure

• Partial withdrawal

• Withdrawal exceptions

• Recipient communication references

• Reassessment

• Reauthorization

• Historical withdrawal continuity

• Lifecycle handoffs

RWM does not independently govern deployment rollback execution, incident remediation, operational recovery, or software retirement.

Governed Object

The primary Governed Object is:

A Software Release Withdrawal State representing the evidence-supported

relationship between an identifiable software release, its applicable withdrawal conditions, legitimate withdrawal authority, affected distribution scope, withdrawal actions, verified availability changes, residual exposure, and resulting governance classification.

The governed state must preserve:

Software Product ID

Release ID

Release Withdrawal ID

Release Record Reference

Withdrawal Trigger

Withdrawal Purpose

Withdrawal Scope

Withdrawal Authority

Decision Actor

Withdrawal Decision

Execution References

Affected Distribution Channels

Withdrawal Evidence

Residual Availability

Withdrawal Effectiveness

Withdrawal Classification

Reassessment Requirement

Lifecycle Handoff

Version

Scope

RWM governs:

• Withdrawal requests

• Withdrawal triggers

• Affected release identification

• Withdrawal boundaries

• Distribution availability references

• Withdrawal authority

• Decision actor eligibility

• Withdrawal urgency

• Withdrawal decisions

• Partial and complete withdrawal classifications

• Execution evidence

• Effectiveness verification

• Residual availability

• Withdrawal exceptions

• Escalation

• Reassessment

• Reauthorization conditions

• Historical withdrawal preservation

• Deployment and lifecycle handoffs

RWM does not independently determine operational safety, perform software remediation, or guarantee removal of all previously distributed software copies.

Foundational Governance Principles8.1 Authorization–Withdrawal

Separation Principle

Release Authorization Revoked ≠ Software Release Automatically Withdrawn. 8.2 Decision–Execution Separation Principle

Release Withdrawal Authorized ≠ Release Withdrawal Executed. 8.3 Distribution Boundary Principle

Release Removed from One Channel ≠ Release Universally Unavailable. 8.4 Deployment Boundary Principle

Release Withdrawal Completed ≠ Deployed Software Removed. 8.5 Effectiveness Principle

Withdrawal Action Executed ≠ Withdrawal Effectiveness Verified. 8.6 Authority Principle

Technical Ability to Remove a Release ≠ Legitimate Withdrawal Authority. 8.7 Scope Principle

Partial Release Withdrawal ≠ Complete Release Withdrawal. 8.8 Evidence Principle

Withdrawal Completion Reported ≠ Withdrawal Completion Proven. 8.9 Continuity Principle

Release Previously Withdrawn ≠ Release Continuously Unavailable. 8.10 Historical Integrity Principle

Release Withdrawn ≠ Historical Release Record Erased.

Release Withdrawal Identity

Every governed withdrawal process must establish:

Release Withdrawal ID

Software Product ID

Release ID

Release Record ID

Withdrawal Purpose

Withdrawal Trigger

Withdrawal Scope

Withdrawal Authority Reference

Withdrawal Initiation Time

Withdrawal Classification

Version

Withdrawal Identity Principle

Withdrawal Request Identified ≠ Affected Release Sufficiently Identified.

Withdrawal Purpose

Withdrawal purposes may include:

Security Exposure Reduction

Critical Defect Containment

Invalid Authorization Response

Release Integrity Protection

Dependency Risk Containment

Distribution Restriction Enforcement

Regulatory or Contractual Response

Release Replacement

Lifecycle Closure Support

The purpose must remain distinguishable from the evidence establishing the need for withdrawal.

Purpose Integrity

Withdrawal Purpose Legitimate ≠ Withdrawal Method Automatically

Appropriate.

Withdrawal Triggers

Withdrawal may be considered when:

Critical Vulnerability Identified

Material Quality Failure Identified

Release Authorization Revoked

Release Authorization Expired

Release Artifact Integrity Compromised

Dependency Risk Becomes Unacceptable

Configuration Defect Identified

Distribution Restriction Violated

Release Evidence Invalidated

Applicable Release Conditions No Longer Satisfied

Authorized Withdrawal Instruction Received

A trigger initiates evaluation.

It does not automatically establish that every possible withdrawal action is required or authorized.

Trigger Principle

Withdrawal Trigger Identified ≠ Withdrawal Decision Automatically

Established.

Affected Release Identification

RWM must establish the software releases affected by the withdrawal condition.

Relevant elements include:

Software Product ID

Release ID

Release Version

Artifact Identity

Build Reference

Configuration Reference

Dependency Reference

Release Record Reference

Related Release References

Release Identification Principle

Software Version Affected ≠ Every Artifact Bearing That Version Identically Affected.

Withdrawal Scope

Withdrawal scope defines the release availability affected by the decision.

Relevant dimensions include:

Software Product Scope

Release Version Scope

Artifact Scope

Distribution Channel Scope

Recipient Scope

Geographic Scope

Temporal Scope

Repository Scope

Update Mechanism Scope

Release Authorization Scope

Scope Integrity

Withdrawal Applied to a Defined Scope ≠ Withdrawal Completed Outside That Scope.

Distribution Availability Baseline

RWM establishes the relevant release availability state before withdrawal.

Relevant elements include:

Distribution Channel

Repository Location

Download Endpoint

Package Registry

Update Service

Release Mirror

Known Recipient Group

Published Artifact Reference

Availability Evidence

Observation Time

Availability Baseline Principle

Known Distribution Locations ≠ Every Existing Software Copy Identified.

Withdrawal Authority

RWM must identify the authority under which withdrawal may legitimately occur.

Relevant elements include:

Authority Reference

Authority Source

Authority Holder

Permitted Withdrawal Function

Authority Scope

Authority Conditions

Authority Validity

Delegation Reference

Revocation Status

The legitimacy of general authority remains governed by the applicable

authority architecture.

Authority Integrity

Repository Administrative Access ≠ Legitimate Release Withdrawal

Authority.

Withdrawal Decision Actor

The withdrawal decision may be executed by:

Authorized Human

Authorized Organizational Function

Automated Release Governance System

Delegated AI Agent

Autonomous Software Governance Agent

Hybrid Human–Machine Decision Process

The decision actor must remain distinguishable from the authority governing the decision.

Actor Principle

Actor Capable of Withdrawal ≠ Actor Authorized to Decide Withdrawal.

Delegated Withdrawal Authority

Where withdrawal authority is delegated, RWM must preserve:

Delegation Reference

Delegating Authority

Receiving Actor

Delegated Withdrawal Function

Permitted Release Scope

Permitted Withdrawal Actions

Delegation Conditions

Delegation Restrictions

Delegation Validity

Revocation Reference

Delegation Principle

Authority to Publish Software ≠ Authority to Withdraw Every Published

Release.

Automated Withdrawal

Automated withdrawal may be used where applicable authority and decision conditions are established.

Relevant elements include:

Automated Withdrawal System ID

Withdrawal Policy Reference

Authority Reference

Permitted Withdrawal Triggers

Permitted Distribution Scope

Required Evidence

Decision Conditions

Execution Restrictions

Escalation Requirements

Withdrawal Event Evidence

Automation must not replace the requirement for legitimate withdrawal authority.

Automation Integrity

Automated Withdrawal Trigger Activated ≠ Legitimate Withdrawal Decision

Established.

Autonomous Agent Withdrawal

Where autonomous AI agents participate in withdrawal decisions or execution, RWM must preserve:

Agent Identity

Authority Reference

Delegated Withdrawal Function

Permitted Tools

Permitted Release Scope

Decision Constraints

Execution Evidence

Escalation Conditions

Override Conditions

Withdrawal State

The agent's authority must cover the specific withdrawal decision and applicable constituent actions.

Autonomous Authority Principle

Agent Authorized to Monitor Release Risk ≠ Agent Authorized to Remove

Software Releases.

Withdrawal Urgency

Withdrawal urgency must reflect the supported severity and time sensitivity of the governing condition.

Relevant elements include:

Trigger Severity

Exposure Scope

Potential Consequences

Affected Recipients

Time Sensitivity

Available Mitigations

Evidence Confidence

Escalation Requirements

Urgency must not silently eliminate mandatory authority conditions.

Urgency Principle

Withdrawal Urgent ≠ Withdrawal Authority Unlimited.

Withdrawal Prerequisites

RWM identifies the conditions required before the applicable withdrawal

decision or action.

Relevant elements include:

Affected Release Identified

Withdrawal Trigger Evaluated

Applicable Authority Established

Withdrawal Scope Defined

Decision Actor Eligible

Required Evidence Available

Execution Mechanism Identified

Applicable Restrictions Preserved

Required Escalation Established

Emergency mechanisms may use different prerequisites only where legitimately established.

Prerequisite Principle

Withdrawal Prerequisites Documented ≠ Withdrawal Prerequisites Satisfied.

Withdrawal Decision

RWM establishes an explicit withdrawal decision.

Relevant elements include:

Withdrawal Decision ID

Affected Release

Withdrawal Trigger

Withdrawal Authority

Decision Actor

Withdrawal Scope

Decision Evidence

Withdrawal Classification

Restrictions

Effective Time

Required Execution Actions

Decision Integrity

Withdrawal Decision Recorded ≠ Withdrawal Decision Executed.

Withdrawal Decision Classification

Possible decisions include:

Withdrawal Not Required

Withdrawal Review Required

Withdrawal Deferred

Restricted Availability Required

Release Suspension Required

Partial Withdrawal Authorized

Complete Withdrawal Authorized Within Defined Scope

Withdrawal Denied

Evidence-Limited

Conflicted

Unknown

A complete withdrawal authorization applies only within its defined boundary.

Classification Principle

Complete Withdrawal Authorized Within Scope ≠ Universal Removal of All Software Copies.

Release Restriction

A release restriction limits continued release availability without

necessarily requiring complete withdrawal.

Relevant elements include:

Restriction ID

Affected Release

Restriction Purpose

Restricted Channel

Restricted Recipient Scope

Restriction Authority

Restriction Effective Time

Restriction Evidence

Reassessment Requirement

Restriction Principle

Release Availability Restricted ≠ Release Fully Withdrawn.

Release Suspension

Release suspension establishes a temporary restriction on continued release

availability or release eligibility.

Relevant elements include:

Suspension ID

Affected Release

Suspension Trigger

Suspension Authority

Suspension Scope

Suspension Start

Suspension Conditions

Reassessment Requirement

Resumption Conditions

Suspension Integrity

Release Suspended ≠ Release Permanently Withdrawn.

Partial Withdrawal

Partial withdrawal concerns the removal or restriction of release

availability within a limited scope.

Relevant elements include:

Affected Artifact

Affected Channel

Affected Recipient Group

Withdrawal Boundary

Completed Actions

Remaining Availability

Residual Exposure

Evidence Basis

Partial Withdrawal Principle

Release Withdrawn from One Repository ≠ Release Withdrawn from Every

Repository.

• Complete Withdrawal Within Scope

A complete withdrawal classification requires evidence that the defined withdrawal scope has been addressed.

Relevant elements include:

Defined Withdrawal Boundary

Known Distribution Channels

Required Withdrawal Actions

Execution Evidence

Availability Verification

Unresolved Exceptions

Residual Availability

Completion Classification

Complete withdrawal within scope must not be represented as universal elimination of software copies.

Completion Principle

Withdrawal Complete Within Defined Scope ≠ All Previously Distributed Copies Eliminated.

Withdrawal Execution References

RWM preserves references to operational withdrawal actions.

Possible actions include:

Repository Removal

Package Registry Withdrawal

Download Endpoint Deactivation

Release Channel Restriction

Update Publication Suspension

Artifact Distribution Blocking

Release Mirror Notification

Recipient Notification

Execution remains performed by the relevant operational systems or

authorized actors.

Execution Principle

Withdrawal Action Requested ≠ Withdrawal Action Completed.

Distribution Channel Withdrawal

RWM governs the release withdrawal state across affected distribution

channels.

Relevant elements include:

Channel ID

Release Artifact Reference

Withdrawal Action

Execution Actor

Execution Time

Execution Evidence

Channel Availability State

Verification Result

Channel Integrity

Primary Distribution Channel Disabled ≠ Secondary Distribution Channels

Disabled.

Repository Withdrawal

Repository withdrawal concerns the removal or restriction of release

availability through a repository.

Relevant elements include:

Repository ID

Release Reference

Package Reference

Removal or Restriction Action

Execution Evidence

Repository State

Verification Time

Residual Availability

Repository Principle

Repository Entry Removed ≠ Previously Downloaded Software Removed.

Package Registry Withdrawal

Where software is distributed through package registries, RWM preserves:

Registry Reference

Package Identity

Package Version

Withdrawal Mechanism

Registry Restrictions

Execution Status

Availability Verification

Known Replication Limitations

Registry Integrity

Package Version Withdrawn from Registry ≠ Package Version Unavailable

Through Every Mirror or Cache.

Update Channel Withdrawal

RWM governs withdrawal implications for software update distribution.

Relevant elements include:

Update Channel ID

Affected Update Package

Update Publication State

Automatic Update Eligibility

Distribution Restriction

Withdrawal Execution Reference

Verification Evidence

Remaining Update Exposure

Update Channel Principle

Update Distribution Suspended ≠ Previously Installed Update Reversed.

Release Mirror and Cache Exposure

RWM must account for known release availability through mirrors, caches, or replicated distribution mechanisms.

Relevant elements include:

Mirror Reference

Cache Reference

Replication Scope

Artifact Availability

Removal Capability

Withdrawal Notification

Verification Evidence

Known Limitations

Replication Principle

Origin Release Removed ≠ Replicated Release Copies Removed.

Recipient Exposure

RWM preserves known recipient exposure relevant to withdrawal effectiveness.

Relevant elements include:

Recipient Group

Distribution Channel

Known Download Events

Known Delivery Events

Installed Software References Where Available

Notification Requirements

Residual Exposure

Evidence Limitations

Recipient Principle

Release No Longer Available for Download ≠ Previously Exposed Recipients

No Longer Affected.

Withdrawal Communication References

RWM may preserve references to withdrawal communications.

Relevant elements include:

Communication ID

Communication Purpose

Affected Release

Recipient Scope

Communication Authority

Communication Channel

Communication Time

Delivery Evidence

Required Follow-Up

Communication Principle

Withdrawal Notice Issued ≠ Withdrawal Notice Received or Acted Upon.

Withdrawal Evidence

RWM may use:

Release Record Profile

Release Authorization Profile

Security Findings

Quality Findings

Dependency Risk Evidence

Artifact Integrity Evidence

Withdrawal Decision Record

Repository Removal Evidence

Registry Withdrawal Evidence

Distribution Channel Evidence

Recipient Notification Evidence

Availability Verification Evidence

Evidence Provenance

Withdrawal evidence must preserve:

Evidence ID

Source

Origin

Collection Method

Affected Release

Affected Distribution Channel

Observation Time

Collection Time

Evidence Content

Known Limitations

Version

Provenance Principle

Withdrawal Evidence Recorded ≠ Withdrawal Evidence Reliable.

Evidence Sufficiency

Evidence sufficiency concerns whether the available evidence supports the

claimed withdrawal state.

Relevant dimensions include:

Release Identity Coverage

Distribution Channel Coverage

Execution Evidence

Availability Verification

Recipient Scope Coverage

Temporal Coverage

Evidence Freshness

Evidence Consistency

Known Replication Exposure

Evidence Sufficiency Principle

Withdrawal Action Logs Available ≠ Withdrawal Effectiveness Sufficiently

Established.

Withdrawal Effectiveness Verification

RWM governs verification of whether the required withdrawal effects have

occurred.

Relevant elements include:

Withdrawal Decision Reference

Required Action

Executed Action

Affected Channel

Observed Availability

Verification Method

Verification Time

Residual Exposure

Verification Classification

Effectiveness Principle

Withdrawal Execution Successful ≠ Withdrawal Objective Fully Achieved.

Residual Availability Assessment

Residual availability concerns release copies or distribution paths that remain accessible after withdrawal actions.

Relevant elements include:

Remaining Distribution Channels

Known Mirrors

Known Caches

Previously Downloaded Artifacts

Previously Distributed Packages

Uncontrolled Copies

Verification Limitations

Residual Availability Classification

Residual Availability Principle

Known Distribution Channels Cleared ≠ No Residual Software Copies Exist.

Withdrawal Exceptions

Withdrawal exceptions may include:

Unavailable Distribution Channel

Uncontrolled External Mirror

Inaccessible Recipient Environment

Conflicting Withdrawal Instruction

Insufficient Artifact Identification

Missing Execution Evidence

Unverified Withdrawal Effect

Legal or Contractual Restriction

Exceptions must remain explicit and traceable.

Exception Principle

Withdrawal Exception Recorded ≠ Withdrawal Exception Resolved.

Withdrawal Uncertainty

Withdrawal uncertainty may arise from:

Incomplete Distribution Records

Unknown Recipients

Unknown Mirrors

Unavailable Verification Evidence

Uncontrolled Software Copies

Conflicting Channel Reports

Delayed Distribution State Updates

Unknown Operational Exposure

Uncertainty Principle

Withdrawal Uncertainty Acknowledged ≠ Withdrawal Uncertainty Eliminated.

Withdrawal Escalation

RWM governs the identification of conditions requiring escalation.

Relevant elements include:

Escalation Trigger

Affected Release

Withdrawal Severity

Residual Exposure

Evidence Basis

Responsible Authority

Required Action

Escalation Status

Escalation Principle

Withdrawal Escalation Initiated ≠ Withdrawal Risk Resolved.

Withdrawal and Deployment Separation

Release withdrawal governs continued release availability and distribution

eligibility.

Deployment governance concerns software installation, activation,

operation, rollback, and recovery within operational environments.

A withdrawn release may remain deployed.

A deployment rollback may occur without withdrawal of the underlying release.

The two mechanisms must preserve their separate governance states.

Deployment Boundary Principle

Release Withdrawal ≠ Deployment Rollback.

Deployment Rollback ≠ Release Withdrawal.

Withdrawal and Remediation Separation

Software remediation concerns correction or mitigation of the underlying

defect, vulnerability, or other condition.

Withdrawal may reduce further distribution exposure.

It does not independently correct the affected software.

Remediation Principle

Release Withdrawn ≠ Underlying Software Defect Remediated.

Withdrawal and Retirement Separation

Software retirement concerns the controlled end of a software product's

supported lifecycle.

Release withdrawal may affect a particular version while the product remains active.

Software retirement may involve many releases and additional operational obligations.

Retirement Boundary Principle

Software Release Withdrawn ≠ Software Product Retired.

Withdrawal Reassessment

Withdrawal reassessment may be required when:

Withdrawal Trigger Changes

Affected Release Scope Changes

Distribution Evidence Changes

New Mirrors Are Identified

Additional Recipients Are Identified

Withdrawal Actions Fail

Residual Availability Changes

Remediation Evidence Becomes Available

Authorization Conditions Change

Reauthorization Is Requested

Reassessment Principle

Withdrawal Reassessment Completed ≠ Release Automatically Reauthorized.

Release Reauthorization References

Where a withdrawn release is proposed for renewed availability, RWM must preserve:

Original Withdrawal ID

Original Withdrawal Trigger

Withdrawal Resolution Evidence

Current Candidate Reference

Current Readiness Reference

Current Authorization Reference

Reauthorization Conditions

Remaining Restrictions

Reavailability Decision Reference

New release authorization remains governed by RAM.

Reauthorization Principle

Withdrawal Cause Resolved ≠ Release Authorization Automatically Restored.

Historical Withdrawal State Preservation

RWM must preserve historical withdrawal states.

Relevant elements include:

Original Release State

Original Authorization State

Withdrawal Trigger

Withdrawal Decision

Withdrawal Scope

Execution Events

Verification Results

Residual Availability

State Transition Time

Superseding State

Historical Integrity

Release Reauthorized Later ≠ Previous Withdrawal History Erased.

Withdrawal Classification

RWM may classify withdrawal states as:

Withdrawal Not Initiated

Withdrawal Review Required

Withdrawal Trigger Identified

Withdrawal Decision Pending

Withdrawal Not Required

Withdrawal Authorized

Withdrawal Denied

Release Availability Restricted

Release Suspended

Partial Withdrawal In Progress

Complete Withdrawal In Progress

Withdrawal Execution Pending

Withdrawal Execution Failed

Withdrawal Verification Pending

Withdrawal Partially Verified

Withdrawal Verified Within Defined Scope

Residual Availability Identified

Withdrawal Evidence-Limited

Withdrawal Exception Identified

Reassessment Required

Reauthorization Required

Conflicted

Unknown

Withdrawal Closed

These are release withdrawal governance classifications, not deployment or software retirement classifications.

Classification Integrity

Withdrawal Verified Within Defined Scope ≠ Universal Software Unavailability Established.

Software Release Withdrawal Profile

The principal governed output is the:

Software Release Withdrawal Profile

It establishes the evidence-supported withdrawal state of an identifiable

software release.

The profile preserves:

• Software product identity

• Release identity

• Release record reference

• Withdrawal identity

• Withdrawal trigger

• Withdrawal purpose

• Withdrawal scope

• Withdrawal authority

• Decision actor

• Withdrawal urgency

• Withdrawal decision

• Execution references

• Distribution channel states

• Recipient exposure references

• Withdrawal evidence

• Effectiveness verification

• Residual availability

• Exceptions

• Escalation

• Withdrawal classification

• Reassessment requirements

• Reauthorization references

• Historical withdrawal states

• Deployment and lifecycle handoffs

Minimum Profile Fields

At minimum:

Software Release Withdrawal Profile ID

Software Product ID

Release ID

Release Withdrawal ID

Release Record Profile ID

Release Authorization Profile ID

Withdrawal Trigger

Withdrawal Purpose

Withdrawal Scope

Withdrawal Boundary

Withdrawal Authority Reference

Decision Actor Reference

Withdrawal Urgency

Withdrawal Prerequisites

Withdrawal Decision

Withdrawal Decision Time

Affected Artifact References

Affected Distribution Channels

Distribution Availability Baseline

Withdrawal Action Register

Execution Actor References

Execution Times

Execution Evidence

Distribution Channel States

Repository Withdrawal References

Package Registry Withdrawal References

Update Channel Withdrawal References

Mirror and Cache Exposure

Recipient Exposure References

Withdrawal Communication References

Withdrawal Evidence Provenance

Evidence Sufficiency

Missing Evidence

Evidence Conflicts

Withdrawal Effectiveness Assessment

Residual Availability Assessment

Withdrawal Exceptions

Withdrawal Uncertainty

Escalation Requirements

Withdrawal Classification

Reassessment Triggers

Reauthorization References

Historical Withdrawal States

Deployment Handoff

Lifecycle Handoff

Effective Time

Version

Minimum Implementation Framework

A minimum operational RWM implementation should contain ten governed layers. Layer 1 — Withdrawal Identity and Trigger

Identify the affected release, withdrawal purpose, and evidence-supported

withdrawal trigger. Layer 2 — Withdrawal Scope and Availability Baseline

Define the affected artifacts, distribution channels, recipients, and

current release availability. Layer 3 — Withdrawal Authority

Establish the applicable authority, decision actor, delegation conditions,

and withdrawal boundaries. Layer 4 — Withdrawal Prerequisites and Urgency

Evaluate mandatory conditions, available evidence, urgency, restrictions,

and escalation requirements. Layer 5 — Withdrawal Decision

Establish an explicit withdrawal decision and classification. Layer 6 — Withdrawal Execution References

Preserve the required operational actions and their execution evidence. Layer 7 — Effectiveness Verification

Evaluate whether withdrawal actions produced the required availability

changes within the defined scope. Layer 8 — Residual Availability and Exceptions

Identify remaining distribution paths, previously distributed copies,

evidence gaps, and unresolved exceptions. Layer 9 — Historical Continuity and Lifecycle Handoff

Preserve withdrawal history and initiate deployment, change management,

remediation, or retirement handoffs where required. Layer 10 — Governed Output and Reassessment

Produce the Software Release Withdrawal Profile and maintain reassessment

requirements until the withdrawal governance state is appropriately resolved.

Minimum Decision States

At minimum:

Withdrawal Not Initiated

Withdrawal Trigger Identified

Affected Release Identified

Withdrawal Purpose Established

Withdrawal Scope Defined

Availability Baseline Established

Withdrawal Authority Verification Pending

Withdrawal Authority Established

Withdrawal Authority Not Established

Decision Actor Identified

Decision Actor Eligibility Established

Withdrawal Prerequisites Pending

Withdrawal Prerequisites Satisfied

Withdrawal Evidence Insufficient

Withdrawal Urgency Classified

Withdrawal Decision Pending

Withdrawal Not Required

Withdrawal Authorized

Withdrawal Denied

Release Restriction Required

Release Suspension Required

Partial Withdrawal Authorized

Complete Withdrawal Authorized Within Scope

Withdrawal Execution Pending

Withdrawal Execution In Progress

Withdrawal Action Completed

Withdrawal Action Failed

Withdrawal Verification Pending

Withdrawal Partially Verified

Withdrawal Verified Within Defined Scope

Residual Availability Identified

Withdrawal Exception Identified

Escalation Required

Reassessment Required

Reauthorization Required

Deployment Handoff Required

Lifecycle Handoff Completed

Conflicted

Unknown

Withdrawal Closed

Minimum Evidence Path

Where withdrawal necessity, legitimacy, or effectiveness cannot be sufficiently established:

Software Release Identity → Release Record Profile → Withdrawal Trigger →

Withdrawal Scope → Distribution Availability Baseline → Authority Reference → Withdrawal Decision → Execution Requirements → Withdrawal Evidence → Availability Verification → Residual Exposure Assessment → Evidence-Limited / Conflicted / Unknown State → Evidence Acquisition / Escalation → Targeted Withdrawal Reassessment → Updated Withdrawal Classification → Software Release Withdrawal Profile → Lifecycle Governance Handoff

Missing withdrawal evidence must not be replaced by assumed release unavailability.

Minimum Reassessment Framework

Current Software Release Withdrawal Profile → New Withdrawal Evidence or

Release Event → Trigger Review → Release Identity Review → Scope Review → Distribution Baseline Review → Authority Review → Decision Review → Execution Review → Effectiveness Verification → Residual Availability Review → Exception Review → Escalation Review → Reauthorization Requirement Review → Withdrawal Reclassification → Historical State Preservation → Profile Update → Version Update

Reassessment must distinguish:

Withdrawal Trigger Changed

Withdrawal Scope Changed

Distribution Availability Changed

Execution Evidence Changed

Residual Exposure Changed

Withdrawal Exception Changed

Authorization State Changed

Reauthorization Required

Withdrawal Verified Within Scope

Withdrawal Still Incomplete

Governance Requirements

A conforming RWM implementation must satisfy the following requirements. Withdrawal Identity and Triggers

• Establish a unique withdrawal identity

• Identify the software product

• Identify the affected release

• Preserve the release record reference

• Establish the withdrawal purpose

• Identify the withdrawal trigger

• Preserve trigger evidence

• Identify the affected artifacts

• Preserve the applicable authorization reference

• Prevent withdrawal triggers from automatically establishing

withdrawal decisions.

Withdrawal Scope and Availability

• Define the withdrawal scope

• Define the distribution boundary

• Identify affected release channels

• Identify relevant repositories

• Identify relevant package registries

• Identify relevant update channels

• Identify known mirrors and caches

• Preserve known recipient exposure

• Establish the distribution availability baseline

• Preserve known availability limitations

• Prevent withdrawal from one channel from establishing universal

• Prevent known distribution coverage from being represented as

withdrawal. complete copy identification.

Withdrawal Authority

• Identify the applicable withdrawal authority

• Preserve authority source

• Preserve authority scope

• Evaluate authority validity

• Identify the decision actor

• Evaluate decision actor eligibility

• Preserve applicable delegation references

• Preserve delegation restrictions

• Identify authority expiration or revocation

• Prevent technical removal capability from replacing legitimate

• Prevent release publication authority from automatically

withdrawal authority. establishing withdrawal authority.

Withdrawal Decision

• Establish withdrawal prerequisites

• Evaluate prerequisite conditions

• Classify withdrawal urgency

• Preserve applicable restrictions

• Establish an explicit withdrawal decision

• Preserve decision evidence

• Preserve decision time

• Preserve withdrawal classification

• Preserve partial withdrawal conditions

• Preserve complete withdrawal boundaries

• Prevent withdrawal authorization from being represented as

withdrawal execution.

Execution and Distribution

• Identify required withdrawal actions

• Preserve execution actor references

• Preserve execution times

• Preserve execution evidence

• Preserve repository withdrawal references

• Preserve package registry withdrawal references

• Preserve update channel withdrawal references

• Preserve distribution channel restrictions

• Preserve communication references where applicable

• Preserve execution failures

• Prevent action requests from being represented as completed actions

• Prevent origin removal from establishing mirror or cache removal

Effectiveness and Residual Availability

• Evaluate withdrawal effectiveness

• Preserve verification methods

• Preserve verification times

• Preserve observed availability states

• Identify residual distribution channels

• Identify known remaining copies

• Preserve previously distributed artifact exposure

• Preserve unresolved recipient exposure

• Preserve verification limitations

• Preserve withdrawal exceptions

• Prevent action completion from establishing verified withdrawal

• Prevent verified withdrawal within scope from establishing universal effectiveness. software unavailability.

Evidence and Classification

• Preserve withdrawal evidence provenance

• Evaluate evidence sufficiency

• Preserve missing evidence

• Preserve conflicting evidence

• Preserve withdrawal uncertainty

• Support Evidence-Limited states

• Support Conflicted states

• Support Unknown states

• Preserve withdrawal classifications

• Preserve classification evidence

• Prevent withdrawal completion reports from replacing effectiveness verification.

Reassessment and Continuity

• Identify reassessment triggers

• Preserve material withdrawal scope changes

• Preserve newly identified distribution channels

• Preserve newly identified recipient exposure

• Preserve withdrawal execution failures

• Preserve reauthorization requirements

• Preserve historical withdrawal states

• Preserve superseding withdrawal decisions

• Preserve state transition times

• Preserve lifecycle handoffs

• Prevent reauthorization from erasing historical withdrawal records

• Prevent withdrawal cause resolution from automatically restoring release authorization.

Architecture Boundaries

• Maintain RCMM candidate governance boundaries

• Maintain RRM readiness governance boundaries

• Maintain RAM authorization governance boundaries

• Maintain RRMM release record governance boundaries

• Maintain SDS dependency governance boundaries

• Maintain SCFS configuration governance boundaries

• Maintain SQS quality governance boundaries

• Maintain SSS security governance boundaries

• Maintain SDPS deployment governance boundaries

• Maintain SCMS change governance boundaries

• Maintain SRTS retirement governance boundaries

• Maintain SLCS lifecycle control boundaries

• Maintain GOA™ authority governance boundaries

• Maintain AGA™ accountability governance boundaries

• Maintain ASGA™ autonomous actor governance boundaries

• Prevent RWM from independently executing deployment rollback

• Prevent RWM from independently establishing software remediation

• Prevent RWM from independently determining Harm or Liability

• Prevent RWM from independently retiring the software product

• Produce a Software Release Withdrawal Profile

Governance Logic

Canonical RWM logic:

Software Release Identity → Release Record Reference → Withdrawal Trigger

→ Withdrawal Purpose → Withdrawal Scope → Distribution Availability Baseline → Withdrawal Authority → Decision Actor Eligibility → Withdrawal Prerequisites → Withdrawal Urgency → Withdrawal Decision → Required Withdrawal Actions → Execution Evidence → Distribution Channel Verification → Residual Availability Assessment → Withdrawal Exceptions → Evidence Sufficiency → Withdrawal Classification → Software Release Withdrawal Profile → Deployment / Change Management / Retirement / Lifecycle Governance Handoff

Governance Outputs

RWM may produce:

Software Release Withdrawal Profile

Withdrawal Identity

Affected Release Register

Withdrawal Purpose Record

Withdrawal Trigger Record

Withdrawal Scope

Withdrawal Boundary

Distribution Availability Baseline

Withdrawal Authority Reference

Decision Actor Record

Delegation Reference

Withdrawal Urgency Classification

Withdrawal Prerequisite Register

Withdrawal Decision

Withdrawal Restriction Record

Release Suspension Record

Partial Withdrawal Record

Complete Withdrawal Within Scope Record

Withdrawal Action Register

Withdrawal Execution Record

Repository Withdrawal Reference

Package Registry Withdrawal Reference

Update Channel Withdrawal Reference

Mirror and Cache Exposure Record

Recipient Exposure Reference

Withdrawal Communication Reference

Withdrawal Evidence Register

Evidence Sufficiency State

Withdrawal Effectiveness Assessment

Residual Availability Assessment

Withdrawal Exception Register

Withdrawal Uncertainty Record

Escalation Requirement

Withdrawal Classification

Reassessment Requirement

Reauthorization Reference

Historical Withdrawal Register

Deployment Governance Handoff

Lifecycle Governance Handoff

Version

Practical ApplicationsAutonomous Software Factories

Withdrawing software releases generated and distributed by autonomous AI

systems when subsequent evidence invalidates release conditions. Software Package Registries

Restricting or withdrawing vulnerable, compromised, unauthorized, or

otherwise unsuitable package versions while preserving evidence of remaining mirrors and caches. Enterprise Software Distribution

Coordinating withdrawal decisions across internal repositories, customer

distribution channels, and software update mechanisms. Security Incident Response

Reducing further distribution exposure after identifying critical

vulnerabilities or compromised release artifacts. Critical Infrastructure Software

Governing withdrawal decisions while preserving the distinction between

release availability and operational deployment consequences. AI-Generated Software Supply Chains

Maintaining withdrawal traceability when AI agents, automated build systems, external dependencies, and multiple distribution mechanisms interact.

• Use Case 1 — A Compromised Software Package Remains Available Through

Mirrors

A software supplier discovers that a published package contains a compromised dependency.

The supplier determines that the affected release should no longer be distributed.

An authorized withdrawal decision is established.

The supplier removes the package from its primary package registry.

The automated withdrawal system reports successful completion.

However, the affected package remains accessible through third-party mirrors and cached distribution endpoints.

RWM evaluates:

Release Identity → Withdrawal Trigger → Withdrawal Scope → Primary

Registry Removal → Mirror Availability → Effectiveness Verification → Residual Exposure

The assessment identifies:

• The withdrawal decision was authorized

• The primary registry action was completed

• The defined distribution environment includes additional known mirrors

• The affected package remains accessible

• Withdrawal effectiveness is incomplete across the intended scope

The appropriate classification is:

Withdrawal Partially Verified — Residual Availability Identified.

The critical distinctions are:

Primary Registry Removal ≠ Complete Distribution Withdrawal.

Withdrawal Execution Successful ≠ Withdrawal Objective Fully Achieved.

Origin Release Removed ≠ Replicated Release Copies Removed.

The result: RWM prevents a successful technical removal event from being

misrepresented as complete release withdrawal.

Use Case 2 — An Autonomous AI Agent Withdraws a Release Without

Applicable Authority

An autonomous AI software governance agent continuously monitors released

applications for security and quality changes.

The agent identifies a potential security vulnerability in a recently

published software release.

Its assigned task includes detecting risks, collecting evidence, and

escalating findings.

The agent also possesses technical access to the organization's software

repository.

Without requesting or establishing release withdrawal authority, the agent

removes the release from public distribution.

The removal succeeds technically.

However, the agent's delegated authority did not include independent

release withdrawal decisions.

RWM evaluates:

Agent Identity → Monitoring Authority → Withdrawal Authority → Delegation

Scope → Withdrawal Decision → Execution Action → Authorization Applicability

The assessment identifies:

• The agent was authorized to monitor release risk

• The security finding may justify withdrawal consideration

• The agent possessed technical repository access

• The agent lacked applicable withdrawal decision authority

• The withdrawal action occurred without an established legitimate

withdrawal decision.

The appropriate classification is:

Withdrawal Executed — Applicable Withdrawal Authority Not Established.

The critical distinctions are:

Monitoring Authority ≠ Withdrawal Authority.

Repository Access ≠ Legitimate Withdrawal Permission.

Technical Removal Success ≠ Governance Legitimacy.

The result: RWM preserves the distinction between autonomous risk

detection, legitimate withdrawal decisions, and operational execution.

Use Case 3 — A Withdrawn Release Remains Deployed in Critical

Infrastructure

A critical infrastructure operator uses a software application supplied by

an external vendor.

The vendor discovers a severe vulnerability affecting a specific software

release.

The vendor authorizes withdrawal and removes the affected version from its

public distribution channels.

The withdrawal is verified within the defined distribution scope.

However, the operator continues running the affected version in its

operational environment.

The vendor's withdrawal decision does not automatically uninstall the software or establish a safe rollback procedure.

RWM evaluates:

Release Identity → Withdrawal Decision → Distribution Withdrawal →

Availability Verification → Known Deployment References → Residual Operational Exposure → SDPS Handoff

The assessment identifies:

• Release withdrawal was legitimately authorized

• Distribution withdrawal was completed within scope

• The affected software remains deployed

• Operational exposure remains possible

• Deployment rollback or recovery requires separate governance

The appropriate classification is:

Withdrawal Verified Within Defined Scope — Deployment Governance Handoff Required.

The critical distinctions are:

Release Withdrawal ≠ Deployment Rollback.

Release No Longer Distributed ≠ Release No Longer Operating.

Distribution Exposure Reduced ≠ Operational Exposure Eliminated.

The result: RWM ensures that release withdrawal does not create a misleading conclusion that deployed software has been removed or operational risk resolved.

Critical Distinctions

Release Authorization Revoked ≠ Software Release Automatically Withdrawn.

Release Withdrawal Authorized ≠ Release Withdrawal Executed.

Release Removed from One Channel ≠ Release Universally Unavailable.

Release Withdrawal Completed ≠ Deployed Software Removed.

Withdrawal Action Executed ≠ Withdrawal Effectiveness Verified.

Technical Ability to Remove a Release ≠ Legitimate Withdrawal Authority.

Partial Release Withdrawal ≠ Complete Release Withdrawal.

Withdrawal Completion Reported ≠ Withdrawal Completion Proven.

Release Previously Withdrawn ≠ Release Continuously Unavailable.

Release Withdrawn ≠ Historical Release Record Erased.

Withdrawal Request Identified ≠ Affected Release Sufficiently Identified.

Withdrawal Purpose Legitimate ≠ Withdrawal Method Automatically

Appropriate.

Withdrawal Trigger Identified ≠ Withdrawal Decision Automatically

Established.

Software Version Affected ≠ Every Artifact Bearing That Version Identically Affected.

Withdrawal Applied to a Defined Scope ≠ Withdrawal Completed Outside That Scope.

Known Distribution Locations ≠ Every Existing Software Copy Identified.

Repository Administrative Access ≠ Legitimate Release Withdrawal

Authority.

Actor Capable of Withdrawal ≠ Actor Authorized to Decide Withdrawal.

Authority to Publish Software ≠ Authority to Withdraw Every Published

Release.

Automated Withdrawal Trigger Activated ≠ Legitimate Withdrawal Decision

Established.

Agent Authorized to Monitor Release Risk ≠ Agent Authorized to Remove

Software Releases.

Withdrawal Urgent ≠ Withdrawal Authority Unlimited.

Withdrawal Prerequisites Documented ≠ Withdrawal Prerequisites Satisfied.

Withdrawal Decision Recorded ≠ Withdrawal Decision Executed.

Complete Withdrawal Authorized Within Scope ≠ Universal Removal of All Software Copies.

Release Availability Restricted ≠ Release Fully Withdrawn.

Release Suspended ≠ Release Permanently Withdrawn.

Release Withdrawn from One Repository ≠ Release Withdrawn from Every

Repository.

Withdrawal Complete Within Defined Scope ≠ All Previously Distributed Copies Eliminated.

Withdrawal Action Requested ≠ Withdrawal Action Completed.

Primary Distribution Channel Disabled ≠ Secondary Distribution Channels

Disabled.

Repository Entry Removed ≠ Previously Downloaded Software Removed.

Package Version Withdrawn from Registry ≠ Package Version Unavailable

Through Every Mirror or Cache.

Update Distribution Suspended ≠ Previously Installed Update Reversed.

Origin Release Removed ≠ Replicated Release Copies Removed.

Release No Longer Available for Download ≠ Previously Exposed Recipients

No Longer Affected.

Withdrawal Notice Issued ≠ Withdrawal Notice Received or Acted Upon.

Withdrawal Evidence Recorded ≠ Withdrawal Evidence Reliable.

Withdrawal Action Logs Available ≠ Withdrawal Effectiveness Sufficiently

Established.

Withdrawal Execution Successful ≠ Withdrawal Objective Fully Achieved.

Known Distribution Channels Cleared ≠ No Residual Software Copies Exist.

Withdrawal Exception Recorded ≠ Withdrawal Exception Resolved.

Withdrawal Uncertainty Acknowledged ≠ Withdrawal Uncertainty Eliminated.

Withdrawal Escalation Initiated ≠ Withdrawal Risk Resolved.

Release Withdrawal ≠ Deployment Rollback.

Deployment Rollback ≠ Release Withdrawal.

Release Withdrawn ≠ Underlying Software Defect Remediated.

Software Release Withdrawn ≠ Software Product Retired.

Withdrawal Reassessment Completed ≠ Release Automatically Reauthorized.

Withdrawal Cause Resolved ≠ Release Authorization Automatically Restored.

Release Reauthorized Later ≠ Previous Withdrawal History Erased.

Withdrawal Verified Within Defined Scope ≠ Universal Software Unavailability Established.

Cross-Architecture Boundary

RWM may consume governed evidence from:

GOA™ — Governance Architecture

AGA™ — Accountability Governance Architecture

ASGA™ — Autonomous Systems Governance Architecture

SDS — Software Dependency Standard

SCFS — Software Configuration Standard

SQS — Software Quality Standard

SSS — Software Security Standard

Within SRLS, RWM receives release governance references from:

RCMM — Release Candidate Management Module

RRM — Release Readiness Module

RAM — Release Authorization Module

RRMM — Release Record Management Module

RWM may provide withdrawal references to:

SDPS — Software Deployment Standard

SCMS — Software Change Management Standard

SRTS — Software Retirement Standard

SLCS — Software Lifecycle Control Standard

RWM governs the withdrawal of release availability and the associated

release governance state.

It does not replace security remediation, operational deployment control, software recovery, or product retirement.

Cross-Architecture Mechanism Principle

An operational mechanism may produce inputs for multiple governance architectures, but it belongs only to the architecture whose governed domain includes that mechanism itself. Other architectures govern only its

domain-specific relevance or consequences.

RWM may receive withdrawal triggers from security, quality, configuration, dependency, authorization, operational, or lifecycle governance mechanisms.

It governs the release withdrawal implications of those conditions.

It does not independently redefine the underlying defect, vulnerability, authority, deployment, or retirement mechanisms.

Canonical Boundary

RWM governs how previously authorized, published, distributed, or

otherwise available software releases are identified, evaluated, restricted, suspended, withdrawn, and reassessed when their continued release availability, authorization applicability, distribution eligibility, or supporting governance conditions can no longer be sufficiently maintained.

It does not independently execute deployment rollback, uninstall operational software, remediate defects, revoke general authority, determine Harm or Liability, or retire the software product.

Its principal governed output is the Software Release Withdrawal Profile.

Canonical Closing Statement

Software release governance does not end when software becomes available. A release that was legitimate yesterday may become unsuitable for continued distribution tomorrow. Vulnerabilities emerge, dependencies become compromised, authorization conditions change, artifacts are found to be defective, and new evidence may invalidate the assumptions supporting an earlier release decision.

The ability to publish software must therefore be accompanied by a governed ability to restrict or withdraw its continued availability.

But withdrawal is not a single technical event.

A release may be removed from its primary repository while remaining accessible through mirrors.

An update may be withdrawn while already installed copies continue operating.

A withdrawal decision may be legitimate while execution remains incomplete.

And an automated system may successfully remove a release without possessing legitimate authority to make that decision.

Removing software from a distribution channel is not the same as establishing that the software is no longer available, installed, or operationally consequential.

RWM establishes the governance conditions required to distinguish these

states.

It requires withdrawal triggers to be identifiable and evidence-supported.

It requires withdrawal authority and scope to remain explicit.

It separates withdrawal decisions from execution actions.

It requires withdrawal effectiveness to be evaluated against the defined

distribution boundary.

It preserves residual availability, uncertainty, exceptions, and historical

release evidence.

And it ensures that consequences extending into deployed software, remediation, change management, or retirement are transferred to the appropriate governance mechanisms.

Withdrawal legitimacy, withdrawal execution, and withdrawal effectiveness

are three separate governance questions.

The same principle applies to human-operated release systems, automated

delivery infrastructure, and autonomous AI software factories.

The actor may change.

The distribution mechanism may change.

The withdrawal process may become automated.

The requirement for legitimate, bounded, evidence-supported, and

verifiable release withdrawal remains.

RWM completes the SRLS governance lifecycle by ensuring that software releases remain governable not only when they are created, assessed, authorized, and recorded, but also when their continued availability must be restricted or ended.

With RWM, SLGA™ establishes a critical boundary between software release

governance and operational deployment governance: a release may cease to be authorized or distributed while its artifacts continue to exist, its copies remain accessible, and its deployed instances continue to operate.

RWM makes that distinction explicit — transforming software release withdrawal from an assumed removal action into a governed, traceable, and evidence-supported lifecycle state.

Module Architecture

→ ### RCMM — Release Candidate Management Module

→ RRM — Release Readiness Module

→ # RAM — Release Authorization Module

→ RRMM — Release Record Management Module

→ RWM — Release Withdrawal Module

Related Documents

→ About Software Release Standard (SRLS)